INCH-POUND
MIL-PRF-23419/12
AMENDMENT 1
30 April 1998

PERFORMANCE SPECIFICATION SHEET

FUSES, CARTRIDGE, INSTRUMENT TYPE, STYLE FM12, (SUBMINIATURE - HIGH PERFORMANCE)

This amendment forms a part of MIL-PRF-23419/12, dated 11 January 1993, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Vibration, high frequency, delete and substitute:

"Vibration, high frequency: Fuses shall be tested in accordance with method 204 of MIL-STD-202. The following details and exceptions shall apply:

a. Mounting - Fuses shall be mounted with their bodies restrained from movement, on an appropriate mounting fixture.

b. Test level - Sinusoidal vibration from 5 to 3,000 hertz, 0.4 inch double amplitude or 30 g's peak, whichever is less. (Method 201 of MIL-STD-202 is not applicable).

c. Sweep rate - Approximately 1/2 octave per minute.

d. Test duration - 12 hours total (4 hours in each of three major axis).

e. Loading during testing - Rated dc current on 1/2 of fuse samples tested.

f. Measurements - DC resistance measurements shall be taken before and after the vibration exposure."

PAGE 6

Quality assurance, paragraph b, delete and substitute:

"b. Visual and mechanical inspection; screen for the following defects:

(1) Cracks in the plastic molded housing (critical at lead egress area).

(2) Insufficient plastic fill (critical at lead egress area).

(3) Excessive plastic flash (part out of dimensional tolerance)."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:51Z
Check the source to verify that this is the current version before use.

Quality assurance, paragraph f, last sentence, delete “50” and substitute “20”.

PAGE 11

TABLE I, delete and substitute the cold resistance, minimum and maximum limits for the type designations shown. The minimum and maximum cold resistance values for type designations not referenced here shall remain the same:

Type designation	Cold resistance (ohms)	
	Minimum	Maximum
FM12A72V15A	0.0038	0.0070
FM12A125V1.5A	0.0850	0.2250
FM12A125V2.0A	0.0450	0.1350
FM12A125V3.0A	0.0350	0.1050
FM12A125V4.0A	0.0300	0.0900
FM12A125V5.0A	0.0220	0.0680
FM12A50V20A	0.0025	0.0050

Custodians:
DLA - CC

Preparing activity:
DLA - CC

(Project 5920-0559)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:51Z
Check the source to verify that this is the current version before use.