INCH-POUND

MIL-F-23419/8F
AMENDMENT 1
10 April 1995

MILITARY SPECIFICATION SHEET

FUSE, CARTRIDGE, INSTRUMENT TYPE, STYLE FM08,
(SUBMINIATURE - HIGH PERFORMANCE)

This amendment forms a part of MIL-F-23419/8F, dated 17 August 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title, delete and substitute "FUSES, CARTRIDGE, INSTRUMENT TYPE, STYLE FM08, (SUBMINIATURE - HIGH PERFORMANCE)"

PAGE 2

REQUIREMENTS, Finish, last sentence, delete and substitute, "For solder coated leads (suffix "T"), the leads of the gold plated cap and lead assemblies shall be solder dipped (see table I)."

PAGE 3

After extent of qualification, add: "Group C inspection and retention of qualification may be extended from MIL-F-23419/11 or extended to MIL-F-23419/4, provided they are all the same design and construction."

TABLE I, footnote 4, delete "five minutes" and substitute "one minute".

PAGE 4

Qualification inspection, delete "Qualification inspection:" and substitute "Qualification and group C inspection:".

Inspection routine, delete and substitute:

"Inspection routine. The number of group II samples for qualification and subgroup 2 samples for group C inspection shall be as shown in table II below:".

TABLE II, title, delete and substitute "Group II and subgroup 2 samples".

TABLE II, Inspection column, delete "Group II" and substitute "Group II and subgroup 2".

TABLE II, Overload interrupt, delete "+85°C" and substitute "+125°C", two places.

TABLE IV, Superseding type designation column, delete "FM08A125V15A" and substitute "FM08A32V15A".

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - AS
Air Force - 19, 99
NSA - NS

Preparing activity:
DLA - ES

(Project 5920-0502-02)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:49Z
Check the source to verify that this is the current version before use.