METRIC

MIL-DTL-16884R
3 January 2025
SUPERSEDING
MIL-DTL-16884P
26 September 2017

DETAIL SPECIFICATION

FUEL, NAVAL DISTILLATE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one grade of naval distillate fuel: NATO symbol F-76.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-32490 - Additive, Lubricity Improver, Distillate Fuel

(Copies of this document are available online at https://quicksearch.dla.mil/.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

NAVAL SEA SYSTEMS COMMAND (NAVSEA) PUBLICATIONS

T9070-AL-DPC-020/077-2 - NAVSEA Hazardous Material Avoidance Process

(Copies of this document are available online via Model Based Product Support (MBPS) at https://mbps.navseaplm.navy.mil/Windchill/app/. To gain access to MBPS, obtain an account with National Help Desk Service Management (NHDSM) at https://nhdsm.navair.navy.mil (a valid CAC is required to access this website) and submit a SAAR-N Request. Refer questions, inquiries, or problems to (888) 292-5919. This document is available for ordering (hard copy) via the Naval Logistics Library (NLL) at https://nll.navsup.navy.mil. For questions regarding the NLL, contact the NLL Customer Service at nllhelpdesk@navy.mil, (866) 817-3130, or (215) 697-2626/DSN 442-2626.)

Comments, suggestions, or questions on this document should be addressed to Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard, DC 20376-5160 or emailed to CommandStandards@navy.mil, with the subject line "Document Comment". Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 9140

Distribution Statement A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AEROSPACE INDUSTRIES ASSOCIATION (AIA)

NAS411-1 - Hazardous Materials Target List

(Copies of this document are available online at www.aia-aerospace.org.)

ASTM INTERNATIONAL

ASTM D86 - Standard Test Method for Distillation of Petroleum Products and Liquid Fuels at Atmospheric Pressure

ASTM D93 - Standard Test Methods for Flash Point by Pensky-Martens Closed Cup Tester

ASTM D97 - Standard Test Method for Pour Point of Petroleum Products

ASTM D130 - Standard Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test

ASTM D189 - Standard Test Method for Conradson Carbon Residue of Petroleum Products

ASTM D287 - Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer/Method)

ASTM D445 - Standard Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)

ASTM D482 - Standard Test Method for Ash from Petroleum Products

ASTM D524 - Standard Test Method for Ramsbottom Carbon Residue of Petroleum Products

ASTM D613 - Standard Test Method for Cetane Number of Diesel Fuel Oil

ASTM D664 - Standard Test Method for Acid Number of Petroleum Products by Potentiometric Titration

ASTM D974 - Standard Test Method for Acid and Base Number by Color-Indicator Titration

ASTM D976 - Standard Test Method for Calculated Cetane Index of Distillate Fuels

ASTM D1141 - Standard Practice for Preparation of Substitute Ocean Water

ASTM D1298 - Standard Test Method for Density, Relative Density, or API Gravity of Crude Petroleum and Liquid Petroleum Products by Hydrometer Method

ASTM D1401 - Standard Test Method for Water Separability of Petroleum Oils and Synthetic Fluids

ASTM D1500 - Standard Test Method for ASTM Color of Petroleum Products (ASTM Color Scale)

ASTM D2274 - Standard Test Method for Oxidation Stability of Distillate Fuel Oil (Accelerated Method)

ASTM D2425 - Standard Test Method for Hydrocarbon Types in Middle Distillates by Mass Spectrometry

ASTM D2500 - Standard Test Method for Cloud Point of Petroleum Products and Liquid Fuels

ASTM D2622 - Standard Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-ray Fluorescence Spectrometry

ASTM D2709 - Standard Test Method for Water and Sediment in Middle Distillate Fuels by Centrifuge

ASTM D2887 - Standard Test Method for Boiling Range Distribution of Petroleum Fractions by Gas Chromatography

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

ASTM D3120 - Standard Test Method for Trace Quantities of Sulfur in Light Liquid Petroleum Hydrocarbons by Oxidative Microcoulometry

ASTM D3605 - Standard Test Method for Trace Metals in Gas Turbine Fuels by Atomic Absorption and Flame Emission Spectroscopy

ASTM D3828 - Standard Test Methods for Flash Point by Small Scale Closed Cup Tester

ASTM D4052 - Standard Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter

ASTM D4057 - Standard Practice for Manual Sampling of Petroleum and Petroleum Products

ASTM D4176 - Standard Test Method for Free Water and Particulate Contamination in Distillate Fuels (Visual Inspection Procedures)

ASTM D4177 - Standard Practice for Automatic Sampling of Petroleum and Petroleum Products

ASTM D4530 - Standard Test Method for Determination of Carbon Residue (Micro Method)

ASTM D4737 - Standard Test Method for Calculated Cetane Index by Four Variable Equation

ASTM D4808 - Standard Test Methods for Hydrogen Content of Light Distillates, Middle Distillates, Gas Oils, and Residua by Low-Resolution Nuclear Magnetic Resonance Spectroscopy

ASTM D5291 - Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants

ASTM D5304 - Standard Test Method for Assessing Middle Distillate Fuel Storage Stability by Oxygen Overpressure

ASTM D5452 - Standard Test Method for Particulate Contamination in Aviation Fuels by Laboratory Filtration

ASTM D5453 - Standard Test Method for Determination of Total Sulfur in Light Hydrocarbons, Spark Ignition Engine Fuel, Diesel Engine Fuel, and Engine Oil by Ultraviolet Fluorescence

ASTM D5771 - Standard Test Method for Cloud Point of Petroleum Products and Liquid Fuels (Optical Detection Stepped Cooling Method)

ASTM D5772 - Standard Test Method for Cloud Point of Petroleum Products and Liquid Fuels (Linear Cooling Rate Method)

ASTM D5773 - Standard Test Method for Cloud Point of Petroleum Products and Liquid Fuels (Constant Cooling Rate Method)

ASTM D5949 - Standard Test Method for Pour Point of Petroleum Products (Automatic Pressure Pulsing Method)

ASTM D5950 - Standard Test Method for Pour Point of Petroleum Products (Automatic Tilt Method)

ASTM D5985 - Standard Test Method for Pour Point of Petroleum Products (Rotational Method)

ASTM D6045 - Standard Test Method for Color of Petroleum Products by the Automatic Tristimulus Method

ASTM D6079 - Standard Test Method for Evaluating Lubricity of Diesel Fuels by the High-Frequency Reciprocating Rig (HFRR)

ASTM D6217 - Standard Test Method for Particulate Contamination in Middle Distillate Fuels by Laboratory Filtration

ASTM D6450 - Standard Test Method for Flash Point by Continuously Closed Cup (CCCFP) Tester

ASTM D6591 - Standard Test Method for Determination of Aromatic Hydrocarbon Types in Middle Distillates—High Performance Liquid Chromatography Method with Refractive Index Detection

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

ASTM D6751 - Standard Specification for Biodiesel Fuel Blendstock (B100) for Middle Distillate Fuels

ASTM D6890 - Standard Test Method for Determination of Ignition Delay and Derived Cetane Number (DCN) of Diesel Fuel Oils by Combustion in a Constant Volume Chamber

ASTM D7039 - Standard Test Method for Sulfur in Gasoline, Diesel Fuel, Jet Fuel, Kerosine, Biodiesel, Biodiesel Blends, and Gasoline-Ethanol Blends by Monochromatic Wavelength Dispersive X-ray Fluorescence Spectrometry

ASTM D7042 - Standard Test Method for Dynamic Viscosity and Density of Liquids by Stabinger Viscometer (and the Calculation of Kinematic Viscosity)

ASTM D7111 - Standard Test Method for Determination of Trace Elements in Middle Distillate Fuels by Inductively Coupled Plasma Atomic Emission Spectrometry (ICP-AES)

ASTM D7171 - Standard Test Method for Hydrogen Content of Middle Distillate Petroleum Products by Low-Resolution Pulsed Nuclear Magnetic Resonance Spectroscopy

ASTM D7668 - Standard Test Method for Determination of Derived Cetane Number (DCN) of Diesel Fuel Oils—Ignition Delay and Combustion Delay Using a Constant Volume Combustion Chamber Method

ASTM D7688 - Standard Test Method for Evaluating Lubricity of Diesel Fuels by the High-Frequency Reciprocating Rig (HFRR) by Visual Observation

ASTM D7777 - Standard Test Method for Density, Relative Density, or API Gravity of Liquid Petroleum by Portable Digital Density Meter

ASTM D7963 - Standard Test Method for Determination of Contamination Level of Fatty Acid Methyl Esters in Middle Distillate and Residual Fuels Using Flow Analysis by Fourier Transform Infrared Spectroscopy—Rapid Screening Method

ASTM E29 - Standard Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

(Copies of these documents are available online at www.astm.org.)

BRITISH STANDARDS INSTITUTE

BS EN 14078 - Liquid Petroleum Products - Determination of Fatty Acid Methyl Ester (FAME) Content in Middle Distillates - Infrared Spectrometry Method

BS EN 14214 - Liquid Petroleum Products - Fatty Acid Methyl Esters (FAME) for Use in Diesel Engines and Heating Applications - Requirements and Test Methods

(Copies of these documents are available online at https://knowledge.bsigroup.com.)

ENERGY INSTITUTE

IP 579 - Liquid Petroleum Products - Determination of Fatty Acid Methyl Ester (FAME) Content in Middle Distillates - Infrared Spectrometry Method

(Copies of this document are available online at www.energyinst.org.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. Requirements contained herein are not subject to corrections for tolerance of standard test methods. If multiple determinations are made by the inspecting laboratory, average results shall be used except for those standard test methods where repeatability data are given. In those cases, the average value derived from the individual results that agree within the repeatability limits given may be used at the discretion of the inspection authority, provided an indication is given of the total number of results obtained and the number falling outside of the repeatability limits. The flash point value is absolute and no value less than 60.0 °C (140.0 °F) is permissible. For purposes of determining conformance with these specifications, an observed value or a calculated value shall be rounded "to the nearest unit" in the last right-hand digit used in expressing the specification limit, in accordance with the rounding method of ASTM E29.

3.2 Material. The fuel supplied under this specification shall consist of refined hydrocarbon distillate fuel, containing no residual fuel, and may contain only those additives specified in 3.2.5. The fuel shall be derived from conventional material sources, synthesized materials, or mixtures thereof. Conventional material sources are defined as crude oil, natural gas liquid condensates, heavy oil, shale oil, and oil sands. The fuel shall not contain any intentionally blended oxygenated compounds including fatty acid methyl esters (FAME) (see 6.3.4) as specified in 3.2.6.

3.2.1 Toxicity and prohibited materials.

3.2.1.1 Toxicity. When evaluated in accordance with 4.3.1, the fuel shall pose no serious or high risk to the health of personnel or the environment when used for its intended purpose (see 4.3.1 and 6.6).

3.2.1.2 Prohibited materials. The fuel shall not contain any chemicals categorized as "prohibited" in accordance with T9070-AL-DPC-020/077-2 for NAVSEA programs or NAS411-1 for all other programs.

3.2.2 Synthesized paraffinic diesels (SPD). A maximum of 50 volume percent of the finished fuel (see 6.3.5) may consist of SPD (see 6.3.12) blend components derived from Hydroprocessed Renewable Diesel (HRD) (see 6.3.7 and 6.3.9) or Fischer-Tropsch (FT) produced SPD. The remainder of the finished fuel shall be comprised of conventional source blending components (see 6.3.3). Fischer-Tropsch Hydroprocessed Synthesized Paraffinic Diesel (FT-SPD) (see 6.3.6) and HRD-derived blend components shall conform to the requirements in appendix A. Finished fuel containing SPD shall conform to the properties listed in table I. If the finished fuel containing SPD requires additives, then only additives in accordance with 3.2.5 shall be used.

3.2.3 Synthesized iso-paraffins (SIP) from hydroprocessed fermented sugars. A maximum of 20 volume percent of the finished fuel may consist of SIP (see 6.3.11) blend components derived from hydroprocessed fermented sugars (see 6.3.8). The remainder of the finished fuel shall be comprised of conventional source blending components. SIP-derived blend components shall conform to the requirements in appendix B. Finished fuel containing SIP shall conform to the properties listed in table I. If the finished fuel containing SIP requires additives, then only additives in accordance with 3.2.5 shall be used.

3.2.4 Co-hydroprocessed synthesized diesel. Hydrocarbons in the diesel boiling range derived from non-petroleum feedstocks that have been processed simultaneously (co-processing) with hydrocarbons from conventional sources are permitted in the manufacture of F-76. The co-hydroprocessed synthesized diesel shall be produced from the feedstocks specified in 3.2.4.1 and 3.2.4.2 and shall not exceed the concentration stated in these sections. The finished fuel shall conform to the properties listed in table I and contain additives in accordance with 3.2.5.

3.2.4.1 Mono-, di-, and triglycerides; free fatty acids; and fatty acid esters. Co-processing of mono-, di-, and triglycerides; free fatty acids; and fatty acid esters with conventionally sourced hydrocarbons is acceptable for the manufacture of F-76. The process streams used for diesel fuel production in co-processing refinery units shall not exceed 40 volume percent mono-, di-, and triglycerides; free fatty acids; and fatty acid esters in feedstock volume, with the balance (≥60 volume percent) being conventionally sourced hydrocarbons. Co-processing shall include hydrocracking or hydrotreating and fractionation. Processing may also include other conventional refinery processes. The finished fuel is limited to 40 volume percent co-hydroprocessed synthesized diesel derived from mono-, di-, and triglycerides; free fatty acids; and fatty acid esters.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

3.2.4.2 Hydrocarbons derived from synthesis gas via the FT process. Co-processing of hydrocarbons derived from synthesis gas via the FT process using iron or cobalt catalyst with conventionally sourced hydrocarbons is acceptable for the manufacture of F-76. The process streams used for diesel fuel production in co-processing refinery units shall not exceed 10 volume percent FT hydrocarbons in feedstock volume, with the balance (≥90 volume percent) being conventionally sourced hydrocarbons. Co-processing shall include hydrocracking and fractionation. Processing may also include other conventional refinery processes. The finished fuel is limited to 10 volume percent co-hydroprocessed synthesized diesel derived from FT feedstock.

3.2.5 Fuel additives. Additives listed herein may be used either singularly or in combination, provided the amounts do not exceed those specified herein. When specified (see 6.2), information concerning the name and dosage rate of each additive used shall be made available when requested by the procuring activity or user. All other additives are prohibited without prior approval from the Technical Authority (see 6.3.13).

3.2.5.1 Metal deactivator. A metal deactivator (N, N-disalicyclidene-1, 2 propanediamine) may be blended into the fuel provided the dosage rate does not exceed 5.8 milligrams (mg) of active ingredient per liter (L) of fuel (2.2 grams per 100 U.S. gallons or 2 pounds per 1,000 barrels).

3.2.5.2 Lubricity improver additives. Lubricity improver additives may be used to meet the lubricity requirement in table I. The lubricity improver additive shall have an approved formulation in accordance with MIL-PRF-32490 and shall not exceed the maximum dosage rate prescribed by MIL-PRF-32490.

3.2.6 FAME. Fuel supplied under this specification shall not intentionally be blended with FAME. The fuel supplied under this specification shall not contain more than 0.1 volume percent FAME (see 3.2), as determined by BS EN 14078, IP 579, or ASTM D7963. FAME that fails to meet the biodiesel quality standards (ASTM D6751 or BS EN 14214) shall not be used in naval distillate fuel and is subject to the same de minimis limit of 0.1 volume percent. Where a risk exists for incidental FAME contamination, the fuel shall not exceed this limit prior to product availability.

3.2.7 Antioxidants. Antioxidant analysis is applicable for synthetic fuels identified in appendices A and B. Antioxidants shall be added immediately after hydroprocessing or fractionation synthesizing and prior to the product or component being passed into storage to prevent peroxidation and gum formation after manufacture. Not less than 17.2 mg/L nor more than 24.0 mg/L of active ingredient shall be used. The following antioxidant formulations are approved:

a. 2,6-di-tert-butyl-4-methylphenol

b. 6-tert-butyl-2,4-dimethylphenol

c. 2,6-di-tert-butylphenol

d. 75 percent minimum 2,6-di-tert-butylphenol
   25 percent maximum tert-butylphenols and tri-tert-butylphenols

e. 72 percent minimum 6-tert-butyl-2,4-dimethylphenol
   28 percent maximum tert-butyl-methylphenols and tert-butyl-dimethylphenols

f. 55 percent minimum 2,4-dimethyl-6-tert-butylphenol
   15 percent minimum 2,6-di-tert-butyl-4-methylphenol
   30 percent maximum mixed methyl and dimethyl tert-butylphenols

3.2.8 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

3.3 Physical and chemical requirements. The naval distillate fuel shall conform to the physical and chemical requirements specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

TABLE I. Physical and chemical requirements.

Characteristic	Requirement		ASTM Test Method
	Minimum	Maximum	
Physical Requirements			
Appearance, at 25 °C (77 °F) or ambient, whichever is higher	Clear, bright, and free of visible particulates		ASTM D4176 [1/]
Demulsification, at 25 °C (77 °F), minutes	--	10	ASTM D1401 [2/]
Density, at 15 °C (59 °F), kg/m³	800.0	876.0	ASTM D1298 (R), ASTM D4052, ASTM D287, ASTM D7777
Distillation: 10% Recovered, °C (°F) 50% Recovered, °C (°F) 90% Recovered, °C (°F) End Point, °C (°F) Residue + Loss, volume %	 Record Record -- -- --	 -- -- 357.0 (674.6) 385.0 (725.0) 3.0	ASTM D86 (R) [3/], ASTM D2887 [4/]
Cloud Point, °C (°F)	--	-1 (30.2)	ASTM D2500 (R), ASTM D5771 [5/], ASTM D5772 [5/], ASTM D5773 [5/]
Color	--	3	ASTM D1500 (R), ASTM D6045
Flash Point, °C (°F)	60.0 (140)	--	ASTM D93 (R) [6/], ASTM D6450 [6/], ASTM D3828 [6/]
Particulate Contamination, mg/L	--	10.0	ASTM D6217 (R), ASTM D5452 [7/]
Pour Point, °C (°F)	--	-6 (21.2)	ASTM D97 (R), ASTM D5949, ASTM D5950, ASTM D5985 [8/]
Viscosity, at 40 °C (104 °F), mm²/second	1.700	4.300	ASTM D445 (R), ASTM D7042
Chemical Requirements			
Acid Number, mg KOH/gram	--	0.30	ASTM D974 (R) [9/], ASTM D664
Ash, mass %	--	0.010	ASTM D482
Aromatics, mass %	8.1 [10/]	--	ASTM D6591 (R), ASTM D2425
Carbon Residue on 10% bottoms, mass %	--	0.20	ASTM D524 (R) [11/]
	--	0.14	ASTM D189, ASTM D4530 [11/]
Corrosion, 2 hours at 100 °C (212 °F)	--	No. 1	ASTM D130
Hydrogen Content, mass %	12.50	--	ASTM D7171 (R), ASTM D4808, ASTM D5291
Ignition Quality: Cetane Number, or Cetane Index, or Derived Cetane Number	 42 43.0 42.0	--	 ASTM D613 (R) ASTM D976 [12/], ASTM D4737 [12/] ASTM D6890, ASTM D7668
Storage Stability, Total Insolubles, mg/100 mL	--	2.0	ASTM D5304 (R) [13/, 14/]
	--	1.0	ASTM D2274 [14/, 15/]
Sulfur Content, mg/kg	--	15	ASTM D5453 (R), ASTM D2622, ASTM D3120, ASTM D7039

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

TABLE I. Physical and chemical requirements – Continued.

Characteristic	Requirement		ASTM Test Method
	Minimum	Maximum	
Chemical Requirements			
Trace Metals, mg/kg: Calcium Lead Sodium plus Potassium Vanadium	 -- 	 1.00 0.50 1.00 0.50	ASTM D7111 (R), ASTM D3605 16/
Lubricity, at 60 °C (140 °F), micrometers	--	460	ASTM D6079 (R), ASTM D7688
Additive Names and Dosage Rates	Record		--

FOOTNOTES:

1/ If the sample has no visible particulates but is otherwise not "clear and bright" (see 6.3.2) in accordance with ASTM D4176, procedure 1, then the product shall meet the requirements of ASTM D2709, maximum 0.05 volume percent of water and sediment. The fuel is acceptable for appearance if the water and sediment content is 0.05 volume percent or less. If the sample fails ASTM D4176, procedure 1, because it contains visible sediment or particulate matter but meets the requirements of a maximum 10mg/L, in accordance with ASTM D6217 or ASTM D5452, then the fuel is considered acceptable provided all other physical and chemical requirements are met.

2/ The demulsification test shall be conducted in accordance with ASTM D1401 with the following exceptions:

a. Synthetic seawater in accordance with ASTM D1141 shall be the emulsifying fluid.

b. The test temperature shall be 25 °C (77 °F).

c. The demulsification time shall be that required for separation into two layers with no visible cuff at the interface. A lacy emulsion or cuff that does not form a band shall be disregarded. The fuel/water/emulsion layer volumes shall be recorded at 1-minute intervals and the demulsification time recorded to the nearest minute.

3/ As the end point of the distillation is approached, if either a thermometer reading of 385 °C (725 °F) or a decomposition point is observed, the heating shall be discontinued and the procedure resumed as directed in ASTM D86.

4/ Results from ASTM D2887 shall be recorded as "Predicted D86" results by application of the correlation in the Correlation for Jet and Diesel Fuel appendix of ASTM D2887 to convert the values. ASTM D86 shall remain as the referee method. Distillation residue and loss limits provide control of the distillation process during the ASTM D86 test method and do not apply to ASTM D2887.

5/ If either ASTM D5771, ASTM D5772, or ASTM D5773 is used, the temperature recorded in each respective test shall be rounded to the next lower integer and recorded as the ASTM D2500 equivalent cloud point in accordance with ASTM D5771, ASTM D5772, or ASTM D5773.

6/ The flash point value is absolute and no value less than 60.0 °C (140 °F) is permissible.

7/ If ASTM D5452 is utilized, a minimum 1-L (1-quart) sample shall be used to meet the sample requirement of ASTM D6217.

8/ If either ASTM D5949, ASTM D5950, or ASTM D5985 is used, the results from these tests shall be based on the observations at 3 °C (5.4 °F) temperature intervals and recorded as the ASTM D97 equivalent.

9/ The sample size when using ASTM D974 shall be 20.0±2.0 grams.

10/ Requirement applies only to finished fuels containing synthesized materials as defined in appendix A, appendix B, and 3.2.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

TABLE I. Physical and chemical requirements – Continued.

FOOTNOTES:

11/ Fuel shall meet the requirements for one of the two test methods. If ASTM D189 or ASTM D4530 is performed in lieu of the referee test method, ASTM D524, the maximum allowable carbon residue shall be 0.14 mass percent.

12/ ASTM D976 is only a valid method when 100 percent of the F-76 is derived from conventional material sources. ASTM D976 is not an acceptable cetane test method for fuels containing synthesized materials as defined in appendix A, appendix B, and 3.2.4.

13/ Only nylon membrane filter media (0.8-micrometer pore size) are acceptable in accordance with ASTM D5304. Glass fiber (type A/E) filter media shall not be used to obtain test results.

14/ Fuel shall meet the requirements for one of the two test methods.

15/ If ASTM D2274 is utilized, the test period shall be extended from 16 hours to 40 hours.

16/ Results by ASTM D3605 shall be recorded in mg/L. Original limits in table I still apply.

NOTES:

1. Table I identifies the referee test method first, followed by the notation "(R)". "(R)" denotes the referee test method.
2. m = meter, mm = millimeter, mL = milliliter

4. VERIFICATION

4.1 Conformance inspection. Bulk samples for tests shall be taken in accordance with ASTM D4057 for manual sampling and ASTM D4177 for automatic sampling (see 6.3.1). Each sample selected shall be tested as specified in table I and 4.3. These tests are performed on the finished product. Where more than one test method is allowed for a specific requirement, table I identifies the referee test method first, followed by the notation "(R)".

4.2 Examination of packaged lots. Packaged lots (see 6.3.10) shall be examined as specified (see 6.2 and 6.5).

4.3 Tests.

4.3.1 Toxicity. A Health Hazard Assessment (HHA) will be conducted to ensure conformance to 3.2.1.1 as specified (see 6.2). The Navy and Marine Corps Force Health Protection Command (NMCFHPC) will evaluate the fuel using data provided by the manufacturer/distributor to the NMCFHPC (see 3.2.1.1 and 6.6).

4.3.2 Prohibited materials. Prohibited materials shall be verified as specified (see 3.2.1.2 and 6.2).

4.3.3 FT-SPD and HRD blend components. If used, FT-SPD and HRD-derived blend components shall be verified as specified in appendix A.

4.3.4 SIP blend components. If used, SIP-derived blend components shall be verified as specified in appendix B.

4.4 Ozone depleting substances (ODS). In any of the test methods, the use of any ODS identified as a class 1 or class 2 ODS by the Environmental Protection Agency is prohibited as specified (see 6.2). An appropriate non-ODS solvent shall be substituted.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Naval distillate fuel is intended for use in all naval shipboard boilers, gas turbines, and diesel engines operating at ambient temperatures above -1 °C (30.2 °F). Other uses may be specified according to the needs of the Department of Defense. Additives as specified in 3.2.5 are permitted. Gas turbines, diesel engines, and boilers operating in ambient temperatures that fall consistently below -1 °C (30.2 °F) should utilize JP-5 fuel in accordance with MIL-DTL-5624. Equipment manufactured in accordance with this document may utilize new technology provided form, fit, and function are maintained as approved by the Technical Authority.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Date of ordering and date of supply.

c. Requirements for an HHA (see 3.2.1.1 and 4.3.1).

d. Requirement for prohibited materials verification (see 3.2.1.2 and 4.3.2).

e. Type and dosage rate of each additive used (see 3.2.5, A.4.3, and B.4.3).

f. Requirements for the examination of packaged lots (see 4.2 and 6.5).

g. Prohibited ODSs (see 4.4).

h. Packaging requirements (see 5.1).

6.3 Definitions.

6.3.1 Bulk lot. An indefinite quantity of a homogeneous mixture of materials offered for acceptance in a single isolated container.

6.3.2 Clear and bright. The terms “clear” and “bright” are independent of the natural color of the fuel. “Clear” means the absence of any cloud, emulsion, or readily visible particulate matter or free water. “Bright” refers to the shiny appearance of clean, dry fuel.

6.3.3 Conventional source blending component. Blending streams derived from the following conventional sources: crude oil, petroleum, oil sands, oil shale, natural gas liquid condensates, or mixtures thereof.

6.3.4 Fatty acid methyl ester (FAME). Synonymous with biodiesel meeting the requirements of ASTM D6751 or BS EN 14214. According to ASTM D6751, biodiesel is a fuel comprised of fatty acids derived from vegetable oils or animal fats, designated B100. The recent introduction of FAME in the commercial middle distillate marketplace has resulted in the potential for trace amounts of FAME in F-76 fuel.

6.3.5 Finished fuel. Fuel conforming to the requirements of section 3 and containing a maximum of 50 volume percent SPDs, a maximum of 20 volume percent SIP materials, a maximum of 40 volume percent mono-, di-, and triglycerides; free fatty acids; and fatty acid esters in feedstock volume when coprocessing, and a maximum of 10 volume percent FT hydrocarbons in feedstock volume when coprocessing.

6.3.6 Fischer-Tropsch hydroprocessed synthesized paraffinic diesel (FT-SPD). SPD synthesized by FT processing. FT-SPD may also be referred to as paraffinic middle distillate (PMD).

6.3.7 Hydroprocessed. Conventional chemical processing in which hydrogen is reacted with organic compounds in the presence of a catalyst to remove impurities, such as oxygen, sulfur, and nitrogen; to saturate unsaturated hydrocarbons; or to alter the molecular structure of the hydrocarbon molecules.

6.3.8 Hydroprocessed fermented sugars. Farnesane that is produced by hydroprocessing and fractionation of farnesene derived from the fermentation of sugars.

6.3.9 Hydroprocessed or hydrotreated renewable diesel (HRD). SPD produced from mono-, di-, and triglycerides; free fatty acids; and fatty acid esters from plant, algal oils, or animal fats (for example, FAME) that have been hydroprocessed to remove essentially all oxygen. HRD may also be referred to as hydroprocessed esters and fatty acids synthesized paraffinic diesel (HEFA-SPD) or PMD.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

6.3.10 Packaged lot. An indefinite number of 208-L (55-gallon) drums or smaller unit containers of identical size and type, offered for acceptance, and filled with a homogeneous mixture of material from one isolated container; or filled with a homogeneous mixture of material manufactured in a single plant run (not exceeding 24 hours) through the same processing equipment, with no change in ingredient material.

6.3.11 Synthesized iso-paraffins (SIP). A middle distillate blending component consisting of nearly all iso-paraffins that meet the requirements of appendix B.

6.3.12 Synthesized paraffinic diesel (SPD). A middle distillate blending component consisting of n-paraffins, iso-paraffins, and cycloparaffins that meet the requirements of appendix A. Hydrocarbons are derived from alternative sources, such as coal, natural gas, biomass, and hydrogenated fats and oils, by processes such as FT synthesis and hydroprocessing.

6.3.13 Technical Authority. The Technical Authority has the authority, responsibility, and accountability to establish, monitor, and approve technical standards, tools, and processes in conformance to higher authority policy, requirements, architectures, and standards. NAVSEA 05S may be contacted to determine the appropriate Technical Authority for any given requirement related to equipment and systems of U.S. Navy ships and submarines.

6.4 Technical Authority approval and direction. Deviation from specified materials, procedures, and requirements, and selection of specific alternative materials and procedures requires Technical Authority approval or direction. Requests should include supporting documentation.

6.5 Examination of packaged lots. A random sample of packaged containers should be taken from each lot in accordance with table II. As specified (see 6.2), samples should be examined for compliance with MIL-STD-290 with regard to fill, closure, sealing, leakage, packaging, packing, and marking requirements. Any container having one or more defects or under the required fill volume should be rejected. If the number of defective or under-filled containers exceeds the reject limit number of table II, the lot represented by the sample should be rejected.

TABLE II. Sampling of packaged lots and acceptance/rejection criteria.

Lot Size	Sample Size	Reject Limit
1–13	All	Any
14–150	13	1
151–250	32	2
251–500	50	3
501–1,200	80	4
1,201–3,200	125	6
3,201–10,000	200	11
10,001–35,000	315	15
35,001 and over	500	22

NOTES:
1. All defective items should be replaced with acceptable items prior to lot acceptance.
2. Inspect sample size until reject criteria are reached.
3. Rejected lots may be screened and resubmitted for inspection and retest.

6.6 Toxicity evaluation. The NMCFHPC requires sufficient information to permit an HHA of the product. Upon completion of the HHA, a copy will be provided by the NMCFHPC to the Government for evaluation. The HHA process is described on the NMCFHPC's website, https://www.med.navy.mil/Navy-and-Marine-Corps-Force-Health-Protection-Command/Environmental-Health/Industrial-Hygiene/Acquisition-Technical-Support/Health-Hazard-Assessments-HHA/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

6.7 Subject term (key word) listing.

Boiler
Diesel
Diesel engine
Fischer-Trosch Hydroprocessed Synthetic Paraffinic Diesel
FT-SPD
Gas turbine engine
HEFA
HRD
Hydroprocessed Esters and Fatty Acids
Hydroprocessed Renewable Diesel
Hydrotreated Renewable Diesel
Lubricity
Marine diesel
Marine gas oil
Metal deactivator
Oil
Paraffinic middle
Refined hydrocarbon
SPD
Synthesized Paraffinic Diesel

6.8 International standardization agreement implementation. This specification implements NATO STANAG 1135, Interchangeability of Fuels, Lubricants and Associated Products Used by the Armed Forces of the North Atlantic Treaty Nations, and NATO STANAG 1385, Guide Specification (Minimum Quality Standards) for Naval Distillate Fuels (F-75 and F-76). When amendment, revision, or cancellation of this specification is proposed, the preparing activity must coordinate the action with the U.S. National Point of Contact for the international standardization agreement, as identified in the ASSIST database at https://assist.dla.mil.

6.9 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

HYDROPROCESSED SYNTHESIZED PARAFFINIC DIESEL (SPD)

A.1 SCOPE

A.1.1 Scope. This appendix defines hydroprocessed SPD for use as a synthetic blending component in naval distillate fuels. This appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

A.2 APPLICABLE DOCUMENTS

A.2.1 General. The documents listed in this section are specified in appendix A of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in appendix A of this specification, whether or not they are listed.

A.2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

ASTM INTERNATIONAL

ASTM D3241 - Standard Test Method for Thermal Oxidation Stability of Aviation Turbine Fuels

ASTM D4629 - Standard Test Method for Trace Nitrogen in Liquid Hydrocarbons by Syringe/Inlet Oxidative Combustion and Chemiluminescence Detection

ASTM D4809 - Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter (Precision Method)

ASTM D6304 - Standard Test Method for Determination of Water in Petroleum Products, Lubricating Oils, and Additives by Coulometric Karl Fischer Titration

ASTM D7261 - Standard Test Method for Determining Water Separation Characteristics of Diesel Fuels by Portable Separometer

(Copies of these documents are available online at www.astm.org.)

A.3 MATERIALS AND MANUFACTURE

A.3.1 SPDs. SPDs shall be derived from FT or HRD methods. FT-SPD blending components shall be wholly derived from synthesis gas via the FT process using iron or cobalt catalyst. HRD blend components shall be comprised of hydrocarbon fuel obtained from hydrogenation and deoxygenation of fatty acid esters and free fatty acids. Subsequent processing of the product shall include hydrotreating, hydrocracking, or hydroisomerization and is expected to include, but not be limited to, a combination of other conventional refinery processes, such as polymerization, isomerization, and fractionation.

A.4 DETAILED BATCH REQUIREMENTS

A.4.1 Batch requirements. Each batch of synthesized blending component shall conform to the requirements specified in table A-I.

A.4.2 Hydroprocessed SPD batch. The hydroprocessed SPD blend component shall meet the requirements of table A-I. It is not necessary to analyze each batch of hydroprocessed SPD for compliance with table A-II once it is demonstrated that the process scheme is adequately controlled to support the expectation that these requirements are always met. At a minimum, batches shall be required to meet the specifications of table A-II when new production facilities or schemes are established, or when significant changes to existing production operations are implemented, such as the introduction of a new feedstock material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

TABLE A-I. Detailed batch requirements; hydroprocessed SPD.

Characteristic	Requirement		ASTM Method
	Minimum	Maximum	
Acid Number, mg KOH/g	--	0.08	ASTM D974 (R), ASTM D664
Carbon Residue on 10% bottoms, mass %	--	0.20	ASTM D524 (R) [1/]
	--	0.14	ASTM D189 [1/], ASTM D4530 [1/]
Cloud Point, °C (°F)	--	-1 (30.2)	ASTM D2500 (R), ASTM D5771, ASTM D5772, ASTM D5773
Corrosion, 2 hours at 100 °C (212 °F)	--	No. 1	ASTM D130
Density, at 15 °C (59 °F), kg/m³	770.0	805.0	ASTM D1298 (R), ASTM D4052, ASTM D287
Cetane Number, or Derived Cetane Number	42 42.0	80 80.0	ASTM D613 (R) ASTM D6890
Distillation: Initial Boiling Point, °C (°F) 10% Recovered, °C (°F) 50% Recovered, °C (°F) 90% Recovered, °C (°F) Final Boiling Point, °C (°F) T50-T10, °C (°F) T90-T10, °C (°F) Residue + Loss, volume %	 Record 191.0 (375.8) Record 290.0 (554.0) 300.0 (572.0) Record 20.0 (68.0) --	 -- 290.0 (554.0) -- 357.0 (674.6) 385.0 (725.0) -- -- 3.0	ASTM D86
Flash Point, °C (°F)	60.0 (140.0)	--	ASTM D93 (R) [2/], ASTM D3828
Heating Value, MJ/kg	43.5	--	ASTM D4809
Hydrogen Content, mass %	14.50	--	ASTM D7171 (R), ASTM D4808, ASTM D5291
Kinematic Viscosity, at 40 °C (104 °F), mm²/second	1.700	4.300	ASTM D445, ASTM D7042
Diesel Microseparometer	85	--	ASTM D7261
Particulate Contamination, mg/L	--	1.0	ASTM D6217 (R), ASTM D5452
Thermal Stability: Change in Pressure Drop, mm of Hg and Tube Deposit Code, less than or Average Deposit Thickness, nm, over area of 2.5 mm²	 -- 	 25 3 [4/] 85	ASTM D3241 [3/]

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

TABLE A-I. Detailed batch requirements; hydroprocessed SPD – Continued.

Characteristic	Requirement		ASTM Method
	Minimum	Maximum	
Total Water, mg/kg	--	100	ASTM D6304

FOOTNOTES:

1/ Fuel shall meet the requirements for one of the three test methods. If ASTM D189 or ASTM D4530 is performed in lieu of the referee test method, ASTM D524, the maximum allowable carbon residue shall be 0.14 mass percent.

2/ ASTM D3828 may give results up to 1.7 °C (3.06 °F) below the ASTM D93 results.

3/ See A.4.4.1 and A.4.4.2 for ASTM D3241 test conditions and procedures.

4/ If the visual rating of the heater tube shows Peacock (P) or Abnormal (A) type deposits, the fuel sample is not acceptable.

NOTES:

1. Table A-I identifies the referee test method first, followed by the notation "(R)". "(R)" denotes the referee test method.
2. MJ = megajoules, nm = nanometer

TABLE A-II. Other detailed requirements; hydroprocessed SPD.

Characteristic	Requirement		ASTM Method
	Minimum	Maximum	
Hydrocarbon Composition			
Cycloparaffins, mass %	--	15 1/	ASTM D2425
Aromatics, mass %	--	0.5	ASTM D2425
Paraffins (normal and iso), mass %	Record	--	ASTM D2425
Carbon and Hydrogen, mass %	99.5	--	ASTM D5291
Non-Hydrocarbon Composition			
Nitrogen, mg/kg	--	10	ASTM D4629
Sulfur, mg/kg	--	15	ASTM D5453 (R), ASTM D2622
Metals 2/ (Al, Ca, Co, Cr, Cu, Fe, Mg, Mn, Mo, Ni, P, Pb, Pd, Pt, Sn, Sr, Ti, V, Zn), mg/kg	--	0.10 per metal	ASTM D7111
Alkali Metals and Metalloids 2/ (B, Na, K, Si, Li), mg/kg	--	1.00 total	ASTM D7111

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

TABLE A-II. Other detailed requirements; hydroprocessed SPD – Continued.

FOOTNOTES:

1/ Maximum cycloparaffin composition is based on current experience with the approved synthetic fuels and is within the range of what is typical for refined diesel fuel.

2/ All detected metals below the detection limits shall be considered as 0 micrograms/kg. Only the metals with measured values higher than their respective detection limits shall be considered as legitimate values for calculation.

NOTE: Table A-II identifies the referee test method first, followed by the notation "(R)". "(R)" denotes the referee test method.

A.4.3 Fuel additives. When specified (see 6.2), information concerning the name and dosage rate of each additive used shall be made available.

A.4.4 Thermal stability. The thermal stability test shall be conducted in accordance with ASTM D3241. The heater tube shall be rated visually in accordance with ASTM D3241, Heater Tubes Annex, Test Method for Visual Rating.

A.4.4.1 Test conditions. The following test conditions shall apply:

a. Minimum heater tube temperature at maximum point: 325 °C (617 °F)

b. Fuel system pressure: 3.45 megapascals (MPa) (500 pounds per square inch gauge [psig])

c. Fuel flow rate: 3.0 mL/minute

d. Test duration: 150 minutes

A.4.4.2 ASTM D3241 procedure.

a. The differential pressure in mm Hg at 150 minutes or the time to differential pressure of 25 mm Hg, whichever comes first, shall be recorded.

b. The heater tube deposit code rating shall be recorded at the end of the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

SYNTHESIZED ISO-PARAFFINS (SIP) FROM HYDROPROCESSED FERMENTED SUGARS

B.1 SCOPE

B.1.1 Scope. This appendix defines SIP produced from hydroprocessed fermented sugars for use as a synthetic blending component in marine diesel fuels. This appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

B.2 APPLICABLE DOCUMENTS

B.2.1 General. The documents listed in this section are specified in appendix B of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in appendix B of this specification, whether or not they are listed.

B.2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

ASTM INTERNATIONAL

ASTM D381 - Standard Test Method for Gum Content in Fuels by Jet Evaporation

ASTM D2710 - Standard Test Method for Bromine Index of Petroleum Hydrocarbons by Electrometric Titration

ASTM D3241 - Standard Test Method for Thermal Oxidation Stability of Aviation Turbine Fuels

ASTM D4629 - Standard Test Method for Trace Nitrogen in Liquid Hydrocarbons by Syringe/Inlet Oxidative Combustion and Chemiluminescence Detection

ASTM D4809 - Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter (Precision Method)

ASTM D6304 - Standard Test Method for Determination of Water in Petroleum Products, Lubricating Oils, and Additives by Coulometric Karl Fischer Titration

ASTM D7261 - Standard Test Method for Determining Water Separation Characteristics of Diesel Fuels by Portable Separometer

ASTM D7359 - Standard Test Method for Total Fluorine, Chlorine and Sulfur in Aromatic Hydrocarbons and Their Mixtures by Oxidative Pyrohydrolytic Combustion Followed by Ion Chromatography Detection (Combustion Ion Chromatography-CIC)

ASTM D7974 - Standard Test Method for Determination of Farnesane, Saturated Hydrocarbons, and Hexahydrofarnesol Content of Synthesized Iso-Paraffins (SIP) Fuel for Blending with Jet Fuel by Gas Chromatography

(Copies of these documents are available online at www.astm.org.)

B.3 MATERIALS AND MANUFACTURE

B.3.1 SIP. SIP shall be derived from farnesene produced from fermentable sugars. Subsequent processing of farnesene into iso-paraffins shall include a combination of hydroprocessing and fractionation operations and may include other conventional refinery processes. In particular, hydroprocessing operations consist of reacting hydrogen with farnesene feedstock, and fractionation operations consist of gas/liquid separation and isolation of SIP. For example, fractionation typically includes a distillation step.

B.4 DETAILED BATCH REQUIREMENTS

B.4.1 Batch requirements. Each batch of synthetic blending component shall conform to the requirements specified in table B-I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

B.4.2 SIP batch. The SIP blend component shall meet the requirements of table B-I. It is not necessary to analyze each batch of SIP for compliance with table B-II once it is demonstrated that the process scheme is adequately controlled to support the expectation that these requirements are always met. At a minimum, batches shall be required to meet the specifications of table B-II when new production facilities or schemes are established, or when significant changes to existing production operations are implemented, such as the introduction of a new feedstock material.

TABLE B-I. Detailed batch requirements; SIP.

Characteristic	Requirement		ASTM Method
	Minimum	Maximum	
Acid Number, mg KOH/g	--	0.015	ASTM D974 (R), ASTM D664
Cloud Point, °C (°F)	--	-70 (-94)	ASTM D2500 (R), ASTM D5771, ASTM D5772, ASTM D5773
Density, at 15 °C (59 °F), kg/m^3	765.0	780.0	ASTM D1298 (R), ASTM D4052, ASTM D287
Cetane Number, or Derived Cetane Number	42 42.0	80 80.0	ASTM D613 (R) ASTM D6890
Distillation: Initial Boiling Point, °C (°F) 10% Recovered, °C (°F) 50% Recovered, °C (°F) 90% Recovered, °C (°F) Final Boiling Point, °C (°F) T90-T10, °C (°F) Residue + Loss, volume %	 Record -- Record Record -- -- --	 -- 250.0 (482.0) -- -- 255.0 (491.0) 5.0 (41.0) 3.0	ASTM D86
Diesel Microseparometer	85	--	ASTM D7261
Existent Gum, mg/100 mL	--	7	ASTM D381
Flash Point, °C (°F)	100.0 (212.0)	--	ASTM D93 (R) [1/], ASTM D3828
Heating Value, MJ/kg	43.5	--	ASTM D4809
Hexahydrofarnesol, mass %	--	1.5	ASTM D7974
Particulate Contamination, mg/L	--	1.0	ASTM D6217 (R), ASTM D5452
Thermal Stability: Change in Pressure Drop, mm of Hg and Tube Deposit Code, less than or Average Deposit Thickness, nm, over area of 2.5 mm^2	 -- 	 25 3 [3/] 85	ASTM D3241 [2/]
Total Water, mg/kg	--	75	ASTM D6304

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

TABLE B-I. Detailed batch requirements; SIP – Continued.

FOOTNOTES:

1/ ASTM D3828 may give results up to 1.7 °C (3.06 °F) below the ASTM D93 results.

2/ See B.4.4.1 and B.4.4.2 for ASTM D3241 test conditions and procedures.

3/ If the visual rating of the heater tube shows Peacock (P) or Abnormal (A) type deposits, the fuel sample is not acceptable.

NOTE: Table B-I identifies the referee test method first, followed by the notation "(R)". "(R)" denotes the referee test method.

TABLE B-II. Other detailed requirements; SIP.

Characteristic	Requirement		ASTM Method
	Minimum	Maximum	
Hydrocarbon Composition			
Saturated Hydrocarbons, mass %	98	--	ASTM D7974
Farnesane, mass %	97	--	ASTM D7974
Olefins, mgBr_2/100 grams	--	300	ASTM D2710
Aromatics, mass %	--	0.5	ASTM D2425
Carbon and Hydrogen, mass %	99.5	--	ASTM D5291
Non-Hydrocarbon Composition			
Nitrogen, mg/kg	--	2	ASTM D4629
Sulfur, mg/kg	--	2	ASTM D5453 (R), ASTM D2622
Metals 1/ (Al, Ca, Co, Cr, Cu, Fe, K, Li, Mg, Mn, Mo, Na, Ni, P, Pb, Pd, Pt, Sn, Sr, Ti, V, Zn), mg/kg	--	0.10 per metal	ASTM D7111
Halogens, mg/kg	--	1 per halogen	ASTM D7359

FOOTNOTE:

1/ All detected metals below the detection limits shall be considered as 0 micrograms/kg. Only the metals with measured values higher than their respective detection limits shall be considered as legitimate values for calculation.

NOTE: Table B-II identifies the referee test method first, followed by the notation "(R)". "(R)" denotes the referee test method.

B.4.3 Fuel additives. When specified (see 6.2), information concerning the name and dosage rate of each additive used shall be made available.

B.4.4 Thermal stability. The thermal stability test shall be conducted in accordance with ASTM D3241. The heater tube shall be rated visually in accordance with ASTM D3241, Heater Tubes Annex, Test Method for Visual Rating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

B.4.4.1 Test conditions. The following test conditions shall apply:

a. Minimum heater tube temperature at maximum point: 325 °C (617 °F)

b. Fuel system pressure: 3.45 MPa (500 psig)

c. Fuel flow rate: 3.0 mL/minute

d. Test duration: 150 minutes

B.4.4.2 ASTM D3241 procedure.

a. The differential pressure in mm Hg at 150 minutes or the time to differential pressure of 25 mm Hg, whichever comes first, shall be recorded.

b. The heater tube deposit code rating shall be recorded at the end of the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
- Army – CR4
- Navy – SH
- Air Force – 68
- DLA – PS

Review activities:
- Army – AT
- Navy – CG, MC, SA
- DLA – GS

Preparing activity:
- Navy – SH
- (Project 9140-2024-001)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:34Z
Check the source to verify that this is the current version before use.