INCH-POUND

MIL-P-608K
20 November 1991
SUPERSEDING
MIL-P-608J
15 May 1987

MILITARY SPECIFICATION

POLE SECTION, TENT: UPRIGHT AND ADAPTER, TENT POLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type of tent pole section and tent pole adapter.

1.2 Classification. This document covers the following items as specified (see 6.2):

Item 1 - Pole section, tent
Item 2 - Adapter, tent pole

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 8340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-16T07:53Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

A-A-208	-	Ink, Marking, Stencil, Opaque (Porous and Non-Porous Surfaces)
A-A-1558	-	Paint, Stencil
QQ-B-613	-	Brass, Leaded and Nonleaded: Flat Products (Plate, Bar, Sheet, and Strip)
QQ-W-321	-	Wire, Copper Alloy
TT-E-529	-	Enamel, Alkyd, Semigloss, Low VOC Content
WW-T-791	-	Tube, Brass, Seamless
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-F-495	-	Finish, Chemical, Black, for Copper Alloys

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-4-53	-	Pole Section, Tent: Upright and Adapter, Tent Pole; Adapter
5-4-136	-	Pole Section, Tent: Upright and Adapter, Tent Pole; Pole Section

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-UX, Natick, MA 01760-5017.)

Source: https://assist.dla.mil -- Downloaded: 202640-16T07:53Z
Check the source to verify that this is the currentversion before use.

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 366 - Steel, Sheet, Carbon, Cold-Rolled, Commercial Quality
A 512 - Cold-Drawn Buttweld Carbon Steel Mechanical Tubing
B 633 - Electrodeposited Coatings of Zinc on Iron and Steel
D 3951 - Standard Practice for Commercial Packaging
D 4442 - Direct Moisture Content Measurement of Wood and Wood-Base Materials

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

* 3.2 Material. The materials used shall conform to the applicable referenced documents specified herein. Where materials are not definitely specified, they shall be of the quality and type normally used by the manufacturer, provided the completed item complies with all provisions of this document. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.2.1 Wood. The wood used for the tent pole section and tent pole adapter shall be uniformly dried without brashness or honeycombing. At the time of fabrication, the wood shall have a moisture content of not more than 12 percent when tested as specified in 4.4.1.1. The slope of the grain shall not exceed 1 inch in 12 inches on any face when tested as specified in 4.4.1.1. The wood shall be any of the following species:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:53Z
Check the source to verify that this is the current version before use.

Soft woods	Hard woods
Cedar, Alaska Yellow	Ash, White
Cedar, Port Orford	Beech
Cypress	Birch
Douglas Fir	Elm, Rock
Hemlock, Western	Hickory
Larch, Western	Keruing/Apitong
Pine, Red (Norway)	Maple, Sugar or Black (Hard)
Pine, Southern Yellow	Oak
Redwood	Pecan
Spruce	Phillipine Kapur Malaysian
	Poplar, Yellow
	Sweet Gum

Soft wood shall have not less than four annual rings per inch, measured radially at either end of the pole. When tested as specified in 4.4.1.1, hardwood, excluding ash, shall weigh not less than 32 pounds per cubic foot at a moisture content of 12 percent. Ash shall weigh not less than 38 pounds per cubic foot at a moisture content of 12 percent.

3.2.2 Steel.

3.2.2.1 Sheet and strip. Steel sheet and strip shall conform to any quality, temper, and finish of ASTM A 366.

3.2.2.2 Tube. Steel tube shall conform to steel number MT 1010, MT 1015, or MT 1020 of ASTM A 512.

3.2.3 Brass.

3.2.3.1 Sheet and strip. Brass sheet and strip shall conform to copper alloy number 268, extra hard temper,or copper allow number 260, half-hard temper of QQ-B-613, as applicable.

3.2.3.2 Tube. Brass tube shall conform to grade B, type IV of WW-T-791.

3.2.3.3 Wire. Copper alloy wire shall conform to alloy numbers 210 or 220, half-hard temper of QQ-W-321.

* 3.2.4 Enamel. Enamel shall conform to Olive Drab 24084 of TT-E-529.

* 3.2.5 Marking ink. The marking ink shall be black in color conforming to class 1 of A-A-1558 or type II, or IV of A-A-208.

3.3 Construction. Construction of the tent pole section and tent pole adapter shall be in accordance with the requirements of Drawings 5-4-53 and 5-4-136, and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:53Z
Check the source to verify that this is the current version before use.

3.3.1 Ferrules, male and female. The male and female ferrules shall remain round without bulging or distortion following staking of the ferrules to the wood component.

3.3.2 Ferrules, 7/8 inch o.d.. The 7/8 inch o.d. brass ferrules shall be placed over the notched ends of the bodies of the adapter and shall be secured with escutcheon pins as shown on Drawing 5-4-53.

3.3.3 Rivets. Rivets for adapter links shall be neatly headed and set so as to permit easy movement of the connected parts without being excessively loose. Peened ends of rivets shall be free from burrs and rough edges.

3.4 Details of components.

3.4.1 Poles. Wood used in the fabrication of the pole section and adapter shall conform to 3.2.1. The surface shall be sanded or otherwise finished to produce a smooth surface free from sanding skip, rough machine marks, splinters, torn grain, machine burn, and gouge. Drilling, counter boring, notching, and machining of ends shall be done with precision. Wood components shall be free from decay, split, wane, and unsound knots. Other defects shall be limited as follows:

(a) Irregularity of grain. Local irregularity of grain shall not exceed one-third the diameter of the pole or adapter.

(b) Knots. Naturally sound, tight knots shall not exceed 1/4 inch in average diameter and shall not occur in cluster (group of more than three). Unsound knots may be removed with the following provisions:

(1) The knot holes are cleaned out and are free of any bark, pitch, or sap.
(2) The cleaned knot holes are completely filled with an epoxy filler.
(3) The epoxy fillings within the holes are sound, tight, and do not exceed the dimension requirements of sound, tight knots as specified herein.

(c) Holes. Any hole having a diameter not exceeding 1/4 inch in average diameter will be acceptable provided the hole is completely filled with an epoxy filler, the epoxy filler within the hole is sound and tight, and epoxy filled holes do not occur within 2 inches of each other.

(d) Checks. Surface checks shall be limited to openings not more than 1/4 inch long or more than 1/32 inch wide. There shall not be more than one such check in any pole section or adapter.

(e) Shakes. Shakes shall be limited in the same manner as checks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:53Z
Check the source to verify that this is the current version before use.

(f) Cracks. Hairline cracks, 1 inch or less in length, caused by drilling the pole, shall be permissible provided the end of pole has been machined with precision specified (e.g., machined end has a uniform thickness around rim of 0.06 inch + 0.01, - 0.00 inch).

3.4.2 Ferrules.

3.4.2.1 Male. The male ferrules shall be fabricated of steel specified in 3.2.2.1 or brass sheet specified in 3.2.3.1. The alloy and temper of the brass sheet shall be as specified on the applicable drawing.

3.4.2.2 Female. The female ferrules shall be fabricated of sheet tube specified in 3.2.2.2 or brass tube specified in 3.2.3.2.

3.4.3 Link. The link shall be fabricated of brass sheet or brass strip specified in 3.2.3.1 except that the alloy and temper shall be as specified on Drawing 5-4-53.

3.4.4 Ferrule, 7/8 inch o.d.. The 7/8 inch o.d. ferrule shall be fabricated of brass tube specified in 3.2.3.2.

3.4.5 Ring. The ring shall be fabricated of brass wire specified in 3.2.3.3 and in accordance with Drawing 5-4-53.

3.4.6 Escutcheon pins. Escutcheon pins shall be of any type brass and shall be made in accordance with the requirements of Drawing 5-4-53.

3.4.7 Rivets. Solid rivets shall be of any type brass and shall be made in accordance with Drawing 5-4-53.

3.5 Finish.

3.5.1 Wood components. One coat of enamel specified in 3.2.4 shall be applied to all surfaces of the wood components except in the recess of the pole section and the slot of the adapter, where overspray may be present but not allowed to build up preventing operation of the pole. The finish coating shall be smooth, uniform and dry without blistering, peeling, chipping, and cracking. The finish shall be free from any area of no film, and any sag, run, and scratch greater than 1/2 inch in length.

3.5.2 Ferrules, steel, male and female. Prior to assembly to pole section and adapter bodies, all surfaces of the male and female steel ferrules shall be given a zinc coating conforming to type IV, SC3, of ASTM B 633, except in places difficult to plate such as internal surfaces of the male ferrule. Color of the type IV chromate finish shall be Olive Drab, free from stain or discoloration. The finish shall be smooth and free from blister, peel, pit, lump, and nodules.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:53Z
Check the source to verify that this is the current version before use.

3.5.3 Brass components. After completion of all brazing, grinding, and machining operations, and prior to assembly to pole section or adapter bodies, all brass components shall be given a black chemical finish conforming to MIL-F-495.

3.6 Marking for identification. The tent pole section and the tent pole adapter shall be marked as shown on Drawings 5-4-53 and 5-4-136 with ink specified in 3.2.5. The markings shall be legible, retain the original color, not smear with vigorous rubbing, nor crack or peel when immersed in water and tested as specified in 4.5.3. In addition to identification marking, the unmarked leg of the tent pole adapter shall be stamped or marked "Adapter, Tent Pole" in characters not less than 1/8 inch high.

* 3.7 Workmanship. The female ferrule cavity after assembly shall be clean, smooth, and free of wood particles and splinters. Wood components shall be free of any crack, break, and chip-out. Wood components shall be not warped more than 3/16 inch. Metal components shall be free from malformation, twisting, fracture, crack, break, hole (except where specified), burr, rough edge, and shall not be bent out of shape. Brazed joints shall be ground smooth. Head of escutcheon pin shall be a close fit to ferrule (e.g. head shall be not cocked more than 1/32 inch). The end item shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:53Z
Check the source to verify that this is the current version before use.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for defects specified in 4.4.3 and 4.4.4 and shall be tested for resistance to water immersion as specified in 4.5.3. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component testing. In addition to the quality assurance provisions of the subsidiary documents and drawings, components shall be tested for the characteristics specified in table I. The inspection level shall be S-1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:53Z
Check the source to verify that this is the current version before use.

TABLE I. Component tests

Component and lot expressed in terms of	Characteristic	Requirement para.	Test method para.	Requirement applicable to: Individual	Requirement applicable to: Lot average	Number determinations per sample unit	Results reported as	Sample unit
Wood (100 board feet)	Moisture content	3.2.1	ASTM D 4442 1/	X	-	3	Average of 3 determinations to nearest 0.1%	One piece prior to milling
	Slope of grain	3.2.1	4.5.1	X	-	1	Pass or fail	One piece prior to milling
	Weight of hardwood	3.2.1	4.5.2	X	-	1	To nearest 0.1 pound per cu. ft.	One piece suitable size

1/ A sample unit of wood having less than 8 or more than 12 percent moisture content shall be classified as defective.

4.4.2 In-process inspection.

4.4.2.1 In-process examination. The zinc coating of steel ferrules prior to assembly to pole section or adapter bodies shall be examined to establish conformance to the requirements in 3.5.2. Whenever a nonconformance is noted, correction shall be made to the affected items, to the lot in process, and to the operation. Parts that cannot be corrected shall be removed.

4.4.2.2 In-process dimensional examination. All dimensions applicable to the wood body of the tent pole adapter section specified on Drawing 5-4-53 and all dimensions applicable to the wood body of the tent pole section specified on Drawing 5-4-136 shall be examined prior to assembly of metal components. Any dimension not within specified requirements shall be classified as a defect. The lot size shall be all the bodies of pole section or adapter, as applicable, submitted for inspection at one time. The sample unit shall be one body of pole section or adapter, as applicable. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:53Z
Check the source to verify that this is the current version before use.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table II. The lot size shall consist of all completely fabricated pole sections or adapters, as applicable, submitted for inspection at one time. The sample unit shall be one pole section or one adapter, as applicable. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 1.5 for major defects, 6.5 for major and minor A combined defects, and 15 for total (major, minor A and minor B combined) defects.

TABLE II. End item visual defects

Examine	Defect	Classification Major	Minor A	Minor B
Wood component finish	Missing	101		
	Color of finish not as specified			301
	Area of no film (except the recess in pole section and the slot in the adapter)		201	
	Coating is not smooth and uniform			302
	Finish is not dry (e.g., wet or tacky to touch)			303
	Coating is blistered, peeled, chipped, or cracked			304
	Sag, run, or scratch greater than 1/2 inch in length			305
Steel component finish	Not zinc plated, chromate finish (except in places difficult to plate such as internal surfaces of the male ferrule)	102		
	Color of finish not as specified.			306
	Stain or discoloration			307
	Not smooth			308
	Presence of blister, peel, pit, lump, or nodules		202	
Brass component finsish	Brazing, grinding, or machining operation was performed after application of finish		203	
	Not black chemical finish	103		
Construction	Any component missing	104		
	Species of wood not as specified	105		
	Any component not fabricated as specified: - Male or female ferrule not staked as shown on applicable drawing		204	

Source: https://assist.dla.mil -- Downloaded: 202610-16T07:53Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Construction (cont'd)	- Points of stake in different direction than shown on applicable drawing			309
	- Male or female ferrule not round following staking of the ferrules to the wood component or having bulging or distortion	205		
	- 7/8 inch o.d. brass ferrule not secured with escutcheon pin as specified on Drawing 5-4-53	206		
	- Ring not brazed as shown on Drawing 5-4-53	207		
	- Wood component not cut in the direction of the grain	208		
	- Rivet not neatly and securely set so as to permit easy movement of the connected parts without being excessively loose	209		
	- Burr or rough edge on peened end of rivet			310
Wood body	Brashness, honeycombing, or case hardening of wood	210		
	Not smooth surface			311
	Evidence of sanding skip, rough machine marks, splinter, torn grain, machine burn, or gouges			312
	Evidence of decay, split, wane, or unsound knot	211		
	Irregularity of grain exceeding one-third the diameter of the wood body			313
	Evidence of sound tight knot exceeding 1/4 inch in average diameter			314
	Evidence of cluster of knots			315
	Evidence of epoxy filled hole exceeding 1/4 inch in average diameter			316
	Any epoxy filled hole having evidence of bark, pitch, or sap			317

Source: https://assist.dla.mil -- Downloaded: 202610-16T07:53Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Wood body (cont'd)	Evidence of epoxy filled holes occurring within 2 inches of each other			318
	Any epoxy filled hole not completely filled with an epoxy filler			319
	The epoxy filling within the hole is loose (e.g., not sound)			320
	Evidence of surface check or shake more than 1/32 inch wide or more than 1/4 inch long			321
	Evidence of more than one permissible check or shake			322
	Less than four annual rings per inch at either end of the soft wood component			323
	Splinter, sliver, gouge, torn grain, or machine burn			324
	Any non-permissable defect that has been filled with plastic wood or other filler material (except for epoxy filled holes as specified herein)			325
Workmanship	Female ferrule cavity not clean or smooth			326
	Cracks more than 1 inch caused by drilling, break, or chip-out in wood component		212	
	Wood component is warped more than 3/16 inch			327
	Metal component is bent out of shape, malformed, twisted, fractured, cracked, or broken		213	
	Metal component has hole (except where specified), burr, or rough edge		214	
	Brazed joint of ring not ground smooth			328
	Head of escutcheon pin is not a close fit to ferrule (e.g., head is cocked more than 1/32 inch)			329

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:53Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Identification marking	Missing	215		
	Illegible, color or marking not as specified, smeared, cracked, peeled, checked, or flaked			330
	Unmarked leg of adapter not stamped or marked as specified			331
	Marking or stamping not size specified, not in specified location, incomplete, or misspelled			332

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions annotated with an asterisk on the drawings. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of pole sections or adapters, as applicable. The sample unit shall be one pole section or one adapter, as applicable. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 End item testing. The end items shall conform to the marking requirements specified in 3.6 when tested as specified in 4.5.3. The lot size shall be expressed in units of pole sections or adapters, as applicable. The sample unit shall be one pole section or one adapter, as applicable. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:53Z
Check the source to verify that this is the current version before use.

Examine	Defect
Content	Number of tent pole sections or tent pole adapters per bundle or container, as applicable, is more or less than required

4.5 Methods of inspection.

4.5.1 Slope of wood grain test. The slope of grain shall be determined by combining the grain direction of two adjacent faces. When one of these faces is straight grained, the true slope of grain is shown on the other face. Where there is a slope in both faces, the true or combined slope is greater than the slope on either face. Slope of grain is shown on edge grained faces by the summer wood bands, on flat grained faces by resin ducts, by the direction in which a free flowing ink or dye spreads, or by the course taken by a narrow strip lifted by a knife and torn out. Direction of fiber may also be measured by a slope of grain detector. Any sample unit having a slope of wood grain exceeding 1 inch in 12 inches shall be classified as a defect.

4.5.2 Weight of wood test. The weight of the wood expressed in pounds per cubic foot shall be determined by any approved commercial method. Any sample unit of hardwood, excluding ash, having a weight less than 32 pounds per cubic foot at a moisture content of 12 percent shall be classified as defective. Any sample unit of ash having a weight less than 38 pounds per cubic foot at a moisture content of 12 percent shall be classified as a defect.

4.5.3 Resistance to water immersion (marking legibility) test. Immerse one tent pole section or tent pole adapter, as applicable, in distilled water at 70°F for a minimum period of 4 hours. Remove from the water and air-dry for a minimum period of 1 hour. Rub the marking vigorously with the finger. Any illegible, color changed, smeared, cracked, or peeled marking shall be classified as a defect.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A preservation. Three tent pole sections shall be placed adjacent to each other and securely tied together at each end with cord or twine to form a compact bundle. Two folded adapters shall be alternated end for end, tied, and bundled in the same manner.

5.1.2 Commercial preservation. Tent pole sections and tent pole adapters shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:53Z
Check the source to verify that this is the current version before use.

5.2.1 Level A packing. Three hundred tent pole sections or one hundred fifty tent pole adapters, preserved as specified in 5.1, shall be packed in the most compact manner in a snug-fitting cleated plywood container conforming to overseas type, style A or J, grade A or B, type 2 load of PPP-B-601 or a nailed lock cornered container conforming to class 2, style 2 or 4, grade A or B, type 2 load of PPP-B-621. Each shipping container shall be closed and strapped in accordance with the appendix of the applicable container specification.

* 5.2.2 Level B packing. Three hundred tent pole sections or one hundred and fifty tent pole adapters, preserved as specified in 5.1, shall be packed in the most compact manner in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF, variety DW, or type SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.6.

5.2.3 Commercial packing. Tent pole sections or tent pole adapters, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The tent pole sections are intended for use with Tent, Shelter Half, MIL-T-3725. The tent pole sections and tent pole adapter are intended for use with Tent, Mountain, Two-Man, MIL-T-1926.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Item required (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article is required (see 3.1, 4.3, and 6.3).
e. Levels of preservation and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:53Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209. The first article should be preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 International standardization agreements. Certain provisions of this document are the subject of international standardization agreement as cited in NATO, STANAG No. 2882, relative to camouflage requirements for tents, shelters, and subsidiary components. When amendment, revision, or cancellation of this document is proposed that will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.5 Subject term (key word) listing.

Adjuster
Shaft part
Wood and metal

6.6 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this specification based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Navy - MC
Air Force - 82
DLA - CT

User activity:

Air Force - 45

Preparing activity:

Army - GL

Project 8340-0554

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:53Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-608K	20 November 1991

3. DOCUMENT TITLE: POLE SECTION, TENT: UPRIGHT AND ADAPTER, TENT POLE

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
Army Natick RD&E Center	(1) Commercial 508-651-4531	(2) AUTOVON 256-4531
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-01-16T07:53Z
Check the source to verify that this is the current version before use.