INCH-POUND

MIL-DTL-24643/60
9 September 2005

DETAIL SPECIFICATION SHEET

CABLE, ELECTRICAL, TYPE LSC5 AND LSC5W

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-24643.

This cable can be manufactured in two variations: LSC5 (Unshielded (UTP), Non-Watertight) and LSC5W (Unshielded (UTP), Watertight).

REQUIREMENTS:

Qualification Required.

Construction (Non-Watertight and Watertight)

First	-	Copper conductor, solid, 24 AWG nominal.
Second	-	Polyolefin insulation. Wall thickness as necessary, in order for the completed cable to meet the specified electrical requirements. Maximum insulation diameter shall not exceed 0.046 inch.
Third	-	Two insulated conductors, twisted together such that they meet the electrical requirements specified below. Wire identification codes shall be in compliance with ANSI/TIA-568-B.2 as follows: Pair 1 – white/blue and blue, Pair 2 – white/orange and orange, Pair 3 – white/green and green, Pair 4 – white/brown and brown.

Construction Variant for type LSC5

Fourth	-	Four pairs cabled together with a lay as required to meet electrical requirements.
Fifth	-	Cross-linked polyolefin jacket. Minimum thickness of 0.040 inch.

Construction Variant for type LSC5W

Fourth	-	Four pairs cabled together with a lay as required to meet electrical requirements.
Fifth	-	For watertight variant, filler material shall meet the requirements of 3.3.5 and 3.3.5.3 of MIL-DTL-24643.
Sixth	-	An optional binder tape applied with overlap.
Seventh	-	Cross-linked polyolefin jacket. Minimum thickness of 0.040 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:19Z
Check the source to verify that this is the current version before use.

TABLE I. Details.

Military Part No. M24643/60	Type	Number of Pairs	Overall Diameter (in.)	
			Minimum	Maximum
-01UN	LSC5-4	4	0.220	0.270
-02UN	LSC5W-4	4	0.230	0.290

EXAMINATION AND TESTS:

Basic Electricals:

DC resistance (ohms/100 m)	9.38 max.
DC resistance unbalance	5% max.
Jacket flaws	No Failure
Conductor continuity	No Failure

Group A:

Visual and dimensional	No Failure
Watertightness (type LSC5W-4 only)	No Failure
Capacitance	
Mutual capacitance of a pair (max. @1 kHz)	5.6 nf/100 m
Pair to ground capacitance unbalance (max. @1 kHz)	330 pf /100 m
Input impedance (1 MHz to 100 MHz)	100 ohms ±15%

TABLE II. Swept electrical parameters.

Frequency (MHz)	**1.0**	**4.0**	**10**	**16**	**31.25**	**62.5**	**100**
Return Loss dB/100 m (min.)	20.0	23.0	25.0	25.0	23.6	21.5	20.1
Insertion Loss dB/100 m (max.)	2.0	4.1	6.5	8.2	11.7	17.0	22.0
NEXT dB/100 m (min.)	65.3	56.3	50.3	47.2	42.9	38.4	35.3
ELFEXT dB/100 m (min.)	63.8	51.8	43.8	39.7	33.9	27.9	23.8
PS NEXT dB/100 m (min.)	62.3	53.3	47.3	44.2	39.9	35.4	32.3
PS ELFEXT dB/100 m (min.)	60.8	48.8	40.8	36.7	30.9	24.9	20.8
Propagation Delay ns/100 m (max.)	570	552	545	543	540	539	538
Delay Skew ns/100 m (max.)	45	45	45	45	45	45	45
Note: Values are for reference only. Actual values shall be determined utilizing the formulas in ANSI/TIA–568-B.2.							

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:19Z
Check the source to verify that this is the current version before use.

Group B:	
Drip – 95 ±1 ºC	Zero
Tear (pounds per inch thickness, min.) (ASTM D470)	35
Physicals (unaged)	
Insulation	
Tensile strength (lb/in^2, min.)	1300
Elongation (percent, min.)	160
Jacket	
Tensile strength (lb/in^2, min.)	1300
Elongation (percent, min.)	160
Cross-linked proof test (percent, max.)	
Jacket	50
Group C:	
Physicals (aged air oven)	
Insulation (polyolefin)	
Tensile strength (percent of unaged, min.)	75%
Elongation – (percent of unaged, min.)	75%
Jacket	
Tensile strength (percent of unaged, min.)	60%
Elongation (percent of unaged, min.)	60%
Shrinkage	No Failure
Cable filler removability	No Failure
Heat distortion (percent of unaged, max.)	30
Conformance to material, construction and coverage	No Failure
Permanence of printing (jacket) (cycles, min.)	125
Group D:	
Flame propagation (cable)	No Failure
Qualification Inspection:	
Qualification inspection shall include basic electrical, all groups A, B and C, plus the following:	
Aging and compatibility (cable) 95 ±1 ºC	No Failure
Abrasion resistance (jacket)	No Failure
Acid gas equivalent (percent, max.)	
Jacket	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:19Z
Check the source to verify that this is the current version before use.

Fillers	8
Insulation	18
Halogen content (percent, max.)	
Jacket	0.2
Fillers	0.2
Immersion (jacket)	
Tensile strength (percent of unaged, min.)	50
Elongation (percent of unaged, min.)	50
Smoke index, max.	
Jacket	25
Fillers	45
Insulation	45
Toxicity index, max.	
Jacket	5
Fillers	5
Insulation	1.5
Durometer (jacket) – Type A (hardness, min.)	80
Weathering (jacket)	No Failure

Custodians:
Army – MI
Navy – SH

Preparing Activity:
Navy – SH
(Project 6145-2005-012)

Review Activities:
Army – AR, AV, CR
Navy – CG, EC
DLA – IS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:19Z
Check the source to verify that this is the current version before use.