INCH-POUND
MIL-DTL-24643/61A
28 January 2010
SUPERSEDING
MIL-DTL-24643/61
9 September 2005

DETAIL SPECIFICATION SHEET

CABLE, ELECTRICAL, TYPE LSC5P, LSC5POS, AND LSC5POSR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-24643.

This cable can be manufactured in three variations: LSC5P (Unshielded Patch Cable, Non-Watertight), LSC5POS (AWG 24, Metallic Foil and Braid Patch Cable, Non-Watertight), and LSC5POSR (AWG 26, Metallic Foil and Braid Patch Cable, Non-Watertight).

Construction (Shielded and UTP, Non-Watertight)

First	-	Copper conductor, tin-coated, stranded, 24 AWG or 26 AWG.
Second	-	Polyolefin insulation. Wall thickness as necessary, in order for the completed cable to comply with the specified electrical requirements. Maximum insulation diameter shall not exceed 0.046 inch.
Third	-	Two insulated conductors, twisted together such that they comply with the electrical requirements specified herein. Wire identification codes shall be in compliance with ANSI/TIA-568-C.2 as follows: Pair 1 – white/blue and blue Pair 2 – white/orange and orange Pair 3 – white/green and green Pair 4 – white/brown and brown
Fourth	-	Four pairs cabled together with a lay as required to comply with electrical requirements.

Construction Variant for Type LSC5P

Fifth	-	Cross-linked polyolefin jacket. Minimum thickness of 0.040 inch.

Construction Variant for Types LSC5POS and LSC5POSR

Fifth	-	An optional binder.
Sixth	-	Metallic foil/polyester tape (metallic foil side facing out and in contact with the braid).
Seventh	-	Braided shield of 36 AWG or 34 AWG tin-coated copper. Coverage as required to comply with shield performance requirements.
Eighth	-	An optional binder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:20Z
Check the source to verify that this is the current version before use.

Ninth - Cross-linked polyolefin jacket. Minimum thickness of 0.040 inch.

TABLE I. Details.

Military part no. M24643/61	AWG	Type	Number of pairs	Overall diameter (in.)	
				Min.	Max.
-01UN	24	LSC5P-4	4	0.230	0.280
-02UD	24	LSC5POS-4	4	0.290	0.370
-03UD	26	LSC5POSR-4	4	0.230	0.280

REQUIREMENTS:

Qualification Required.

INSPECTION:

Basic Electricals:

DC resistance (ohms/100 m)	
26 AWG (max.)	14
24 AWG (max.)	9.38
DC resistance unbalance (percent, max.)	5
Voltage withstand	
Conductor to conductor	1.5kVAC or 2.5kVDC
Conductor to shield	1.5kVAC or 2.5kVDC

Group A:

Visual and dimensional	No failure
Capacitance	
Mutual capacitance of a pair (nominal @1 kHz)	5.6 nf/100 m
Pair to ground capacitance unbalance (max. @1 kHz)	330 pf /100 m
Input impedance (1 MHz to 100 MHz)	100 ohms ±15%

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:20Z
Check the source to verify that this is the current version before use.

TABLE II. Swept electrical parameters.

Frequency (MHz)	1.0	4.0	10	16	31.25	62.5	100
Return loss dB/100 m (min.)	20.0	23.0	25.0	25.0	23.6	21.5	20.1
Insertion loss dB/100 m 24 AWG (max.)	2.4	4.9	7.8	9.8	14.0	20.4	26.4
Insertion loss dB/100 m 26 AWG (max.)	3.0	6.2	9.8	12.3	17.6	25.5	33.0
NEXT dB/100 m (min.)	65.3	56.3	50.3	47.2	42.9	38.4	35.3
ELFEXT dB/100 m (min.)	63.8	51.8	43.8	39.7	33.9	27.9	23.8
PS NEXT dB/100 m (min.)	62.3	53.3	47.3	44.2	39.9	35.4	32.3
PS ELFEXT db/100 m (min.)	60.8	48.8	40.8	36.7	30.9	24.9	20.8
Propagation delay ns/100 m (max.)	570	552	545	543	540	539	538
Delay skew ns/100 m (max.)	45	45	45	45	45	45	45
NOTE: Values are for reference only. Actual values shall be determined utilizing the formulas in ANSI/TIA-568-C.2.							

Group B:

Drip (95±1 °C)	Zero
Tear (lb/in thickness, min.) (ASTM D470)	35
Physicals (unaged)	
Insulation (polyolefin)	
Tensile strength (lb/in^2 min.)	700
Elongation (percent, min.)	160
Jacket	
Tensile strength (lb/in^2 min.)	1300
Elongation (percent, min.)	160
Thermoset proof test (percent, max.)	
Jacket	50

Group C:

Physicals (aged air oven)

Insulation (polyolefin)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:20Z
Check the source to verify that this is the current version before use.

Tensile strength (percent of unaged, min.) (lb/in^2 min.)	75
Elongation (percent of unaged, min.)	75
Jacket	
Tensile strength (percent of unaged, min.) (lb/in^2 min.)	60
Elongation (percent of unaged, min.)	60
Shrinkage	No failure
Heat Distortion (percent of unaged, max.)	30
Conformance to material, construction and coverage	No failure
Surface transfer impedance (Types LSC5POS and LSC5POSR)	
Milliohms (per meter, max.)	700
EMP response (dB, min.)	60
Permanence of printing (jacket) (cycles, min.)	125
Group D:	
Flame propagation (cable)	No failure
Qualification Inspection:	
Qualification inspection shall include basic electricals; groups A, B, C, and D; plus the following:	
Aging and compatibility (cable) (95±2 °C)	No failure
Abrasion resistance (jacket)	75
Acid gas equivalent (percent, max.)	
Jacket	2
Insulation	18
Halogen content (percent, max.)	
Jacket	0.2
Insulation	0.2
Immersion (jacket)	
Tensile strength (percent of unaged, min.)	50
Elongation (percent of unaged, min.)	50
Smoke index, max.	
Jacket	25
Insulation	45
Toxicity index, max.	
Jacket	5
Insulation	1.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:20Z
Check the source to verify that this is the current version before use.

Durometer (jacket) – Type A (hardness, min.)	80
Weathering (jacket)	No failure

UNIT ORDERING LENGTHS:

Type and size	Feet (nominal)
LSC5P, LSC5POS, LSC5POSR	500

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army – MI
Navy – SH

Preparing Activity:
Navy – SH
(Project 6145-2009-104)

Review Activities:
Army – AR, AV, CR
Navy – CG, EC
DLA – CC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:20Z
Check the source to verify that this is the current version before use.