BY ORDER OF THE COMMANDER
AIR FORCE GLOBAL STRIKE COMMAND

AIR FORCE GLOBAL STRIKE COMMAND
INSTRUCTION 21-105

22 APRIL 2026

Maintenance

CORROSION PREVENTION AND CONTROL PROGRAM

COMPLIANCE WITH THIS PUBLICATION IS MANDATORY

ACCESSIBILITY: Publications and forms are available for downloading or ordering on the e-Publishing website at **www.e-Publishing.af.mil**.

RELEASABILITY: There are no releasability restrictions on this publication.

OPR: AFGSC/A4MQ — Certified by: AFGSC/A4M

Supersedes: AFGSCI 21-105, 17 June 2022 — Pages: 35

This instruction implements Air Force Policy Directive (AFPD) 21-1, *Maintenance of Military Material*, and is consistent with AFPD 13-5, *Air Force Nuclear Enterprise*. It references Department of the Air Force Instruction (DAFI) 21-101, *Aircraft and Equipment Maintenance Management*, and Air Force Manual (AFMAN) 21-202, *Missile Maintenance Management*, and establishes policy and assigns responsibility to establish and support the Corrosion Prevention and Control Program for Air Force Global Strike Command (AFGSC). This instruction applies to all military and civilian members of the United States Air Force (USAF), Air Force Reserve (AFR) and Air National Guard (ANG) upon mobilization, and/or AFGSC-led classic AFRC and ANG associations as well as those with contractual obligation to comply with Air Force (AF) publications. It does not apply to United States Space Force. Ensure all records created as a result of processes prescribed in this publication adhere to AFI 33-322, *Records Management and Information Governance Program*, and disposed IAW the Air Force Records Disposition Schedule located in the Air Force Records Information Management System. Refer recommended changes and questions about this publication to the Office of Primary Responsibility (OPR), AFGSC/A4MQ, using the Department of the Air Force (DAF) Form 847, *Recommendation for Change of Product*. Route DAF Form 847s from the field through the appropriate functional chain of command to **AFGSC.A4M.workflow@us.af.mil**. This publication may be supplemented at any level, but all supplements must be routed to the OPR of this publication for coordination prior to certification and approval. The authorities to waive wing, and unit level requirements in this publication are identified with a Tier ("T-0, or T-3") number following the compliance statement. See Department of the Air Force Manual (DAFMAN) 90-161, *Publishing Processes and Procedures*, for a description of the authorities associated with the tier numbers. Submit requests for waivers through the chain of command to the appropriate tier waiver approval authority. For

non-tiered compliance items, the Publication OPR will serve as the focal point for all waiver requests. Submit waiver requests to Aircraft Policy Branch (AFGSC/A4MQ) at AFGSC.A4M.workflow@us.af.mil.

SUMMARY OF CHANGES

This publication has been substantially revised and must be reviewed in its entirety. These revisions include, but are not limited to, the realignment and renaming of **Chapter 1**, **Chapter 2**, and **Chapter 3**; modified AFGSC/A4M coordination procedures on approved packages; the change of the 576th Flight Test Squadron (FLTS) to the 377th Test and Evaluation Group (TEG); revised Aircraft Marking Specifications; an updated B-2 AFGSC Distinctive Unit Aircraft Identification Markings List and the addition of the MH-139 Aircraft Marking Specifications.

Chapter 1—OVERVIEW **4**

1.1. Overview. 4

Chapter 2—ROLES AND RESPONSIBILITIES **5**

2.1. Aircraft and Equipment Corrosion Prevention and Control. 5

2.2. Wing Commander Responsibilities. 5

2.3. Maintenance Group Commander Responsibilities. 5

2.4. Wing Corrosion Manager Responsibilities. 6

2.5. Maintenance Supervision (Director of Operations or Maintenance Superintendent). 7

2.6. ASM/Low Observable Aircraft Structural Maintenance (LOASM) Section Chief Responsibilities. 7

2.7. Wash Rack Facility Manager Responsibilities. 8

2.8. Wash Crew Supervisor Responsibilities. 8

2.9. ICBM Corrosion Prevention and Control. 8

2.10. Missile Wing Commander Responsibilities. 9

2.11. Missile Wing Corrosion Prevention and Control Program Manager Responsibilities. 9

Chapter 3—AIRCRAFT AND EQUIPMENT CORROSION PREVENTION AND CONTROL PROGRAM **11**

3.1. General Policy. 11

3.2. Aerospace Vehicle Coating and Marking Requirements. 11

3.3. AGE Tone-Down Procedures. 16

Chapter 4—ICBM CORROSION PREVENTION AND CONTROL PROGRAM **17**

4.1. General Policy. 17

4.2. Murals. 19

Attachment 1—GLOSSARY OF REFERENCES AND SUPPORTING INFORMATION 20

Attachment 2—AIRCRAFT MARKING SPECIFICATIONS 24

Attachment 3—AFGSC DISTINCTIVE UNIT AIRCRAFT IDENTIFICATION MARKINGS LIST 31

Attachment 4—ICBM PAINT PLAN 32

Chapter 1

OVERVIEW

1.1. Overview. AFGSC21-105, *Corrosion Prevention and Control Program*, establishes the policies and procedures necessary to effectively manage and mitigate corrosion across AFGSC assets. To provide maximum clarity and address the unique requirements of the command's primary weapon systems, this instruction is organized into two distinct sections: Aircraft and Equipment Corrosion Prevention and Control and Intercontinental Ballistic Missile (ICBM) Corrosion Prevention and Control. This dual-focus approach provides essential clarity due to the fundamental differences in the operational environments, maintenance concepts, and material of these two critical weapon systems, ensuring tailored guidance for both platforms.

Chapter 2

ROLES AND RESPONSIBILITIES

2.1. Aircraft and Equipment Corrosion Prevention and Control.

2.1.1. Headquarters (HQ) AFGSC Maintenance Division (AFGSC/A4M) Responsibilities. HQ AFGSC/A4M, will designate the AFGSC Fabrication Functional Manager or Low Observable (LO) Functional Manager as the Command Aircraft Corrosion Prevention and Control Program Manager. The program manager will:

2.1.1.1. Manage the Corrosion Prevention and Control Program for all assigned aircraft.

2.1.1.2. Once WG/CC approved packages are received, file locally with the appropriate functional manager and forward the approved package to the AFGSC History Office (AFGSC/HO) for archive.

2.1.1.3. Represent command at assigned weapon systems Corrosion Prevention Advisory Boards (CPAB), AF/DoD corrosion conferences, field surveys, and other Environmental/Technical conferences as applicable.

2.1.1.4. Ensure adequate corrosion control training is available and current for all aircraft and Aerospace Ground Equipment (AGE) maintenance personnel.

2.1.1.5. Serve as the Command's interface with Air Education and Training Command (AETC) and the Air Force Institute of Technology (AFIT) for corrosion training course content changes.

2.1.1.6. Coordinate Major Command (MAJCOM) approval for test programs through appropriate Weapon System Team.

2.2. Wing Commander Responsibilities. The WG/CC will:

2.2.1. Approve all aircraft paint waivers and nose art requests. Ensure all requests have been routed through local Historian, Public Affairs, Wing Corrosion Manager, and Judge Advocate Office. Submit all required documents to the HQ AFGSC/A4M, Aircraft Corrosion Prevention and Control Program Manager via email at: **AFGSC.A4M.Workflow@us.af.mil**.

2.3. Maintenance Group Commander Responsibilities. The MXG/CC (or equivalent) will:

2.3.1. Ensure adequate corrosion control facilities are available to wash aircraft, perform minor maintenance, and paint assigned aircraft on a year-round basis. An outside wash rack may be used on an interim basis when weather conditions permit and when approved by Base Civil Engineer.

2.3.2. Ensure requirements outlined in UFC 4-211-02, *Corrosion Control and Paint Facilities*, and DAFMAN 32-1084, *Standard Facility Requirements,* are met for Support Equipment (SE) and aircraft small parts. **Note:** This capability can be incorporated in the aircraft corrosion control facility if space permits.

2.3.3. Ensure facility control technology meets local, state, and federal Environmental Protection Agency requirements in conjunction with current National Emission Standards for Hazardous Air Pollutants.

2.3.4. Ensure frequency of wash/rinse cycles are maintained in accordance with Technical Order (TO) 1-1-691, *Cleaning and Corrosion Prevention and Control, Aerospace and Non-Aerospace Equipment*, and revised as necessary based on changes in mission and location.

2.3.4.1. Ensure Plans, Scheduling & Documentation (PS&D) section schedule aircraft washes through applicable Maintenance Information System (MIS).

2.3.4.2. Ensure waiver requests are submitted for any assigned aircraft wash that will be overdue more than 30 days with an official memo to HQ AFGSC/A4M prior to the 30th day from the due date.

2.3.4.2.1. Notification shall include:

2.3.4.2.1.1. Aircraft tail number.

2.3.4.2.1.2. Date of last wash.

2.3.4.2.1.3. Reason for overdue condition.

2.3.4.2.1.4. Corrective action taken to prevent further occurrences.

2.3.4.2.2. MAJCOM Corrosion Program Manager ensures the routing of waiver requests to the System Program Office and the engineer and the Air Force Corrosion Prevention Control Office. The SPO engineer has final approval authority for waiver requests IAW TO 1-1-691, Chapter 3.

2.3.4.2.3. When aircraft are in severe corrosion environments, report overdue Clear Water Rinse (CWR) to AFGSC/A4M within seven calendar days after the 30th day of the CWR requirement IAW TO 1-1-691, Chapter 3.

2.4. Wing Corrosion Manager Responsibilities. Wing Corrosion Manager will:

2.4.1. Serve as the focal point for all aircraft and SE cleaning, corrosion and organic coating related information and taskings.

2.4.2. Serve as the point of contact for corrosion prevention and control between the MXG and AFGSC/A4M.

2.4.3. Ensure creation of a supplement to this instruction, to include, but not limited to the following:

2.4.3.1. Numbered Air Force (NAF), Wing, Operations Group (OG), Operational Test (OT) and Bomb Squadron commander aircraft designation and marking requirements of identified aircraft.

2.4.3.2. Local unit marking requirements (e.g. tail stripes, crew names, nose art, etc.).

2.4.3.3. Aircraft paint identification placard size, shape, and information requirements.

2.4.4. Train wash crew supervisors in all aspects of aircraft wash and to develop and implement a wash crew supervisor training plan. Units may designate a 7-level technician to fulfill these training responsibilities.

2.4.5. Ensure development and utilization of local aircraft wash checklists IAW TO 00-5-1, *AF Technical Order System*.

2.4.6. Ensure personnel are trained prior to taking receipt/custody of wash rack facilities and equipment.

2.4.6.1. Base-specific training is required for all newly assigned personnel. Training from another base is not sufficient.

2.4.7. Enforce the use of approved coating materials and cleaning compounds as determined by TOs, Qualified Products Listings (QPL), and Qualified Products Database (QPD).

2.4.8. Ensure coating system scoring and maintenance is accomplished IAW **paragraph 3.2.2**.

2.4.9. Maintain records of all approved requests for aircraft names, nose art, tail flashes, internal nose art, and score sheets of maintained aircraft, as well as appointment letters for the Wing Corrosion Manager and Wash Rack Facility Manager. Maintain full length color photographs of all approved aircraft names and nose art along with approval documentation.

2.4.10. Attend assigned weapon systems CPAB, AF/DoD corrosion conferences, field surveys, and other Environmental/Technical conferences as specified by the Command Aircraft Corrosion Prevention and Control Program Manager.

2.4.11. Wing Corrosion Manager will be a 2A7XX AFSC or civilian equivalent.

2.5. Maintenance Supervision (Director of Operations or Maintenance Superintendent). Maintenance Supervision will:

2.5.1. Ensure owning activities wash and clean their aircraft and SE, as outlined in specific TOs.

2.5.1.1. Ensure Wing Corrosion Manager and/or Aircraft Structural Maintenance (ASM) personnel assist the owning activities in their corrosion prevention efforts by accomplishing scheduled corrosion inspections on aircraft, support, and test equipment.

2.5.2. Ensure wash crew supervisors are experienced/qualified 7-level or above. Wash crew supervisors will be trained by the Wing Corrosion Manager or a qualified 7-level ASM technician. Training shall be documented in the wash crew supervisor's training record.

2.5.3. Ensure trained wash crew supervisors are present throughout the duration of aircraft washes.

2.5.4. Provide a task trained and qualified aircraft wash crew. Ensure availability of Personal Protective Equipment (PPE) within the work center. When possible, the crew should include a dedicated crew chief or assistant dedicated crew chief.

2.6. ASM/Low Observable Aircraft Structural Maintenance (LOASM) Section Chief Responsibilities. ASM/LOASM Section Chief will:

2.6.1. Ensure no other maintenance is accomplished on aircraft, equipment, or within environmentally controlled/cordoned off areas when hazardous/toxic materials are in use that requires the use of specialized PPE. In the event specialized respiratory protection equipment is required, personnel will be properly fitted for the equipment and trained in its use IAW DAFI 48-137, *Respiratory Protection Program.*

2.6.2. Forecast funding to attend and participate in applicable CPABs and other corrosion/structural related programs/meetings.

2.6.3. Submit CPAB agenda items to the Aircraft Corrosion Prevention and Control Program Manager in HQ AFGSC/A4M.

2.6.4. Appoint, in writing, a Wash Rack Facility Manager.

2.7. Wash Rack Facility Manager Responsibilities. Wash Rack Facility Manager will:

2.7.1. Ensure the required number and size of fire extinguishers are available and serviceable IAW weapon system specific technical data and local requirements.

2.7.2. Ensure grounding points are inspected and approved IAW TO 00-25-172, *Ground Servicing of Aircraft and Static Grounding/Bonding*.

2.7.3. Ensure fall protection equipment is available, used, and maintained IAW DAFMAN 91-203, *Air Force Occupational Safety, Fire, and Health Standards,* to allow coverage of all surface areas of aircraft during washing operations.

2.7.4. Ensure aircraft wash rack has cleaners identified in weapon system specific technical data. When cleaning products are not listed in weapon system specific technical data, ensure at least two types of approved cleaners IAW TO 1-1-691 are properly used, including proper mix ratio and the correct cleaner for each area cleaned.

2.7.5. Ensure wash rack facility and surrounding area is kept clean and properly maintained.

2.7.6. Procure PPE used during wash process. Maintains wash rack facilities and equipment in serviceable condition (e.g., water hoses, pumps, air hoses, powered wash equipment, SE, PPE, etc.). This may not apply to units utilizing wash contracts.

2.7.7. Coordinate with Installation CES on regulatory monthly inspection of oil water separator (OWS) and when required; process of requesting disposal of OWS waste**.**

2.8. Wash Crew Supervisor Responsibilities. Wash Crew Supervisor will:

2.8.1. Provide safety briefings explaining hazards associated with wash rack operations.

2.8.2. Ensure aircraft wash crews are task trained and qualified.

2.8.3. Ensure proper safety equipment, PPE, cleaning materials and fall protection lifeline cables (installed when required) are properly maintained IAW manufacturer's instructions and DAFMAN 91-203.

2.8.4. Document the requirement for wash, sign the wash completion, and document the lubrication requirement in the Air Force Technical Order (AFTO) Form 781A, *Maintenance Discrepancy and Work Document,* or other electronic form of documentation.

2.8.5. Ensure all wash rack equipment is inspected for serviceability (e.g., water hoses, pumps, air hoses, powered wash equipment, support equipment, etc.).

2.8.6. Ensure wash rack facility, surrounding area and equipment is clean and equipment is properly stored before and after use.

2.9. ICBM Corrosion Prevention and Control.

2.9.1. HQ AFGSC/A4B Responsibilities. HQ AFGSC/A4B is responsible for overall Intercontinental Ballistic Missile (ICBM) corrosion program management within the command. HQ AFGSC/A4B will appoint an ICBM Corrosion Prevention and Control Functional Manager. The functional manager will:

2.9.2. Manage AFGSC's Corrosion Prevention and Control Program for the ICBM weapon system.

2.9.3. Serve as the command's focal point for corrosion prevention and control issues and coordinate all actions with staff directorates as appropriate.

2.9.4. Ensure adequate corrosion control training is available and current for all ICBM maintenance personnel.

2.9.5. Serve as the Command's interface with Air Education and Training Command (AETC) and the Air Force Institute of Technology (AFIT) for corrosion training course content changes.

2.9.6. Ensure Air Force Materiel Command conducts annual site surveys for ICBM facilities.

2.9.7. Represent Command at assigned weapon systems CPAB, AF/DoD corrosion conferences, field surveys, and other Environmental/Technical conferences as applicable to ICBMs.

2.10. Missile Wing Commander Responsibilities. The MW WG/CC will:

2.10.1. Approve all Missile Alert Facility (MAF) mural requests. Ensure all requests have been routed through Corrosion Manager for tracking.

2.10.2. Missile Maintenance Group and 377 TEG Commander Responsibilities. The MXG/CC and 377 TEG/CC are responsible for establishing and maintaining effective Corrosion Prevention and Control Programs. The MXG/CC and 377 TEG/CC will:

2.10.2.1. Ensure adequate facilities, equipment, manpower, material and funding are available to support a sound corrosion prevention and control program.

2.10.2.2. Utilization of corrosion specialists for anything other than weapon system maintenance requires authorization of the MXG/CC or 377 TEG/CC.

2.11. Missile Wing Corrosion Prevention and Control Program Manager Responsibilities. Wing Corrosion Prevention and Control Program Manager will:

2.11.1. Also be the Corrosion Shop Foreman and QAE for their respective units. (377 TEG will utilize a Corrosion Shop Foreman or QAE only).

2.11.2. Act as the Subject Matter Expert (SME) for all corrosion and coatings related information and taskings.

2.11.3. Serve as the point of contact for corrosion prevention and control between the MXG/TEG and AFGSC/A4B.

2.11.4. Develop and publish local corrosion prevention training requirements, as required.

2.11.5. Ensure military technicians, Department of Air Force civilians, and government contracted corrosion control technicians:

2.11.5.1. Inspect for and treat corrosion IAW technical orders using approved products.

2.11.5.2. Handle and dispose of hazardous materials/waste IAW local, state, and federal guidelines.

2.11.6. Ensure only authorized chemical cleaning materials and corrosion removal methods are used, and that Safety Data Sheets are available and adhered too for each chemical used.

2.11.7. Ensure required equipment is obtained for an efficient and effective corrosion prevention and control program.

2.11.8. Enforce the use of approved coating materials and cleaning compounds as determined by TOs, QPL, and QPD.

2.11.9. Attend annual CPAB, AF/DoD Corrosion Conferences, Foreman's Meeting and other Environmental/Technical conferences as specified by the ICBM Corrosion Prevention and Control Functional Manager.

2.11.10. Track MAF mural information.

2.11.11. Ensure ICBM corrosion control specialists attend site-specific environmental compliance training as designated by the installation Environmental Office

Chapter 3

AIRCRAFT AND EQUIPMENT CORROSION PREVENTION AND CONTROL PROGRAM

3.1. General Policy.

3.1.1. Maintain aircraft paint scheme, markings, and decals IAW TOs 1-1-691, 1-1-8, *Application and Removal of Organic Coatings, Aerospace and Non-Aerospace Equipment,* 1-1-694, *Application and Removal of Low Observable Coatings on Aerospace* and this instruction.

3.1.1.1. Damage markings on Low Observable Aircraft are authorized IAW TO 1-1-694, Chapter 4 to easily identify damage and track defects.

3.1.2. Do not apply unauthorized decals or markings to aircraft. All deviations must be approved by the designated waiver authority and final packages will be sent to AFGSC/A4M for filing. Include digital photographs using criteria in **paragraph 3.2.4.23**.

3.1.3. Aircraft transferring from other commands should comply with AFGSC instructions within 90 days after transfer.

3.1.4. Appearance Standards. Maintain aircraft paint, markings, and corrosion preventive coatings in a manner that will enhance the overall appearance and provide for the best corrosion protection.

3.1.4.1. Markings, warnings, and decals shall be legible and distinct.

3.1.5. Repainting aircraft, communications-electronic systems, or support equipment solely for beautification purposes is not authorized.

3.1.6. CPAB requirements for aircraft units will be fulfilled through the annual aircraft/helicopter CPABs.

3.1.7. Apply soil barrier, as needed, to the tail boom areas affected by engine exhaust on the UH-1 and MH-139 helicopters.

3.1.8. Aircraft coatings. Repair deteriorated aircraft coatings and areas of corrosion when discovered to provide continued surface protection. For metals unable to receive a primer, protect with an approved coating such as corrosion preventative compound.

3.2. Aerospace Vehicle Coating and Marking Requirements.

3.2.1. This section provides guidance for applying command approved, non-USAF standard aircraft coatings and markings as authorized in TO 1-1-8. Paint schemes/configurations and USAF standard aircraft markings will be applied in accordance with TO 1-1-8 and the applicable aircraft technical order.

3.2.2. Coating System Scoring and Maintenance. All AFGSC units, except for the 509 BW B-2 fleet, are required to score aircraft coating systems every 6 months, or as designated by aircraft specific technical guidance, to determine when restoration or touch-up is required. Aircraft painting will be scheduled on a “worst is first” basis to maintain coating system integrity. Supervisors will use ratings to determine corrosion treatment/paint scheduling

priority. Units are required to adopt maintenance-painting techniques IAW TO 1-1-8 to maintain aircraft corrosion protection between overcoats.

3.2.3. Paint Scheme. UH-1 aircraft will use a camouflage paint scheme on main airframes. MH-139 aircraft will maintain FED STD 36118 Grey Type IV paint scheme on main airframes.

3.2.4. Aircraft markings will be applied to aircraft as specifically authorized by this instruction, TO 1-1-8, and the applicable aircraft technical orders. LO aircraft markings not currently approved require a waiver from HQ AFGSC/A4M with SPO approval due to strict survivability analysis requirements. Aircraft inputs to depot will be marked IAW with USAF directives and this instruction only, unless otherwise approved by HQ AFGSC/A4M. HQ AFGSC/A4M is the point of contact for B-1, B-2, B-52, E-4, UH-1, MH-139, and T-38 aircraft painting and markings. All aircraft markings and basic paint schemes will be maintained intact, legible and distinct in color. Command standardization of markings by Mission Design Series (MDS) is of primary concern. AFGSC specific requirements are located within **Attachment 2**.

3.2.4.1. Stenciling. Markings may be applied using stencils or decals. Refer to TO 1-1-8 and TO 1H-1(U)N-3, *Structural Repair, USAF Series TH-1H and UH-1N Helicopters*, if applicable, to determine the compatibility of stenciling paints, paint finishes and decal applications.

3.2.4.2. Command Insignia. The application of command insignia on aircraft is mandatory. **Exception:** Command Insignia is not authorized on the MH-139. Size and location of command insignias by MDS are specified in **Attachment 2**.

3.2.4.3. Organizational Insignia (Wing). The application of wing insignia is mandatory. Insignia will be applied IAW **Attachment 2**. **Note:** Wing insignia is optional for UH-1 and is not authorized on the MH-139. If used, Wing insignias will be the same color scheme as the command insignia.

3.2.4.4. Organizational Insignia (Squadron). Squadron insignia may be applied to aircraft at the wing's option IAW **Attachment 2**. **Note:** Squadron insignia is optional for UH-1 and is not authorized on MH-139. If used, Squadron insignias will be the same color scheme as the command insignia.

3.2.4.5. Distinctive Unit Aircraft Identification Marking. The application of the unit designator is mandatory for AFGSC aircraft unless otherwise directed. HQ AFGSC/A4M is the OPR for the assignment of unit designators. The primary factor used to determine appointment of unit designators is the aircraft/unit assignment location. TO 1-1-8, or the applicable aircraft technical guidance, will provide color restrictions and location for the unit designator. The unit designator will be applied in accordance with guidelines in **Attachment 2** and **Attachment 3**.

3.2.4.6. Tail Stripe/Art. Tail stripe/art are applied as a wing option, used to identify aircraft operation squadrons and display unit heritage. The Wing Commander must approve all tail stripe/art designs. Each operations squadron may have a tail stripe/art unique to that squadron. The use of the same tail stripe/art by two or more squadrons within a wing is not permitted. The stripe may be any color or pattern and may contain a logo. Photographs of locally approved tail stripe designs must be provided to HQ AFGSC/A4M for review and

file. Units will not repaint tail flashes/stripes during deployed operations. See **Attachment 2. Note:** MH-139 tail stripe/art is not authorized.

3.2.4.6.1. Tail stripe/art previously approved are authorized, provided that designs meet the criteria outlined in **paragraph 3.2.4.6**.

3.2.4.7. Tail Markings (UH-1 applicable): See **Attachment 2.**

3.2.4.8. Aircrew and Crew Chief Names (Optional). Aircrew/Crew Chief names may be applied to all command aircraft**.** Crew Chief/assistant(s) names may be applied to all aircraft assigned to units with an established Dedicated Crew Chief (DCC) program. All names must be removed IAW TO 1-1-8 prior to deployment from home station in direct combat zones or when participating in contingencies that may subject aircraft to hostile fire abroad. Application of nicknames, punctuation, and/or call signs is not permitted. All aircraft in the wing will be standard with exception of the designated Commander's aircraft, which may have different lettering but will not exceed established height requirements (N/A for B-2). UH-1 and MH-139 lettering will not exceed 3" height. A background block for pilot/Crew Chief names may be used. The block should be in a color that contrasts with the section of the aircraft to which it's applied. For B-1 and B-52 aircraft, the Wing Commander may approve a locally designed name block to promote unit pride. Photographs must be provided to HQ AFGSC/A4M for review and file. See **Attachment 2** for approved locally designed name blocks.

3.2.4.9. Commander's Aircraft Markings. Commander's aircraft referred to in this instruction are those designated as NAF, Wing, or OG commanders of flying squadrons and OT aircraft. The NAF Commander may select one wing within the command to have an aircraft specifically marked. Wing Commanders may select one aircraft per MDS to apply commander type markings. All other commanders are authorized only one aircraft each to be marked with standardized commander type markings. Standard insignias and markings will not be altered in location, dimension, or configuration to accommodate commander's aircraft markings. The following are markings authorized for use on commander's aircraft:

3.2.4.10. Wing and/or NAF insignias. The wing and/or NAF insignias will be applied on the right forward fuselage, and a collage of assigned flight/operations squadron insignias will be applied on the left forward fuselage.

3.2.4.11. Highlighting of unit designator and bomb wing designator. All highlighting will be done in contrasting gray, black or white if it meets primary basecoat gloss requirements (e.g., gloss, camouflage or gunship). All unit designators and serial numbers will remain on vertical stabilizers or as depicted in applicable technical orders.

3.2.4.12. Wing Commanders must approve the markings. Final packages will be sent to AFGSC/A4M at, **AFGSC.A4M.Workflow@us.af.mil** for filing. Include digital photographs using criteria in **paragraph 3.2.4.23**.

3.2.4.13. Nose Numbers (optional). If used, aircraft nose numbers shall be in block or Helvetica letters, not to exceed five digits. Specific location and size for each different type of aircraft is listed in **Attachment 2**. The paint material(s) used to apply nose numbers shall have the same gloss requirement as the base aircraft coating.

3.2.4.14. Bomber Combat Marking. Designated bomber aircraft with a successful weapons release in combat operations are authorized to display a conventional bomb and/or conventional missile silhouette on that aircraft. These markings will be applied in contrasting shades that conform to the basic aircraft camouflage requirements. B-1, B-2 and B-52 combat marking configurations are located within **Attachment 2**.

3.2.4.15. Nose Art. For purposes of clarification, "nose art" shall be the term used to identify specialized artwork applied to any area of the aircraft. B-1 and B-52 art is authorized on the left side of the aircraft only. B-2 nose art is authorized on the inner mold line of the left main landing gear door. E-4 nose art is authorized on the interior of the crew entry area in conjunction with the crew chief placard and/or on the exterior, left side of the aircraft only. UH-1 nose art is authorized on the Upper Hinged Nose Door of the aircraft only and art is limited to size of the door. Authorized nose art is limited to 3 feet by 3 feet in size. All nose art information shall be incorporated in each base's supplement to this instruction. Nose art shall meet the following criteria:

3.2.4.15.1. Be distinctive, symbolic, and designed in good taste.

3.2.4.15.2. Enhance unit pride.

3.2.4.15.3. Comply with equal opportunity policies.

3.2.4.15.4. Match gloss requirements of the basic paint scheme and utilize MDS approved paint or stencil material.

3.2.4.15.5. All designs will be reviewed IAW **paragraph 3.1.2** and approved by WG/CC. Once approved by the WG/CC, send final packages to AFGSC/A4M for filing. Include digital photographs using criteria in **paragraph 3.2.4.23**.

3.2.4.15.6. Nose art previously approved is authorized, permitting designs meet criteria outlined in **paragraph 3.2.4.15** through **paragraph 3.2.4.15.5**.

3.2.4.16. Unique Unit Markings.

3.2.4.16.1. Anniversary Markings. When applied, anniversary markings will not interfere with required aircraft markings and must be removed immediately after the anniversary period (1-year maximum). Waivers are not required. Wing Commanders must approve the markings, and digital photographs must be provided to AFGSC/A4M for review and file.

3.2.4.16.2. State flags and logos other than anniversary type are not considered unit unique markings.

3.2.4.17. Aircraft Naming. Route requests to name AFGSC aircraft through wing Public Affairs (PA) to AFGSC/A4M. AFGSC/A4M will coordinate with AFGSC/PA before submitting to AFGSC/A4 for approval at, **AFGSC.A4M.Workflow@us.af.mil**. This includes markings previously considered unit unique and are community related/appreciation types such as "Spirit of," "City of" and "State of." Naming aircraft is a tradition designed to commemorate or honor individuals, geographic locations, or events either for the support provided by the USAF on a long-term basis, or because of its significance to USAF history or heritage. Recommendations must include a proposed name, suggested aircraft and tail number, and detailed justification for the proposed name. Contact wing PA Office for details.

3.2.4.18. Aircraft Travel Pods. Travel pods will be painted in gloss paint the same color as the aircraft with no additional markings. Travel pods designated for commanders may contain the position and name of the individual and appropriate insignia. Lettering may be of any color and style but shall not exceed 6” height. Commander’s travel pod paint scheme, final marking sizes, and placements will be approved by the WG/CC and documented within local unit operating instructions.

3.2.4.19. Paint Identification Placard. The paint identification block is a mandatory marking. The block may be of a unique design, or state outline, but must not exceed 6” by 6” size and will match the color of other markings on the aircraft. Waiver requests are not required for this item. However, WG/CC approval is required, and photographs of the design must be provided to HQ AFGSC/A4M for review and file (not applicable for B-2).

3.2.4.20. Competition Aircraft. Units participating in competitions will follow the guidelines established in competition rules for aircraft appearance. Competitions shall be considered "come as you are" and no waivers will be granted. "Come as you are" is defined as no special effort, painting, or additional markings applied to enhance or improve the overall appearance of the aircraft. This includes polishing of titanium, commander markings, etc.

3.2.4.21. Aircraft Transfer. The following markings must be removed prior to formal transfer of aircraft to other units or MAJCOMs (aircraft retiring to the Aerospace Maintenance and Regeneration Group, need not have any markings removed).

3.2.4.21.1. Organizational insignias.

3.2.4.21.2. Distinctive unit aircraft identification.

3.2.4.21.3. Tail stripe.

3.2.4.21.4. Aircrew and Crew Chief names.

3.2.4.21.5. Unit-unique markings.

3.2.4.21.6. Nose art may be retained if gaining unit agrees.

3.2.4.22. Waivers. WG/CC must submit waiver requests for non-standard markings to HQ AFGSC/A4M for approval/disapproval at, **AFGSC.A4M.Workflow@us.af.mil.Waivers** that are in violation of aircraft technical orders will not be accepted. Waiver requests must include the following:

3.2.4.22.1. Clear statement of present procedure/marking.

3.2.4.22.2. Clear statement of proposed change.

3.2.4.22.3. Justification to include historical significance, if applicable.

3.2.4.22.4. Photographs: Two high-quality digital color photographs, one of present marking and one of requested change.

3.2.4.23. Photo Requirements. All photo requirements may be met by a high-quality digital photograph. All AFGSC units must submit one full length (landscape orientation) of the commander's aircraft each time a marking change occurs to HQ AFGSC/A4M for review and file. Units will provide photos of unique markings for all local option changes authorized by this instruction (e.g., tail stripe/name block design and/or color changes,

paint data placard, nose art, etc.) to HQ AFGSC/A4M for review and file at **AFGSC.A4M.Workflow@us.af.mil**.

3.2.4.24. Total Force Integration (TFI). For TFI locations under the classic association, coordination is required from both Wing Commanders to identify specific aircraft for unit identification and/or organizational insignia changes. These proposed changes are in support of ownership, pride and esprit de corps between active duty, reserve, and guard partnering wings. Once insignia change is approved by the owning WG/CC, the supporting documents will be routed to HQ AFGSC/A4M for validation IAW TO 1-1A-8, *Aircraft & Missile Repair Structural Hardware.*

3.3. AGE Tone-Down Procedures.

3.3.1. When feasible, equipment will be completely stripped and properly prepared IAW TO 1-1-8 and TO 35-1-3, *Corrosion Prevention and Control, Cleaning, Painting, and Marking of USAF Support Equipment (SE)* before applying polyurethane coatings.

3.3.2. Minimum reflectorizing requirements will be IAW TO 35-1-3. Black subdued reflectorized tape will be used in lieu of white when TO 35-1-3 makes white tape optional.

3.3.3. Dedicated squadron identification markings will not exceed a 2” by 6” area below two field numbers if the equipment area permits.

3.3.4. Locally devised field numbers will be black.

3.3.5. Interior areas of AGE exposed during operation will be toned down to match exterior painted surfaces.

3.3.6. AGE arriving on base and requiring tone down will be scheduled for painting within 90 days of receipt and completed within 24 months.

Chapter 4

ICBM CORROSION PREVENTION AND CONTROL PROGRAM

4.1. General Policy.

4.1.1. Only qualified government or contract corrosion control technicians will perform coating removal/application tasks when required by applicable technical guidance.

4.1.1.1. Repainting weapon system components and structures solely for beautification purposes is not authorized.

4.1.2. Master Change Log activities and real property/real property installed equipment changes will be coordinated through the Wing Corrosion Prevention and Control Program Manager.

4.1.3. On-base LF trainers will be scheduled on a 3-year cycle for corrosion inspection/treatment using the applicable LF -6 work cards.

4.1.4. Federal, state, and local environmental regulations must be followed.

4.1.5. The Society for Protective Coatings (SSPC) and the National Association of Corrosion Engineers (NACE) offer various training courses for coating systems, application and inspection. As unit funds are available, corrosion program/functional managers, instructors and evaluators should attend SSPC or NACE course(s) that relate to their position and enhance their professional knowledge.

4.1.6. The ICBM Corrosion Prevention and Control Program consists of frequent cleaning, corrosion inspections and early detection, application of proper treatment materials/procedures, and maintenance painting. Maintenance painting is defined for field purposes such as spot painting, sectionalized painting, and complete scuff sand and overcoat. The corrosion prevention and control program is divided into three components, prevention, detection and treatment.

4.1.6.1. Prevention. Corrosion prevention must be a proactive part of the overall program. Use of proper materials and technical order procedures during maintenance activities are critical to program success.

4.1.6.1.1. Frequent cleaning has proven to be the most effective means of preventing corrosion.

4.1.6.1.2. All maintenance personnel must perform general housekeeping and cleaning as part of every maintenance activity; supervisors are required to enforce these standards.

4.1.6.2. Detection.

4.1.6.2.1. All maintenance personnel will perform corrosion inspections as part of routine maintenance activities.

4.1.6.2.2. Supervision at all levels must emphasize active participation by all technicians during scheduled periodic inspections as well as unscheduled maintenance.

4.1.6.2.3. Conduct inspections for corrosion in concealed/hard to access locations when opened for any other work.

4.1.6.2.4. Inspections will be documented in the appropriate MIS.

4.1.6.3. Treatment.

4.1.6.3.1. Units will maintain weapon system components IAW **Attachment 4**.

4.1.6.3.2. There are two general categories of treatment.

4.1.6.3.2.1. Remove and replace. Performed by maintenance technicians responsible for system maintenance when component is beyond repair or treatment in place is not possible or cost effective.

4.1.6.3.2.2. Treatment in place. Minor corrosion can be treated by maintenance technicians during routine maintenance as directed by weapon system specific TOs. Large-scale or more severe corrosion on installed equipment/components will be treated by corrosion specialists.

4.1.6.3.3. LF topside areas are extremely susceptible to environmental factors. The Corrosion Shop Foreman or designated personnel must exercise sound professional judgment when determining when to spot paint or completely recoat surfaces. Complete recoats are authorized for topside surfaces.

4.1.6.3.3.1. For areas other than LF topside, limit painting to the smallest practical area required to maintain a professional appearance and an effective coating system.

4.1.6.3.4. All coating systems used on weapon system components and structures, to include real property installed equipment and operational ground equipment, will comply with technical requirements in TOs 21M-LGM30F-101, *LGM30 Weapon System Corrosion Control and Treatment*, 1-1-8, 1-1-691, 35-1-3, or applicable equipment TOs.

4.1.6.3.5. Units will deplete existing stocks of paint prior to switching to color schemes specified in this instruction. All coatings purchased after implementation of this instruction will be IAW **Attachment 4**.

4.1.6.3.6. A detailed painting plan for living facilities or other above ground facilities at the MAF is not required.

4.1.6.3.7. Repainting missile system facilities/components, communications-electronic systems, or support equipment solely for beautification purposes is not authorized.

4.1.6.3.8. Do not paint equipment/components where the operational capability or designed function of an item would be impaired by paint. Corrosion specialists will not paint the following areas:

4.1.6.3.8.1. Fabric or plastic surfaces.

4.1.6.3.8.2. Bare or untreated concrete surfaces. **Exception:** warning lines, caution lines, designators, etc. required by technical orders.

4.1.6.3.8.3. Surfaces in contact with weather seals and gaskets. **Exception:** surfaces specifically directed by TO 21M-LGM30F-101 and TO 21M-2 LGM30F-112, *General Inspection and Repair Procedures ICBM Systems*.

4.1.6.3.8.4. Radio Frequency Interference (RFI) gaskets/shields and surfaces in contact with RFI gaskets/shields.

4.1.6.3.8.5. Machined surfaces of moving parts.

4.1.6.3.8.6. Identification plates and warning signs.

4.1.6.3.8.7. Lubrication devices and grease fittings.

4.1.6.3.8.8. Electrical terminal strips, ground straps, connectors, wires, and bus bars.

4.1.6.3.8.9. Blast valve assemblies, hydraulic and pneumatic tubing, fittings and controls.

4.1.6.3.8.10. Shock Isolator piston rods.

4.1.6.3.8.11. Abrasive (non-skid) surfaces/floor plates.

4.1.6.3.8.12. Asphalt shingles.

4.1.6.3.8.13. Equipment drawers.

4.1.6.3.8.14. Sound-proofed surfaces.

4.1.6.3.8.15. Wooden ladders.

4.2. Murals.

4.2.1. MAF Murals (optional). For purposes of clarification, “mural” shall be the term used to identify specialized artwork applied to a MAF. All mural information, including location and size limitations as applicable, shall be incorporated in each base’s supplement to this instruction. Murals shall meet the following criteria:

4.2.1.1. Be distinctive, symbolic, and designed in good taste.

4.2.1.2. Enhance unit pride.

4.2.1.3. All designs will be reviewed and approved by the WG/CC.

JAMES M. MILLER, GS-15, DAF
Executive Director, Logistics and Engineering

Attachment 1

GLOSSARY OF REFERENCES AND SUPPORTING INFORMATION

References

UFC 4-211-02, *Aircraft Corrosion Control and Paint Facilities,* 1 December 2012

AFPD 21-1, *Maintenance of Military Material, 2*1 February 2024

AFPD 13-5, *Air Force Nuclear Enterprise,* 17 July 2018

DAFI 48-137, *Respiratory Protection Program*, 12 September 2018

DAFI 21-101, *Aircraft and Equipment Maintenance Management,* 16 January 2020

AFI 33-322, *Records Management and Information Governance Program,* 23 March 2020

DAFMAN 32-1084, *Standard Facility Requirements,* 15 January 2020

DAFMAN 90-161, *Publishing Processes and Procedures,* 18 October 2023

AFMAN 21-202, *Missile Maintenance Management*, 30 May 2024

DAFMAN 91-203, *Air Force Occupational Safety, Fire, and Health Standards,* 24 February 2026

TO 00-5-1, *AF Technical Order System,* 19 November 2024

TO 00-25-172, *Ground Servicing of Aircraft and Static Grounding/Bonding,* 06 February 2026

TO 1-1-8, *Application and Removal of Organic Coatings, Aerospace and Non-Aerospace Equipment,* 02 Mar 2026

TO 1-1A-8, *Aircraft & Missile Repair Structural Hardware,* 01 January 2026

TO 1-1-691, *Cleaning and Corrosion Prevention and Control, Aerospace and Non-aerospace Equipment,* 13 December 2024

TO 1-1-694, *Application and Removal of Low Observable Coatings on Aerospace*, 5 March 2024

TO 1B-2A-2-11GS-00-1, *Placards and Markings,* 13 December 2024

TO 1H-1(U)N-3, *Structural Repair, USAF Series TH-1H and UH-1N Helicopters*, 28 January 2026

TO 21M-LGM30F-101, *LGM30 Weapon System Corrosion Control and Treatment VAFB, Wings I, III, and V USAF SERIES LGM30G MISSILE,* 1 December 2025

TO 21M-LGM30F-112, *General Inspection and Repair Procedures ICBM Systems,* 5 April 2026

TO 35-1-3, *Corrosion Prevention and Control, Cleaning, Painting, and Marking of USAF Support Equipment (SE),* 13 December 2024

Prescribed Forms

None

Adopted Forms

DAF Form 847, *Recommendation for Change of Product*

AFTO Form 781A, *Maintenance Discrepancy and Work Document*

Abbreviations and Acronyms

AETC—Air Education and Training Command

AFRC—Air Force Reserve Command

AFGSC—Air Force Global Strike Command

AFGSCI—Air Force Global Strike Command Instruction

AFI—Air Force Instruction

AFIT—Air Force Institute of Technology

AFMAN—Air Force Manual

AFPD—Air Force Policy Directive

AFRC—Air Force Reserve Command

AFRIMS—Air Force Records Information Management System

AFTO—Air Force Technical Order

AGE—Aerospace Ground Equipment

ANG—Air National Guard

ASM—Aircraft Structural Maintenance

CPAB—Corrosion Prevention Advisory Board

DAFI—Department of the Air Force Instruction

DAFMAN—Department of the Air Force Manual

DCC—Dedicated Crew Chief

DoD—Department of Defense

ESA—Electrical Surge Arrestor

HQ—Headquarters

IAW—In Accordance With

ICBM—Intercontinental Ballistic Missile

LCC—Launch Control Center

LF—Launch Facility

LO—Low Observable

LOASM—Low Observable Aircraft Structural Maintenance

MAF—Missile Alert Facility

MAJCOM—Major Command

MDS—Mission Design Series

MIS—Maintenance Information System

MXG—Maintenance Group

NACE—National Association of Corrosion Engineers

NAF—Numbered Air Force

OG—Operations Group

OPR—Office of Primary Responsibility

OT—Operational Test

PA—Public Affairs

PPE—Personal Protective Equipment

QAE—Quality Assurance Evaluator

QPD—Qualified Products Database

QPL—Qualified Products Listings

RDS—Records Disposition Schedule

RFI—Radio Frequency Interference

SE—Support Equipment

SME—Subject Matter Expert

SPD—System Program Directorate

SPO—System Program Office

SSPC—Society for Protective Coatings

TFI—Total Force Integration

TO—Technical Order

URD—Unit Reference Designator

USAF—United States Air Force

Office Symbols

AFGSC/A1—AFGSC Manpower, Personnel & Services

AFGSC/A4—AFGSC Logistics and Engineering Directorate

AFGSC/A4B—AFGSC ICBM/ Helo Maintenance Division

AFGSC/A4M—AFGSC Maintenance Division

AFGSC/A4MQ—AFGSC Maintenance Management Branch

AFGSC/AHO—AFGSC History Office

Attachment 2

AIRCRAFT MARKING SPECIFICATIONS

A2.1. Aircraft Marking Specifications. Due to the mission of the E-4, no command markings will be applied to the aircraft.

Table A2.1. B-1 Aircraft Marking Specifications.

B-1	
COMMAND INSIGNIA:	24” (subdued). Located 11” down from the tail stripe, top of patch 38” from tail leading edge and 36” from leading edge of rudder on both sides.
ORGANIZATIONAL INSIGNIA:	24” (subdued). Located 6” below and centered on the OSO/DSO windows.
UNIT IDENTIFIER:	30”. Located 7” down from command insignia. On right side of tail, trailing edge of first letter will lay along a vertical line from center of sword in command insignia. On left side of tail, trailing edge of second letter in unit designator will lay along a vertical line from center of sword in command insignia.
TAIL STRIPE:	Wings will identify tail stripe specifications for authorized variants in supplements to this instruction.
PILOT/AIRCREW/CREW CHIEF NAMES:	Pilot/aircrew: Centered on forward escape hatch side window. Crew chief/assistant: Left nose gear door, centered.
NOSE NUMBERS:	Last three/four digits of tail number, 3” height, on nose gear strut, both sides.
COMBAT MARKINGS:	Bomb markings will be located on the right portion of the left nose gear door exterior. These markings will consist of a 5” conventional Missile/Bomb silhouette applied in a row not to exceed 10 in each row. Once 10 silhouettes are achieved, a single conventional Missile/Bomb silhouette with the number a “10” will represent a row.

Table A2.2. B-2 Aircraft Marking Specifications.

B-2	
COMMAND INSIGNIA:	24” (subdued). Located on left side at FS 304.5 (center of crest), with crest bottom at WL 167.2.

B-2	
ORGANIZATIONAL (WING) INSIGNIA:	24” (subdued). Located on right side of aircraft at FS 304.5 (center of crest), crest bottom at WL 167.2. The WG/CC may approve an additional insignia to be installed 6” aft of organizational insignia on aircraft for esprit-de-corps in classically associated TFI units.
DISTINCTIVE UNIT AIRCRAFT IDENTIFICATION MARKING:	16” (subdued). 30° negative slant. Top of unit designator to be 15” from top of main landing gear door, 50” from extreme aft end of door.
TAIL STRIPE:	The “tail stripes” will be 18’ long by 11.25” high from leading edge to trailing edge of main landing gear doors.
AIRCRAFT NAME:	(all measurements to top of letters) “SPIRIT” located: 10.5” from top of main landing gear door, 57” from extreme forward of door in 8” block letters with a 30° negative slant. “OF” located: 19.5” down from top of main landing gear door, centered underneath the “SPIRIT” in 6” block letters with a 30° negative slant. “STATE/CITY” located: 26.5” from top of main landing gear door, centered beneath the “SPIRIT” in 8” block letters with a 30° negative slant.
PILOT/AIRCREW/CREW CHIEF NAMES:	Pilot/Aircrew/Crew Chief names are applied IAW TO 1B-2A-2-11GS.
NOSE NUMBERS:	Nose numbers are applied IAW TO 1B-2A-2-11GS.
COMBAT MARKINGS:	Units may apply a single Missile/Bomb silhouette, not to exceed 3” height, on the exterior of the nose landing gear door for each combat sortie flown with a successful weapons release. Once the area is full, an existing column of Missile/Bombs will be removed and replaced with a single Missile/Bomb silhouette containing a number 10 at the top of the applicable row.

Table A2.3. B-52 Aircraft Marking Specifications.

B-52	
COMMAND INSIGNIA:	24” (subdued). Insignia is applied to both sides of the vertical stabilizer. Top of insignia will be located 41.5” below tail stripe. Leading edge of insignia will

B-52	
	be 62” from leading edge of tail on both sides of tail. Bottom point/tip of insignia will be located on center seam of main spar line.
ORGANIZATIONAL INSIGNIA:	24” (subdued). Right side: On forward fuselage, center of insignia at B.S. 218.7 and W.L.187.5. Left side: On forward fuselage, center of insignia at B.S. 218.7 and W.L.187.5.
DISTINCTIVE UNIT AIRCRAFT IDENTIFICATION MARKING:	Use two-letter base designation **(Attachment 3)** in 42” black block letters. Left side: Top of unit designator located 36” below box antenna. The trailing edge of the second letter is on a vertical line down from the tip of the command insignia, using the lower point of the center lightning bolt in the insignia as a line up reference. Right side: Top of unit designator located 36” below box antenna. The trailing edge of the first letter is on a vertical line down from the tip of the command insignia, using the lower point of the center lightning bolt in the insignia as a line up reference.
DISTINCTIVE UNIT AIRCRAFT IDENTIFICATION MARKINGS ON COMMANDER’S AIRCRAFT:	Use two-letter base designation **(Attachment 3)** in 42” black block letters. When used in conjunction with the bomb wing designator the location will be as follows: Left Side: Top of unit designator located 20” below box antenna. The trailing edge of the second letter is on a vertical line down from the tip of the command insignia, using the lower point of the center lightning bolt in the insignia as a line up reference. Right Side: Top of unit designator located 20” below box antenna. The trailing edge of the second letter is on a vertical line down from the tip of the command insignia, using the lower point of the center lightning bolt in the insignia as a line up reference.
DISTINCTIVE UNIT AIRCRAFT IDENTIFICATION MARKINGS ON BOMB WING COMMANDER’S AIRCRAFT:	Use two-letter base designation **(Attachment 3)** in 18” black block letters.

B-52	
	Left and right side: Top of bomb wing designator will be located 6” below unit designator and aligned with serial numbers.
TAIL STRIPE:	The tail stripe will be applied at the upper portion of the vertical stabilizer and must be in the form of a straight horizontal stripe. The overall height will not exceed 15”.
PILOT/AIRCREW/CREW CHIEF NAMES:	Pilot/aircrew: Centered under pilot’s window. Crew Chief/assistant: Block is 15” by 36”. Block is located on BS 261.00 and WL 139.00. 2 BW Crew chief/assistant: Block is the shape of Louisiana and 30” by 24”. Forward bottom edge of block is aligned with BS 258.70 and WL 139. 5 BW Crew Chief/assistant: Block is the shape of North Dakota and 15” by 35.547”. Forward bottom corner of block is aligned with BS 267 and WL 139. Style and size of letters are a unit option but will not exceed 3” height. A background block for Pilot/Crew Chief names may be used. The block should be in contrasting color to the section of the aircraft where applied. The WG/CC may approve a locally designed name block to promote unit pride.
NOSE NUMBERS:	Last four digits, 12” height, located immediately aft of BS 236.30 and centered on WL 187.5.
COMBAT MARKINGS:	Bomb markings will be enclosed in a 27” by 27”, 1” bordered area centered on BS 218.70 and the bottom edge on WL 139. A conventional bomb/missile silhouette may be displayed in the box for each combat sortie flown with a successful weapons release. The missile marking will be a maximum of 10” and the conventional bomb silhouette a maximum of 5”. Once the box is full, an existing column of Missile/Bombs will be removed and replaced with a single Missile/Bomb silhouette containing a number 10 at the top of the applicable row.

Table A2.4. T-38 Aircraft Marking Specifications.

T-38	
COMMAND INSIGNIA:	10” centered. Insignia is applied to both sides of the vertical stabilizer. Vertically: Top of insignia 4” below anti-collision light. Horizontally: On line with trailing edge of anti-collision light.
ORGANIZATIONAL INSIGNIA:	10” (subdued/CTP, full color AT-38) centered. Vertically: On 3 o'clock position (left) and 9 o'clock position (right). Horizontally: Center of insignia 24” aft of intake lower opening.
DISTINCTIVE UNIT AIRCRAFT IDENTIFICATION MARKING:	Use two-letter base designation **(Attachment 3)** in 12’’ block letters centered. Vertically: 4” below command insignia. Horizontally: Leading edge of first letter centered on command insignia.
TAIL STRIPE:	The tail stripe will be applied at the upper portion of the vertical stabilizer and must be in the form of a straight horizontal stripe. The overall height will not exceed 9”.
PILOT / CREW CHIEFS NAMES:	Pilot: Name centered on left forward canopy rail. Assistant Crew Chief: Name centered on right aft canopy rail. Style and size of letters are a unit option but will not exceed 3” in height. A background block for Pilot/Crew Chief names may be used. The block should be in contrasting color to the section of the aircraft where applied.
NOSE NUMBER:	4’’ block numbers. Last three/four digits of the tail number horizontally on both sides of nose gear door.
UNIQUE PAINT SCHEME:	Companion Trainer Program T-38 aircraft are authorized a gloss gray paint scheme, federal stock code number 16099.

Table A2.5. UH-1 Aircraft Marking Specifications.

UH-1	
COMMAND INSIGNIA:	10’’ black insignia, placed on right side door, under hinge door window and centered.
ORGANIZATIONAL INSIGNIA (Optional):	10’’ black insignia, placed on left side door, under hinge door window and centered.
DISTINCTIVE UNIT AIRCRAFT IDENTIFICATION MARKING:	Use two-letter base designation **(Attachment 3)** in 10’’black block letters placed 29.5” above the tail stinger cowling edge and 2” from the trailing edge.
PILOT / CREW CHIEFS NAMES (Optional):	May be applied to either or both pilot and co-pilot’s doors. Style and size of letters are a unit option but will not exceed 3” in height. A background block for Pilot/Crew Chief names may be used. The block may be in contrasting color, using approved UH-1 color scheme to the section of the aircraft where applied.
TAIL STRIPE / ART:	The tail stripe/art will be applied at the lower portion of the vertical stabilizer, with the bottom of stripe/art no less than 3.5” above stringer cowling. The height of the stripe/art will not exceed 12.5” from the stringer cowling edge. Art will be centered; stripe will span vertical surface. The stripe/art must match gloss requirements of the basic paint scheme, (e.g., aircraft with flat camouflage schemes require application of stripe/art in flat colors).
TAIL NUMBERS:	The serial numbers will be 5’’ black block numbers, placed 15” above stinger cowling and 2” from trailing edge.
TAIL “USAF” MARKING:	“USAF” marking will be 5’’ black block letters placed 22.5” above stinger cowling edge with letters grounded 2” from trailing edge.
NOSE NUMBERS (Optional):	4’’ numbers. Last four digits of the tail number horizontally centered beneath the glide slope antenna.
SIDE FUSELAGE NUMBERS (Optional):	6’’ numbers. Last two digits of the tail number, centered vertically and horizontally between steps on right side only, 2” aft of crew door.

Table A2.6. MH-139 Aircraft Marking Specifications.

MH-139	
COMMAND INSIGNIA:	Not Authorized.
ORGANIZATIONAL INSIGNIA:	Not Authorized
DISTINCTIVE UNIT AIRCRAFT IDENTIFICATION MARKING:	Not Authorized
AIRCREW / CREW CHIEF NAMES (Optional):	May be applied under the flight engineer sliding window. Style and size of letters are a unit option but will not exceed 3” in height. A background block for aircrew/crew chief names may be used. The block will be FS36293 (Light Gray).
TAIL STRIPE / ART:	Not Authorized
TAIL STRIPE / ART:	Not Authorized
TAIL NUMBERS:	Not Authorized
TAIL “USAF” MARKING:	Not Authorized
NOSE NUMBERS (Optional):	Not Authorized
SIDE FUSELAGE NUMBERS (Optional):	Not Authorized

Attachment 3

AFGSC DISTINCTIVE UNIT AIRCRAFT IDENTIFICATION MARKINGS LIST

Table A3.1. AFGSC Distinctive Unit Aircraft Identification Marking List.

CODE	AIRCRAFT	UNIT/LOCATION
DY	B-1	7 BW / Dyess AFB, TX
EL	B-1	28 BW / Ellsworth AFB, SD
FE	UH-1	582 HG Supporting 90 MW / F.E. Warren AFB, WY
LA	B-52	2 BW / Barksdale AFB, LA
MM	UH-1	582 HG Supporting 341 MW / Malmstrom AFB, MT
OT	B-52 B-1 B-2	53 TEG / Barksdale AFB, LA 53 TEG / Dyess AFB, TX 72 TES / Whiteman AFB, MO
MT	B-52 UH-1	5 BW / Minot AFB, ND 582 HG Supporting 91 MW / Minot AFB, ND
WA	B-1 B-2	77 WPS / Dyess AFB, TX 325 WPS / Whiteman AFB, MO
WM	B-2 / T-38	509 BW / Whiteman AFB, MO

Attachment 4

ICBM PAINT PLAN

Table A4.1. Paint Plan.

Item	Paint Color Code	Color
Launch Control Center (LCC)	**Paint Color Code**	**Color**
Acoustical enclosure – external	16473	Lt Grey
Acoustical enclosure – internal	17925	White
Battery Storage below LCC floors	16473	Lt Grey
Blast door exterior and racings (except machined surfaces)	16473	Lt Grey
Blast door interior	16473	Lt Grey
Cable trays	16473	Lt Grey
Ducts, pipes and conduits	Same as associated equipment/fixtures	
Electrical Surge Arrestor (ESA) room walls/floor	16473	Lt Grey
Equipment racks	24525	Lt Green
ESA room panels, door and trim	16473	Lt Grey
External metal racks	24525	Lt Green
LCC liner	16473	Lt Grey
Miscellaneous tanks and brackets	Same as associated equipment/fixtures	
Shock isolators	17925	White
Tunnel junction floor	16473	Lt Grey
Tunnel junction walls	17925	White
Unit Reference Designator (URD) background	23538	Yellow
URD stencils	17038	Black
Launch Control Equipment Building		
Air conditioning equipment	16473	Lt Grey
Automatic switching unit	16473	Lt Grey
Diesel engines and switch gear	Per Manufacturer	Per Manufacturer
Diesel start battery rack	17038	Black
Electrical panels - exterior	16473	Lt Grey
Floors	16473	Lt Grey
Tanks, Ducts, pipes and conduits	Same as associated equipment/fixtures	
URD background	23538	Yellow
URD stencils	17038	Black
Walls	17925	White
Launch Control Support Building		
Air conditioning equipment	16473	Lt Grey

Item	Paint Color Code	Color
Automatic switching unit	16473	Lt Grey
Diesel engines and switch gear	Per Manufacturer	Per Manufacturer
Diesel start battery rack	17038	Black
Electrical panels - exterior	16473	Lt Grey
Floors	16473	Lt Grey
Tanks, Ducts, pipes and conduits	Same as associated equipment/fixtures	
URD background	23538	Yellow
URD stencils	17038	Black
Walls	17925	White
Missile Alert Facility Topside		
Air intake/ exhaust stacks	33578	Beige/tan
Air intake/ exhaust stacks lid/cap	20040	Bronze/brown
Launch Facility Support Building		
Air conditioning equipment	16473	Lt Grey
Diesel engine and switch gear	Per Manufacturer	
Diesel start battery racks	17038	Black
Electrical panels	16473	Lt Grey
Exhaust fan	16473	Lt Grey
Exposed metal and hangar supports	Same as associated equipment/fixtures	
Floors		Red Oxide Primer
Instrument air compressor	16473	Lt Grey
Pipes, conduits and tanks	Same as associated equipment/fixtures	
Repeater telephone set	24525	Lt Green
Under floor ducting	16473	Lt Grey
URD background	23538	Yellow
URD stencils	17038	Black
Walls	17925	White
Launch Facility Topside		
Air intake vent plate	16473	Lt Grey
Clutter plate mast	16473	Lt Grey
Collimator Bench	17925	White
Diesel fill cover (metal or fiberglass)	16473	Lt Grey
Diesel fill pipe and cap	16473	Lt Grey
Hatch covers, grates and ladders	16473	Lt Grey
IMPSS antenna	17925	White
Launcher closure arrestors (Vandenberg)	16473	Lt Grey
Launcher closure door (top trim)	16473	Lt Grey

Item	Paint Color Code	Color
Launcher closure door (front, metal portion)	16473	Lt Grey
Launcher closure door revetment walls (Vandenberg)	16473	Lt Grey
Launcher closure thermal shield	36440	Non-skid Grey
Launcher closure thermal shield alternate coating	16473	Non-skid Grey
Launch facility support building door/frame	16473	Lt Grey
Miscellaneous exposed metal surfaces	16473	Lt Grey
Primary access hatch hand driven linear actuator	16473	Lt Grey
Security pit and cover	16473	Lt Grey
A-Vault door	15045	Blue
Sump pump drain line	16473	Lt Grey
Transporter-erector pylons	16473	Lt Grey
Transporter-erector tie-down slots	16473	Lt Grey
UHF radio marker posts	17925	White
URD background	23538	Yellow
URD stencils	17038	Black
Launch Facility Equipment Rooms		
Walls and ceiling	17925	White
Ballistic actuator Piston Rod Support	15045	Blue
Launch tube heater	16473	Lt Grey
Umbilical retract	15045	Blue
Sump pump (SP-102) control box	No coating authorized	
Work cage distribution box	15045	Blue
Electro-Mechanical Actuator	15045	Blue
Motor generator	15045	Blue
Battery support brackets	17925	White
Launcher closure ballistic actuator	15045	Blue
Air handler control panel	16473	Lt Grey
Emergency fan	15045	Blue
Safety stripes	23538	Yellow
Air handler drain line protection ramp	23538	Yellow
Launch tube heater control panel	16473	Lt Grey
Emergency fan air duct	15045	Blue
Secondary door	24300	Sea Foam Green
Ladder (1st to 2nd level)	17925	White
Monorail I-beam assembly	17925	White
Shock isolators	24300	Sea Foam Green
Shock isolated floor movement limit lines	17038	Black
Primary door (interior)	17925	White
Primary door (exterior band)	16473	Lt Grey
Personnel access shaft	17925	White

Item	Paint Color Code	Color
Primary door bearing surface	17925	White
Pipes and conduits	Same as associated equipment/fixtures	
Launcher distribution panel	16473	Lt Grey
Communications jack boxes	17925	White
Rattle space EMI screen	IAW TO 21M-LGM30F-101	
Rattle space floor under foam blocks	16473	Lt Grey
Floors	16473	Lt Grey
ESA room walls/floor	16473	Lt Grey
ESA room panels, door and trim	16473	Lt Grey
Air conditioner equipment (New)	16473	Lt Grey
Electro-Mechanical Actuator support racks	16473	Lt Grey
Equipment rack air duct	17925	White
J-Ladder platform	No coating authorized	
LER Safety Posts	23538	Yellow
URD background	23538	Yellow
URD stencils	17038	Black
Launch Tube		
Launch tube steel liner	17925	White
Launch tube floor	17925	White
Pipes and conduits	17925	White
Missile suspension system travel limit markings	17038	Black
Missile suspension system and components	15045	Blue