BY ORDER OF THE COMMANDER
12TH FLYING TRAINING WING
(AETC)

12TH FLYING TRAINING WING
INSTRUCTION

21-105

1 JULY 2025

Maintenance

FUNCTIONAL CHECK FLIGHT AND HIGH-SPEED TAXI OPERATIONS

COMPLIANCE WITH THIS PUBLICATION IS MANDATORY

ACCESSIBILITY: Publications and forms are available on the e-Publishing website at **www.e-Publishing.af.mil** for downloading or ordering.

RELEASABILITY: There are no releasability restrictions on this publication.

OPR: 12 MXG/MXQ | Certified by: 12 MXG/CD

Supersedes: 12 FTWI 21-105, 20 July 2020 | Pages: 13

This instruction implements the guidance of (DAFI) 21-101, *Aircraft and Equipment Maintenance Management,* It assigns responsibilities and establishes procedures for the 12th Flying Training Wing (FTW) functional check flight (FCF) program and applies to all 12 FTW maintenance and flying operations personnel at Joint Base San Antonio (JBSA)-Randolph and NAS Pensacola, including those assigned to the Air Force Reserve Command and its units flying in support of the 12 FTW. This publication does not apply to the Air National Guard.

Ensure all records generated as a result of processes prescribed in this publication adhere to Air Force Instruction (AFI) 33-322, *Records Management and Information Governance Program*, and are disposed in accordance with the Air Force Records Disposition Schedule, which is located in the Air Force Records Information Management System. Refer recommended changes and questions about this publication to the Office of Primary Responsibility (OPR) using the DAF Form 847, *Recommendation for Change of Publication*; route DAF Forms 847 from the field through the appropriate functional chain of command. This publication may not be supplemented or further implemented/extended.

SUMMARY OF CHANGES

The revision of this publication ensures an aircraft is flight-ready prior to quality assurance (QA) forms review by the functional check flight (FCF) aircrew (unless not flying that day), clarifies ground-abort documentation, clarifies 12 FTW Form 232, *Aircraft Functional /Operational Check*

flight and High-Speed Taxi Order transmitting procedures, clarifies AFTO Form 781A, *Maintenance Discrepancy and Work Document,* documenting procedure, removes requirement for tire pressure check/exceptional release prior to QA review and removes all operational check flight (OCF) requirements. 12 FTW Aircraft Maintenance Division has been changed to 12th Maintenance Group (12 MXG). 12 FTW/MXOOM has changed to 12 MXG/MXOO. 12 FTW/MXQI has changed to 12 MXG/MXQ. AFI 11-401 *Aviation Management* has changed to DAFMAN 11-401 *Aviation Management*. All information applicable to the T-1 aircraft has been removed.

1. ROLES AND RESPONSIBILITIES.

1.1. **12th Maintenance Group Responsibilities.**

1.1.1. 12th Maintenance Group (12 MXG) will ensure the following is completed:

1.1.1.1. Prepare the aircraft and ensure a current combined basic post-flight operations (BPO)/pre-flight inspection is accomplished.

1.1.1.2. Make the following red dash entries in the AFTO Form 781A, *Maintenance Discrepancy and Work Document*: "Supervisory forms review due prior to FCF/high-speed taxi (HST)"; "Quality assurance (QA) forms review due prior to FCF/HST"; and "FCF/HST due for" (include the reason for the FCF or HST). Maintenance Information Systems (MIS) will match aircraft forms with the same entries.

1.1.1.3. Ensure the appropriate supervisor reviews the aircraft forms, MIS, and engine/propeller logbooks as applicable. Deliver the following to Quality Assurance as applicable: aircraft forms, engine/propeller logbooks, Integrated Maintenance Data System screen 380, and a serviceable tag (or equivalent) for each engine changed.

1.1.1.4. Notify 12 MXG/MXOO of aircraft status as soon as practical following each attempt of an FCF sortie or HST check.

1.1.2. **The 12 MXG Quality Assurance inspectors [12 MXG/MXQ (JBSA-Randolph) or 812 AMXS/MXQC (NAS Pensacola)] will:**

1.1.2.1. **(JBSA-Randolph)** Compile information regarding upcoming FCF/HST requirements and transmit a weekly forecast to all pertinent agencies. This forecast is intended to provide awareness only and will not be used for scheduling purposes.

1.1.2.2. Review all applicable maintenance documentation. Once all documentation is found to be satisfactory, 12 MXG/MXQI or 812 AMXS/MXQC will contact the appropriate flying squadron and/or FCF pilot(s) that same day in order to schedule the FCF/HST to be flown no later than the end of the following duty day, excluding weather delays.

1.1.2.3. **(JBSA-Randolph)** Initiate a 12 FTW Form 232, *Aircraft Functional Check Flight and High-Speed Taxi Order*, and provide it to the FCF pilot(s) for further use.

1.1.2.4. Brief the FCF pilot(s) prior to FCF/HST using the applicable 12 FTW/MX check sheet and enter the applicable information into Quality Assurance Tracking and Trend Analysis System (QANTTAS).

1.1.2.5. Notify the applicable Maintenance Operations Center (12 MXG/MXOO) of the proposed FCF/HST takeoff time, call sign, FCF pilot(s) show time and FCF aircrew complement (i.e. dual, solo, etc).

1.1.2.6. **(JBSA-Randolph)** Debrief the FCF/HST after flight in accordance with (IAW) DAFI 21-101 using information from the completed 12 FTW Form 232 and enter the applicable information into QANTTAS. Submit completed 12 FTW Form 232 to Chief, 12 OG/FCF.

1.1.2.7. **(NAS Pensacola)** Debrief the FCF/HST after flight IAW DAFI 21-101 and enter the applicable information into QANTTAS.

1.1.2.8. Attend FCF pilot(s) maintenance debrief upon request.

1.2. **12th Operations Group (12 OG) Responsibilities.**

1.2.1. **Chief, 12 OG Functional Check Flight (12 OG/FCF) will** :

1.2.1.1. Supervise and administer the JBSA-Randolph portion of the 12 FTW FCF program IAW AFMAN 11-2 for the Mission Design Series Volume 1, (ex. AFMAN 11-2T-38V1, *T-38 Aircrew Training*) and applicable supplements for all JBSA-Randolph-assigned aircraft, in addition to DAFI 21-101 and applicable supplements.

1.2.1.2. Ensure adequate FCF-qualified aircrew manning to accomplish all JBSA-Randolph FCF/HST requirements. **Note:** Mission design series (MDS) lead FCF pilots will coordinate with flying squadron commanders and operations officers to replace FCF pilot losses. Forward names of FCF pilot nominees to Chief, 12 OG/FCF for FCF upgrade training coordination.

1.2.1.3. Maintain a current list of qualified 12 OG FCF pilots and provide copies to pertinent agencies on demand.

1.2.1.4. Maintain all 12 OG FCF pilot training folders.

1.2.1.5. Maintain the 12 OG FCF read file and review the read file quarterly, at a minimum, to ensure currency and accuracy of content.

1.2.1.6. Maintain the historical record of completed 12 FTW Form 232 for T-6A and T-38C FCF sorties and HST checks.

1.2.1.7. Ensure the 12 MXG/MXQ FCF program manager is updated on FCF pilot status and any other information which may affect the JBSA-Randolph portion of the 12 FTW FCF program.

1.2.2. **12 OG FCF Pilot Responsibilities** :

1.2.2.1. Ensure the 12 OG FCF read file is reviewed and signed off prior to each FCF sortie or HST check. The primary method will be via Training Integration Management System (TIMS) Go/No-Go Module. The alternate method will be via a printed copy located in the office of the Chief, 12 OG/FCF.

1.2.2.2. Receive a briefing from 12 MXG/MXQ prior to each attempt of an FCF sortie or HST check.

1.2.2.3. Utilize the 12 FTW Form 232 initiated by 12 MXG/MXQ to serve as authorization for the FCF/HST. The MDS lead FCF pilot, Chief, 12 OG/FCF or Operations Group Commander/Deputy Commander will be the designated approval authority on the 12 FTW Form 232 (**Note:** Additional guidance may be found in DAFMAN 11-401, *Aviation Management,* Air Education and Training Command supplement). Add the sortie to the appropriate flying squadrons daily flight authorization and notify the squadron operations supervisor of the added sortie.

1.2.2.4. Accomplish all FCF sorties and HST checks in accordance with Technical Order 1-1-300, *Maintenance Operational Checks and Check Flights,* DAFI 21-101 and applicable supplements, AFMAN 11-2MDS Volumes 1 and 3, applicable aircraft Dash-6 technical orders, and this instruction.

1.2.2.5. Completely and accurately fill out the 12 FTW Form 232 and return it to 12 XG/MXQ following each attempt of an FCF sortie or HST check. Treat all ground aborts as a failed FCF attempt and submit the 12 FTW Form 232 accordingly. The primary method will be to email a copy of the 12 FTW Form 232 to the FCF program manager (12MXG/MXQ) and alternate, or hand-deliver as necessary.

1.2.2.6. FCF pilots will ensure all items requiring maintenance are written up in the AFTO Form 781. These include broken safety wires, emergency gear and flap deployments, etc. If in doubt, aircrews will include a write-up.

1.2.3. **The 12 OG Flying Squadron Responsibilities** .

1.2.3.1. Squadron operations supervisors will ensure FCF pilot(s) are afforded every opportunity to conduct the FCF/HST within the timeline of **Paragraph 2.1**, when contacted by 12 FTW/MXQI or 12 OG/FCF. If operational requirements prevent the scheduling of an aircrew within this timeline, notify 12 MXG/MXQ. Notify 12 OG/FCF if unable to contact 12 MXG/MXQ.

1.2.3.2. Squadron aviation resource management (SARM) personnel will track FCF pilot currency requirements. Incorporate these requirements into the squadrons Go/No-Go process.

1.2.3.3. Each flying squadron will track FCF pilot and FCF instructor pilot qualification on its Letter of Xs.

1.3. **The 479th Flying Training Group (FTG) Responsibilities.**

1.3.1. **Chief, 479 FTG Functional Check Flight (479 FTG/FCF) will:**

1.3.1.1. Supervise and administer the NAS Pensacola portion of the FCF Program IAW AFMAN 11-2MDS Volume 1 and applicable supplements for all NAS Pensacola-assigned aircraft, in addition to DAFI 21-101 and applicable supplements.

1.3.1.2. Ensure adequate FCF-qualified aircrew manning to accomplish all NAS Pensacola FCF/HST requirements. **Note:** MDS lead FCF pilots are responsible for coordinating with flying squadron commanders and operations officers to replace FCF pilot losses. Forward names of FCF pilot nominees to Chief, 479 FTG/FCF for FCF upgrade training coordination.

1.3.1.3. Maintain a current list of qualified 479 FTG FCF pilots and provide copies to pertinent agencies on demand.

1.3.1.4. Ensure SQ/DOT maintain all 479 FTG FCF pilot training folders.

1.3.1.5. Maintain the historical record of completed 12 FTW Form 232 for T-6A FCF sorties and HST checks.

1.3.1.6. Ensure the 812 AMXS/MXQC FCF program manager is updated on FCF pilot status and any other information which may affect the NAS Pensacola portion of the 12 FTW FCF program.

1.3.2. **The 479 FTG FCF Pilot Responsibilities:**

1.3.2.1. Ensure the 479 FTG FCF read file is reviewed and signed off prior to each FCF sortie or HST check. The primary method will be via TIMS Go/No-Go Module.

1.3.2.2. Receive a briefing from 812 AMXS/MXQC prior to each attempt of an FCF sortie or HST check.

1.3.2.3. Utilize the 12 FTW Form 232 form initiated by 479 FTG/FCF to serve as authorization for the FCF/HST. The MDS lead FCF pilot, Chief, 479 FTG/FCF or Flying Training Group Commander/Deputy Commander will be the designated approval authority on the 12 FTW Form 232. (**Note:** Additional guidance may be found in DAFMAN 11-401, 12 AETC supplement). Add the sortie to the appropriate flying squadrons daily flight authorization and notify the squadron operations supervisor of the added sortie.

1.3.2.4. Accomplish all FCF sorties and HST checks in accordance with T.O. 1-1- 300, DAFI 21-101 and Supplements, AFMAN 11-2MDS Volumes 1 and 3, applicable aircraft Dash-6 technical orders, and this instruction.

1.3.2.5. Completely and accurately fill out the 12 FTW Form 232 and return it to Chief, 479 FTG/FCF following each attempt of an FCF sortie or HST check.

1.3.3. **The 479 FTG Flying Squadron Responsibilities:**

1.3.3.1. Squadron operations supervisors will ensure FCF pilot(s) are afforded every opportunity to conduct the FCF/HST within the timeline of **Paragraph 2.1** of this instruction, when contacted by 812 AMXS/MXQC or 479 FTG/FCF. If operational requirements prevent the scheduling of FCF pilot(s) within this timeline, notify 812 AMXS/MXQC. Notify 479 FTG/FCF if unable to contact 812 AMXS/MXQC.

1.3.3.2. SARM personnel will track FCF pilot currency requirements. Incorporate these requirements into the squadron's Go/No-Go process.

1.3.3.3. Each flying squadron will track FCF pilot and FCF instructor pilot qualification on its Letter of Xs.

2. POLICIES AND PROCEDURES.

2.1. **General Information.** Timely completion of FCF sorties and HST checks is extremely important. FCF sorties and HST checks take priority over student training and instructor development missions. FCF sorties and HST checks will normally be conducted no later than

the end of the next duty day following notification by 12 MXG/MXQ or 812 MXS/MXQC, excluding weather delays.

2.2. **FCF Policies and Procedures.** FCFs will be flown when dictated by the applicable aircraft Dash-6 series technical orders or when directed by the 12 MXG Director of Maintenance (DOM) in consultation with subordinate 12 MXG agencies and with 12 OG and/or 479 FTG representatives.

2.2.1. **(JBSA-Randolph)** A full-profile FCF for T-38C aircraft will be accomplished during the initial FCF sortie (fuel permitting) for major phase maintenance, double engine change, or replacement of any major fixed flight control surface. Re-attempt sorties or sorties intended to test specific equipment, or systems may be flown as a full or partial profile, as deemed appropriate by the T-38C lead FCF pilot or Chief, 12 OG/FCF.

2.2.2. Full-profile FCFs on T-6A aircraft will be minimized and are only flown as required by MDS Dash-6 series technical orders or for FCF pilot upgrade/currency. In these cases, full-profile FCFs will be coordinated with 12 MXG/MXQ or 812 AMXS/MXQC as necessary.

2.2.3. Current FCF pilots will accomplish all FCF checklist actions. Current 12 FTW assigned/attached MDS instructor pilots may fly on MDS FCF sorties to assist the FCF pilot, but will not directly perform any FCF checklist actions. During T-6A and T-38C FCF sorties, the FCF pilot will occupy the front cockpit.

2.2.4. **FCF Weather Requirements** . Weather requirements for conducting FCFs are IAW T.O. 1-1-300, in addition to any applicable MDS-specific requirements.

2.2.4.1. Weather requirements may be reduced to 1500 feet / 3 miles for partial profile FCFs. FCF pilots must be able to maintain visual meteorological conditions throughout the entire profile when verifying functionality of flight instruments.

2.2.5. **Group FCF Chief Pilot MDS Inter-fly Authorization (FCF).** The Chief, 12 OG/FCF and the Chief, 479 FTG/FCF may fly on any respective group FCF sortie, provided all required life support and egress training is current for the MDS. If the group FCF chief pilot is not also a qualified MDS FCF pilot, the group FCF chief pilot will occupy the rear cockpit on T-6A and T-38C FCF sorties.

2.3. **In flight operational Checks.** Some aircraft will require an in-flight ops check due to the performance of certain maintenance actions and when operational checks cannot be performed adequately on the ground, test equipment is not available or maintenance is unable to simulate fault on the ground. In addition to criteria published in DAFI 21-101, and IAW T.O. 1-1-300, these check flights will be flown when deemed appropriate by 12 MXG/CL, in consultation with subordinate 12 MXG agencies, 12 OG or 479 FTG representatives, the 12 OG Chief FCF pilot, or respective aircraft lead FCF pilots.

2.3.1. The 12 MXG agencies will coordinate in-flight operational checks through the 12 MXG/MXQ or 812 AMXS/MXQC when operational check is required.

2.3.2. 12 MXG/MXQ or 812 AMXS/MXQC will contact the 12 OG or 479 FTG lead FCF pilot to determine if the check will require an FCF pilot and what profile will be flown for each particular check.

2.3.3. 12 MXG will follow procedures for all in-flight operational check flights requiring FCF pilot will be accomplished IAW Paragraph **1.1** through **1.1.2.8** of this instruction.

2.3.4. Perform only the operational check or fly the designated profile at the discretion of the 12 OG/CC or 479 FTG/CC, or the respective group MDS lead FCF pilot for the applicable aircraft. Every effort will be made to tailor the profile for the discrepancy driving the requirement for an in-flight ops check.

2.4. **High-Speed Taxi Check Policies and Procedures.** HST checks may be utilized when maintenance operational checks require the aircraft to be taxied higher-than-normal taxi speeds. When possible, FCF sorties are preferred over HST checks. In addition to compliance with **Paragraph 1** of this instruction, the following procedures will be accomplished when conducting HST checks:

2.4.1. Only aircraft which are considered completely airworthy will conduct HST checks. If airworthiness is undetermined, an FCF will be conducted in lieu of (or prior to) conducting HST checks.

2.4.2. HST checks will only be conducted by a current, qualified FCF pilots. Current 12 FTW assigned/attached MDS instructor pilots may accompany 12 OG and 479 FTG FCF pilots on MDS HST checks to assist the FCF pilot but will not directly perform any HST check actions. During T-6A and T-38C HST checks, the FCF pilot will occupy the front cockpit.

2.4.3. Prior to stepping, the FCF pilot(s) will compute the takeoff landing data (TOLD) for the highest speed expected. The FCF pilot(s) will review MDS flight manual abort procedures and associated notes, warnings and cautions.

2.4.4. **(JBSA-Randolph)** The FCF pilot will notify JBSA-Randolph Tower, JBSA-Randolph Supervisor of Flying (SOF) (Hangover Tower and Hangover SOF as appropriate) and the respective squadron operations supervisor prior to performing the HST check. The FCF pilot may request the runway barrier be raised, if applicable, and in IAW MDS restrictions.

2.4.5. **(JBSA-Randolph) JBSA** -Randolph SOF or Hangover SOF will coordinate with the Tower Watch Supervisor to ensure crash, fire and rescue personnel are notified of the proposed HST check. **Note:** This is done merely to provide advance notification to crash, fire and rescue personnel. No further readiness posture beyond that of normal flying operations is required or expected.

2.4.6. **(NAS Pensacola) The** FCF pilot will notify NAS Pensacola Tower and the respective squadron operations supervisor prior to performing the HST check. The FCF pilot may request the runway barrier be raised, if applicable, and in IAW MDS restrictions.

2.4.7. **(NAS Pensacola) The** FCF pilot will notify crash, fire and rescue personnel of the proposed HST check. **Note:** This is done merely to provide advance notification to crash, fire and rescue personnel. No further readiness posture beyond that of normal flying operations is required or expected.

2.4.8. During HST checks, the following speeds shall not be exceeded:

2.4.8.1. T-6A: Maximum Abort Speed as calculated using 1T-6A-1.

2.4.8.2. **(JBSA-Randolph)** T-38C: Refusal Speed – Both Engines Operating as calculated using 1T-38C-1.

2.4.9. IAW DAFI 21-101 the fuel load will be the minimum fuel practical to accomplish the HST check, but not less than MDS Volume 3 and applicable technical order minimums. Factors to consider are the weight of the aircraft at the time the discrepancy was noted and fuel required to safely recover the aircraft when the possibility of becoming airborne exists.

2.4.10. Following completion of the check, the FCF pilot will taxi the aircraft clear of the runway. If no problems are noted by the FCF pilot, the aircraft may be taxied to parking or returned to the runway for takeoff (if a subsequent FCF sortie is also required). If the check is being performed as part of an FCF flight, the FCF pilot must ensure all takeoff and landing data is still valid following the HST check.

2.4.11. **HST Weather and Runway Condition Requirements** . The HST check will only be performed during day with a minimum of 1500 feet/3 miles requirement and on a dry runway. Crosswinds will not exceed:

2.4.11.1. T-6A: 10 knots.

2.4.11.2. T-38C: 15 knots.

2.4.12. **Group FCF Chief Pilot MDS Inter-fly Authorization (HST)** . The Chief, 12 OG/FCF and the Chief, 479 FTG/FCF may accompany the MDS FCF pilot on any respective group HST check, provided all required life support and egress training is current for the MDS. If the group FCF chief pilot is not also a qualified MDS FCF pilot, the group FCF chief pilot will occupy the rear cockpit on T-6A and T-38C HST checks.

2.5. **Fuel Load for FCF Sorties and HST Checks.** Full fuel load requirements are waived for FCF sorties requiring full-stop taxi-backs for maintenance, as long as the subsequent flight portions can recover with appropriate fuel reserves.

2.6. **FCF Conditional Release.**

2.6.1. If an FCF conditional release occurs (IAW DAFI 21-101), the FCF pilot(s) or maintenance personnel will add the discrepancy that caused the conditional release in the next available AFTO Form 781A block. Cross reference will be made to the FCF discrepancy using the “see Job Control Number (JCN) & page item format.” A second 781A discrepancy will be created stating: “FCF pilot forms review required of maintenance action prior to FCF release.” Reference will be made to the conditional release discrepancy using the “see page, item format.”

2.6.2. Once the discrepancy is corrected, the appropriate maintenance supervisor will review maintenance actions performed and present the aircraft forms to the FCF pilot for review. If the FCF pilot is satisfied with the maintenance actions performed, the FCF pilot may release the aircraft from FCF by clearing the forms review and FCF entries in the AFTO Form 781A. Another FCF may be flown if deemed necessary by 12 MXG/CL IAW **Paragraphs 2.2** of this instruction.

2.7. **Off-Station FCF/HST Procedures.** When an aircraft is off-station and requires an FCF/HST, and the aircraft MDS is not supported by the transient base, 12 MXG maintenance repair teams (MRT) and 12 FTW FCF pilots will follow home-station FCF procedures to the

maximum extent possible. Expected deviations from home-station procedures will be briefed to 12 OG/CC prior to execution.

2.7.1. **The MRT Will** :

2.7.1.1. Contact home-station 12 MXG/MXQ or 812 AMXS/MXQC for guidance as necessary.

2.7.1.2. Create a red dash entry in the AFTO Form 781A for the FCF/HST requirement, to include the reason, and a red dash entry for a forms review prior to FCF/HST.

2.7.1.3. Ensure a current combined BPO/pre-flight inspection is accomplished.

2.7.1.4. Review the aircraft forms for completeness and accuracy and clear the forms review in the AFTO Form 781A.

2.7.1.5. Brief the FCF pilot(s) on maintenance performed, to include the reason for the FCF/HST prior to flight and debrief the aircrew after flight. Ensure the FCF pilot makes appropriate AFTO Form 781A entries and completes the FCF checklist as applicable. Leave the completed FCF checklist with the aircraft forms.

2.7.1.6. Ensure home-station Quality Assurance is informed of mission status.

2.7.2. **FCF Pilot Responsibilities During Off-Station FCF/HST** :

2.7.2.1. Ensure the appropriate 12 FTW Form 232 is initiated prior to flight or HST check (contact home station to obtain the form, if necessary).

2.7.2.2. Review the AFTO 781 forms and receive a brief and debrief with MRT personnel.

2.7.2.3. **(JBSA-Randolph) Ensure** the completed 12 FTW Form 232 is returned to 12 FTW/MXOQI (see 12 FTW 232 instructions).

2.7.2.4. **(NAS Pensacola)** Ensure the completed 12 FTW Form 232 is returned to 479 FTG/FCF (see 12 FTW Form 232 instructions).

2.7.3. **Quality Assurance Responsibilities During Off-Station FCF/HST.** 12 MXG/MXQ or 812 AMXS/MXQC will coordinate with the MRT and FCF pilot(s) to provide guidance as necessary. When the aircraft returns to home station, 12 MXG/MXQ or 812 AMXS/MXQC will review the FCF checklist for completeness and ensure all documentation is completed and filed per requirements.

2.8. **FCF/HST Requirements for Transient Aircraft Located at NAS Pensacola or JBSA-Randolph:**

2.8.1. If the aircraft is a supported MDS, follow local FCF procedures IAW this instruction, DAFI 21-101 and supplements in addition to AFMAN 11-2MDS series publications.

2.8.2. If the MDS is not supported locally, the owning unit will provide qualified FCF/HST maintenance and aircrew personnel. The 12 MXG/MXQ or 812 AMXS/MXQC will coordinate with the owning unit and provide assistance as required/requested.

3. FCF PILOT MANAGEMENT.

3.1. **FCF Pilot Upgrade Training and Instructor Development (ID).**

3.1.1. FCF pilot selection criteria and appointment procedures are outlined in AFMAN 11-2MDS Volume 1 series publications. FCF pilot upgrade training will be conducted IAW AFMAN 11- 2MDS Volume 1 series publications and the appropriate 12 OG or 479 FTG FCF upgrade training program.

3.1.1.1. In addition to FCF training folder, all FCF certifications and de-certifications must be documented on AF Form 4348, *USAF Aircrew Certifications.*

3.1.2. Mission-capable aircraft may be used for the upgrade/continuation training of FCF pilots. Mission-capable aircraft used for the training of FCF pilots will not count toward the FCF release/non-release rate.

3.1.3. MDS lead FCF pilots will conduct an MDS-specific ID meeting as frequently as deemed necessary. Focus of the ID meetings should be on changes to applicable FCF checklists, procedures, policies, and techniques. The Chief, 12 OG/FCF and Chief, 479 FTG/FCF will hold group-wide FCF ID meetings as required to disseminate information. Minutes from each of these meetings will be published via FCF read file for review by FCF pilots not in attendance.

3.2. **FCF Pilot Currency and Decertification.** FCF currency requirements and procedures for loss of currency and/or de-certification are listed in AFMAN 11-2T-MDS, Volume 1. All instances of loss of FCF currency and/or de-certification will be documented via 12 OG/FCF or 479 FTG/FCF memorandum and will be filed in the FCF pilot's FCF training folder.

3.2.1. **T-6A FCF Pilot Currency Procedures** . T-6A lead FCF pilots will coordinate with their respective squadrons for FCF upgrade training and ID sorties as required to ensure all T-6A FCF pilots remain current and qualified.

3.2.2. **(JBSA-Randolph) T-38C FCF Pilot Currency Procedures.** T-38C lead FCF pilots will coordinate with their respective squadrons for FCF upgrade training and ID sorties as required to ensure all T-38C FCF pilots remain current and qualified.

3.3. **FCF Pilot Re-currency and Recertification.** FCF re-currency and recertification requirements and are listed in AFMAN 11-2T-MDS, Volume 1. All instances of FCF re-currency and/or recertification will be documented via 12 OG/FCF or 479 FTG/FCF memorandum and will be filed in the FCF pilot's FCF training folder.

PETER J. LEE, Colonel, USAF
Commander, 12th Flying Training Wing

Attachment 1

GLOSSARY OF REFERENCES AND SUPPORTING INFORMATION

References

AFI 33-322, *Records Management and Information Governance Program*, 23 Mar 2020

AFMAN 11-2T-38V1, *T-38 Aircrew Training,* 13 May 2020

AFMAN 11-2T-38V1, *AETC SUP, T-38 Aircrew Training*, 7 Feb 2024

AFMAN 11-2T-38V3, *T-38 Operations Procedures,* 13 May 2020

AFMAN 11-2T-38V3, *AETC SUP, T-38 Operations Procedures,* 23 Aug 2022

AFMAN 11-2T-6V1, *T-6A Aircrew Training*, 31 Mar 2020

AFMAN 11-2T-6V3, *T-6A Operations Procedures,* 16 Dec 2020

DAFI 21-101, AETC SUP1, *Aircraft and Equipment Management* 10 August 2020

DAFI 21-101, *Aircraft and Equipment Maintenance Management,* 16 January 2020

DAFMAN 11-401, *AETC SUP*, *Aviation Management,* 6 Jun 2023

T.O. 1-1-300, *Maintenance Operational Checks and Check Flights,* 15 Dec 2023

T.O. 1T-38C-6CF-1, *T-38C Acceptance and Functional Check Flight Procedures Manual,* 27 Sep 2022

T.O. 1T-6A-6CF-1, *T-6A Acceptance and Functional Check Flight Procedures Manual,* 1 Nov 2024

Prescribed Form

12 FTW Form 232*, Aircraft Functional/Operational Check flight and High-Speed Taxi Order*

Adopted Forms

DAF Form 847, *Recommendation for Change of Publication*

AF Form 4348, *USAF Aircrew Certifications*

AFTO Form 781A, *Maintenance Discrepancy and Work Document*

Abbreviations and Acronyms

AETC—Air Education and Training Command

AFMAN—Air Force Manual

AFRC—Air Force Reserve Command

ANG—Air National Guard

BPO—Basic Post-Flight Operations

DAFMAN—Department of the Air Force Manual

DOM—Director of Maintenance

FCF—Functional Check Flight

FTG—Flying Training Group

FTW—Flying Training Wing

HST—High-Speed Taxi

IAW—In Accordance With

ID—Instructor Development

IMC—Instrument Meteorological Conditions

JBSA—Joint Base San Antonio

JCN—Job Control Number

KIAS—Knots Indicated Airspeed

MDS—Mission Design Series

MIS—Maintenance Information Systems

MRT—Maintenance Repair Team

NAS—Naval Air Station

OG—Operations Group

OCF—Operational Check Flight

OPR—Office of Primary Responsibility

QANTTAS—Quality Assurance Tracking and Trend Analysis System

QA—Quality Assurance

SARM—Squadron Aviation Resource Management

SOF—Supervisor of Flying

T.O.—Technical Order

TOLD—Takeoff Landing Data

TIMS—Training Integration Management System

VFR—Visual Flight Rules

VMC—Visual Meteorological Conditions

Office Symbols

12 MXG/MXOO—Maintenance Operations Center

12 MXG/MXQ—FCF Program Manager/Quality Assurance Inspector (JBSA—Randolph)

12 MXG—Maintenance Group (JBSA Randolph)

12 OG/FCF—Functional Check Flight Chief T-38C

479 FTG/FCF—Functional Check Flight Chief T-1/T-6

812 AMXS/MXQC—FCF Program Manager/Quality Assurance Inspector (NAS Pensacola)