BY ORDER OF THE
SECRETARY OF THE AIR FORCE

DEPARTMENT OF THE AIR FORCE
INSTRUCTION 21-101

16 JANUARY 2020
Incorporating Change 1, 20 DECEMBER 2023

AIR FORCE GLOBAL STRIKE COMMAND
Supplement

18 FEBRUARY 2026

Corrective Action Applied on
27 FEBRUARY 2026

Maintenance

AIRCRAFT AND EQUIPMENT
MAINTENANCE MANAGEMENT

COMPLIANCE WITH THIS PUBLICATION IS MANDATORY

ACCESSIBILITY: Publications and forms are available for downloading or ordering on the e-Publishing website at **www.e-publishing.af.mil**.

RELEASABILITY: There are no releasability restrictions on this publication.

OPR: AF/A4LM

Certified by: SAF/AQD
(Ms. Angela L. Tymofichuk)

Supersedes: AFI 21-101, 1 May 2015
AFI 21-110, 16 Jun 2016
AFI 21-123, 3 Feb 2017
AFI 21-124, 12 Jan 2017
and AFI 21-136, 3 Feb 2017

Pages: 306

(AFGSC)

OPR: AFGSC/A4M

Certified by: AFGSC/
A4M Pages: 107

This publication implements Air Force Policy Directive (AFPD) 21-1, Maintenance of Military Materiel. It is the basic Department of Air Force Instruction (DAFI) for all weapon system and support equipment maintenance management guidance. It provides the minimum essential guidance and procedures to safely and effectively maintain, service, and repair weapon systems and support equipment. This publication applies to all military and civilian members of the United

States Air Force (USAF), United States Space Force (USSF), Air Force Reserve (AFR), and Air National Guard (ANG) as well as those with contractual obligation to comply with Air Force publications. Supplements and addendums are written in accordance with (IAW) Department of the Air Force Manual (DAFMAN) 90-161, *Publishing Processes and Procedures*. Supplements must identify and document major command (MAJCOM), AFR, and ANG required deviations (applicability, variance, exception, and differences in organizational placement of responsibilities/processes) in their supplement and addendums with the abbreviation (DEV). Place the "DEV" entry after the paragraph number and directly preceding the affected text, such as "(AMC) (DEV) Use the..." or "(ADDED-AMC) (DEV) Use the...)." MAJCOMs supplements are submitted to the Air Force Maintenance Division (AF/A4LM) @ **AF.A4LM.Maintenance.Policy@us.af.mil** for approval. Supplements and addendums are to be published in the e-Publishing website. The authorities to waive wing and unit level requirements in this publication are identified with a Tier ("T-0, T-1, T-2, or T-3") number following the compliance statement. See DAFMAN 90-161 for a description of the authorities associated with the Tier numbers. Submit requests for waivers through the chain of command to the appropriate Tier waiver approval authority, or alternately, to the requestor's commander for non-tiered compliance items. All approved waivers must be sent to AF/A4LM Maintenance Policy org box: **AF.A4LM.Maintenance.Policy@us.af.mil**, within 30 days of approval, for situational awareness and process improvement considerations. For questions on interpreting this instruction, first contact your MAJCOM maintenance functional activity. Refer recommended changes and questions about this publication through your assigned MAJCOM, AFR or ANG, to the Office of Primary Responsibility (OPR) using the Department of the Air Force (DAF) Form 847, Recommendation for Change of Publication; route DAF Forms 847 from the field through the appropriate functional chain of command. Ensure all records created as a result of processes prescribed in this publication adhere to AFI 33-322, Records Management and Information Governance Program, and disposed IAW the Air Force Records Disposition Schedule located in the Air Force Records Information Management System. The use of the name or mark of any specific manufacturer, commercial product, commodity, or service in this publication does not imply endorsement by the AF.

(AFGSC) This supplement implements and extends the guidance of DAFI 21-101, *Aircraft and Equipment Maintenance Management*. It provides Air Force Global Strike Command (AFGSC) supplemental guidance and procedures to safely and effectively maintain, service, and repair weapon systems and support equipment. It applies to Air Force Global Strike Command (AFGSC) organizations and personnel that maintain aircraft, aircraft systems, communication systems, equipment, support equipment, and components. Contracted maintenance requirements will be stated in the Performance Work Statement (PWS). This publication applies to all military and civilian members of the United States Air Force (USAF), Air Force Reserve (AFR) and Air National Guard (ANG) upon mobilization, and/or AFGSC-led classic AFRC and ANG associations as well as those with contractual obligation to comply with Air Force publications. This publication does not apply to the United States Space Force. Supplements and addendums are written in accordance with (IAW) Department of the Air Force Manual (DAFMAN) 90-161, *Publishing Processes and Procedures.* The authorities to waive wing and unit level requirements in this publication are identified with a Tier ("T-0, T-2, or T-3") number following the compliance statement. See DAFMAN 90-161 for a description of the authorities associated with the Tier numbers. Submit requests for waivers through the chain of command to the appropriate tier waiver

approval authority. Refer recommended changes and questions about this publication to the Office of Primary Responsibility (OPR) using the DAF Form 847, *Recommendation for Change of Product;* route DAF Form 847s from the field through the appropriate functional's chain of command to **AFGSC.A4M.Workflow@us.af.mil**. Ensure all records created as a result of processes prescribed in this publication adhere to AFI 33-322, *Records Management and Information Governance Program,* and disposed IAW the Air Force Records Disposition Schedule located in the Air Force Records Information Management System. The use of the name or mark of any specific manufacturer, commercial product, commodity, or service in this publication does not imply endorsement by the Air Force (AF). Units will publish a single supplement to consolidate local policies mandated by the AFI and this supplement. Units may develop separate Operating Instructions as long as they are referenced in their DAFI 21-101 supplements. Supplements must be routed to the OPR of this instruction for coordination prior to certification and approval. AFGSC/CD is the Tier 2 Waiver Authority for this publication. For non-tiered compliance items in the AFGSC portion of the publication, the AFGSC Publication OPR will serve as the focal point for all waiver requests. Submit waiver requests to Aircraft Policy Branch (AFGSC/A4MQ) at **AFGSC.A4M.workflow@us.af.mil**. AF/A4LM IAW DAFMAN 90-161 has approved deviations [Dev] for **paragraph 2.2.2** for the 582 HG/CC has responsibility to conduct Wing Stand up meeting for the 582 HG at FE Warren AFB, Malmstrom AFB, and Minot AFB and **paragraph 2.4.2.50.1** for the 95 WG Quality Assurance Superintendent/Chief Inspector to be appointed as Group Corrosion Control Managers, as of 23 September 2025 documented on DAF Form 673.

SUMMARY OF CHANGES

This corrective action revises the following paragraphs: 10.3.1.; 10.3.3.3.3.; 10.11.1.; 10.11.2.1.1.; 10.12.; 10.13.1.; 10.13.1.1., 10.13.6.1 and 11.8.3.15. Additionally, this corrective action deletes **para 6.10.1.3.3.1**. Significant changes include the addition of Maintenance Cyber Discipline requirements, Decentralized Materiel Support, incorporation of four AFIs superseded above and establishes a Wing Avionics Manager Position requirement. Additionally, eTool and Worldwide Identification (WWID) management procedures were expanded to provide standardized enterprise requirements. MAJCOMs/ANG designated to establish Special Certification Roster (SCR) prerequisites to optimize workforce alignment to mission requirements.

SUMMARY OF CHANGES

This publication has been substantially revised and must be completely reviewed in its entirety. Significant changes include the addition of Maintenance Cyber Discipline requirements, Decentralized Materiel Support, incorporation of four AFIs superseded above and establishes a Wing Avionics Manager Position requirement. Additionally, eTool and Worldwide Identification (WWID) management procedures were expanded to provide standardized enterprise requirements. MAJCOMs/ANG designated to establish Special Certification Roster (SCR) prerequisites to optimize workforce alignment to mission requirements.

This publication has been revised and includes published guidance implemented under DAFI 21-101_DAFGM2022-01; Chapter 2, Roles and Responsibilities to support organizational structures where an MXG is not assigned (i.e., AFFORGEN deployed construct); waiver

authorities to the appropriate level; accident investigation recommendations; audit corrective actions; recommended changes from the field; and updated references.

Chapter 1—MANAGEMENT OVERVIEW, SUPPORTING CONCEPTS AND REQUIREMENTS. 13

1.1. Introduction. 13
1.2. Organization. 13
1.3. Maintenance Concept. 13
1.4. Aircraft Maintenance Tactics, Techniques and Procedures (TTP). 14
1.5. Aircraft and Equipment Readiness. 14
1.6. Maintenance Discipline. 15
1.7. Communications Security (COMSEC)/Controlled Cryptographic Item (CCI). 16
Table 1.1. Tiered Interface Examples. 17
1.8. Environmental Compliance. 19
1.9. Publications. 19
1.10. Maintenance Training. 19
1.11. Modification Management. 19
1.12. Maintenance Information System (MIS). 19
1.13. General Safety Guidance. 20
1.14. Duty Shifts and Rest Periods. 22
1.15. Communications. 22
1.16. Maintenance Repair Priorities. 23
Table 1.2. Maintenance Repair Priority Designators. 24
1.17. Associate Unit Program/Total Force Integration (TFI). 27
1.18. Performance-Based Activities. 27
1.19. Changes to Technical Orders. 28

Chapter 2—ROLES AND RESPONSIBILITIES 29

2.1. General. 29
2.2. Wing Commander (WG/CC) Responsibilities. 29
2.2. (AFGSC) Wing Commander (WG/CC) Responsibilities. 29
2.3. Wing Vice Commander (WG/CD) Responsibilities. 31
2.4. Maintenance Group Commander (MXG/CC) Responsibilities. 31
2.4. (AFGSC) Maintenance Group Commander (MXG/CC) Responsibilities. 31

2.5. Deputy Maintenance Group Commander (MXG/CD)..... 41
2.6. MXG Senior Enlisted Leader (SEL) Responsibilities. 41
2.7. Wing Weapons Manager..... 42
2.8. Squadron Commander (SQ/CC) Responsibilities..... 42
2.9. Maintenance Supervision Responsibilities. 43
2.9. (AFGSC) Maintenance Supervision Responsibilities..... 44
2.10. Flight Supervision..... 45
2.11. Production Superintendent (Pro Super). 48
2.12. Section NCOIC/Chief. 48

Chapter 3—AIRCRAFT MAINTENANCE SQUADRON (AMXS)/GENERATION SQUADRON. 52

3.1. General..... 52
3.1. (AFGSC) General. 52
3.2. Maintenance Supervision Responsibilities. 52
3.3. Aircraft Maintenance Unit (AMU). 53
3.4. AMU OIC/SUPT Responsibilities..... 53
3.4. (AFGSC) AMU OIC/SUPT Responsibilities. [..... 53
3.5. Production Superintendent (Pro Super). 53
3.6. Flightline Expediter. 55
3.6. (AFGSC) Flightline Expediter. [BGS units]..... 55
3.7. Aircrew and Maintenance Debrief Section..... 56
Table 3.1. Landing Status Codes. 58
Table 3.2. System Capability Codes..... 59
Table 3.3. Deviation Cause Codes..... 60
3.8. Aircraft Section..... 60
3.9. Specialist Section..... 61
3.9. (AFGSC) Specialist Section. 61
3.10. Weapons Section/Expediter/ Loading Element/ Maintenance Element/ Non-Standard Weapons Sections..... 63
3.11. Support Section..... 63
3.12. Unit Decentralized Materiel Support (DMS)..... 63
3.12. (AFGSC) Unit..... 63
3.13. (Added-AFGSC) Software Analysis Section [B-2 Units]. 64

Chapter 4—MAINTENANCE SQUADRON (MXS)/GENERATION SQUADRON. 66

4.1. General. 66

4.2. Maintenance Supervision Responsibilities. 66

4.3. MXS Production Superintendent (Pro Super). 66

4.4. Accessories Flight. 67

4.5. Aerospace Ground Equipment (AGE) Flight. 75

4.6. Armament Flight. 77

4.7. Avionics Flight. 78

4.7. (AFGSC) Avionics Flight. 78

4.8. Fabrication Flight. 79

4.9. Maintenance Flight. 84

4.10. Munitions Flight. 87

4.11. Propulsion Flight. 88

4.12. Test, Measurement, and Diagnostic Equipment (TMDE) Flight. 96

4.13. (Added-AFGSC) Signature Diagnostics Section. 98

Chapter 5—MAINTENANCE OPERATIONS (MXO). 99

5.1. General. 99

5.2. Maintenance Operations. 99

5.3. Maintenance Training (MT). 112

5.4. Programs and Resources (P&R). 113

Chapter 6—QUALITY ASSURANCE (QA) 115

6.1. General. 115

6.2. Responsibilities. 115

6.2. (AFGSC) Responsibilities. 115

6.3. QA Superintendent (QA SUPT) Responsibilities. 117

6.4. Chief Inspector Responsibilities. 118

6.5. Quality Assurance Inspector Responsibilities. 120

6.6. Quality Assurance Inspector Training. 120

6.7. Maintenance Standardization and Evaluation Program (MSEP). 121

6.8. LEAP QA Database. 134

6.9. QA Product Improvement Programs (PIP). 136

6.10. Technical Order Distribution Office (TODO). 138

6.11. One-Time Inspections (OTI) program. 140

6.11. (AFGSC) One-Time Inspections (OTI) program. 140
6.12. Functional Check Flights (FCFs) to include Operational Check Flights (OCFs). 140
6.12. (AFGSC) Functional Check Flights (FCFs) to include Operational Check Flights (OCFs). 140
6.13. Inflight Operational Checks. 143
6.14. High Speed Taxi Checks. 143
6.15. Weight and Balance (W&B) Program. 143
6.15. (AFGSC) Weight and Balance (W&B) Program. 143

Chapter 7—IMPOUNDMENT PROCEDURES 145

7.1. Aircraft and Equipment Impoundment. 145
7.2. Specific Guidance. 145
7.2. (AFGSC) Specific Guidance. 145
7.3. Impoundment Authorities. 145
7.4. Impoundment Official Responsibilities. 146
7.5. Mandatory Impoundments. 146
7.6. Impoundment Procedures. 147
7.7. Rules of Impoundment Specifically for Explosive-Related Events/Mishaps. 148

Chapter 8—TOOL AND EQUIPMENT MANAGEMENT 150

8.1. Tool and Equipment Management. 150
8.2. Guidelines for Program Management. 150
8.3. General Program Guidelines. 151
8.4. TMDE Management Guidelines. 154
8.5. Tool Accountability and Serviceability. 155
8.6. Tool and Equipment Marking and Identification. 158
8.7. Locally Manufactured, Developed, or Modified Tools and Equipment. 160
8.8. Tool Room Operations and Tool Security. 161
8.9. Lost Item/Tool Procedures. 162

Chapter 9—MATERIEL MANAGEMENT SUPPORT 164

9.1. General. 164
9.2. Decentralized Materiel Support. 164
9.3. Supply Discipline. 165
9.4. Readiness Spares Package Review. 165
9.5. Bench Stock. 165

9.5. (AFGSC) Bench Stock. 165
9.6. Consumable Readiness Spares Package. 166
9.7. Shop Stock. 166
9.7. (AFGSC) Shop Stock. 166
9.8. Operating Stock. 166
9.8. (AFGSC) Operating Stock. 166
9.9. Work Order Residue. 166
9.9. (AFGSC) Work Order Residue. 166
9.10. Adjusted Stock Levels. 166
9.11. Shelf-life Items. 167
9.12. Equipment Items. 167
9.13. Special Purpose Recoverable Authorized Maintenance (SPRAM). 167
9.14. Supply Assets Requiring Functional Check, Calibration, or Operational Flight Programming. 167
9.15. Time Compliance Technical Order (TCTO) Kit Procedures. 168
9.15. (AFGSC) Time Compliance Technical Order (TCTO) Kit Procedures. 168
9.16. Supply Points. 168
9.17. Local Manufacture. 168
9.18. DIFM Management. 169
9.19. Tail Number Bins (TNB). 170
9.19. (AFGSC) Tail Number Bins (TNB). 170
9.20. CANN Actions. 171
9.21. Bench Check and Repair Policy. 171
9.22. Maintenance Turn-Around Record Update Processing. 171
9.23. Buildup Items. 171
9.24. DR Exhibits. 172
9.25. Destruction of TOP SECRET Material. 172
9.26. Certifying Items Associated With Explosives. 172
Chapter 10—MUNITIONS POLICY AND WEAPONS LOAD CREW PROGRAM 173
10.1. See AFMAN 21-206 for Munitions Policy and Weapons Load Crew Program. 173
10.1. (AFGSC) See AFMAN 21-206 for Munitions Policy and Weapons Load Crew Program. 173

Chapter 11—ADDITIONAL MAINTENANCE REQUIREMENTS AND PROGRAMS 174

11.1. Facility Housekeeping and Contamination Control. 174
11.2. Personal Wireless Communications Systems Management. 174
11.3. MAJCOM/ANG Special Certification Rosters (SCR) 174
Table 11.1. Mandatory Special Certification Roster and Prerequisites. 177
Table 11.1. (AFGSC) Mandatory Special Certification Roster and Prerequisites. 180
11.4. Aircraft Grounding. 185
11.5. Ramp Inspection Program. 186
11.6. Red Ball Maintenance. 186
11.7. Maintenance Recovery Team. 187
11.8. Foreign Object Damage (FOD) Prevention Program. 188
11.9. Dropped Object Prevention (DOP) Program. 197
11.9. (AFGSC) Dropped Object Prevention (DOP) Program. 197
11.10. Aircraft Structural Integrity Program (ASIP). 199
11.11. Identification Friend or Foe (IFF) Program. 200
11.12. Radar Warning Receiver/Radar Threat Warning Testing. 201
11.13. Cannibalization Program. 201
11.14. Hangar Queen Aircraft. 203
11.15. Ground Instructional Trainer Aircraft (GITA) 206
11.16. Aircraft Inlet/Intake/Exhaust Certification. 209
11.17. Engine Run Training and Certification Program. 209
11.18. Engine Blade Blending Training and Certification Program. 219
11.19. Engine Flexible Borescope Inspection Training and Certification Program. 220
11.20. Flying Crew Chief (FCC) Program 221
11.21. Maintenance of Flash Blindness Protective Devices. 227
11.22. WRM External Nestable Fuel Tank Build-Up. 227
11.23. Protective Aircraft Shelters (PAS). 228
11.24. Combat Sortie Generation. 228
11.24. (AFGSC) Combat Sortie Generation. 229
11.25. Hot Refueling Procedures. 229
11.25. (AFGSC) Hot Refueling Procedures. 229
Table 11.2. (Added-AFGSC) Hot Aircraft Refueling Training/Certification Requests. (T-2) ... 236
11.26. Aircraft Rapid/Hot Defueling. 236

11.27. 406 MHz Emergency Locator Transmitter Systems Program. 236
11.28. Crashed, Damaged or Disabled Aircraft Recovery (CDDAR) Program. 237
11.29. Aircraft Battle Damage Repair (ABDR). 238
11.30. Egress/Cockpit Familiarization Training. 241
11.31. Aircraft Defensive Systems Loading Program. 242
11.32. Aircraft and Equipment Decontamination. 247
11.33. End-of-Runway (EOR) Inspection. 247
11.34. Wing Avionics Manager (WAM). 247
11.35. Fire Extinguisher Requirements. 248
11.36. Air Force Repair Enhancement Program (AFREP). 248
11.37. Calibration Limitation Approval Certification Program. 254
11.38. Oil Analysis Program (OAP). 254
11.39. Air Force Engineering and Technical Services (AFETS). 259
11.40. Senior Leader Mission Generation (SLMG) Course. 265
11.41. Condition Based Maintenance Plus (CBM+). 265
11.42. (Added-AFGSC) Deicing/Anti-icing Training. 266
11.43. (Added-AFGSC) Maintenance Flash/QA Flash. 266
11.44. (Added-AFGSC) Hangar Door Program. 266
11.45. (Added-AFGSC) [B-52 units] Bomber Airborne Maintenance Support (BAMS) Program. 267
11.46. (Added-AFGSC) Egress Augmentees. 269
11.47. (Added-AFGSC) Software Analysis Section [B-1 units]. 269

Chapter 12—MAINTAINING COMMERCIAL DERIVATIVE AIRCRAFT (CDA). 271

12.1. Background Information, Objective and Roles and Responsibilities. 271
12.2. AF/A4L will: 271
12.3. The Program Manager (PM) will: 272
12.4. Lead Commands will: 273
12.5. Units will: 273
12.6. Maintenance Personnel Requirements. 274
12.7. Deviations/Changes to Inspection Requirements, Time Change Intervals, and Component/Aircraft Overhaul. 274
12.8. Air Force Modifications to CDA and Components. 274
12.9. Certification Basis for CDA. 274

Chapter 13—CENTRALIZED REPAIR FACILITIES (CRF). 275

13.1. Introduction. 275

13.2. Organization. 275

13.3. CRF Production Requirements. 275

13.4. MGN Support. 275

13.5. CRF Enterprise Information Management. 276

13.6. Documentation. 276

13.7. Metrics. 276

Chapter 14—MAINTENANCE PLANS, SCHEDULING AND DOCUMENTATION (PS&D). 277

14.1. Responsibilities: 277

14.2. Data Documentation. 279

14.3. Configuration, TCTO, SI and TCI Management. 288

14.4. ENGINE MANAGEMENT (EM). 302

14.5. Maintenance and FHP Planning Cycle. 308

14.6. Contingency and Expeditionary Responsibilities. 320

Chapter 15—AIRCRAFT SUNSHADE MANAGEMENT 323

15.1. Purpose: 323

15.2. Scope: 323

15.3. Definitions. 323

15.4. Headquarters Air Force. 324

15.5. MAJCOM A4s will: 324

15.6. Owning Organization. 324

15.7. New Procurements. 325

15.8. Design Criteria/Standards of Aircraft Sunshades. 328

15.9. Current Aircraft Sunshades. 330

15.10. Sustainment and Accountability. 330

15.11. Allied Support (Electricity, Water, Communications, Lighting). 332

15.12. Crew Shelters and Portable/Inflatable Shelters. 333

Attachment 1—GLOSSARY OF REFERENCES AND SUPPORTING INFORMATION 335

Attachment 2—AIRCRAFT COMMANDER FEEDBACK ON FCC 374

Attachment 3—QUARTERLY FCC REPORT FORMAT 375

Attachment 4—ANNUAL FCC REPORT **376**

Attachment 5—FCC SDAP REQUEST **377**

Attachment 6—FOREIGN OBJECT DAMAGE (FOD) REPORT **378**

Attachment 7—CRITICAL APPLICATION ITEMS & CRITICAL SAFETY ITEMS **379**

Attachment 8—(Added-AFGSC) MAINTENANCE RECOVERY TEAM (MRT) TASKING CHECKLIST **380**

Attachment 9—(Added-AFGSC) MAINTENANCE RECOVERY TEAM (MRT) CHIEF RESPONSIBILITIES **382**

Attachment 10—(Added-AFGSC) MAINTENANCE RECOVERY TEAM (MRT) CHIEF TASKING CHECKLIST **384**

Attachment 11—(Added-AFGSC) MAINTENANCE SCHEDULING EFFECTIVENESS **385**

Attachment 12—(Added-AFGSC) DEPLOYED OPERATIONS AND OFF-STATION SORTIES **388**

Attachment 13—(Added-AFGSC) NONSTANDARD AIRCRAFT ROTATION JUSTIFICATION TEMPLATE **391**

Attachment 14—(Added-AFGSC) FLYING SCHEDULING EFFECTIVENESS **393**

Attachment 15—(Added-AFGSC) ATTRITION AND SPARE FACTOR **406**

Attachment 16—(Added-AFGSC) A4 EXECUTIVE REPORTING PROCEDURES **410**

Attachment 17—(Added-AFGSC) MAINTENANCE RISK MANAGEMENT (MRM) ASSESSMENT **412**

Chapter 1

MANAGEMENT OVERVIEW, SUPPORTING CONCEPTS AND REQUIREMENTS.

1.1. Introduction. This instruction prescribes basic aircraft and equipment maintenance management policy implementation and procedures used throughout the United States Air Force (USAF) to perform Mission Generation (MG) functions.

1.2. Organization. AF organizations are structured according to AFI 38-101, *Air Force Organization*, or as authorized by the Director of Manpower, Organization & Resources (AF/A1M). Contracted maintenance functions are not required to organize IAW AFI 38-101 but will implement the organization as outlined in their proposal as accepted by the government. For the definition of "Lead Command" see AFPD 10-9, *Lead Command Designation and Responsibilities for Weapon Systems.*

1.3. Maintenance Concept. Per AFPD 21-1, organizational, intermediate, and depot maintenance capabilities for operational readiness will be maintained to ensure effective and timely response to peacetime operations, mobilizations, national defense contingencies, and other emergencies. **Note:** Guidance for the use of Additive Manufacturing to build replacement parts is prescribed in AFI 63-101/20-101, *Integrated Life Cycle Management*.

1.3.1. As a minimum each capability will be able to:

1.3.1.1. Organizational: launch and recover sorties, maintain, and repair materiel coded for organizational level repair.

1.3.1.2. Intermediate: repair materiel coded for organizational and intermediate level repair in back shops, centralized repair facilities, or both.

1.3.1.3. Depot-level Maintenance: Provides the capability to maintain materiel coded for organizational, intermediate and depot levels of maintenance. Includes maintenance requiring the overhaul, upgrading, or rebuilding of parts, assemblies, or subassemblies, and the testing and reclamation of equipment as necessary.

1.3.2. Organizational and intermediate-level maintenance is organized into two mutually exclusive networks, the Mission Generation Network (MGN) and the Repair Network (RN). The MGN is optimized for mission generation at the wing level and consists of authorized "on-equipment" and "off-equipment" maintenance capabilities required to launch, recover, configure, inspect, and repair AF systems and equipment. The RN supports the MGN by providing the maintenance required to fulfill operational needs outside the capability or capacity of MGN activities. The interface between the two networks takes place when the MGN activity relinquishes control of reparable assets to the RN activity (such as, supply counter turn-in) or changes an end item Purpose Identifier Code (PIC) from an operational activity to a repair network activity (such as, depot maintenance).

1.3.2.1. Most MGN units possess a complement of equipment and supplies necessary to perform on-equipment and off-equipment maintenance.

1.3.2.2. RN units may reside at bases that perform mission generation. RN requirements and processes are identified in DAFI 20-117, *Repair Network Management*.

1.3.3. MAJCOMs assigned combat coded fighter aircraft will coordinate with Mission Design Series (MDS) lead and using commands and the MAJCOM Operations Directorate (MAJCOM/A3) to develop and document standardized MDS and Primary Aerospace Vehicle (Aircraft) Authorized (PAA) specific utilization rate standards in their supplements to this instruction. At a minimum the rates will:

1.3.3.1. Consider aggregated and analyzed unit generation capability data to identify and document standard MDS turn patterns by PAA in their supplements to **Chapter 14**.

1.3.3.2. Account for standard avionics and weapons training configurations.

1.3.3.3. Account for standard Technical Order (TO) driven turn time inspections and Average Sortie Duration.

1.3.3.4. Include a process for supporting units in assessing shortfalls and developing action plans.

1.3.4. Requests for Assistance. If a maintenance activity requires assistance for evaluation, repair, or both, beyond unit capability, requests are made IAW DAFI 21-103, *Equipment Inventory, Status and Utilization Reporting*; TO 00-25-107, *Maintenance Assistance*; and TO 00-20-14, *AF Metrology and Calibration Program*, or automated process as approved by the MDS Program Manager (PM) (for example, C-130 Automated Inspection, Repair, Corrosion and Aircraft Tracking (AIRCAT), F-16 Technical Assistance Request). All requests for assistance must be coordinated through the originating MAJCOM and Lead Command as applicable.

1.4. Aircraft Maintenance Tactics, Techniques and Procedures (TTP). TTPs are developed from lessons learned and best practices that provide valuable reference documents to improve maintenance processes and procedures. Maintenance leaders should utilize the maintenance fundamentals TTP volumes (Aircraft, Munitions and Missile) to support mission generation effectively and efficiently. Maintainers who attend the USAF Advanced Maintenance and Munitions Operations School are trained in advanced operational, expeditionary, and tactical maintenance management concepts stemming from the alumni's development and formalization of TTPs. Maintenance Group Commanders (MXG/CC) should identify their Advanced Maintenance and Munitions Operations School graduates and utilize them as advisors and instructors to enhance mission capability. AFTTP 3-4.21V1, *Aircraft Maintenance*, can be found at: **https://www.e-publishing.af.mil** or **https://usaf.dps.mil/teams/TTP/SitePages/Home.aspx**. For additional information on Advanced Maintenance and Munitions Operations School and TTP development see Air Force Manual (AFMAN) 21-111, *Advanced Maintenance and Munitions Operations School*.

1.5. Aircraft and Equipment Readiness. Aircraft and equipment readiness is the maintenance mission. The maintenance function ensures assigned aircraft and equipment are safe, serviceable, and properly configured to meet mission needs. Maintenance actions include, but are not limited to, inspection, repair, overhaul, modification, preservation, refurbishment, troubleshooting, testing, analyzing condition, performance, and maintenance documentation. All levels of supervision need to place emphasis on safety, quality, and timeliness in the performance of maintenance. The concept of quality maintenance must be fostered by each supervisor and technician to ensure the integrity and skill of each maintainer is not degraded. To the greatest extent possible, maintenance is accomplished on a preplanned scheduled basis. Planning provides

the most effective and efficient use of people, facilities, and equipment; reduces unscheduled maintenance; and allows for progressive actions toward maintaining and returning aircraft and equipment to safe operating condition. Exploiting repair network capability and maintaining visibility of repair cycle assets throughout the maintenance cycle are also critical elements of the equipment maintenance program.

1.5.1. The Air Force has established strategic-level aviation support equipment management within the 440 SCOS: Aviation Support Equipment Management Flight (ASEMF). The ASEMF has the responsibility to align with the integration of Aviation Support Equipment Maintenance Information System (AvSE MIS), also referred to as Defense Property Accountability System (DPAS) Maintenance and Utilization (M&U) Module capabilities. As AvSE MIS (DPAS M&U) comes online and units migrate assets into the new system, ASEMF will start to stand up and data mine available metrics on AvSE from AvSE MIS. These efforts combined (AvSE MIS and ASEMF) give the AF the greatest return to increasing one element of overall readiness in support of the National Defense Strategy (NDS).

1.5.2. Preventive Maintenance. AF units implement and manage the tasks specified in the scheduled recurring maintenance program for their assigned aircraft and associated support equipment (SE). Preventive maintenance is achieved through the inspection requirement concepts described in TO 00-20-1, *Aerospace Equipment Maintenance Inspection, Documentation, Policy, and Procedures*, and applicable weapon system -6 TO.

1.5.3. MAJCOMs that conduct Mission Generation Assessments or similar weapon system logistic evaluations in order to validate unit readiness will:

1.5.3.1. Provide units a standardized assessment report containing, at a minimum, positive, negative, and areas for improvement feedback to facilitate cross tell to like units.

1.5.3.1.1. Analyze unit generation processes to capture and communicate best practices.

1.5.3.1.2. Analyze unit generation performance to identify and communicate noteworthy trends.

1.5.3.2. Directorates of Logistics, Engineering & Force Protection (MAJCOMs A4s) will semi-annually report their top three trends and causal factors to the Logistics Board to facilitate debate to identify and mitigate potential limiting factors. Submit MAJCOM top three trends to the AF/A4LX workflow no later than 30 days prior to each Logistics Board meeting for consolidation at: **AF.A4LX.Workflow@us.af.mil**.

1.6. Maintenance Discipline. It is the responsibility of all maintenance personnel to comply with all written guidance to ensure required repairs, inspections, and documentation are completed in a compliant, safe, timely, and effective manner. Supervisors are responsible for enforcing and establishing a climate that promotes maintenance and supply discipline. Unless expressly stated otherwise in a particular instruction, waiver, or deviation in this DAFI granted by the appropriate authority, all Airmen must follow AFIs. AFIs do not provide optional guidance, and failure to comply with DAFIs can result in disciplinary action as described in AFI 1-1, *Air Force Standards*. Civilian personnel who violate punitive publications may also be subject to disciplinary action. See DAFMAN 90-161 for more detailed information on the use of punitive language in publications.

1.6.1. Compliance Terminology. For the purposes of this instruction, the following definitions apply:

1.6.1.1. Must, Will - Indicates mandatory requirements. **Note:** "Will" is also used to express a declaration of purpose for a future event.

1.6.1.2. Should - Indicates a preferred method of accomplishment.

1.6.1.3. May - Indicates an acceptable or suggested means of accomplishment.

1.6.2. Use of TOs and TO Supplements. All personnel will enforce compliance with technical data. **(T-2)** Use of prescribed technical data to maintain aircraft and equipment is mandatory and will be conducted and managed IAW TO 00-5-1, *Air Force Technical Order System*.

1.6.3. AFTO Form 492, *Maintenance Warning Tag*. The Air Force Technical Order (AFTO) Form 492, *Maintenance Warning Tag*, is used as prescribed in technical data, local procedures, or both, to flag a condition that could cause damage or injury if ignored. Refer to TO 00-20-1 for additional guidance. **Note:** The AFTO Form 492 is replacing the AF Form 1492, *Warning Tag* referenced in DAFMAN 91-203, Air *Force Occupational Safety, Fire, and Health Standards*. Use of the AF Form 1492 is authorized until supplies are exhausted.

1.7. Communications Security (COMSEC)/Controlled Cryptographic Item (CCI). The Air Force CCI Central Authority is AFLCMC/HNC, Cryptologic and Cyber Systems Division (CCSD), Joint Base San Antonio-Lackland, Texas.

1.7.1. COMSEC/CCI will be managed, and personnel trained IAW AFMAN 17-1302-O, *Communications Security (COMSEC) Operations* and AFI 23-101, *Air Force Material Management*. Ensure all serially controlled and serially tracked COMSEC/CCI information is entered into the Maintenance Information System (MIS) IAW TO 00-20-2, *Maintenance Data Documentation*. **Note:** AFMAN 17-1302-O is accessible through the AF e-Pubs Warehouse Management System (WMS) at **https://wmsweb.afncr.af.mil/wms**.

1.7.1.1. Maintain serial number inventory accountability for all COMSEC/CCI issued or removed to Facilitate Other Maintenance (FOM).

1.7.1.2. Questions concerning COMSEC/CCI can be directed to the AF CCI Central Authority (**aflcmc.hncls.cciworkflow@us.af.mil**).

1.7.2. Maintenance Cybersecurity Discipline.

1.7.2.1. Maintaining positive maintenance cyber discipline practices of Department of Defense (DoD) Information Technology (IT) is critical to sustaining the mission. Department of Defense Instruction (DoDI) 8500.01, *Cybersecurity*, defines both hardware and software that is physically part of, dedicated to, or essential in real-time to the mission assurance of special purpose weapon systems. DoD IT is the most common IT encountered in flightline environments and includes (but is not limited to) electronic tools, aircraft, and associated support equipment. The culture of positive cybersecurity awareness and actions necessary to sustain cyber resiliency is required by all maintenance personnel to mitigate allusive cyber threats and optimize enduring mission generation capabilities.

1.7.2.1.1. All users perform an integral role in prevention, detection, and reporting suspected corrupted software of DoD IT which includes Information Systems (IS) and

Platform Information Technology (PIT), which is an electronic platform with information technology for a specific function. See **Table 1.1**.

Table 1.1. Tiered Interface Examples.

TIER	Type of Interface	Examples	Applicable TOs
1	On-Board	EC-130, XX-135, E-3, E-8	Device TO
2	Directly Connected	F-22 PMA, F-35 PMA, Viper MLV, CAPRE, CETS, DTADS	Device TO
3	Indirectly Connected	Test Eqpt., Support Eqpt., ATS, ATE, AIS, VDATS	TO 33-1-38
4	Not Connected	eTools	TO 00-5-1

1.7.2.1.1.1. All users must consult airframe Security Classification Guides, TO 33-1-38, *Cybersecurity for Automatic Test Equipment and Support Test Equipment (ATE/STE)*. TO 33-1-38 provides guidance for Cybersecurity Incident Reporting and refers users to applicable technical manuals, instructions, and publications when determining the classification of cybersecurity incidents and vulnerability documents.

1.7.2.1.2. Authorized and unauthorized uses of IT and PIT. All users must have the ability to distinguish between authorized and unauthorized uses.

1.7.2.1.2.1. Authorized uses must be vetted through a formal cybersecurity assessment process and be directed in specific TO guidance. **(T-2)** The governing TOs or equivalent publications specifically define authorized uses.

1.7.2.1.2.2. Unauthorized uses include connecting any hardware, uploading, or downloading software, or media not explicitly defined by TOs. This includes but is not limited to personal devices, phones, tablets, computers, Universal Serial Bus drives, and similar devices.

1.7.2.1.2.3. DoD IT, derivative AF Publications, and TOs provide users guidance on Automated Computer Program Identification Number System devices acquired from local Communications Squadrons and media obtained from DoD contractors.

1.7.2.1.2.4. All users will follow the applicable TO when directly or indirectly connecting computers and equipment to the aircraft or support equipment and when uploading or downloading data. **(T-2)**

1.7.2.1.2.5. All users will immediately discontinue use, report, and turn into the appropriate functional authority IT and PIT (WAM, Wing Cybersecurity Office, and the Mission Defense Teams/Cyber Squadron, if assigned) that are suspect for containing malicious software, malicious code, software bugs or unauthorized use. **(T-2)**

1.7.2.1.2.6. All users will complete Maintenance Cyber Discipline Training annually in MyLearning. **(T-2)**

1.7.2.1.3. MDS Lead Commands in coordination with the applicable PM will develop MDS and Support Equipment (SE) cyber threat mitigation methods and procedures for Organizational and Intermediate level maintenance activities. The methods and procedures must detect malicious code, report cyber incidence and issues, and remediate the incidence and issue affecting the MDS or SE. **Note:** Mitigation plan should be developed per DoDI 8500.01; TO 33-1-38, DoD 8570.01, *Information Assurance Workforce Improvement Program*; Military Standard (MIL-STD)-38784A, *General Style and Format Requirements For Technical Manuals*; 17- series AFIs.

1.7.2.1.3.1. The cyber threat mitigation methods must include MDS and SE specific training requirements. **(T-2) Note:** Training requirements could include training aids, for example, computer-based training on how the flightline maintainer should scan support equipment for malicious software.

1.7.2.1.3.2. Lead Commands must ensure current MDS and SE specific malicious code definitions are available to ensure positive cyber threat mitigation management support is available. **(T-2)**

1.7.2.1.3.2.1. MAJCOM and ANG will report system-specific cyber incidents to the applicable MDS Lead Command.

1.7.2.1.3.2.2. MAJCOM and ANG will follow airframe Security Classification Guides, TOs, and applicable technical manuals when providing "cross tell" to inform their subordinate units about system-specific cyber incidents, threats, and issues.

1.7.3. eTools.

1.7.3.1. eTools are portable electronic devices (such as laptop computer, handheld device) that operate in a disconnected mode and are certified to inter-operate on AF networks. eTools are mission critical: the primary purpose is for viewing electronic technical publications and in some cases are used to exchange maintenance data with approved MIS at the point of maintenance. eTools are procured IAW DAFMAN 17-1203, *Information Technology (IT) Asset Management (ITAM)*. **Note:** eTools do not include electronic devices and test equipment issued and configuration managed by a system PM (aircraft test and support equipment).

1.7.3.2. MAJCOM/ANG A4s will develop and implement standardized guidance on the management, use, storage, configuration, content update, security, and cyber hygiene processes necessary to support the approved use of all assigned eTools consistent and IAW the weapon system MDS specific technical orders and threat specific Air Force and DoD cyber publications.

1.7.3.2. **(AFGSC)** See TO 00-5-1, *AF Technical Order System*, and AFGSC Supplement for eTool management. **(T-2)**

1.7.3.3. The MAJCOM/ANG A4 guidance will include any assigned command-wide cyber threat awareness and mitigation strategies with reference to supporting publications, technical orders, and MAJCOM eTool OPR contact information in their supplement or addendum to this DAFI.

1.8. Environmental Compliance. It is the responsibility of all maintenance personnel to comply with all written guidance to ensure compliance with hazardous material, hazardous waste management and air emissions record keeping as required for environmental compliance IAW AFI 90-821, *Hazard Communication (HAZCOM) Program*, installation Environment, Safety, and Occupational Health Management System/Environment Management System (ESOHMS/EMS) policy/guidance and applicable environmental requirements and guidance.

1.9. Publications. Units may tailor procedures to the unique aspects of their own maintenance operation and publish directives, instructions, supplements, addendums, and, for functional areas, Operating Instructions (OI) IAW DAFMAN 90-161.

1.9.1. Develop, control, and maintain functional and emergency action checklists. At a minimum, each checklist is titled, dated, and coordinated with the wing safety office. Functional checklists are not to be used in place of or to circumvent technical data for operation, servicing, inspection or maintenance of aircraft, aircraft systems, munitions, and all other equipment supporting aircraft and munitions maintenance.

1.9.2. Methods and Procedures Technical Orders (MPTOs): Due to the close relationship between MPTOs and this DAFI, all changes and revisions to the MPTOs cited in **Attachment 1,** References of this DAFI will be routed from Air Force Material Command (AFMC) to AF/A4LM for content review for conflicts and policy gaps identification and mitigation prior to submission for publication.

1.10. Maintenance Training. Maintenance training provides initial, recurring, and advanced proficiency, qualification, or certification skills needed by a technician to perform assigned duties. Maintenance training includes combat and sortie generation skills not normally integrated into peacetime operations (such as, Multi-Capable Airmen, munitions handling, and external fuel tank build-up, hot refueling). Maintenance training carries an equal priority with the operational training mission. For maintenance training policy and guidance, refer to AFI 36-2650, *Maintenance Training* and MAJCOM supplements.

1.11. Modification Management. A modification proposal is a recommendation to change the operation, use, or appearance of AF equipment. Modifications (temporary, permanent, or safety) to AF aircraft or equipment are expressly prohibited without PM approval. **Note:** PM is used in this publication as defined in AFPD 63-1, *Integrated Life Cycle Management*. Refer to AFI 63-101/20-101, for modification management procedures.

1.11.1. Modifications to Munitions. All proposed modifications to aircraft-carried munitions include AFI 63-101/20-101 and SEEK EAGLE certification IAW AFI 63-101/20-101 and Air Force Pamphlet (AFPAM) 63-129, *Air System Development Process and Procedures*. All modifications to AF nuclear munitions or their associated support and training equipment are nuclear certified IAW AFI 63-125, *Nuclear Certification Program*. All modifications to AF conventional munitions or their associated support and training equipment are certified IAW DAFI 91-205, *Non-Nuclear Munitions Safety Board*.

1.12. Maintenance Information System (MIS). MIS refers to automated maintenance information systems that support and enable maintenance business processes. The MIS is used to document maintenance actions and track fleet health. The information entered into the MIS is accomplished IAW TO 00-20-2 and matches the content of the aircraft forms. MIS data entries do not have to be accomplished by the same individual who documented the aircraft forms, but

employee numbers, man numbers, and User IDs of individuals accomplishing the actual work are entered into the MIS. Red Ball maintenance is documented IAW **Chapter 11**. Data integrity is the responsibility of every member of the unit. All personnel are responsible for ensuring accuracy and completeness.

1.12.1. Units use the approved MIS for their assigned weapon system.

1.12.2. Serial numbers will be documented in the MIS for all serially controlled and tracked assemblies that are identified by an asterisk in the Work Unit Code (WUC) or Logistics Control Number (LCN) manual IAW TO 00-20-2.

1.13. General Safety Guidance. Maintenance personnel are exposed to a large variety of hazardous situations, machinery, equipment, and chemicals. Most hazardous situations can be avoided by following approved procedures, asking for assistance when needed, and using all required personal protective equipment (PPE).

1.13.1. Safety "Knock It Off" and Risk Management. Due to the inherent danger to life, limb, and property associated with maintenance operations, personnel are empowered to terminate an operation or situation which they perceive is unsafe or too dangerous. When supervisors or crew leaders become task-focused, junior personnel are often better able to assess the danger; however, deferring to the experience and judgment of the supervisor or crew leader, they may choose to remain silent, missing an opportunity to break the mishap sequence chain. Maintenance commanders and supervisors are responsible for fostering a culture in their units so that a simple, but recognizable "audible" from anyone can prevent a potential mishap. **Note:** See AFI 90-802, *Risk Management*, and DAFPAM 90-803, *Risk Management (RM) Guidelines and Tools* for additional information.

1.13.1.1. **(Added-AFGSC)** Aviation Safety Action Program (ASAP). During day-to-day maintenance operations, unnecessarily hazardous situations can go by that are witnessed, but never reported. These unreported hazards could lead to an actual mishap if steps are not taken to prevent them from re-occurring. This is where ASAP can be used as a helpful tool for all maintainers to prevent mishaps from occurring. ASAP is a web-based, self-reporting system that provides individuals with a proactive, non-retribution, and identity-protected means to report and address errors, hazardous situations and events, and/or high-risk activities not identified by other reporting means prior to an actual mishap. Any person who has experienced or observed a hazardous situation error is encouraged to submit a report via the SAFEREP App or website, **https://saferep.safety.af.mil** or call the local safety office. For more information see DAFI 91-225 AFGSCSUP, *Safety Programs*. **(T-2)**

1.13.2. Visitors. Unit Commanders will not permit visitors to operate any AF equipment unless they are qualified to operate such equipment and are doing so in the performance of their assigned official duties. **(T-2)** Visitors will not be allowed in the flightline area if munitions operations are present IAW DESR6055.09_AFMAN 91-201, *Explosive Safety Standards*.

1.13.3. **(Added-AFGSC)** AFGSC Aircraft Maintenance Risk Management (MRM) Assessment. The AFGSC Maintenance Risk Management (MRM) Assessment is designed to enhance risk awareness and mitigation practices within AFGSC maintenance activities. It is specifically focused on tasks identified as having elevated risk profiles. By proactively identifying and analyzing risks, the MRM Assessment aims to empower technicians and

supervisors to implement effective control measures, thereby reducing the likelihood of incidents, injuries, and equipment damage during the execution of elevated-risk maintenance operations. Ultimately, the MRM Assessment contributes to a safer and more efficient maintenance environment by fostering a culture of proactive risk management and informed decision-making.

1.13.3.1. **(Added-AFGSC)** All non-contract aircraft maintenance personnel will complete the AFGSC Maintenance Risk Management (MRM) Assessment **(Attachment 17)** while performing elevated risk tasks. See **paragraph 1.13.3.2**. **(T-2) Note:** National Airborne Operations Center (NAOC) alert and Global Command and Control Missions (GC2M) missions (595AMXS) do not have to complete MRM Assessment. Commanders will determine usage of MRM Assessment during contingency operations.

1.13.3.1.1. **(Added-AFGSC)** If the same team performs multiple instances of the same operation or related task (e.g., non-standard towing operations, landing gear extensions and retraction) in the same shift, they are not required to perform additional AFGSC MRM Assessments unless factors change in a manner that increases risk.

1.13.3.1.2. **(Added-AFGSC)** The completed copy of the AFGSC MRM Assessment will be given to Quality Assurance (QA) within 24 hours of task completion for historical data and be kept on file for a minimum of one year.

1.13.3.1.3. **(Added-AFGSC)** The MXG/CC or equivalent may expand upon the list of elevated risk tasks to include non-standard tasks and operations that increase the risk of damage to aircraft, equipment, other resources or injury of personnel.

1.13.3.2. **(Added-AFGSC)** The following tasks are deemed elevated risk by AFGSC and require an AFGSC MRM Assessment:

1.13.3.2.1. **(Added-AFGSC)** Aircraft Hoisting and Jacking. **Note:** This does not include axle jacking.

1.13.3.2.2. **(Added-AFGSC)** Landing gear extension/retraction operational checkouts.

1.13.3.2.3. **(Added-AFGSC)** Concurrent Servicing Operations.

1.13.3.2.4. **(Added-AFGSC)** Flight Control Operational Checkouts where the potential for injury to personnel from a moving surface exists. All personnel should remain aware of their surroundings and maintain a distance of five feet from moving surfaces at all times unless specified in technical data.

1.13.3.2.5. **(Added-AFGSC)** Towing (e.g., austere location, close proximity clearance). **Note:** AFGSC MRM Assessment is not required for standard towing operations.

1.13.3.2.6. **(Added-AFGSC)** Oxygen System Maintenance (e.g., O2 regulator maintenance, hot gas purge) excluding pre/post flight LOX/GOX servicing tasks. **(T-3)**

1.13.3.2.7. **(Added-AFGSC)** Crane/Hoist operations during adverse weather and when clearance is limited. **Note:** AFGSC MRM Assessment is not required for standard Crane/Hoist operations.

1.13.3.2.8. **(Added-AFGSC)** Cabin Pressure Check. **(T-3)**

1.14. Duty Shifts and Rest Periods. MXG/CC or equivalent will establish minimum requirements that ensure units maintain an equitable distribution of supervision (Officer and Senior Non-Commissioned Officer (SNCO)) across all on-duty shifts in their supplement to this DAFI. **(T-3)**

1.14.1. During normal operations, maintenance personnel are scheduled for duty based on a 40-hour work week. Maintenance personnel duty hours are aligned to provide optimal mission support.

1.14.2. Personnel will not be scheduled for more than 12 hours of continuous duty time. **(T-3)** Duty time begins when personnel report for duty and ends when their supervisor releases them. Time spent in exercise or contingency deployment processing lines and in-transit counts toward the total duty day. SQ/CCs are the final approval authority for duty time extensions exceeding the 12-hour limit up to a maximum of 16 hours. **(T-3) Note:** Aircraft or detachment commanders assume this responsibility in Temporary Duty (TDY) or travel status.

1.14.2.1. **(Added-AFGSC)** If operational requirements justify extending the duty time, approval will be documented using email, memo, etc.

1.14.2.2. **(Added-AFGSC)** All 12-hour duty time limit and rest period extensions will be reported monthly using the AFGSC 0901 process. **(T-2)**

1.14.3. Commanders and supervisors will provide a rest period after each shift. **(T-3)** A rest period is a block of time that gives a person the opportunity for 8 hours of uninterrupted sleep in a 24-hour period.

1.14.4. When handling, loading, or performing maintenance on nuclear weapons, conventional munitions, or egress explosives, personnel will follow requirements IAW AFMAN 21-200.

1.14.5. In alert force or standby duty situations where facilities are available for resting, established norms may be exceeded. Adjust rest periods to allow for 8 hours of uninterrupted sleep.

1.14.6. Commanders and supervisors will ensure individuals are afforded adequate duty rest periods and breaks to prevent fatigue or thermal injury. Stop anyone if fatigue may jeopardize safety. In all cases, aircraft commanders or supervisors ensure aircraft maintenance personnel are not required to perform duty when they have reached the point of physical or mental fatigue rendering them incapable of performing their assigned duties safely and reliably.

1.14.7. MAJCOM Commanders will assume the risk for any Flying Crew Chief (FCC) deviations from normal duty shifts, rest periods, and exceedance of the 16-hour maximum duty day. MAJCOM Commanders will publish risk-mitigation procedures in order to meet critical mission requirements.

1.14.7. **(AFGSC)** For risk-mitigation procedures utilize AFPD 90-8, *Environment, Safety, and Occupational Health Management and Risk Management*, and AFI 90-802, *Risk Management*. Use DD Form 2977, *Deliberate Risk Assessment Worksheet*, (as required).

1.15. Communications. Commanders will develop communication plans according to AF mission requirements. See **Chapter 11** for detailed communication requirements.

1.15.1. Effective maintenance accomplishment requires the ability to communicate across all facets of the maintenance operation efficiently and effectively. Communication technology (government issued Portable Electronic Devices (PED), Portable Maintenance Aid (PMA), radios, cell phones, computers, wireless internet) must be available to expedite personnel, equipment, material, and maintenance data throughout the maintenance complex. **(T-2)**

1.15.2. MAJCOMs will publish guidance for the use and control of personal communications devices (personal cell phones, tablets, and computers) on the flightline, in munitions areas, hangars, and other industrial work areas as required to mitigate cyber risk and ensure compliance with cyber and communication AFI requirements relevant to their operational environments.

1.15.2. **(AFGSC)** Personal electronic or communication devices (e.g., cell phones, portable music/video players, electronic games, tablets, etc.) are prohibited on the flightline, munitions areas, hangars, and/or other industrial work areas. This prohibition does not include common areas such as office areas, break rooms, or locker/ready rooms. Government equipment issued for the performance of official duties with proper authorization is exempt from this prohibition.

1.15.3. Unit Commanders will enforce procedures that prohibit the introduction of government or personal cellular, personal communications system, Radio Frequency (RF), Infrared (IR) wireless devices, and other devices such as cell phones, tablets, and devices that have photographic or audio recording capabilities into areas (e.g., rooms, offices) where classified information is stored, processed, or discussed IAW AFMAN 17-1301, *Computer Security (COMPUSEC)*. Coordinate waiver requests with the applicable Approving Official (AO), and ensure adherence to Certified TEMPEST Technical Authority (CTTA) requirements IAW Department of Defense Directive (DoDD) 8100.02, *Use of Commercial Wireless Devices, Services, and Technologies in the DoD Global Information Grid (GIG)* written approval by the AF CTTA IAW NIST SP 800-53A Revision 4, *Assessing Security and Privacy Controls in Federal Information Systems and Organizations: Building Effective Security Assessment Plans*, and the Enterprise Authorizing Official (AO) IAW DAFI 31-101, *Integrated Defense (ID)* and AFMAN 17-1301.

1.16. Maintenance Repair Priorities. Maintenance repair priorities are listed in **Table 1.2**. This does not prohibit the Production Superintendent (Pro Super), in coordination with the Maintenance Operations Center (MOC), from changing the maintenance repair priority when warranted. During tasked Operational Plan (OPLAN) or operational exercise, the pre-planned maintenance flow determines the job sequence. The maintenance repair priority and the Logistics Readiness Squadron (LRS) delivery priorities (listed in Air Force Handbook (AFH 23-123V, *Materiel Management Reference Information*) are normally identical. Raising or lowering maintenance repair priorities does not necessarily require a corresponding change in the LRS delivery priority. However, the Pro Super may authorize the use of a less responsive LRS delivery priority.

Table 1.2. Maintenance Repair Priority Designators.

PRIORITY	APPLICATION
1	Aircraft on alert status, war plan or national emergency missions, including related Aerospace Ground Equipment (AGE), munitions and Munitions Support Equipment.
2	Primary mission aircraft, related AGE, munitions, and munitions support equipment, for the first 8 work hours after landing or start of recovery or within 6 work hours of a scheduled launch, alert or test flight and during simulated generation or Operational Readiness Exercises (ORE). Air evacuation, rescue, weather (WX) mission aircraft, related AGE, munitions, and munitions support equipment. All transient support, and FAA aircraft. Flight or missile crew training simulator, other training equipment or related AGE required repair, which is impacting the mission by preventing or delaying student training.
3	Primary mission aircraft, engines, air launched missiles and related AGE, munitions and munitions equipment, and equipment undergoing scheduled or unscheduled maintenance, if not performed or repaired will prevent or delay mission accomplishment. Transient air vehicles not otherwise listed. Administrative aircraft within 8 hours of scheduled flight or on alert status with standby crews. Time change requirements for nuclear weapons. Repair cycle assets to satisfy a Mission Impaired Capability Awaiting Parts (MICAP) condition. Spares not available in supply. Critical end items and spares not available in supply. Routine maintenance of aircrew or missile-training simulator, or other training devices or related AGE or sites and aircraft or equipment used for maintenance training. Avionics shop electronic AGE and automated test stations.

4	Routine or extensive repair of primary air mission and related AGE and repair cycle assets. Administrative aircraft undergoing scheduled or unscheduled maintenance. Routine maintenance of AGE not otherwise listed above. War Reserve Materiel (WRM) items due maintenance or inspection. Inspection, maintenance, and Time Compliance Technical Order (TCTO) compliance of Mission Support Kit or Mobility Readiness Spares Package (MRSP) materiel. Extensive repair of aircrew or missile training simulators, other training devices, or related AGE. Inspection, maintenance, and TCTO compliance of munitions and munitions equipment, excluding spares excess to base requirements not listed above. Scheduled calibration and unscheduled repairs on Precision Measurement Equipment (PME) not listed above. Scheduled maintenance to include periodic inspections, routine TCTO, Master Configuration Lists (MCL) Grounding, and Time Change Items (TCIs). Primary mission Comprehensive Engine Management System (CEMS) or equipment including associated AGE undergoing extensive repair or modification.
5	Non-tactical or non-primary-mission aircraft undergoing extensive repair. Fabrication and repair of aeronautical items not carrying a higher priority. Bench stock requirements. Extensive repair of aircrew training devices. Time change requirements not listed above. Routine repair of AGE and repair cycle assets. Alternate and other CEMS or equipment, including associated AGE undergoing extensive repair or modification. Clearing routine delayed discrepancies on training equipment or AGE, and routine maintenance which will not impair or affect mission accomplishment. Equipment requirements.

6	Fabrication and repair of non-aeronautical items. Repair cycle asset shortages required to fill a peacetime operating stock authorization
7	Spares/repair cycle assets excess to base requirements.

1.17. Associate Unit Program/Total Force Integration (TFI). The USAF employs the Associate Unit/TFI program in some locations where RegAF and Air Reserve Component (ARC) units are collocated and share aircraft, equipment, facilities, and other resources IAW AFI 90-1001, *Planning Total Force Associations (TFAS)*, and MAJCOM supplements. For the purpose of this instruction, in an Active Association, the ANG or AFR owns the aircraft, and RegAF personnel will follow ANG or AFR maintenance policy. In an ARC association, AFR owns the aircraft, and ANG personnel will follow AFR guidance, or vice versa. In a classic association, RegAF owns the aircraft, and ANG or AFR personnel will follow RegAF maintenance policy. Type of association is determined by the Program of Record for the associated unit.

1.18. Performance-Based Activities. MAJCOMs may publish the basic responsibilities for managing performance-based activities.

1.18.1. If published MAJCOMs will:

1.18.1.1. Designate focal points for organizational, functional, and technical questions pertaining to each performance-based activity program.

1.18.1.1. **(AFGSC)** For maintenance contracts, the contract program manager is the designated focal point for all organizational, functional, and technical questions pertaining to each contract. Focal points for MAJCOM owned contracts concerning aircraft maintenance/support related programs are program managers located within HQ AFGSC/A4A and HQ AFGSC/A4M. Focal points for base level contracts will be the applicable Group contract program managers. The program manager is the designated person with the responsibility to monitor/provide oversight functions for the contract. **(T-2)**

1.18.1.2. Specify measurement areas and performance levels required for aircraft, systems, and equipment operated or maintained by performance-based activities.

1.18.1.3. Specify the forms, methods of documentation, and frequency of reporting used to assess performance-based activities and ensures these requirements are included in the Quality Assurance Surveillance Plan (QASP).

1.18.1.4. Ensure units with assigned Contracting Officer Representative personnel meet requirements in AFI 63-138, *Acquisition of Services*.

1.18.1.5. Ensure aircraft depot maintenance contracts, Statements of Work (SOW), and Performance Work Statements (PWS) are coordinated with the applicable MAJCOM Functional, to include Munitions.

1.18.2. Unit Commanders will:

1.18.2.1. Designate a focal point for all functional, technical, and contracting officer representative matters pertaining to performance-based activities. **(T-3)**

1.18.2.2. In coordination with the contracting officer and the Program Manager of Functional Services Manager, provide specific guidance to the performance-based activity to ensure proper maintenance discipline and flight worthiness of aircraft and subsystems. **(T-3)**

1.18.2.3. Develop and publish contingency procedures for support of continuing operations in the event of disruption, termination, or default of contracts. **(T-3)**

1.19. Changes to Technical Orders. Official TO updates are the only valid authority for maintaining TO accuracy and currency. To maintain this currency, the AF has instituted an enterprise electronic TO Recommended Change (RC) process.

1.19.1. The Enhanced Technical Information Management System (ETIMS) is the required system for Recommended Change management and this process replaces the AFTO Form 22, *Technical Manual (TM) Change Recommendation and Reply*, AFTO Form 252, *Technical Order Publications Change Request* and the DAF Form 847.

1.19.2. There are specific organizations that may require the deviations or exceptions for those who do not have access to ETIMS. Refer to TO 00-5-1 for specific guidance on the RC process.

Chapter 2

ROLES AND RESPONSIBILITIES

2.1. General. This chapter outlines responsibilities for commanders and key leaders involved in maintenance activities. Decisions made that increase risk to safety of flight will be communicated with operations. In units where there is not a military commander responsible for maintenance, the applicable civilian Director of Maintenance (DOM) will ensure compliance with all responsibilities in this instruction. For organizations without all commanders and key leaders assigned, MAJCOMs will identify equivalent positions of authority commensurate with the responsibilities of the leadership positions identified in this **Chapter** in a MAJCOM supplement to this instruction.

2.1.1. For the purpose of this instruction, contractor equivalents are as follows: A1C—aircraft servicer or apprentice/journeyman; SrA (1-year time-in-grade)—aircraft worker or field maintenance worker or higher; SSgt—aircraft mechanic or field maintenance mechanic or higher; TSgt—senior mechanic or craftsman; MSgt—lead mechanic; SMSgt/CMSgt/maintenance officer—foreman, branch chief or higher. MAJCOMs may determine grade and skill level equivalents for civilians.

2.1.1. **(AFGSC)** For this supplement only, the following equivalencies in **Table 2.1** and **Table 2.2** will be used by civilian personnel assigned to the MXG.

2.1.2. The functional authority to determine the need and design for civilian uniforms, under the purview of maintenance is delegated to the MAJCOMs/ANG. As such, all functional authority requirements set forth in AFI 36-128, *Pay Settings and Allowances* will also reside at the respective MAJCOM. The routing requirements for final approval of uniform requests and the establishment of uniform allowances will be IAW AFI 36-128.

2.2. Wing Commander (WG/CC) Responsibilities. The WG/CC allocates resources to meet all mission requirements. The WG/CC will:

2.2. (AFGSC) Wing Commander (WG/CC) Responsibilities. [DEV] The 582 HG/CC will ensure (WG/CC) compliance responsibilities for this paragraph for UH-1/MH-139 maintenance operations assigned to the 582 HG at FE Warren, Malmstrom, and Minot AFBs.

2.2.1. Ensure that maintenance organizations are not overtasked with augmentation duties outside maintenance functional areas. **(T-2)**

2.2.2. Conduct a "Wing Standup" meeting. **(T-3)** The MAJCOM/ANG will establish “Wing Standup” meeting frequency that synchronizes communications necessary to optimize fleet readiness and mission generation capability in their supplement to this DAFI.

2.2.3. Ensure a coordinated wing or base instruction is developed that implements procedures to control tools, equipment, electronic devices, and establishes cyber discipline and reporting requirements that provide operational guidance across all wing or base agencies dispatching to aircraft runway, taxiways, parking, and maintenance areas. **(T-2)**

2.2.3. **(AFGSC)** AFGSC tenant units follow host unit instruction, as applicable.

2.2.3.1. Ensure home station Base Support Plans (BSP) include contingency bare base, comm-out, and cyber-out operating procedures. Periodically exercise operations (as part of

scheduled local exercises) in this simulated deployed environment to validate equipment, personnel, and processes provide the required mission generation capability. **(T-2)**

2.2.3.1.1. Develop and maintain local cyber abatement and status reporting procedures that optimize cyber resiliency and the ability to mitigate and recover from cyber threats affecting assigned mission or sortie generation operations. **(T-2)**

2.2.3.1.2. Ensure Wing Cybersecurity Office directs Wing cybersecurity compliance per AFI 17-101, Risk Management Framework (RMF) for Air Force Information Technology (IT), specifically to address cybersecurity assurance of Wing aircraft and support equipment categorized as Operational Technology (OT). **(T-2) Note:** Currently known as Platform Information Technology (PIT).

2.2.4. Ensure maintenance and operations develop a joint annual maintenance and Flying Hour Program (FHP) that establishes a balance between the requirement for sorties and maintenance capability. **(T-2)**

2.2.4.1. Establish a joint MXG and OG planning and scheduling cycle to ensure the best use of aircraft, equipment, and personnel to accomplish short-term sortie production and long-term fleet health. **(T-3)**

2.2.4.2. Approve the weekly; monthly, quarterly, and annual flying or test schedules IAW **Chapter 14**. **(T-3)**

2.2.4.3. DELETED.

2.2.5. Vector future leaders to attend the Senior Leader Mission Generation (SLMG) Course following the course description and criteria listed in **Chapter 11**. **(T-2)**

2.2.6. Ensure a Crashed, Damaged, or Disabled Aircraft Recovery (CDDAR) capability exists for assigned active airfields and runways IAW **Chapter 11** and develop a wing publication IAW DAFMAN 90-161 containing specific responsibilities for all applicable base support agencies. **(T-2)**

2.2.6. **(AFGSC)** Ensure the publication contains a plan adequately covering Crash Damage or Disabled Aircraft Recovery (CDDAR) capabilities for all aircraft that frequently transit the base (averaging 3 or more times per month within one year). This plan will include coordination and agreements with applicable local emergency/medical and security services, contract functions, in-theater aircraft wings, MAJCOMs, and other branches of service, etc. Consider establishing an agreement with local airports to further enhance rapid response capability.

2.2.6.1. Collaborate with Fire Emergency Services, Wing Safety, CES, LRS, SFS, MDS, OSS, and other on-/off-base agencies to develop a publication IAW DAFMAN 90-161, that assigns specific responsibilities and procedures to implement a sustainable CDDAR program IAW TO 00-80C-1. Ensure wings with GSU/auxiliary fields outline support requirements in their publication.

2.2.6.2. **(Added-AFGSC)** The 95 WG captures support agreements in the host unit directive, instruction, supplement, or Memorandum of Agreement/Understanding (MOA/MOU) that outlines CDDAR requirements.

2.2.7. Identify specific responsibilities and outline unique materiel management support requirements necessary to optimize wing level maintenance and mission generation operations. Establish processes and responsibilities for maintenance units and work centers without material management support in a local publication. **(T-2)**

2.2.8. Approve hot refueling site certification(s). **(T-3)**

2.3. Wing Vice Commander (WG/CD) Responsibilities. The WG/CD (or equivalent) will:

2.3.1. Manage the Foreign Object Damage (FOD) and Dropped Object Prevention (DOP) Programs. **(T-2)** The WG/CD is the FOD/DOP Prevention Program Manager and will appoint a FOD/DOP Prevention Monitor(s) IAW **Chapter 11**.

2.3.2. Ensure the wing safety office, base operations, and emergency services actively participates in development and coordination of base functional and emergency action checklists. **(T-2)** Ensure content includes and complies with all required safety standards, evacuation distances and MDS specific hazards (such as, egress systems, Hydrazine). **(T-2)** Ensure checklists address all known hazards associated in responding to mishaps, adverse weather, natural disaster, and other emergency responses. **(T-2) Note:** Review, update, and coordinate functional and emergency action checklist with using units every two years.

2.3.3. Chair the FOD/DOP meeting, if required, and will determine minimum required attendees. **(T-3)** The purpose of this meeting is to identify negative trends and develop and execute action plans to resolve them.

2.4. Maintenance Group Commander (MXG/CC) Responsibilities. In addition to the responsibilities listed below, the MXG/CC or equivalent must ensure compliance with the maintenance requirements and programs of this instruction. **(T-3)** Approved variations in the MXG organization does not relieve the MXG/CC of compliance with all the requirements of this DAFI. In organizational structures where an MXG/CC is not assigned (i.e., AFFORGEN deployed construct), all 2.4.1. paragraphs will move up to the WG/CC and all 2.4.2. paragraphs will move down to the Mission Generation Force Element (MGFE) leader, delegable to the senior maintenance leader. Additionally, all 2.4.3. paragraphs' responsibilities will remain with the home unit's MXG/CC, or WG/CC in the absence of an MXG/CC, and any guidance or documentation necessary to support the mission will be brought with the unit.

2.4. (AFGSC) Maintenance Group Commander (MXG/CC) Responsibilities. The 95 WG Deputy Commander for Sustainment (DCOM-S) will execute (MXG/CC) compliance responsibilities of this paragraph and all sub paragraphs for E-4 maintenance operations assigned to the 95 WG at Offutt AFB.

2.4.1. The MXG/CC will:

2.4.1.1. Ensure standardization of maintenance discipline, procedures, organizational structures, compliance, and management philosophy. **(T-3)**

2.4.1.2. Establish a radiation protection program IAW AFI 48-109, *Electromagnetic Field Radiation Occupational & Environmental Health Program,* when applicable.

2.4.1.3. Designate a focal point for all functional, technical, and COR matters pertaining to performance-based activities. **(T-3)** Refer to **Chapter 1**.

2.4.1.4. Ensure munitions are accounted for IAW DAFMAN 21-201, *Munitions Management*, AFMAN 21-200, *Munitions and Missile Maintenance Management*, AFMAN 21-203, *Nuclear Accountability Procedures*, and AFI 20-110, *Nuclear Weapons-Related Materiel Management*.

2.4.1.5. Ensure a nuclear surety program is implemented (if applicable) IAW DAFI 91-101, *Air Force Nuclear Weapons Surety Program*, and nuclear munitions are maintained, handled, and accounted for IAW AFMAN 21-204, *Nuclear Weapons Maintenance*, AFMAN 21-203.

2.4.1.5.1. For units possessing Nuclear Certified Equipment (NCE), the MXG/CC will ensure personnel are trained in the proper use of nuclear flagwords, mishap, and deficiency reporting instructions IAW AFMAN 91-221, *Weapons Safety Investigations and Reports* and DAFI 91-204, *Safety Investigation and Reports*.

2.4.1.6. Establish CDDAR capability IAW **Chapter 11** and applicable MDS technical data. **(T-2)** The MXG/CC will ensure resources and trained personnel are available to perform responsibilities of the CDDAR Program. **(T-3)**

2.4.1.7. Sustain a Transient Alert (TA) function (if required). **(T-3)** The MXG/CC will establish procedures and furnish necessary personnel and facilities for handling transient aerospace vehicles to ensure that servicing, inspection, and maintenance are consistent with the mission of each transient aerospace vehicle. **(T-3)** Special consideration should be given to medical or air evacuation aerospace vehicle, emergency missions, and special missions.

2.4.1.7.1. Approve FCF requirements, submitted by the TA Section NCOIC/Chief to off-station TA and off-station QA sections. **(T-3)**

2.4.1.7.2. For transient alert, the MXG/CC may direct the WS Personnel to arm, de-arm, and unload an aircraft on which they are not certified and/or qualified if appropriate technical data and support equipment is available. **(T-3)**

2.4.1.7.2.1. The host MXG/CC or authorized representative may delegate this responsibility to the transient aircraft commander/pilot for new or experimental aircraft. **(T-3)**

2.4.1.8. Direct QA to develop/manage local OTIs IAW TO 00-20-1 and this instruction for Aircraft Grounding. **(T-3)**

2.4.1.9. Endorse TCTO notification messages to MAJCOM when anticipated problems will prevent compliance within prescribed time limits. **(T-3)**

2.4.1.10. Ensure a read file or equivalent exists for distributing maintenance crosstalk messages, QA newsletters, Higher Headquarters (HHQ) and local policy announcements, technical notifications, and other important maintenance information to all assigned airman. **(T-3)**

2.4.1.11. Ensure direct mission generations support focuses on readiness and the unit's ability to execute daily and deployed flying operations simultaneously. **(T-3)**

2.4.1.12. Chair the FOD meeting in the absence of the WG/CD. **(T-3)**

2.4.1.13. Ensure maintenance requirements (such as, aircraft turnaround, alternate fuel cell, hot refueling, end-of-runway (EOR) check area, engine run spots, explosive load (cargo) areas) are included in the base parking plan. **(T-3)**

2.4.1.14. Communicate constraints with OG to decide what portion of the mission to support and to what degree if conflicts arise between operational requirements and maintenance capability. **(T-3)**

2.4.2. The MXG/CC will:

2.4.2.1. Appoint an MXG Environmental Coordinator IAW AFI 32-7001, *Environmental Management.* Refer to AFI 90-821, installation ESOHMS/EMS policy, guidance, and applicable environmental requirements and guidance, DAFMAN 91-203, and AFMAN 32-7002, *Environmental Compliance and Pollution Prevention*, for additional guidance.

2.4.2.2. Establish and support a Data Integrity Team (DIT). **(T-3)**

2.4.2.3. Ensure the Maintenance Standardization and Evaluation Program (MSEP) requirements are implemented IAW **Chapter 6**. **(T-3)**

2.4.2.4. Establish measures that ensure all maintenance personnel are assigned IAW the Duty Title Tool, are available, and utilized to accomplish critical maintenance tasks necessary to integrate maintenance capabilities that optimize Aircraft Availability (AA). **(T-3)** Maximize utilization of 7-skill level maintenance personnel in the grade of E-5 to E-7 in direct mission generation roles and minimize their use in staff positions or non-maintenance duties. **(T-3)** Note: Consider utilization of Civil Service MXG/SQ Unit Program Coordinators to consolidate programs to maximize availability of sortie generation maintainers on the flightline to maximize AA.

2.4.2.5. Implement an effective Corrosion Prevention and Control Program IAW TO 1-1-8, Application and Removal of Organic Coatings, Aerospace and Non-Aerospace Equipment; TO 35-1-3, Corrosion Prevention and Control, Cleaning, Painting, and Marking of USAF Support Equipment; TO 1-1-691 Cleaning and Corrosion Prevention and Control, Aerospace and Non-Aerospace Equipment.

2.4.2.6. Ensure effective use of the assigned AF Engineering and Technical Services (AFETS), Contractor Engineering and Technical Services (CETS), and contracted Field Service Representatives (FSRs) IAW **Chapter 11**.

2.4.2.7. Ensure the applicable section “safes” all static display aircraft/systems IAW the applicable 00-80-series and weapon system-specific TOs.

2.4.2.8. Ensure the MXG Oil Analysis Program (OAP) complies with **Chapter 11**. **(T-3)**

2.4.2.9. Ensure Engine Health Management Plus (EHM+) duties are performed IAW AFMAN 20-116 for EHM products managed by Air Force Life Cycle Management Center AFLCMC/LP. If EHM data is not managed by AFLCMC/LP, ensure Contractor Logistics Support (CLS) provided EHM products are managed according to respective contract. **(T-3)**

2.4.2.9. **(AFGSC)** Personnel performing this duty will be a qualified 2A6X1 with a minimum 7-skill level (or civilian equivalent).

2.4.2.10. Appoint a hot refueling/hot defueling OPR for the Wing (WG) and designate an OPR for hot refuel training (if applicable). **(T-3)**

2.4.2.11. Ensure unit personnel collect and report Aircraft Structural Integrity Program (ASIP) data IAW DAFI 63-140, *Aircraft Structural Integrity Program and Air and Space Equipment Structural Management,* and **Chapter 11**. **(T-3)**

2.4.2.12. Ensure aircraft and equipment sunshades are maintained IAW **Chapter 15**. **(T-3)**

2.4.2.13. Ensure management of the Weight and Balance (W&B) program IAW **Chapter 6**. **(T-3)**

2.4.2.14. Coordinate with the Operations Group (OG) and establish Functional Check Flight (FCF), Operational Check Flight (OCF), and High-Speed Taxi Check programs. **(T-3)**

2.4.2.15. Implement the Hangar Queen Program IAW **Chapter 11**. **(T-3)**

2.4.2.16. Ensure compliance with Identification Friend or Foe Program or equivalent IAW **Chapter 11** (if equipped). **(T-3)**

2.4.2.17. Provide Subject Matter Expertise (SME) support for the development of the wing or installation instruction to control tools, equipment, and electronic devices from all wing agencies dispatching to aircraft parking, runway, taxi areas, and aircraft maintenance areas IAW **Chapter 2** and **Chapter 8**. **(T-3)**

2.4.2.18. Ensure Air Force Repair and Enhancement Program (AFREP) is managed IAW **Chapter 11**. **(T-3)**

2.4.2.19. Establish procedures to ensure assigned units have sufficient eTools available for technical order viewing. **(T-3)**

2.4.2.20. Develop procedures and assign responsibilities to ensure aircraft, aircraft system forms, equipment forms, and MIS documentation are complete, accurate, and are thoroughly reviewed each shift. **(T-3)** Documented procedures as a minimum will include:

2.4.2.20.1. The process for recovering aircraft, aircraft systems from extensive maintenance events, and down time ((cannibalization (CANN), local depot maintenance (MX)) include independent screening and validation that all maintenance actions (IPIs, operational checks, configuration management, W&B, serial number (S/N) tracking (COMSEC/CCI and other significant items as designated by an asterisk in the applicable WUC/LCN Manual)) and AFTO Form 95, *Significant Historical Data*, have been accurately documented in the forms, MIS, or both before being scheduled for a sortie or mission. **(T-3)**

2.4.2.20.2. The process for determining if an OCF or FCF is required. **(T-3)**

2.4.2.21. Ensure that when no 2W1X1 weapons AFSCs are assigned and units are required to install/remove chaff/flare on unique mission aircraft, personnel will be trained and qualified to perform these tasks IAW procedures outlined in AFMAN 21-206, *Aircraft Armament Systems Management,* and **Chapter 11** and approved by the WWM.

2.4.2.22. Ensure storage, physical security, corrupt systems quarantine procedures, and cyber threat mitigation management of MXG assigned PIT and eTools is supported and

sustained. **(T-3)** If deployed without an MXG/CC, corrupted systems and cybersecurity issues will be coordinated with the WG/CC.

2.4.2.23. Ensure personnel are trained and appointed as Aircraft Battle Damage Evaluators IAW **Chapter 11**. **(T-3)**

2.4.2.24. Establish minimum requirements that ensure units maintain an equitable distribution of supervision (Officer and Senior Non-Commissioned Officer (SNCO)) across all on-duty shifts. **(T-3)**

2.4.2.25. Ensure compliance with the local Impoundment Program. **(T-3)**

2.4.2.26. Be the Impoundment Release Authority, along with the MXG/CD. **(T-3)**

2.4.2.27. Designate Impoundment Authorities and track them on the SCR. **(T-3)**

2.4.2.28. Determine the need for an FCF for an uncommanded flight control movement. **(T-3)**

2.4.2.29. Coordinate with all wing organizations that work in or enter any maintenance area under his or her responsibility to ensure they have documented tool/equipment control procedures. **(T-3)**

2.4.2.30. Approve all locally manufactured, developed, or modified tools and equipment. **(T-3)**

2.4.2.31. Coordinate to ensure direct mission generations support focuses on readiness and the unit's ability to execute daily and deployed flying operations simultaneously. **(T-3)**

2.4.2.32. Approve items identified in **Table 11.1.**, **Note 1**. **(T-2)** The MXG/CC at their discretion, may delegate approval authority to MXG Squadron Commanders. **(T-3)**

2.4.2.33. Coordinate with the OG/CC or WG/CC to develop procedures to ensure pilots and aircrew members account for all equipment and personal items after each flight and ensure any items that become lost during flight are documented in the aircraft AFTO Form 781A. **(T-3)**

2.4.2.34. Approve CANN Authorities (CA). **(T-3)**

2.4.2.35. Designate qualified TSgts or higher, civilian equivalent, fully qualified/certified contractors, or AFETS/CETS personnel to serve as engine run certifying officials IAW criteria established in **Table 11.1**. **(T-3)**

2.4.2.36. Select maintenance, TD, or AFETS/CETS personnel as instructors, and ensure instructors maintain blade blending proficiency and certification requirements. **(T-3)**

2.4.2.37. Approve and track Hot Pit certifying officials on the SCR. **(T-3)**

2.4.2.38. Ensure CDDAR mobility UTC equipment requirements are available to deploy and accounted for on an AS (if applicable). **(T-3)**

2.4.2.38.1. Coordinate functional and emergency action checklist with Fire Emergency Services, Wing Safety, and the Airfield Operations Flight in developing adverse weather procedures for protecting aircraft and equipment IAW DAFMAN 91-203, DAFI 10-2501, *Air Force Emergency Management Program*, and MDS-specific technical data. **(T-3)**

2.4.2.38.2. In coordination with the MSG/CC, determine unit vehicle/equipment requirements beyond those authorized in the AS(s) to provide 24/7 CDDAR response/runway clearing capability. **(T-3)** Units must identify vehicles and SE designated to support CDDAR recovery in a local publication to ensure 24-hour availability. **(T-3)**

2.4.2.38.3. Ensure as a minimum, units with a CDDAR requirement possess sufficient equipment to accomplish a recovery of the assigned MDS aircraft. **(T-3)**

2.4.2.38.4. Establish an IFE response capability. **(T-3)**

2.4.2.38.5. Participate in CDDAR training exercises. **(T-3)**

2.4.2.38.6. Manage CDDAR equipment to minimize duplication of resources. **(T-3)**

2.4.2.38.7. Ensure an annual CDDAR equipment inventory is completed and an inventory report containing DPAS Property Accountability (PA) inventory of CDDAR equipment that indicates excess, or shortage items is completed, signed by MXG/CC or equivalent, and sent to the MAJCOM CDDAR OPR, NLT 30 Sep. **(T-3)**

2.4.2.39. Ensure EM is the wing focal point for both the ET&D, Engine Health Management (EHM+) and Condition Based Maintenance Plus (CBM+) program when applicable. **(T-3)**

2.4.2.40. Review and approve the assessment of the wing's ability to execute the FHP, in coordination with the OG/CC, prior to submission to the WG/CC. **(T-3)**

2.4.2.41. Review first look packages before being presented to the WG/CC. **(T-3)**

2.4.2.42. Formalize the next month's flying and maintenance plan prior to presenting it to the WG/CC for approval NLT the third scheduling meeting of the preceding month. **(T-3)**

2.4.2.43. Review the weekly, monthly, quarterly, annual flying or test schedules IAW **Chapter 5** and **Chapter 14**. **(T-3)**

2.4.2.44. Ensure effective management of the Engine Trending and Diagnostic (ET&D) program IAW AFMAN 20-116, *Propulsion Life Cycle Management for Aerial Vehicles*.

2.4.2.45. Focus unit MSEPs on problem areas where improvements are needed. **(T-3)**

2.4.2.46. Ensure maintenance actions for Ground Instructional Training Aircraft (GITA)/Training Aircraft Aids (TAA) are documented IAW TO 00-20-1.

2.4.2.47. Ensure repair cost evaluations are performed and appropriate levels of review and repair authorization are established in squadrons, flights, and repair sections IAW TO 00-20-3, *Maintenance Processing of Repairable Property and The Repair Cycle Asset Control System*, TO 00-25-240, *Uniform Repair/Replacement Criteria for Selected USAF Support Equipment* (SE), and TO 35-1-24, *Air Force Economic Repair/Replacement Criteria For Selected Warner Robins Logistics Complex* (ALC) *Managed Support Equipment* (SE).

2.4.2.48. Collaborate with the WG/CC and forward a recommendation to the MAJCOM if an initial OTI sampling indicates the discrepancy is widespread and has the potential for personal injury and/or further equipment damage. **(T-3)**

2.4.2.49. Approve requests for assistance IAW **Chapter 1** after they are coordinated with Plans, Scheduling, and Documentation (PS&D), Quality Assurance (QA), and all applicable maintenance organizations. **(T-3)**

2.4.2.50. Appoint a Wing Corrosion Manager (2A7X3, 2A7X5) to implement local requirements, ensure implementation of MAJCOM directed requirements and act as the focal point for communicating with external stakeholders. **(T-3)**

2.4.2.50.1. **(Added-AFGSC) [DEV]** The 95 WG Quality Assurance Superintendent/Chief Inspector will be appointed as Group Corrosion Control Managers (no AFSC restrictions) for E-4 maintenance operations assigned to the 95 WG at Offutt AFB.

2.4.2.50.2. **(Added-AFGSC)** Wing Corrosion Manager will be appointed in writing.

2.4.2.51. Be the approval authority for cannibalization of egress explosive components and/or seats to ensure system integrity and validation of explosive CAD/PAD listing. **(T-3)**

2.4.2.52. Establish a Memorandum of Understanding (MOU) for organizational level Maintenance Interoperability or Aircraft Cross-servicing with joint forces or partner nations, if requested. See DAFI 25-301, *Aircraft Cross-Servicing Agreements*, for further guidance.

2.4.2.53. If applicable, establish a Primary, Alternate, Contingency, and Emergency (PACE) plan(s) to conduct operations in a contested, degraded, or operationally limited environment. (T-3) Note: Use AFTTP 3-4.21V1, *Aircraft Maintenance*, Attachment 10, *Contested, Degraded, and Operationally Limited Operations*, as a guide for development of PACE plan and AFI 90-802, *Risk Management*.

2.4.2.54. **(Added-AFGSC)** Ensure the on-time submission of monthly Executive Reports to HQ AFGSC/A4, see **Attachment 16**.

2.4.3. The MXG/CC will:

2.4.3.1. Approve and publish In Process Inspection (IPI) listings every two years IAW **Chapter 6. (T-3)**

2.4.3.2. Approve MXG Key Task List (KTL) and Routine Inspection Lists (RIL). **(T-3)**

2.4.3.3. Implement MAJCOM Lead the Fleet (Pacer) Program for engine type IAW AFMAN 20-116. **(T-2)**

2.4.3.4. Ensure aircraft possessed by AFMC for depot maintenance are not cannibalized without coordination through the MAJCOM functional manager who will then request approval from the applicable Air Logistics Complex (ALC) Maintenance Group Commander/Director and Program Manager. **(T-2)**

2.4.3.5. Establish local procedures for management and maintenance of assigned GITA and TAA to ensure they remain useful and safe within guidelines stated in **Chapter 11**, AFI 84-103, *Department of the Air Force Heritage Program*, DAFI 21-103, and 23-series publications. **(T-3)**

2.4.3.6. Appoint a Wing Avionics Manager (WAM) or designated representative to act as the maintenance focal point for wing avionics related programs. **(T-3) Note:** See **Chapter 11** for WAM responsibilities.

2.4.3.7. Determine the Routine Inspection List (RIL) frequency if not mandated by the MAJCOM. **(T-3)**

2.4.3.7.1. Approve Maintenance Supervision inputs and suggested changes to the RIL submitted from QA. **(T-3)**

2.4.3.7.2. Approve the Evaluation and Inspection (E&I) Plan. **(T-3)**

2.4.3.7.3. Establish AQLs for tasks/inspections not included on the MAJCOM AQL listing. **(T-3)**

2.4.3.7.4. Establish quarterly meetings to review a summary of MSEP data. **(T-3)**

2.4.3.8. Oversee GITA/TAA IAW **Chapter 11**. **(T-2)**

2.4.3.8.1. Develop an installation publication or supplement to define the scope of training functions for GITA/TAA use, functional responsibility for funding, operations, maintenance, and records management. **(T-3)**

2.4.3.8.2. Ensure maintenance support of GITA/TAA used for training. **(T-3)** Units that do not have organic maintenance capability will establish a Support Agreement or MOA assigning maintenance responsibility for GITA/TAA training use. **(T-3)**

2.4.3.8.3. Ensure explosive components are removed that are not required to support training requirements.

2.4.3.8.4. Place retained systems and subsystems not currently being used for training into extended storage IAW applicable technical data.

2.4.3.8.5. Ensure standard maintenance practices regarding inspection appearance, cleanliness, ground safety, and prevention of corrosion are met. Corrosion control procedures are outlined in TO 1-1-691.

2.4.3.8.6. Develop and prepare inspection technical data check lists for use in inspecting the condition and safety of equipment before use and ensure inspections are performed. **(T-3)**

2.4.3.8.7. Prepare a separate memorandum for each GITA/TAA, addressed to the appropriate PM for the aircraft and inform them of the systems and subsystems that will be maintained in operational configuration. **(T-3)**

2.4.3.8.8. Report air and space vehicle inventory IAW DAFI 21-103 as required for ground trainers. Aircraft used for ground trainers are exempt from status and utilization reporting.

2.4.3.8.9. Ensure proper coordination and documentation of parts removed from training aircraft are accomplished.

2.4.3.8.10. Designate a GITA/TAA Manager as an additional duty. **(T-3)**

2.4.3.9. Ensure all items being repaired by AFREP have been approved by the appropriate repair authority. **(T-3)**

2.4.3.9.1. Assign an AFREP Manager. **(T-3)**

2.4.3.10. Chair a maintenance and FHP planning meeting quarterly, NLT 14 days before the next quarter. **(T-3)**

2.4.3.11. Establish Minimum Equipment Levels (MELs) for essential maintenance assets to include engines, pods, AGE, vehicles, advocate and reconcile authorized shortfalls and overages. **(T-2)** Coordinate with the applicable MAJCOM functional to advocate with the respective Program Manager to address any requests to change authorized quantities. **(T-3)**

2.4.3.11. **(AFGSC)** Designate mission-critical equipment for aircraft generation, outlining reporting, mitigation procedures, and applicable MELs. Conduct monthly serviceability and repair status reviews. The MXG will incorporate all equipment essential for home station and mobility mission success.

2.4.3.11.1. **(Added-AFGSC)** Send copy of serviceability and repair status monthly to A4MA workflow, **AFGSC.A4M.Workflow@us.af.mil**, by the last duty day of the month.

2.4.3.12. Establish the group maintenance awards and recognition program to meet AF and MAJCOM requirements refer to **https://access.afpc.af.mil/Trophies/searchtrophies.aspx**. **(T-3)**

2.4.3.13. Ensure an orientation program is developed and conducted for all personnel newly assigned to MXG maintenance or equivalent maintenance activities IAW AFI 36-2650.

2.4.3.14. Develop a MXG Impoundment Program and ensure compliance with the procedures IAW **Chapter 7**. **(T-3)**

2.4.3.15. Establish written procedures to review and clear “repeat”, “recur”, and “cannot duplicate” (CND) discrepancies. **(T-3)**

2.4.3.16. Approve the Dedicated Crew Chief (DCC) program, when implemented.

2.4.3.17. Review and coordinate the AGE MEL annually with applicable Maintenance Supervision. **(T-3)** The MXG/CC approves the identified types and quantities of AGE for the MEL.

2.4.3.18. Develop and implement a standardized Impound Official training course and Impoundment Program. **(T-3)**

2.4.3.19. Appoint an Identification Friend or Foe Program Manager for Identification Friend or Foe systems cryptographically keyed by MXG personnel. **(T-3)**

2.4.3.20. Appoint a Radar Warning Receiver/Radar Threat Warning Manager (if equipped as required). **(T-3)**

2.4.3.21. Develop a 10-year facility plan specifying maintenance, upgrade, and replacement projections for the group’s facilities. **(T-3)**

2.4.3.22. Ensure aircraft shelters at bases are maintained, unless otherwise stipulated in contracting arrangements, IAW **Chapter 11**. **(T-2) Note:** If an aircraft shelter is used for other than its designed purpose, the using activity will maintain it.

2.4.3.23. Establish and document MXG local manufacture procedures and controls in a supplement to this instruction. **(T-3)**

2.4.3.24. Appoint a Stock Record Account Number (SRAN) Engine Manager (EM) or a Unit Engine Manager (UEM) to accomplish duties outlined in TO 00-25-254-1, *Comprehensive Engine Management System* (CEMS) (D042) *Engine Status, Configuration, and TCTO Reporting Procedures*.

2.4.3.25. Establish written guidance on individual responsibilities and specific procedures for Cannibalization (CANN) actions IAW **Chapter 11**. **(T-3)**

2.4.3.26. Publish directives outlining procedures covering the manufacture of items source coded local manufacture. **(T-3)**

2.4.3.27. Ensure the MT develops and manages an effective engine run certification program. **(T-3)**

2.4.3.28. For calibration limitation Approval Certification Program, appoint maintenance, TD, or PMEL personnel as instructors, and ensure requisite certification and proficiency requirements are tracked in the MIS by course code.

2.4.3.29. For engine management, appoint a qualified 2A6X1, minimum 7-skill level, (or civilian equivalent) technician to manage the EHM+ and CBM+ program IAW AFMAN 20-116 for EHM products managed by AFLCMC/LP. If EHM data is not managed by AFLCMC/LP, ensure Contractor Logistics Support (CLS) provided EHM products are managed according to respective contract.

2.4.3.30. Ensure the Aero Club is operated IAW DAFI 34-101, *Department of the Air Force Morale, Welfare, and Recreation (MWR) Programs and Use Eligibility*, when assigned.

2.4.3.31. **(Added-AFGSC)** Ensure Maintenance Operations Center develops procedures to ensure Geographical Location (GEOLOC) codes for on/off station possessed aircraft are updated/correct in MIS location subsystem.

2.4.3.32. **(Added-AFGSC)** Conduct an "MXG Standup" meeting. The MXG/CC will determine the meeting topics and the required attendees. Daily meetings are highly encouraged; however, MXG/CC may determine meeting frequency.

2.4.3.33. **(Added-AFGSC)** Ensure Hangar Door Program processes and procedures are complied with as outlined in **paragraph 11.44**.

2.4.3.34. **(Added-AFGSC)** The MXG/CC or equivalent is the certifying official for unit-level welding examinations. This responsibility may be delegated IAW TO 00-25-252, *Aeronautical Equipment Welding*.

2.4.3.35. **(Added-AFGSC)** Establish selection requirements for personnel to be assigned to the QA Section (e.g., rank, skill level, time on airframe, etc.) and ensure QA evaluators are on a 24–36-month rotation cycle.

2.4.3.36. **(Added-AFGSC)** Establish minimum Time on Station and MDS experience requirements for personnel to be selected for QA positions.

2.4.3.37. **(Added-AFGSC) [Aircraft Units]** Ensure standardized training is provided to all maintenance personnel in nuclear operations in the vicinity of a Tamper Detection Indicator (TDI). The training course documents will be maintained by AFGSC/A4MA Functional Area Managers and taught by the local Maintenance Training. The course may be included in Block Training and Mission Orientation.

2.4.3.38. **(Added-AFGSC) [Aircraft Units]** Ensure all 2AX personnel assigned to nuclear units receive initial and annual standardized Sole Vouching Authority (SVA) training. AFGSC/A4 FMs maintain the training course requirements. While local Maintenance Training personnel can download materials to facilitate offline instruction if needed, the preferred delivery method is through MyLearning. Individuals that will be performing SVA duties will be added to the SCR utilizing an AFGSC Form 64, *Request for Special Certification*.

2.4.3.39. **(Added-AFGSC)** Ensure CBM+ is managed to replace components within time change thresholds IAW **paragraph 11.41**. MXG/CC has the authority to waive thresholds due to supply constraints.

2.4.3.40. **(Added-AFGSC)** Units selected to participate in CBM+ program, designated work center responsible for CBM+ management of all CBM+ maintenance activities IAW **paragraph 11.41**.

2.4.3.41. **(Added-AFGSC)** The MXG/CC or equivalent will ensure that assigned personnel are using an AFGSC MRM Assessment while performing elevated risk maintenance tasks or when existing conditions may elevate any task risk conditions.

2.4.4. - 2.4.58. DELETED.

2.5. Deputy Maintenance Group Commander (MXG/CD). In organizational structures where an MXG/CC or MXG/CD is not assigned, (i.e., AFORGEN deployed construct), **paragraph 2.5.1** will move up to the WG/CC commander to ensure effective communication across all units.

2.5.1. Establish maintenance production/scheduling meeting. **(T-3)** This meeting is to verify aircraft and equipment utilization, scheduled maintenance requirements, evaluate predictive maintenance forecast, establish work priorities, and coordinate schedule changes. It should synchronize communications necessary to optimize fleet readiness and mission generation capability.

2.5.1.1. -2.5.13. DELETED.

2.6. MXG Senior Enlisted Leader (SEL) Responsibilities. In addition to the Group SEL responsibilities outlined in Brown Book, *The Enlisted Force Structure*, the MXG SEL is responsible to the MXG/CC and will advise and assist the MXG/CC on their responsibilities as outlined in this **Chapter**. In organizational structures where an MXG is not assigned (i.e., AFORGEN deployed construct), the following responsibilities will remain with the home unit's SEL and any guidance/documentation necessary to support the deployed operation will be brought with the unit. The MXG SEL will:

2.6.1. Conduct a quarterly manning meeting with Squadron SELs and Wing Weapons Manager (WWM) to review MXG manning status, Duty Title Tool usage, and ensure manning resources are strategically distributed to provide the greatest possibility for mission success.

(T-3) The MXG SEL is the focal point for ensuring squadron SELs receive adequate manpower management training.

2.6.1.1. Meeting will consist of a review and evaluation of the impact on the MXG of personnel actions such as: work center/organizational manpower Authorization Change Requests (ACR), AFSC changes, re-training, special duty requests, special assignment actions (SWAP, Palace Chase), SEI balance, overseas Date Eligible for Return from Overseas extensions/In Place Consecutive Overseas Tour (IPCOT) requests, physical profile changes and personnel rotation plans as applicable to enhance mission effectiveness. **(T-3)**

2.6.1.2. MXG SEL will provide the MXG/CC coordinated manning recommendations that develop enlisted individual experience and knowledge for consideration. **(T-3)**

2.6.1.2.1. **(Added-AFGSC)** The MXG SEL will approve the selection of maintenance instructors.

2.6.2. Ensure all AFSC 2A and 2W maintenance personnel are only assigned authorized duty titles. **(T-3)** Reference the Duty Title Tool: **https://usaf.dps.mil/teams/10820/medac/2A_DTT/SitePages/Home.aspx**, and the AFSC 2W1 Standardized Duty Titles located at **https://usaf.dps.mil/teams/11262/HAF/HAF-A4LW/Standardized%20Duty%20Titles** for all assigned AFSC 2W1X1 and 2W100 positions.

2.6.2. **(AFGSC)** Review duty titles quarterly to ensure compliance and standardization.

2.6.3. **(Added-AFGSC)** Establish time frames for senior enlisted personnel to attend AFGSC Maintenance Supervision and Production Course (MSPC).

2.7. Wing Weapons Manager. See AFMAN 21-206 for duties and responsibilities.

2.7.1. - 2.7.28. DELETED.

2.8. Squadron Commander (SQ/CC) Responsibilities. The SQ/CC will:

2.8.1. Ensure compliance with AFI 90-821, DAFI 91-202, *The US Air Force Mishap Prevention Program*, DAFMAN 91-203 and other publications necessary to perform the commander functions assigned to the squadron.

2.8.2. Establish and administer squadron training programs IAW AFI 36-2650 and DAFMAN 36-2689, *Training Program*; monitor upgrade training, Personnel Reliability Program (PRP) status, and qualifications of assigned work center personnel; and ensure MAJCOM Mandatory Course List requirements are met (if applicable). **(T-3)**

2.8.3. Ensure upgrade training and maintenance qualification programs emphasize quality and are not primarily focused on meeting minimum upgrade time frames. **(T-3)**

2.8.3.1. Ensure all maintenance personnel who utilize DoD Information Technology have received appropriate Maintenance Cyber Discipline Training. **(T-3)**

2.8.4. Monitor all personnel working outside of their primary AFSC to ensure that it does not degrade mission accomplishment. **(T-3)**

2.8.5. Establish a squadron Vehicle Control Program IAW AFI 24-302, *Vehicle Management*.

2.8.6. Establish and manage squadron FCC program IAW **Chapter 11** (if applicable).

2.8.7. Protect and secure munitions as outlined in DAFI 31-101. The SQ/CC will ensure Intrusion Detection Systems requirements are identified when required to store munitions IAW DoDM 5100.76 and DAFI 31-101.

2.8.8. Appoint equipment custodians to manage the Custodian Authorization/Custody Receipt Listing (CA/CRL) (R14) of assigned equipment IAW AFI 23-101 and DAFMAN 23-122, *Materiel Management Procedures*.

2.8.8.1. **(Added-AFGSC)** Provide unit level readiness leadership POC's (Support Flight Chief, Unit Deployment Managers, and Equipment Custodian's) to AFGSC A4M at org box **AFGSC.A4M.Workflow@us.af.mil** on a bi-annual basis or when a new Commander takes command.

2.8.9. Ensure personnel and equipment are identified and prepared to deploy for taskings IAW AFI 23-101, AFI 10-403, *Deployment Planning and Execution*, DAFI 36-3802, *Force Support Readiness Programs*, and AFMAN 10-409-O, *Support to Adaptive Planning*.

2.8.10. Recommend personnel for QA duty positions. **(T-3)**

2.8.11. Designate Flight CC/Chiefs. **(T-3)**

2.8.12. Ensure the UMD is consistent with the approved organizational structure. **(T-3)**

2.8.13. Coordinate support from the local communication squadron or equivalent functional entity to ensure proper eTools configuration (operating system, virus checkers) are maintained. **(T-3)** The SQ/CC will coordinate with lead TODO/Functional System Administrator to resolve TO requirements that are not being satisfied. **(T-3)**

2.8.13.1. Ensure licenses, certification, maintenance, and security of eTools (hardware and software) is conducted IAW 33/17-series AFIs, TO 31S5-4-ETOOL-1, and **Chapter 8**.

2.8.14. Ensure members assigned to the DIT are qualified to accurately assess the Maintenance Data Documentation. **(T-3)**

2.8.15. Ensure maintenance is only performed by personnel who are trained, qualified, and certified, unless under the direct supervision of a trainer or certifier. **(T-3)**

2.8.16. Ensure procedures are followed to properly turn in recoverable and consumable items IAW AFI 23-101. **(T-3)**

2.8.17. **(Added-AFGSC)** Ensure all personnel, prior to entering a No-Lone Zone, receive a pre-task/safety brief or visitors brief, to include nuclear surety, IAW DAFI 91-101, *Air Force Nuclear Weapons Surety Program*.

2.9. Maintenance Supervision Responsibilities. Maintenance Supervision consists of the Director of Operations (DO) and Maintenance Superintendent (MX SUPT). Maintenance Supervision advises the SQ/CC on technical matters, leads a mission-focused maintenance effort, and manages resources necessary to accomplish the mission. They provide necessary administration to manage assigned responsibilities and control maintenance through Pro Supers, Flight CC/SUPT, and Section NCOICs/Chiefs. The MX SUPT is responsible to the DO. Maintenance Supervision will:

2.9. (AFGSC) Maintenance Supervision Responsibilities. Ensure Production Superintendent (Pro Super) attends the Global Strike Command MSPC prior to, but no later than six months after assuming Production Superintendent responsibilities. Expediters and Section Chiefs are encouraged to attend. Personnel who attended another MAJCOM's MSPC are not required to attend the Global Strike Command specific course. Attendance costs will be covered by unit funds.

2.9.1. Ensure adequate levels of supervision and manning are balanced across all shifts to accomplish the mission safely and efficiently. **(T-3)**

2.9.2. Ensure timely and accurate engine data is provided to the EM element for all engines IAW **Chapter 14**. **(T-3)**

2.9.3. Enforce procedures to prevent FOD and dropped objects IAW **Chapter 11**. **(T-3)**

2.9.4. Monitor and recommend updates to local IPI requirements and recommendations to QA IAW **Chapter 6**. **(T-3)**

2.9.5. Ensure a sufficient number of personnel are qualified to perform mission critical tasks listed on the SCR **Table 11.1** in **Chapter 11**. **(T-3)** Review and/or recommend individuals for addition to the SCR. **(T-3)** Approve individuals for addition to the SCR. **(T-3)** Review and approve individuals for addition to the SCR. **(T-3)**

2.9.6. Ensure aircraft systems and equipment are available to support unit training objectives. **(T-3)**

2.9.7. Ensure distribution of maintenance cross-tell messages, QA newsletters, policy announcements, technical notifications, and other important maintenance information to all members of the organization. **(T-3)**

2.9.8. Review and evaluate management and production effectiveness. **(T-3)** Maintenance Supervision will analyze personnel and equipment performance history. **(T-3)** Initiate management actions to meet new workloads or correct reported/perceived deficiencies. **(T-3)**

2.9.9. Ensure an annual maintenance plan is developed and reconciled with the flying schedule and flying requirements to ensure maintenance can support the annual flying hour/test program. **(T-3)**

2.9.9.1. Participate in the maintenance planning cycle. **(T-3)**

2.9.9.2. Utilize a sortie production model or equivalent for the assigned MDS (if available). **(T-2)**

2.9.10. Ensure a squadron SERENE BYTE or PACER WARE response capability is available to support reprogramming requirements IAW DAFMAN 10-703, *Electromagnetic Warfare Integrated Reprogramming* (if applicable).

2.9.11. Ensure a squadron Corrosion Control Program is implemented and managed IAW TO 1-1-8, TO 35-1-3, TO 1-1-691, MDS-specific TOs and MAJCOM instructions.

2.9.12. Ensure squadron ASIP responsibilities are accomplished IAW **Chapter 11** and DAFI 63-140.

2.9.13. Develop written procedures in coordination with the WWM, Weapons Safety Manager, and Airfield Management to establish EOR inspection procedures as required by aircraft specific -6 TO, MAJCOM directed requirements and **Chapter 11**.

2.9.13.1. Ensures sufficient personnel, equipment, and facilities are assigned, maintained, and available to properly perform EOR inspections IAW **Chapter 11**.

2.9.13.2. Ensure EOR procedures for transient aircraft are developed IAW TO 00-20-1 and MAJCOM directives.

2.9.14. Review and support the monthly Weapons Load Training (WLT) schedule. **(T-3)**

2.9.14. **(AFGSC)** Coordinate with Weapons Standardization Superintendent to ensure sufficient training aircraft are provided to support Weapons Load Crew training program.

2.9.15. Ensure deferred maintenance, Pilot Reported Discrepancy, and back-ordered parts are properly managed. **(T-3)**

2.9.16. Review supply products to monitor supply discipline. **(T-3)**

2.9.16.1. Maintenance Supervision will manage DIFMs IAW AFI 23-101. **(T-3)**

2.9.16.2. Monitor and reconcile changes in base-level repair capabilities under their supervision as they occur with the LRS/Material Management activities IAW AFI 23-101.

2.9.17. Ensure lost, damaged, destroyed, or stolen government assets are dispositioned IAW DoD 7000.14-R, *DoD Financial Management Regulation*, Vol 12, **Chapter 7**, Financial Liability for Government Property Lost, Damaged or Destroyed (Formerly Report of Survey).

2.9.18. Ensure Special Purpose Recoverable Authorized Maintenance (SPRAM) accounts are established IAW DAFI 21-103, **Chapter 9**, and maintained IAW AFI 23-101.

2.9.19. Ensure reporting of materiel deficiencies IAW TO 00-35D-54, *USAF-Deficiency Reporting, Investigating, and Resolution*.

2.9.20. Monitor requirements for CTK, special tools, and SE and take necessary action to ensure availability, as required IAW **Chapter 8**.

2.9.21. **(Added-AFGSC)** Review monthly maintenance plan inputs and forward to MXO PS&D for publication.

2.9.22. **(Added-AFGSC)** Review Unit Manning Document (UMD) manpower authorizations, changes to authorizations, and Functional Activity Codes (FACs) and work center alignment. **Note:** All FACs may not be identified in the organizational chart as they appear on the UMD. Organizational charts reflect AFI 38-101, *Manpower and Organization,* requirements, and some sub-functional areas (below flight level) may not be depicted.

2.9.23. **(Added-AFGSC)** Maintain current listing of certified Egress Augmentees and ensure it is available to expediters. Notify MXS Production when violations are detected.

2.10. Flight Supervision. Flight Supervision consists of the Aircraft Maintenance Unit (AMU) Officer in Charge (OIC)/Superintendent and Flight Commander/Flight Superintendent (Flight CC/Chief). Flight Supervision will:

2.10.1. Provide management and oversight and ensure each section is adequately resourced to efficiently execute their mission. **(T-3)**

2.10.2. Manage, distribute, and adjust the flight's manning to support the maintenance plan across all shifts. **(T-3)**

2.10.2.1. Distribute all levels of supervision based on manning and workload to supervise all duty periods. **(T-3)**

2.10.2.2. Identify imbalances between authorizations and the number of personnel assigned, or between authorized and assigned skill levels or grades to SQ/CC and Maintenance Supervision. **(T-3)**

2.10.2.2.1. Review unit DOC Statements, OPLANs, unit-tasked UTC requirements for personnel and equipment then compare requirements to UMD to identify existing shortfalls. Scrutinize critical AFSCs qualifications and equipment based on their impact on mission generation. Document and report personal and equipment deficiencies through the chain of command and monitor until resolved. **(T-3)**

2.10.2.3. Manage additional duties, leaves, ancillary training, and rotate/assign manning across shifts to balance the workload and minimize negative impacts on the workforce. **(T-3)**

2.10.3. Execute the squadron's Mishap Prevention Program for the flight/work center IAW **Chapter 1** and DAFI 91-202.

2.10.3.1. Ensure all personnel obtain the required safety training, and document it on the AF Form 55, Employee Safety and Health Record, or equivalent IAW DAFI 91-202.

2.10.4. Coordinate occupational and environmental health risk assessments with Bioenvironmental Engineering IAW AFMAN 48-146, *Occupational & Environmental Health Program Management*, to identify, assess and evaluate process hazards in the workplace and identify controls. **(T-3)**

2.10.4.1. Monitor and ensure environmental and applicable health requirements, physicals and respirator training, initial and recurring requirements are accomplished when required for assigned personnel IAW AFMAN 48-146; AFI 48-137, *Respiratory Protection Program*; and AFI 48-127, *Occupational Noise and Hearing Conservation Program.*

2.10.5. Ensure organizational compliance IAW the installation ESOHMS/EMS Program. **(T-3)**

2.10.6. Advocate use of the TO improvement program and ensure work center TO files are maintained IAW TO 00-5-1.

2.10.7. Ensure Materiel Potentially Presenting an Explosive Hazard requirements in DAFMAN 21-201 and TO 11A-1-60, *General Instructions Inspection of Reusable Munitions Containers and Scrap Material* Generated from Items Exposed to or Containing Explosives, are complied with when certifying items associated with explosives such as: Multiple Ejector Rack, Triple Ejector Rack, pylons, launchers, rafts, bomb racks, ejection seats, fire suppression bottles, and gun systems and components.

2.10.7.1. Ensure associated items are explosive free prior to being turned in to LRS or the Defense Logistics Agency Disposition Services (DLADS).

2.10.8. Review deferred maintenance in the MIS and coordinate with the Pro Super to schedule and/or validate task accomplishment. **(T-3)**

2.10.9. Ensure operator inspections and user servicing requirements are accomplished on all assigned support equipment IAW TO 00-20-1.

2.10.10. Ensure records of inspection, lubrication, and maintenance of industrial equipment are maintained IAW TO 00-20-1, TO 34-1-3, *Machinery and Shop Equipment*, to include documentation of records maintained in a MIS.

2.10.11. Ensure proper calibration, use, care, handling and transportation of Test Measurement and Diagnostic Equipment (TMDE) IAW TO 00-20-14 and AFMAN 21-113, *Air Force Metrology and Calibration (AFMETCAL) Program Management*, and applicable Calibration Measurement Summaries.

2.10.12. Evaluate maintenance quality, personnel qualifications, and training of assigned personnel. **(T-3)**

2.10.13. Review/update flight IPI requirements listing every two years and route through Maintenance Supervision. **(T-3)**

2.10.14. Ensure only designated personnel identified in the MIS verify MICAPs/Urgency of Need Designator 1A and JA requirements. **(T-3)**

2.10.15. Select personnel to perform special certification tasks IAW **Chapter 11** and **Table 11.1** and forward names to Maintenance Supervision for approval and addition to the SCR. **(T-3)**

2.10.16. Ensure training requirements are executed to support established training plan and individual AFSC Career Field Education and Training Plans (CFETP) IAW DAFMAN 36-2689and AFI 36-2650.

2.10.17. Ensure Cross Utilization Training requirements are identified as required by the unit mission IAW AFI 36-2650.

2.10.17.1. Ensure Cross Utilization Training does not interfere with upgrade/qualification training. **(T-3)**

2.10.18. Review Maintenance Management Analysis (MMA), QA, and other management reports to determine appropriate management actions to meet new workloads, target deficiencies, and identify and correct root causes. **(T-3)**

2.10.19. Develops maintenance and flying schedules and execute scheduled maintenance plans. **(T-3)**

2.10.20. Establish flight/AMU-specific emergency action procedures to respond to disaster control and severe weather and forward to MOC. **(T-3)**

2.10.20.1. Review unit responsibilities pertaining to aircraft/SE movement and personnel evacuation IAW DAFI 10-2501. **(T-3)**

2.10.21. Manage the flight/AMU's participation in the FOD and DOP program IAW **Chapter 11**.

2.10.22. Oversee the flight/AMU's FCC/Dedicated Crew Chief (DCC) Program (if applicable). **(T-3)**

2.10.23. Establish and enforce a flight/AMU Precious Metals Recovery Program, as applicable, IAW AFI 23-101 and TO 00-25-113, *Conservation and Segregation of Critical Alloy and Precious Metal Bearing Parts and Scrap*.

2.10.24. Assign section supervisors IAW this instruction and the UMD. **(T-3)**

2.10.25. Ensure proper asset management by reviewing MIS data records, the Repair Cycle Asset Management Listing (D23) and other pertinent products to minimize shortfalls. **(T-3)**

2.10.25.1. When applicable, ensure warranty items are loaded in MIS according to applicable directives. **(T-3)**

2.10.25.2. Ensure Deficiency Reports (DR) are accomplished IAW TO 00-35D-54.

2.10.26. Ensure repairable/non-repairable parts are promptly processed through repair channels within the required time frame IAW AFI 23-101.

2.10.26.1. Team with Decentralized Materiel Support (DMS) Flight Service Center to conduct a quarterly reconciliation of all DIFM assets and follow up on delinquent DIFMs and document action taken to correct identified discrepancies. **(T-3)**

2.10.26.2. Immediately identify lost, damaged, destroyed, or stolen assets that require a financial liability investigation IAW DoD 7000.14-R, Vol 12, **Chapter 7**, *Financial Liability for Government Property Lost, Damaged or Destroyed* (Formerly Report of Survey) and forward to Maintenance Supervision for review and processing. **(T-3)**

2.10.27. Approve requirements for bench stocks IAW qualification criteria in DAFMAN 23-122. **(T-3)**

2.10.28. Consolidate lists of items received in supply requiring functional check, operational programming, user calibration or corrosion control/painting. **(T-3)**

2.10.28.1. Submit listing to the LRS Materiel Management Flight IAW TO 00-20-3. **Note:** Does not include TMDE IAW TO 00-20-14.

2.10.29. Coordinate all AGE requirements through the AGE Flight Chief to ensure support capability and eliminate unnecessary duplication of equipment. **(T-3)**

2.10.30. Report cyber threats, incidents, and issues per Wing cyber status reporting procedures. **(T-3)**

2.10.30.1. Consult airframe Security Classification Guides, TOs, and/or applicable technical manuals, instruction and publication when addressing or reporting cybersecurity threats, incidents, and issues. **(T-3)**

2.10.31. Ensure Nuclear Weapons-Related Materiel (NWRM) is controlled IAW AFI 20-110.

2.11. Production Superintendent (Pro Super). Senior NCO responsible for squadron maintenance production. The Pro Super directs the overall maintenance effort of their unit. The Pro Super will be a SNCO or civilian equivalent. **(T-3)** Squadron specific Pro Super responsibilities are outlined in their respective chapters of this DAFI.

2.12. Section NCOIC/Chief. The Section NCOIC/Chief is responsible to the Flight CC/SUPT or AMU OIC/SUPT for the leadership, supervision, and training of assigned personnel. The Section NCOIC/Chief is a first-line manager and supervisor of maintenance production and is the technical authority and advisor in that area. When sections are subdivided, element leaders perform the appropriate functional responsibilities. The Section NCOIC/Chief will:

2.12.1. Establish a Work Center Safety Program IAW DAFI 91-202, DAFMAN 91-203, and include any locally prescribed safety requirements (if applicable).

2.12.2. Monitor, track, and ensure occupational safety, fire prevention, and occupational and environmental health requirements are accomplished for assigned personnel IAW DAFMAN 91-203.

2.12.2.1. Ensure Job Safety Training is documented IAW DAFI 91-202, (AF Form 55 or equivalent) for each assigned individual.

2.12.3. Ensure maintenance is performed by personnel who are trained, qualified, and certified, unless under the direct supervision of a trainer or certifier. **(T-3)**

2.12.4. Advocate use of the TO improvement program and ensure work center TO files are maintained according to TO 00-5-1. **(T-3)**

2.12.5. Establish procedures and ensure configuration control for all applicable software required for the sections assigned systems. **(T-3)** Section NCOIC/Chief will:

2.12.5.1. Access Computer Program Identification Number System (CPINS) in ETIMS or equivalent system. **(T-3)**

2.12.5.2. Ensure technicians check ETIMS/equivalent system for software updates for assigned systems. **(T-3)**

2.12.5.3. Ensure software configuration control is maintained IAW TO 00-5-16, *Management of Computer Program Identification Number System (CPINS)* and equivalent systems are maintained by use of AF approved and authorized publications.

2.12.6. Perform production and supervisory inspections. **(T-3)**

2.12.7. Validate classified parts/materiel are managed IAW AFI 23-101. **(T-3)**

2.12.8. On a daily basis review, monitor, and correct, as needed, the work center's scheduled and deferred events in the MIS. **(T-3)**

2.12.8.1. Close, reschedule, or defer all events beyond their scheduled start date and time (Integrated Maintenance Data System (IMDS)-CDB screen #100/380 and Field Maintenance Command and Control (FMxC2) Screen #8035/8069/67150). **(T-3) Note:** G081 was renamed to FMxC2 August 2022.

2.12.9. Review transcribed AFTO Form 781-series forms, work center MIS data entries for the previous day, and all preceding non-duty days, for job accuracy and completeness (IMDS-CDB Screen #100 and FMxC2 Screen #9154). **(T-3)**

2.12.10. Validate scheduled aircraft document reviews using applicable MIS/records check package and automated aircraft forms IAW **Chapter 14**.

2.12.11. Develop and manage the Work Center Training Program. **(T-3)**

2.12.11.1. Evaluate the quality of maintenance, training, and personnel qualifications, track training requirements and ensure training documentation is complete and accurate. **(T-3)**

2.12.11.2. Conduct On-the-Job training (OJT)/certifying as required. **(T-3)**

2.12.11.3. **(Added-AFGSC)** Review QA Personnel Evaluations (PE) and ensure MIS is accurate with the current completion date.

2.12.11.4. **(Added-AFGSC)** Track initial and annual PE requirements and coordinate with QA to schedule PEs for those individuals coming due, overdue, or missing evaluations.

2.12.12. Review and recommend changes for maintenance tasks requiring IPIs to the Flight Supervision. **(T-3)**

2.12.13. Review, evaluate, and take corrective action based on QA and other inspection reports. **(T-3)**

2.12.14. Ensure all required work center publications necessary for the work center to meet its functional requirements are current and available for use. **(T-3)**

2.12.15. Ensure section personnel coordinate all flightline maintenance with the Flightline Expediter. **(T-3)**

2.12.16. Manage CTK and supply programs (such as, bench stocks, and operating stocks) IAW **Chapter 8** and **Chapter 9**. **(T-3)** Section NCOIC/Chief will:

2.12.16.1. Ensure sections are organized with tools, equipment, and materiel as close to the Point of Maintenance as possible, as approved by the Flight Supervision, without jeopardizing accountability and control procedures. **(T-3)**

2.12.16.2. Ensure the Bench Stock Review Listing (M04) is reviewed monthly, and all recommendations are adjudicated to meet mission needs most efficiently. **(T-3)**

2.12.16.3. Ensure work centers team with Decentralized Materiel Support or LRS/materiel management activity, to properly identify and dispose of all unserviceable or excess consumable items IAW AFMAN 23-122. **(T-3)**

2.12.17. Ensure custodial responsibilities are accomplished on all assigned equipment IAW AFI 23-101, and DAFMAN 23-122. **(T-3)**

2.12.18. Manage the section's Repair Cycle Program. **(T-3)** The Section NCOIC/Chief will review the D23 and other pertinent supply products to ensure proper supply discipline daily. **(T-3)**

2.12.19. Establish procedures to control, store, and manage Alternate Mission Equipment (AME); Maintenance, Safety, and Protective Equipment; and -21 equipment IAW DAFI 21-103. **(T-3)**

2.12.20. Identify items requiring calibration (does not include TMDE calibrated by the Precision Measurement Equipment Laboratory (PMEL)) or operational check before installation and provide a list of these items to the Flight Supervision. **(T-3)**

2.12.21. Recommend individuals for addition to the SCR to the Flight Supervision. **(T-3)**

2.12.22. Participate in and enforce the Bad Actor Program IAW TO 00-35D-54.

2.12.23. Manage Hazardous Materiel (HAZMAT) and Environment Safety and Occupational Health (ESOH) items IAW AFI 32-70XX-series instructions, and AFI 90-821.

2.12.23.1. Ensure HAZMATs are used IAW TOs and conform to indicated Military Specifications (MIL-Spec) and monitor the Qualified Products List/Qualified Product Database for changes to specified HAZMAT.

2.12.24. Ensure assigned NCE (applies to both nuclear and non-nuclear tasked units) comply with requirements outlined in AFI 63-125 and associated MAJCOM supplements.

2.12.25. Ensure Dull Sword reports are submitted for nuclear deficiencies IAW AFMAN 91-221 and DAFI 91-204.

2.12.26. Ensure aircraft -6 TO system, inspections, TCTOs and aircraft functional checks (except Isochronal (ISO), Phase (PH)/ Hourly Post-flight (HPO)) are accomplished as required to prevent overdue or over flight of equipment. **(T-3)**

2.12.27. Comply with TCTO performing work center requirements below:

2.12.27.1. Report all deficiencies in technical instructions and applicability to the TCTO managing agency and QA. **(T-3)**

2.12.27.2. Attend TCTO planning meetings. **(T-3)** Review the TCTO prior to the meeting and request clarification of any requirements from QA and the appropriate TCTO managing agency during the meeting.

2.12.27.3. Inventory TCTO kits for completeness prior to starting work. **(T-3)** If a discrepancy exists, contact the TCTO managing agency to resolve shortages.

2.12.27.4. Perform the inspection or modification procedures outlined in the TCTO and document results or findings in the MIS. **(T-3)**

2.12.27.5. If an inspection TCTO generates a requirement for parts, the performing workcenter will create a new Job Control Number (JCN) and enter the discrepancy in the AFTO Form 781A, Maintenance Discrepancy and Work Document, or applicable equipment record and order the required parts. **(T-3)** Inspection TCTOs are complete when the inspection is finished.

2.12.27.6. Order and maintain all HAZMAT required to comply with TCTOs and provide document numbers to the TCTO managing agency and supply TCTO monitor. **(T-3)**

2.12.27.7. Validate technical instructions and data on AFTO Form 82, *TCTO Verification Certificate*, when performing TCTO kit proofing IAW TO 00-5-15, *Air Force Time Compliance Technical Order Process*.

2.12.28. **(Added-AFGSC)** Appoint DIT monitors in writing to MMA.

Chapter 3

AIRCRAFT MAINTENANCE SQUADRON (AMXS)/GENERATION SQUADRON.

3.1. General. The AMXS/Generation Squadron provides direct MGN support by consolidating and executing on-equipment activities necessary to produce properly configured, mission ready weapon systems to meet contingency or training mission requirements. AMXS personnel service, inspect, maintain, launch, and recover assigned/transient aircraft (if applicable).

3.1. (AFGSC) General. Aircraft Maintenance Squadrons where the primary aircraft are bombers will be incorporated as a BGS.

3.1.1. **(Added-AFGSC)** BGSs include the following flights: Sortie Generation Flight, Weapons Generation Flight, and Sortie Support Flight. **Note:** Organization modifications must be approved IAW AFI 38-101.

3.1.2. **(Added-AFGSC)** AFGSC has transitioned away from AMUs and are using BGSs and AMXSs. Going forward, AMXSs will be structured to mirror the organization of traditional AMUs.

3.1.3. **(Added-AFGSC)** In lieu of AMUs, BGS units are constructed of the following flights:

3.1.3.1. **(Added-AFGSC)** Sortie Generation Flights includes the Production Section and Maintenance Operations Section. MXGs may approve additional sections and AFSC make up within existing sections to efficiently meet unique weapon system maintenance support requirements.

3.1.3.2. **(Added-AFGSC) [BGS Units]** Maintenance Operations Section is comprised of the following functions: PS&D, MMA, and Debrief.

3.1.3.3. **(Added-AFGSC)** Weapons Generation Flights, See AFMAN 21-206**,** *Aircraft Armament Systems Management,* for duties and responsibilities.

3.1.3.4. **(Added-AFGSC)** Support Flights may include the following sections: Aircraft (APG/Crew Chiefs), Specialists, and Support.

3.2. Maintenance Supervision Responsibilities. In addition to common responsibilities outlined in **Chapter 2**, Maintenance Supervision will:

3.2.1. Ensure standardized procedures and organizations among units as applicable to optimize effectiveness. **(T-3)**

3.2.2. Establish hot brake response procedures in coordination with base support agencies, for example, Fire Emergency Services and CDDAR Team. **(T-2)**

3.2.3. Monitor the squadron FCC program, if applicable. **(T-3)**

3.2.4. Ensure personnel use and understand the purpose of the AF Form 2408, *Generation Maintenance Plan*, and the AF Form 2409, *Generation Sequence Action Schedule*, or electronic equivalent. **(T-3)**

3.2.5. Ensure an explosive safety and chaff/flare academics and loading program is established for units without a 2W1 AFSC assigned (when applicable) IAW DESR6055.09_AFMAN91-201.

3.2.6. Publish procedures covering the storage, control, and handling of starter cartridges (if applicable). **(T-3)**

3.2.7. Provide input to MMA for the monthly metrics report to MAJCOM. **(T-2)**

3.2.8. Develops the annual maintenance plan IAW **Chapter 14**.

3.2.9. **(Added-AFGSC)** Ensure full and timely utilization of the On-Board Test System (OBTS)/OBTS Ground Processor (OGP) systems to support the production efforts of the B-2 units.

3.3. Aircraft Maintenance Unit (AMU). AMUs may include the following sections: Aircraft, Specialist, Weapons, Debrief, Supply and Support. MAJCOMs may approve additional sections and AFSC make up within existing sections to efficiently meet unique weapon system maintenance support requirements. **Note:** Organization modifications must be approved IAW AFI 38-101. In a Generation Squadron, AMUs are obsolete, but responsibilities of the unit and duty positions remain.

3.4. AMU OIC/SUPT Responsibilities. Allocates personnel and resources to the production effort. In addition to the common responsibilities in **Chapter 2**, the AMU OIC/SUPT will:

3.4. (AFGSC) AMU OIC/SUPT Responsibilities. [BGS Units, BGS DO/SEL Responsibilities]. Allocates personnel and resources to the production effort. In addition to the common responsibilities in **Chapter 2** of this instruction, the BGS DO/SEL will:

3.4.1. Review Pilot Reported Discrepancies daily and ensure proper maintenance actions are taken. **(T-3)**

3.4.2. Review all aborts and ensure proper maintenance actions are taken. **(T-3)**

3.4.3. Monitor aircraft PH/ISO/Periodic (PE)/Home Station Check (HSC) flow. **(T-3)**

3.4.4. Ensure a sufficient number of personnel are engine run qualified to meet maintenance requirements IAW **Chapter 11**.

3.4.5. **(Added-AFGSC)** Chair a BGS/AMXS maintenance production meeting as required. **(T-2)**

3.5. Production Superintendent (Pro Super). In squadrons with eight or fewer assigned aircraft, Pro Super and Flightline Expediter duties may be combined. The Pro Super has responsibilities for:

3.5.1. Make the final determination on aircraft status after reviewing aircraft forms. **(T-3)** Additionally, the Pro Super will review the forms after aircrew debrief. **(T-3)**

3.5.2. Sign the Exceptional Release (ER) IAW TO 00-20-1 when authorized by the MXG/CC IAW **Chapter 11** and **Table 11.1**.

3.5.3. Participate in developing and executing the monthly and weekly flying and maintenance schedules/plans. **(T-3)**

3.5.4. Manage the maintenance production effort by assigning priorities to meet the flying and maintenance schedules. **(T-3)**

3.5.5. Fully understand actions required by the squadron under OPLAN 8010 or contingency plans. **(T-3)**

3.5.5.1. Develop, ensure currency of, and direct the aircraft generation sequence. **(T-3)**

3.5.6. Fully understand and be prepared to implement specific disaster control duties and squadron responsibilities pertaining to aircraft/SE movement and personnel evacuation procedures developed IAW DAFI 10-2501 and emergency response guidebook. **(T-3)**

3.5.6.1. Pro Super will maintain a current copy of the on-base disaster map with cordon overlay and appropriate functional checklists outlining duties during disaster scenarios. **(T-2)**

3.5.6.1. **(AFGSC)** Electronic versions of all products, except for base grid map with cordon overlay, are acceptable. **(T-2)**

3.5.6.2. **(Added-AFGSC)** Ensure procedures are developed for communications outage situations. (e.g., AFTO 367, *Aircraft Discrepancy Gig Sheet* on hand and AFTO 781 series forms printed and stored)

3.5.7. Determine, track, and report aircraft/systems status IAW DAFI 21-103.

3.5.7. **(AFGSC)** Determine, track, and report NC3 Equipment ID/system status IAW DAFI 21-103_AFGSCSUP.

3.5.8. Establish and track Estimated Time In Commission (ETIC). **(T-3)**

3.5.9. Monitor unit CDDAR Program activities and local procedures designed to protect personnel and prevent further damage to aircraft, equipment, and other resources. **(T-3)**

3.5.10. Inform MOC of the maintenance effort and coordinate with MOC, Flightline Expediter, and other squadrons for support. **(T-3)**

3.5.10.1. Pro Super will provide MOC with aircraft/systems status updates as required. **(T-3)**

3.5.10.1. **(AFGSC)** Pro Super will provide MOC with the NC3 Equipment ID/system status updates as required.

3.5.11. Verify aircraft/system is in an authorized status IAW MDS-specific Minimum Essential Subsystem List (MESL) or MDS equivalent and DAFI 21-103 prior to verifying MICAP conditions. **(T-3)**

3.5.12. Verify aircraft weapons/load configurations are authorized IAW AFI 63-101/20-101. **(T-3)**

3.5.13. Review Condition Based Maintenance (CBM+) component forecast to ensure proactive maintenance practices are accomplished.

3.5.14. **(Added-AFGSC)** All Pro Supers, when assigned to nuclear units, will be qualified and added to the SCR for SVA utilizing an AFGSC Form 64. **(T-2)**

3.5.14.1. **(Added-AFGSC)** Nuclear units will certify Pro Supers in SVA procedures in-order to prevent dispatched technicians from unknowingly violating established procedures.

3.5.15. **(Added-AFGSC)** Monitor Enhanced Reliability Centered Maintenance (eRCM) thresholds and seek opportunities to utilize unscheduled downtime to accomplish CBM+ maintenance IAW **paragraph 11.41**.

3.6. Flightline Expediter. The Flightline Expediter ensures maintenance is accomplished and coordinates on all aircraft maintenance actions. Flightline Expediters manage, control and direct resources to accomplish maintenance. Flightline Expediters or equivalent will:

3.6. (AFGSC) Flightline Expediter. [BGS units] Flightline Expediters are assigned to the Production Section. While Lead Technicians may occasionally perform Expediter duties, they are not permanently assigned to that section.

3.6.1. Remain on the flightline when maintenance personnel are performing flightline maintenance and launching/recovering aircraft. **(T-3)** Flightline Expediters engage in direct sortie generation activities and work directly for the production superintendent.

3.6.1.1. Not perform production inspections (such as, sign off "Red Xs" and perform IPIs) unless authorized by the SQ/CC. **(T-3)**

3.6.2. Coordinate with the Weapons Expediter, ensure requirements in DAFMAN 21-201 for flightline munitions accountability are strictly followed.

3.6.3. Develop and implement disaster control duties and squadron responsibilities pertaining to aircraft/SE movement and personnel evacuation IAW DAFI 10-2501.

3.6.4. Maintain and have available for immediate use copies of the following as a minimum: flying schedule, emergency action and functional checklists, base grid map with cordon overlay, IPI listings, MESL, Quick Reference List (QRL) (if developed), WUC manual, and tracking device for aircraft status. **(T-3) Note:** Base grid maps and cordon overlays may not always be available during contingency operations at austere locations. Effort should be made to obtain maps and overlays but may not be available.

3.6.4. **(AFGSC)** Electronic versions of all products, except for base grid map with cordon overlay, are acceptable. **(T-2)**

3.6.4.1. Track, as a minimum, the following aircraft status information: aircraft serial number, location, priority, status and ETIC, configuration, OAP condition codes, fuel load, munitions load, and remarks. Show all limitations against the Full Systems List (FSL) and Basic System List (BSL) column as itemized on the MESL or MDS equivalent. **(T-3)** Ensure devices depicting aircraft status comply with program security requirements. **(T-3)**

3.6.4.1. **(AFGSC)** Track as a minimum, the following NC3 status information: NC3 Equipment ID, priority, status and ETIC and remarks. Show all limitations against the Full Systems List (FSL) and the Air to Surface, Nuclear List (ASN) column as itemized on the NC3 MESL. Ensure devices depicting NC3 status comply with program security requirements.

3.6.5. Follow established CANN procedures and ensure all CANNs are accurately documented in the aircraft/system forms and MIS as described in **Chapter 11**.

3.6.6. Ensure aircraft OAP sampling is completed IAW **Chapter 11** and applicable technical data. **(T-3)**

3.6.6. **(AFGSC)** Maintain an OAP status on each assigned aircraft (if applicable) showing all lab recommendation codes next to the aircraft/engine serial numbers. Prior to commencing the flying day, verify status of aircraft or engines on special surveillance. **(T-2)**

3.6.7. Ensure parts are ordered with appropriate priorities and relay document numbers to the Pro Super, MOC, and appropriate technicians. **(T-3)**

3.6.7.1. Ensure timely turn in of DIFM items to DMS/supply IAW AFI 23-101.

3.6.8. Request support beyond unit capability to the MOC. **(T-3)**

3.6.9. Direct AGE drivers to position AGE as required and notify the driver of AGE on the flightline or sub-pools that require maintenance. **(T-3)**

3.6.10. Ensure timely and accurate aircraft status (for example, discrepancies, WUC/LCN, ETIC, job completion) and configuration status is reported IAW DAFI 21-103 to the Pro Super and MOC. **(T-3)**

3.6.10. **(AFGSC)** Ensure timely and accurate NC3 status (for example, discrepancies, WUC/LCN, ETIC, job completion) and configuration status is reported IAW DAFI 21-103 to the Pro Super and MOC.

3.6.11. Ensure completed aircraft forms are provided to the debrief function by the end of the flying day if debriefs have been suspended due to surges. **(T-3)**

3.6.12. **(Added-AFGSC)** Notify MOC and Pro Super when aircraft are ready for flight (crew ready and crew show), engine start, taxi, block-in, and aircraft configuration (e.g., fuel, munitions, cargo).

3.6.13. **(Added-AFGSC)** Expediters will, when assigned to nuclear units, be certified in SVA procedures to prevent dispatched technicians from unknowingly violating established procedures. **(T-2)**

3.6.14. **(Added-AFGSC)** When assigned, expediters will maintain a copy of the current Augmentee listing and ensure that Augmentees under their supervision do not perform Egress maintenance without 2A6X3 personnel present, unless such activity is specifically exempted in **paragraph 4.4.3.2.6.7**. Notify MXS Production when violations are detected.

3.7. Aircrew and Maintenance Debrief Section. Debrief is conducted at the termination of each sortie/mission or when a sortie/mission is aborted. Aircraft scheduled for turn-around sorties/missions need not be debriefed if returned in landing status Code 1 or 2. However, debriefing is required, regardless of landing status, after the last flight of the day for each aircrew. MAJCOMs operating RPAs will develop and publish debrief procedures for Remote Split Operations in their supplements or addendum for both aircraft and ground control stations to adequately capture all maintenance discrepancies. The Debrief Section will:

3.7.1. Use aircraft fault reporting manuals and include fault codes when documenting discrepancies in the aircraft forms. **(T-3)** Debrief Section will use automated debrief tools such as the Computerized Fault Reporting System. **(T-3)**

3.7.1.1. Debrief Section will develop local aircrew debriefing guides when not provided and managed by the Weapon System PM. **(T-3)** QA will review and approve local aircrew debriefing guides every two years. **(T-3)**

3.7.1.1.1. **(Added-AFGSC) [NC3]** For NC3 equipped aircraft, the Debrief Section will also incorporate NC3 Equipment Designators and Equipment IDs, into local debriefing guides. These guides will, at a minimum, contain the following NC3 information:

3.7.1.1.2. **(Added-AFGSC) [NC3]** Identify aircraft with NC3 Equipment IDs.

3.7.1.1.3. **(Added-AFGSC) [NC3]** Identify systems that are on the NC3 MESL for local MDS.

3.7.2. Implement procedures for reporting dropped objects, aborts, code 3 flight control malfunctions and engine malfunctions. **(T-3)**

3.7.3. Use operational utilization update screens in MIS to enter flying time information. **(T-2)** Debrief Section will ensure flying times and installed engine Event History Recorder (EHR) readings, for both home station and deployed sorties/missions, are updated no later than the next duty day after occurrence. **(T-3)**

3.7.3. **(AFGSC)** Update all sorties and flying hours in the MIS upon aircraft return from Depot or Contractor maintenance. **(T-2)**

3.7.4. Check AFTO Form 781H, *Aerospace Vehicle Flight Status and Maintenance*, to ensure updates to airframe time and applicable servicing data (in-flight/hot pit refueling) are entered on the AFTO Form 781H or equivalent and/or applicable debrief system during the pilot/aircrew debrief. **(T-3)**

3.7.5. Input discrepancy verbatim and deviation information, utilization, and applicable flight data (to include landing status, system capability IAW DAFI 21-103 and other applicable cause codes) into the MIS. **(T-3)** Unless using an automated 781 process, do not send AFTO Form 781-series forms to Operations Squadron(s) or to Aviation Resource Management before MIS updates. Use local backup procedures for recording data when the MIS is unavailable.

3.7.6. Utilize MIS to identify and research discrepancies for repeat/recur trends and document them accordingly on the AFTO Form 781A. **(T-3)** Debrief Section will ensure previously documented discrepancies are reviewed and identified as repeat/recurs. **(T-3)**

3.7.6.1. Debrief Section will identify repeat/recurs on automated debriefing sortie recaps and on the AFTO Form 781A. **(T-3)**

3.7.6.1. **(AFGSC)** A discrepancy identified during an in-flight operational check of a maintenance action will not be counted as a repeat/recur. Any subsequent sortie that the discrepancy returns on will not follow repeat/recur guidelines if an in-flight operational check is requested**. (T-2)**

3.7.6.2. **(Added-AFGSC)** The local aircrew debriefing guide will document in-flight refueling boom strike/fuel overspray information. At a minimum, identify Air Refueling Wing, tanker call sign, tanker tail number, air refueling track, air refueling time (Zulu) and refueling track events.

3.7.7. Use the appropriate landing status code (**Table 3.1**) and the appropriate system capability code (**Table 3.2**) for the completion of a sortie/mission. **(T-3)**

3.7.8. Provide the MOC with aircraft identification numbers and system WUCs for each aircraft debriefed with a landing status Code-3 IAW **Table 3.1** using the approved MESL or MDS equivalent IAW DAFI 21-103.

3.7.9. Enter one of the deviation cause codes (**Table 3.3**) into the MIS. **(T-3)** Indicate the reason for the deviation and the agency that caused a deviation as referenced in applicable MIS guidance.

3.7.9. **(AFGSC)** See **Attachment 14**, for MAJCOM Deviation Cause Codes.

3.7.10. Collect and submit ASIP aircraft usage data IAW the MDS specific TOs, DAFI 63-140, and **Chapter 11** of this instruction.

3.7.11. If MIS is not available, use blank printouts as manual documentation method. **(T-3)** If deployed, send documents to home station for data transcribing by the most expeditious means available. Debrief Section will turn in, validate, and reconcile all documents with the MIS when it becomes available. **(T-2)**

Table 3.1. Landing Status Codes.

CODE	STATUS
Code 0	Ground Abort
Code 1	Aircraft Mission Capable (MC) with no additional discrepancies
Code 2	Aircraft or system has minor discrepancies but is capable of further mission assignment.
Code 3	Aircraft or system has major discrepancies in mission essential equipment that may require extensive repair or replacement prior to further mission assignment. The discrepancy may not affect safety-of-flight and the aircraft may be Non-Mission Capable (NMC) flyable.
Code 4	Aircraft or system has suspected or known radiological, chemical, or biological contamination.
Code 5	Aircraft or system has suspected or known battle damage.
Note: Debrief will enter code “8” in MIS for aircraft debriefed as code “4” or “5”. MESL or MDS equivalent requirements determine if aircraft status is NMC or Partially Mission Capable (PMC).	

Table 3.2. System Capability Codes.

CODE	STATUS
Code 0	System flown with a known discrepancy; no additional discrepancies noted. System can be used.
Code 1	System used and performed satisfactorily. No maintenance required.
Code 2	System used and performed satisfactorily. A minor malfunction exists, but system is capable of further mission assignment.
Code 3	System performance was unsatisfactory. This system did not cause an abort.
Code 4	System performance was unsatisfactory. This system caused or contributed to an abort.
Code 5	System out-of-commission prior to takeoff.
Code 6	System installed but not used.
Code 7	System not installed.
Code 8	Aircraft or system has suspected or known radiological/biological contamination.

Table 3.3. Deviation Cause Codes.

CODE	DEVIATION REASON
ATx	Air Traffic
GAA	Ground Abort, before engine start, maintenance
GAB	Ground Abort, after engine start, before taxi, maintenance
GAC	Ground Abort, after taxi, maintenance
HQT	Higher Headquarters
HQN	Higher Headquarters, NAF
HQP	Higher Headquarters, other
MTx	Maintenance
OPx	Operations
SUx	Supply
SYx	Sympathy
WXx	Weather
OTx	Other
Xxx	MAJCOM/local use
Note: Use x for any character for MAJCOM/local use.	

3.8. Aircraft Section. The Aircraft Section is the primary work center responsible for maintaining assigned aircraft. This section performs tasks to include servicing, scheduled and unscheduled maintenance, pre-flights, thru-flights, basic post-flights, home station checks, special inspections, corrosion control, cleaning, ground handling, launch/recovery of aircraft, troubleshooting and adjustment, on-equipment repairs and component removal/replacement, documenting maintenance actions, and managing aircraft forms. AMUs with 18 or more Primary Aerospace Vehicle (Aircraft) Inventory (PAI) aircraft may have two Aircraft Sections. The Aircraft Section consists of Aircraft Technicians. Refer to **Chapter 11** for FCC responsibilities.

3.8.1. Aircraft Technician:

3.8.1.1. Perform ground handling, servicing, -6 inspections, alert duties, maintenance ground tests, corrosion control, lubrication and maintenance and modification preparations, as applicable, on the assigned aircraft/system.

3.8.1.2. Inventory on-aircraft -21 equipment when this responsibility is not assigned to another function.

3.8.1.3. Perform engine operation when qualified and certified.

3.8.1.4. **(Added-AFGSC)** Perform helicopter vibration analysis in flight.

3.8.2. Dedicated Crew Chief (DCC) Program. The objective of a DCC program is to directly assign a maintenance person to each aircraft to provide continuity/accuracy of aircraft forms, aircraft status, scheduled maintenance, and improve aircraft appearance. DCCs manage and supervise maintenance on their aircraft. DCCs are selected on the basis of initiative, management and leadership ability, and technical knowledge. When authorized, ensure the DCC's and Assistant Dedicated Crew Chief name and rank is stenciled or painted on their assigned aircraft. Use only authorized wing paint scheme and marking procedures in TO 1-1-8. In addition to Aircraft Technician responsibilities, DCCs, if assigned:

3.8.2.1. Accompany their aircraft through scheduled inspections and assist the Inspection Section NCOIC/Chief as needed.

3.8.2.1.1. Attend pre- and post-dock meetings.

3.8.2.1.2. Assist the Inspection Section NCOIC/Chief with completing the required document review and validation at the end of the inspection.

3.8.2.2. Coordinate with Pro Supers and expediters for downtime to accomplish scheduled and unscheduled maintenance.

3.8.2.3. Manage deferred discrepancies.

3.9. Specialist Section. The Specialist Section is responsible for aircraft systems troubleshooting, on-equipment repairs, component removal and replacement, aircraft avionics systems, classified item management, aircraft ground handling, servicing, and cleaning. The section may include avionics, propulsion, hydraulic, and electro/environmental technicians, and other specialties approved through higher headquarters. When used, the Specialist Section Expediter coordinates maintenance priorities with the Pro Supers and Flightline Expediters.

3.9. (AFGSC) Specialist Section. The Specialist Section will provide support for Phase/Isochronal Inspections as required and attend Phase/Isochronal Pre-Dock meetings to provide specialist support if required.

3.9.1. In addition to the common responsibilities in **Chapter 2**, the Specialist Section Chief:

3.9.1.1. Ensures accurate and timely pod and support equipment status is updated or verified daily in Reliability, Availability, Maintainability, for Pods IAW DAFI 21-103 for pods under the control of the Aircraft Maintenance Squadron.

3.9.2. Avionics Specialists:

3.9.2.1. Perform PACER WARE, SERENE BYTE message, or TCTO reprogramming of avionics systems. **(T-3)**

3.9.2.2. **(Added-AFGSC)** Perform Mode V checks as required on IFF Mode V equipped aircraft IAW MDS -6 requirements. Document operational checks in the MIS. **Note:** IFF Mode IV cryptographic keys are no longer attainable due to discontinuation.

3.9.2.3. **(Added-AFGSC)** Perform operational checks on aircraft NC3 systems during nuclear generation or when scheduled for HHQ or USSTRATCOM level NC3 communication exercises and Continuing Evaluation Program (CEP) sorties (if advance notice is provided) prior to flight. Document operational checks in the MIS. Operational checks should be complete "end-to-end" checks that verify function of the system to external transmitters such as a UHF radio call to tower or checking VLF receive capability utilizing the URM-215 (or similar VLF test set).

3.9.3. Electronic Warfare (EW) specialist functions may be combined with the avionics specialists. EW Specialists:

3.9.3.1. Maintain inventory control of all installed Electronic Counter Measure (ECM) AME and ECM pods. **(T-3)**

3.9.3.2. Perform reprogramming of avionics/electronic warfare systems (to include electronic attack pods) IAW applicable mission directives, PACER WARE/SERENE BYTE messages, or TCTO requirements. **(T-3)**

3.9.3.3. Load contingency and training configuration settings in ECM pods, infrared countermeasures systems, and Radar Warning Receiver/Radar Threat Warning systems, unless the equipment is assigned to another section. **(T-3)**

3.9.3.4. **(Added-AFGSC)** Verify operation of the installed Radar Warning Receiver/Radar Threat Warning (RWR)/(RTHW) systems.

3.9.3.5. **(Added-AFGSC) [B-52 units]** Load/maintain chaff magazines.

3.9.4. Propulsion Specialists:

3.9.4.1. Troubleshoot, repair, and replace aircraft propulsion systems and components. **(T-3)**

3.9.4.2. Perform engine flightline blade blending. **(T-3)**

3.9.4.3. Perform flightline engine borescope inspections. **(T-3)**

3.9.5. Electrical & Environmental (E&E) Specialists:

3.9.5.1. Troubleshoot, repair, and replace aircraft E&E system components including aircraft environmental control, bleed air, vacuum, pneumatic, installed fire extinguishing and suppressant systems, Liquid Oxygen (LOX) and Gaseous Oxygen (GOX) systems, and On-Board Oxygen Generating Systems (OBOGS), On-Board Inert Gas Generation Systems (OBIGGS) and components. **(T-3)**

3.9.5.2. Remove and install In Flight Refueling (IFR) carts and fire bottle squibs. **(T-3)** **Note:** Ensure only approved temporary storage locations are used for these components.

3.9.6. Hydraulic Specialists will maintain authorized on-equipment/off-equipment pneumatic and hydraulic systems and components. **(T-3)**

3.9.6.1. **(Added-AFGSC)** Maintain and inspect inflight refueling receptacle systems, as applicable.

3.9.7. **(Added-AFGSC) Communications Section.** This section is responsible for Ground Control Element and Network Management systems troubleshooting, on-equipment repairs,

component removal and replacement, classified item management, servicing, and cleaning. The section may include Communications and Network Management technicians. When used, the communication specialist expediter coordinates maintenance priorities with the Pro Super and Flightline Expediters.

3.10. Weapons Section/Expediter/ Loading Element/ Maintenance Element/ Non-Standard Weapons Sections. See AFMAN 21-206 for duties and responsibilities.

3.10.1. - 3.10.5.8. DELETED.

3.11. Support Section. The Support Section may include the following elements/functions to support unit flightline maintenance activities; support (CTKs/special tools, eTools, test equipment, TOs, bench stock), -21 equipment, AME, mobility equipment and DMS. Personnel will be assigned to the Support Section for a minimum of 12 months. **(T-3)** Personnel may be required to maintain task qualifications/certifications to ensure units can meet readiness and Core Mission Essential Task List (METL) requirements in Defense Readiness Reporting System-Strategic (DRRS-S) IAW AFI 10-201. Support Sections must standardize procedures across the squadron for security, control, and accountability of equipment. **(T-2)** Materiel support procedures in this section do not apply to aircraft supported by Contractor Operated and Maintained Base Supply. The Support Section:

3.11.1. Maintains TOs IAW TO 00-5-1.

3.11.2. Maintains bench, shop, and operating stocks IAW AFI 23-101, and **Chapter 9** of this instruction.

3.11.3. Ensures maintenance, control, and storage of assigned AME, -21 equipment, and Maintenance, Safety, and Protective Equipment IAW DAFI 21-103.

3.11.3.1. Develops local procedures to control and store other equipment not identified as -21 equipment (such as, aircraft galley items, U-2 pod panels, aircraft pylon attachment cover panels, aircraft covers/plugs) using DAFI 21-103 guidelines.

3.11.4. Ensures proper calibration, use, care, handling, and transportation of TMDE IAW TO 00-20-14, AFMAN 21-113, and applicable Calibration Measurement Summaries.

3.11.5. Maintains and manages squadron Land Mobile Radio (LMR) IAW **Chapter 11** (as applicable).

3.11.6. Monitors the status of critical support equipment and testers for serviceability, accountability, and status of TCTO modifications. **(T-3)** Support Section will provide monthly critical support equipment status update to Maintenance Supervision. **(T-3)**

3.11.7. Maintains tools/CTKs IAW **Chapter 8**.

3.12. Unit Decentralized Materiel Support (DMS). In addition to the responsibilities in **Chapter 9** for DMS procedures, DMS personnel:

3.12. (AFGSC) Unit Decentralized Materiel Support (DMS). In addition to the responsibilities in **Chapter 9** of this instruction for DMS procedures, unit DMS personnel:

3.12.1. Requisition parts and use supply management products. Initiate follow-up action when necessary. **(T-3)**

3.12.2. Notifies Flightline Expediter of all back-ordered parts. **(T-3)**

3.12.3. Develops and maintains a QRL as needed and provide it to technicians. **(T-3)**

3.12.4. Tracks and processes DIFM assets, to include warranty parts IAW AFI 23-101. **(T-3)**

3.12.4.1. Notifies unit leadership when DIFM asset turn-in times exceed requirements outlined in AFI 23-101. **(T-3)**

3.12.5. Manages reusable containers IAW DAFI 24-602V2, *Cargo Movement*, and TO 00-20-3. **(T-3)**

3.12.6. Controls and manages aircraft TNB if stored within the Support Section. **(T-3)** When FOM assets are collocated with TNB, the items must be similarly controlled and managed. **(T- 3)**

3.12.7. Coordinates with the Pro Super and Flightline Expediter(s) for "mark for" changes. **(T- 3)**

3.12.8. Manages the unit's CANN program supply transactions and the associated documentation. **(T-3)**

3.12.9. **(Added-AFGSC)** CBM+ parts will be requisitioned using Project Code: 063 and UJC: AU/BU and must be processed through LRS/DMS. CBM+ parts will be ordered as not to exceed DIFM turn-in timelines IAW **paragraph 9.18** and AFMAN 23-300, *Materiel Management Procedures*.

3.12.9.1. **(Added-AFGSC)** Coordinate with the Pro Super to ensure CBM+ parts are not pulled from Readiness Spares Package (RSP). Use of RSP parts for CBM+ maintenance must be approved by MXG/CC.

3.12.9.2. **(Added-AFGSC)** When a CBM+ part is being turned into LRS, the unserviceable tag will be annotated with "G" condition code. If the CBM+ part fails prior to scheduled maintenance, the unserviceable tag will be annotated with "F" condition code.

3.13. (Added-AFGSC) Software Analysis Section [B-2 Units]. The Software Analysis Section processes and analyzes B-2 OBTS or OGP data, as applicable, to provide timely and accurate information to aid the maintenance effort, identify software discrepancies to the appropriate OPRs, and identify trends to maintenance supervisors and assigned engineers. B-2 Units address all hardware and software deficiencies/anomalies associated with aircraft diagnostics using the OBTS and the OGP. A team of maintenance technicians compares data extracted from the OGP and the OBTS paper tape to ensure accuracy and validity of the data in support of airframe availability. This section works closely with maintenance analysis functions to identify trends in system performance. Demonstrated knowledge and ability should be of primary importance in assigning personnel to this section; however, each flightline avionics AFSC should be represented. All assigned personnel should be competent and experienced in their assigned AFSC duties.

3.13.1. **(Added-AFGSC)** At a minimum, the responsibilities of this section are to:

3.13.1.1. **(Added-AFGSC)** Analyze and establish the accurate status of all reported Reference Designator Indicators.

3.13.1.2. **(Added-AFGSC)** Identify to appropriate maintenance supervisors (and engineers, if assigned to the unit), adverse system/maintenance trends.

3.13.1.3. **(Added-AFGSC)** Identify/Report OBTS/OGP software deficiencies via. The Joint Deficiency Reporting System (JDRS) program IAW TO 00-35D-54, *USAF Deficiency Reporting, Investigation, and Resolution*.

3.13.1.4. **(Added-AFGSC)** Assist maintenance technicians in identifying and reporting Ground Readiness Test deficiencies.

3.13.1.5. **(Added-AFGSC)** Provide OBTS/OGP information products, as required, to support the production effort.

3.13.1.6. **(Added-AFGSC)** Assist/train maintenance technicians to use OGP maintenance reports in troubleshooting malfunctions.

3.13.1.7. **(Added-AFGSC)** Maintain historical data for each assigned aircraft in accordance with the Records Disposition Schedule (RDS).

3.13.1.8. **(Added-AFGSC)** Analyze data-dependent maintenance codes to determine whether maintenance action is required. Generate, retrieve, and analyze the debrief report from the OGP in support of each sortie debrief. Provide the Debrief Section with a list of OBTS reported aircraft malfunctions/faults to be entered into MIS/AFTO Form 781A. **(T-2)**

Chapter 4

MAINTENANCE SQUADRON (MXS)/GENERATION SQUADRON.

4.1. General. The MXS/Generation Squadron supports MGN operations by providing centralized back shop support to perform on and off equipment maintenance tasks that are assigned to a specific back shop function. The MXS provides both organizational and intermediate level maintenance described in the "Maintenance Concept" section in **Chapter 1** of this DAFI. Bases with permanently assigned Centralized Repair Facilities (CRF), which support enterprise RN functions, will develop, and document the division of responsibilities between the MGN and RN, as outlined in **Chapter 13** of this DAFI, to ensure both local and enterprise mission requirements are met. IAW AFI 38-101, the MXS may consist of personnel from various AFSCs organized into flights: Propulsion Flight, Avionics Flight, TMDE Flight, Accessories Flight, AGE Flight, Fabrication Flight, Armament Flight, Maintenance Flight, and Munitions Flight. The MXS maintains AGE, munitions, off-equipment aircraft, and support equipment components; performs on-equipment maintenance of aircraft and fabrication of parts; and provides repair and calibration of TMDE. **Note:** For purpose of this instruction, MXS represents MXS, Equipment Maintenance Squadron (EMS), and Component Maintenance Squadron (CMS).

4.2. Maintenance Supervision Responsibilities. Maintenance Supervision manages the resources to accomplish the workload. **Note:** In a Generation Squadron, MXSs are obsolete but responsibilities of the unit and duty positions remain. In addition to general responsibilities in **Chapter 2**, Maintenance Supervision:

4.2.1. Reviews and consolidates monthly maintenance plan inputs from flights/sections and forward to Maintenance Operations PS&D. **(T-3)**

4.2.2. Optimizes local repair capability by ensuring base level repair constraints (for example, lack of equipment, manpower, parts) are elevated to the Repair Network Manager (RNM) and applicable stakeholder(s) IAW DAFI 20-117, TO 00-20-3, and **Paragraph 1.3.2** of this DAFI, and MAJCOM supplements to keep repair at the lowest level. **(T-2)**

4.2.3. Ensures EOR procedures for transient aircraft are developed IAW TO 00-20-1 and MAJCOM supplements. **(T-3)**

4.2.4. Ensures the MXS and WS develop procedures for required weapons loading actions on transient aircraft, storage of transient aircraft impulse cartridges, and requisition and maintenance of weapons safing equipment for common transient types of aircraft. **(T-3)**

4.2.5. Ensures local manufacture capability and fabrication process is controlled IAW this instruction. **(T-3)**

4.2.6. Ensures MXS personnel utilize Engineering Technical Service (ETS) personnel and the Joint Engineering Data Management Information and Control System (JEDMICS) **https://jedmics.af.mil/webjedmics/index.jsp** to obtain information and specifications when the information in TOs does not provide enough detail. **(T-3) Note:** For drawings not available electronically, contact the appropriate JEDMICS help desk.

4.2.7. DELETED.

4.3. MXS Production Superintendent (Pro Super). Monitor backshop production and flightline operations and coordinate support and priority with other squadron Pro Supers and MOC.

(T-3) Focuses overall maintenance efforts toward MXG maintenance priorities. Identifies production requirements and shortfalls to Maintenance Supervision. **(T-3)**

4.3.1 . DELETED.

4.4. Accessories Flight. The Accessories Flight normally consists of four sections; Electrical and Environmental (E&E), Egress, Fuels, and Hydraulics and is responsible for performing on/off-equipment maintenance of systems and equipment.

4.4.1. Accessories Flight CC/Chief Responsibilities. In addition to the common responsibilities in **Chapter 2**, the Accessories Flight CC/Chief:

4.4.1.1. Ensures an egress training program is established IAW this instruction. **(T-3)**

4.4.1.2. Coordinates with squadron superintendents or civilian equivalent to ensure assigned personnel rotation plans are established to comply with core task upgrade requirements. **(T-3)**

4.4.1.3. Ensures explosives are controlled and stored in approved storage areas/containers IAW DESR6055.09_AFMAN91-201.

4.4.1.4. **(Added-AFGSC)** Owning agency monitors and reports the status of aircraft liquid and gaseous servicing carts in repair status to Director of Operations (DO) /SEL.

4.4.1.5. **(Added-AFGSC)** When applicable, the Accessories Flight CC/Chief will appoint a Repair Network Node Manager for Electrical & Environmental and Hydraulic Sections. Update Repair Network CAP2 annually or as directed. Ensure Node Managers complete training per DAFI 20-117.

4.4.1.6. **(Added-AFGSC)** Ensures notification of Egress Augmentee violations to and supporting details are reported to QA Supt within 24 hours of receipt.

4.4.2. Electrical and Environmental (E&E) Section. The E&E Section performs authorized local manufacture, repair, overhaul, testing, modification, and inspection of aircraft and SE electrical components, wiring harnesses, batteries, and charging units. The E&E Section:

4.4.2.1. Ensures battery disposal procedures meet applicable environmental standards and batteries are controlled for accountability purposes. **(T-0)**

4.4.2.2. Performs on/off-equipment maintenance on aircraft electrical and environmental systems and components. **(T-3)**

4.4.2.3. Repairs LOX/GOX/Liquid Nitrogen servicing units/carts. **(T-3) Note:** AGE performs chassis, enclosure, and trailer maintenance on gaseous and cryogenic servicing units and all maintenance on Self-Generating Nitrogen Servicing Carts.

4.4.2.4. Performs off-equipment maintenance for aircraft and aircrew Carbon Dioxide cylinders. **(T-3)**

4.4.2.5. Performs off-equipment maintenance on type MA-1 portable breathing oxygen cylinders (portable walk around bottles) and regulators, to include removing/replacing the regulator and purging the bottle. **(T-3) Note:** Ownership and storage of these cylinders remain with the appropriate support section.

4.4.2.6. **(Added-AFGSC)** Maintain, repair, orders parts, and keep historical records on the gaseous and cryogenic portion of aircraft oxygen/nitrogen gaseous and cryogenic servicing units. Maintain historical records in accordance with the RDS.

4.4.3. Egress Section. The Egress Section maintains aircraft egress systems, components, and trainers (such as, aircraft ejection seats, extraction and escape systems, egress components of jettisonable canopies, explosive components of escape hatches/doors) and stores egress explosive components that are removed to FOM. Wings will identify the base level organization responsible for locating inadvertent beacon activations on the flightline and configuring survival kit personnel locator beacons (on-aircraft). **(T-3)**

4.4.3.1. The Egress Section:

4.4.3.1.1. Performs all off-equipment ejection seat maintenance in the egress maintenance facility compliant with Defense Explosives Safety Regulation 6055.09_DESR6055.09_AFMAN 91-201and TO requirements.

4.4.3.1.2. Ensures all personnel use the Demand Response Team during any task requiring the removal/installation of explosive components, and during egress final inspections. **(T-3)=3**

4.4.3.1.2.1. Demand Response Teams will be comprised of individuals who are certified to perform egress maintenance. **(T-3)** At least one team member must be a certified egress journeyman. **(T-3)**

4.4.3.1.2.1. **(AFGSC)** Unless specified in aircraft specific tech data, the requirements of the demand-response team (also known as the two-person concept) are satisfied so long as the members of the team performing hands-on explosive maintenance are certified IAW **paragraph 4.4.3.2.6.2** and the MMCL. Secondary tasks related to this work (such as crane operation) do not require demand-response certification, as these tasks do not contribute to the safety of the explosive operation. Furthermore, 2A6X3 personnel in upgrade training and Egress Augmentees in training who have not met the certification requirement may be present for explosive operations to gain familiarity as part of their OJT, provided all other applicable safety prerequisites have been met. Such members must not interfere with the safety of the operation. Prior to each explosive task, the team lead will provide the team with a pre-task safety brief that identifies who has demand-response responsibilities, who will be performing secondary tasks, and who will be authorized to observe. If the team size is smaller than three, both members must be certified IAW **paragraph 4.4.3.2.6.2** and the MMCL. **(T-2)**

4.4.3.1.3. Coordinate with PS&D and monitor the weekly maintenance schedule to identify egress items requiring removal for scheduled time changes/maintenance. **(T-3)**

4.4.3.1.4. Utilize a facility that meets the requirements of DAFMAN 32-1084, *Facility Requirements*. Locations are established IAW DESR6055.09_AFMAN 91-201 to store explosive components and ensure they are properly licensed.

4.4.3.1.4.1. Egress Section will ensure licensed explosive area will not exceed the licensed Net Explosive Weight capacity for each Hazard Division without approval from Wing Safety. IAW DESR6055.09_AFMAN 91-201.

4.4.3.1.5. **(Added-AFGSC) [B-52 units]** Contact Aircrew Flight Equipment (AFE) personnel to locate inadvertent beacon activation on the flightline. **(T-2)**

4.4.3.1.6. **(Added-AFGSC) [B-52 units]** During contingency operations, AFE personnel are responsible to configure personnel locator beacons in the correct mission configuration and theater requirements, or as directed by Crisis Action Team or Special Instructions. **(T-2)**

4.4.3.1.7. **(Added-AFGSC)** Stop all egress maintenance/inspections at outdoor locations equipped with a Lightning Protection System (LPS) and all locations not equipped with an LPS when lightning is within 5 nautical miles of the installation (including in-shop, hangar, HAS, etc.). The MOC will confirm lightning proximity. Explosive operations may continue in a lightning-protected facility only for priority aircraft and with the approval of the MXG Commander or Deputy. This restriction does not affect non-explosive operations or non-destructive visual inspections performed within a lightning protected facility.

4.4.3.2. The Egress Section NCOIC/Chief will:

4.4.3.2.1. Ensure ejection systems are “safed” IAW with 00-80G-series technical orders and DESR6055.09_AFMAN 91-201 prior to an aircraft being placed on static display. **(T-3)**

4.4.3.2.2. Ensure egress systems on training aircraft are de-armed/“safed” IAW MDS specific TOs when an aircraft is used for Fire Emergency Services and/or aircrew extraction training. **(T-3)**

4.4.3.2.3. Ensure aircraft (to include GITA) are "safed” IAW 00-80-series TOs.

4.4.3.2.4. Ensure all permanently decommissioned static display aircraft explosive devices are removed and turned in to munitions inspections IAW DAFMAN 21-201. Egress Section will sign the appropriate block on the AF Form 3580, *USAF Heritage Program Aerospace Vehicle Static Display Egress and Safety Certificate*, which is retained by the Historical Property Custodian(s). **(T-3)**

4.4.3.2.5. Request assistance from Explosive Ordnance Disposal (EOD) when egress explosive devices are damaged or suspected to be unsafe. **(T-3)**

4.4.3.2.6. Establish egress training program requirements and conduct reviews IAW AFI 36-2650. **(T-2)**

4.4.3.2.6.1. As a minimum, the program will include: a master training plan, explosive safety certification requirements, and MIS time change documentation qualification minimums. **(T-3)**

4.4.3.2.6.2. Certification requirements.

4.4.3.2.6.2.1. Trained and certified egress 5-levels and above reassigned to another base or unit are not required to complete the Organizational Maintenance (on-equipment) egress technician course unless required by the Egress Section NCOIC/Chief.

4.4.3.2.6.3. Decertification requirements:

4.4.3.2.6.3.1. Decertify egress personnel after not having performed egress maintenance for more than 18 months. **(T-3)** Instructing and inspecting egress maintenance is not considered performing maintenance.

4.4.3.2.6.3.2. Document decertification IAW DAFMAN 36-2689.

4.4.3.2.6.4. Recertification requirements:

4.4.3.2.6.4.1. Recertify egress personnel who have not performed egress maintenance for 18 months. **(T-3)**

4.4.3.2.6.4.2. Recertification must be accomplished by a 2A673 trainer and certifier. **(T-3)**

4.4.3.2.6.5. **(Added-AFGSC)** The Egress NCOICs will establish an Egress Augmentee training plan. This plan will include:

4.4.3.2.6.5.1. **(Added-AFGSC)** A list of 2A6X3 CEFTP qualification tasks to which Augmentees will be qualified. This list will be developed, maintained, and meet the approval of the Egress NCOIC. This list will consist of the minimum number of essential and routine tasks required for Augmentees to perform as members of a demand-response team and will be uniformly applicable to all Augmentees. This listing will not consist of the entire 2A6X3 CFETP. Units Egress NCOICs will consider only tasks which are essential in an austere, deployed environment for inclusion in this training plan. Augmentees candidates will not be considered 'certified' until fully qualified on all tasks in the NCOICs training plan. If new tasks are added to the training plan, current Augmentees will remain qualified until the biannual records review (see **paragraph 4.4.3.2.6.8.1**), unless they become qualified on the new tasks before the review.

4.4.3.2.6.5.2. **(Added-AFGSC)** MAJCOM mandatory course listing prerequisites IAW DAFI 36-2650 and the 2A6X3 CFETP. Prerequisites must be met for an Augmentee candidate to be considered 'certified'.

4.4.3.2.6.5.3. **(Added-AFGSC)** Annual Explosive safety IAW DAFI 91-202. Current explosive safety must be maintained for an Augmentee candidate to be considered 'certified'.

4.4.3.2.6.5.4. **(Added-AFGSC)** Listing of trainers within the Egress Section who may provide initial certification and recertification training. Trainers must be PAFSC 2A673 Staff Sergeants or above who are qualified on the tasks listed in the training plan.

4.4.3.2.6.5.5. **(Added-AFGSC)** Means through which Augmentees will be decertified/recertified. At a minimum, augmentees will adhere to the time requirements set forth in **paragraph 4.4.3.2.6.4.1** (Example: Once certified, augmentees will recertify annually by performing and demonstrating proficiency on select 2A6X3 CEFTP tasks before an approved Egress trainer.) Members will not be considered certified if annual explosive safety requirements are allowed to lapse.

4.4.3.2.6.6. **(Added-AFGSC)** Augmentee Prohibitions: Unless exempted by this

instruction, Augmentees are prohibited from performing Augmentee duties without the assistance of at least one qualified PAFSC 2A653 (or higher) member. Certified Egress Augmentees will not be authorized to sign the 'inspected by' portion of "Red X" discrepancies, nor will they sign for any task for which they were not specifically qualified IAW the Egress NCOIC's Augmentee training plan. Furthermore, augmentees are prohibited from training non-2A6X3 personnel on the Augmentee tasks for which they become qualified. Augmentees will be briefed and sign acknowledging their understanding. Violations of these prohibitions will result in immediate decertification IAW **paragraph 4.4.3.2.6.3** of this instruction and revocation of Augmentee certification. Egress NCOICs are required to report all violations through their chain of command to AFGSC/A4M. In the event these prohibitions are violated, aircraft will be "Red-X'd" until such time that qualified 2A6X3 personnel may investigate and inspect the work performed.

4.4.3.2.6.7. **(Added-AFGSC)** Augmentee Exception: When away from home station, and 2A6X3 personnel are not available, MGFE/CC's may direct certified egress augmentees to clear "Red X" discrepancies for which they have been qualified, if notification is provided to the home station MXG/CC. Refer to TO 00-20-1 for home station acceptance requirements when Egress maintenance is performed solely by Augmentees away from home station. This provision will not be used as a planning factor when determining personnel requirements for deployment or TDY and should only be invoked in extreme circumstances.

4.4.3.2.6.8. **(Added-AFGSC)** Augmentee Documentation Requirements.

4.4.3.2.6.8.1. **(Added-AFGSC)** Biannually, the Egress NCOIC will review records and publish via a Memorandum for Record (MFR) a listing of certified current Egress Augmentees. Members listed on this MFR will remain current through the applicability of the memorandum. This memorandum will include:

4.4.3.2.6.8.2. **(Added-AFGSC)** Augmentee's Rank/Name.

4.4.3.2.6.8.3. **(Added-AFGSC)** Augmentee's Employee Number.

4.4.3.2.6.8.4. **(Added-AFGSC)** Augmentee's MMCL prerequisite completion date.

4.4.3.2.6.8.5. **(Added-AFGSC)** Augmentee's task fully qualified date.

4.4.3.2.6.8.6. **(Added-AFGSC)** Due date for Augmentee's explosive safety refresher training.

4.4.3.2.6.8.7. **(Added-AFGSC)** Due date for Augmentee's Egress recertification.

4.4.3.2.6.8.8. **(Added-AFGSC)** Statement from Egress NCOIC indicating that the prohibitions listed in **paragraph 4.4.3.2.6.6** were briefed and understood by the augmentee.

4.4.3.2.6.8.9. **(Added-AFGSC)** Expiration date of the memorandum. In the event the listing expires without a replacement, the MFR may continue to be considered current so long as none of the Augmentee training dates have expired.

4.4.3.2.6.8.10. **(Added-AFGSC)** Completed MFR will be distributed to MXS Production, BGS/AMXS Production, MOC, Quality Assurance, and the Command Egress Manager (AFGSC/A4MA).

4.4.3.2.6.9. **(Added-AFGSC)** Augmentees are to forward evidence of completed training to the Egress NCOIC. Egress NCOICs will maintain a record of individual Augmentee training listed above, to include 797s (if used) and Computer Based Training (CBT) certificates, so long as the Augmentee remains on the roster.

4.4.3.2.6.10. **(Added-AFGSC)** For ease of tracking, units may elect to assign course codes in the MIS to track MMCL compliance, annual explosive safety, and Egress Augmentee recertification. This will not be used to circumvent the requirement to publish and distribute a consolidated list of current Augmentees.

4.4.3.2.7. Review and validate all egress familiarization training documents at least every 24 months. **(T-3)**

4.4.3.2.8. Ensure the egress Time Change Item (TCI) data in the MIS is accurate. **(T-3)**

4.4.3.2.8.1. Ensure automated data products will be updated whenever an egress item is replaced to ensure the annual TCI forecast is correct. **(T-3)**

4.4.3.2.8.2. Ensure separate databases are not used to manage the egress TCI program. **(T-3)**

4.4.3.2.8.3. Ensure component background information is provided to PS&D to include a list of all components having multiple part numbers with a different service life. **(T-3)**

4.4.3.2.9. Reconcile and verify each aircraft's egress data annually with PS&D. **(T-3)**

4.4.3.2.9.1. Document the annual verification on the AF Form 2411, *Inspection Document* maintained in the aircraft jacket file. **(T-3)**

4.4.3.2.10. Establish local egress systems documentation requirements: **(T-3)**

4.4.3.2.10.1. Egress Section will maintain an egress tail number binder for each assigned aircraft. **(T-3) Note:** This binder should not be confused with the aircraft jacket file of historical records maintained by PS&D but serves to standardize the format for maintaining egress documentation requirements across AF egress shops. As a minimum the binder will include:

4.4.3.2.10.1.1. Binder Spine - Aircraft assigned Serial Number. **(T-3)**

4.4.3.2.10.1.2. Front Cover - Delayed Discrepancies. **(T-3)**

4.4.3.2.10.1.3. Tab A – PRA or 5th Gen equivalent (Cross reference sheet stating digital location of data). **(T-3)**

4.4.3.2.10.1.4. Tab B – Completed In-Shop Maintenance Flow Sheet(s). **(T-3)**

4.4.3.2.10.1.5. Tab C – Completed Major Inspection Flow sheet(s) (for example, 36 month), or equivalent (if Mission Design Series applicable). **(T-3)**

4.4.3.2.10.1.5.1. Annotate pull check/inspection results on the flow sheet. **(T-3)**

4.4.3.2.10.1.6. Tab D – Egress Configuration Screen (IMDS 257 or 5th Generation equivalent), current manual Cartridge Actuated Device/Propellant Actuated Device (CAD/PAD) collection sheets. **(T-3)**

4.4.3.2.10.1.7. Tab E – Completed Time Change Item Replacement Sheets, for example, locally generated or equivalent. **(T-3)**

4.4.3.2.10.1.8. Tab F – Significant Historical Data (AFTO 95 or equivalent (cross reference to MIS maybe used), Depot/Program Depot Maintenance (PDM) package, -107 TAR or ETARs). **(T-3)**

4.4.3.2.10.1.9. Tab G – Misc. (example, PAIR, Extension Letters). **(T-3)**

4.4.3.2.10.1.10. Tab H AF Form 2411, *Inspection Document*. **(T-3)**

4.4.3.2.11. A certified egress inspector (for example, Red X, IPI certified and tracked on the SCR IAW **Table 11.1**) will inspect any integral part of the egress system when any maintenance other than a visual inspection is performed. **(T-3)**

4.4.3.2.11.1. The inspection must be an egress final inspection unless another inspection is prescribed by technical data. **(T-3)**

4.4.3.2.11.2. Egress personnel will conduct an egress final every 30 days on ejection seats that have integrated personnel/recovery parachutes and/or survival kits as part of the seat if prescribed by technical data. **(T-3)**

4.4.3.2.12. Egress Sections may store spare parachutes and survival kits for use in responding to Red Ball and unscheduled maintenance events.

4.4.4. Fuel Systems Section. The Fuel Systems Section repairs, functionally checks, and inspects aircraft fuel systems, fuel tanks, hydrazine systems, in-flight refueling receptacle systems, and related components. This section also performs maintenance on AME external fuel tanks, Conformal Fuel Tanks, and Weapons Bay Tanks and provides temporary storage for Conformal Fuel Tanks, and Weapons Bay Tanks.

4.4.4.1. The Fuels Systems Section will:

4.4.4.1.1. Maintain serial number inventory accountability for all removable external fuel tanks IAW DAFI 21-103. **(T-3)**

4.4.4.1.2. Purge and preserve fuel tanks for storage and shipment. **(T-3) Note:** LRS is responsible for the storage, delivery, and shipment of fuel tanks in their possession.

4.4.4.1.3. Establish a local Memorandum of Agreement (MOA) or Memorandum of Understanding (MOU) (MXS with squadron or equivalents) governing the storage, issue, receipt, and inventory control of in-use removable external fuel tanks. **(T-3)**

4.4.4.1.4. Perform all maintenance and inspections on WRM fuel tanks. **(T-3)**

4.4.4.1.4.1. Meet quarterly with installation War Reserve Materiel Officer/WRM Non-Commissioned Officer (NCO) and LRS representatives to review inspection criteria for stored WRM tanks, schedule tank inspections and maintenance, and report discrepancies identified during WRM monthly walk-through inspections. **(T-3)**

4.4.4.2. In addition to the common responsibilities outlined in **Chapter 2**, the Fuel Systems Section NCOIC/Chief will:

4.4.4.2.1. Establish controls to prevent unauthorized entry into fuel cell and hydrazine repair areas. **(T-3)**

4.4.4.2.2. Provide required qualification training to all personnel who enter aircraft fuel tanks and/or open fuel tank areas to perform maintenance or to provide assistance. **(T-3)**

4.4.4.2.3. When required, ensure Hydrazine Response Teams are formed. The HRT supervisors must possess 2A6X4 AFSC. Team members can be any qualified personnel provided they are certified IAW with TO 00-25-172, *Ground Servicing of Aircraft and Static Grounding/Bonding*, TO 00-105E-9, *Aerospace Emergency Rescue and Mishap Response Information*, TO 42B1-1-18, *General Procedures for Handling of H-70*, and review MDS-specific TOs and MAJCOM/Lead Command directives for additional information on hydrazine hazards and management. **(T-2)**

4.4.4.2.3.1. Ensure initial and refresher hydrazine safety training is completed for all hydrazine response team members IAW TO 42B1-1-18.

4.4.4.2.3.2. Integrate Hydrazine Response Team responsibilities into the CDDAR Program and local In-Flight Emergency (IFE) functional checklists (as applicable). **(T-3)**

4.4.4.2.4. Perform safety inspections on facilities to ensure open tank repair areas, and equipment used for open fuel tank or hydrazine maintenance meet MDS-specific TOs, TO 42B1-1-18 and TO 1-1-3, *Inspection and Repair of Aircraft Integral Tanks and Fuel Cells* requirements.

4.4.4.2.5. Establish a Confined Space Entry Program IAW TO 1-1-3 and AFMAN 91-203.

4.4.4.2.6. Establish a Respiratory Protection Program IAW AFI 48-137.

4.4.4.2.6.1. All respiratory training requirements are documented on AF Form 55 or equivalent IAW DAFI 91-202.

4.4.4.3. Ensure assigned personnel receive periodic physical examinations as established by the base medical service as required IAW TO 1-1-3. Track periodic physical examinations in the MIS. **(T-3)**

4.4.5. Hydraulic Section. The Hydraulic Section performs on- and off-equipment maintenance on pneumatic and hydraulic systems, components (except environmental and egress systems) and provides maintenance support for SE and test equipment. The Hydraulic Section also maintains hydraulic test stands, pumping units, and associated components.

4.4.5.1. The Hydraulic Section will:

4.4.5.1.1. Perform maintenance on munitions loading and handling equipment with discrepancies that exceed the munitions flight repair capabilities.

4.4.5.1.2. Maintain and inspect refueling drogues, booms, and refueling receptacle systems for large aircraft.

4.4.5.1.3. Repairs, overhauls, and bench checks flight control, landing gear, and hydraulic power system components (such as, brakes, struts, accumulators, reservoirs, actuators).

4.4.5.1.3. **(AFGSC)** May **l**ocal manufacture and test hose assemblies and test rigid tube assemblies.

4.5. Aerospace Ground Equipment (AGE) Flight. The AGE Flight is normally organized as a consolidated maintenance unit (repair, inspection, and servicing sections). The AGE Flight is responsible for providing powered and Non-Powered AGE (NPA) as defined in TO 00-20-1 to support both aircraft and non-aircraft weapon systems.

4.5.1. The AGE Flight will:

4.5.1.1. Maintain and inspect AGE, IAW TO 00-20-1, and equipment specific TOs in support of sortie production and back shop maintenance activities.

4.5.1.1. **(AFGSC)** AGE does not maintain propulsion support equipment, vehicle support equipment, non-powered dock stands, avionics support equipment, or non-powered Munitions Materiel Handling Equipment. **(T-2) Exceptions:** Launcher-Module Handling Adapter (LMHA), Manually Operated Lift Truck (MOLT), and ram assemblies.

4.5.1.2. Pick up, service, deliver, repair, and perform approved modifications, TCTOs, inspect AGE and perform corrosion control tasks.

4.5.1.2.1. **(Added-AFGSC)** Using organizations are responsible to inspect and service oil and hydraulic servicing carts prior to use. Servicing carts will be located in the using organization unless maintenance or inspection requirements dictate returning the carts to AGE flight.

4.5.1.3. Utilize AF Form 864, *Daily Requirement and Dispatch Record*, or MAJCOM-approved electronic product to record all equipment pickup and delivery.

4.5.1.4. Perform chassis, enclosure, and trailer maintenance on gaseous and cryogenic servicing units.

4.5.1.5. Manage maintenance and inspection scheduling activities for flight-maintained equipment. **Note:** Maintain oversight of additional requirements for assigned Nuclear Certified Equipment IAW AFI 63-125.

4.5.1.6. Safeguard any Item Unique Identification (IUID) marks during maintenance activities to the extent possible. **(T-3)** In the event the Unique Item Identifier (UII) is damaged during maintenance activities, the AGE Flight notifies the responsible Equipment Custodian.

4.5.1.7. **(Added-AFGSC)** Ensure AGE is used solely to support the servicing, maintenance, handling, and mission generation of Mission Design Series (MDS) related weapons systems based on applicable Allowance Source Codes (ASC). Any use outside of these activities, regardless of duration, requires MXG/CC coordination and/or approval. Notify MAJCOM A4MA for situational awareness of equipment. **(T-2)**

4.5.1.8. **(Added-AFGSC)** Ensure semi-annually that the most current MEL and any known Enterprise Logistics Management System (ELMS) (or current MIS for support

equipment) inventory discrepancies are submitted to the MAJCOM AGE functional managers no later than 30 April and 31 October.

4.5.2. AGE Flight Chief Responsibilities. In addition to the applicable Flight CC/Chief responsibilities in **Chapter 2**, the AGE Flight Chief will:

4.5.2.1. Review and coordinate the AGE MEL annually with applicable Maintenance Supervision. **(T-3)**

4.5.2.1.1. Provides copies of the approved MEL to the MOC. **(T-3)**

4.5.2.2. Track AGE status/scheduling daily using the MIS. **(T-3)** Once available and training is complete, DPAS M&U will be the MIS for tracking AGE Status and Scheduling. **(T-2)** Additional guidance for stand up and integration of DPAS M&U is available at: **https://usaf.dps.mil/teams/afdpassemis**.

4.5.2.2.1. Provide status and ETIC information to the MOC when it falls below MEL. **(T-3)**

4.5.2.3. Ensure newly assigned AGE receives acceptance inspections IAW TO 00-20-1. **(T-3)**

4.5.2.4. Control fuel dispensed from issue tanks IAW DAFI 23-201, *Fuels Management*.

4.5.2.5. Ensure the Uniform Repair and Replacement Criteria Program is implemented IAW TO 00-25-240 and TO 35-1-24.

4.5.2.6. Coordinate welding requirements with the Fabrication Flight Chief. **(T-3)**

4.5.2.7. Manage AGE CANN actions IAW **Chapter 9** and **Chapter 11**. **(T-3)**

4.5.2.8. Establish and monitor the AGE Operator Training Program and assist in the development of course control documents in conjunction with Maintenance Training (MT). **(T-3)**

4.5.2.9. Ensure an AGE Corrosion Control and Prevention Program is maintained and a field number system is established IAW TO 35-1-3, TO 1-1-8, TO 1-1-691, MAJCOM instructions, and equipment specific TOs.

4.5.2.10. Develop and implement a tracking system to prioritize complete repainting for AGE equipment based on a “worst is first” principle.

4.5.2.10.1. Coordinate with Fabrication Flight Chief for work beyond the AGE work center capability.

4.5.2.11. Ensure equipment is prepared for storage or shipment IAW TO 35-1-4, *Processing and Inspection of Support Equipment for Storage and Shipment*, and applicable end item TOs.

4.5.2.12. Submits annual transient aircraft landing data to the respective MAJCOM AGE functional manager by 1 February. Data will reflect previous year's TA aircraft landings by aircraft MDS and is obtained from local Transient Alert managing office.

4.5.2.13. Establish AGE sub-pools, as needed, in coordination with OSS’s Airfield Operations Flight.

4.5.2.14. Ensure AGE tow vehicles are two-way radio equipped, permanent or hand-held, to expedite AGE deliveries. **(T-3)** Ensure any permanent installation of radios are accomplished IAW AFI 24-302. **(T-3)**

4.5.2.15. **(Added-AFGSC)** Ensure tone-down procedures are followed as described in AFGSCI 21-105, *Corrosion Prevention and Control Program*. **(T-2)**

4.5.3. AGE Pro Super Responsibilities (if not assigned, the AGE Flight Chief will fulfill these responsibilities). The AGE Pro Super will:

4.5.3.1. Monitor the production of AGE Flight and recommend equipment/personnel adjustments to the AGE Flight Chief as required. **(T-3)**

4.5.3.2. Monitor adherence to AGE Flight's safety, training, and CTK programs. **(T-3)**

4.5.3.3. Monitor serviceability status of equipment parked in sub-pools. **(T-3)**

4.5.3.4. Monitor distribution, control, and condition of AGE Flight's assigned vehicles.

4.5.3.5. Monitor shop equipment for condition and documentation. **(T-3)**

4.5.4. AGE Production Support Section. The AGE Production Support Section provides administration and ancillary services for TO file maintenance, supply support, and fuels management. A full-time Materiel Management Journeyman/craftsman (AFSC 2S0X1) should be assigned to the AGE Production Support Section when the workload warrants. In addition to the applicable Section NCOIC/Chief responsibilities outlined in **Chapter 2**, the AGE Production Support Section NCOIC/Chief will:

4.5.4.1. Manage the AGE Flight's TO libraries IAW TO 00-5-1.

4.5.4.2. Manage the AGE Flight's tool storage and issue areas IAW **Chapter 8**. **(T-3)**

4.5.4.3. Manage the AGE Flight's TMDE program IAW TO 00-20-14 and AFMAN 21-113. **(T-3)**

4.5.4.4. Manage the AGE Flight's materiel management function IAW **Chapter 9** and AFI 23-101.

4.5.4.4.1. Pre-assembled part kits are authorized; if required, assemble from bench stock in minimum quantities necessary to support workload requirements.

4.5.4.5. Coordinate the AGE Flight's scheduling function with PS&D. **(T-3)** The AGE Production Support Section NCOIC/Chief will:

4.5.4.5.1. Maintain AGE historical records. **(T-3)**

4.5.4.5.2. Prepare an AGE scheduled maintenance plan and maintain a current equipment scheduling report for all assigned equipment. **(T-3)**

4.5.4.6. Manage the AGE Flight's organizational fuel tank(s) IAW DAFI 23-201.

4.5.4.7. Manage the AGE Flight's HAZMAT/ESOH programs IAW AFI 90-8XX series ESOH instructions and the AFI 32-70XX series environmental instructions.

4.6. Armament Flight. See AFMAN 21-206 for duties and responsibilities.

4.6.1. - 4.6.4.2. DELETED.

4.7. Avionics Flight. The Avionics Flight normally consists of some combination of; a Communication-Navigation Section, an Radio Frequency (RF) Multiplexing Section, an Instrument and Flight Control Systems (IFCS) section, a Weapons Control System Section, a Sensors Section, an Electronic Warfare System (EWS) Section, an Avionics Intermediate Section, a Computer Section, a Surveillance Radar Section, a Combat Systems Section, a Cryptographic Section, an Offensive Avionics Section, and a Cyber/Information Security Section. **Note:** Do not authorize additional manpower positions to form sections resulting from local management decisions.

4.7. (AFGSC) Avionics Flight. Avionics Sections may be organized with a section chief, Pro Super, repair monitors, team leaders, and repair team members. The section chief will have overall responsibility for the effective management of their assigned resources. If Avionics Sections are utilized, they will be published in the local supplement. Note: Duties may be combined.

4.7.1. Sections within the Flight are responsible for maintaining avionics systems and components and the associated test/support equipment. They perform authorized equipment repairs, TCTOs, component programming/reprogramming, troubleshooting, CND/BCS screening of line replaceable units (LRUs), sub-component removal and replacement, management, programming, and status reporting for assigned pods and SE, and in-work classified avionics systems component management. Repairs above and beyond those listed require approval from the appropriate approval authority (Lead Command, Depot).

4.7.2. Avionics Flight CC/Chief Responsibilities. In addition to the applicable Flight CC/Chief responsibilities listed in **Chapter 2**, the Avionics Flight CC/Chief will:

4.7.2.1. Support Wing EW system programming. **(T-3)**

4.7.2.2. Ensure control and storage of assigned AME IAW DAFI 21-103. Develop local procedures for control and storage of items not specified in -21 TOs. **(T-3)**

4.7.2.3. Ensure avionics POD status is updated in RAMPOD or approved MIS IAW DAFI 21-103. **(T-3)**

4.7.2.4. Ensure personnel do not make unauthorized or false transmissions on international distress frequencies IAW TO 31R2-1-251, *General Instructions-Transmission of False Distress Signals on Emergency Frequencies*. **(T-3)**

4.7.2.5. Ensure cryptography components are controlled and maintained IAW National Security Agency publications and directives for the functions performed. **(T-3)**

4.7.2.6. When applicable, determine maintenance responsibility for aircraft adapter group equipment. **(T-3)**

4.7.2.7. **(Added-AFGSC)** When applicable, appoint a Repair Network Node Manager for the Avionics Section. Update Repair Network CAP2 annually or as directed. Ensure Node Managers complete training per DAFI 20-117.

4.7.3. Section NCOICs will maintain AFTO Form 95, or equivalent, on selected, repairable, serialized components for which historical failure data will enhance repair. **(T-3)** Historical records are mandatory for SPRAM LRUs, and items asterisked in weapons system -6 TOs. Historical records will be maintained IAW TO 00-20-1.

4.7.3.1. The record will remain with the component anytime it is undergoing maintenance. **(T-3) Note:** Data is provided from these records, upon request, to the analysis function to aid in defining avionics maintenance problems and recommended solutions.

4.7.4. Avionics Flight's within established Repair Networks will collaborate with the Repair Network Manager (RNM) for maintenance constraint resolution. If the SMR code in the 4th position is "F" (I-Level Repair) will require RNM and all applicable stakeholders to determine next step or appropriate Action Taken Code to use when resolving the maintenance constraint.

4.7.5. Implement the “Bad Actor” program IAW TO 00-35D-54. The purpose of the Air Force Bad Actor Program is to identify serial-numbered items that enter the repair cycle at an abnormally high rate when compared to the total population of like assets and to repair them or remove them from the exhibit holding activity.

4.7.6. Repair Monitor Responsibilities. Monitors the status of items processed into the section for repair. Each shift may have a repair monitor assigned. Maintain records used by the repair monitor according to AFI 33-322. Each Repair Monitor will:

4.7.6.1. Process items into and out of the section, ensuring all documentation is accurate and complete. **(T-3)**

4.7.6.2. Advise the section NCOICs and Pro Supers of item status. **(T-3)**

4.7.6.3. Assist the section NCOICs in managing the DIFM program by complying with MAJCOM instructions to ensure ordered and received parts are documented; and uses, maintains, and files, management and computer records. **(T-3)** Repair Monitors will maintain and update a working copy of the D-23, *Repair Cycle Asset Management Listing*, sorted by location and detail number. **(T-3)**

4.7.6.4. Designate and maintain an AWP area, ensure accurate documentation, and submit supply assistance requests, as required. **(T-3)**

4.7.6.5. Track and monitor MICAP status for all assigned DIFM and parts affecting section repair capabilities using automated Integrated Logistics System -Supply (ILS-S) reports. **(T-3)**

4.7.6.6. Ensure the MIS is updated with current supply data, location changes and DIFM status changes. **(T-3)**

4.8. Fabrication Flight. The Fabrication Flight may consist of four sections; Aircraft Structural Maintenance (ASM), Metals Technology, Nondestructive Inspection (NDI), and Low Observable Aircraft Structural Maintenance (LOASM) and is responsible for performing on/off-equipment maintenance of systems and equipment.

4.8.1. Fabrication Flight CC/Chief Responsibilities. In addition to the applicable Flight CC/Chief responsibilities outlined in **Chapter 2**, the Fabrication Flight CC/Chief will:

4.8.1.1. Provide local manufacture capability to meet mission requirements and monitor all local manufacture work order requests. **(T-3)**

4.8.1.2. Coordinate AGE welding requirements with the AGE Flight Chief. **(T-3)**

4.8.1.3. Assist WG Corrosion Manager in efforts to ensure effective corrosion prevention and control requirements, wash rack procedures, and established paint schemes are

accomplished IAW TO 1-1-691, TO 1-1-8, TO 35-1-3, MAJCOM/Lead Command instructions, and MDS-specific TOs.

4.8.1.3. **(AFGSC)** Corrosion prevention, corrosion control requirements, wash rack procedures, and established paint schemes are prescribed in the AFGSCI 21-105.

4.8.1.4. Coordinate with squadron SUPTs or civilian equivalent to ensure assigned personnel rotation plans are established to comply with core task upgrade requirements. **(T-3)**

4.8.2. Aircraft Structural Maintenance (ASM) Section. Manages structural repair, corrosion control, Low Observable, inspection, damage evaluation, repair, manufacture, and/or modification of metallic, composite, fiberglass, plastic components, and related hardware associated with aircraft and SE. In addition to applicable Section NCOIC/Chief responsibilities in **Chapter 2**, the ASM Section NCOIC/Chief will:

4.8.2.1. Ensure appropriate resources are available to all personnel to chemically or mechanically inspect, remove, and treat corrosion on aircraft, engines, AGE, and components. **(T-3)**

4.8.2.2. Monitor the aircraft wash and corrosion inspection schedule in the weekly and monthly maintenance plans. **(T-3)**

4.8.2.3. Provide training and assistance to sections managing their own corrosion programs to include cleaning operations, corrosion prevention, inspection, removal, and treatment techniques. **(T-3)**

4.8.2.4. Develop maintenance procedures IAW **Chapter 11** of this instruction, DAFMAN 91-203, and ensure assigned ASM personnel are trained and qualified on aircraft intake maintenance. **(T-3)**

4.8.2.5. Review the Qualified Product List/Qualified Product Database for changes to cleaners that must conform to a MIL-Spec as specified in applicable TOs for aircraft wash rack. **(T-3)**

4.8.2.6. Stock supplies and equipment necessary to support aircraft and equipment washing, inspection, and treatment. **(T-3)**

4.8.3. Metals Technology Section. Inspects, repairs, services, manufactures, fabricates, performs heat treating, cleans, welds, and tests aircraft and equipment, components, and tools. In addition to responsibilities outlined in **Chapter 2**, the metals technology section NCOIC will:

4.8.3. **(AFGSC)** Ensure all journeyman, craftsman (SSgt and TSgt), or civilian equivalent welders assigned to the Aircraft Metals Technology Section are certified IAW TO 00-25-252 to perform welding operations in the following base metal groups: I (Carbon and Low Alloy Steel), II (Stainless Steels), IV (Aluminum Base Alloys). Additional metal groups can be added to support specific weapon system requirements through the unit supplement to this instruction if necessary. **(T-2)**

4.8.3.1. Ensure assigned welders are certified in all base metal groups prescribed by the MAJCOM Fabrication functional manager (or equivalent) IAW TO 00-25-252, *Aeronautical Equipment Welding*. **(T-3)**

4.8.3.1.1. Ensure assigned welders conducting Gas Tungsten Arc Welding, Gas Metal Arc Welding, or Shielded Metal Arc Welding repairs on support equipment are certified IAW TO 00-25-252.

4.8.3.1.2. Ensure welding proficiency is documented IAW TO 00-25-252.

4.8.3.2. Provide safety briefings stressing Arc radiation hazards. **(T-3)**

4.8.3.3. Ensure special tools, jigs, and fixtures are designed, fabricated, protected, and properly stored. **(T-3)**

4.8.3.4. **(Added-AFGSC)** Coordinate requests for an ALC or other qualified organization to qualify welders. If qualifications and certifications are accomplished locally, coordinate certification requirements with the Non-Destructive Inspection (NDI) Section to ensure X-Ray capability exists.

4.8.3.5. **(Added-AFGSC)** Ensure the Observing Official is a 7-level Aircraft Metals Technology technician or civilian equivalent welder and properly documents DD Form 2757, *Welding Examination Record*. The Observing Official will sign block 13.

4.8.3.6. **(Added-AFGSC)** Ensure a 7-Level Aircraft Metals Technology technician or civilian equivalent welder performs a complete visual inspection as the Testing Official. The Testing Official (not the NDI technician) will sign and date block 20.

4.8.3.7. **(Added-AFGSC)** Ensure a qualified NDI technician performs radiographic inspection and properly documents DD Form 2757. The NDI technician will complete blocks 14-18.

4.8.4. Nondestructive Inspection (NDI) Section. Performs NDI of aircraft, engines, AGE, other equipment and manages the Oil Analysis Program (OAP). Inspection findings are limited to a description of the size, location, and type of any defect discovered. NDI personnel do not make serviceability determinations except for "inspect only" TCTOs and if NDI actions constitute a completed maintenance action. In addition to the applicable Section NCOIC/Chief responsibilities in **Chapter 2**, the NDI Section NCOIC/Chief will:

4.8.4.1. Ensure OAP requirements are accomplished (if applicable to assigned MDS) IAW AFI 21-131, Joint Oil Analysis Program and **Chapter 11**. **(T-3)**

4.8.4.1.1. If the NDI laboratory providing OAP support is not located on the same base as the supported unit, or the supported unit does not have NDI/OAP personnel assigned, assign the OAP responsibilities to the owning organization IAW TO 33-1-37-1, *Joint Oil Analysis Program Volume II* and TO 33-1-37-3, *Joint Oil Analysis Program Laboratory Manual, Volume III*, TO 33-1-37-4, *Joint Analysis Program Manual, Volume IV*. The owning organization provides samples in an expeditious manner to the supporting OAP laboratory.

4.8.4.1.1.1. The owning organization will establish collection points and procedures to receive and forward OAP samples to the supporting laboratory, monitor sample collection, assign control numbers, and provide blocks of sample control numbers for use in other squadrons. **(T-3)**

4.8.4.2. Advise Maintenance Supervision, MOC and the owning work center of abnormal OAP trends. **(T-3)**

4.8.4.3. Ensure capability exists to perform optical, dye-penetrant, magnetic particle, ultrasonic, eddy current, radiographic, and special inspections as required. **(T-3)**

4.8.4.4. Ensure process control procedures IAW TO 33B-1-2, *Nondestructive Inspection General Procedures and Process Controls* are completed at the required or established frequency. **(T-3)**

4.8.4.5. Establish technique files using AFTO Form 242, *Nondestructive Inspection Data*, and TO 33B-1-1, *Nondestructive Inspection Methods Basic Theory*. **(T-3) Note:** Locally developed inspection techniques for use on aircraft and their components will be approved by the responsible ALC NDI manager prior to use. All other non-aircraft related AFTO Form 242 established techniques may be approved by the lab Chief.

4.8.4.6. Maintain coordination with the base medical service that provides occupational physicals, emergency treatments, film badge services, and acts as radiographic advisors IAW DAFMAN 48-125, *Personnel Ionizing Radiation Dosimetry*, and TO 33B-1-1.

4.8.4.7. Ensure a Radiation Safety Program is established IAW TO 33B-1-1.

4.8.4.8. Control and dispose of radiographic silver-bearing materiel IAW AFI 23-101.

4.8.4.9. Ensure radiographic film files and computed radiography files contain, as a minimum:

4.8.4.9.1. The last complete set of radiographs taken by owning organization, for each assigned aircraft and engine by serial number or identification number. **(T-3)**

4.8.4.9.2. The name of the person who interpreted the radiography. **(T-3) Note:** Radiography identification procedures will be followed IAW TO 33B-1-1.

4.8.4.9.2.1. Ensure the person interpreting the film also initials the set of radiographs or a locally developed interpretation worksheet, as applicable. **(T-3)**

4.8.4.9.3. All NDI radiographic film exposures, to include paper, will be filed and maintained for all One Time Inspection (OTI), TCTO, -6 TO, -9 TO, and -36 TO inspection requirements. **(T-3)** The NDI Section NCOIC/Chief will ensure disposition of radiographic film IAW Air Force Records Disposition Schedule located at **https://afrims.cce.af.mil. (T-3)**

4.8.4.10. Ensure all NDI technicians are certified IAW TO 33B-1-1.

4.8.4.11. **(Added-AFGSC)** Ensure accurate oil analysis data is distributed to the central Air Force database by the 15th and last day of every month.

4.8.4.12. **(Added-AFGSC)** Ensure all deployable spectrometers are properly secured and protected before being deployed out of the OAP Laboratory.

4.8.4.13. **(Added-AFGSC)** Perform and document daily (every duty day) Standardization checks IAW applicable technical orders on all assigned spectrometers. **Exception:** 3 duty days prior to deployment for a specific spectrometer and 3 duty days after receipt of a spectrometer returning from deployment.

4.8.4.14. **(Added-AFGSC)** Ensure all assigned spectrometers are left in standby mode when analysis is not being conducted.

4.8.4.15. **(Added-AFGSC)** Develop a local checklist for analyzing correlation samples, checklist will be developed IAW TO 00-5-1.

4.8.4.16. **(Added-AFGSC)** Ensure all assigned oil analysis spectrometers are Joint Oil Analysis Program approved and certified IAW TO 33-1-37-1, *Joint Oil Analysis Program Laboratory Manual, Vol I, Introduction, Theory, Benefits, Customer Sampling Procedures, Programs and Reports*.

4.8.4.17. **(Added-AFGSC)** Request contractor repair through the Air Force OAP Office whenever an oil analysis spectrometer cannot be repaired locally or is out of service due to maintenance for more than 24 hours.

4.8.4.18. **(Added-AFGSC)** AFGSC/A4M will designate the Fabrication MAJCOM Functional Manager (MFM) as the NDI/OAP program manager. The designated program manager will ensure responsibilities outlined in AFI 21-131, *Joint Oil Analysis Program* in **paragraph 4.2**. **(T-2)**

4.8.4.19. **(Added-AFGSC)** Comply with contingency operations in TO 33-1-37-2, *Joint Oil Analysis Program Laboratory Manual, Vol II, Spectrometric and Physical Test Laboratory Operating Requirements and Procedures*, when no back up oil analysis spectrometer is available locally.

4.8.4.20. **(Added-AFGSC)** AFGSC/A4MA is responsible for the overall LOASM program administration within the command. AFGSC/A4MA will designate the Fabrication MAJCOM Functional Manager (MFM) as the LOASM program manager. **(T-2)**

4.8.5. Low Observable (LO) Aircraft Structural Maintenance Section. LO ASM Section manages structural repair, corrosion control, composite repair, LO coatings. **Note:** The Fabrication Flight CC/Chief will determine which tasks listed in **Paragraph 4.8.2** in this instruction (ASM Section) will be applicable to this section based on flight configuration. In addition to applicable Section NCOIC/Chief responsibilities in **Chapter 2**, the LO ASM Section NCOIC/Chief will:

4.8.5.1. Provide inspection, damage evaluation, repair, manufacture, and/or modification of LO components, and related hardware associated with aircraft. **(T-3)**

4.8.5.2. Ensure appropriate resources are available to perform all LO related tasks. **(T-3)**

4.8.5.3. Stock supplies and equipment necessary to support aircraft inspection, and treatment. **(T-3)**

4.8.5.4. Monitor the inspection schedule in the weekly and monthly maintenance plans. **(T-3)**

4.8.5.5. Ensure protective/LO coatings are applied to aircraft, AGE, applicable munitions, and components IAW applicable TOs. Ensure protective/LO coatings are applied IAW local, state, and federal environmental directives. **(T-0)**

4.8.5.6. Provide training and assistance to sections managing their own LO programs. **(T-3)**

4.8.5.7. **(Added-AFGSC)** Ensure no other maintenance is accomplished on aircraft, equipment, or within environmentally controlled/cordoned off areas when hazardous/toxic

materials are in use that requires the use of specialized personal protective equipment. In the event specialized respiratory protection equipment is required, personnel will be properly fitted for the equipment and trained in its use IAW AFI 48-137. **(T-2)**

4.9. Maintenance Flight. May consist of Repair and Reclamation, Wheel and Tire, Inspection, and TA Sections.

4.9.1. The Maintenance Flight CC/Chief will comply with the common Flight CC/Chief responsibilities in **Chapter 2** and locally established management requirements. **(T-3)**

4.9.1. **(AFGSC)** Maintenance Flight will ensure compliance with CDDAR program responsibilities IAW **Chapter 11** of this instruction. **(T-2)**

4.9.2. Repair and Reclamation Section. When established, removes, replaces, and rigs flight control surfaces/systems on assigned aircraft. Troubleshoots, rigs, and replaces landing gears, actuated doors, canopies, and associated equipment requiring component maintenance beyond the capability of other activities. MAJCOM or MXG/CC may identify delineation of complex tasks to optimize maintenance capability in supplements or addendums to this DAFI as required.

4.9.2.1. Repair and Reclamation Section, when established, will remove, install, and repair towed targets and airborne reel pods. **(T-3)**

4.9.3. Wheel and Tire Section. Manages the build-up, repair, test, and storage of wheel and tire assemblies and components. Wheel and Tire Section will:

4.9.3.1. Degrease and disassemble wheel components for NDI inspection IAW TO 4W-1-61, *Maintenance and Overhaul Instruction - All Types Aircraft Wheels*, prior to processing through the ASM and NDI Sections.

4.9.3.2. Clean, inspect, and properly store (do not co-mingle) wheel bearings. **(T-3)**

4.9.4. Aircraft Inspection Section. Performs aircraft PH, PE, ISO, or letter check inspections. **Note:** Section may be divided into separate elements for each type aircraft maintained. In addition to the applicable Section NCOIC/Chief responsibilities in **Chapter 2**, the Inspection Section NCOIC/Chief will:

4.9.4.1. Ensure assigned non-powered SE (such as, dock stands) is maintained. **(T-3)**

4.9.4.2. Review inspection schedules and ensure dock teams are available to meet inspection needs. **(T-3)**

4.9.4.3. Develop standardized inspection flow plan to aid in managing the inspection progress and to control dock personnel and support specialists. **(T-3)**

4.9.4.3.1. DELETED.

4.9.4.3.2. Inspection Section NCOIC/Chief will ensure flow plan data remains current with -6 TO requirements. **(T-3)**

4.9.4.4. Inform the MOC and owning agency of all MICAP parts. **(T-3)**

4.9.4.5. Provide PS&D with an inspection document record upon completion of the inspection. **(T-3)**

4.9.4.5. **(AFGSC)** Units that use an alternate means for maintenance discrepancy documentation (gig-sheets, work control documents (WCD), locally developed lists, etc.) must ensure that these documents are annotated and filed IAW TO 00-20-1 and applicable supplements.

4.9.4.6. Ensure components are tagged with an AFTO Form 350, *Reparable Item Processing Tag*, IAW TO 00-20-2.

4.9.4.6.1. Ensure serially controlled components are reinstalled on the same aircraft and position from which they were removed. **(T-3) Exception:** If it is absolutely necessary to install serially controlled components in a different position, the Inspection Section NCOIC/Chief will notify PS&D to update the records.

4.9.4.7. **(Added-AFGSC)** Utilize a status tracker (either paper or digital) to display in-progress and scheduled inspections, ensuring the status tracker shows the following information:

4.9.4.7.1. **(Added-AFGSC)** Aircraft type.

4.9.4.7.2. **(Added-AFGSC)** Aircraft serial number.

4.9.4.7.3. **(Added-AFGSC)** Inspection type and when due (sequence).

4.9.4.7.4. **(Added-AFGSC)** Scheduled in (date and time).

4.9.4.7.5. **(Added-AFGSC)** Actual start (date and time).

4.9.4.7.6. **(Added-AFGSC)** Scheduled out (date and time).

4.9.4.7.7. **(Added-AFGSC)** Remarks (status of aircraft, delays, possible MICAP conditions, etc.).

4.9.4.7.8. **(Added-AFGSC)** Safety/danger considerations (power/hydraulic applications, stress panels removed, aircraft on jacks, Weight and Balance, etc.).

4.9.4.8. **(Added-AFGSC)** Develop a plan to ensure maintenance is documented if MIS-CDB is down; units may use an AFTO 367, *Aircraft Discrepancy Gig Sheet*, or a locally developed/approved worksheet. Documentation must be tracked to ensure all discrepancies have been cleared or transferred to AFTO Form 781-series /MIS IAW TO 00-20-1 and TO 00-20-2. These documents will be treated the same as aerospace vehicle documents and filed with the inspection historical documents.

4.9.5. Transient Aircraft (TA) Section. Recovers, services, inspects, maintains, and launches transient aircraft. Transient aircraft are those aircraft not assigned to a base that are enroute from one location to another that may require routine servicing. Aircraft are not considered transient aircraft when deploying to, staging from, or departing from any location for the purpose of flying sorties or conducting training, either with or without the necessary maintenance support from the aircraft's home base. MOC coordinates specialist support for transient aircraft through appropriate squadrons. For off-station recovery procedures refer to owning MAJCOM instructions and command-to-command agreements. In addition to the applicable Section NCOIC/Chief responsibilities outlined in **Chapter 2**, the TA Section NCOIC/Chief will:

4.9.5.1. Recover and deliver all deceleration chutes for assigned, transient, and tenant aircraft to the AFE. **(T-3)**

4.9.5.2. Complete reimbursement documentation. **(T-3)**

4.9.5.2.1. AFTO Form 726, T*ransient Aircraft Service Record*, may be used for documenting maintenance servicing requirements and necessary billing information and is prescribe in TO 00-20-1.

4.9.5.3. Record arrivals and departures of transient aircraft on AF Form 861, *Base/Transient Job Control Number* Register or locally approved form if it captures all AF Form 861 fields. **(T-3)** TA Section NCOIC/Chief (or equivalent) will:

4.9.5.3.1. Assign each aircraft a single Event Identification Description (EID) for all support general work performed by TA. **(T-3)**

4.9.5.3.2. Enter, as a minimum, "P" for park, "I" for inspect, "S" for service, "L" for launch, and "E" for EOR in the job description/remarks block. **(T-3)**

4.9.5.3.3. Forward completed AF Form 861 for contracted TA activities to the COR monthly. **(T-2)** The COR forwards completed forms to the applicable contracting officer managing the TA contract for inclusion in the contract file.

4.9.5.3.4. Route the AF Form 861 for non-contracted TA activities to the Maintenance Flight CC/Chief for review. **(T-3)**

4.9.5.3.4.1. After review, the TA Section NCOIC/Chief will file AF Form 861 for a minimum of 1 year. **(T-3)**

4.9.5.3.4.2. AF Form 861 may be used as a reference to quantify tasked performed to validate manpower and equipment requirements against current AF standards.

4.9.5.4. Close out support general EIDs daily. **(T-3)**

4.9.5.4.1. Use the same last four digits on subsequent days for the same aircraft.

4.9.5.4.2. Use a separate EID for each discrepancy that is not support general.

4.9.5.5. Ensure that when a FCF is required on transient aircraft, QA at the transient base serves as the focal point and ensures all FCF requirements are completed. **(T-3)**

4.9.5.5.1. DELETED.

4.9.5.5.2. If no off-station agencies exist, owning MXG/CC and owning OG/CC will issue guidance directly to the aircraft commander and off-station maintenance personnel. **(T-3)**

4.9.5.6. Supervise maintenance performed by assigned personnel on transient aircraft. **(T-3)**

4.9.5.7. Maintain the appropriate TOs for aircraft that can be expected to transit the function on a regular basis. **(T-3)**

4.9.5.8. Ensure personnel are trained and strictly adhere to oil sample requirements specified in the respective -6 TO. **(T-3)**

4.9.5.9. Ensure personnel authorized to run engines are qualified IAW **Chapter 11**.

4.9.5.9.1. Request the aircrew to run engines if TA or maintenance personnel are not authorized.

4.9.5.9.2. If qualified aircrew members are not available, contact MOC to request assistance from the home station.

4.9.5.10. Ensure transient aircraft status changes are reported to MOC. **(T-3)** If support is required, the MOC notifies the home station for support.

4.9.5.11. Ensure EOR procedures for transient aircraft are developed IAW TO 00-20-1.

4.9.5.12. Ensure procedures exist for required weapons loading actions on transient aircraft, transient aircraft impulse cartridge tracking and storage, and weapons "safing" equipment requisition and maintenance for frequently transiting aircraft. **(T-3)**

4.9.5.12.1. Arming, de-arming and munitions unloading/loading operations on transient aircraft will be performed by a weapons load crew certified/qualified on the munitions and aircraft. **(T-3)**

4.9.5.12.2. DELETED.

4.9.5.12.2.1. In such cases, the aircrew will be available for consultation on aircraft peculiarities. **(T-3)**

4.9.5.12.2.2. If these criteria cannot be met, request assistance from higher headquarters.

4.9.5.13. Ensure checklists exist to ask pilots about explosive egress systems pertaining to unfamiliar aircraft that do not normally transit their base. **(T-3)**

4.9.5.13.1. Aircrew members remove and install flight status safety pins on aircraft when transient maintenance personnel are not qualified.

4.9.5.13.1.1. DELETED.

4.9.5.13.1.2. If TA cannot accomplish the required inspections, servicing, or repairs because of a lack of qualified personnel, facilities, or materiel (or there is no TA support available), and the transient aircraft commander does not wish to continue the flight without accomplishment of these items, the transient aircraft commander is responsible for requesting assistance through the appropriate external organizations.

4.9.5.14. **(Added-AFGSC)** Ensure aircraft intake inspections are performed on transient aircraft IAW MDS -6 TO requirements.

4.9.5.15. **(Added-AFGSC)** Ensure personnel are trained and strictly adhere to Master Chip Detector (MCD) inspection requirements specified in the respective TOs. **(T-2)**

4.10. Munitions Flight. Controls, accounts for, stores, ships, receives, inspects, maintains, assembles, and delivers conventional, precision guided and nuclear munitions. Manages and maintains all assigned tools, test and munitions handling equipment. Refer to AFI 21-2XX series instructions for specific guidance. **Note:** Munitions may be part of the MXS or established in a Munitions Squadron IAW AFMAN 21-200.

4.11. Propulsion Flight. Maintains aircraft engine propulsion units, propulsion components, and propellers. Performs engine/module/accessory disassembly, inspection, assembly, test, and repair. Responsible for Jet Engine Intermediate Maintenance (JEIM); Engine Test Stands (ETS) and Noise Suppression Systems (NSS); accessory and Quick Engine Change (QEC) repair; small gas turbine; module/accessory repair section; support equipment; and turboprop/turbo-shaft repair, engine PH/ISO inspections, as required. Sections may be combined or grouped at the discretion of the squadron commander. When an engine CRF is co-located with an operational wing, a MOA or MOU may be developed to clarify mutual support responsibilities. In addition, the flight will be the focal point for common propulsion support equipment, for example, flexible borescopes, engine trailers and download equipment.

4.11.1. In addition to the applicable Flight CC/Chief responsibilities in **Chapter 2**, the Propulsion Flight CC/Chief will:

4.11.1.1. Perform as the wing focal point for propulsion maintenance programs, focusing on continuity, compliance, and standardization, provide advice to wing leadership on propulsion issues and monitor all aspects of wing propulsion maintenance program. **(T-3)**

4.11.1.2. Act as the wing 2A6X1 AFSC functional manager and provide technical guidance to maintain propulsion systems to support the wing mission. **(T-3)**

4.11.1.3. Coordinate with Engine Manager (EM) and organization leadership to support War Readiness Engine (WRE) requirements. **(T-3)**

4.11.1.3.1. Track the status of ready spare engines using a visual display or automated product showing serial number, configuration (type and position, if applicable), time remaining until next scheduled engine removal, overhaul or reconditioning, preservation date, type accomplished, re-preservation due date, OAP code (if applicable), and remarks. **(T-3)**

4.11.1.4. Review production data to ensure propulsion units and components processed through the flight are repaired and functionally checked IAW TO 2-1-18, *Aircraft Engine Operating Limits and Factors*, including QEC configuration when applicable. **(T-3)**

4.11.1.5. Coordinate with the EM to ensure accurate engine and equipment status reporting IAW **Chapter 14**, DAFI 21-103, AFMAN 20-116, AFPAM 63-129, and TO 00-25-254-1.

4.11.1.5.1. **(Added-AFGSC)** Propulsion Flight, Maintenance Flight, and UH-1/MH-139 contract maintenance within Maintenance Operations Flight (MOF) will coordinate with the EM to ensure accurate engine status reporting.

4.11.1.6. Develop guidelines to comply with AF and wing OAP requirements IAW 33-series TOs and **Chapter 11**. **(T-3)**

4.11.1.7. Review/analyze all unscheduled engine or module removals and ETS rejects. **(T-3)**

4.11.1.7.1. Review/analyze major component failure trends. **(T-3)**

4.11.1.8. Ensure in-shop CANN actions are accomplished IAW local procedures, **Chapter 9**, **Chapter 11**, and TO 00-20-2.

4.11.1.8.1. Ensure local procedures are coordinated with Engine Management (EM) to ensure sufficient time remains on TCIs prior to CANN action approval. **(T-3)**

4.11.1.9. Coordinate with base civil engineering to provide maintenance on NSS and ETS supporting structures that are categorized as real property. **(T-3)** If the wing or squadron is a tenant, incorporate this maintenance requirement into the host-tenant support agreement. **(T-3)**

4.11.1.9.1. Ensure NSS and/or ETS repair discrepancies that exceed the base repair capability are reported in Web Applications Software Product (WASP). **(T-3) Note:** Entering repair requirements into WASP establishes official repair request and ensures visibility to MAJCOM and SE Product Group Manager at Robins AFB (AFLCMC/WN).

4.11.1.10. Ensure an uninstalled engine run qualification and certification program is established IAW **Chapter 11**.

4.11.1.11. Ensure specialized and long-life shipping devices and containers are accounted for and maintained in a serviceable condition IAW AFI 23-101 and TO 00-85-20, *Engine Shipping Instructions*.

4.11.1.12. Ensure engines and engine components removed from crash damaged aircraft are correctly dispositioned for termination IAW DAFI 21-103 and disposed of IAW AFI 23-101.

4.11.1.13. Ensure an engine flexible borescope certification and blade-blending certification program, for each Type, Model, Series (TMS) possessed, is established IAW **Chapter 11**.

4.11.1.14. Monitor scheduled and unscheduled engine removals to balance Propulsion Flight workload with production capability and coordinate with EM section to program engine removals for the weekly and monthly maintenance plans. **(T-3)**

4.11.1.14.1. Coordinate with EM to develop a 6-month plan to smooth surges in the engine maintenance workload. **(T-3)**

4.11.1.14.1.1. Use automated methods to develop the 6-month plan and include scheduled engine removals for TCIs, PE, TCTOs and a projected unscheduled removals factor.

4.11.1.14.1.2. Ensure Reliability-Centered Maintenance principles IAW AFMAN 20-116 are followed. **(T-3)**

4.11.1.15. Ensure Engine Automated Work Package (EAWP) user permissions mirror current training and certification authorizations. **(T-3)**

4.11.1.15.1. Ensure EAWP users use the EAWP program in lieu of a work folder to meet minimum requirements of this DAFI.

4.11.1.16. Coordinate with the OAP laboratory to obtain maximum benefits from OAP data when abnormal wear-metal trends are indicated. **(T-3)**

4.11.1.16.1. Ensure all OAP responsibilities are performed IAW **Chapter 11**.

4.11.1.16.2. Establish procedures to monitor OAP trends. **(T-3)**

4.11.1.16.3. Ensure personnel are trained to identify and respond to wear metal limits for assigned and maintained engines and are trained to perform sampling procedures IAW TO 33-1-37-2.

4.11.1.16.4. Ensure oil samples taken at the ETS are promptly delivered to the OAP laboratory. **(T-3)**

4.11.1.16.5. Act as a central point-of-contact for all abnormal OAP laboratory results. **(T-3)**

4.11.1.16.6. Forward information to the OAP laboratory concerning actions taken as a result of OAP recommendations. **(T-3)**

4.11.1.16.7. Review OAP response time (from sampling to receipt at the laboratory and return to the unit) to ensure processing time meets mission needs. **(T-3)**

4.11.1.17. **(Added-AFGSC)** When applicable, appoint a Repair Network Node Manager for the Propulsion Section. Update Repair Network CAP2 annually or as directed. Ensure Node Managers complete training per DAFI 20-117.

4.11.2. Support Section. The Support Section manages the flight's HAZMAT program and operates tool storage areas. DMS or designated personnel process supply requests to facilitate the issue request, tracks MICAP due-outs, monitors bench stock, conducts bench stock/adjusted stock level reviews IAW DAFMAN 23-122. **(T-3)** In addition to the applicable Section NCOIC/Chief responsibilities outlined in **Chapter 2**, the Support Section NCOIC/Chief will:

4.11.2.1. Ensure a flight due-out release point and holding bins are established, and Urgency of Need Designator "A" and Urgency Justification Code BQ requirements are verified. **(T-3)**

4.11.3. Jet, Turboprop, Turbo-shaft Engine Intermediate Maintenance (JEIM) section. Stores, builds up, tears down, inspects, modifies, and repairs engines, QEC kits, and tests components. In addition to the applicable Section NCOIC/Chief responsibilities in **Chapter 2**, the JEIM Section NCOIC/Chief will:

4.11.3.1. Plan and monitor the progress of propulsion system maintenance production, ensuring maintenance schedules are met by anticipating materiel required and managing delays to prevent schedule disruptions to support operational requirements and maintain required WRE levels. **(T-3)**

4.11.3.1.1. Report production to Propulsion Flight CC/Chief and immediately inform EM of engine status changes.

4.11.3.2. Ensure personnel prepare propulsion units and components for shipment and properly identify units to be returned to depot. **(T-3)**

4.11.3.2.1. Attach CEMS and/or MIS paper products to life-limited components IAW 00-20-series TOs if required by the source of repair.

4.11.3.3. Ensure documentation of TCTO compliance IAW 00-20-series TOs.

4.11.3.4. Ensure CEMS and/or MIS products obtained from EM are used for all assigned engines. **(T-3)**

4.11.3.4.1. CEMS and/or MIS products will list all parts and serial numbers installed on the engine. **(T-3)**

4.11.3.5. Establish procedures to ensure all parts and serial numbers are inventoried when an engine is received or released by the section. **(T-3)**

4.11.3.5.1. The JEIM Section NCOIC will notify EM when a different serial numbered part is installed or changed so the automated record is updated. **(T-3)**

4.11.3.5.2. EAE is the change correction authority on Part Number/Serial Number Record updates in EAWP. **(T-3)**

4.11.3.6. Ensure an engine work folder is established for each engine during PE, reconditioning, or other maintenance. **(T-3)**

4.11.3.6.1. One work order is initiated in MIS for an entire job.

4.11.3.6.1.1. MIS work orders are completed during inspection, reconditioning or maintenance.

4.11.3.6.1.2. Separate JCN/Work Center Event (WCE)/Work Event Separator are initiated for discrepancies found during the look phase of an inspection, subsequent to repair, or when maintenance is required beyond the scope of the JEIM induction JCN.

4.11.3.6.1.3. **(Added-AFGSC)** Also include the total operating time of old and new components. **(T-2)**

4.11.3.6.2. Establish engine work folders on all possessed engines and EM or JEIM will maintain the folders until the engine is transferred. **(T-3)** As a minimum, engine work folders will contain the following:

4.11.3.6.2.1. List of all parts, TCTOs and TCI requirements for the engine. **(T-3)**

4.11.3.6.2.1.1. **(Added-AFGSC)** All Engineering Technical Assistance Request (ETAR) guidance related to the assigned engine.

4.11.3.6.2.2. Engine/Module/Accessories Information Worksheet. **(T-3)** This document is used to provide a quick synopsis of maintenance accomplished. Minimum requirements will include engine serial number, type, position (if applicable), engine operating time, date started work, date turned serviceable, job control number, maintenance required, reason for removal, list of time change and TCTO requirements. **(T-3)**

4.11.3.6.2.2.1. A supervisory review of signature blocks (Crew Chief, Support Section, EM Section) to verify all repair requirements have been accomplished and are correctly documented in the work folder. **(T-3)**

4.11.3.6.2.2.2. Validation that a JCN was created by the JEIM/Module/Accessories Section or EM section and used to account for maintenance events completed in the process of repairing the engine and modules. **(T-3)** This procedure ensures all maintenance data is documented against one JCN and engine failure information is connected to the in-shop action.

4.11.3.6.2.3. Receiving Inspection Worksheet. **(T-3)** The worksheet is used for documenting items to be accomplished by JEIM prior to engine repair. Minimum requirements will include: FOD check of engine inlet and exhaust, inspection of engine for general condition and fluid leakage, EHR/Turbine Engine Monitoring System data (if applicable), ET&D (if applicable), borescope inspection (if applicable), a check with OAP lab for possible problems, and a list of unique or problem areas to be checked prior to engine disassembly or maintenance. **(T-3)**

4.11.3.6.2.4. Serially Controlled/Time-Tracked Item Replacement Record. **(T-3)** This document shows a list of components replaced by nomenclature, old and new part number (if applicable), and serial number.

4.11.3.6.2.5. Daily Summary Record. **(T-3)** This document provides a synopsis of maintenance performed during each shift.

4.11.3.6.2.5.1. Each entry in the Daily Summary Record includes the Employee Number of the person who accomplished the maintenance action. For EAWP users, this process may be automated.

4.11.3.6.2.5.2. Include a sufficient reference in the summary block (such as, work package, TO) used to perform the task or determine the work performed (subordinate work packages are not required to be listed if the work package for the primary task identifies all required work packages for the task).

4.11.3.6.2.5.3. At the end of each shift, the crew chief who verified the entries listed in the Daily Summary Record will annotate their shift, rank, last name, and employee number. **(T-3)** Units may use a general purpose or MAJCOM/locally approved form.

4.11.3.6.2.6. IPI Worksheet. **(T-3)** This form includes the WUC, nomenclature, specific step required for the IPI, and space for employee numbers and signatures of technicians and inspectors performing maintenance. **Note:** Organizations using digital systems may file a printed report in lieu of signatures (such as, Interactive Electronic Technical Manual (IETM)).

4.11.3.6.2.7. Parts Requisition Record. **(T-3)** This document is used to list all parts (including TCIs) on order. As a minimum, this document will include the following headings: Engine/ Module/Accessory, TMS, Engine/Module/Accessory Serial Number, Nomenclature, Part Number, National Stock Number (NSN), Requisition Number, Priority, Status, and DIFM Clear with “Yes” and “No” sections. **(T-3)**

4.11.3.6.2.8. JEIM ETS Preparation Worksheet. **(T-3)** This worksheet contains a list of items/tasks to be accomplished by JEIM prior to sending an engine to the ETS. As a minimum, document the following:

4.11.3.6.2.8.1. Inlet and exhaust FOD inspection; any pre-run servicing required (such as, cap open lines, cannon plugs, engine intake and exhaust inspection). **(T-3)**

4.11.3.6.2.8.2. A thorough tool inventory and an inspection for loose hardware. **(T-3)**

4.11.3.6.2.8.3. The section supervisor will document a review of the work

folder to ensure maintenance performed or required actions are documented. **(T-3)**

4.11.3.6.2.9. ETS Pre-run Worksheet. **(T-3)** ETS personnel will complete this document prior to an engine run. **(T-3)**

4.11.3.6.2.9.1. As a minimum, this document will include the following headings: Engine TMS; Engine Serial Number; Engine Operating Time (EOT)/Cycles; JCN; Remarks; Pre-run Emergency Briefing Accomplished with run Supervisor's Name, Signature and Date sections; and Inspection with Area, Employee Number, and Date sections. **(T-3)**

4.11.3.6.2.9.2. As a minimum, area inspections will include Inlet FOD/Foreign Object (FO); Exhaust FOD/FO; Engine Exterior and FO; General Engine Serviceability; Test Stand/Thrust Bed/Test Equipment for FO; CTK Inventory Complied With (C/W); Engine Servicing Check; all preliminary engine installation and run requirements C/W; and serviceable fire extinguisher on hand. **(T-3)**

4.11.3.6.2.9.2. **(AFGSC)** Review all ETAR guidance related to assigned engine.

4.11.3.6.2.9.2.1. Each area inspection will have the performing technician's employee number and date accomplished annotated. **(T-3)**

4.11.3.6.2.10. ETS Post Run Worksheet. **(T-3)** This document is used to document items/tasks accomplished by ETS personnel after engine run.

4.11.3.6.2.10.1. As a minimum, this document will include the following headings: Engine TMS; Engine Serial Number; EOT/Cycles; JCN; Maintenance Actions Performed; Engine Monitoring System (EMS) operational/performance data collected and provide to EM; ETS Supervisors Post-run Review with Name, Signature and Date; and Area Inspections, Employee Number and Date. **(T-3)**

4.11.3.6.2.10.2. As a minimum, area inspection will include: Inlet FOD/FO; Exhaust FOD/ FO; CTK Inventory C/W; Post-Run OAP Samples C/W (if applicable); AFTO Form 350 or AFTO Form 20, *Caution and Inspection Record,* annotate: Engine Preservation Type and Date; Throttle Secured to Off Position (if applicable) and Tagged; Cap Open Lines/Cannon Plugs; Install Intake/Exhaust Covers; Servicing Amount; ETS Discrepancies Cleared; 7-Level Inspection of Components Replaced or Disconnected; and Final Leak Check. **(T-3)**

4.11.3.6.2.10.3. ETS personnel will leak-check items not accessible with the engine installed in or on the aircraft prior to leaving ETS. **(T-3)**

4.11.3.6.2.10.4. Each area inspection will have the performing technician's employee number and date accomplished annotated. **(T-3)**

4.11.3.6.2.11. Final Inspection Worksheet. **(T-3)** This document is used to document JEIM requirements after repair or testing has been completed.

4.11.3.6.2.11.1. As a minimum, this worksheet will include: FOD inspection of intake, exhaust, and external engine; borescope engine (if applicable); ensuring throttle is secured and tagged to "off" position (if applicable); capping, plugging and covering fittings and lines; attaching AFTO Form 350 to lines, fittings or plugs that require "leak check" when installed in aircraft (items not accessible in aircraft must be leak checked on ETS); attaching AFTO Form 350 and/or serviceable tag to engine, ensure supply accounts and MIS entries have been cleared. **(T-3)**

4.11.3.6.2.12. Borescope Worksheets. **(T-3)** Borescope inspection worksheets will be used for engines requiring borescope documentation. **(T-3)**

4.11.3.6.2.13. Uninstalled Engine/Module Blade Blending/FOD Damage Worksheet. **(T-3)** This worksheet is used to document blade blending/FOD damage for uninstalled engines/modules. As a minimum, this worksheet will include Engine/Module Serial Number, Date, Discrepancy, Stage and Corrective Action including number of blades blended, depth of damage before and after blend, area of damage and Employee Number. **(T-3)**

4.11.3.6.2.14. Reliability Centered Maintenance Worksheets (if applicable). **(T-3)**

4.11.3.6.2.14.1. For JEIM engine builds, a copy of the "Reliability Centered Maintenance Build Options" and "Reliability Centered Maintenance Calculator Summary" worksheets are maintained in the engine work folder or EAWP for documenting life-limited component engine build recommendations.

4.11.3.6.2.14.1.1. Utilize Reliability Centered Maintenance calculator software accessed through CEMS prior to engine build.

4.11.3.6.2.14.1.2. The sheets are required only if life-limited components (excluding LRU) are removed and replaced during the JEIM engine build and the TMS engine is available in the Reliability Centered Maintenance Calculator. The calculator is not used for engines which do not have the calculator developed.

4.11.3.6.2.15. Worksheets that document engine historical information, critical maintenance management stages, and employee numbers of technicians and supervisors completing maintenance and inspections.

4.11.3.6.2.15.1. Supplement work folders and worksheets to fit unit needs.

4.11.3.6.2.15.2. Flights may use computer-generated products, provided they include all required information. If TMS has an established EAWP, it will be utilized. **(T-3)**

4.11.3.6.2.15.2.1. EAWP users will ensure all maintenance discrepancies are documented in the system's appropriate discrepancy block. **(T-3)**

4.11.3.7. Ensure MICAPs are processed in Enterprise Solution-Supply; ensure all pertinent data is included. **(T-3)**

4.11.3.8. Upgrade, downgrade and cancel MICAP requirements. **(T-3)**

4.11.3.9. **(Added-AFGSC)** Engine shipping documents received from the EM will be used to adjust Custodian Authorization/Custodian Receipt List inventory as engine spare levels change.

4.11.3.10. **(Added-AFGSC)** The EM NCOIC or assistant will contact MXS Pro Super and BGS/AMXS Pro Super for engine maintenance assistance as necessary.

4.11.3.11. **(Added-AFGSC)** The EM NCOIC or assistant will ensure locally developed Engine Work Packages are used per **paragraph 4.11.3.6.2** when directed by technical guidance.

4.11.4. Noise Suppression Systems (NSS) and Engine Test Stands (ETS) Section. Tests engines to evaluate the quality of maintenance, engine performance, and accomplish engine preservation including engines installed on aircraft in coordination with owning squadron. In addition to the applicable Section NCOIC/Chief responsibilities outlined in **Chapter 2**, the NSS and ETS Section NCOIC/Chief will:

4.11.4.1. Assign primary and alternate AutoTAR or Air Force Lifecycle Management (AF-PLM) custodians to perform -107 ETAR and status updates in AutoTAR/AF-PLM for AFLCMC/WN-managed NSSs and ETSs. **(T-2)**

4.11.4.2. Monitor repair activity and ensure reporting and status updates are timely, accurate, and kept current in AutoTAR/AF-PLM. **(T-3)**

4.11.4.3. Ensure NSS and ETS personnel accomplish minor maintenance, make adjustments to engines, document engine condition, and collect EMS operational/performance data and deliver to EM. **(T-3)**

4.11.4.3.1. Ensures ETS components are calibrated on site, if practical. **(T-3)**

4.11.4.4. Brief maintenance personnel on NSS/ETS operating/emergency procedures. **(T-3)**

4.11.4.5. Handle and report halon releases IAW AFMAN 32-7002.

4.11.5. Module/Accessory Repair Section. Repairs, stores, and maintains fuel nozzles, fuel manifolds, oil pumps, accessory housings, afterburners, thrust reversers, augmentors, engine components, time change modules, and shop replaceable units. Operates and maintains the bearing room IAW TO 44B-1-15, *General Instructions - Jet Engine Anti-friction Bearing Handling, Removal, Cleaning, Inspecting, and Installation at Jet Engine Base Maintenance Facilities* (if applicable).

4.11.6. Small Gas Turbine Engine Section. Repairs and maintains small gas turbines used in aircraft. In addition to applicable Section NCOIC/Chief responsibilities outlined in **Chapter 2**, the Small Gas Turbine Engine Section NCOIC/Chief will ensure personnel are qualified to operate small gas turbine engines and test stands. **(T-3)**

4.11.7. Engine Equipment Maintenance Section. Maintains, manages, and stores engine support and removal/installation/transportation equipment and trailers. The Engine Equipment Maintenance Section NCOIC/Chief will:

4.11.7.1. Ensure engine removal/installation/transportation trailers and adapters status is properly reported IAW DAFI 21-103 and MAJCOM supplements. **(T-3)**

4.11.7.2. Track and schedule all inspections and maintenance, removal, installation, transportation trailers and adapters in the MIS. **(T-3)**

4.11.7.3. Ensure equipment forms and MIS documentation are complete, accurate, and accomplished for all maintenance and scheduled inspections. **(T-3)**

4.11.7.4. Ensure status is accurately reflected in both the maintenance forms and the MIS. **(T-3)**

4.11.8. Propeller Section. Repairs, builds up, tears down, inspects, tests, and modifies propellers, valve housings, pump housings, and associated components.

4.11.9. Quick Engine Change (QEC) Kit Management. QEC kit removals and installations are coordinated with the SRAN EM and loaded in MIS as a part number-serial number item, reflecting where the kit is installed or spared.

4.11.9.1. In addition to repair cycle procedures outlined in **Chapter 9** in this instruction, the technician removing a QEC kit item from an engine will complete an AFTO Form 350, enters the reason for removal in Block 14, and annotates the QEC kit inventory for each repairable item. **(T-3)**

4.11.9.2. Technicians will complete the AF Form 596, *Quick Engine Change Kit Inventory* for on repair cycle items and QEC kit unique items, when an engine enters the section for tear down. **(T-3)**

4.11.9.2.1. If TO requirements restrict reuse of items, the technician will mark the AF Form 596 with an asterisk to show a demand has been placed on supply. **(T-3)**

4.11.10. **(Added-AFGSC)** Units without full intermediate level repair capability will perform the tasks outlined in **Table 4.1** if the required support equipment and expertise is authorized and on-hand. Repairs above and beyond those listed require approval from HQ AFGSC/A4MA Aircraft Systems Branch. All other engines are returned to their assigned Centralized Repair Facility or Depot/equivalent. **(T-2)**

4.11.11. **(Added-AFGSC)** Determine kit requirements (and procedures for maintaining kits if established) for recurring maintenance actions. Kits are pre-assembled from bench stock, in minimum quantities necessary to support workload requirements. Repair cycle assets are not included in kits. **(T-2)**

4.11.12. **(Added-AFGSC)** Establish a forecast list of supplementary part requirements based on a review of repair documentation for the preceding 6 months and ensure adequate stock of the items are available as applicable to the MDS.

4.11.13. **(Added-AFGSC)** Determine if pre-maintenance test cell runs are required for all engines removed.

4.11.14. **(Added-AFGSC)** Ensure personnel qualified to operate the NSS IAW **Chapter 11** are present whenever the NSS is in use. If required, provide NSS personnel to augment AMXS deployment requirements. **(T-2)**

4.12. Test, Measurement, and Diagnostic Equipment (TMDE) Flight. Maintains, calibrates, and certifies TMDE, traceable through the AF Primary Standards Laboratory (AFPSL) to the National Institute of Standards and Technology (NIST), or other AF Metrology and Calibration (AFMETCAL)-approved source. Provides base-level support of aircraft, precision-guided

munitions, ground systems, and other equipment assigned to the base or GSU. TMDE Flight ensures Calibration, certification, and maintenance of TMDE is accomplished IAW AFMAN 21-113, TO 00-20-14, TO 33K-1-100-1, *Calibration Procedure for Maintenance Data Collection Codes and Calibration Measurement Summaries*. A Rapid Assistance Support for Calibration may also be assigned.

4.12.1. In addition to applicable Flight CC/Chief responsibilities in **Chapter 2**, the TMDE Flight Chief will:

4.12.1.1. Establish a PMEL Quality Assurance Section IAW AFMAN 21-113 and TO 00-20-14. **(T-3)**

4.12.1.2. Publish a monthly PMEL Activity Summary and route it through the Maintenance Supervision to the SQ/CC (or organizational equivalent). **(T-3)**

4.12.1.2.1. The report format will comply with TO 00-20-14 and meet local requirements. **(T-3)**

4.12.1.3. Ensure all Groups with TMDE Flights assigned include the TMDE Quality Program Activity Summary in the QA monthly summary IAW **Chapter 6**. **(T-3)**

4.12.1.3.1. **(Added-AFGSC)** Forward a copy of the monthly Quality Program activity summary to AFGSC PMEL Functional. This report is due NLT than the 8th day of the following month. **(T-2) Note:** Monthly Quality Program activity summary is not required for Acquisition Management & Integration Center (AMIC) contracted labs.

4.12.1.3.1.1. **(Added-AFGSC)** The summary will include at a minimum:

4.12.1.3.1.2. **(Added-AFGSC)** Average backlog for the month and the 6-month average. **(T-2)**

4.12.1.3.1.3. **(Added-AFGSC)** Monthly average of percent of inventory overdue calibration. **(T-2)**

4.12.1.3.1.4. **(Added-AFGSC)** Monthly average of percent of inventory awaiting parts. **(T-2)**

4.12.1.3.1.5. **(Added-AFGSC)** Monthly average of percent of inventory on hold. **(T-2)**

4.12.1.3.1.6. **(Added-AFGSC)** Environmental Control System (ECS) performance (temperature and relative humidity) for each monitor in use. ECS data will include the percentage in tolerance for the last 12 months and percent in tolerance for the latest month. **(T-2)**

4.12.1.3.2. **(Added-AFGSC)** Ensure the discovery of and correct prioritization of defects and verify repairs to the LO systems on the aircraft.

4.12.2. The NCOIC, PMEL Logistics will:

4.12.2.1. Ensure TMDE monitors are properly trained and maintain a database or log to track training events (dates, names, organizations). **(T-3)**

4.12.2.2. TMDE will be scheduled with input priorities IAW TO 00-20-14, Air Force Metrology and Calibration Program.

4.12.2.2.1. DELETED.

4.13. (Added-AFGSC) Signature Diagnostics Section. [B-2 Units only] The Signature Diagnostics (SD) Section will be separated from the LO Flight and part of the Fabrication Flight within the 509th Maintenance Squadron and is an Air Force approved deviation from the standard Maintenance Squadron organization. The section consists of military personnel assigned to 509th Maintenance Squadron and civilian contracted personnel that are not assigned to 509th Maintenance Squadron (survivability supporting role) that perform on-aircraft inspections, measurements and analysis critical to the signature confidence and survivability of the B-2 using radio frequency diagnostic tools and physical inspections of the Low Observable (LO) characteristics of the fleet.

Chapter 5

MAINTENANCE OPERATIONS (MXO).

5.1. General. MXO is directly responsible to the MXG/CC for the administration, analysis, training management of assigned personnel, and programs and resources necessary to support the group's production effort. MXO is comprised of the following sections: EM, PS&D, MMA, MOC, MT, and Programs and Resources (P&R). In missile organizations, MXO will be organized as a Maintenance Operations Squadron, as applicable. For the purposes of this instruction, the term MXO is equivalent with Maintenance Operations Flight for ANG units.

5.2. Maintenance Operations. MXO is the central agency for monitoring and developing long-range strategies of fleet management to sustain the health of the fleet. Fleet management is defined as the effective utilization of available resources to accomplish the aircraft support cycle from planned maintenance events to operations schedule execution. It is a disciplined and prioritized scheduling effort that optimizes support to aircraft requirements such as flying/operational events, ground training events, scheduled maintenance inspections, aircraft/system configuration control, aircraft/system modification schedules and aircraft/system recovery maintenance. Effective fleet management results in consistent availability of quality aircraft/systems to meet operational requirements. The Maintenance Operations Superintendent position will be filled by SNCO 2RXXX personnel and act as the 2R Base Functional Manager for their component. **(T-2)**

5.2.1. Base 2R Functional Manager will be the senior ranking enlisted member, possessing a 7-skill level or higher, assigned to the host MAJCOM of the installation. **(T-2)** They are responsible for both AFSC 2R0X1 and 2R1X1 personnel development, training, and assignment for their component. HQ MAJCOM personnel may not fill this position.

5.2.1. **(AFGSC)** The 2R1X1 and 2R0X1 AFSCs have merged into the 2R2XX AFSC category and will be considered synonymous within this supplement. The training for all 2R2XX personnel, as outlined in the Career Field Education and Training Plan (CFETP) and Command Job Qualification Standard (CJQS), is the responsibility of the installation's 2R2XX Functional Manager. The installation's 2R2XX Functional Manager is responsible for:

5.2.1.1. **(Added-AFGSC)** Ensuring that all 2R2XX personnel are trained in accordance with the CFETP and CJQS. **(T-2)**

5.2.1.2. **(Added-AFGSC)** Providing resources and support to ensure that 2R2XX personnel receive the training and guidance needed to perform their duties effectively.

5.2.2. Develop a 2R0X1 and 2R1X1 training plan for all assigned personnel, to include tenant units. Determine utilization and assignment of installation AFSC 2R0X1 and 2R1X1 personnel and a rotation plan for their respective 2R0X1 and 2R1X1 wing resources based on mission requirements. **(T-3)**

5.2.2.1. **(Added-AFGSC)** 2R2XX personnel assigned to Munition, Missile, or NC3 positions will complete the respective 2R CJQS requirements as identified by the 2R MAJCOM Functional Manager. **(T-2)**

5.2.3. Ensure 2R0X1 and 2R1X1 are trained and qualified by establishing a structured training program. **(T-3)** Ensure training sessions for 2R0X1 and 2R1X1 are conducted and documented

monthly. Maintain training session documentation to include attendance logs for at least one year.

5.2.3.1. **(Added-AFGSC)** Conduct regular evaluations to assess the effectiveness of the training program and identifying areas for improvement.

5.2.3.2. **(Added-AFGSC)** Advise the Unit Commander to ensure that 2R2XX personnel are assigned to duties that align with their training and qualifications.

5.2.4. Maintenance Operations, Director of Operations /Superintendent (DO/SUPT). In addition to the applicable Maintenance Supervision responsibilities in **Chapter 2**, the MXO OIC/SUPT will:

5.2.4.1. Develop and publish the wing operations/maintenance schedule in coordination with other squadrons and submit to both the OG/CC and MXG/CC for approval. **(T-3)**

5.2.4.2. Determine long-range fleet health maintenance priorities. **(T-3)**

5.2.4.3. Manage the data collection process, review data, and verify analysis for maintenance data collection requirements. **(T-3)**

5.2.4.4. Evaluate and provide trend analysis information to the MXG/CC and SQ/CCs. **(T-3)**

5.2.4.5. Ensure aircraft status is properly reported and maintained IAW DAFI 21-103.

5.2.4.5.1. Coordinate with the PS&D Aerospace Vehicle Distribution Officer (AVDO) to ensure all assignment and possession changes are accurately reported to the MAJCOM AVDO IAW DAFI 21-103 and AFI 16-402, *Aerospace Vehicle Programming, Assignment, Distribution, Accounting, and Termination*.

5.2.4.5.1.1. **(Added-AFGSC)** Ensure NC3 Equipment IDs/systems status is properly reported and maintained IAW DAFI 21-103.

5.2.4.6. Initiate, review, and validate special analysis studies. **(T-3)**

5.2.4.6.1. Determine planning factors for the next year's flying hour program. **(T-3)**

5.2.4.6.2. Utilize a sortie production model or equivalent for the assigned MDS, if available. **(T-3)**

5.2.4.7. Develop procedures to update Geographical Location (GEOLOC) codes for all on and off-station possessed aircraft and ensure GEOLOC codes are updated/correct in the MIS "Location Subsystem" (FMxC2 units are exempt as long as a HHQ agency accomplishes this requirement). **(T-3)**

5.2.4.8. IMDS units will use code "XXXX," and FMxC2 units will use "CCCC" for classified locations. **(T-3)**

5.2.1.8.1. DELETED.

5.2.4.9. Host DFTs/CFTs, provide in-briefs on unit-specific maintenance and tool-control requirements, review plans, coordinate/monitor status of aircraft and progress of repair work. **(T-3)**

5.2.4.10. Participate in the review of base level repair capability IAW TO 00-20-3, AFREP in **Chapter 11** of this DAFI, and supplements.

5.2.4.11. Publish wing notification requirements for munitions-loaded or unloaded aircraft. **(T-3)**

5.2.4.12. Establish/sustain local radio call signs for maintenance LMR networks IAW AFI 17-210, Radio Management. **(T-3)**

5.2.4.12. **(AFGSC)** The MOC will publish local procedures for establishing new requirements and/or changes.

5.2.4.13. Develop a training plan for individuals assigned to QA that will inspect MXO functions. Minimum training requirements will include MIS (FMxC2/IMDS/or equivalent) online and background products for inspections, time changes, TCTOs, and aircraft configuration management. **(T-3)** For units with IMDS, the QA inspector will be trained on the use of DS Maintenance Scheduling Module (MSM) to provide the capability for a qualified QA inspectors to evaluate and report PS&D compliance with functional requirements. **(T-3)** The senior 2R in the MXO will provide assistance to the inspector as required. **(T-3)**

5.2.4.14. Ensure MAJCOM Master Course Listing includes 2R weapon system familiarization courses requirements. **(T-3)**

5.2.4.14.1. As a minimum, the course will include weapon system/communications electronics familiarization, flightline and shop operations, organizational structure and roles of each group, squadron, and flight. **(T-3)**

5.2.4.14.2. Analysts will attend the course within 6 months of assignment to the unit. **(T-3)**

5.2.4.14.2. **(AFGSC)** All 2R2XXs will attend the course within 6 months of assignment to the unit, or once the minimum class size can be met. **(T-2)**

5.2.4.14.3. For remote assignments, analysts will attend within 1 month of assignment. **(T-3)**

5.2.4.14.4. DELETED.

5.2.4.15. **(Added-AFGSC)** Ensure data is valid prior to Executive Report submission for AFGSC requirements, see **Attachment 16.**

5.2.5. Maintenance Operations Center (MOC). The MOC monitors and coordinates sortie generation, maintenance production, and execution of the operations and maintenance schedules while maintaining visibility of fleet health indicators. Through coordination with maintenance units, the MOC communicates priorities for competing limited resources (such as, fuel or calibration docks, wash racks, and dispatched specialists from the maintenance squadron(s) (for example, egress) based on daily operations schedule and maintenance priorities. The exchange of information between squadrons and the MOC must be in sufficient detail to allow the MOC to comply with reporting requirements and to identify potential problems.

5.2.5.1. The MOC will:

5.2.5.1.1. Monitor the status of aircraft/systems, as directed, (through the use of electronic or manual visual aids) including ETIC, progress of FCFs, and location of each aircraft on station. **(T-3)**

5.2.5.1.1. **(AFGSC)** Monitor the status of the NC3 Equipment IDs/systems, as directed, (using electronic or manual visual aids) including ETIC and location of each NC3 equipment IDs on station.

5.2.5.1.2. Track contingency and exercise aircraft generation activities. **(T-3)**

5.2.5.1.2.1. Maintain and update aircraft generation line up and display aircraft status using AF Form 2408, *Generation Maintenance Plan* and AF Form 2409, *Generation Sequence Action Schedule* or locally computer-generated equivalents. **(T-3) Note:** If the tail number, mission number or specifically tasked no-later-than times are linked, this form becomes classified. See DODM 5200.01V1_AFMAN 16-1404, *Information Security Program: Overview, Classification and Declassification*.

5.2.5.1.2.1. **(AFGSC)** Ensure current Aircraft Generation flow plans are coordinated with the Joint Nuclear Operations Center (JNOC) for review and approval. **(T-2)**

5.2.5.1.2.2. Monitor and report aircraft generation progress with a minimum of the following information: ETIC, location of each aircraft, status of generation actions, progress against timeline necessary to meet mission requirements. **(T-3) Note:** The display format should be compatible with OPLANS and command post displays.

5.2.5.1.2.2. **(AFGSC)** Establish Conventional Aircraft Generation flow plans and coordinate with Air Forces Strategic-Air/A4 (AFSTRAT/A4) annually for review and validation. **(T-2)**

5.2.5.1.3. Utilize the Enhanced Maintenance Operations Center. **(T-3) Note:** BLADE will be used to track classified aircraft status.

5.2.5.1.4. Track aircraft maintained or supported by the unit but not on station. (Aircraft cross-country). **(T-3)**

5.2.5.1.5. Coordinate maintenance on the alert force, if applicable. **(T-3)**

5.2.5.1.6. Ensure status boards depict aircraft status and location comply with Security Program guidelines. **(T-3)**

5.2.5.1.7. Monitor the status and ETIC of MEL-designated AGE if it falls below critical levels. **(T-3)**

5.2.5.1.8. Monitor the status of ECM and sensor pods IAW AFI 10-201, *Force Readiness Reporting*. **(T-3)**

5.2.5.1.8.1. When MC pod availability falls below requirements per the DOC or OPLAN, the MOC will track/monitor the following information: pod serial number, status (AWP/Awaiting Maintenance (AWM)), MICAP NSN, off-base requisition numbers, and ETIC. **(T-3)**

5.2.5.1.9. Classify information IAW AFI17-130, *Cybersecurity Program Management.*

5.2.5.1.10. Verify aircraft status and ETICs with the Pro Super(s) and ensure they are properly documented in the MIS IAW DAFI 21-103**.** Reference AFCSM, 21-564, V2, *Status and Inventory Reporting Software User Manual* or equivalent for MIS guidance.

5.2.5.1.10. **(AFGSC)** Verify NC3 Equipment ID/System status and ETICs with the Pro Super(s) and ensure they are properly documented in the MIS IAW DAFI 21-103**.** Reference AFCSM, 21-564, V2, *Status and Inventory Reporting Software User Manual* or equivalent for MIS guidance.

5.2.5.1.10.1. When the Production Superintendent (Pro-Super) or equivalent notifies the Maintenance Operations Center (MOC) that an aircraft is "Crew Ready" the MOC will review the Maintenance Information Systems (MIS) for each Crew Ready aircraft to ensure there are no open Red Xs. **(T-3)** If open Red X(s) are present in the MIS, the MOC will notify the Pro-super or equivalent for action. **(T-3)**

5.2.5.1.11. The MOC will verify aircraft status using the MIS and ETIC before reporting it. **(T-3)**

5.2.5.1.12. Inform affected activities of changes in priorities, plans, and schedules. **(T-3)**

5.2.5.1.13. Coordinate on changes to the operations schedule with applicable agencies by use of AF Form 2407. **(T-3)**

5.2.5.1.14. Ensure all deviations to the daily operations schedule are reviewed and accurately reported. **(T-3)**

5.2.5.1.14.1. Forward a copy of each AF Form 2407 and the daily flying schedule, with all annotated deviations, to MMA. **(T-3)**

5.2.5.1.15. Request support services outside the scope of the MXG (such as, standby firefighting capability, aircraft water, snow removal, fueling and defueling service, civil engineer support, or control tower clearances for ground movement of aircraft and equipment). **(T-3)**

5.2.5.1.15.1. Coordinate on all aircraft engine runs and all aircraft ground movements conducted by maintenance personnel prior to execution. **(T-3)**

5.2.5.1.16. Develop, coordinate, implement, and maintain functional and emergency action checklists. **(T-3)** Checklists contain those actions required to be taken by functional area(s).

5.2.5.1.16.1. Functional checklists are required for use during actions such as nuclear mass loads, Broken Arrow, Dull Swords, Bent Spear, aircraft crash/mishap/incident, aircraft FOD, aircraft damage, flightline fire, severe weather warning or evacuation, runway closure, hazardous chemical release (example, Hydrazine, Broken Pod Glass release of Thorium Fluoride or Americium), Quick Reaction Checklists, injuries resulting from aircraft maintenance and any other unusual circumstances deemed necessary.

5.2.5.1.16.2. For OPLAN 8010 notification, use the plan implementation checklists.

5.2.5.1.16.3. Use unit OPLANs as a guide in developing these checklists.

5.2.5.1.16.4. DELETED.

5.2.5.1.16.5. The MOC will maintain checklists that implement all approved MAJCOM and local requirements. **(T-3)**

5.2.5.1.16.6. Establish a command/contingency focal point to coordinate ABDR and or Joint Combat Assessment Team (JCAT) response requests with AFMC. **(T-3) Note:** If data collection forms are required forms will be forwarded to the Aircraft Battle Damage Repair (ABDR) Technical Support Office (TSO) and JCAT. **(T-3)** For ABDR TSO, CLASSIFIED messages must be sent to: **usaf.wright-patt.afsc-lg.mbx.afsc-lgpm-abdr-tso@mail.smil.mil** and UNCLASSIFIED messages must be sent to NIPR: **afsc.lgpm.abdrtso@us.af.mil** for filing in the historical archives. For JCAT, CLASSIFIED data must be submitted via the Intellipedia Secret Internet Protocol Router Network (SIPRNET) link **https://www.intellipedia.intelink.sgov.gov/wiki/Portal:Joint_Combat_Assessment_Team**. UNCLASSIFIED data can be sent to: JCAT (**JCAT@us.af.mil**).

5.2.5.1.17. Coordinate munitions delivery priorities with flying units and munitions maintenance activities, and control when tasked. **(T-3)**

5.2.5.1.17.1. Maintain a contact list and notify the base Fire Emergency Services and all applicable agencies that require notification of munitions-loaded or unloaded aircraft. **(T-3)**

5.2.5.1.17.1.1. The MOC will provide agencies with the aircraft type, tail number, location, type of explosives, and arming status. **(T-3)**

5.2.5.1.18. Upon notification of deployments, ensure all deploying equipment is identified and loaded into the IMDS-CDB, Aerospace Expeditionary Force subsystem or designated MIS equivalent for the duration of the deployment. **(T-3)**

5.2.5.1.19. Monitor and manage reporting of Hangar Queen aircraft/systems IAW **Chapter 11**.

5.2.5.1.20. Notify Flightline Expediters of all OAP code conditions. **(T-3)**

5.2.5.1.21. Ensure facilities and visual aids meet the following minimum standards:

5.2.5.1.21.1. A completely enclosed room with air conditioning and heating. **(T-3)** An observation room is permitted.

5.2.5.1.21.1.1. Doors to the MOC and the observation room will be either mechanically or electrically locked to control access. **(T-3)**

5.2.5.1.21.2. Isolate MOC electrical power circuits and provide a standby power source and emergency lighting. **(T-3)**

5.2.5.1.21.2.1. The MOC will establish procedures to operate standby power sources. **(T-3)**

5.2.5.1.22. Maintain the status and location of all transient aircraft. **(T-3)**

5.2.5.1.22.1. Post the priority of each transient aircraft on the status board, based on the maintenance priorities listed in **Table 1.2** **(T-3)**

5.2.5.1.22.2. Coordinate with the appropriate agency for aircraft maintenance support. **(T-3)**

5.2.5.1.22.3. Contact WS for arming or de-arming of transient aircraft IAW **Chapter 11**. **(T-3)**

5.2.5.1.23. **(Added-AFGSC)** Maintain a current listing of Egress Augmentees.

5.2.5.2. MOC Maintenance Communications. Reliable, redundant, and effective communications systems are essential for efficient operation. Communications equipment will be operated and managed IAW AFI 17-210, DAFI 17-220, *Spectrum Management*, and AFI 17-130. The MOC NCOIC/SUPT will:

5.2.5.2.1. Establish a procedure to process requests for specific radio equipment to support MXG maintenance activities IAW DAFMAN 23-122.

5.2.5.2.1.1. Specific radio allowances are stated in Allowance Standard 660 at **https://usaf.dps.mil/teams/12599/AFKN_Docs/ASC%20Prefaces/ASC%20660%20Ground%20Communications%20-%20Operations%20Support.pdf**.

5.2.5.2.2. Ensure a Very High Frequency (VHF) and/or Ultra High Frequency (UHF) and/or High Frequency (HF) radio is authorized and available to provide communications between aircraft and maintenance.

5.2.5.2.3. Ensure the MOC has a hotline on the secondary crash phone net. **(T-3)**

5.2.5.2.3.1. When required, direct communications lines will be provided to QA, Munitions Control, EOD, airfield operations, base fire department, NDI, control tower and the central security control. **(T-3)**

5.2.5.2.4. Develop and exercise comm-out procedures to include loss of radios, Local Area Network (LAN) and phone. **(T-3)**

5.2.5.2.5. Ensure MOC personnel receive initial radio operating training before assuming duties involving radio operations IAW AFI 17-210 and **Chapter 11**. **(T-3)**

5.2.5.3. **(Added-AFGSC)** Validate aircraft and NC3 statuses in the MIS for accuracy. **(T-2)** At a minimum verify status codes, reason codes, status detail codes, WUCs, and GEOLOCs/Base codes. **(T-2)**

5.2.5.4. **(Added-AFGSC)** Ensure the accuracy of WUCs for aircraft status updates. The use of __000 or ___00 or ___99 (not otherwise code WUCs) will not be used when a more specific WUC is available**. (T-2)**

5.2.5.5. **(Added-AFGSC)** Reconcile uncompleted sorties daily in the MIS and coordinate with PS&D to resolve any issues. **(T-2)**

5.2.6. Engine Management. EM manages unit efforts to maintain adequate engine support for mission requirements by monitoring engine removals and replacements, component tracking, engine TCTOs and TCIs, engine records in the MIS and CEMS; and perform Engine Manager duties. Functions supporting EM will be combined within the wing and physically co-locate

with the Propulsion Flight. **(T-3)** The SRAN Engine Manager works and is co-located with the EM section. **(T-3)**

5.2.6.1. Specific EM responsibilities are detailed AFMAN 20-116, AFPAM 63-129, TO 00-25-254-1, -2 and **Chapter 14**.

5.2.7. Plans, Scheduling, and Documentation (PS&D). PS&D is responsible for coordinating aircraft maintenance requirements and utilization scheduling between maintenance, operations, and external agencies. PS&D oversees the entire maintenance scheduling effort throughout the wing and notifies applicable senior managers of scheduling process discrepancies and recommended courses of action.

5.2.7.1. Specific PS&D responsibilities are detailed in **Chapter 14**.

5.2.8. Maintenance Management Analysis (MMA). MMA tracks, analyzes, and presents information to help senior leadership assess the health of the units' weapon systems and equipment. MMA acts as the group POC for MIS issues and performs analyses to assess and improve unit performance (such as, effectiveness and efficiency of unit resources and logistical support processes). The MIS provides the main source of information used by analysts to assess unit performance and capability.

5.2.8.1. MMA will:

5.2.8.1.1. Be centrally organized but may locate analysts in the squadron to enable maximum responsiveness and effectiveness. **(T-3)**

5.2.8.1.1.1. When analysts are located in the squadron, they will still work directly for the MMA Section NCOIC/Chief who will provide their training and monitor the quality/relevancy of their workload. **(T-3)**

5.2.8.1.2. Provide information on analysis services, capabilities and training to units and maintenance supervision. **(T-3)** At a minimum, the following will be covered; MIS changes, on-going special studies, trend analysis, performance indicators/metrics TTP. **(T-3)** For units where MMA is centralized, perform monthly visits to maintenance work centers directly associated with aircraft generation. **(T-3)**

5.2.8.1.2.1. Work with MTS and/or FTD for opportunities to provide training on analysis services and capabilities (example, Mx Orientation, DCC Course). **(T-3)**

5.2.8.1.2.2. DELETED.

5.2.8.1.3. Calculate maintenance metrics and compare unit performance against MAJCOM and locally developed goals (if applicable). **(T-3)**

5.2.8.1.4. Develop products to track, monitor and identify seasonal and cyclical trends at the group, squadron, and unit level for MAJCOM reportable leading and lagging indicators. **(T-3)**

5.2.5.1.4.1. & 5.2.5.1.4.2. DELETED**.**

5.2.8.1.5. Review data for anomalies, variations, and trends to identify areas requiring further study. **(T-3)**

5.2.8.1.5.1. When significant seasonal or cyclical trends are identified in leading or lagging indicators, accomplish and document further analysis. **(T-3)**

5.2.8.1.5.1.1. Provide presentations, reports, studies/analyses, and briefings as requested or deemed appropriate. **(T-3)**

5.2.8.1.5.2. Units with like MDSs will compare and contrast metrics to identify significant variation. **(T-3)**

5.2.8.1.5.2.1. When significant variation is identified, accomplish and document further analysis. **(T-3)**

5.2.8.1.5.2.2. Provide presentations, reports, studies, analyses, and briefings as requested or deemed appropriate. **(T-3)**

5.2.8.1.6. Monitor wing, group, and squadron utilization rates. **(T-3)**

5.2.8.1.6.1. When operational requirements are not achieved, determine if assignable causes are present. Recommend corrective actions or measures when necessary. **(T-3)**

5.2.8.1.7. Assist unit leaders with the application and interpretation of maintenance data. **(T-3)**

5.2.8.1.8. Coordinate with PS&D and unit's Maintenance Supervision to provide monthly airframe, facility, and personnel capabilities (as required), attrition, and spare factors for use in planning the annual FHP. **(T-3)**

5.2.8.1.8.1. MAJCOMs will publish attrition and spare factors computations in a supplement to this instruction reference TO 00-20-2.

5.2.8.1.8.1. **(AFGSC)** Refer to **Attachment 15** for MAJCOM supplement guidance.

5.2.8.1.8.1.1. MMA will use MAJCOM supplement guidance to calculate attrition and spare factor computations. **(T-3)**

5.2.5.1.8.1.2. DELETED.

5.2.8.1.9. Analyze equipment performance trends to identify problems affecting the unit mission and, whenever possible, provide predictive analytical information with recommendations to unit's Maintenance Supervision. **(T-3)**

5.2.8.1.10. Verify accuracy of Job Data Documentation (JDD), flying schedule deviations, aircraft status and utilization within the MIS. **(T-3)**

5.2.8.1.10.1. Validate data entered into the MIS as part of daily analysis duties and inform affected agencies of discrepancies. **(T-3)**

5.2.8.1.10.1.1. **(Added-AFGSC)** Validate CANN documentation in MIS weekly, with materiel management, and inform unit supervision of its accuracy. If errors exist, reconcile with materiel management. More frequent validation may be required if recurring problems present themselves. Errors will be identified in DIT meetings. If analysts are assigned to a BGS or are decentralized then they will perform this function.

5.2.8.1.10.2. Identify erroneous or missing data to the responsible agency for correction or completion. **(T-3)**

5.2.8.1.11. Control the assignment of unit work center and mnemonic codes. **(T-3)**

5.2.8.1.11.1. Coordinate with P&R, MTS, or responsible agency on the assignment of alphanumeric and work center codes. **(T-3)**

5.2.8.1.11.2. Publish written guidance to control these codes when not provided by higher headquarters. Multiple mnemonic codes may be used within a work center code to accommodate different AFSCs assigned. **(T-3)**

5.2.8.1.11.2.1. **(Added-AFGSC)** Work center mnemonics are unique to IMDS and may be locally determined. Unit database managers will review work center codes annually to ensure compliance with guidance IAW TO 00-20-2, Appendix A. **(T-2)**

5.2.8.1.11.3. Coordinate new or revised mnemonic codes with affected activities for planning purposes. **(T-3)**

5.2.8.1.11.4. **(Added-AFGSC)** All work centers containing AFGSC equipment and personnel in IMDS will be loaded to AFGSC organization identifiers denoted by "GS" in the first two positions.

5.2.8.1.12. Be responsible for MIS database management. **(T-3)**

5.2.8.1.13. Assists MIS users in developing procedures for collecting information from deployments and exercises where the MIS is not available. **(T-3)**

5.2.8.1.14. **(Added-AFGSC)** All units possessing NC3 Standard Reporting Designator (SRD) /Equip-ID (e.g., ANXXX), will report Operational Availability "Ao" in their leading and lagging indicators on the Executive Summary as defined in TO 00-20-2 AFGSC supplement. **(T-2)**

5.2.8.1.15. **(Added-AFGSC)** Provide AFGSC/A4MQ with inputs used during development of the aircraft availability and maintenance metric standards, as requested. **(T-2)**

5.2.8.1.16. **(Added-AFGSC)** Submit AFGSC/A4-directed Sortie Utilization (SUTE) model or equivalent no later than 1 June to HQ AFGSC/A4MQ. **(T-2)**

5.2.8.2. In addition to the applicable Section NCOIC/Chief responsibilities outlined in **Chapter 2**, the MMA Section NCOIC/Supervisor will:

5.2.8.2.1. Ensure growth of analysis personnel by developing and maintaining a plan to rotate personnel through various duty positions within MMA.

5.2.8.2.1.1. Establish and coordinate plans for rotating 2R0XX personnel to increase field knowledge and experience every 24 months, not to exceed 36 months. **(T-3)**

5.2.8.2.1.2. This rotation plan applies to TSgts and below as well as 3- or 5-skill level personnel of any rank. **(T-3)**

5.2.8.2.2. Define the daily, weekly, monthly, and annual roles and responsibilities for each duty position within MMA. **(T-3)**

5.2.8.2.3. Ensure the CFM approved AFSC duty titles are utilized for all MMA personnel. **(T-3)**

5.2.8.3. Maintenance Information Systems (MIS). For management of IMDS-CDB, FMxC2, and Reliability and Maintainability Information System (REMIS), follow AFCSM 21-556, Vol 2, *Intro to IMDS CDB*, MAJCOM/Lead Command guidance, unit procedures, and REMIS user manuals. Personal computers and software used as "stand-alone" systems are not considered MIS.

5.2.8.3.1. Request to modify/create new functionality within IMDS-CDB IAW AFCSM 21-556V2. FMxC2 units will submit a System Change Request for any new requirements or corrections to existing features. **(T-3)**

5.2.8.3.2. Database Manager (DBM) will identify functions that require subsystem monitors and provide applicable training to those responsible for ensuring the accuracy/sustainment of their subsystem. **(T-3)**

5.2.8.3.2.1. Subsystem monitors will be appointed by the Section Chief of subsystem functions (such as, PS&D Section Chief appoints and signs appointment letter for configuration management). **(T-3)**

5.2.8.3.2.2. MMA is responsible for the overall management of the JDD subsystem. **(T-3)**

5.2.8.3.3. MAJCOMs will provide guidance describing the management of the MIS listed in **paragraph 5.2.8.3** within their command.

5.2.8.3.4. At a minimum, the MMA MIS/Host DBM will ensure:

5.2.8.3.4.1. MAJCOM coordination occurs when problems exist that are beyond the scope of responsibilities of Host DBMs. **(T-3)**

5.2.8.3.4.2. IMDS-CDB/FMxC2 security is maintained IAW AFI 17-130, *Cybersecurity Program Management*.

5.2.8.3.4.2.1. MMA personnel coordinate MIS access permission requirements to enable MDD on non-possessed aircraft. **(T-3)**

5.2.8.3.4.2.2. **(Added-AFGSC)** MIS managers will annually review a listing of outside ELC users. Requests must have an access expiration date. Renew or remove ELC guest users when they exceed the expiration date. **(T-2)**

5.2.8.3.4.2.3. **(Added-AFGSC)** MMA will retain a DD Form 2875, *System Authorization Access Request,* for all users requesting initial access to IMDS-CDB/FMxC2, unless an Air Force Identity, Credential, and Access Management (ICAM) system becomes available. **(T-2)** Perform annual audits of retained forms to verify users still require access to the MIS. **(T-2)**

5.2.8.3.4.3. MMA personnel provide expertise on IMDS-CDB/FMxC2 for resolution of problems beyond the work center and sub-system monitors' control. **(T-3)**

5.2.8.3.4.4. Support is provided to tenant organizations and users. **(T-3)**

5.2.8.3.4.4. **(AFGSC)** DBM support requirements will be identified in an MOA

or the Host Tenant Support Agreement. **(T-2)**

5.2.8.3.4.5. Coordination with the Defense Enterprise Computing Center or AF Network Control Center on all matters concerning IMDS-CDB. **(T-3)**

5.2.8.3.4.6. The Defense Enterprise Computing Center supports all requirements concerning the operation and maintenance of IMDS-CDB. **(T-3)**

5.2.8.3.4.7. Scheduled MIS downtime is published for users. **(T-3)**

5.2.8.3.4.8. MMA personnel control and monitor submissions of IMDS-CDB Difficulty Report(s). **(T-3)**

5.2.8.3.4.9. Coordination occurs on matters pertaining to the interface of other automated systems with IMDS-CDB. **(T-3)**

5.2.8.3.4.10. A functional checklist is developed to establish timelines and MIS data capture requirements for use in the event of a weapon system mishap. **(T-3)**

5.2.8.3.4.10.1. The checklist must require immediate capture and isolation of the historical data for the mishap weapon system regardless of the time or day of week. **(T-3)** Contact the Host DBM to immediately put the IMDS-CDB in File Update Mode (when required) until the functional checklist can be completed. FMxC2 equipment records will be locked using screen 9012 (Lock/Unlock Aircraft/Data Records). **(T-3)**

5.2.8.3.4.10.1. **(AFGSC)** Notify AFGSC/A4MQ within 24 hours of mishaps, incident, or crashes via email at: **AFGSC.A4M.Workflow@us.af.mil**. **(T-2)** This does not apply to impounds that are self-induced or mishaps where the cause is known (DOPs, FOD incidents, etc.)

5.2.8.3.4.10.2. **(Added-AFGSC)** At a minimum, the checklist will require actions in **Table 5.1** for IMDS bases (for other primary MISs use locally established procedures).

5.2.8.3.4.11. Support of the Communications-Electronics maintenance community referring to DAFI 21-103 and TO 00-33A-1001, *Methods and Procedures, General Cyber Defense Operations Activities Management Procedures and Practice Requirements,* for maintenance analysis and host DBM responsibilities.

5.2.8.3.4.12. Control of access to specific IMDS-CDB programs and subsystems by utilizing Transaction Identification Codes (TRICs) security profiles or screen 9057 (program access) for FMxC2. **(T-3)**

5.2.8.3.4.12.1. Audit permissions to IMDS security profiles and FMxC2 access keys annually. Take appropriate measures when a compromise is suspected or reported. **(T-3)**

5.2.8.3.4.12.2. Semi-annually audit IMDS ELC access. **(T-3)**

5.2.8.3.4.13. IMDS-CDB subsystem managers are informed of the status of applicable TRICs prior to turning the TRIC on or off. **(T-3)**

5.2.8.3.4.14. **(Added-AFGSC)** A User Group meeting is held at least quarterly to identify user problems, provide on the spot training to correct user documentation

problems, and to discuss other issues relating to operation of the system.

5.2.8.3.4.14.1. **(Added-AFGSC)** Tenant unit database managers will be invited to this meeting.

5.2.8.3.4.15. **(Added-AFGSC)** Procedures identified in IMDS User's Manual AFCSM 21-571, *Database Management,* are performed in case of inadvertent entry of classified information into the MIS. **(T-2)** Notify AFGSC/A4MQ or AFGSC/A4N within 24 hours if classified data has been input into the MIS via email at: **AFGSC.A4M.Workflow@us.af.mil**. or **AFGSC.A4N.Workflow1@us.af.mil**. Note: Do not send classified information in the e-mail. Further instructions will be provided by email.

5.2.8.3.5. MMA is the focal point for codes used on the maintenance data documentation process. This includes maintenance deferred codes, delayed status codes, flying scheduling deviation and cause codes listing. **(T-3)**

5.2.8.3.5.1. Use the MAJCOMs approved codes and narrative for official use. Code listings will be adjudicated yearly by all commands. **(T-2)**

5.2.8.3.5.2. Recommended changes, additions, and deletions to these codes and/or data elements will be adjudicated and approved by all MAJCOMs. MMA will submit request to their respective MAJCOM to initiate and coordinate any updates to the code listings. **(T-2)**

5.2.8.3.6. Data Integrity. MMA is the OPR for the Data Integrity Team (DIT). All maintenance units will participate in the DIT program. **(T-3)**

5.2.8.3.6.1. The purposes of the DIT include: (1) ensuring the unit has complete and accurate data in the MIS and aircraft forms, (2) identifying and quantifying problems within the unit preventing complete and accurate documentation, and (3) identifying and correcting the root causes for poor data integrity. The DIT is established to evaluate/isolate/eliminate documentation problems in IMDS-CDB/FMxC2/DPAS M&U Module. MMA will ensure that all assigned DIT members are trained in the use of MIS applicable programs for the data integrity review/correction process. **(T-3)** Errors identified by the DIT team will be reconciled IAW **Paragraph 5.2.5.3.6.5**. **(T-3) Note:** DIT should be aware of Logistics Interference (LI) and data errors that may be the result of purposeful efforts. DIT will note possible LI and monitor for trends and report unusual behavior IAW AFI 17-130.

5.2.8.3.6.2. The DIT will include, at a minimum, one representative from each squadron under the MXG. It will include participation from PS&D, MOC, DMS, EM, Debrief Section, and QA as determined by MMA. **(T-3)**

5.2.8.3.6.3. MAJCOMs will determine the frequency of DIT meetings.

5.2.8.3.6.3. **(AFGSC)** DIT meetings will be held quarterly with squadron representatives. **(T-2)**

5.2.8.3.6.4. Representatives will be at least a SrA that possesses a 5-skill level and is familiar with the unit's assigned weapon system(s). **(T-3)**

5.2.8.3.6.5. As a minimum, the following functions will be performed by the DIT:

5.2.8.3.6.5.1. Educate group, squadron, and AMU leadership on the importance of data integrity including the impacts of erroneous data.

5.2.8.3.6.5.2. Ensure MIS accurately reflects AFTO Form 781-series forms entries.

5.2.8.3.6.5.2. **(AFGSC)** Perform a 10% spot check for paper AFTO Form 781A/K to ensure that jobs are documented in the MIS**. (T-2)**

5.2.8.3.6.5.3. Run maintenance action review background reports for all work accomplished by squadrons and work centers.

5.2.8.3.6.5.3.1. Audit the report by JCN/WCE (Work Event Separator for FMxC2) to identify suspected errors.

5.2.8.3.6.5.3.2. Responsibility for correcting errors belongs to the performing work center.

5.2.8.3.6.5.3.2.1. The use of general WUCs/LCNs when a component level WUC/LCN exists will be counted as an error. **(T-3)**

5.2.8.3.6.5.3.3. Audit for Weapons System status, flying schedule deviation and utilization errors. **(T-3)**

5.2.8.3.6.5.3.4. Use of automated processes is authorized.

5.2.5.3.6.5.4.1. DELETED.

5.2.8.3.6.5.3.5. Develop a system to track, measure and report data integrity errors by work center, AMU, and squadron. **(T-3)**

5.2.8.3.6.5.3.6. Implement training programs that are geared toward correcting data integrity trends. **(T-3)**

5.2.8.3.6.5.4. **(Added-AFGSC)** The Data Integrity Management Tool in Envision will be used for DIT tracking, however, locally built products may be used if the tool is unavailable**.**

5.2.8.3.6.5.4.1. **(Added-AFGSC)** Units will have a 5-duty day suspense to correct errors and report back to the DIT. **(T-2)**

5.2.8.3.6.5.4.2. **(Added-AFGSC)** Data integrity metrics will be reported monthly to the MXG/CC and all applicable squadron commanders. **(T-2)** Metrics will include capturing data errors for statusing, utilization, deviations, and job data documentation.

5.3. Maintenance Training (MT). MT consists of the Training Management Element and the Development and Instructor Element. Maintenance Training assists SQ/CCs by providing Unit Training Managers (UTM) to manage the enlisted specialty training program. MT will:

5.3.1. Provide initial, recurring, and advanced proficiency, qualification, or certification training needed by a technician to perform duties in their primary AFSC and manage course codes to track training IAW AFI 36-2650 and DAFMAN 36-2689.

5.3.2. Serve as the single point of contact for all training matters affecting maintenance. **(T-3)**

5.3.2. **(AFGSC)** Coordinate training Course Control Documents (CCD) for explosive safety training through the wing weapons safety office annually. **(T-2)**

5.3.2.1. **(Added-AFGSC)** Ensure all maintenance personnel (AFSC 2A7X3/2A7X5 personnel are exempt) receive annual Corrosion Prevention and Control training. CBT is available and is the preferred method. Additionally, annual training will include specific excerpts regarding local/unique corrosion factors. **(T-2)**

5.3.2.1.1. **(Added-AFGSC)** Training will be documented in MIS. **(T-2)**

5.3.2.1.2. **(Added-AFGSC)** Training programs will be forwarded to MAJCOM Corrosion Prevention and Control Program Manager at AFGSC.A4M.Workflow@us.af.mil, for review and approval. **(T-2)**

5.3.3. The MT Superintendent/NCOIC will maintain administrative responsibility for UTMs whether UTMs are centralized or decentralized. **(T-3)**

5.3.4. Develop and administer appropriate Maintenance Cyber Discipline training. Training will be tailored to DoD Information Technology used locally and will emphasize authorized, and unauthorized uses, prevention, detection, remediation, and provide an overview of recent negative trends and effective mitigation techniques. **(T-3)**

5.3.4.1. Coordinate with Quality Assurance, MXG/CC designated responders, and facilitators for action when discovery that DoD Information Technology lacks the capability to perform a mission function. **(T-3)** Example: Enhanced Technical Information Management System containing software for a TO task that does not have a hardware TO approving its installation or use.

5.4. Programs and Resources (P&R). P&R serves as the MXG focal point for interaction with external functional support activities to ensure critical mission generations support, infrastructure personnel management and resources are configured to maximize mission capability/AA. P&R program configurations may vary based on mission but generally P&R coordinates with functional base OPRs to interact on Facility Management (FM), Vehicle Control (VCO), Support Agreements, Unit Safety, Security, Resources, Manpower, Environment, Deployment and Maintenance Information System programs as applicable. Units will maximize consolidation of personnel assigned in P&R as described in **Paragraph 2.4.14**. P&R will:

5.4.1. Develop, maintain, and coordinate all applicable AFI-directed programs and plans affecting maintenance. **(T-3)**

5.4.2. Act as the resource advisor to the MXG/CC. **(T-3)**

5.4.3. Coordinate with the MXG/Squadron SUPTs to manage manpower authorizations for the MXG. **(T-3)**

5.4.4. Serve as the focal point within the MXG for management of facilities. **(T-3)**

5.4.4.1. Ensure fire detection and foam suppression training is included in unit facility manager/ occupant training briefings. **(T-3)**

5.4.5. Serve as the Environmental Coordinator focal point within the MXG. **(T-3)**

5.4.6. Serve as the focal point for MXG deployment planning and execution actions. **(T-3)** If designated as a UTC pilot unit IAW DAFI 10-401, *Operations Planning and Execution*, P&R will:

5.4.6.1. Coordinate with other UTC tasked units on cargo and equipment authorizations/requirements to develop and maintain a standardized package to meet specific mission capability requirements. **(T-3)**

5.4.6.2. Coordinate with the unit equipment custodian(s) to review equipment changes and new equipment requirements driven by changes to UTCs and/or Allowance Standards (AS). **(T-3)**

5.4.6.3. Assist with coordination of site surveys for deployment locations and maintain copies of the Expeditionary Site Plan (ESP) **Part I** for deployment locations IAW AFI 10-404, *Base Support and Expeditionary (BAS&E) Site Planning*.

5.4.6.4. Coordinate with QA biennially to verify aircraft MDS Hot Pit refueling capabilities are current and accurate in Base Support and Expeditionary and ensure applicable ESP/BSP **Parts I** and **II** accurately reflect unit capabilities IAW AFI 10-404, if applicable. **(T-3)**

5.4.7. Oversee local, functional or host country unique support agreements applicable to the MXG IAW AFI 25-201, *Intra-Service, Intra-Agency, and Inter-Agency Support Agreements Procedures*.

5.4.8. Develop and coordinate MXG commercial contracts as directed by the MXG/CC. **(T-3)**

5.4.9. Manage readiness reporting for the MXG IAW AFI 10-201.

5.4.10. Coordinate with LRS Deployment & Distribution Flight to obtain unit assistance in interpreting guidance for marking, packing, and marshaling of tasked equipment IAW DAFMAN 24-604, *Preparing Hazardous Materials for Military Air Shipments*, DAFI 10-401 and DESR6055.09_AFMAN 91-201.

Chapter 6

QUALITY ASSURANCE (QA)

6.1. General. Maintenance quality and equipment reliability is the responsibility of all maintenance personnel. The combined efforts of QA personnel, maintenance leaders, and technicians are necessary to ensure high quality maintenance production and equipment reliability. The QA staff evaluates the quality of maintenance accomplished and performs necessary functions to manage the MSEP. Personnel assigned to QA are not an extension of the work force and will not be tasked to perform sortie production inspections unless authorized by the MXG/CC or MGFE/CC on a case-by-case basis. **(T-2)** QA serves as the primary technical advisory agency in the maintenance organization, assisting maintenance supervision at all levels to identify, validate and/or resolve quality, proficiency and/or compliance issues impacting mission generation. The evaluation and analysis of deficiencies and problem areas identified are key functions of QA that highlight and reveal underlying causes of poor quality in the maintenance production effort. Aircraft and equipment condition and personnel proficiency are validated through the MSEP and recorded in the Logistics Evaluation Assurance Program (LEAP) QA database. Civil service and contracted personnel are to follow requirements established in their respective civilian position description/contract and accepted quality assessment system.

6.1.1. **(Added-AFGSC)** For munitions units not aligned under a maintenance group or geographically separated from parent group, the QA munitions inspectors may be directly responsible to the assigned squadron commander. This will be documented by a delegation letter from the group commander.

6.1.2. **(Added-AFGSC)** The MXG may assign QA augmentees for shops with unique requirements (e.g., Egress, NDI, etc.). The MXGs will develop a training plan for augmentees, if assigned.

6.1.2.1. **(Added-AFGSC)** For the purposes of this instruction, QA Egress Augmentees and their training are considered separate from Egress Augmentees, and their training will be managed IAW **Chapter 6** of this instruction.

6.1.3. **(Added-AFGSC)** CORs, and personnel who oversee CORs, such as QA Superintendent and Chief Inspectors, must be trained, managed and evaluated IAW DAFI 63-138, *Acquisition of Services*. **(T-2) Note:** These requirements are only necessary if a contract currently needs surveilling.

6.1.4. **(Added-AFGSC)** Additional program information and definitions unique to Nuclear and ICBM personnel are described in AFMAN 21-200.

6.2. Responsibilities. QA is responsible to the MXG/CC or equivalent to perform as the primary technical advisory agency for maintenance actions and to assist work center supervisors in reviewing tasks involved in supporting the maintenance effort. MXG QA Inspectors have the authority to observe, correct and document applicable maintenance activities performed within the MXG. QA will:

6.2. (AFGSC) Responsibilities. QA authorizations are based on tasks described in the Air Force Manpower Standard. The MXG/CC has the option of centralizing certain programs (e.g., Wing Inspection Team (WIT) members, Self-Assessments, COR, etc.). However, while centralized control of these programs is desirable and often necessary, management of excessive programs

diminishes QA's ability to administer functions required by this chapter. Commanders should consider augmenting UMD-authorized QA personnel to fulfill obligations of locally imposed programs. Additional QA authorizations must be funded utilizing existing manpower resources.

6.2.1. Implement and administer the MSEP and other programs as applicable to include:

6.2.1.1. Product Improvement Program (PIP). **(T-2)**

6.2.1.1.1. DR. **(T-2)**

6.2.1.1.2. Product improvement inputs. **(T-2)**

6.2.1.2. Aircraft and equipment impoundment procedures IAW **Chapter 7**.

6.2.1.3. Functional Check Flight (FCF) program IAW this **Chapter**. **(T-2)**

6.2.1.4. W&B Program IAW this **Chapter**.

6.2.1.5. Hot Refuel/Defuel and Aircraft-to-Aircraft Refuel Programs if applicable. **(T-2)**

6.2.2. Review and analyze aircraft aborts, IFEs, and incidents involving damage to equipment or injury of personnel to determine if trend analysis, cross-tell or MSEP focus is warranted. **(T-2)**

6.2.3. Comply with the configuration management program requirements IAW **Chapter 14**. **(T-2)**

6.2.4. In coordination with PS&D, comply with TCTO Program requirements IAW **Chapter 14**, TO 00-5-1 and TO 00-5-15.

6.2.5. In conjunction with PS&D, develop a local Job Standard (JST) for both gaining and losing aircraft and equipment transfer inspection IAW **Chapter 14**. **Note:** For the purpose of this instruction JST is an alpha code identifying the type of job represented in a job standard (defined in IMDS User's Manual AFSM 21-566, Volume 2).

6.2.6. Coordinate with PS&D on all AFTO Form 103s. **(T-2)**

6.2.7. Manage OTIs. **(T-2)**

6.2.8. Augment evaluations at the request of the WS. **(T-2)** Flightline weapons loading inspections/evaluations are the responsibility of WS evaluators.

6.2.9. Evaluate unit maintenance management procedures, including locally developed forms, publications, OIs, checklists, for accuracy, intent, and necessity as referenced in this DAFI.

6.2.9.1. **(Added-AFGSC)** QA will perform a final comprehensive review of all aircraft forms and MIS documentation initiated from the last flight prior to the first flight on Hangar Queen Aircraft. **(T-2)**

6.2.10. Evaluate cyber hygiene, discipline practices, and cyber incident reporting per applicable TO, Wing directive, and this instruction for compliance. **(T-2)**

6.2.10.1. Report weapons system and support equipment cyber related deficiencies to the applicable Program Manager IAW T.O. 00-35D-54.

6.2.10.1.1. Elevate resolution of deficient cyber-requirements or issue via an AF Form 1067, Modification Proposal IAW AFI 63-101/20-101, and/or maintenance assistance

request (such as, Technical Assistance Request) IAW TO 00-25-107 *Maintenance Assistance*.

6.2.11. **(Added-AFGSC)** QA is not responsible for inspecting tenant units, unless outlined in a support agreement or a memorandum. For observations or QA concerns, host QA should notify tenant's chain of command. **(T-2)**

6.3. QA Superintendent (QA SUPT) Responsibilities. In addition to the applicable Flight CC/SUPT duties in **Chapter 2** the QA SUPT will:

6.3.1. Develop and maintain a master training plan to train all QA Inspectors, and include augmentees, if applicable. **(T-2) Note:** See **Paragraph 5.2.1.13** for minimum MAJCOM training requirements for inspectors inspecting MXO function.

6.3.1. **(AFGSC)** Master training plan will include the AFGSC standardized QA task list on a DAF Form 797 or digital equivalent. AFGSC standardized QA training guide is located on the AFGSC A4MQ Maintenance Policy SharePoint site. **(T-2)**

6.3.2. Develop and monitor the MSEP using the LEAP QA database and provide supervisors access to MSEP data. **(T-2)**

6.3.3. Notify the appropriate agencies when deficiencies are found in (AF, MAJCOM/Lead Command, WG, Group (GP)) instructions. **(T-2)**

6.3.3.1. **(Added-AFGSC)** Notify Command Egress Manager within 24 hours of notification of Egress Augmentee violations.

6.3.4. Review maintenance-related instructions, supplements, operating instructions, forms, and local/functional and emergency action checklists every two years or when source data changes for accuracy, intent, and necessity. **(T-2)**

6.3.4.1. The QA SUPT will document the review once complete. **(T-2)**

6.3.5. Review JSTs annually or when source data changes for accuracy, intent, and necessity. **(T-2)**

6.3.5. **(AFGSC)** Publish a list of approved job standards managed by QA at least annually. **(T-2)**

6.3.5.1. The QA SUPT will document the review once complete. **(T-2)**

6.3.5.2. **(Added-AFGSC)** For JST updates outside of annual reviews, units will monitor weekly TO changes and initiate package updates when necessary. The owning work center will submit proposed changes using local procedures through the unit's QA office.

6.3.6. Ensure management and special inspections are performed (when required). **(T-2)**

6.3.7. Ensure the GP portion of the FOD Prevention Program is conducted IAW **Chapter 11**. **(T-2)**

6.3.8. Oversee and implement the GP Impoundment Procedures IAW **Chapter 7**. **(T-2)**

6.3.9. Coordinate on all requests for locally manufactured, developed, and modified tools and equipment, and maintain records for approved requests. **(T-2)**

6.3.9.1. This includes pictures or drawings and a description of the use for each item.

6.3.9.1.1. If applicable technical data contains the option for use of these tools and equipment, QA does not need to coordinate or maintain the records on these items.

6.3.9.1.2. Locally manufactured, developed, or modified equipment for weapons loading, maintenance and the armament systems flight must be coordinated through the WWM before routing to QA. **(T-2)**

6.3.9.2. **(Added-AFGSC)** Develop local manufacturing request/routing form and file all approved requests within the QA office for future use. **(T-2)**

6.3.10. Verify IPI requirements from MAJCOM and sources outlined in TO 00-20-1 and publish combined MXG IPI listing every 2 years as a minimum or when source data changes. **(T-2)**

6.3.11. Develop KTL/RIL to supplement MAJCOM listings (if required). **(T-2)**

6.3.11.1. Provide copies of approved KTL/RIL to all affected organizations. **(T-2)**

6.3.12. Ensure Acceptable Quality Level (AQL) Standards are developed for all tasks including key tasks and routine inspections not included on the MAJCOM AQL. **(T-2)**

6.3.13. Ensure agendas and presentations are compiled for the MSEP summary. **(T-2)**

6.3.14. Review wing requests for assistance IAW **Chapter 1** and **Chapter 14**.

6.3.15. Designate a Chief Inspector. **(T-2)**

6.3.16. Designate individuals to be the Technical Order Distribution Office (TODO) and Product Improvement Manager (PIM). **(T-2)**

6.3.17. Designate individuals to be the W&B and FCF Program managers. **(T-2)**

6.3.18. Monitor the ASIP IAW **Chapter 11**.

6.3.19. Maintain DOP program oversight IAW **Chapter 11**.

6.3.20. When hot refueling is performed by maintenance personnel, ensure Hot Refueling Program is accomplished IAW TO 00-25-172 and this DAFI.

6.3.21. Ensure non-resident organizations hot refueling aircraft at an AF certified hot pit coordinate site/personnel certification, utilization and documentation requirements with the supporting QA and Airfield Management/Operations. **(T-2)**

6.3.21.1. Using units are responsible for maintaining currency/reporting requirements. **(T-2)**

6.3.22. Ensure designated Responders/facilitators respond to DoD IT incidents that lack the capability to perform a mission function. **(T-2)**

6.3.22.1. Consolidate and report incidents in conjunction with appropriate POC (e.g., WAM, TODO, or designated official). **(T-2)** Example: ETIMS containing software for a TO task that does not have a hardware TO approving its installation or use.

6.4. Chief Inspector Responsibilities. The Chief Inspector is responsible to the QA SUPT for ensuring functions listed below are performed and is responsible for applicable Section NCOIC/Chief duties in **Chapter 2**. The Chief Inspector will:

6.4.1. Use assigned inspectors/augmentees to provide on-the-spot assistance to correct problems. **(T-2)**

6.4.2. Spot-check TOs, inspection work cards, checklists, job guides and WUC manuals during evaluations and inspections for currency and serviceability. **(T-2)**

6.4.3. Assist MMA with investigations and studies. **(T-2)**

6.4.4. Review QA LEAP MSEP inspection summary inputs for accuracy and content. **(T-2)**

6.4.5. Initiate actions when additional attention is required to resolve adverse maintenance trends or training problems. **(T-2)**

6.4.5.1. Actions include preparing cross-tell information bulletins and messages for MXG/CC release to other similarly equipped units and higher headquarters.

6.4.6. Review and compile inputs for updating the IPI listing. **(T-2)**

6.4.6.1. Maintain a copy of the MXG/CC or equivalent approved IPI listing with the signature and date of review and certification. **(T-2)**

6.4.7. Review Category II major discrepancies for trends quarterly. **(T-2)**

6.4.7.1. If frequency or severity of identified discrepancies warrant inclusion of that item into a specific TO governing an action or inspection, the QA Chief Inspector must submit an RC or develop a local work card, local page supplement or checklist IAW TO 00-5-1.

6.4.8. Establish procedures for QA Inspectors to document completed inspections. **(T-2)**

6.4.9. Perform inspections on GITA IAW **Chapter 11**. **(T-2)**

6.4.9. **(AFGSC)** Perform semi-annual inspections.

6.4.10. Construct and maintain a master standardized AFTO Form 781-series forms binder IAW TO 00-20-1.

6.4.10.1. **(Added-AFGSC)** Maintain a master AFTO Form 781-series forms binder for each MDS assigned.

6.4.10.2. **(Added-AFGSC) [NC3]** Units must incorporate the use of two AFTO Form 781As and two AFTO Form 781Ks when standardizing forms binders for aircraft with NC3 platforms assigned. See TO 00-20-1 AFGSC SUP for specific instructions on documenting aircraft and NC3 forms.

6.4.11. Develop an aircrew briefing checklist specifically for high-speed taxi checks (see **Paragraph 6.14**). **(T-2)**

6.4.12. Review MSEP data monthly to identify high-missed carded items from Personnel Evaluations and Quality Verification Inspections (QVI). **(T-2)** A high-missed carded item is defined as any work card item missed at least three times during a one-month period.

6.4.12.1. Coordinate with MMA to identify any relationships with repeat, recur and CND trends. **(T-2)**

6.4.12.2. Include this data in the monthly MSEP summary. **(T-2)**

6.4.13. Conduct Evaluator Proficiency Evaluations on each inspector. **(T-2)**

6.4.13.1. Evaluators Proficiency Evaluation (EPEs) will be conducted while the Chief Inspector assesses one Personnel Evaluation (PE) and one technical inspection (QVI/Special Inspection (SI)). **(T-2)**

6.4.13.2. Each QA Inspector, permanent or augmentee, must pass both EPEs prior to performing unsupervised evaluations and inspections. **(T-2)**

6.4.14. Document QA Inspector training in the MyTraining. **(T-2)**

6.4.15. Ensure each discrepancy/finding within rated inspections, evaluation, and observation reports have been assigned both a Category (CAT I or CAT II) and a Finding Severity (Maj or Min).

6.5. Quality Assurance Inspector Responsibilities. QA Inspectors will:

6.5.1. Evaluate flightline and back shop maintenance tasks/inspections and MXO functions to include items identified by the KTL/RIL. **(T-2)**

6.5.2. Enter inspection and evaluation reports into the LEAP QA database. **(T-2)**

6.5.3. Perform QA review of Dull Swords, TCTOs, OTIs, modification proposals, DRs, RCs, instructions, and supplements. **(T-2)**

6.5.4. Provide training/instruction as applicable to address deficiencies identified during evaluations/inspections. **(T-2)**

6.5.5. Evaluate forms and MIS documentation to evaluate compliance IAW MXG written procedures described in **Chapter 2**. **(T-2)**

6.5.6. Evaluate maintenance TO files that are kept on the aircraft (G files). **(T-2)**

6.6. Quality Assurance Inspector Training. As a minimum, the local QA Inspector Training Plan will include the applicable items listed below to ensure QA program standardization. **(T-2)**

6.6.1. Training must cover inspection and evaluation techniques, documenting inspection worksheets and actions to prevent injury to personnel or property/equipment damage. **(T-2)**

6.6.1.1. **(Added-AFGSC)** New MXG/QA personnel will be scheduled for QA Inspector Course (QAIC) within 30 days of assignment and will be completed prior to the first unsupervised evaluation. Refer to AFGSC MCL at: **https://usaf.dps.mil/sites.AFGSCHQ/hq/A4/A4M/A4BX/MaintenanceTraining/SitePages/AFGSC%20Maintenance%20Training.aspx**. **(T-2)**

6.6.1.2. **(Added-AFGSC)** QA Superintendent Course (QASC) is optional but highly encouraged, for QA Superintendents and Chief Inspectors.

6.6.2. All EPEs must be tracked in the MIS and/or the LEAP QA database. **(T-2) Note:** Additional requirements for Nuclear Weapons Certifying Officials are located in AFI 21-204.

6.6.2. **(AFGSC)** EPEs will be conducted annually for all personnel conducting inspections or evaluations. Completed training will be documented in the MIS and/or the LEAP QA database **(T-2)**

6.6.3. QA Inspectors inspecting outside of their AFSC will be task qualified on a Work Center Job Qualification Standard (WJQS) in MyTraining for the KTL requirements they evaluate. **(T-2)**

6.6.3.1. Chief Inspectors will identify other critical tasks requiring DAF Form 797, *Job Qualification Standard Continuation/Command JQS*, qualification (QA WJQS) within MyTraining as required. **(T-2)**

6.6.3.2. For all other tasks, QA Inspectors must be familiar with the requirements/procedures of tasks they evaluate. **(T-2)**

6.6.3.2.1. Cross-utilization for QA Inspectors is not allowed for 2W1, 2W0, 2A7X2, or 2P0X1 career field specific tasks. Inspectors will hold the respective AFSC, have accomplished any required ancillary/safety training, and evaluate IAW their respective AFIs/TOs. **(T-2)**

6.6.3.2.1.1. QA inspectors evaluating Scheduling and Analysis functions must be trained and qualified. **(T-2)** **Note:** See **Paragraph 5.2.1.13** for additional requirements.

6.6.4. & 6.6.5. DELETED.

6.6.6. MAJCOMs will determine if QA personnel who conduct engine run evaluations are required to maintain the engine run proficiency requirements outlined in **Chapter 11** and document requirements in their supplement to this DAFI. **(T-2)**

6.6.6. **(AFGSC)** AFGSC QA personnel who conduct engine run evaluations are not required to maintain the engine run proficiency requirements.

6.6.7. - 6.6.10.2. DELETED.

6.7. Maintenance Standardization and Evaluation Program (MSEP). The purpose of the MSEP is to provide units with a method of evaluating technical compliance and measure how well they comply with established standards.

6.7.1. Units will develop a MSEP and conduct local inspections to ensure their programs, processes, maintenance technician proficiency, equipment condition and other focus areas are in compliance with AF, MAJCOM, and local directives. **(T-2)** The unit level MSEP is not applicable to contract maintenance activities unless required by the contract SOW or PWS.

6.7.1.1. The MSEP will be developed in conjunction with inputs from assigned squadron Maintenance Supervision and Group Leadership and will be executed by QA. **(T-2)**

6.7.1.1.1. **(Added-AFGSC)** MXG MSEP reviews will be held quarterly, at a minimum, to discuss trending items, areas of improvement, and potential revisions to the local Evaluation and Inspection (E&I) Plan.

6.7.1.2. DELETED.

6.7.1.3. The following types of evaluations, inspections and observations support the MSEP: PEs, QVIs, SIs, Management Inspection (MI)s, Detected Safety Violation (DSV)s, Technical Data Violation (TDV)s, Unsatisfactory Condition Report (UCR)s, and when directed, other inspections.

6.7.1.3.1. These inspection terms may differ in the LEAP QA database however, MAJCOMs must provide non-standard terms and definitions in their supplement to this DAFI when used.

6.7.1.3.2. Develop the monthly MSEP on the minimum personnel evaluations, inspections or observation requirements as depicted in Air Force Manpower Standard 21QX Quality Assurance Application Tool, located on the Air Force Manpower Analysis Agency SharePoint site: **https://cs2.eis.af.mil/sites/11190/AFMDandAFMS/AFMS/Forms/FAC1stFAC2nd.aspx**.

6.7.2. Unit MSEP Focus Areas. QA will assess how units are meeting compliance goals and will identify areas of opportunity for improvement. **(T-2)** A unit's MSEP will focus on:

6.7.2.1. Compliance with and currency of TOs and directives. **(T-2)**

6.7.2.1.1. Ensure personnel at all levels are responsible and accountable for enforcing mandatory standards and ensuring all applicable TOs and directives are complete, current, and used.

6.7.2.2. Aircraft, systems, and equipment forms documentation. **(T-2)**

6.7.2.2.1. Ensure forms used to document any maintenance related action for aircraft, systems or equipment are documented IAW 00-20 series TOs, specific equipment TO requirements, and other applicable directives and supplements. **(T-2)**

6.7.2.2.2. MSEP will validate compliance with the MXG's or equivalents' written procedures to ensure aircraft/system forms, equipment forms and MIS documentation are complete, accurate, and accomplished for each shift as referenced in **Paragraph 2.4.53**. **(T-2)**

6.7.2.3. Aircraft, Systems and Equipment Inspections. **(T-2)**

6.7.2.3.1. Ensure aircraft and equipment, including munitions, are inspected IAW TOs and directives. **(T-2)**

6.7.2.4. Compliance and Management of Occupational Safety and Health, Environmental, Bioenvironmental, Housekeeping, and FOD Programs. **(T-2)**

6.7.2.4.1. Personnel at all levels are responsible for minimizing risk to equipment, personnel, and the environment. **(T-2)**

6.7.2.5. Training. **(T-2)**

6.7.2.5.1. Verify training is correctly documented and ensure individuals are qualified/certified to perform evaluated tasks. **(T-2)**

6.7.2.6. Unit-Directed Programs. **(T-2)**

6.7.2.6.1. Verify units' programs are in compliance with local directives. **(T-2)**

6.7.2.7. Key Task List (KTL). The KTL is an AF, MAJCOM or unit developed list of required inspections that cover tasks that are complex and tasks affecting safety of flight.

6.7.2.7.1. MAJCOMs will identify minimum KTLs for each MDS. **(T-2)**

6.7.2.7.1.1. **(Added-AFGSC)** AFGSC Key Task List (KTL) will only be waived with MXG/CC approval. Include, at a minimum, the following categories on the unit's KTL if applicable: **(T-2)**

6.7.2.7.1.2. **(Added-AFGSC)** Engine final inspection (JEIM) (propulsion shop).

(T-2)

6.7.2.7.1.3. **(Added-AFGSC)** Engine bay inspections prior to engine installation. (Only applies to B-1 and B-2). **(T-2)**

6.7.2.7.1.4. **(Added-AFGSC)** Engine, after installation. **(T-2)**

6.7.2.7.1.5. **(Added-AFGSC)** Engine throttle at time of installation. **(T-2)**

6.7.2.7.1.6. **(Added-AFGSC) [JEIM Only]** On F118-100 and F101-102 engines, whenever maintenance is performed on the variable stator vane system. **(T-2)**

6.7.2.7.1.7. **(Added-AFGSC)** Phase/Isochronal Inspections: MXG/CC will establish percentage requirements for work cards/inspection items to evaluate for each inspection area (APG, HYD, E/E, etc.). These areas will be identified in the MSEP. **(T-2)**

6.7.2.7.2. All maintenance actions/functions listed on the KTL require mandatory call-in to QA each time the maintenance action/function is accomplished. **(T-2)**

6.7.2.7.2.1. QA evaluators will respond and perform an evaluation. **(T-2)**

6.7.2.7.2.1.1. The MXG/CC may waive the inspection or designate authorized a representative(s) to waive the inspection.

6.7.2.7.2.1.2. QA will track all KTLs called in, waived, or completed and maintain a list of MXG-designated KTL waiver authorities. **(T-2)**

6.7.2.7.2.1.3. **(Added-AFGSC)** KTL inspections will be documented on a Red Dash (-), referenced to the original Red X discrepancy, and signed off by the QA evaluator who performed the inspection IAW TO 00-20-1.

6.7.2.7.3. QA will review and update the KTL list at least every 2 years to ensure it encompasses those maintenance actions/functions directly affecting quality of maintenance. **(T-2)**

6.7.2.8. Routine Inspection List (RIL). The RIL is an AF, MAJCOM, or unit developed list of routine inspections that must be performed.

6.7.2.8. **(AFGSC)** The Air Force and AFGSC established Routine Inspection List (RIL) items will be evaluated in conjunction with MSEP review. **(T-2)** AFGSC standardized RIL items are on the AFGSC A4 External SharePoint® site: **https://usaf.dps.mil/sites/AFGSC-HQ/hq/A4/A4M/A4BX/AFGSCacftmxpolicy/SitePages/Home.aspx**.

6.7.2.8.1. QA will consolidate Maintenance Supervision inputs and suggested changes for the RIL. **(T-2)**

6.7.2.8.2. Additional RIL requirements for nuclear capable units are located in AFMAN 21-200.

6.7.2.8.3. Tasks will not be removed from the RIL without issuing authorities' approval (such as, AF, MAJCOM, MXG/CC). **(T-2)**

6.7.2.8.4. The RIL must contain the following if applicable to the unit:

6.7.2.8.4.1. Pre-flight. **(T-2)**

6.7.2.8.4.2. Thru-flight. **(T-2)**

6.7.2.8.4.3. Basic post-flight. **(T-2)**

6.7.2.8.4.4. HSC/HPO inspections. **(T-2)**

6.7.2.8.4.5. Aircraft forms/MIS documentation. **(T-2)**

6.7.2.8.4.6. Equipment forms/MIS documentation. **(T-2)**

6.7.2.8.4.7. Aircraft and munitions flightline accountability/accountable property system of record (APSR). **(T-2)**

6.7.2.8.4.8. Aircraft ground handling. **(T-2)**

6.7.2.8.4.9. Launch and recovery. **(T-2)**

6.7.2.8.4.10. Servicing tasks. **(T-2)**

6.7.2.8.4.11. Technical data. **(T-2)**

6.7.2.8.4.12. CTK Program. **(T-2)**

6.7.2.8.4.13. TMDE calibrations when the performing work center is not a PMEL IAW TO 00-20-14. **(T-2)**

6.7.2.8.4.14. AGE maintenance. **(T-2)**

6.7.2.8.4.15. AGE flightline use. **(T-2)**

6.7.2.8.4.16. Housekeeping. **(T-2)**

6.7.2.8.4.17. Vehicles. **(T-2)**

6.7.2.8.4.18. Aircraft washes/aircraft corrosion inspections. **(T-2)**

6.7.2.8.4.19. Supply discipline (example, TNB, DIFM management & coding). **(T-2)**

6.7.2.8.4.20. Equipment washes/ equipment corrosion inspections. **(T-2)**

6.7.2.8.4.21. Environmental compliance. **(T-2)**

6.7.2.8.4.22. NWRM accountability and forms documentation. **(T-2)**

6.7.2.8.4.23. TCTO Program. **(T-2)**

6.7.2.8.4.24. Time-Change Program. **(T-2)**

6.7.2.8.4.25. FHP management. **(T-2)**

6.7.2.8.4.26. Maintenance Cyber Discipline. **(T-2)**

6.7.2.8.4.26.1. Upload and download of software and data. **(T-2)**

6.7.2.8.4.26.2. Malicious code detection and reporting. **(T-2)**

6.7.2.8.4.26.3. Verify personnel upload required CPINS updates prior to use. **(T-2)**

6.7.2.8.4.26.4. Verify personnel validate antivirus scans of external media are

complete prior to use. **(T-2)**

6.7.2.8.4.26.5. Account for ATS/ATE in the appropriate APSR. **(T-2)**

6.7.2.8.4.26.6. Cyber hygiene. **(T-2)**

6.7.2.8.4.27. Repair Network Node Management. **(T-2)**

6.7.2.8.4.28. **(Added-AFGSC)** Aircraft status reporting. **(T-2)**

6.7.2.8.4.29. **(Added-AFGSC)** Aircraft engine intake/exhausts inspections. **(T-2)**

6.7.2.8.4.30. **(Added-AFGSC)** Weapons, flightline and back shop maintenance. **(T-2)**

6.7.2.8.4.31. **(Added-AFGSC)** Weapons maintenance and munitions build-up. **(T-2)**

6.7.2.8.4.32. **(Added-AFGSC)** Technical order management (inspection of a TO library). **(T-2)**

6.7.2.8.4.33. **(Added-AFGSC)** TO spot inspection (inspection of a single TO pulled off a shelf). **(T-2)**

6.7.2.8.4.34. **(Added-AFGSC)** Oil Analysis Program (to include sampling procedures, documentation, etc.).

6.7.2.8.4.35. **(Added-AFGSC)** Egress maintenance (except for egress tasks that require mandatory follow-up). **(T-2)**

6.7.2.8.4.36. **(Added-AFGSC)** Paint/corrosion control maintenance. **(T-2)**

6.7.2.8.4.37. **(Added-AFGSC)** Borescope program and procedures. **(T-2)**

6.7.2.8.4.38. **(Added-AFGSC)** Flight control rigging procedures and primary flight control rigging tasks as designated in aircraft MDS-specific technical data. **(T-2)**

6.7.2.8.4.39. **(Added-AFGSC)** Cannibalization aircraft review, (e.g., Warning tags, 781A documentation, aircraft condition, etc.) **(T-2)**

6.7.2.8.4.40. **(Added-AFGSC)** Support Equipment (SE defined in TO 00-20-1). **(T-2)**

6.7.2.8.4.41. **(Added-AFGSC)** Aircraft Jacket File Forms. **(T-2)**

6.7.2.8.4.42. **(Added-AFGSC)** Tail Number Bins (TNB)/Facilitate Other Maintenance (FOM), unless the inspection entity is determined to be MSG responsibility. **(T-2)**

6.7.2.8.4.43. **(Added-AFGSC)** Facility Inspection. **(T-2)**

6.7.2.8.4.44. **(Added-AFGSC)** Aircraft weapons systems reconfiguration activities (installation/removal of racks, adapters, launchers, pylons, etc.) **(T-2)**

6.7.2.8.4.45. **(Added-AFGSC)** Engine blade blending. **(T-2)**

6.7.2.8.4.46. **(Added-AFGSC)** Uninstalled engine test cell operation. **(T-2)**

6.7.2.8.4.47. **(Added-AFGSC)** Engine magnetic chip detector and oil filter inspection. **(T-2)**

6.7.2.8.4.48. **(Added-AFGSC)** Engine run hush house facility, test cell, and aircraft/engine run trim pad foreign object inspection. **(T-2)**

6.7.2.8.4.49. **(Added-AFGSC)** Inspect a minimum of 10 percent of aircraft every quarter for cleanliness and lubrication after aircraft wash.

6.7.2.8.4.50. **(Added-AFGSC)** Inspect the unit's Nuclear Certified Equipment program management for 100% accountability, serviceability and proper documentation annually **(T-2)**

6.7.2.8.4.51. **(Added-AFGSC)** Egress jacket files for currency and configuration.

6.7.2.8.4.52. **(Added-AFGSC)** Egress Augmentee training program for currency and standardization.

6.7.2.8.4.53. **(Added-AFGSC)** AvSE Management (account accuracy within ELMS or current MIS for support equipment. Ex: Custodian Responsibilities, on hand vs authorized and accuracy).

6.7.2.8.4.54. **(Added-AFGSC)** AvSE MIS Utilization (ELMS M&U scheduling and documentation).

6.7.2.9. QA will coordinate with the Munitions Activity (Munitions Supervision with in the MUNS) and will develop quarterly standards (such as, number of inspections and frequency) for the following areas:

6.7.2.9.1. Munitions accountability. **(T-2)**

6.7.2.9.2. Munitions storage practices, security, and safety. **(T-2)**

6.7.2.9.3. Munitions inspections. **(T-2)**

6.7.2.9.4. Munitions materiel handling and test equipment. **(T-2)**

6.7.2.9.5. Munitions stockpile management. **(T-2)**

6.7.2.9.6. Tactical missile reporting system. **(T-2)**

6.7.2.9.7. Munitions infrastructure (such as, adequacy of lightning protection and grounding systems, bonding of facility doors, adequate power conversion equipment). **(T-2)**

6.7.2.9.8. Munitions training programs. **(T-2)**

6.7.2.9.9. Maintenance Cyber Discipline. **(T-2)**

6.7.3. Unit MSEP Evaluation and Inspection (E&I) Plan. QA will develop an E&I Plan specifying numbers of approved areas and types (PE, QVI, SI, MI) of inspections and evaluations to complete during the month. Types of inspections must be separated and will not be combined (such as, PE/QVI). **(T-2)**

6.7.3.1. The E&I Plan, and changes to it, will be coordinated through each squadron Maintenance Supervision. **(T-2)**

6.7.3.2. The E&I Plan will be reviewed and updated monthly based on trends in the maintenance complex and will be adjusted to meet the MXG/CC's focus areas. **(T-2)**

6.7.3.2. **(AFGSC)** The E&I Plan will be published quarterly. **(T-2)**

6.7.3.3. When developing the E&I Plan, the QA SUPT will:

6.7.3.3.1. Address areas of concern identified by maintenance managers and the WWM. **(T-2)**

6.7.3.3.2. Tailor the plan for each squadron, flight, and section. **(T-2)**

6.7.3.3.3. Coordinate and distribute the E&I Plan. **(T-2)**

6.7.4. Evaluation Criteria.

6.7.4.1. Acceptable Quality Levels (AQL). AQLs denotes the maximum allowable number of minor findings that a process or product may be charged for the task to be rated "Pass" and are used to minimize subjectivity in assessing tasks identified by the MSEP.

6.7.4.1.1. MAJCOMs may develop standardized AQLs by weapon system and establish procedures to review at least annually.

6.7.4.1.1. **(AFGSC)** AFGSC standardized AQLs are found on the AFGSC A4 External SharePoint® site: **https://usaf.dps.mil/sites/AFGSC-HQ/hq/A4/A4M/A4BX/AFGSCacftmxpolicy/SitePages/Home.aspx**. These standardized AQLs may be adjusted more stringent than AFGSC standard, but not more lenient without AFGSC/A4MQ concurrence. AFGSC/A4MQ in conjunction with MXG QAs will perform annual AFGSC common and MDS standardized AQL reviews. **(T-2)**

6.7.4.1.2. MXG/CCs establish AQLs for local tasks/inspections.

6.7.4.1.2.1. AQLs need to be derived/revised from QA performance-based data.

6.7.4.1.3. AQLs/baselines for nuclear maintenance, cruise missile maintenance and nuclear weapons handling tasks are defined in AFMAN 21-200.

6.7.4.1.4. All findings will be rated Cat I or Cat II with a severity of Major or Minor. **(T-2)**

6.7.4.2. Discrepancy Categories.

6.7.4.2.1. Category I (CAT I). A required inspection/TO/AFI procedural item missed or improperly completed. This category is a specific AFI requirement, work card item or TO step, warning, caution, or note for a specific condition or action. Use findings of major or minor to indicate the discrepancy's relative severity.

6.7.4.2.2. Category II (CAT II). An obvious defect, which could have been readily detected by a technician or supervisor, but is not a specific AFI requirement, work card item or TO step, warning, caution, or note for that specific evaluated task. Use findings of major or minor to indicate the discrepancy's relative severity.

6.7.4.2.2.1. **(Added-AFGSC)** Zonal observations are defects observed while performing an inspection/evaluation and not part of the task/work card being inspected/evaluated. These observations will be CAT II. **(T-2)**

6.7.4.2.2.2. **(Added-AFGSC)** QA will review CAT II major discrepancies quarterly. Chief Inspectors will determine if items severity or frequency warrant inclusion in TOs. If so, QA submits a TO change request through ETIMS, or develops a local work card or checklist. **(T-2)**

6.7.4.3. Findings.

6.7.4.3.1. A major finding is defined as a condition that may endanger personnel, jeopardize equipment or system reliability, impact safety of flight or warrant discontinuing the process or equipment operation.

6.7.4.3.2. Any major discrepancy will result in an automatic inspection failure. **(T-2)**

6.7.4.3.3. The QA Inspector will intercede and declare a major finding when one additional action will result in one of the following: endanger personnel, jeopardize equipment or system reliability, impact safety of flight or warrant discontinuing the process or equipment operation. **(T-2)**

6.7.4.3.3.1. The QA Inspector will write up the major finding even though the jeopardizing action was never taken due to their intercession. **(T-2)**

6.7.4.4. A minor finding is defined as an unsatisfactory condition that requires repair or correction, but does not endanger personnel, impact safety of flight, jeopardize equipment reliability or warrant discontinuing a process or equipment operation.

6.7.4.4.1. CAT II minors will be documented for trends but must not be counted against the AQL. **(T-2)**

6.7.4.4.2. Soft FO contained in tool kits or found in cargo areas of aircraft which pose no FOD threat are classified as a minor finding since it will require more than one additional action to meet the definition of a major finding.

6.7.5. Observations. This category represents observed events or conditions with safety implications or technical violations not related to an evaluation or inspection, are considered unsafe, in violation of established procedures, or in the case of equipment, unfit for operations. Observations include: DSVs, TDVs and UCRs. The LEAP QA database is used to document any of the following conditions:

6.7.5.1. DSV. An observed unsafe act by an individual.

6.7.5.1.1. The QA Inspector must stop the unsafe act immediately. **(T-2)**

6.7.5.1.2. The QA Inspector will not document a separate DSV on an individual undergoing a PE since the unsafe act automatically results in a "Fail" rating on the PE. **(T-2)**

6.7.5.1.2.1. The QA Inspector will use DSV verbiage in the PE summary when a safety violation is committed during a PE. **(T-2)**

6.7.5.2. TDV. An observation of any person performing maintenance without the proper technical data available, available but not in use or not following the correct sequence of steps (if directed).

6.7.5.2.1. The technician must have knowledge of all general directives associated with the job prior to performing the task. **(T-2)** However, those general directives need not be present at the job site.

6.7.5.2.2. Do not document a separate TDV on an individual undergoing a PE but use TDV verbiage in the PE summary since failure to use technical data automatically results in a "Fail" rating.

6.7.5.3. UCR. An unsafe or unsatisfactory condition, other than a DSV, chargeable to the work center supervisor.

6.7.5.3.1. UCRs will be documented even when it is not possible to determine who created the condition. **(T-2)**

6.7.6. Evaluations. An evaluation represents the direct evaluation of a logistics action, inspection, or training conducted/performed by an individual or team. Evaluations are used to evaluate job proficiency, degree of training, and compliance with technical data or instructions.

6.7.6.1. PE. A PE is an over-the-shoulder (direct) evaluation of a maintenance action, inspection, or internal MXG support process (such as, PS&D, Analysis, MOC). Individuals performing, supervising, or evaluating tasks are subject to a PE. PEs may be performed on individuals working alone or as part of a team.

6.7.6.1.1. Rate PEs “Pass or Fail” based on established AQLs/standards. **(T-2)**

6.7.6.1.2. Document the PE in the LEAP QA database. **(T-2)**

6.7.6.1.3. PEs will be accomplished on all technicians who perform maintenance. **(T-2)** MAJCOMs will “establish” the frequency. **(T-2)**

6.7.6.1.3.1. **(Added-AFGSC)** Ensure a PE is accomplished annually on all technicians that perform maintenance to include MT instructors who accomplish maintenance tasks (pass or fail), not to exceed 12 months from the time the individual performed their last PE. **(T-2)**

6.7.6.1.3.2. **(Added-AFGSC)** Traditional Reservists and Drill Status Guardsmen performing maintenance will receive a rated PE as applicable to their MAJCOM 21-101 supplement. **(T-2)**

6.7.6.1.4. Personnel in any AFSC certified to perform nuclear maintenance or logistics operations (example, limited general maintenance, transfer, transport) will also comply with applicable PE requirements in AFMAN 21-200.

6.7.6.1.5. Types of PEs.

6.7.6.1.5.1. Individual Evaluations. This is a QA over-the-shoulder (direct) evaluation of a technician or supervisor performing a job.

6.7.6.1.5.2. Team Evaluations. This is a QA over-the-shoulder (direct) evaluation of technicians and supervisors performing a team task.

6.7.6.1.5.2.1. A team task is one requiring more than one person to complete the task (for example, refueling, ECM pod up/downloading, bomb build-up, towing, weapons maintenance, pylon installation).

6.7.6.1.5.2.2. Team evaluations must accurately assess the proficiency of each individual under evaluation.

6.7.6.1.5.2.2. **(AFGSC)** Errors committed by the team member(s) and not detected by the team chief/supervisor will also be attributed to the team chief/supervisor. Team evaluations are rated the same as PEs. **(T-2)**

6.7.6.1.5.2.3. Refer to AFMAN 21-200 for nuclear weapons maintenance and handling evaluations.

6.7.6.1.6. QA Inspectors will conduct on each NDI technician, for each NDI method annually (every 2 years for the ARC) to ensure effective trending on NDI methods. **(T-2)**

6.7.6.2. Performing a PE. When performing a PE, the QA Inspector will brief the individual or team on the evaluation and how it will be rated. **(T-2)**

6.7.6.2.1. The QA inspector will determine what task will be evaluated. **(T-3)**

6.7.6.2.2. The PE will include an evaluation of the individual's training records, SCR (if task requires), tools, equipment, TMDE (use/impact of certification label limitation on maintenance being performed), and TOs used to perform the task. **(T-2)**

6.7.6.2.2.1. **(Added-AFGSC)** If the PE to be conducted involves Egress Augmentees, ensure Augmentees are listed on current authorized Augmentee listing, and are current on their training.

6.7.6.2.3. The evaluation starts when the individual or team begins the task, or portion of the task to be evaluated, and is completed when the task or previously determined portion of the task is finished. **(T-2)**

6.7.6.2.4. Provide feedback to the individual or team and supervision upon completion. **(T-2)**

6.7.6.2.5. **(Added-AFGSC)** The QA inspector will update the individual's MIS (if system permissions allow) or provide the member an AF IMT 2426, Training Request and Completion, to document the annual PE requirement.

6.7.6.3. Rating PEs. QA Inspectors rate each evaluation based on AQLs/standards. The rating applies only to the specific task evaluated and not to other tasks that a technician or supervisor is qualified to perform. Upon completion of a failed evaluation, the QA Inspector must provide on-the-spot feedback. **(T-2)** Determine ratings as follows:

6.7.6.3.1. Pass: Number of discrepancies does not exceed AQL/standards.

6.7.6.3.2. Fail: An evaluation that results in any of the following:

6.7.6.3.2.1. Number of discrepancies exceeds the established AQL/standards.

6.7.6.3.2.2. A technician fails to detect a major discrepancy while complying with an inspection or TO requirement.

6.7.6.3.2.3. A technician fails to comply with a technical data step.

6.7.6.3.2.3.1. QA Inspectors will notify individuals immediately during the PE that a TDV was committed. **(T-2)**

6.7.6.3.2.3.2. Do not document a separate TDV on an individual undergoing a PE, since failure to use technical data automatically results in a "Fail" rating.

6.7.6.3.2.4. A technician demonstrates a lack of technical proficiency, system knowledge or demonstrated knowledge commensurate with skill grade.

6.7.6.3.2.5. Training and certification not documented.

6.7.6.3.2.6. A technician commits a safety violation.

6.7.6.3.2.6.1. Use the word "Safety" when a safety violation is committed during a PE.

6.7.6.3.2.6.2. Do not document a separate DSV on an individual undergoing a PE since the unsafe act automatically results in a "Fail" rating on the PE.

6.7.6.3.2.7. A technician fails to document maintenance actions in appropriate equipment records.

6.7.6.3.2.8. For nuclear weapons maintenance, an unsatisfactory rating must be given when any deficiencies or applicable unsatisfactory conditions exist IAW AFMAN 21-200. **(T-2)**

6.7.7. Inspections: An inspection represents inspections of equipment, programs, and processes to ensure compliance with established standards. Inspections are rated as "Pass" or "Fail". Inspections include:

6.7.7.1. QVIs. A QVI is an inspection of equipment condition, or a maintenance process, an assessment following a maintenance inspection, servicing or repair action, or verification that a technician or supervisor properly completed an inspection or repair action.

6.7.7.1.1. QVIs will not be conducted after equipment operation when such operation could invalidate indications of proper job accomplishment.

6.7.7.1.2. Limit QVIs to the same inspection card deck or technical data required for the job. This inspection does not require disassembling parts, removing stress panels or like actions.

6.7.7.1.3. A QVI required for -6 TO inspections may be accomplished by checking a portion of the required card or area.

6.7.7.1.4. The QVI report should reflect deficiencies by the individual who accomplished the task and identify specific discrepancies.

6.7.7.1.5. Document these discrepancies in active equipment records and forms, for example AFTO Form 781A, AFTO Form 244, *Industrial/Support Equipment Record*.

6.7.7.1.6. Rate QVIs "Pass" or "Fail" by comparing the number of discrepancies with the established AQLs/standards.

6.7.7.1.6.1. Pass: Number of discrepancies does not exceed established AQL/standard.

6.7.7.1.6.2. Fail: An inspection that results in any of the following:

6.7.7.1.6.2.1. A technician fails to detect a major discrepancy while complying

with an inspection or TO requirement.

6.7.7.1.6.2.2. Number of CAT I minor discrepancies exceeds the established AQL/standard.

6.7.7.1.6.2.3. A technician is not signed off in training records as task qualified.

6.7.7.1.6.3. Document the QVI in the LEAP QA database.

6.7.7.1.6.3.1. Each QVI is chargeable to the technician or supervisor who signed off/cleared the "corrected by" block or "inspected by" block of the applicable maintenance form or equipment record.

6.7.7.1.6.3.2. When evaluating the technician who signed off the "inspected by" block, evaluate only the items normally verified by signing off the "Red-X".

6.7.7.1.6.3.3. Only one evaluation is scored for each inspection.

6.7.7.2. Management Inspection (MI). Perform these inspections to follow-up on trends, conduct investigations or conduct research to get to the root cause of problems. MXG/CCs, SQ/CCs or work center supervisors may request MIs. MIs may encompass PE/QVI trends and other inspection data, NMC causes, aborts and trends, IFE trends, high component or system failure rates, suspected training deficiencies, and tasks outlined in aircraft -6 TOs. MI results are reported to the requester. MIs can be non-rated and may be counted in QA trends. The LEAP QA database will be used to document MIs. **(T-2)**

6.7.7.3. Special Inspections (SIs) are inspections not covered by QVIs, PEs or MIs. SIs may include, but are not limited to, aircraft and equipment forms inspections, document file inspections, CTKs, TO files, vehicle inspections, housekeeping, safety practices, FOD Program, SIs may be condition, procedural, or compliance oriented.

6.7.7.3.1. The LEAP QA database will be used to document special inspections. **(T-2)**

6.7.7.3.2. SIs will be rated as "Pass" or "Fail" based on established AQLs/standards.

6.7.8. Discrepancy Reporting. Report all discrepancies to the applicable work centers. **(T-2)**

6.7.8.1. QA will provide an authoritative, validated source reference for all reported discrepancies (such as, work cards, job guides, WUC manuals, checklists, occupational safety requirements, TOs, and other applicable references). **(T-2)**

6.7.9. Units will grade their MSEP evaluations monthly using objective ratings based on the following five-tier rating system:

6.7.9.1. Outstanding: 95-100% **(T-2)**

6.7.9.2. Excellent: 90-94.99% **(T-2)**

6.7.9.3. Satisfactory: 80-89.99% **(T-2)**

6.7.9.4. Marginal: 70-79.99% **(T-2)**

6.7.9.5. Unsatisfactory: 0-69.99% **(T-2)**

6.7.9.6. Inspections and evaluations performed (such as, PE, SI, QVI) are rated "Pass/Fail". Exception: Unless otherwise directed by AFMAN 21-200 and AFI 21-204 for Nuclear Weapons PEs and Certification Program.

6.7.9.7. Ratings are calculated by dividing the total number of inspections passed by total completed. For example, QA inspects 10 aircraft preflights with the following results: 9 "passes" and 1 "failure". Divide the total "passes" by the total inspections (9/10=0.90) 90 percent for an "Excellent" rating.

6.7.9.7.1. Deduct 0.5 percentage points from overall percentage grade for each TDV, DSV, and UCR monthly. For example, a squadron earns an overall rating of 90 percent, "Excellent", however, QA observed 4 TDVs and 3 DSVs. Multiply the sum (7) by 0.5 and subtract the product (3.5) from the original 90 percent. The adjusted total is 86.5 percent; therefore, the squadron is rated "Satisfactory".

6.7.10. A cumulative MXG score will be determined by dividing the Group's total number of inspections and evaluations passed by the total inspections and evaluations completed. **(T-2)**

6.7.10.1. Deduct 0.5 percentage points for each TDV, DSV, and UCR from the overall percentage grade, using same formula in **Paragraph 6.7.9.7.1**.

6.7.11. Monthly Summary. QA will publish and distribute the monthly summary to the MXG/CC or equivalent and inspected organizations. **(T-2)**

6.7.11.1. For security purposes, classified portions of the MSEP will be published separately from the main summary. **(T-2)**

6.7.11.2. QA will compile the summary from inspection data and attach the load crew evaluation statistics provided by WS. **(T-2)**

6.7.11.3. The MSEP summary should include visual information, graphs, narratives, quality trends identified through inspections and evaluations, discussion of common problem areas and descriptions of successful programs or initiatives.

6.7.11.4. The following areas must be addressed in the summary:

6.7.11.4.1. Compliance with and currency of TOs and directives to include unit. **(T-2)**

6.7.11.4.2. Aircraft and equipment forms documentation. **(T-2)**

6.7.11.4.3. Compliance and management of Safety, Environmental, Housekeeping, cyber discipline/Hygiene and FOD Programs. **(T-2)**

6.7.11.4.4. Training Program. **(T-2)**

6.7.11.4.5. Key Task List (KTL). **(T-2)**

6.7.11.4.6. Routine Inspection List (RIL). **(T-2)**

6.7.11.4.7. TDVs, DSVs, and UCRs. **(T-2)**

6.7.11.4.8. Munitions Program. **(T-2)**

6.7.11.4.9. TMDE PMEL Activity Summary (if TMDE lab assigned). **(T-2)**

6.7.11.4.10. High-missed carded items. **(T-2)**

6.7.11.4.10.1. A high-missed carded item is defined as any work card item missed

at least three times during a one-month period.

6.7.11.4.10.2. Units should use the high-missed carded items to enhance maintenance training programs, detect trends and improve the quality of maintenance.

6.7.11.4.10.3. MMA will review items to identify any relationships with repeat, recur and CND trends. **(T-2)**

6.7.11.4.11. Narrative Report: The monthly narrative report must contain an analysis of the MSEP results, a summary of significant CAT I and II discrepancies, technical inspections, and recommendations for improvement.

6.7.11.4.11.1. Prior to preparing the narrative report, QA will conduct a study of trends. **(T-2)**

6.7.11.4.12. Trend Analysis. QA will review previous reports to determine if inspected areas have improved or declined. **(T-2)**

6.7.11.4.12.1. Consistent high scores in any category may indicate the programs emphasis is not focused on the unit's actual problem areas. Low scoring areas may require a reassessment of the corrective actions taken by management. Continuous communication between MMA, unit leadership, maintenance supervision, and QA personnel is essential.

6.7.11.4.12.2. Highlight trends and root causes in the summary.

6.7.12. - 6.7.12.2. DELETED.

6.7.13. **(Added-AFGSC)** MSEP Meetings.

6.7.13.1. **(Added-AFGSC)** The MXG/CC will determine the agenda for MSEP meetings (e.g., KTL/RIL, AQL/baselines, QVI, PE, DSV/TDV/UCR, SI review etc.)

6.7.13.2. **(Added-AFGSC)** The MXG/CC will determine MSEP meeting attendees.

6.8. LEAP QA Database. Units will use the LEAP QA database to capture MSEP data. **(T-1)** The LEAP User's Manual provides information on registration, site management, and evaluation/inspection input and can be found at: **https://leap.disa.mil/mi/LEAPQA/Account/Login.aspx?ReturnUrl=%2fmi%2fLEAPQA%2fDefault.aspx**.

6.8.1. LEAP QA Database Roles and Responsibilities. Roles in LEAP are assigned based on each user's authorized level of control needed. The roles themselves operate in a hierarchical manner with each successively higher role possessing all of the rights of the subordinate roles. Only one role will be assigned to a LEAP user at any given time.

6.8.1.1. Application Administrator. This role is limited to Defense Information System Administration (DISA) programming staff and Program Management Office (PMO) personnel only. They perform Department of the AF-wide database management and modification. LEAP Application Administrator will:

6.8.1.1.1. Host a quarterly (virtual) Functional Review Board (FRB) and an annual (Physical or Virtual) Functional Review Board. **(T-2)**

6.8.1.1.1.1. Attendees will include: DISA Programming staff, PMO, AF/A4LM LEAP representative, Functional Administrators, and when possible, Site Managers. **(T-2)**

6.8.1.2. Provide initial training to Functional Administrators and Site Managers as necessary. **(T-2)**

6.8.1.3. Update the LEAP User's Manual as necessary. **(T-2)**

6.8.1.4. Provide a monthly status of all System Change Requests (SCRs). **(T-2)**

6.8.2. Functional Administrator. LEAP Functional Administrators provide overall database management and typically operate at the MAJCOM level. Usually assigned to a MAJCOM's policy section, they ensure proper use and alignment of the database with current policy guidelines. They also operate as the primary focal point for all LEAP-related issues within their MAJCOM and coordinate directly with the LEAP PMO. LEAP Functional Administrators will:

6.8.2.1. Manage access to LEAP either directly or through local site offices that have the capability for delegation for Site Managers only, for example, FMxC2 Manager on site. **(T-2)**

6.8.2.2. Develop and assign LEAP Finding Codes IAW MAJCOM directives. **(T-2)**

6.8.2.2. **(AFGSC)** LEAP finding codes correlate with the "Malfunction Codes" in the applicable -06 manual but are more general in nature since they are not used to report maintenance actions in MIS-CDB. These categories are located at **Table 6.1.**. **(T-2)**

6.8.2.3. Create, modify, and manage sites within the LEAP Database for their MAJCOM. **(T-2)**

6.8.2.4. Transcribe and manage Command Task Lists (CTL) in LEAP IAW MAJCOM directives (example, RILs).

6.8.2.4. **(AFGSC)** Command Task Lists will be published by 15 Dec.

6.8.2.5. Assist local Site Managers with day-to-day operations in LEAP to include troubleshooting and reporting SCRs to the PMO. **(T-2)**

6.8.3. Site Manager. LEAP Site Managers provide local oversight for their respective Group (or equivalent). Possessing "base level" control, they are able to approve and modify LEAP Users and assign roles up to and including other Site Managers. While there is no limitation to how many Site Managers can be assigned per site, the level of control available should warrant assignment based on appropriate rank/position (typically, QA Superintendent and Chief Inspector). LEAP Site Managers will:

6.8.3.1. Manage access to LEAP by coordinating new user documentation with their assigned FMxC2 Manager and approving accounts in LEAP after user registration. **(T-2)**

6.8.3.2. Modify user accounts according to need. **(T-2)**

6.8.3.3. Ensure LEAP users are deactivated or downgraded in LEAP when out-processing the QA office. **(T-2)**

6.8.3.4. Create Flights and Sections in LEAP to which evaluations will be assigned. **(T-2)**

6.8.3.5. Assign RILs (Command Task Lists/Site Task Lists) within the LEAP application to Organizational Sites in order to facilitate entry of the MXG's Evaluation and Inspection Plan. **(T-2)**

6.8.3.6. Build and manage the E&I Plan (if used) in LEAP and ensure it incorporates all MAJCOM specific requirements. **(T-2)**

6.8.3.6. **(AFGSC)** E&I plans will be utilized.

6.8.4. Read-Only Guest. LEAP Read-Only Guests are intended to be supervisory personnel and unit leadership who require regular access to LEAP Reports and Evaluation documentation.

6.9. QA Product Improvement Programs (PIP). QA runs PIP for the maintenance complex. Combined with daily maintenance data reporting, the PIP monitors, and reviews maintenance data to identify opportunities to improve aircraft and equipment. PIP includes the following programs:

6.9.1. DR Reporting.

6.9.2. TO RC requests.

6.9.3. SMR code change request(s).

6.9.4. Configuration Management (CM) and Modification Management Program; AF Form 1067, Modification Proposal; and TCTOs.

6.9.4.1. QA is responsible for CM and Modification Management. This includes reviewing, submitting, and tracking unit modification proposals being worked by MAJCOMs/Lead Commands and ensuring proper implementation of approved modification instructions or TCTOs.

6.9.4.1. **(AFGSC)** The PIM will monitor the configuration management process.

6.9.4.1.1. **(Added-AFGSC)** QA is responsible for ensuring modifications or improvements for AvSE are submitted to the appropriate authority.

6.9.4.2. QA will manage/document modifications IAW **Chapter 14**, AFI 63-101/20-101, TO 00-20-2, and TO 00-5-15.

6.9.4.2. **(AFGSC)** If the TCTO or modification affects nuclear certified products, as defined in DAFMAN 91-118, *Air Force Nuclear Safety Design Certification Program* and DAFI 91-101, *Air Force Nuclear Weapons Surety Program*, TODO's will: **(T-2)**

6.9.4.2.1. **(Added-AFGSC)** Forward a copy to the unit Weapon Safety Manager for review. **(T-2)**

6.9.4.2.2. **(Added-AFGSC)** Verify all items annotated as nuclear certified are correctly listed at: **https://members.lcmp.af.mil/mncl**.

6.9.4.3. QA will establish a process for updating the weapon systems MIS that require manual updates for TCTO configuration. **(T-2)**

6.9.4.3.1. **(Added-AFGSC)** PMEL TCTOs are reviewed by the TMDE flight. **(T-2)**

6.9.5. Product Improvement Manager (PIM). The PIM promotes deficiency reporting and provides a sound PIP based on inputs from maintenance activities. The PIM interacts with assigned AFETS personnel, FSR and MAJCOM/Lead Command as applicable to remain

cognizant of ongoing and new improvement initiatives. The PIM emphasizes and promotes product improvement initiatives and ensures maintenance personnel are familiar with them by circulating flyers/newsletters, visiting commander's calls, presenting the program at maintenance orientation briefings, and making routine visits to maintenance areas.

6.9.5.1. Deficiency Reporting. DR is the process of reporting prescribed by TO 00-35D-54. Maintenance processing of warranty items is located in TO 00-20-3. The PIM's will:

6.9.5.1.1. Monitor the DR process to ensure items are properly loaded in the MIS database. **(T-2)**

6.9.5.1.2. Ensure compliance with acceptance inspection reporting requirements on DRs for aircraft returning from depot or contractor maintenance. **(T-2)**

6.9.5.1.3. Ensure DRs are submitted using Joint Deficiency Reporting System (JDRS) at **https://jdrs.mil. (T-2)**

6.9.5.1.4. Review the DR prior to releasing to the ALC or AFMC Maintenance Wings IAW TO 00-35D-54. **(T-2)**

6.9.5.1.5. Verify each report against pertinent publications and assign the appropriate precedence and category. **(T-2)**

6.9.5.1.6. Screen reported deficiencies for possible unit-unique contributing factors and initiate management action on unsatisfactory conditions resulting from local procedures or a lack of technical capability. **(T-2)**

6.9.5.1.7. Perform/coordinate a technical review of DRs returned to the unit without an adequate response to determine whether resubmitting with additional information is warranted. **(T-2)**

6.9.5.1.8. Perform exhibit-processing oversight by coordinating with the ALC and the LRS to ensure proper exhibit control and handling. **(T-2)**

6.9.5.1.9. **(Added-AFGSC)** Identify potential PIWG items by the letter "P" on the DR logs. **(T-2)**

6.9.5.1.10. **(Added-AFGSC)** Forward consolidated proposed PIWG/Weapons System Review (WSR) items to the appropriate MAJCOM weapons system team (WST) for approval. **(T-2)**

6.9.5.2. RC Process. The PIM will review and route RCs IAW TO 00-5-1.

6.9.5.3. SMR code change request. Submit an SMR code change request IAW TO. 00-25-195, *AF Technical Order System Source, Maintenance, and Recoverability Coding of Air Force Weapons, Systems, and Equipment*. The PIM will:

6.9.5.3.1. Track the status of SMR change requests. **(T-2)**

6.9.5.3.2. Conduct a technical review of SMR change requests returned from depots and item managers with an unsatisfactory answer to determine whether to resubmit with additional information. **(T-2)**

6.9.5.3.3. Coordinate repair evaluation meetings when approved SMR change requests affect several agencies. **(T-2)** Ensure units with active AFREP coordinate SMR code changes through the PIM prior to submission to the MAJCOM AFREP Manager. **(T- 2)**

6.9.5.3.4. Serve as focal point for base-level repair and manufacturing capability. **(T-2)**

6.10. Technical Order Distribution Office (TODO). The TODO ensures TOs and CPINS are managed IAW AFI 63-101/20-101, TO 00-5-1, TO 00-5-15 and TO 00-5-16. TO 00-5-1 provides criteria for establishing levels of TO distribution activities. Additionally, TODOs will control electronic technical data configuration IAW **Chapter 8**. Establish the PMEL TODO under the control of the TMDE Flight. **(T-2)** The TODO will:

6.10.1. Coordinate with QA SME for each incoming TCTO to determine applicability. **(T-2)**

6.10.1.1. All TCTOs received from outside agencies need to be routed through QA for the review process.

6.10.1.2. TCTO applicability is determined by aircraft serial number for aircraft, engine serial number for engines, and by part number or other specific criteria for commodities.

6.10.1.3. TCTOs need to be manually or electronically date stamped to reflect the date the electronic or hard copy is received.

6.10.1.3.1. Date stamping all TCTOs with the date received indicates QA has reviewed the TCTO and that applicability has been determined.

6.10.1.3.1. **(AFGSC)** Distribute TCTO copies within 1 duty day of QA date stamp. **(T-2)**

6.10.1.3.2. TCTO electronic date stamping can be accomplished by either (1) utilizing a locally developed spreadsheet containing the minimum following information: TCTO number, MDS, receiving TODO name, applicability determination and the date received, all of which must be associated with the corresponding TCTO or (2) inserting the receipt date on the TCTO utilizing the Adobe Tools feature. For either option, the date received will be entered by the QA TODO responsible for tracking TCTOs. **(T-2)**

6.10.1.3.2.1. If used, the TCTO tracking spreadsheet or Adobe-inserted date stamped TCTOs will be electronically secured and controlled by the receiving QA office. **(T-2)**

6.10.1.3.3. Only date stamped TCTOs are authorized for use. **(T-2)**

6.10.1.4. Post TCTO file copies IAW TO 00-5-1.

6.10.1.4.1. TCTO file copies may be posted and distributed in electronic format provide all requirements of TO 00-5-1 and AFI 33-322 are sustained. Electronic TCTO distribution is automated for ETIMS/IETM.

6.10.1.5. For hard copy TCTOs, provide a file copy of the TCTO to PS&D. **(T-2)**

6.10.1.6. Ensure personnel assigned as TODO/Technical Order Distribution Account (TODA) managers meet requirements set forth in TO 00-5-1 and AFI 63-101/20-101. **(T-2)**

6.10.2. Manage the QA Central TO File. **(T-2)**

6.10.2.1. As a minimum, the QA Central TO File must contain copies of general and procedural TOs and copies of all TCTOs pertaining to the assigned aircraft and equipment owned, operated, or maintained. (Paper copies for paper TOs or local access for digital TOs) **(T-2)**

6.10.2.2. The file is kept to meet QA requirements, not to duplicate TOs held by maintenance work centers.

6.10.3. Manage TO accounts using ETIMS IAW TO 00-5-1. **(T-2)**

6.10.4. Limit use of Local Work Cards, Local Job Guides, Local Page Supplements or Local Checklists to accomplish maintenance on AF equipment. **(T-2)** Locally prepared technical instructions will not be used to circumvent approved technical data (see TO 00-5-1). **(T-2)**

6.10.4.1. The TODO will review and manage all locally developed products IAW TO 00-5-1 and MAJCOM supplements for safety and adequacy of procedures. **(T-2)**

6.10.4.2. Local Work Cards, Local Job Guides, Local Page Supplements and Local Checklists need to be reviewed for currency when source reference data changes.

6.10.4.3. TODO will develop local publications IAW DAFMAN 90-161 to ensure compliance with these policies. **(T-2)**

6.10.5. Prepare a list of all changes and revisions to indexes, TOs, inspection work cards and checklists. **(T-2)**

6.10.5.1. This list will include TO number and date received. **(T-2)**

6.10.5.2. The TODO will date stamp the cover page of all paper TOs, changes, supplements, Local Work Cards, Local Job Guides, Local Checklists and CPINS to reflect the date the hard copy is received. **(T-2)**

6.10.5.2.1. This list will be sent out electronically weekly to all affected agencies. **(T-2)**

6.10.5.2.2. Supervisors should review the list of changes and ensure all personnel are aware a change or revision has been received.

6.10.5.3. "Immediate" action TCTOs must be implemented upon receipt, and "Urgent Action" TCTOs, safety supplements and interim supplements must be brought to the attention of local maintenance supervision within 24 hours of receipt. **(T-2) Note:** Communication of a grounding, or potential grounding event (TCTO, OTI, PM event) to weapon systems operating in a deployed environment and/or under the authority of an operational command must follow the grounding procedures outlined in DAFMAN 11-401, *Aviation Management*, and AFI 63-101/20-101. Units will not directly communicate home station requirements to its deployed forces but provide communication through their respective MAJCOM. **(T-2)**

6.10.6. Ensure all authorized technical data variances are kept with aircraft and equipment historical records IAW **Chapter 14**. **(T-2)**

6.10.7. If designated as Lead TODO (primary as designated in block 5 of the AFTO Form 43 per TO 00-5-1), will conduct a management inspection on other maintenance TODOs/TODAs

in the maintenance complex at least annually along with performing spot checks of TO files. **(T-2)**

6.10.7.1. As part of this inspection, the TODO will confirm TODO/TODA personnel and Library Custodian have completed the mandatory minimum requirements of TO System training. **(T-2)**

6.10.7.2. The Lead TODO(s) will coordinate with other TODOs and TODAs, and local Client Support Administrators, Functional Systems Administrators, and applicable functional OPRs to ensure eTools are configured with current and only authorized software to support TO and maintenance documentation. **(T-2) Note:** Coordination with the local Communications Squadron to verify network configuration requirements for eTools are available and sustained to meet the requirements listed in TO 31S5-4-ETOOL-1-WA-1. Additional user support available through the Air Force Technical Order Functional Support Team, **af.etimstofst@us.af.mil** or DSN 872-9300.

6.10.7.2. **(AFGSC)** Ensure that users receive comprehensive training on the proper use of eTools and viable features as part of a structured OJT program IAW TO 00-5-1. This will enable full utilization of associated capabilities and functions.

6.10.8. Control the electronic data configuration on applicable eTools IAW **Chapter 8**. **(T-2)**

6.10.8.1. TODO/ Functional Systems Administrators will develop local procedures to quarantine eTools and eTool update history in the event of a mishap. **(T-2)**

6.10.9. Maintain records of ETIMS IAW TO 00-5-1.

6.10.9.1. TODOs will set up software sub-accounts with each appropriate shop/section and ensure each shop/section has the most current software on hand. **(T-2)**

6.10.9.2. TODOs will include ETIMS or equivalent system in the routine and annual checks required by TO 00-5-1. **(T-2)**

6.10.10. **(Added-AFGSC)** Coordinate with AFGSC/A4MQ when establishing eTool requirements. **(T-2)**

6.10.11. **(Added-AFGSC)** MAJCOM and Base ETOOL Group Manager/Administrator Functions: See TO 00-5-1, *AF Technical Order System*, and AFGSC Supplement for eTool management. **(T-2)**

6.11. One-Time Inspections (OTI) program. The OTI program is managed by the MXG IAW TO 00-20-1. OTIs are normally look-only actions to verify the existence of suspected equipment conditions or malfunctions.

6.11. (AFGSC) One-Time Inspections (OTI) program. For MAJCOM directed OTIs, the applicable AFGSC/A4A/A4B WST or (A4 Division) will draft inspection requirements IAW TO 00-20-1 and send it to A4MQ Maintenance Management and Policy for review. The OTI will be routed to AFGSC/A4 for final signatures and the A4M Division Chief for distribution. **(T-2)**

6.12. Functional Check Flights (FCFs) to include Operational Check Flights (OCFs).

6.12. (AFGSC) Functional Check Flights (FCFs) to include Operational Check Flights (OCFs). The requirement for an aircraft FCF is driven primarily by MDS specific technical

orders. However, the requirement for an aircraft OCF is to be determined by the OG/CC and MXG/CC.

6.12.1. Check Flights are performed to ensure an aircraft is airworthy and/or capable of accomplishing its mission. Additional guidance may be found in DAFMAN 11-401, AFMAN 11-202 V3, *Flight Operations*, DAFMAN 13-201, *AF Airspace Management*; TO 1-1-300, *Maintenance Operational Checks and Check Flights*; TO 00-20-1; and applicable -6 TOs and -1 Flight Manuals.

6.12.1.1. OCF will be kept to a minimum and are not used to replace TO 1-1-300, *Maintenance Operational Checks and Check Flights* or MDS specific -6 TO Functional Check Flight (FCF) requirements. OCFs must be flown by experienced aircrews (not required to be an FCF qualified aircrew), must be briefed by QA for aircraft condition, and accomplished following the same maintenance criteria as FCFs. **(T-2)**

6.12.2. The QA FCF Program Manager will:

6.12.2.1. Establish local FCF procedures IAW TO 1-1-300 and checklists for any specific local aircraft requirements to include configuration, administration, control, and documentation of the FCF Program. **(T-2)**

6.12.2.1.1. Coordinate these procedures with OG Standardization/Evaluation and publish them in a wing publication/supplement IAW DAFMAN 90-161. **(T-2)**

6.12.2.2. Support the appropriate squadron to facilitate FCF.

6.12.2.3. Maintain an information file containing unit directives concerning FCF procedures and an FCF checklist for each MDS assigned for briefing aircrews. **(T-2)**

6.12.2.3.1. DELETED.

6.12.2.4. Ensure a FCF checklist is used for each FCF. **(T-2)**

6.12.2.5. Ensure all FCFs are debriefed with the appropriate debrief function. **(T-2)**

6.12.2.5.1. During debriefing, the FCF checklist and aircraft forms will be reviewed to determine if all requirements have been accomplished. **(T-2)**

6.12.2.5.2. After completing the review, the FCF checklist will be sent to PS&D for inclusion in the aircraft jacket file. **(T-2)**

6.12.2.6. Maintain a copy of the AF Form 2400, *Functional Check Flight Log*, or equivalent automated product for deficiency and trend analysis. **(T-2)**

6.12.3. FCF-qualified QA Inspectors will:

6.12.3.1. Ensure the FCF aircrew is briefed on the purpose and extent of the flight, previous maintenance problems and discrepancies recorded on the aircraft or engines related to the FCF. **(T-2)**

6.12.3.2. Review aircraft W&B documents. **(T-2)**

6.12.3.3. Ensure AF Form 2400 or an equivalent automated product is maintained to provide information for evaluation and analysis. **(T-2)**

6.12.3.3.1. Include the date and time of the FCF, aircraft serial number, reason for FCF, name of debriefer and name of aircraft commander. **(T-2)**

6.12.3.3.2. The AF Form 2400 or equivalent automated product will also indicate if the aircraft was released for flight, reasons for any non-release, action taken, and date completed, and the date maintenance documents were forwarded to PS&D or records section. **(T-2)**

6.12.3.4. Ensure all maintenance actions are completed and all AFTO Form 781-series forms are documented IAW MDS specific -6 TO and TO 00-20-1 or electronic equivalent. **(T-2)**

6.12.3.5. All maintenance actions on transient aircraft requiring FCF must be reviewed by QA prior to FCF. **(T-2)**

6.12.3.5.1. If the aircraft MDS/type is not assigned at the transient base, then the owning unit must provide a qualified FCF pilot/crew and maintenance as required. **(T-2)**

6.12.4. Flight Requirements. The mandatory requirements for FCF are outlined in TO 1-1-300 and the applicable -6 TO. FCF profiles are determined by the maintenance requirement causing the FCF. The FCF profile will be tailored for the discrepancy causing the FCF by applying the following guidance:

6.12.4.1. Require a clean configuration whenever FCFs are flown for flight controls, fuel controls or engine changes. **(T-2)**

6.12.4.2. Do not remove fixed wing pylons, fixed wing tip tanks and fixed external stores unless they interfere with fuel scheduling, aerodynamic reaction, air loading, signal propagation. **(T-2)**

6.12.4.3. DELETED.

6.12.5. FCF Release. An FCF release occurs upon the successful completion of all requirements as determined by the FCF aircrew. The final decision to release rests solely with the aircraft commander. An aircraft may be released for flight if a malfunction occurs during an FCF, which is not related to the condition generating the FCF and the original condition checks good.

6.12.5.1. An FCF conditional release may occur when the aircraft does not successfully complete FCF requirements due to a specific system malfunction. The FCF aircrew, in coordination with maintenance, determines a FCF conditional release if the malfunction may be corrected without generating another FCF. If upon review of the corrective action, the FCF aircrew accepts the maintenance action as a satisfactory repair of the malfunction, they may release the aircraft from FCF.

6.12.6. MAJCOMs will determine the process and level of command that will issue instructions for FCF procedures away from home station in their supplements to this DAFI.

6.12.6. **(AFGSC)** Coordinate required FCF through owning MXG/CC, off-station transient alert and off-station QA Sections. If no off-station agencies exist, owning MXG/CC and owning OG/CC issue guidance directly to the aircraft commander and off-station maintenance personnel. **(T-2)**

6.12.7. **(Added-AFGSC)** Debrief all FCF crews to determine if all requirements were accomplished. **(T-2)**

6.13. Inflight Operational Checks. Inflight operational checks (as applicable) will be accomplished IAW TO 1-1-300, TO 00-20-1 and applicable -6 and -1 TOs.

6.13.1. Document inflight operational checks IAW TO 00-20-1.

6.14. High Speed Taxi Checks. The MXG/CC and OG/CC may authorize high speed taxi checks when a maintenance ground operational check requires aircraft movement at higher-than-normal taxi speeds (with qualified FCF aircrews) to operationally check completed maintenance.

6.14.1. High speed taxi checks (as applicable) will be accomplished IAW TO 1-1-300 instead of FCFs. **(T-2)**

6.14.1.1. Process aircraft forms through QA using FCF procedures. **(T-2)**

6.14.1.2. QA will develop an aircrew briefing checklist specifically for high-speed taxi checks, to include the required FCF briefing items and pertinent warnings, cautions. **(T-2)**

6.14.2. Configure aircraft with the minimum -1 operational fuel requirements. **(T-2)**

6.14.3. Ensure aircraft is prepared for flight and the Exceptional/Conditional Release is signed off prior to conducting high speed taxi checks. **(T-2)**

6.15. Weight and Balance (W&B) Program. QA will maintain the W&B Program IAW TO 1-1B-50, *Basic Technical Order for USAF Aircraft Weight and Balance*.

6.15. (AFGSC) Weight and Balance (W&B) Program. The W&B program NCOIC/Manager will attend an in-resident W&B practical course. **(T-2)**

6.15.1. W&B manuals for Class I and II aircraft are maintained in a central file. **(T-2)**

6.15.1.1. The Lead Command will standardize the method of supplemental handbook storage and physical location for like-MDS aircraft. **(T-2)**

6.15.1.1. **(AFGSC)** Supplemental W&B handbooks will be maintained and stored for flights on aircraft for all Class 1B and Class II MDS.

6.15.2. QA will manage W&B on commercial derivative aircraft IAW **Chapter 6**. **(T-2) Note:** The contractor is responsible for managing W&B programs on contract logistics supported aircraft.

6.15.2. **(AFGSC)** For units that perform local aircraft weighing operations, MXG/CC is the approval authority to waive the W&B Practical Course for weight and balance technicians. **(T-2)**

6.15.3. The W&B Program Manager will ensure:

6.15.3.1. Sufficient personnel are qualified on assigned aircraft IAW TO 1-1B-50. **(T-2)**

6.15.3.1. **(AFGSC)** Tracking and documentation of W&B qualified/certified technicians who perform actual aircraft weighs must perform a weigh annually to maintain proficiency. **(T-2)**

6.15.3.2. All assigned aircraft are weighed IAW prescribe MDS specific publications and directives. **(T-2)** The W&B Program Manager will:

6.15.3.2.1. Keep W&B documents required by TO 1-1B-50 for each assigned aircraft. **(T-2)**

6.15.3.2.2. Use the Automated Weight and Balance System and maintain a back-up copy of all W&B documents. **(T-2)**

6.15.3.3. Procedures are established for routing completed TCTO and modification information for W&B changes. **(T-2)**

6.15.3.4. Essential W&B data and changes to the basic weight and moment are available for appropriate mission planning (such as, Standard Configuration Loads, updates to supplemental handbook). **(T-2)**

6.15.3.5. Periodic serviceability inspections are accomplished on unit-stored and maintained W&B equipment (as applicable). **(T-2)**

6.15.3.6. Coordination with Maintenance Supervision in developing a W&B Preparation Checklist if the aircraft -5 TO is not comprehensive enough for the task. **(T- 2)**

6.15.3.7. The SCR reflects W&B certification. **(T-2)**

6.15.3.7.1. **(Added-AFGSC)** W&B certification will be tracked on SCR and in MIS using course code 002326, CERT WEIGHT AND BAL CERT CLR R/X. Refer to **Table 11.1**. **(T-2)**

6.15.3.7.1.1. **(Added-AFGSC)** Use of course code 004215, CERT WEIGHT AND BAL DOC ONLY, is prohibited. **(T-2)**

6.15.3.7.1.2. **(Added-AFGSC)** Weighing aircraft and AWBS qualifications will be documented in a training database. **(T-2)**

6.15.4. W&B Qualified QA Inspector Responsibilities. The W&B Qualified QA Inspector will:

6.15.4.1. Verify scale readings and accomplish/oversee the actual computations. **(T-2)**

6.15.4.2. Supervise the preparation, leveling and weighing of the aircraft IAW MDS specific –2 and –5 series TOs and TO 1-1B-50.

6.15.4.3. Inspect W&B documents before flight when locally accomplished modifications affect the basic aircraft weight and moment. **(T-2)**

6.15.4.4. Review computations for accuracy. (T-2)

6.15.4.5. **(Added-AFGSC)** Create and maintain a MAJCOM approved Automated Weight and Balance System (AWBS) familiarization course for certified QA inspectors. **(T-2)**

6.15.4.5.1. **(Added-AFGSC)** Plans will be submitted to AFGSC/A4MQ for approval prior to first use and anytime changes are made.

6.15.4.5.2. **(Added-AFGSC)** AWBS familiarization training will be documented in DAF Form 797 or electronic training record.

6.15.5. **(Added-AFGSC)** The W&B Program Authority will be the most qualified W&B technician in QA. **(T-2)**

6.15.6. **(Added-AFGSC)** Ensure any maintenance actions affecting basic aircraft weight and moment will be deemed unsafe conditions and are non-airworthy discrepancies. Refer to TO 00-20-1, Chapter 4. **(T-2)**

Chapter 7

IMPOUNDMENT PROCEDURES

7.1. Aircraft and Equipment Impoundment. Aircraft or equipment is impounded when intensified management is warranted due to system or component malfunction or failure of a serious or chronic nature. Refer to DAFI 91-204 for aircraft and equipment involved in accidents, mishaps, or incidents. Impounding aircraft and equipment enable investigative efforts to systematically proceed with minimal risk relative to intentional/unintentional actions and subsequent loss of evidence.

7.2. Specific Guidance. MXGs will develop and implement a standardized Impound Official training course. The course will include review of applicable AFIs, TOs, impoundment clearing procedures, and leverage FSR and AFETS expertise to ensure Impound Official is prepared to assume all duties and responsibilities of an impoundment official.

7.2. (AFGSC) Specific Guidance. Units will use AFGSC Form 147, *QA Impoundment Record*. **(T-2)**

7.2.1. Local program procedures, requirements and responsibilities will be captured in a local supplement to this instruction. **(T-3)**

7.2.1.1. QA is the OPR for the Impoundment Program and will develop local impoundment checklists. **(T-3)**

7.2.1.2. QA in coordination with MT, will serve as the OPR and focal point for the management of the Impound Official training course. The course completion is mandatory prior to being assigned as an Impound Official. **(T-3)**

7.2.2. - 7.2.2.1. DELETED.

7.2.3. The Impoundment Release Authority determines the need for a one-time flight and will coordinate appropriate authorization IAW TO 00-20-1. **(T-3) Note:** If the aircraft/equipment were impounded for a mishap, coordinate with the safety office prior to releasing the aircraft/equipment from impound. **(T-3)**

7.2.4. MAJCOMs will determine the amount of time unit QAs will maintain copies of finalized Impoundment reports in their supplement to this DAFI. **Note:** See Air Force Records Information Management System (AFRIMS) Reference.

7.2.4. **(AFGSC)** Records will be maintained for a minimum of two years. **(T-2)**

7.2.5. **(Added-AFGSC)** Aircraft impounded will be statused as NMC for the discrepancy that drove the impound and will remain in a NMC condition until the aircraft is released from impound by the Impoundment Release Official**. (T-2)**

7.3. Impoundment Authorities.

7.3.1. Impoundment Authorities will:

7.3.1.1. Make impoundment determination when extraordinary measures are required to address any degradation of aircraft airworthiness or serious aircraft/equipment anomaly, not listed in section 7.5. **(T-2)**

7.3.1.2. Select the Impoundment Official. **(T-2)**

7.3.1.2.1. - 7.3.1.2.3. DELETED.

7.4. Impoundment Official Responsibilities. The Impoundment Official is designated as the single POC for impounded aircraft or equipment and will hold the minimum rank of MSgt and will be tracked on the SCR. **(T-2)** The Impoundment Official will:

7.4.1. Be responsible for controlling and monitoring the investigation of impounded aircraft or equipment. **(T-2)**

7.4.2. Use established checklists to guide the sequence of actions. **(T-2)**

7.4.3. Control and track access of personnel to impounded aircraft or equipment. **(T-2)**

7.5. Mandatory Impoundments. Aircraft and/or equipment will be impounded:

7.5.1. DELETED.

7.5.2. Following an aircraft mishap as defined in DAFI 91-204 and DAFMAN 91-223, *Aviation Safety Investigations and Reports*. **(T-2)**

7.5.3. When support equipment is known or suspected to have been a factor in a mishap or may have contributed to injuries. **(T-2)**

7.5.4. Following an un-commanded flight control movement. **(T-2)**

7.5.5. Following an inadvertent ordnance release or explosive mishap. **(T-2)**

7.5.6. When authorized procedures are not adequate or the unit is unable to identify/repair loaded nuclear weapons system malfunctions IAW DAFI 91-101. **(T-2)**

7.5.7. Following aircraft engine anomalies to include but not limited to:

7.5.7.1. Unselected propeller reversal. **(T-2)**

7.5.7.2. Flameout/stagnation (for single engine aircraft). **(T-2)**

7.5.7.3. Unselected power reversal. **(T-2)**

7.5.7.4. Engine case penetrations, ruptures, or burn-through from an internal engine component. **(T-2)**

7.5.7.5. When an aircraft experiences a loss of thrust sufficient to prevent maintaining level flight at a safe altitude. **(T-2)** This includes all cases of multiple engine power loss or roll back.

7.5.7.6. Engine damage due to a foreign object and source of FO is determined to be internal to the engine. **(T-2)** For Propeller driven aircraft, both the propeller and engine will be impounded as a single unit when the engine has confirmed internal damage due to a foreign object. **(T-2)**

7.5.7.7. Engine damage which occurs during transport. **(T-2)**

7.5.8. Following an in-flight fire. **(T-2)**

7.5.9. When an aircraft experiences an in-flight loss of all pitot-static system instruments or all gyro stabilized attitude or direction indicators. **(T-2)**

7.5.10. When there is evidence of intentional damage, tampering, or sabotage. **(T-2)** **Exception:** Intentional damage due to combat is not mandatory.

7.5.11. When physiological incidents attributable to aircraft systems or cargo occurs. **(T-2)**

7.6. Impoundment Procedures.

7.6.1. When the Impoundment Authority directs impoundment, a Red X symbol will be placed in the applicable AFTO Form 781A for aircraft, applicable engine work packages for uninstalled engines or AFTO Form 244 for equipment (or electronic form equivalents) with a statement indicating the reason for impoundment and the name of the assigned Impoundment Official. **(T-2)**

7.6.2. The MOC will be notified when an impoundment decision has been made. **(T-2)**

7.6.3. Aircraft or equipment records will be controlled at the discretion of the Impoundment Official. **(T-2)** When required, the Impoundment Official will:

7.6.3.1. Obtain and secure the current aircraft forms and the aircraft jacket file for aircraft, applicable engine work packages for uninstalled engines, or the AFTO Form 244 for equipment (or electronic form equivalents). **(T-2)**

7.6.3.2. Notify the MIS DBM administrator to isolate the aircraft or equipment serial number in order to prevent any changes and maintain the integrity of the historical data until the aircraft or equipment is released. **(T-2)**

7.6.3.3. Request and collect any training records, required to complete the impoundment investigation. **(T-2)**

7.6.3.4. On aircraft impounded for potential safety related incidents, ensure the Cockpit Voice Recorder/Flight Data Recorder circuit breakers are pulled immediately after engine shutdown or before applying external power to safeguard Cockpit Voice Recorder/Flight Data Recorder data, if equipped. **(T-2)**

7.6.3.5. Ensure impounded aircraft/equipment is identified by cordon with cones, ropes or placards indicating impound condition and aircraft location. **(T-2)**

7.6.4. Impoundment Official will limit maintenance actions on impounded aircraft or equipment until the cause is determined. **(T-2)**

7.6.4.1. The Impoundment Official will determine what maintenance can be performed in conjunction with the maintenance required to release the aircraft or equipment from impoundment. **(T-2)**

7.6.4.1.1. Impoundment Official will coordinate with Wing Safety or equivalent for aircraft, equipment, and parts disposition to support any ongoing safety or mishap investigation. **(T-2)**

7.6.4.2. Parts removed from impounded aircraft or equipment will be carefully controlled until impound has been cleared and/or a safety investigation determination has been made. **(T-2)** This is to ensure that parts, once confirmed as the cause for impoundment, are available to be processed as DR exhibits.

7.6.5. The Impoundment Official will select a team of qualified technicians dedicated to determining the cause of the problem that led to the impoundment. **(T-2)**

7.6.5.1. Impoundment team members will be relieved of all other duties until released by the Impoundment Official. **(T-2)**

7.6.6. Once the cause of the malfunction or failure has been positively determined, the Impoundment Official will brief the Impoundment Release Authority on findings, corrective actions, and requests release of the aircraft or equipment from impoundment. **(T-2)**

7.6.7. If the cause of the discrepancy could potentially affect other aircraft or equipment in the fleet, QA will provide cross-tell information for up-channeling to the MAJCOM and the designated Lead Command IAW AFPD 10-9. **(T-2)**

7.6.8. Clear impoundments from forms/MIS IAW TO 00-20-1. **(T-2)**

7.6.9. If the cause of a reported malfunction cannot be determined or a positive corrective action cannot be confirmed, the Impoundment Release Authority will determine if further actions are required (such as, requesting depot assistance, further troubleshooting, FCF/OCF). **(T-2)**

7.6.10. MAJCOMs will publish guidance outlining impoundment and release procedures for transient aircraft.

7.6.10. **(AFGSC)** Coordinate required transient aircraft impoundments through owning MXG/CC, off-station transient alert and off-station QA sections. Impoundment Release Authority will be coordinated between owning MXG/CC and the transient location MXG/CC. If no off-station agencies exist, the owning MXG/CC and the owning OG/CC will issue guidance directly to the aircraft commander and off-station maintenance personnel**. (T-2)**

7.6.10.1. At locations where no MXG/CC or designated representative is available, the aircraft assigned MXG/CC may temporarily delegate Impoundment and Release Authority.

7.7. Rules of Impoundment Specifically for Explosive-Related Events/Mishaps. When an inadvertent release or an explosive mishap is reported, the following procedures will apply:

7.7.1. In-flight:

7.7.1.1. When the involved aircraft returns to the de-arm or parking area, the aircraft will be impounded. **(T-2)** Limit maintenance actions to those required to make the aircraft safe.

7.7.1.2. The MXG/CC, MOC, Munitions Control, WWM, QA and Wing Safety or equivalent will be notified of the impoundment action. **(T-2)**

7.7.1.3. The aircraft with unsafe munitions will be parked and isolated in an area approved by the weapons safety office or equivalent and airfield management. **(T-2)**

7.7.1.4. Investigate and report the incident IAW DAFI 91-204.

7.7.2. Ground:

7.7.2.1. The senior ground crew member will be in charge of the aircraft or equipment until relieved and will ensure involved persons remain at the scene. **(T-2)**

7.7.2.2. Protect other aircraft or equipment located near the incident if an explosive hazard exists. **(T-2)**

7.7.2.3. Do not change the position of any switches except as needed for safety. **(T-2)**

7.7.2.4. Limit maintenance actions to those actions required to make the aircraft or equipment safe. **(T-2)**

7.7.3. Preserve mishap evidence to the maximum extent possible. **(T-2)** An example would be segregating an aircraft gun versus destroying it if it poses no immediate danger. This allows for evaluation of all the evidence and the ability to recreate the mishap conditions.

7.7.4. If an incident, malfunction, or mishap is suspected to have occurred or caused by in-use, installed, or otherwise configured munition (live or inert), or a 20 or 30MM gun system jam creating a safety condition, notify the Global Ammunition Control Point Air Force Life Cycle Management Center, Munition Division (AFLCMC/EBH) Munitions Rapid Response Team: DSN: 312-777-2666; COMM: (801) 775-2666, and the MAJCOM munitions staff. **(T-2)**

7.7.4. **(AFGSC)** Notify AFGSC munitions staff at DSN: 781-1996 or COMM: 318-456-1996.

7.7.4.1. Refer to DAFI 91-202 for additional information about the Munitions Rapid Response Team. **Note:** The Munitions Rapid Response Team can also provide units technical assistance in resolving recurring 20 or 30MM gun system jams and malfunction isolation.

7.7.5. For impoundments involving nuclear loaded weapon systems see **Paragraph 7.5.6**. **(T-2)**

Chapter 8

TOOL AND EQUIPMENT MANAGEMENT

8.1. Tool and Equipment Management. The objectives of the Tool and Equipment Management Program are to prevent and eliminate FOD to aircraft, engines, missiles, training, and support equipment, and to reduce costs through strict effective control and accountability of assets. To ensure standardization among maintenance units, commanders and key leaders are responsible for executing an effective tool program. MAJCOMs will identify small unique unit tool and equipment management requirements in a supplement, addendum or deviation as described in the purpose statement of this DAFI. DFT/CFT will adhere to local tool control policies and procedures provided in the MXG/MXO in-brief (see **Paragraph 5.2.1.9**) when working on aerospace equipment possessed by the unit. The AF enterprise Tool Accountability System is TCMax®. **(T-2) Exception:** N/A to aircraft/weapon system programs that provide tool and equipment accountability support as an internal function of the program (e.g., F-35 ALIS).

8.2. Guidelines for Program Management. Wings will document procedures for the control and management of all tools/equipment used for aircraft/aerospace equipment maintenance or which enter the flightline or aerospace equipment maintenance industrial areas, to include all wing organization's (Hospital, CE, vehicle Mx, Security Forces), to provide mission support in a wing level publication IAW DAFMAN 90-161. As a minimum, guidance will address the following:

8.2.1. Standardized procedures for security, control, and accountability of tools and equipment. **(T-3)**

8.2.1.1. DELETED.

8.2.2. Inventory requirements. **(T-3)** As a minimum, units will conduct and document an annual inventory of all tools and equipment. **(T-3)**

8.2.3. Procedures for warranted tool management. **(T-3)**

8.2.3.1. Procedures to tag/segregate unserviceable warranty tools. **(T-3)**

8.2.4. Procedures for control and management of replacement, expendable and consumable hand tools, HAZMATs, and other items contained in CTKs. **(T-3)**

8.2.5. Procedures for transfer of tools/CTKs at the job site (on-site transfers). **(T-3)**

8.2.5.1. Ensure tool accountability and control is maintained when transfer occurs between the individuals. As a minimum the individuals involved in the transfer will accomplish a joint inventory and document accordingly. **(T-3)**

8.2.6. Procedures for lost or missing tools. **(T-3)**

8.2.7. Assignment of Equipment Identification Designators (EID) for CTKs, non-CA/CRL equipment, and assignment of CTK numbers for tools. **(T-3)**

8.2.8. Procedures for issue, marking, and control of PPE, tools, or equipment (such as, hearing protectors, reflective belts, headsets) assigned/issued to individuals. **(T-3)**

8.2.8.1. At a minimum, individual issued equipment will be marked with first name initial, last name, and employee number. **(T-3)** For members without employee numbers,

organizational items will be marked with first name initial, last name, and organization. **(T-3)**

8.2.9. Procedures to ensure positive accountability and control of rags. **(T-3)**

8.2.9.1. A rag is defined as a remnant of cloth purchased in bulk or a standardized, commercial quality, vendor-supplied shop cloth used in general industrial, shop, and flightline operations.

8.2.9.1.1. Cheesecloth is considered a rag; however, paper products/paper towels are not considered rags.

8.2.9.2. Rags should be uniform in size and color.

8.2.9.3. Marking or identifying each shop rag with a CTK number is not necessary.

8.2.10. Procedures to limit numbers of personnel authorized to procure tools. **(T-3)**

8.2.11. Procedures for control of locally manufactured or developed tools and equipment. **(T-3)**

8.2.12. Procedures for FSRs/DFTs/CFTs when working on equipment within the unit. **(T-3)**

8.2.13. Standardized procedures and responsibilities for decentralizing CTKs, tools, and equipment outside tool room/support section to meet mission requirements. **(T-3)**

8.2.13.1. Inventory and accountability requirements described in this DAFI apply equally to all decentralized CTKs tools, and equipment. **(T-3)**

8.2.14. Procedures for control of response equipment permanently stored/located in trailers or vehicles. **(T-3)**

8.2.15. Procedures for requiring a second party or on-duty supervisor inspection of CTKs when conditions warrant a single person shift. **(T-3)**

8.2.15.1. The same individual that signs out a CTK cannot sign it back in. **(T-3)**

8.2.16. Procedures for controlled access to tool rooms. **(T-3)**

8.3. General Program Guidelines.

8.3.1. The Flight CC/SUPT will designate CTK custodians. **(T-3)**

8.3.1.1. CTK custodians are responsible for tool, HAZMAT, and consumable asset accountability and control. **Exception**: A separate person may be designated as the HAZMAT monitor.

8.3.2. Flight CC/SUPT and/or Section NCOICs/Chiefs (or equivalents) will determine the type, size, contents, and number of CTKs required for their work centers. **(T-3)**

8.3.2.1. The WWM will make this determination for load crew CTKs, when assigned. **(T-3)**

8.3.3. Design CTKs to provide for quick inventory and accountability of tools. CTKs and tools will be clearly marked with the Equipment Identification Designator (EID) (follow guidance below). **(T-3)**

8.3.4. CTK contents will be standardized to the maximum extent possible within functional elements of a squadron that have similar missions (such as, aircraft flights/sections and Combat Armament Support Team). **(T-3)**

8.3.5. Each tool, item of equipment, or consumable contained in a CTK will have an assigned location identified either by inlay cuts in the shape of the item, shadowed layout, label, or silhouette. **(T-3)**

8.3.5.1. No more than one item will be stored in a cutout, shadow, or silhouette. Tools too small to be etched individually may be place in CTKs as a set (such as, drill bits, Allen wrenches, apexes, or paired items like gloves, booties). **(T-3)**

8.3.5.2. **(Added-AFGSC)** Special purpose CTK/TKs that are kept in carrying bags or cases (e.g., marshalling kits, recovery kits, etc.) because of the nature of contents or type of container are not required to have identified inlay cuts, shadowed layout, label, or silhouette in the shape of the item, but will contain a content inventory as an integral part of the kit. **(T-2)**

8.3.6. A Master Inventory List (MIL) will be required for each CTK or series of identical CTKs. **(T-3)**

8.3.6. **(AFGSC)** Dispatchable support equipment (SE) or special tools (ST) inventory must match MIL in TCMax®. The Dispatchable SE/ST will follow the same rules for broken/missing items IAW **paragraph 8.3.6.7**. **(T-2)**

8.3.6.1. The WWM will approve/sign a single MIL to be used as the standard for all Load Crew CTKs on like mission-design-series aircraft; a copy will be maintained in each support section. **(T-3)**

8.3.6.2. When items such as dispatchable support equipment or dispatchable special tools are issued separately (not contained in a CTK) and contain multiple parts that are required for its use (such as, cartridges containing consumables, cables, hoses, adapters), a MIL of all the items will be provided with the support equipment or special tools to facilitate positive accountability of all items during checkout, transfer, and check in. **(T-3)**

8.3.6.3. The MIL resides in the TCMax®, but a hard copy of the signed MIL must reside with each dispatchable CTK to provide the ability to verify the inventory regardless of location. **(T-3)**

8.3.6.4. If items such as identification tags or dust caps are attached to tools/equipment, they will be secured in a manner that will minimize any possibility of FOD. **(T-3)**

8.3.6.4.1. Items not permanently attached, will be marked/etched with the appropriate CTK number. **(T-3)**

8.3.6.4.2. All items will be listed on the MIL. **(T-3)**

8.3.6.5. Consumables may be placed in CTKs. If so, they will be identified on the MIL as consumables. **(T-3)** Examples of consumables include safety wire, adhesive, wire bundle lacing, solder.

8.3.6.5.1. Do not include common hardware items such as bolts, nuts, and/or screws unless they are required for the tool to perform its intended function. Cartridges or

equivalents containing consumable items whether disposable or not will be accounted for to mitigate FOD hazards. **(T-3)**

8.3.6.5.2. **(Added-AFGSC)** If lead seals are kept in CTKs they will be listed as consumable items. Lead seals include the following: lead, tool-less Roto, or other approved sealing devices listed in applicable TOs. **(T-2)**

8.3.6.6. Tool sets placed within a CTK will be identified on the CTK MIL by total number of items in the set (such as, Allen wrench set - 9 each Allen wrenches + container for a total of 10). **(T-3)**

8.3.6.6.1. Items identified as too small to be marked, etched, or stamped, as approved by QA, will be annotated with a description of the individual items contained within the set on the CTK/MIL (such as, the variation in the size of the items contained within the set, Apex, file, drill bit, size). **(T-3)**

8.3.6.7. Missing, removed and/or broken tools/items will be documented in the TCMax® if they cannot be replaced immediately. **(T-3)**

8.3.6.7.1. In addition, for dispatchable CTKs, dispatchable support equipment, and dispatchable special tools containing multiple parts, missing, removed and/or broken tools/items will be documented on a MAJCOM/locally generated form, or on the hard copy MIL. **(T-3)**

8.3.6.7.1.1. If a MAJCOM/locally generated form is used, the form will be kept with each dispatchable CTK, dispatchable support equipment and dispatchable special tools. **(T-3)**

8.3.6.7.1.1. **(AFGSC)** If a locally generated form is used the form will be standardized by the MXG and used by all subordinate sections. **(T-2)**

8.3.6.7.1.2. Pencil/pen may be used for hard copy MIL documentation and erased/lined through when cleared.

8.3.6.7.2. The EID will be removed from any permanently removed item/tool. **(T-3)**

8.3.6.7.3. A permanently removed (without planned replacement) item/tool constitutes a change to the inventory and requires a new MIL.

8.3.6.7.4. The CTK custodian has the authority to interchange "like" (form, fit, function) items.

8.3.7. Equipment and accessories that do not present a FOD potential and will not leave the work center, support section, or tool room, need not be included in a CTK; however, this equipment must have designated storage locations established. **(T-3)**

8.3.7.1. Designated locations may be work areas or stations.

8.3.8. The CTK Custodian will establish designated locations for test equipment and common accessories (such as, waveguides, attenuators, fittings, cables, adapters) that are not part of a CTK. **(T-3)**

8.3.8.1. As a minimum, designated locations will be labeled to identify the contents. **(T-3)**

8.3.8.2. Industrial shop machinery accessories/attachments (example, blades, arbors, chucks, gears) need not be controlled as tools; however, these items will be maintained in designated storage locations for accountability. **(T-3)**

8.3.8.2.1. As a minimum, storage cabinets/drawers will be labeled to identify the contents. **(T-3)**

8.3.9. Tools/expendable items used for titanium engine blade blending or oxygen system maintenance will be kept in special purpose kits separate from other tools. **(T-3)**

8.3.9.1. In addition to normal CTK identification, the titanium engine blade blending kits will be marked "For Titanium Engine Blade Blending Only". **(T-3)**

8.3.9.2. In addition to normal CTK identification, oxygen system maintenance kits will be marked "For Oxygen System Use Only". **(T-3)**

8.3.10. Discard removable (slide on) pocket clips and spare parts from tools when possible (flashlights, continuity testers, small screwdrivers) prior to placement in tool kits. **(T-3)**

8.3.10. **(AFGSC)** Annotate removed items on MIL and in TCMax®. **(T-2)**

8.3.10.1. Do not disassemble or damage tools for sole purpose of removing clips (example, tape measures, rubber switch guards).

8.3.11. Tools not controlled through CTK procedures are NOT authorized on the flightline, or in any maintenance area (for example, personal Mini Maglite® flashlights, Leatherman®, Buck Knives®). **(T-3)**

8.3.11.1. Units will mark and control equipment that a workcenter assigns/issues to an individual IAW MAJCOM supplements. **(T-3)**

8.3.11.1.1. **(Added-AFGSC)** Mark all individually issued equipment with the owner's first initial, last name and employee number (e.g., J. Doe, 01234).

8.3.11.2. Personally purchased tools are not authorized. **(T-3)**

8.3.12. Flashlights, lanterns, portable lighting devices and light sources will conform to the requirements of TO 00-25-172 when used during servicing operations; TO 1-1-3 when used during fuel cell maintenance; and DESR6055.09_AFMAN 91-201 when used in explosive environments. **Note:** Aircraft and equipment TOs may dictate additional restrictions.

8.3.13. **(Added-AFGSC)** Layout dye will be controlled through TCMax® to ensure only a qualified 7-level or above can obtain for marking damaged fan/compressor blades or marking dented tubing. Not applicable to 2A7XX AFSC. **(T-2)**

8.4. TMDE Management Guidelines. Support Sections will designate a TMDE Monitor who will act as the focal point with the designated servicing PMEL (whether on-base or off-base) for managing the TMDE calibrations requirements for the owning work center. **(T-3)** The TMDE Monitor will:

8.4.1. Establish procedures for turn-in and pick-up of TMDE requiring calibration. **(T-3)**

8.4.2. Coordinate emergency calibration requirements. **(T-3)**

8.4.3. Review quarterly TMDE schedules and annual master identification (ID) lists within 5 duty days of receipt from servicing PMEL. **(T-3)**

8.4.3.1. Forward any corrections to the servicing PMEL within 3 duty days to have the PMEL Automated Management System/MIS updated. **(T-3)**

8.4.4. Take necessary actions to minimize the late delivery of TMDE for scheduled calibration. **(T-3)** Servicing PMEL will notify OWC of overdue TMDE under established procedures. **(T-3)**

8.4.5. Use PMEL Automated Management System or equivalent MIS (as coordinated with supporting PMEL) to control TMDE processed for maintenance. **(T-3)**

8.4.6. Ensure TMDE submitted for calibration has all required documentation complete, the AFTO Form 350 (as applicable) provides adequate malfunction description and accessories/ items required for calibration accompany the TMDE to include batteries (as applicable). **(T-3)**

8.4.7. Ensure classified TMDE is protected IAW AFI 16-1404.

8.4.8. Ensure TMDE shipped off base for calibration or repair and return is shipped by traceable means and IAW DAFI 24-602V2.

8.4.8.1. The TMDE Monitor will maintain a file consisting of all supporting documentation for each type of shipment. **(T-3)**

8.4.8.2. Safeguard any IUID marks during calibration/TMDE activities to the extent possible. In the event the UII is damaged during calibration activities, the TMDE Monitor will notify the responsible Equipment Custodian and/or EAE to replace the mark with the same UII. **(T-3)**

8.4.9. For deployment purposes, ensure equipment, tools, and HAZMAT items are properly identified, prepared, and documented IAW AFI 10-403.

8.5. Tool Accountability and Serviceability. Flight CC/SUPT and Section NCOICs/Chiefs, through CTK Custodians, are responsible for tool and equipment accountability and control (knowing where tools are and who has responsibility for them). When a person signs for a tool or piece of equipment, they are considered the user and accountable for the item until it is returned to the tool room and accountability transfers back to the CTK Custodian (through a representative or tool room employee).

8.5.1. All units must use TCMax® for accountability and control of tools and equipment. **(T-3)** Contractors and MEOs are not required to use TCMax® unless specified in the Performance Work Statement/Statement of Work. **Note:** Refer to **Paragraph 8.1** for exceptions.

8.5.1.1. Units are required to electronically back up TCMax® at least once a month. **(T-3)**

8.5.1.1.1. This backup must be kept physically and electrically separate from the computer that houses the tool control database. **(T-3)**

8.5.1.2. Units will use TCMax® to:

8.5.1.2.1. Track the issuance and receipt of all assigned tools, equipment, tool kits, HAZMAT items, TOs (does not apply to TOs, equipment and HAZMAT kept in a shop and not dispatched). **(T-3)**

8.5.1.2.1.1. HAZMAT items issued for one time use (oil cans, hydraulic cans, mixing compounds) are supply items and do not have to be tracked in TCMax®.

However, HAZMAT and supply procedures will be followed. **(T-3)**

8.5.1.2.2. Track authorizations/restrictions for special tools/equipment (by individual). **(T-3)**

8.5.1.2.3. Track CTK and Support Section inspections. **(T-3)**

8.5.1.2.4. Track spare, lost, damaged, and/or removed tools. **(T-3)**

8.5.1.2.5. Develop and manage tool/equipment inventories. **(T-3)**

8.5.1.2.6. Develop and manage deployment kits (import/export). **(T-3)**

8.5.1.3. If TCMax® is not available (such as at a deployed location), units will use the AF Form 1297, Temporary Issue Receipt, a MAJCOM, or locally approved form for accountability and control of CTKs, equipment, and tools. **(T-3)**

8.5.1.3. **(AFGSC)** Use AFGSC Form 140, *CTK Inventory and Control Log*, as the MAJCOM approved form.

8.5.2. The CTK Shift Supervisor will account for all dispatchable/decentralized CTKs, tools, and equipment at the beginning and end of each shift. **(T-3)**

8.5.2.1. Shift inventories must be documented by both outgoing and incoming personnel. **(T-3)**

8.5.2.2. CTKs present during tool room shift inventories do not need to be opened for inventory.

8.5.2.3. **(Added-AFGSC)** Units may establish a program for secure sealing of low-use tools. This method involves identifying items that ordinarily require counting during shift inventories and sealing the items with a physical indicator to speed inventory by avoiding unnecessary counting. Tools that are not signed out for 45 calendar days or more are considered low use. Examples are drill bit kits, Allen key sets, and tap and die sets, files, etc. Inventory the identified low-use items any time they are returned from a job and seal them in a way that prevents opening without breaking the seal (e.g., computer label sticker, lead seal, plastic zip strip, etc.). Label the item with the signature of individual performing tool count, date counted and sealed, number of pieces, tool kit number or item number. The low use sealed items are only required to be verified as "present" during daily shift inventories if the seal is intact. The seal remains valid as long as the item is unused and the seal remains secure, or until the next annual CTK inventory. Low use items will be identified on the appropriate MIL. **(T-2)**

8.5.3. At least annually or when the CTK Custodian changes, conduct a comprehensive inventory of all dispatchable/decentralized tools, non-Custodian Authorization/Custody Receipt Listing (CA/CRL) equipment, and CTKs. **(T-3)**

8.5.3.1. The purpose of this inventory is to perform an extensive inspection of all tools and non-CA/CRL equipment, to include condition, identification markings, and accuracy of the MIL/CRL Supplemental Listing.

8.5.3.2. CTK Custodians will ensure all tools are inspected for serviceability IAW TO 32-1-101, *Use and Care of Hand Tools and Measuring Tools*.

8.5.3.3. CTK Custodians will document these inventories and maintain the most current inventory. **(T-3)**

8.5.4. Users will perform a visual inventory of all dispatchable/decentralized CTKs when issued for use, at the completion of each job or tasks, and when returned to the tool storage facility. **(T-3)** Users will refuse unserviceable items and return to CTK custodian. **(T-3)**

8.5.4.1. Users will accomplish a CTK inventory prior to operation of any aircraft or equipment when maintenance actions are performed (such as, engine run, landing gear retraction, flight control operational checks). **(T-3)**

8.5.4.2. Users will perform an immediate and complete inventory of all CTKs when returning to the work area after sheltering for real-world/exercise events. **(T-3)**

8.5.4.3. Users will ensure dispatchable tools, equipment, eTools and CTKs are locked and/or secured when left unattended. **(T-3)**

8.5.4.4. CTK's signed out to deployed ABDR Individual/Assessor are not considered "issued-for use" unless signed open on an AFSC Form 309, *AFSC Tool Control Inventory Record*, or issued from a local deployed support section for the purpose of inventory requirements.

8.5.5. eTools: Units will use the following procedure to maintain positive control of assigned eTools:

8.5.5.1. Manage eTools IAW TO 00-5-1, and this instruction. **(T-3)**

8.5.5.2. Track dispatchable eTools in TCMax®. **(T-3)**

8.5.5.3. Ensure only serviceable eTools with current technical data are available for checkout, and any missing plugs/covers/doors are documented IAW **Paragraph 8.3.6.7**. **(T-3)**

8.5.5.4. Make maximum use of eTool warranties. **(T-3)**

8.5.5.5. Ensure eTools are used for official and authorized purposes IAW TO 31S5-4-etool, 17 & 33 Series instructions, MAJCOM guidance, and this DAFI.

8.5.5.5. **(AFGSC)** ETools are used for viewing electronic technical orders and maintenance documentation. ETools are also authorized for accessing .mil and .gov web sites along with technical order web sites, for official business only. ETools will not be used for e-mail or other personal computer type uses. **(T-2)** ETools that require Microsoft applications or other software applications to support viewing electronic technical orders and maintenance documentation may be loaded on eTools.

8.5.5.5.1. Not install unauthorized files or software (such as, games, mp3s). **(T-3)**

8.5.5.5.2. Not use unauthorized external media devices to retrieve data from removable hard drives. **(T-3)**

8.5.5.6. Coordinate with the local Cybersecurity Liaison and/or Information System Security Managers to identify publish local guidance on restrictions for the use of eTools/PEDs in classified processing areas. **(T-3)**

8.5.5.7. Establish procedures for shipping TOs, eTools, and required support equipment needed to ensure eTools availability to support mobility and deployed operational requirements. **(T-3)**

8.5.5.8. If applicable, units will update Defense Integration and Management of Nuclear Data Services (DIAMONDS) hardware and status IAW TO 11N-3150-8-1, *USAF DIAMONDS Policy and Procedures*. **(T-3)**

8.5.5.8.1. For accountability, DIAMONDS laptops and hardware must be managed and tracked in TCMax®, but do not require placement on unit equipment account IAW TO 11N-3150-8-1.

8.6. Tool and Equipment Marking and Identification.

8.6.1. To ensure tool rooms have unique identifiers, wings (or equivalent) must ensure other units within the same wing or Personnel Assignment Symbol (PAS) code do not duplicate the WWID. **(T-2)** MAJCOMs/ANG will develop, sustain, and review annually a complete listing of all the WWID utilized within their MAJCOM/ANG. MAJCOMs will update AF/A4LM with WWID changes as they occur. Reference the AF/A4LM SharePoint® site: **https://usaf.dps.mil/sites/haf-a4/A4L/AF_A4LM/Policy/SitePages/Home.aspx**

8.6.1.1. All units must permanently mark their tools and equipment with the standard EID. **(T-3)** GSU may use the parent wing EID. Replacement spare tools stored in the tool room do not need to be etched until placement in a specific CTK.

8.6.1.2. The EID will consist of nine characters (numbers/letters) of which the first four characters will be a unique WWID code. **(T-3)**

8.6.1.2.1. The WWID identifies the base (first and second character), unit (third character), and shop (fourth character). The remaining five characters are available for tool/CTK equipment numbering.

8.6.1.2.1.1. The first two characters of the WWID in the EID are based on the wing/unit PAS base code. Multiple wings (or equivalent) at the same base (example, ANG, AFR, and RegAF) must have different WWID codes. **(T-3)**

8.6.1.2.1.2. The third and fourth characters designate the unit and shop by using unique/distinguishable characters. To ensure tool rooms have unique identifiers, wings (or equivalent) must ensure other units within the same wing or PAS code do not duplicate the first 4 characters of the EID. **(T-3)**

8.6.1.2.1.3. Request additional "base" code information from AF/A4LM at: **AF/A4LM Maintenance Policy, AF.A4LM.Maintenance.Policy@us.af.mil**.

8.6.1.3. The unit will establish the remaining five characters (any combination of numbers/letters) for CTKs, tools, and dispatchable equipment identification. **(T-3)**

8.6.1.4. Units must place the 9-digit EID on all CTKs, tools not assigned to a box, and dispatchable equipment that is of sufficient size. **(T-3)**

8.6.1.4.1. The 9-digit EID must be placed on the outside of dispatchable CTKs. **(T-3)**

8.6.1.4.2. Tools located inside the toolbox may be marked with less than 9-digits but must contain the 4-digit WWID and will have identifying character(s) that ties the tool

back to the CTK. **(T-2)** For example, tools inside an assigned dispatchable CTK "U6JG00001" may be marked "U6JG1." Units may affix non-metallic barcode labels on tools to prevent re-etching as long as the use of the tool and its work environment does not normally result in excessive damage to the label making it unreadable.

8.6.1.4.3. Tools will be marked with the most current EID. **(T-3)**

8.6.1.4.4. All previous CTK identifiers will either be removed or marked out (this does not include PMEL markings). **(T-3)**

8.6.1.4.5. Small tool sets and/or items that cannot be marked as described in **Paragraph 8.3.6.6** above (such as drill bits, Allen wrenches in sets, apexes) will be maintained in a container marked with the EID and an identifying character(s) that ties the tool back to the CTK along with the number of tools contained. **(T-3)**

8.6.1.4.5.1. The container is counted as one of the items.

8.6.1.5. MXG/CCs may require use of the EID in addition to AFTO Form 66, *TMDE Bar Codes (Polyester Film)*, for TMDE routinely (example, once per week) dispatched from a work center or use of the AFTO Form 66 alone.

8.6.1.6. For items that physically or mechanically check tolerances that require calibration, do not etch, or stamp an EID in any manner that will affect calibration or the ability to calibrate. **(T-3)**

8.6.1.6.1. If marking is in question consult TO 00-20-14 and/or PMEL to validate applicable marking criteria.

8.6.2. Permanently mark (by etching or other means) grease guns, dispensing cans, spray bottles, pump oilers, and similar containers with the type of grease, fluid, or other liquids and Military Specification (MILSPEC) of the contents. **(T-3)** If the MILSPEC is subdivided into Grades, Classes, or Types, include that info on the permanent marking. **(T-3)**

8.6.2.1. If no MILSPEC exists, the item will be marked with the manufacturer's name, part number/NSN from the applicable Safety Data Sheet. **(T-3)**

8.6.2.2. Keep hoses and fittings separate for each type of grease. **(T-3)**

8.6.2.3. If containers are used to hold or apply substances classified as hazardous materials, ensure labeling requirements are IAW AFI 90-821, *Title 29 Code of Federal Regulations 1910.1200(f), Occupational Safety and Health Standards, Toxic and Hazardous Substances*. **(T-0)**

8.6.3. Prior to etching tools and equipment, consult applicable technical order to ensure no special circumstances apply for the item being etched (such as, fiberglass handled hammers are etched IAW TO 32-1-101 and safety glasses. **(T-3)**

8.6.4. CTKs, tools, and dispatchable equipment that may possess a unique serial/tracking number must be marked with an EID number. **(T-3)**

8.6.4.1. If the item cannot be marked, etched, or stamped, annotate the additional designator on the CTK contents list. **(T-3)**

8.6.5. Items that are assembled and are not intended to be disassembled during use, require only one mark/etch/stamp and one entry in the MIL (such as, scribes, flashlights, grease guns, feeler gauges). **(T-3)**

8.6.6. Remove the EID from unserviceable tools and tools removed from the CTK (with the exception of warranty tools where removal of EID may void the tool warranty) and update TCMax® and the MAJCOM/locally generated form or hard copy MIL accordingly. **(T-3)**

8.6.7. Ensure all tools which are accountable on a CA/CRL must be marked with a UII. **(T-3)** Units need to safeguard any IUID marks. In the event the UII is damaged, notify the responsible Equipment Custodian and/or EAE to replace the mark with the same UII.

8.7. Locally Manufactured, Developed, or Modified Tools and Equipment. All locally manufactured, developed, or modified tools and equipment used on aerospace equipment must be approved by the MXG/CC, their equivalent, or a designated representative and meet the requirements described in **Chapter 9**.

8.7.1. This procedure does not apply to tools and equipment authorized for local manufacture in MDS specific technical data or equivalent engineering approved document. QA will coordinate on all requests for approval and use of locally manufactured, developed, or modified tools or equipment. **(T-3)**

8.7.2. Work centers will review items and requirements every two years for applicability and current configuration. **(T-3)** See **Chapter 6** and **Chapter 9** for additional guidance.

8.7.3. Weapons loading, maintenance and armament systems locally designed equipment must be coordinated through the WWM. **(T-3)** Weapons loading, maintenance and armament systems locally designed equipment must meet the following requirements:

8.7.3.1. In the event munitions/armament LME, is not included in technical data or listed on the MMHE Focal Point website **https://cs2.eis.af.mil/sites/10134/sitepages/home.aspx**, contact the MMHE Focal Point AFLCMC/EBDW, 615 Apalachicola Road, Suite 101, Eglin AFB, FL 32542-6845 to establish/validate LME disposition.

8.7.3.1.1. Units must use MMHE Focal Point-designed munitions/armament LME for new procurements if a design exists and fills the requirement. **(T-2)**

8.7.3.1.1.1. Munitions/armament LME is specialized equipment designed to interface with or support munitions or armament suspension equipment (such as, tools, handling dollies, storage racks, maintenance stands, transport adapters). All munitions/armament LME contained on the MMHE Focal Point web site meets applicable DAFMAN 91-203 and USAF standards and is approved for local manufacture and use at unit level AF-wide. Drawing packages for these items are available to the unit via the MMHE Focal Point website.

8.7.3.1.1.2. Munitions/armament LME specifically designed to interface with or support munitions that are not contained in technical data or on the MMHE Focal Point website (such as, hardened/protective aircraft shelter missile racks, Y-stands, munitions chocks, specialized tools) must be coordinated at unit level and forwarded to the MAJCOM Functional Manager for coordination, evaluation, or both. **(T-2)**

8.7.3.1.1.2. **(AFGSC)** MAJCOM Functional Manager is AFGSC/A4W.

8.7.3.1.1.2.1. If the MAJCOM Functional Manager determines the item has AF utility, the drawings will be forwarded to ACC/A4WC for review and addition to the MMHE Focal Point Master Project List that results in formal development and placement onto the MMHE Focal Point website.

8.7.3.1.1.3. Munitions/armament LME not designed to interface with or support munitions that are not contained in technical data or on the MMHE Focal Point web site must be approved by QA. **(T-2)**

8.7.3.1.1.3.1. Units are encouraged to forward any such approved LME for possible inclusion on MMHE Focal Point web site by sending an approved drawing package to the MAJCOM Functional Manager for coordination/evaluation.

8.7.3.1.2. All LME must meet applicable DAFMAN 91-203 and USAF standards.

8.7.3.1.3. All equipment designated for use with nuclear weapons test and handling must meet requirements in DAFI 91-101.

8.7.3.1.4. All weapons loading, maintenance and armament systems LME must be maintained and inspected for serviceability on a regular basis IAW applicable TO 00-20-series, TO 35D-1-2, *Maintenance Instructions WIPB-Miscellaneous Munitions Handling and Support (Munitions Related)*, and TO 35D-2-2 *Munitions Materiel Handling Equipment Miscellaneous And Locally Manufactured – Armament Related*.

8.7.3.1.4.1. AFTO Form 244, or equivalent, must be maintained for all LME items (racks, stands, adapters) except hand tools. **(T-3)**

8.7.3.1.4.2. Equipment without technical data must, as a minimum, be inspected every 180 days for corrosion, physical defect, and lubrication as required. **(T-3)**

8.8. Tool Room Operations and Tool Security.

8.8.1. Operations. Tool rooms will be set up to ensure accountability. **(T-3)**

8.8.1.1. Procedures will be established to ensure custodial control. **(T-3)**

8.8.1.2. Tools will not be issued individually from dispatchable CTKs. **(T-3)**

8.8.1.2.1. When a recurring need exists for common tools to be issued individually, (such as, hammers, screwdrivers, pliers, drills, wrenches) individual issue bins/drawers may be established as a CTK within the tool room. **(T-3)**

8.8.1.3. Process reports for tools that are lost, damaged, or destroyed, due to neglect IAW AFI 23-101. **(T-3)**

8.8.2. Security.

8.8.2.1. The tool room must be capable of being locked and afford protective measures such as monitoring, 24-hour coverage, or controlled key access. **(T-3)**

8.8.2.1.1. When all CTKs are not capable of being secured in the tool room, the Section NCOIC/Chief will design a process to prevent the unauthorized use or access to tools and equipment. **(T-3)**

8.8.2.1.2. Due to space and facility limitations, it may not be possible to store oversized tool kits in the tool room.

8.8.2.2. Locks will be used on tool kits stored outside the CTK to provide a physical barrier to opening the container lid, drawer or door and prevent the unauthorized removal of tools. **(T-3)**

8.8.2.2.1. Locks are not required on tools and equipment that are stored within secured tool rooms or work centers.

8.8.2.2.2. Tools and equipment will never be secured to the exterior of an aircraft. **(T-3)**

8.8.2.2.3. Tool kits located within high traffic, controlled movement areas or that could limit aircraft movement or be exposed to jet blast are required to be locked when unattended/not in use and moved to un-obstructive/exposed location. **(T-3)**

8.8.2.2.3.1. Alert Aircraft in Protection Level Areas 1, 2, and Alert Status Aircraft in Protection Level Area 3. CTKs in these areas that are directly supporting alert status aircraft do not have to be locked when unattended and not in use as long as they are inventoried at the beginning of each shift, after each maintenance task, and at the end of each shift.

8.9. Lost Item/Tool Procedures.

8.9.1. Authorization to clear Red X's when an item/tool cannot be located should be no lower than Maintenance Supervision IAW **Chapter 2**. **Exception:** For contingency operations with absence of Maintenance Supervision, aircraft commander assumes responsibility.

8.9.2. Supervisors need to ensure all assigned personnel are familiar with lost item/tool procedures. If an item/tool or a portion of a broken item/tool is discovered missing, the following procedures apply:

8.9.2. **(AFGSC)** When an item/tool is discovered missing after an aircraft has taxied, maintenance (e.g., Expediters, Pro-supers, shift supervisors, etc.) will notify MOC, who in turn notifies appropriate agencies to recall the aircraft if necessary. **(T-2)**

8.9.2.1. The person identifying the missing item/tool will search the immediate work area for the item/tool. **(T-3)**

8.9.2.1.1. If not found, after completing an initial search the individual will notify the expediter/Pro Super or equivalent. **(T-3)**

8.9.2.1.1. **(AFGSC)** The AFGSC Form 145, *Lost Tool/Object Report*, will be initiated if the tool/item is not found during the initial search. (**Note:** The AFGSC Form 145 must be completed even if the lost tool/item is found). **(T-2)**

8.9.2.2. Place a Red X in the aircraft or equipment forms of all affected aircraft or equipment with a description of the item/tool and a specific, last known, location of the item/tool. **(T-3)**

8.9.2.3. Expediter/Pro Super or equivalent will immediately notify the Flight CC/SUPT, Support Section, MOC, and QA. **(T-3)**

8.9.2.3.1. Initiate a thorough search for the item/tool. **(T-3)**

8.9.2.3.2. Initiate the lost tool report if tool is not located during initial search. **(T-3)**

8.9.2.4. If it is suspected that the item/tool has fallen into an inaccessible or unobservable aircraft area, perform an NDI or use borescope equipment to locate the lost item/tool. **(T-3)**

8.9.2.4.1. If the item/tool is in an inaccessible area that poses no FOD threat and the action is to leave the item/tool in place, the x-ray (or equivalent) with the identification of the exact item/tool location and copies of all information concerning the lost item/tool are maintained in the aircraft historical file until the item/tool is recovered. **(T-3)**

8.9.2.5. If at any time during the investigation the item/tool is found, notify the Flight CC/SUPT, Support Section, MOC, QA, expediter, Pro Super or equivalent, and the owning work center. **(T-3)**

8.9.2.5.1. If the item/tool is found, but is inaccessible, Maintenance Supervision may explore other possible actions to include having the unit or a DFT disassemble the aircraft to remove the item/tool.

8.9.2.5.1.1. If the aircraft MDS is one that has a PDM or is scheduled for depot modification, any inaccessible lost item/tool will be listed with location on the AFTO Form 345, Aerospace Vehicle Transfer Inspection Checklist and Certification, for removal by the depot. **(T-3)**

8.9.2.5.1.1. **(AFGSC)** Also ensure AFTO Form 103, *Aircraft/Missile Condition Data*, is annotated for depot to remove the item/tool. **(T-2)**

8.9.2.6. Maintenance Supervision will determine when the search for the lost item/tool may be discontinued. **(T-3)** If the item/tool is not found:

8.9.2.6.1. Notify the MOC and the MXG/CC when the search for the lost item/tool has been discontinued. **(T-3)**

8.9.2.6.2. Ensure lost item/tool report is completed IAW locally established procedures. **(T-3)**

8.9.2.6.2. **(AFGSC)** Units will use the AFGSC Form 145, *Lost Tool/Object Report*. Use of an electronic AFGSC Form 145 is authorized for routing purposes. Units will develop local procedures for initiating and routing to ensure proper tracking, reporting and accountability for all AFGSC Forms 145 that are initiated/issued. The completed original Lost Tool/Object report must be submitted to QA within 5 duty days from date of initiation for filing. Additionally, a copy of the report may be filed and maintained by the Wing FOD Monitor if the Wing CV has assigned responsibility for tracking lost tools/items. Maintain the original report in QA for one year. **(T-2)**

8.9.2.6.2.1. **(Added-AFGSC)** CTK custodians will inform QA when lost tools are found after the AFGSC Form 145 has been closed out. The CTK custodian will retain the AFGSC Form 145 in accordance with the RDS. QA will inform the Wing FOD manager when lost tools are found. **(T-2)**

8.9.2.6.3. If applicable, ensure the TCMax® is documented IAW **Paragraph 8.3.6.7**. **(T-3)**

Chapter 9

MATERIEL MANAGEMENT SUPPORT

9.1. General. Material management plays a critical role in optimizing mission generation capabilities. Although assigned to LRS, all DMS personnel must be integrated into daily mission generation operations both at home station and deployed. The critical nature of direct interaction between maintenance and materiel management activities at the point of maintenance provides units direct access to materiel management SMEs to accurately identify, communicate, acquire, or disposition materiel management support necessary to maximize combat capability. This **Chapter**, coupled with AFI 23-101, provides the minimum materiel management support requirements necessary to provide the best possible opportunity for success in meeting mission generation requirements. The AF has consolidated materiel management support under the AF Sustainment Center. The AF Sustainment Center provides fleet-wide supply support to all AF weapon systems and leverages consolidated repair facilities and ALCs capability to optimize weapon system availability.

9.2. Decentralized Materiel Support. Decentralized Materiel Support personnel coordinate maintenance and materiel management actions and manage supply transactions for the MXG. The duty location for DMS personnel is the applicable maintenance unit as agreed upon by the MXG and base 2S0 functional manager. Personnel rotations, as determined by the base 2S0 functional manager will be accomplished with consideration of operational, career development, and training requirements. **(T-3)**

9.2.1. In units with Decentralized Materiel Support personnel, the LRS Superintendent exercises control and career-field development opportunities for Decentralized Materiel Support (2S0XX) personnel. **(T-3)**

9.2.2. In units/work centers directly supported by Decentralized Materiel Support personnel, the Logistics Readiness Squadron Materiel Management Flight is responsible for ensuring materiel management support roles and responsibilities listed are completed IAW 23-series publications.

9.2.3. LRS Superintendent will ensure complete DMS coverage of MXG duty periods, to include weekend duty. **(T-3)**

9.2.4. At a minimum, DMS personnel will provide the following support functions to the maintenance unit: monitor and track assets in the repair cycle, resolve supply support problems, and report aircraft parts status and changes in base level repair capability to maintenance supervision. **(T-3)**

9.2.4.1. Decentralized Materiel Support personnel also support maintenance in processing issue requests, researching sources of supply, entering manual requisitions (part number only), updating exception code lists, and resolving other peculiar maintenance supply problems. **(T-3)**

9.2.4.2. DMS personnel will manage processes, in addition to those previously described, such as parts ordering, backorder review and validation, Readiness Spares Packages, and TNB. **(T-3)**

9.2.4.3. **(Added-AFGSC) [NC3]** Maintenance will process their issue requests directly from their external maintenance IT system (e.g., Integrated Maintenance Data System (IMDS) and G081, etc.) to ensure that aircraft with a **NC3 equipment designator** assigned will be applied against the proper end item (e.g., AN001, or AN135), not the aircraft (e.g., A0001, or A1035).

9.2.4.4. **(Added-AFGSC) [NC3]** If the asset does not issue when input into the external maintenance system, maintenance personnel will provide a copy of an AF Form 2005, *Issue/Turn-In Request* (or locally developed product with required information) to DMS or Customer Support personnel to ensure that aircraft with a NC3 equipment designator assigned will be applied against the proper end item (e.g., AN001, or AN135), not the aircraft (e.g., A0001, or A1035).

9.3. Supply Discipline. Supply discipline is the responsibility of all military and civilian personnel regardless of grade or position. Personnel at all levels need to ensure the practice of good supply discipline.

9.4. Readiness Spares Package Review. Maintainers play a critical role in the annual Readiness Spares Package review process. This role includes active maintenance participation in the base level validation process conducted by the LRS and their MAJCOM during the annual Readiness Spares Package pre-review process in preparation for the Weapon System Program Manager final review. Close maintenance-materiel management collaboration is essential to ensure RSPs are properly sized to support contingency maintenance requirements. See DAFMAN 23-122 for further details.

9.5. Bench Stock. Flight CCs/SUPT and/or Section NCOICs/Chiefs will determine the contents of their bench stock IAW qualification criteria in DAFMAN 23-122. **(T-3)** Examples of bench stock items include nuts, bolts, cotter keys, washers, resistors, capacitors, light bulbs, sealants, and batteries. Bench stock levels are managed and based predominantly on consumption. Monthly and semi-annual bench stock listings are provided by the LRS/DMS. A thorough review of these listings is extremely important to ensure that bench stock supports the mission efficiently and economically.

9.5. (AFGSC) Bench Stock. Maintain a master inventory of items. **Note:** Assets cannot be commingled. **(T-2)**

9.5.1. Bench stock assets are organizationally purchased and therefore organizationally owned. Appointment of DMS personnel as bench stock monitors must be agreed upon by the applicable Squadron Superintendents.

9.5.2. Mark bins containing 50 percent or less of the authorized quantity to facilitate monthly inventories. **(T-3)** Do not include items coded TCTO, unacceptable for AF use and critical in bench stock. Controlled Item Code S and C may be in bench stock with MAJCOM approval. Other controlled Item Codes are authorized with written approval from Unit Commander. See DAFMAN 23-122 for additional information.

9.5.3. Work center supervisors will:

9.5.3.1. Semi-annually complete a bench stock joint review with the Customer Support Liaison Element, Materiel Control. **(T-3)**

9.5.3.1.1. During these reviews, special emphasis needs to be given to items with no demands in the past year and items with excessive quantities not supported by demands. The continuance of stocking such items is the exception and not the normative process. See DAFMAN 23-122 for further details.

9.5.3.2. Work with DMS or LRS/materiel management activity to ensure demilitarization criteria is identified, and used or excess items are disposed of IAW procedures in DAFMAN 23-122.

9.6. Consumable Readiness Spares Package. The Consumable Readiness Spares Package process provides requirement and asset visibility, has automated transfer and deployment procedures, has the capability to provide the correct priority and project-coded replenishment requisitions, and eliminates redundant requirements. Additionally, Consumable Readiness Spares Package procedures provide MAJCOMs with a standard process to support consumable item requirements during contingency operations. Refer to DAFMAN 23-122 for Consumable Readiness Spares Package procedures and options.

9.7. Shop Stock. Shop stock includes gas cylinders, random length bar stock, sheet metal, plastic, fabric, electrical wire, and similar items not normally included in bench stocks. Maintain shop stock for day-to-day operations. Monitor shop stock to prevent materiel from becoming excessive or outdated. Shop stock should not normally exceed 90-days usage, or the unit of issue or unit pack, whichever is greater. Store shop stock near/adjacent to bench stock items, if practical, but do not mix them together. Clearly identify materiel as "Shop Stock" and label them with noun, national stock number or part number, unit of issue, and shelf-life, if applicable.

9.7. (AFGSC) Shop Stock. Maintain a master inventory of items. **Note:** Assets cannot be commingled. **(T-2)**

9.8. Operating Stock. Operating stock includes connector dust covers, hydraulic line caps/plugs, and similar items that are normally recovered after use and re-used. Store operating stock near/adjacent to bench stock items, if practical, but do not mix them together. Monitor operating stock to prevent it from becoming excessive or outdated. Retain partially used bench stock items in bench stock and not in operating stock. Identify, tag, and turn in items with no forecasted use IAW AFI 23-101. Clearly identify items as "Operating Stock" and label them with noun, national stock number or part number, unit of issue, and shelf-life as applicable.

9.8. (AFGSC) Operating Stock. Maintain a master inventory of items. **Note:** Assets cannot be commingled. **(T-2)**

9.9. Work Order Residue. Work order residue includes expendable bit/piece items left over from maintenance work orders or bench stock deletions. Store work order residue near/adjacent to bench stock items, if practical, but do not mix them together. Ensure excesses are consolidated for turn-in to LRS at least annually. Clearly identify items as "Work Order Residue" and label them with noun, national stock number or part number, unit of issue, and shelf-life as applicable. Control all work order residues used on or around aircraft, uninstalled engines, and AGE.

9.9. (AFGSC) Work Order Residue. Maintain a master inventory of items. **Note:** Assets cannot be commingled. **(T-2)**

9.10. Adjusted Stock Levels. Adjusted stock levels are used when the demand level or consumption is inadequate to support the requirement. A single occurrence of a mission limiting

status is not sufficient reason to establish an adjusted stock level but should result in an LRS/materiel management activity review of demand data for accuracy. The using work center, with assistance from LRS/materiel management activity, will prepare the request IAW DAFMAN 23-122 and provide adequate justification (such as, seasonal materiel requirements, long lead-time items, infrequent use components that cause an NMC condition and result in a new procurement or excessive lead-time to restock). Route the request through the applicable Squadron Maintenance Supervision for approval prior to submitting to LRS/materiel management activity. Using work centers will maintain a master file of approved adjusted stock level items and follow-up on all requests until completed. **(T-3)**

9.11. Shelf-life Items. Using work centers will control the quantity and inspect (Type I and Type II) shelf-life items kept in unit bench stock, operating/shop stock, and work order residue IAW DAFMAN 23-122. Personnel managing bench, shop, or operating stocks will:

9.11.1. Identify serviceable shelf-life items/locations with a colored and/or highlighted label that clearly states the items expiration date. **(T-3)**

9.11.2. Check expiration dates on issued items and do not accept outdated items. **(T-3)** Refer to DAFMAN 23-122 for outdated and/or unserviceable shelf-life items.

9.11.3. Not open shelf-life containers until needed and use the oldest items first. **(T-3)**

9.11.4. Ensure shelf-life material stored in other than original containers are marked with original shelf-life expiration codes. **(T-3)**

9.11.5. Recycle, reclaim, or turn-in for disposal, shelf-life items which are loose in the bin and expiration dates cannot be determined. **(T-3)**

9.12. Equipment Items. Flight CCs/SUPTs and/or Section NCOICs/Chiefs will review equipment items needed for mission accomplishment IAW AFI 23-101.

9.12.1. Equipment Custodians will contact the EAE for assistance in researching and preparing documents for gaining authorizations and ordering equipment items IAW AFI 23-101. Refer to DAFMAN 23-122, for the required procedures to order and deploy equipment items.

9.13. Special Purpose Recoverable Authorized Maintenance (SPRAM). SPRAM assets are fault isolation spares, shop standard spares, training spares, -21 TO spares (AME), test station spares, and stand-alone spares. These assets are Expendability, Recoverability, Reparability Code (ERRC) XD/XF items, which are controlled and managed as in-use supplies.

9.13.1. Flight CCs/SUPTs and/or Section NCOICs/Chiefs will review all SPRAM authorizations annually and certify as valid IAW AFI 23-101, DAFMAN 23-122, and DAFI 21- 103. **(T-3)**

9.14. Supply Assets Requiring Functional Check, Calibration, or Operational Flight Programming. Maintenance sections must identify items requiring functional checks, calibration, or operational flight programming prior to use. **(T-3)**

9.14.1. Maintenance sections will prepare a list of items, (including the repair section's organization and shop code) for items requiring functional checks, calibration, or operational flight programming. **(T-3)**

9.14.1.1. The list will be routed through Maintenance Supervision to the LRS. **(T-3)**

9.14.1.2. This list will be updated/validated IAW DAFMAN 23-122. **(T-3)**

9.14.2. The LRS/management materiel activity issues the items to repair sections when assets are initially received on station, when functional checks, calibration, or programming is due or when serviceability is doubtful.

9.14.3. If a Part issue requiring a functional check, ensure it is not restricted in the weapon system -6 TO. Refer to TO 00-20-3 for functional check and frequency requirements.

9.15. Time Compliance Technical Order (TCTO) Kit Procedures. TCTO kit management is a shared responsibility between maintenance and supply IAW TO 00-5-15 and AFI 23-101.

9.15. (AFGSC) Time Compliance Technical Order (TCTO) Kit Procedures. Supply TCTO Kit Monitor will schedule and chair a monthly TCTO kit reconciliation meeting with wing TCTO monitor. **(T-2)**

9.15.1. Initiate requests for kits, parts, and special tool requirements through LRS as outlined in **Chapter 14**.

9.15.2. Transfer TCTO kits with aircraft or equipment. DAFMAN 23-122, TO 00-5-15, and TO 00-5-1 contain detailed guidance for the transfer of TCTO kits.

9.15.3. Retain TCTO kits for aircraft returning to the unit for TCTO compliance.

9.16. Supply Points. Supply points may be established within individual work centers when time or resources required to move items dictates the need to do so.

9.16.1. Storage space for the supply points is provided by the supported work center.

9.16.2. Management of the supply point processes will be agreed to and documented by participating group commanders. **(T-3)** Participating group commanders will require appointment of supply point monitors to manage and account for supply point assets as part of their agreement. **(T-3)** LRS Materiel Management Activities will maintain overall accountability and control of supply point assets. **(T-3)**

9.16.3. Supply points must be reconciled semi-annually by the Supply Point Monitor. **(T-3)**

9.16.3.1. One of the semiannual reconciliations will be done at the same time as the annual supply point inventory IAW AFI 23-101.

9.17. Local Manufacture. Local manufacturing is an essential part of maintenance unit support. The applicable end-item TOs identify items subject to local manufacture and specific procedures for processing are in DAFMAN 23-122.

9.17.1. DELETED.

9.17.2. MXG directive at a minimum will include:

9.17.2.1. Procedures that specify coordination requirements to include QA, EAE, Wing/Base Safety, and endorsement by the approval authority. **(T-3)**

9.17.2.2. DELETED.

9.17.2.3. Identifying drawing, sample, technical data and DD Form 1348-6, *DoD Single Line Item Requisition System Document*, source requirements as required. **(T-3)**

9.17.2.3.1. Ensure guidance identifies that drawings are obtained from the appropriate repository (such as, Engineering Data Service Center or JEDMICS).

9.17.2.4. Establishing coordination process for all the appropriate fabricating sections to determine the bits and pieces required to manufacture the item. **(T-3)**

9.17.2.4.1. Coordinating bit and piece parts requirements and availability with the LRS/DMS.

9.17.2.5. Identifying all work centers that have action on the AFTO Form 350 for items requiring multiple section processing. **(T-3)**

9.18. DIFM Management.

9.18.1. DIFM inputs are critical to recording and getting credit for proper repair cycle times.

9.18.2. DIFM status codes are broken down into three categories: delayed maintenance time, repair time, and AWP time. Repair time is the only time recorded and used to determine the number of assets that should be stocked. Not using the proper codes when they change reduces the number of assets on base.

9.18.3. The roles and responsibilities for DIFM management are identified in AFI 23-101. The LRS/DMS provides the D23 or equivalent to assist each repair section in DIFM Management. The D23 is provided in both maintenance location and stock number sequence. Repair sections use the D23 to manage the flow of serviceable and unserviceable DIFM assets in the repair cycle and to ensure the DIFM status and location is updated.

9.18.3.1. If a parts request is backordered and the removal of the unserviceable DIFM item does not further limit or restrict the operational capability of the end item, it will be removed and sent to the applicable support section for either repair, NRTS approval, or condemnation with a subsequent turn-in to LRS/materiel management activity (as a credit DIFM) IAW TO 00-20-3.

9.18.3.1.1. Repair assets to the fullest extent authorized.

9.18.3.2. Repairable components will be processed, repaired, and returned to the FSC within the required time frame IAW AFI 23-101.

9.18.3.3. The D23 will not be used to manage serviceable assets.

9.18.4. Repair Cycle Throughput. Throughput is the average time it takes to move individual items through the repair cycle. Timelines for turn-in are outlined in AFI 23-101.

9.18.5. Units will establish local procedures for the control of repair cycle assets throughout the maintenance repair cycle IAW AFI 23-101 and DAFMAN 23-122.

9.18.5.1. Procedures will include methods of accounting for all components and accessories, procedures for control of assets in AWP or AWM status, and procedures and responsibilities for cross CANN, removal of bits and pieces, and scheduling and control of repair cycle assets. **(T-3)**

9.18.6. AWP and cross-CANN assets will be controlled and managed IAW DAFMAN 23-122.

9.18.6.1. Maintenance activities will closely control reparable assets in AWP status. **(T-3)**

9.18.7. Maintenance Turn-In to Supply. Maintenance is responsible for DIFM items until the item is returned to LRS/DMS.

9.18.7.1. Work centers must properly tag and secure repair cycle assets and place items in a leak–proof containment liner (no leaks/stains/tears/punctures), as required. **(T-3)**

9.18.7.1.1. To prevent spillage, any item containing any type of residual fluid, regardless of hazard classification, will be drained, purged, preserved, capped, plugged, and placed in a leak-proof containment liner before placement into a serviceable reusable container for storage or shipment. **(T-3)**

9.18.7.1.2. The work center must comply with packaging, environmental control, inert certification, purge, and preservation requirements as specified in applicable TOs, DAFI 24-602V2, DAFMAN 24-604, and place sufficient copy(s) of the technical document(s) for handling, storage, shipping, and distribution of copies inside the container. **(T-3)**

9.18.7.2. Include AFTO Form 350, **Parts I** and **II**, and a condition tag or label with all items turned into supply IAW TO 00-20-3. **(T-3) Note:** Some DIFM assets may require additional tags.

9.18.7.2.1. Enter the correct action taken code on AFTO Form 350, **Part II.**

9.18.7.3. Accomplish proper reclamation and demilitarization actions on condemned repair cycle assets IAW DAFMAN 23-122 and AFH 23-123, Vol. 2, **Part I**, Sec. 6C.

9.18.7.4. DIFM items (serviceable or unserviceable) will be processed and turned in to LRS IAW AFI 23-101.

9.19. Tail Number Bins (TNB).

9.19. (AFGSC) Tail Number Bins (TNB). The designation for AGE due out release items is Hold Bin. **(T-2)**

9.19.1. Establishment and management of TNBs is a shared responsibility between maintenance and supply. TNBs are storage locations established and controlled to store issued parts awaiting installation and parts removed to FOM. TNBs are set up by tail number, serial number, or identification number.

9.19.1. **(AFGSC)** The OPR for TNB inspection/oversight will be determined in writing by MXG/CC and MSG/CC.

9.19.2. TNB items used to satisfy MICAP conditions are not CANNs. If a TNB asset is issued to satisfy a part request, maintenance personnel will:

9.19.2.1. Reorder the item and notify the expediter of the new document number. **(T-3)**

9.19.2.2. Update the aircraft forms and the MIS. **(T-3)**

9.19.2.3. If a due-out is created prior to transfer of these items, notify the LRS/materiel management activity to change the "mark-for" field on the due-out detail. **(T-3)**

9.19.3. Seal and store partially completed TCTO kits and parts in the TNB and mark the container or package with the tail number, serial number, or equipment identification number and TCTO number. **(T-3)**

9.19.4. Maintain security and control of TNB assets. **(T-3)**

9.19.5. Track property placed in the TNB by tail number, serial number, or equipment identification number. Each entry will indicate:

9.19.5.1. Date received. **(T-3)**

9.19.5.2. Noun/nomenclature. **(T-3)**

9.19.5.3. Document number. **(T-3)**

9.19.5.4. Status (FOM, Issue/Due-Out Release (ISU/DOR), TCTO). **(T-3)**

9.19.5.5. Removal information (date, time, signature, and employee number of the person who picked up the property). **(T-3)**

9.19.5.6. Remarks. **(T-3)** Enter "NONE" if no remarks are necessary.

9.19.5.7. Current JCN. **(T-3)**

9.20. CANN Actions. See **Chapter 11** for CANN procedures and responsibilities.

9.21. Bench Check and Repair Policy. Maintenance sections bench check items as part of the off equipment troubleshooting process. When workload requires, the Section NCOIC/Chief determines the priority for bench check actions. Specific procedures for bench check and repair policy are provided in TO 00-20-3. The following general guidelines apply:

9.21.1. Order required parts "fill or kill."

9.21.1.1. If the part is not in stock and a MICAP condition exists, backorder the new request.

9.21.1.2. Determine local repair capability before requisitioning off-base support or going lateral support.

9.21.2. Remove the suspected item, fill out the AFTO Form 350, and annotate it as repair and return. Attach AFTO Form 350 to the item; place the item in the repair cycle; and annotate the name of the repair section on the form.

9.21.3. Bench-check, repair, take NRTS action, or condemn the item.

9.21.3.1. If the item is repaired or otherwise determined to be serviceable, the repair section informs the Support Section the item is available for pick-up so on-equipment maintenance action may resume.

9.21.3.2. If the item cannot be repaired, the repair section informs the Support Section to initiate a backordered request and takes appropriate NRTS and condemnation action on the unserviceable asset.

9.22. Maintenance Turn-Around Record Update Processing. Work centers processing TRNs will coordinate with LRS/DMS and follow requirements outlined in AFI 23-101, DAFMAN 23-122, and AFH 23-123.

9.23. Buildup Items. Maintain items requiring build-up prior to use (such as, wheels and tires) in supply points in a built-up configuration.

9.23.1. Send items to appropriate work centers for build-up and return them to the supply point for re-issue.

9.23.1.1. Use AF Form 1297 or control log to control assets sent for build-up when the supply point is operated by other than maintenance personnel.

9.23.1.2. Validate AF Form 1297 daily if over 10 days old.

9.23.2. Local procedures will be established to control assets when maintenance operates the supply point and assets are sent to another organization for build-up. **(T-3)**

9.24. DR Exhibits. DR exhibit procedures for issue, turn-in, and storage are contained in TO 00-35D-54 and AFI 23-101. DRs will be input into the JDRS at **https://jdrs.mil.**

9.25. Destruction of TOP SECRET Material. Destruction of TOP SECRET material requires a receipt according to DODM 5200.01, Vol 3, DOD Information Security Program: Protection of Classified Information and AFI 16-1404. A copy of the destruction certificate will be included with the turn-in documentation. **(T-0)**

9.25.1. Provide sensitive instruments interior container protection. **(T-3)**

9.25.2. Ensure a copy of the LRU/SRU historical record accompanies turn-in of all items. **(T-3)**

9.26. Certifying Items Associated With Explosives. Ensure items such as MERS, TERS, pylons, launchers, rafts, bomb racks, ejection seats, fire suppression bottles, gun systems and components are certified explosive-free prior to turn-in to LRS and/or Defense Logistics Agency (DLA) Disposition Services. **(T-3)** Refer to TO 11A-1-60 and DAFMAN 21-201 for specific certification requirements.

Chapter 10

MUNITIONS POLICY AND WEAPONS LOAD CREW PROGRAM

10.1. See AFMAN 21-206 for Munitions Policy and Weapons Load Crew Program.

10.1. (AFGSC) See AFMAN 21-206 for Munitions Policy and Weapons Load Crew Program. See DAFMAN 21-201, 21-200, and DoDM 5100.76 for Conventional Munitions policy and requirements. AFGSC/A4WC is the OPR for all policy, QA and requirements for all conventional munitions under 21-101, 21-200, and 21-201.

10.1.1. - **Table 10.3**. DELETED.

Chapter 11

ADDITIONAL MAINTENANCE REQUIREMENTS AND PROGRAMS

11.1. Facility Housekeeping and Contamination Control. Units will publish housekeeping and contamination procedures which protect the health of workers and maintain areas as free as practical from surface contamination. **(T-3)** Units will:

11.1.1. Ensure Bioenvironmental Engineering approved workplace-housekeeping procedures are employed to prevent the spread of contamination within a work center. **(T-3)**

11.1.2. Emphasize controlling the source of the contamination and ensure workplace personnel follow proper work procedures, PPE use, and hygiene practices. **(T-3)**

11.1.3. Ensure housekeeping procedures will account for the dangers and hazard exposures found in the work center and will be consistent with mitigation methods outlined in DAFMAN 91-203. **(T-3)**

11.2. Personal Wireless Communications Systems Management.

11.2.1. Maintenance Communications. Reliable, redundant, cyber resilient, and effective communications systems are essential for efficient maintenance operations. These systems will provide accurate, timely, secure, programmable frequency and jam resistant communications needed to securely accomplish the maintenance mission in a fully deployed and isolated mode.

11.2.2. Commanders or designated representative will coordinate base Communication Squadron or equivalent to ensure compliance with Personal Wireless Communications Systems management requirements IAW AFI 17-210, DAFI 17-220, *Spectrum Management*, AFI 17-130, and DAFMAN 17-1203. The following general guidelines apply:

11.2.2.1. Allowance for specific radios is shown in AS 660, *Equipment Allowances for Non-Weapon Systems Communications Requirements*, Repair Cycle Data Listing. Process requests for specific radio equipment to support maintenance activities IAW AFI 23-101, AFI 17-210, DAFI 17-220, AFI 17-130, and AFH 23-123 V3, *Air Force Equipment Management*.

11.2.3. A VHF/UHF radio is authorized for use in maintenance operations to facilitate communications between aircraft and maintenance personnel. Additionally, aircrews may relay advance aircraft status information to maintenance personnel using VHF/UHF channels.

11.2.3.1. Maintenance Operations will coordinate procedures for use of these radio communications with operations and other essential wing organizations. **(T-3)**

11.2.3.2. For effective flightline operations, more than one non-tactical radio nets are authorized when large numbers or different types of weapon systems are assigned or when Allowance Standards specify.

11.3. MAJCOM/ANG Special Certification Rosters (SCR). The SCR is a management tool providing supervisors a clear and concise listing of personnel who have been appointed to perform, evaluate, and/or inspect work of a critical nature. Normally, only maintenance requirements that have a definite potential for personal injury or damage to equipment will be included in the SCR. Other tasks requiring special training or qualifications may be managed on the SCR. The SCR is used to build personnel rosters for deployments, shift schedules, and assess workforce capability.

AF/A4LM establishes mandatory SCR Item Titles in Column A of **Table 11.1**. Based on the evolving complexity of weapon systems and the associated task diversity the process of assigning prerequisite to SCR tasks are assigned to using MAJCOMs/ANG as follows: MAJCOMs/ANG A4s will coordinate with their applicable Lead Commands to develop and document SCR item "Prerequisite" criteria in Column B of **Table 11.1** based on task complexity of their assigned weapons systems. MAJCOMs/ANG may add additional items and remove non-applicable Items on their SCR using the standardized **Table 11.1** format provided. MAJCOM/ANG Supplements must include their complete SCR table when coordinating supplement approval with AF/A4LM as described in the opening **Paragraph** of this DAFI. Special Certification approval authority will be accomplished IAW notes at the bottom of the SCR. The MXG/CC and CD are not required to be on the SCR by virtue of their position as the SCR approval authority.

11.3.1. DELETED.

11.3.1.1. Squadron Maintenance Supervision approves individuals in their primary AFSC based on their experience and technical expertise regardless of their assigned skill or position. **(T-3)**

11.3.1.2. MXG/SEL will review and sign SCR actions for those individuals administratively assigned to MXO (QA, AFREP). **(T-3)**

11.3.1.2.1. MXG/SEL will coordinate with the Field Training Detachment (TD) CC/SUPT to validate currency of Field TD personnel on the SCR. **(T-3)**

11.3.1.3. WWM will review and sign WS SCRs. **(T-3)**

11.3.1.4. **(Added-AFGSC)** The SCR will be reviewed and signed semi-annually by the DO/SEL or equivalents to verify all entries/task certifications are current and accurate.

11.3.2. TFI units will establish a process for approving SCR additions in a MOA/MOU to provide visibility across participating organizations. **(T-3)**

11.3.3. The MXG/CC may waive selected 5-skill level personnel, in the rank of SrA or higher, for tasks normally requiring a 7-skill level requirement to facilitate the production effort. Waived 5-skill level personnel should be closely monitored and kept to the minimum required to accomplish mission generation.

11.3.3.1. Maintenance Supervision or equivalent will retain file copies of approved waivers. **(T-3)**

11.3.3.1.1. Approved waiver file copies may be discarded if SCR specifically identifies task as waived in the Maintenance Information System.

11.3.3.2. Certified weapons load crew chiefs (load crew member position number 1) by virtue of their task certification and position, serve as inspectors for weapons loading tasks only and do not require a waiver. **Note:** 2W0XX certified munitions inspectors are exempt from these requirements.

11.3.4. MAJCOM Waiver Policy. If local conditions require assignment of other than MAJCOM approved mandatory SCR grade (to include civilian equivalents) and skill level prerequisite requirements and cannot be fulfilled using the MXG/CC authority stated in **Paragraph 11.3.3** then the MXG/CC (or equivalent) must request a waiver from the MAJCOM. **(T-3)**

11.3.5. MAJCOMs may add additional mandatory critical tasks or inspections they deem necessary.

11.3.5.1. Identify each task on the SCR by a specific course code.

11.3.6. SCR Documentation. Flight CCs/SUPTs and Section NCOICs/Chiefs will review each individual's qualifications prior to recommending approval to perform SCR tasks to the appropriate approval level. **(T-3)**

11.3.6.1. AF Form 2426, *Training Request and Completion* or MAJCOM-approved (ANG locally approved) form is used by the work center supervisor to add or remove an individual to the SCR. Additionally, removal from the SCR may be accomplished by lining through the task on the SCR and notifying the training section to update the MIS.

11.3.6.1. **(AFGSC)** Use AFGSC Form 64, *Request for Special Certification*, to add personnel to the SCR. Use of an electronic AFGSC Form 64 is authorized. **(T-2)**

11.3.6.2. The appropriate level of authority approves the individual for addition to the SCR as listed in **Table 11.1**.

11.3.6.3. On approval, the UTM IAW AFI 36-2650, loads the approved name into the Maintenance Information System.

11.3.6.4. Flight CCs/SUPTs and Section NCOICs/Chiefs will retain their copy of AF Form 2426 or MAJCOM-approved form until they verify proper loading. **(T-3)**

11.3.6.5. Appointment letters are not required if loaded in the MIS.

11.3.6.6. Work center supervisor, AMU/Flight supervision, Maintenance Supervision, SQ/ CC, or MXG/CC may decertify individuals at any time and remove them from the SCR.

11.3.7. Units will ensure a current copy of the SCR is taken on all deployments. **(T-3)**

11.3.7. **(AFGSC)** For civilian equivalents addressed in **Table 11.1** refer to **Table 2.1**.

Table 11.1. Mandatory Special Certification Roster and Prerequisites.

	A	B
ITEM	**Mandatory SCR Item Titles**	**MAJCOM/ANG Prerequisites**
1	All Systems “Red-X” (no egress, welding, munitions, fuel cell (in-tank work)) (Note 1)	Refer to MAJCOM Supplement
2	Exceptional Release (ER) (Note 1)	Refer to MAJCOM Supplement
3	“Red-X” Downgrade (Note 1)	Refer to MAJCOM Supplement
4	All Systems In Process Inspection (no egress, welding, munitions, fuel cell in-tank work) (Note 1)	Refer to MAJCOM Supplement
5	Installed Engine Run Certifying Officials (Note 1)	Refer to MAJCOM Supplement
6	Aircraft Inlet/Intake/Exhaust Certifying Officials (Note 1)	Refer to MAJCOM Supplement
7	Flexible Borescope Certifying Officials (Note 1)	Refer to MAJCOM Supplement
8	Engine Blade Blending Certifying Officials (Note 1)	Refer to MAJCOM Supplement
*9	“Red-X” by Mission Design Series (Notes 2 and 6)	Refer to MAJCOM Supplement
*10	IPI by Mission Design Series (Notes 2 and 6)	Refer to MAJCOM Supplement
11	“Red-X” and/or In Process Inspection - Limited (Note 2)	Refer to MAJCOM Supplement
*12	DELETED.	DELETED.
13	NWRM packaging (Notes 4 and 5)	Refer to MAJCOM Supplement
14	Installed Engine Run by Mission Design Series (Note 2)	Refer to MAJCOM Supplement
15	Engine Blade Blending	Refer to MAJCOM Supplement
16	QA hot pit certifying officials and QA hot pit certifier augmentees (squadron certifying officials) (Note 1)	Refer to MAJCOM Supplement
17	Hot Refueling PAD Supervisor/"A" Member (Note 2)	Refer to MAJCOM Supplement
18	Hot Refueling Team Member (“B” or “D” member) (Note 2)	Refer to MAJCOM Supplement
19	Aircraft to Aircraft Refueling Supervisor (Note 2)	Refer to MAJCOM Supplement

20	Uninstalled Engine Operations (Test Stand and ETS) Run by TMS (Note 2)	Refer to MAJCOM Supplement
21	Uninstalled Engine Run Certifying Officials by TMS (Note 1)	Refer to MAJCOM Supplement
22	Aircraft Inlet/Intake/Exhaust Inspection/Certification (Note 2)	Refer to MAJCOM Supplement
23	Engine Flexible Borescope Inspections (Note 2)	Refer to MAJCOM Supplement
24	Chief Servicing Supervisor (Heavy Aircraft/Commercial Derivative Aircraft) (Note 2)	Refer to MAJCOM Supplement
*25	Concurrent Servicing Supervisor/Aircraft Turnaround Supervisor (Fighter Aircraft) (Note 2)	Refer to MAJCOM Supplement
26	W&B Certified/Clear Red X (refer to TO 1-1B-50) (Note 2)	Refer to MAJCOM Supplement
27	Impoundment Official (refer to **Chapter 7**) (Note 2)	Refer to MAJCOM Supplement
*28	Impoundment Authority (refer to **Chapter 7** of this DAFI) (Note 1)	Refer to MAJCOM Supplement
29	CANN Authority (Note 1)	Refer to MAJCOM Supplement
30	Auxiliary Power Unit (APU) Operation (In Cockpit) (Note 2)	Refer to MAJCOM Supplement
*31	Calibration Limitation Approval (refer to TO 00-20-14) (Notes 2)	Refer to MAJCOM Supplement
32	CDDAR Team Chief (Note 1)	Refer to MAJCOM Supplement
33	Weapons Task Qualification Manager (WTQM) (Note 1)	Refer to MAJCOM Supplement
34	Weapons Task Qualification Crew (WTQC) (Note 2)	Refer to MAJCOM Supplement
35	NSS and T-9/T-10/T-11/T-12/T-20 sound suppressor Fire Control Panel (Note 2)	Refer to MAJCOM Supplement
36	Aircraft Rapid/Hot Defueling Supervisor (Note 2)	Refer to MAJCOM Supplement
37	Clear Red X when a lost item/tool cannot be located (refer to **Chapter 8**) (Note 1)	Refer to MAJCOM Supplement
38	Aircraft APU Run Certifying Officials (In Cockpit) (Note 1)	Refer to MAJCOM Supplement

Notes:
1. Approved by MXG/CC or equivalent may be delegated IAW **Paragraph 2.4.2.27.**
*2. Approved by Maintenance Supervision or equivalents. May delegate approval authority to the OIC/SUPT or Flight CC/SUPT.
*3. DELETED.
4. Munitions inspectors who are trained and certified may annotate serviceability tags for munitions items (TO 11A-1-10).
5. Appointed by the unit commander (or equivalent) of units possessing NWRM.
6. MAJCOMs determine the AFSC applicability.

Table 11.1. (AFGSC) Mandatory Special Certification Roster and Prerequisites.

	A	**B**
ITEM	**Mandatory SCR Item Titles**	**AFGSC Prerequisites**
1	All Systems "Red-X" (no egress, welding, munitions, fuel cell (in-tank work)) (Note: 1)	MSgt or higher (or civilian equivalent).
2	Exceptional Release (ER) (Note: 1)	MSgt or higher (or civilian equivalent). MSgt or higher (or civilian equivalent), or a fully qualified/certified contractor or AFETS/CETS representative and possess one of the following AFSCs: 2A671, 2A571/2/4, and 2A373/7/8. One year minimum engine-run experience on applicable MDS (not applicable at short tour locations). MXG/CC may waive qualified TSgts. MAJCOMs will determine and document AFSC and skill level requirements for 5th Generation aircraft.
3	"Red-X" Downgrade (Note: 1)	
4	All Systems In Process Inspection (no egress, welding, munitions, fuel cell in-tank work) (Note: 1)	
5	Installed Engine Run Certifying Officials (Note: 1)	
6	Aircraft Inlet/Intake/Exhaust Certifying Officials (Note: 1)	Qualified/certified 7 or 9-skill level (or civilian equivalent), or a fully qualified/certified contractor, AFETS or CETS representative and possess one of the following AFSCs: 2A6X1, 2A5X1/2/4, 2A3X3/8. One year of minimum experience on applicable MDS/TMS (not applicable at short tour locations). MAJCOMs will determine and document AFSC and skill level requirements for 5th Generation aircraft.

	A	B
ITEM	**Mandatory SCR Item Titles**	**AFGSC Prerequisites**
7	Flexible Borescope Certifying Officials (Note: 1)	Qualified/certified 7 or 9-skill level (or civilian equivalent), or a fully qualified/certified contractor, AFETS or CETS representative and possess one of the following AFSCs: 2A6X1, 2A5X1/2/4, 2A3X3/8. One year of minimum experience on applicable MDS/TMS (not applicable at short tour locations). MAJCOMs will determine and document AFSC and skill level requirements for 5th Generation aircraft.
8	Engine Blade Blending Certifying Officials (Note: 1)	
9	"Red-X" by Primary AFSC (PAFSC) and Mission Design Series (For multiple Mission Design Series, list separately) (Note: 2)	SSgt or higher, minimum 7-skill level (or civilian equivalent). Includes MXG/CC- appointed exceptional SrA per **paragraph 11.3.3.**
10	IPI by PAFSC and Mission Design Series (For multiple Mission Design Series, list separately) (Note: 2)	SSgt or higher, minimum 7-skill level (or civilian equivalent). Includes MXG/CC- appointed exceptional SrA per **paragraph 11.3.3.**
11	"Red-X" and/or In Process Inspection - Limited (Note: 2)	5-skill level (or civilian equivalent) personnel certified on limited tasks as determined by the unit **in writing**. 5-skill level Certified Weapons Load Crew Chiefs (or civilian equivalent) on loading tasks only.
12	"Red-X" and/or In Process Inspection - Cross Utilization Training (For multiple MDSs, list separately), for tasks outside PAFSC (Note: 2)	SSgt or higher, minimum 7-skill level (or civilian equivalent), Use for personnel certified on tasks in other AFSCs through CUT training.
13	NWRM packaging (Notes: 4 and 5)	Minimum 7-skill level (or civilian equivalent). Must have sufficient subject matter expertise of packaged item to identify asset, must be tasked qualified on accompanying documentation and must have

	A	B
ITEM	**Mandatory SCR Item Titles**	**AFGSC Prerequisites**
		appropriate security clearance and background investigation for asset.
14	Installed Engine Run by Mission Design Series (Note: 2)	SrA or higher, minimum 5-skill level (or civilian equivalent), with at least 6 consecutive months of experience on MDS for which engine run training is required. (Experience must have occurred immediately prior to course enrollment). The MXG/CC may waive the weapons system experience. MXG/CCs may waive qualified 5-skill level A1C (or civilian equivalent) for critical manpower shortages. The time on the weapon system may also be waived by MXG/CC.
15	Engine Blade Blending (Note: 2)	Minimum 5-skill level or civilian equivalent. MAJCOMs will determine and document AFSC and skill level requirements for personnel performing blade blending on 5th Generation aircraft.
16	QA hot pit certifying officials and QA hot pit certifier augmentees (squadron certifying officials) (Note: 1)	TSgt or higher (or civilian equivalent) MXG/CC may waive grade requirement.
17	Hot Refueling PAD Supervisor/"A" Member (Note: 2)	Minimum 5-skill level, 2AX5X (or civilian equivalent), with a minimum of one year of weapons system experience.
18	Hot Refueling Team Member (“B” or “D” member) (Note: 2)	Flightline maintenance AFSC (or civilian equivalent), with a minimum of one year of weapons system experience.
19	Aircraft to Aircraft Refueling Supervisor (Note: 2)	Minimum 5-skill level (or civilian equivalent) with a minimum of 1 year weapon system experience.
20	Uninstalled Engine Operations (Test Stand and ETS) Run by TMS (Note: 2)	SSgt or higher 7-skill level 2A6X1 (or civilian equivalent) with a minimum of 6 months current experience on each applicable TMS, unless previously qualified (N/A to short tour assignments). If previously qualified on a different

	A	B
ITEM	**Mandatory SCR Item Titles**	**AFGSC Prerequisites**
		TMS, the 6-month experience requirement may also be waived. MXG/CC may waive 5-skill level SrA (or civilian equivalent) with a minimum of 6 months' time on applicable TMS.
21	Uninstalled Engine Run Certifying Officials by TMS (Note: 1)	Fully qualified/certified TSgt or higher 2A671 AFSC, civilian equivalent, contractor, or AFETS/CETS personnel with a minimum of one year engine run experience on the applicable TMS. (One year run experience not applicable to short tour assignments). The MXG/CC may waive qualified SSgts and may authorize MT uninstalled engine run instructors as certifying officials.
22	Aircraft Inlet/Intake/Exhaust Inspection/Certification (Note: 2)	SrA or higher, minimum 5-skill level (or civilian equivalent). MAJCOMs will determine and document AFSC and skill level requirements for 5th Generation aircraft.
23	Engine Flexible Borescope Inspections (Note: 2)	Minimum 5-skill level 2A3X3/8, 2A5X1/2/4, and 2A6X1 (or civilian equivalent). MAJCOMs will determine and document AFSC and skill level requirements for 5th Generation aircraft.
24	Chief Servicing Supervisor (Heavy Aircraft/Commercial Derivative Aircraft) (Note: 2)	Minimum 5-skill level (or civilian equivalent) with one year of weapons system experience. Time requirement may be waived by MXG/CC in short tour/enroute locations.
25	Concurrent Servicing Supervisor (Fighter Aircraft) (Note: 2)	Not applicable for AFGSC aircraft.
26	W&B Certified/Clear Red X (refer to TO 1–1B-50) (Note: 2)	7-skill level (or civilian equivalent), with a minimum of one year time on the weapon system. Time requirement may be waived by MXG/CC.

	A	B
ITEM	**Mandatory SCR Item Titles**	**AFGSC Prerequisites**
27	Impoundment Official	MSgt or higher (or civilian equivalent). (refer to Chapter 7 of this DAFI). (Note: 2)
28	Impoundment Authority	MSgt or higher (or civilian equivalent). (refer to Chapter 7 of this DAFI). (Note: 1)
29	CANN Authority (Note: 1)	MSgt or higher, minimum 7-level (or civilian equivalent) (refer to Chapter 11).
30	Auxiliary Power Unit (APU) Operation (In Cockpit) (Note: 2)	3-skill level or higher maintenance AFSC.
31	Calibration Limitation Approval (refer to TO 00-20-14) (Notes: 2 and 3)	SSgt or higher, minimum 7-skill level (or civilian equivalent).
32	CDDAR Team Chief (Note 1)	MSgt or higher (or civilian equivalent). MXG/CC may waive grade requirement.
33	Weapons Task Qualification Manager (WTQM) (Note: 1)	TSgt or higher, minimum 7-skill level AFSC 2A871X or 2AX7X (or civilian equivalent).
34	Weapons Task Qualification Crew (WTQC) (Note: 2)	Lead will be SSgt or higher, minimum 7- skill level 2AX7X (or civilian equivalent); other crew members minimum 5-skill level 2AX5X (or civilian equivalent).
35	NSS and T-9/T-10/T-11 /T-12/T-20 sound suppressor Fire Control Panel (Note 2)	SrA or higher, (or civilian equivalent) with AFSC 2A6X1 must have a minimum of 6 months experience.
36	Aircraft Rapid/Hot Defueling Supervisor (Note: 2)	Minimum 5-skill level (or civilian equivalent), one year of weapons system, with 6 months weapon system experience.
37	Clear Red-X when a lost item/tool cannot be located (refer to Chapter 8 of this instruction) (Note 1)	DO/MX SUPT or above.
38	Aircraft APU Run Certifying Officials (In Cockpit) (Note: 1)	7-skill level (or civilian equivalent), or a fully qualified/certified contractor or AFETS/CETS representative. MXG/CCs may also waive qualified 5-skill level SSgts.
39	Tow Team Supervisor	SSgt or higher, minimum 5 Skill level AFSC 2AXXX (or civilian equivalent) with a minimum of 6

	A	B
ITEM	**Mandatory SCR Item Titles**	**AFGSC Prerequisites**
		months weapons systems experience (**Note:** 2) or SrA (or civilian equivalent) with one year weapons systems experience. (**Note:** 1)
40	MICAP Approval	MSgt or higher, minimum 7-level (or civilian equivalent) (**Note:** 2)
41	NRTS and Serviceability Tag	SSgt or higher, minimum 7-level (or civilian equivalent). (Notes: 2, 3, and 4). Includes MXG/CC-appointed exceptional SrA per **paragraph 11.3.3.**
42	Jacking supervisor	SSgt or higher, minimum 5-skill level (or civilian equivalent), and one year of weapons system experience. (**Note:** 2)
43	Gear Retraction supervisor (This person is the only individual that can authorize gear handle movement)	SSgt or higher, minimum 5 skill level (or civilian equivalent), and one year of weapons system experience. (**Note:** 2)
44	Sole Vouching Authority (SVA)	AFSC 2AXXX, minimum 5-skill level (or civilian equivalent), one year of flightline experience, with 6 months of weapon system experience. (Note 2)
Notes:		
1----Approved by MXG/CC or equivalent may be delegated IAW **paragraph 2.4.2.32.**		
2----Approved by DO/SEL or equivalents		
3---- DO/SEL may delegate approval authority to the Sortie Generation Flight Commanders (SGF CC) and Sortie Generation Flight Chiefs (SGF Chief).		
4----Munitions inspectors who are trained and certified may annotate serviceability tags for munitions items (TO 11A-1-10, Air Force Munitions Surveillance Program and Serviceability Procedures).		
5----Appointed by the Unit Commander (or equivalent) of units possessing NWRM.		

11.4. Aircraft Grounding.

11.4.1. Aircraft grounding is defined in DAFMAN 11-401, *Aviation Management*.

11.4.1.1. Communication of a grounding, or a potential grounding event (TCTO, OTI, PM event) to weapon systems operating in a deployed environment and/or under the authority of an operational command must follow the grounding procedures outlined in DAFMAN 11-401 and 63-101/20-101.

11.4.1.1.1. Units must not directly communicate home station requirements to its deployed forces but provide communication through their respective MAJCOM. **(T-2)** **Note:** This section does not apply to conditions which are clearly limited to the affected unit/base (such as, lost tool, fluid contamination, aircraft and equipment damage of known origin, or other strictly local event). In these circumstances, the affected unit follows the impoundment procedures specified in **Chapter 7**.

11.4.2. Initial Investigation.

11.4.2.1. The OTI will require an inspection of a representative number of systems or units (aircraft, engines, missiles, or munitions) of the same mission and design to determine if the condition exists on other aerospace equipment within the wing's assigned aircraft/systems or equipment. **(T-2)**

11.4.2.1.1. If initial sampling indicates the discrepancy is widespread and has the potential for personal injury and/or further equipment damage, wings will coordinate with MAJCOM. **(T-2)**

11.4.2.2. If there is no repair or corrective action specified in technical data, QA will also submit a technical assistance request through the MAJCOM to the appropriate weapon system program manager IAW TO 00-25-107 or equivalent process. **(T-2)**

11.4.3. Grounding Authority. The approved procedures for grounding aircraft or stand-down for operational reasons are determined and executed IAW DAFMAN 11-401.

11.4.3.1. Notification and final reporting for grounding and release status will be accomplished IAW AFMAN 10-206, *Operational Reporting (OPREP)*.

11.4.3.2. Annotate aircraft grounding in the aircraft forms IAW TO 00-20-1.

11.5. Ramp Inspection Program. Public Law 99-661, section 2638, National Defense Authorization Act for Fiscal Year 198 requires a pre-flight safety inspection of all internationally scheduled charter missions for the transportation of members of the Armed Forces departing the United States. **(T-0)**

11.5.1. Air Mobility Command (AMC) is lead for the DoD in the management and administration of the Ramp Inspection Program.

11.5.1.1. AMC will publish specific guidance for this Program in a supplement/addendum/or equivalent publication IAW DAFMAN 90-161 to communicate requirements and processes necessary for MAJCOMS to effectively comply with public law requirements in all using commands.

11.5.1.2. AMC will coordinate with other MAJCOMs as required to accomplish ramp inspections to ensure the maximum efficiency and utilization of resources.

11.5.1.3. When requested by AMC, MAJCOMs if able should provide support to reduce the TDY and manpower impact associated with the execution of this program.

11.6. Red Ball Maintenance. The term "Red Ball" is a traditional descriptor, recognized throughout aircraft maintenance, and defines a situation requiring a sense of urgency and priority actions. Red Ball maintenance normally occurs two hours prior to launch and until aircrew have released the aircraft back to maintenance. The Red Ball maintenance concept is intended to prevent late takeoffs and aborts by having qualified maintenance personnel available (such as, in a truck

or standby in the shop) during launch and recovery operations to troubleshoot, isolate, and repair system malfunctions. Red Ball maintenance does not authorize technicians to take shortcuts or deviate from TOs, disregard personnel safety requirements or fail to properly document the aircraft forms and the MIS for all completed repair actions.

11.6.1. Units will ensure all maintenance repair actions (does not apply to incorrect switch settings due to operator error) are documented in the aircraft forms and MIS during Red Ball, launch, or EOR operations and cleared from the aircraft forms prior to flight. **(T-3)**

11.6.2. Maintenance repair actions must be cleared in the MIS as soon as possible. **(T-3)** It is imperative that maintenance documentation is performed regardless of the timing of the action in the generation and launching of the aircraft.

11.6.3. All grounding inputs must be cleared from the forms prior to flight. **(T-3)**

11.6.4. If aircraft status changes, an ER must be re-accomplished by a certified individual upon completion of maintenance and before the aircraft is released for flight IAW TO 00-20-1.

11.6.5. Units will develop written procedures to capture, document, and clear Red Ball maintenance actions in the event the MIS is down. **(T-3)**

11.6.5.1. Procedures must require MIS entry of Red Ball maintenance actions as soon as the MIS becomes operable. **(T-3)**

11.7. Maintenance Recovery Team. MAJCOMs will publish standardized procedures to recover assigned aircraft at remote locations.

11.7.1. Procedures at a minimum will identify how resources, including personnel, supplies, and equipment will be made available to support transient aircraft recovery.

11.7.1. **(AFGSC)** At a minimum, MXG/CC (or equivalent) will ensure the following Maintenance Recovery Team (MRT) procedures are accomplished: **(T-2)**

11.7.1.1. **(Added-AFGSC)** MXG/CC, or designated representative, will appoint an MRT POC. **(T-2)**

11.7.1.1.1. **(Added-AFGSC)** MRT POC should use **Attachment 8**, MRT Tasking Checklist as a starting point for planning**. (T-2)**

11.7.1.2. **(Added-AFGSC)** MRT Chief should reference responsibilities outlined in **Attachment 9** and **Attachment 10**, MRT Chief Tasking Checklist as a planning guide. **(T-2)**

11.7.1.3. **(Added-AFGSC)** Ensure the MOC is informed of personnel and equipment deployed on MRT and status of the recovery. **(T-2)**

11.7.1.4. **(Added-AFGSC)** Ensure applicable WST (AFGSC/A4A or A4B) is notified of stranded aircraft. **(T-2)**

11.7.1.5. **(Added-AFGSC)** Request MRT through 608th Air Operations Center and AFSTRAT/A4. 608 AOC and AFSTRAT will coordinate support through home station wings or nearest capable base with repair capability. Contact 608 AOC by DSN: 781-0608 or Comm: 318-456-0608 and email AFSTRAT at NIPR Workflow: **8AF.LG@us.af.mil**

or SIPR Workflow: usaf.barksdale.afgsc.mbx.jgsoc-afstrat-a4-mailbox@mail.smil.mil.

11.7.1.6. **(Added-AFGSC)** MOC will notify MXG/CC or designated representative regarding MRT request/approval. **(T-2)**

11.7.1.6.1. **(Added-AFGSC)** MXG/CC, or representative, is responsible for tasked MRTs and equipment to recover aircraft at off-station locations when directed. Unit resources, including personnel, supplies, and equipment will be made available as tasked to support aircraft recoveries, regardless of aircraft ownership. **(T-2)**

11.7.2. If required, establish multiple command MOUs/MOAs/collaboration necessary to achieve efficient aircraft recovery and MIS documentation.

11.8. Foreign Object Damage (FOD) Prevention Program. All personnel (military, civilian, and contractors) working in, on, around, or traveling through areas near aircraft, flightline munitions, AGE, engines, or components thereof will comply with FOD prevention. **(T-2)** FOD prevention training requirements are outlined in AFI 36-2650. This section establishes minimum requirements for a FOD Prevention Program.

11.8.1. The WG/CD is responsible for ensuring an effective FOD prevention program is established.

11.8.2. Definition. FOD: Any damage to an aircraft, engine, aircraft system, component, tire, munitions, or SE caused by a foreign object(s) (FO) which may or may not degrade the required safety and/or operational characteristics of the aforementioned items.

11.8.2.1. **(Added-AFGSC)** Domestic Object Damage: Any damage to an aircraft engine, aircraft system or equipment caused by internal failure of a component. **(T-2)**

11.8.3. FOD Prevention.

11.8.3.1. On aircraft, uninstalled engines, LRUs and AGE. Openings, ports, lines, hoses, electrical connections, and ducts will be properly plugged or capped to prevent FO from entering the systems. **(T-2) Note:** Do NOT place items (such as, trash bags, rags, cloths) inside open cavities or ducts. When no approved manufactured coverings and/or caps are available for use, securely cover open ducts and/or cavities externally to prevent foreign objects from being introduced. Prior to installation, inspect openings, cavities, and ducts for FO.

11.8.3.1.1. Items that are actively being disconnected, installed, and/or removed will be capped IAW technical data or at completion of the task. **(T-2)**

11.8.3.1.2. At no time will items, (such as, aircraft forms binders, video tape recorder tapes, checklists, tools.), be placed in or on engine intakes. **(T-2) Note:** Does not apply to technicians performing inlet maintenance, inspections and blade blending requiring lights, files, or other tools inside aircraft inlets.

11.8.3.1.3. Inventory all items IAW **Chapter 8**. **(T-2)**

11.8.3.2. MAJCOMs in coordination with Safety, applicable MDS Lead Commands and Weapon System Teams will review FOD, Incident, and Mishap reports to determine if MAJCOM directed IPI or KTL additions are needed to mitigate identified FOD trends.

11.8.3.2.1. Units will establish MDS specific procedures that ensure pre-launch removal and post-recovery installation of intake/inlet plugs and covers (such as, pitot tubes to include ejection seats as required) remain installed on aircraft as close to crew show as possible to prevent FOD, as determined by MXG/CC guidance. **(T-3)**

11.8.3.2.2. Units will establish MDS specific FOD prevention guidance that standardizes mitigation procedures when performing high FOD risk maintenance task (use of plugs/barrier paper, tape, inlet/intake/ECS maintenance or equivalent tasks). **(T-2)**

11.8.3.2.3. Technicians will ensure engine inlet run-up screens and anti-personnel guards are used IAW applicable weapon system TOs. **(T-2)**

11.8.3.3. Covers (such as, engine, pitot tube(s) to include ejection seat) need to remain installed on aircraft as close to crew show as possible to prevent FOD, as determined by MDS/local MXG/CC guidance.

11.8.3.4. Technicians should use a light source of sufficient illumination to inspect the aircraft intakes and exhaust for FO/FOD.

11.8.3.5. Whenever physical entry into an aircraft intake or exhaust is required, technicians will wear a pocket-less, zipper-less, button-less, bunny-suit marked "Intakes Only" and cloth over-booties or stocking feet, (Boots may be worn if not restricted for use by TO/MAJCOM and are authorized by the MXG or equivalent), boots if worn must be inspected and FOD removed from boots prior to installing cloth over-booties. **(T-2)**

11.8.3.5.1. When performing intake inspections while wearing a Chemical Warfare Defense Equipment, pockets will be emptied, and all accessories removed. **(T-2)**

11.8.3.5.1.1. During exercises/inspections, the Chemical Warfare Defense Equipment will be removed, and the bunny-suit will be utilized. **(T-2)**

11.8.3.5.1.2. Chemical Warfare Defense Equipment will only be worn during “real world” situations. **(T-2)** To minimize the potential for FOD and intake damage where Chemical Warfare Defense Equipment zippers are exposed, cover them with any type of tape and account for the tape upon completion of the inspection. **(T-2)**

11.8.3.6. Each base will develop a local flightline clothing policy that addresses wearing of hats, badges, and passes aimed at FOD prevention while considering climate and safety. **(T-2)** As a minimum, it will include the following requirements:

11.8.3.6.1. Restricted area badges will be secured with a subdued non-metallic cord or plastic armband when worn on the flightline. **(T-2)**

11.8.3.6.2. Restricted area badges will be removed when performing intake/inlet/exhaust inspections if personnel physically enter these areas. **(T-2)**

11.8.3.6.3. Metal insignias/badges will not be worn on the flightline. **(T-2)**

11.8.3.6.3.1. **(Added-AFGSC)** Remove or stow restricted area badge within 25 feet of operating engine(s). Ensure line badge clips are secured to prevent loss. For those individuals using the cord/rope for security, pass the cord/rope through the clip eyelet. It is recommended to remove clip eyelets from line badge holders. **(T-2)** **Exception:** Restricted area badges completely secured inside of an armband pouch

do not need to be removed. **(T-2)**

11.8.3.6.4. Wigs, hairpieces, metal hair fasteners, earrings, or any other jewelry/loose items that may fall off without notice, are not authorized on the aircraft and industrial work areas. **(T-2)**

11.8.3.6.5. Escorts of visiting personnel will ensure FOD prevention measures are taken. **(T-3)**

11.8.3.7. All maintenance production areas must have FO containers readily accessible. **(T-2)**

11.8.3.7.1. All vehicles driven primarily on the flightline for direct aircraft maintenance support activities must be equipped with secured and lidded FO containers. **(T-2) Note:** Permanently affixed FO containers must be approved by Vehicle Management prior to installation IAW AFI 24-302.

11.8.3.8. Control all work order residue used on or around aircraft, uninstalled engines, and AGE. **(T-2)**

11.8.3.8. **(AFGSC)** Establish rivet replacement procedures for local operation of assigned weapons systems. Include them as part of the FOD orientation/familiarization for personnel working in these areas. Include work order residue control procedures for all maintenance performed in and around intake areas. **(T-2)**

11.8.3.8.1. **(Added-AFGSC)** Structural Maintenance shops will document all material installed and removed from the aircraft. Tools and hardware used will be verified by a 7-level upon completion.

11.8.3.9. Rags will be controlled and accounted for IAW **Chapter 8**. **(T-2)**

11.8.3.9.1. Rag control applies to all organizations and personnel performing aircraft, missile, munitions, and equipment maintenance.

11.8.3.10. FOD walks are mandatory to remove FO from ramps, runways, taxiways, maintenance areas and access roads.

11.8.3.10. **(AFGSC)** Units will develop local guidance for FOD walks, to include applicable areas and when the FOD walks are required. **(T-2)**

11.8.3.10.1. In addition, mechanical/vacuum sweepers, magnetic bars or sweeping by hand are highly encouraged to supplement FOD walks.

11.8.3.11. When FOD is discovered on a transient aircraft, depot input/output or CRF engine, the host FOD monitor, or aircrew must notify the owning organization within 24 hours. **(T-2)**

11.8.3.11.1. An informational copy of the FOD report must be provided to the owning organization's flight safety office and FOD monitor to ensure compliance with DAFI 91-204. **(T-2)**

11.8.3.11.2. For depot input/output or CRF engine. If the FOD is found during the receiving inspection at one of the aforementioned locations, it will be tracked/charged (if necessary) to the owning MAJCOM unit. **(T-2)** If discovered any other time at one of the aforementioned locations, it will be tracked/charged to the ALC or CRF. **(T-2)**

11.8.3.12. Ensure local FOD Prevention Program addresses the elimination of FOs to include aircraft cockpits and flight decks before and after flight. **(T-2)**

11.8.3.12.1. When an item is lost on or in the vicinity of aircraft or equipment, lost item/tool procedures in **Chapter 8** will be followed.

11.8.3.12.2. DELETED.

11.8.3.12.3. These procedures will be documented in the wing tool/equipment management publication referenced in **Paragraph 8.2**. **(T-2)**

11.8.3.13. Use extreme care during engine ground runs. Jet blast and helicopter hover power check areas need to be free of debris that could cause FOD.

11.8.3.14. Special emphasis is required for items such as: remove before flight streamer attachment, safing pin condition, hinge pin security, dust and FO prevention cover condition/security, and aircraft forms binder condition. Periodically check these types of items for FO prevention compliance.

11.8.3.14.1. Units will account for -21 equipment and covers IAW DAFI 21-103.

11.8.3.14.2. Weapons Expediters must ensure all mission specific safing gear is controlled and accounted for to preclude loss and potential FOD. **(T-2)**

11.8.3.15. Refer to DAFI 13-213, *Airfield Driving and* DAFMAN 91-203, for vehicle FOD check requirements.

11.8.3.15. **(AFGSC)** Vehicle operators will stop and perform a visual FOD inspection on all vehicles, equipment and tires prior to entering the flightline. If FOD check points are not illuminated during periods of darkness, vehicle operators will use a flashlight during vehicle FOD inspection.

11.8.3.16. Grounding wires/points:

11.8.3.16.1. Two Allen head screws, or equivalent, will be utilized to secure cable to grounding clip. **(T-2)**

11.8.3.16.1.1. Screw heads will be coated with sealant or screws will be staked in order to prevent screws from backing out. **(T-2)**

11.8.3.16.1.2. Unused screws will be removed. **(T-2)**

11.8.3.16.2. All grounding points will be kept clean of debris at all times and will be a high interest item for FOD walks. **(T-2)**

11.8.3.17. Use of magnetic bars on the flightline is optional. If used, the magnetic bars will be towed by, or attached to vehicles primarily used on the flightline and will be inspected and made FOD free daily. **(T-2)**

11.8.3.18. A locally manufactured tool for removing debris from tire treads is authorized for use and will be identified to the vehicle by using the vehicle ID number. **(T-2)**

11.8.3.19. Remove metal identification bands from all tubing (except aircraft installed egress system components) and cables on the aircraft.

11.8.3.19.1. With the exception of factory-installed ID tags attached to cargo chains/devices to identify the type being used, remove metal identification bands from cargo tie-down chains/devices prior to use around aircraft.

11.8.3.19.2. Do not remove manufacturer installed metal identification bands from hydraulic hoses.

11.8.3.19.3. Mark hydraulic lines IAW TO 42E1-1-1, *Organizational, Intermediate and Depot Maintenance; Aviation Hoses and Tube Manual.*

11.8.3.20. Use X-ray, borescope, and other equipment to locate FO in inaccessible areas.

11.8.3.20. **(AFGSC)** When any FO is suspected to be in an inaccessible area follow procedures for inaccessible item/tool in **Chapter 8**.

11.8.3.21. WG/CD may institute real-time FOD detection (automated FOD detectors) based upon risk analysis IAW AFI 90-802 and DAFI 91-202.

11.8.3.22. **(Added-AFGSC)** Documenting FOD inspections on engines shut down for "Red Ball" maintenance is not required.

11.8.3.23. **(Added-AFGSC)** FOD inspections performed on uninstalled test cell engines will be documented on the test cell worksheet.

11.8.4. FOD Prevention Responsibilities.

11.8.4.1. The WG/CD will be assigned as the FOD Prevention Program Manager and will appoint a qualified maintenance AFSC, civilian equivalent or contractor if designated by SOW or PWS, to the position of FOD Monitor. **(T-2)**

11.8.4.1.1. The appointed individuals name will be posted in a prominent place within the unit on a locally developed visual aid which also provides contact information. **(T-2)**

11.8.4.2. The WG/CD will:

11.8.4.2.1. Ensure all personnel actively support the FOD Prevention Program. **(T-2)**

11.8.4.2.2. Provide local guidance to ensure each FOD mishap is investigated, and action taken to solve any underlying problems. **(T-2)**

11.8.4.2.3. Review all unit FOD mishap reports and analyze the reports and other data for trends identifying areas requiring management action. **(T-2)**

11.8.4.2.4. Coordinate FOD prevention needs with the airfield manager and other agencies when construction is in progress on or near the flightline, or other areas where FOD incidents could occur. **(T-2)**

11.8.4.2.5. Ensure FOD prevention is part of QA inspections. **(T-2)**

11.8.4.2.6. Coordinate with the airfield manager to identify and properly mark FOD checkpoints. **(T-2)**

11.8.4.2.7. **(Added-AFGSC)** Budget for and allocate funds to support the wing's FOD program. **(T-2)**

11.8.4.3. Tenant Unit FOD Prevention Responsibilities. The host base FOD Prevention Program Manager will incorporate tenant units in the host unit program. **(T-2)**

11.8.4.3.1. Tenant units will establish their own FOD Prevention Program but will still participate in the host program and comply with host program requirements. **(T-2)**

11.8.5. FOD Monitor. The Wing FOD Monitor's office will be located within QA or at the discretion of the WG/CD. **(T-3)** The Wing FOD Monitor, at a minimum, will:

11.8.5.1. Inform all wing agencies of FOD hazards. **(T-2)**

11.8.5.2. Develop wing procedures to document and perform spot checks of "high risk" areas weekly. **(T-2)**

11.8.5.3. Be involved in each FOD investigation and help ensure corrective actions are sound. **(T-2)**

11.8.5.4. Monitor and recommend changes to FOD prevention training. **(T-2)**

11.8.5.4.1. Those units having several types of aircraft assigned will have their FOD prevention training incorporated into one wing/center training program. **(T-2)**

11.8.5.4.2. Units will ensure an initial FOD awareness and responsibilities briefing is given to all newly assigned personnel. **(T-2)**

11.8.5.5. Periodically inspect and report damaged pavement, flightline construction, or other hazards in or near aircraft parking ramps or taxiways to the airfield manager and monitor status to ensure timely repairs. **(T-2)**

11.8.5.6. **(Added-AFGSC)** Ensure evaluated or repaired FOD is documented IAW TO 00-20-1; in Comprehensive Engine Management System (CEMS), automated history (E407), or AFTO Form 95. **(T-2)**

11.8.6. FOD Investigation and Reporting.

11.8.6.1. When suspected or confirmed FOD is discovered, the MOC will be notified immediately. **(T-2)**

11.8.6.1.1. Upon notification, the MOC will immediately notify the Wing FOD Monitor, and Wing Safety, IAW DAFMAN 91-223.

11.8.6.2. Units must make every attempt to determine the root cause of FOD-related mishaps before returning engines and modules to the depot for investigation. **(T-2)**

11.8.6.2.1. If engines/modules are returned to the depot, an information DR will be completed and forwarded IAW procedures outlined in DAFI 91-204 and TO 00-35D-54.

11.8.6.2.2. All FOD-mishap engines and modules returned to the depot must be properly marked on the outside of the packaging as a FOD-mishap asset. **(T-2)**

11.8.6.2.3. Mark container or package in red with the following statement, "FOD mishap investigation required." **(T-2)**

11.8.6.3. FOD incidents are classified as preventable and non-preventable. Only preventable FOD over $60K (parts and labor) are to be chargeable to the FOD rate. FOD is considered preventable except when the damaged can be attributed to the following:

11.8.6.3.1. Caused by natural environment or wildlife. This includes hail, ice, animals, insects, sand, and birds. Report this type of damage IAW DAFI 91-204. Do not include these in the FOD rates.

11.8.6.3.2. From internal engine materiel failure as long as damage is confined to the engine.

11.8.6.3.2. **(AFGSC)** If no evidence of FOD impact is found upstream in the engine, submit DR/mishap report(s) IAW DAFI 91-204 and TO 00-35D-54. **(T-2)**

11.8.6.3.3. Caused by materiel failure of an aircraft component if the component failure is reported as a DR using the combined mishap DR reporting procedures of DAFI 91-204 and TO 00-35D-54.

11.8.6.3.4. Found during depot overhaul for maximum operating time.

11.8.6.3.5. **(Added-AFGSC)** Found during Jet Engine Intermediate Maintenance (JEIM) maintenance for maximum operating time. **(T-2)**

11.8.6.4. Additionally, the following apply:

11.8.6.4.1. Engine damage caused by improper anti-ice/de-ice procedures by either flight or ground crews are considered preventable.

11.8.6.4.2. Engine or airframe damage caused by gunnery or rocket mission ricochets are considered non-preventable provided mission parameters were not exceeded and range cleaning was sufficient.

11.8.6.4.3. Engine and propeller damage caused by rocks, stones, wood, or other objects ingested during low hover operations or unimproved runway landings are considered non-preventable, provided mission parameters were not exceeded.

11.8.6.4.4. MAJCOMs will determine reporting criteria for FOD incidents that result in a blade blending requirement IAW applicable tech-data.

11.8.6.4.4.1. **(Added-AFGSC)** Blade blending procedures for installed/uninstalled engines/modules: **(T-2)**

11.8.6.4.4.1.1. **(Added-AFGSC)** Notify the Wing/Center FOD Monitor prior to blade blending whenever Foreign Object Damage (FOD) is identified, except for minor sand nicks or scratches (e.g., those addressed by blending with emery cloth). **(T-2)**

11.8.6.4.4.1.2. **(Added-AFGSC)** Fill out locally developed Blade Blending/FOD Damage worksheet or applicable form with the following information: engine serial number, stage number, number of blades blended, depth of damage before and after blend, area of damage and employee number/stamp number of maintenance personnel. **(T-2)**

11.8.6.4.4.1.3. **(Added-AFGSC)** Notify EM Section and forward Blade Blending/FOD Damage worksheet or applicable form to EM Section for filing. The EM Section will transcribe information provided in the Blade Blending/FOD Damage worksheet into the applicable engine/module records (e.g., AFTO Form 95; if applicable) and CEMS, IAW TO 00-20-1. **(T-2)**

11.8.6.5. Preventable FOD over $60K incurred at ETS or on trim pad will be chargeable. **(T-2)**

11.8.6.5. **(AFGSC)** Preventable FOD incurred at test cells will be chargeable towards rate regardless of cost. **(T-2)**

11.8.6.6. Appropriate MAJCOM offices will assist in resolving any questionable FOD issues, preventable or non-preventable.

11.8.6.6. **(AFGSC)** AFGSC/A4MA will assign accountability in those instances where conflict/peculiar circumstances occur. **(T-2)**

11.8.6.7. The Wing FOD Monitor will provide an initial report of all FOD incidents to the MAJCOM FOD monitor within 24 hours of occurrence. **(T-2)**

11.8.6.7.1. A follow-up report will be required every 45 days until closeout. **(T-2)** Use the FOD report format as listed in **Attachment 6**.

11.8.6.7.1. **(AFGSC)** All FOD incidents exceeding $60K will be reported to AFGSC using the command standard format and the local base safety office. FOD incidents under $60K will be tracked locally and reviewed by the Wing CV and FOD manager every 6 months for trends, these incidents require phone or e-mail notification to **AFGSC.A4M.Workflow@us.af.mil**.

11.8.6.7.2. MAJCOMs will determine FOD standards, MDS specific flying hour source data, period of time for calculation, reporting procedures, and meeting frequency for units that exceed standards in their supplement to this DAFI.

11.8.6.7.2. **(AFGSC)** Wing FOD/DOP managers will submit AFGSC FOD/DOP Incident Worksheet within 72 hours of any FOD/DOP incident. Additionally, all incidents must be annotated within the ACC.A4MP Propulsion FOD/DOP Reports **https://usaf.dps.mil/sites/ACC-A4/A4M/A4MP/Lists/FOD%20Rate/Allitemsg.aspx**. The monthly report must be completed in its entirety and submitted via email to the AFGSC/A4MA Workflow inbox monthly, no later than the 10th calendar day of each month. E-mail to **AFGSC.A4M.Workflow@us.af.mil**. Quarterly meetings will be conducted by units exceeding standard. **(T-2)**

11.8.6.8. FOD rates are computed by MDS as follows: Number of Preventable FODs (damage exceeding $60K) ÷ Aircraft Flying Hours X 10,000 = FOD Rate. **Note:** ALCs compute FOD rates as follows: Number of Preventable FODs (damage exceeding $60K) ÷ Aircraft Flying Hours X 1,000 = FOD Rate. ALCs compute aircraft flying hours by using acceptance flights, functional check flights, ground runs, and the number of un-installed ETS starts.

11.8.6.8. **(AFGSC)** Parent wings are responsible for the FOD prevention program of detachments. Parent wings will collectively report FOD rates. **(T-2)**

11.8.6.8.1. **(Added-AFGSC)** Wing rates are computed monthly. Each wing FOD manager will submit by the 10th of each month FOD-DOP WORKBOOK to **AFGSC.A4M.Workflow@us.af.mil**. The report will include monthly cumulative data. A fiscal year roll up will be provided NLT 15 Oct. **(T-2)**

11.8.6.8.1.1. **(Added-AFGSC)** Causes of Preventable and Non-Preventable FODs. **(T-2)**

11.8.6.8.1.2. **(Added-AFGSC)** Cumulative cost of Preventable and Non-Preventable FODs. **(T-2)**

11.8.6.8.1.3. **(Added-AFGSC)** MDS flying hours. **(T-2)**

11.8.6.8.1.4. **(Added-AFGSC)** Calculated unit FOD rate by MDS and current cumulative fiscal year FOD rate. **(T-2)**

11.8.6.9. **(Added-AFGSC)** FOD accountability will be in accordance with the following guidance:

11.8.6.9.1. **(Added-AFGSC)** When transient/deployed aircraft incur FOD, the host unit will conduct the investigation and notify the owning organization within 72 hours. If the owning organization's maintainers are deployed with the aircraft and the FOD appears to be a direct result of transient/deployed unit negligence, the owning organization will conduct the investigation. During deployed operations where mixed unit crews are flying or maintaining aircraft, FOD incidents will be charged to unit receiving flying hour credit. **(T-2)**

11.8.6.9.2. **(Added-AFGSC)** The owning organization is responsible for FOD incidents on transient aircraft/engines when one of the following conditions applies: **(T-2)**

11.8.6.9.2.1. **(Added-AFGSC)** FOD discovered upon arrival at a transient base with no intermediate stops or prior to any engine run. **(T-2)**

11.8.6.9.2.2. **(Added-AFGSC)** FOD found during initial tear down on "Queen Bee/ERRC" engines. **(T-2)**

11.8.6.9.2.3. **(Added-AFGSC)** Aircraft is maintained on transient/TDY base by owning organization maintenance personnel. **(T-2)**

11.8.6.10. **(Added-AFGSC)** The preventable FOD standard is 1.0. **Note:** Tenant units will use their parent unit FOD standard. **(T-2)**

11.8.6.11. **(Added-AFGSC)** The unit safety representative in coordination with the wing FOD manager will submit mishap reports IAW DAFI 91-204. **(T-2)**

11.8.6.12. **(Added-AFGSC)** Each unit will establish their own FOD control number(s) as follows: wing designator, fiscal year, and a three-digit number; for example, 5BW15001. **(T-2)**

11.8.6.13. **(Added-AFGSC)** FOD discovered by transient alert facilities or by depot and contractor facilities during acceptance inspections will be charged to the base from which the aircraft last departed if a FOD inspection was not accomplished/documented. The owning organization will be charged if there are no intermediate stops. FOD incidents caused by transit bases, depot or contractors, will refer to the responsible command for determination of accountability. **(T-2)**

11.8.6.14. **(Added-AFGSC)** Wings will submit maintenance cross-tell reports by message to HQ AFGSC/A4MA and to all units with like MDSs for those incidents that have FOD potential for the fleet. **(T-2)**

11.8.7. FOD Prevention Committee Meeting. This meeting is mandatory for units that exceed the MAJCOM-established standard. **(T-2)**

11.8.7.1. - 11.8.7.1.1. DELETED.

11.8.7.2. Meeting agenda items should include issues that resulted in the wing exceeding the FOD standard, such as:

11.8.7.2.1. Total number of airframes, engine, and tire FOD incidents during the reporting period. Indicate quantity and cause. Current status of all other pending incidents will be discussed.

11.8.7.2.2. Mechanical/vacuum sweeper status.

11.8.7.2.3. Review and refinement of the existing FOD prevention program.

11.8.7.2.4. New directives/actions established to minimize FOD.

11.8.7.2.5. Status and condition of engine run-up screens as applicable.

11.8.7.2.6. Results of X-rays for FOs during engine bay inspections, acceptance inspections, and PH inspections. Maintenance trends should be discussed when an increase in FO is discovered during these X-rays.

11.8.7.2.7. Identification of potential FOD sources.

11.8.7.2.8. Lost tools/items.

11.8.7.2.9. Increased potential for FOD within the next 30-60 days.

11.8.7.2.10. Dropped objects. Pay particular attention to those that result in downstream FOD.

11.8.7.2.11. Breakdown of FOD inspections/assessments.

11.8.7.2.12. Cockpit FO incidents.

11.8.7.2.13. Recognition of personnel making significant contributions to FOD prevention (such as, golden bolt program, FOD poster contests, or other FOD recognition programs locally developed at each unit).

11.8.8. Bird Strikes. Consult TO 1-1-691 for bird strike clean-up procedures and DAFMAN 91- 223, *Aviation Safety Investigation and Reports* for bird strike reporting procedures.

11.9. Dropped Object Prevention (DOP) Program. A dropped object is any aircraft part, component, surface, or other item lost during aircrew operations (unless intentionally jettisoned) from engine start to engine shutdown. Inadvertently released munitions are not considered dropped objects and will be reported IAW DAFI 91-204. **Note:** Missing Chaff/Flare/Decoy endcaps/LO coating are not reportable dropped objects.

11.9. (AFGSC) Dropped Object Prevention (DOP) Program. Note: Missing minor hardware (bolts, nuts, rivets, fasteners, etc.) are not reportable dropped objects. **(T-2)**

11.9.1. Responsibilities. All units, which fly, service, or maintain aircraft, will develop a DOP Program with the following provisions: **(T-2)**

11.9.1.1. MAJCOM DOP monitors or aircraft functional managers will act as OPR for all dropped object inquiries IAW MAJCOM established standards.

11.9.1.1. **(AFGSC)** The Wing DOP monitor will identify and develop training standards. Maintenance personnel involved in on-equipment maintenance will receive DOP training. **(T-2)**

11.9.1.1.1. **(Added-AFGSC)** Annotate DOP training in the appropriate training records or in MIS-CDB. Training should include, but is not limited to, inspection, installation, removal, and repair procedures for aircraft panels, doors, access covers, cowlings, etc. Also, include in training the care of panel latches, fasteners, nut plates, and other locking devices. Security of hardware, particularly those causing a high incidence of dropped objects, will be high interest items on flight crew walk-around. **(T-2)**

11.9.1.2. The WG/CD serves as the Wing DOP Program Manager and will appoint a Wing DOP Monitor. **(T-2)**

11.9.2. Investigation. The DOP Monitor will investigate each dropped object incident. **(T-2)**

11.9.2. **(AFGSC)** In-flight dropped object incidents will be immediately brought to the attention of the Wing DOP Monitor and QA. Quality Assurance or the Wing DOP Monitor will investigate each dropped object incident. **(T-2)**

11.9.2.1. Every effort needs to be made to determine the precise cause to ensure positive corrective action is accomplished. Anytime a materiel or design deficiency is the cause, or suspected cause, a DR will be submitted IAW TO 00-35D-54, even when an exhibit is not available.

11.9.2.2. Investigation results will be distributed to each appropriate work center for inclusion in personnel training and education programs. **(T-2)**

11.9.3. Reporting. Units will follow MAJCOM DOP Program reporting procedures. **(T-2)**

11.9.3.1. Transient Aircraft. The host Wing DOP Monitor will be responsible to investigate dropped objects from a transient aircraft. **(T-2)**

11.9.3.1.1. The host Wing DOP Monitor will provide the home station Wing DOP Monitor with sufficient data to generate a report for trending and tracking purposes. **(T-2)**

11.9.3.2. **(Added-AFGSC)** Initial dropped object report will be made to the MAJCOM via telephone, e-mail, or message within 24 hours of occurrence. If it involves casualties, property damage, or if adverse publicity is likely, report IAW AFMAN 10-206. The Wing DOP Monitor notifies the base/wing safety office of all dropped objects. Units will maintain reports for a minimum of 24 months (can be electronic). **(T-2)**

11.9.3.3. **(Added-AFGSC)** Follow-up final report will be made to the MAJCOM within 3 duty days after the occurrence. The final format will be used as listed in **Attachment 6**. In addition, all incidents must be annotated within the AFGSC approved records maintained by A4MA Propulsion Functional Area Manager **(T-2)**

11.9.4. **(Added-AFGSC)** The Wing DOP Monitor will submit quarterly reports to AFGSC (Oct, Nov and Dec data will be reported in Jan, NLT the 15th). These reports will contain the following data: Number of incidents, number preventable/non-preventable, submitted during that quarter. **(T-2)**

11.9.4.1. **(Added-AFGSC)** A summary of DOP incidents will be briefed in conjunction with the quarterly FOD meeting. **(T-2)**

11.9.4.2. **(Added-AFGSC)** DOP Incidents are categorized as preventable or non-preventable, both are reportable. All preventable incidents will be chargeable. DOPs are considered preventable except those listed below: **(T-2)**

11.9.4.2.1. **(Added-AFGSC)** Caused by natural environment or wildlife. This includes but is not limited to hail, ice, animals, insects, sand, and birds. Report this type of damage IAW DAFI 91-204, *Safety Investigations and Reports*. Do not include these in the DOP rates. **(T-2)**

11.9.4.2.2. **(Added-AFGSC)** Caused by material failure of an aircraft component if the component failure is reported as a DR using the combined mishap DR reporting procedures of DAFI 91-204 and TO 00-35D-54, *USAF Deficiency Reporting, Investigation, and Resolution*. **(T-2)**

11.9.4.2.3. **(Added-AFGSC)** Helicopter damage caused by rocks, stones, wood, or other objects during low hover operations or unimproved runway operations are considered non-preventable, provided mission parameters were not exceeded. **(T-2)**

11.9.4.3. **(Added-AFGSC)** DOP program report number (unit, year, and month, followed by sequence number -- example, 509BW-150501). **(T-2)**

11.10. Aircraft Structural Integrity Program (ASIP). The ASIP includes requirements for collection and evaluation of aircraft usage data to update or confirm the original design or baseline spectrum and to adjust maintenance intervals on an individual aircraft basis. The Loads/Environment Spectra Survey data is collected via flight data recorders of instrumented aircraft to evaluate the loads spectrum. The Individual Aircraft Tracking data is collected via flight data recorders or manual forms such as “bubble sheets” and the data is used to make maintenance/inspection/force structure decisions. Both the Loads/Environment Spectra Survey and Individual Aircraft Tracking usage data programs are established by applicable MDS-specific TOs and DAFI 63-140 and require coordinated action by a number of base-level maintenance activities to achieve the required data capture rates. An effective ASIP aircraft usage data collection program is essential to establish, assess and support inspections, maintenance activities, repairs and required modification/replacement actions. MAJCOMs will:

11.10.1. Publish ASIP roles and responsibilities for each assigned weapon system IAW DAFI 63-140.

11.10.2. Ensure operational units continuously meet authorized reporting requirements established by Program Offices.

11.10.3. Document causes and corrective actions for units that fail to meet reporting requirements and retain until resolved or relief of the reporting requirement is granted from the Program Office in writing.

11.10.4. **(Added-AFGSC)** Roles and responsibilities apply to B-1, B-2, B-52, E-4 and UH-1/MH-139. **(T-2)**

11.10.4.1. **(Added-AFGSC)** AFGSC/A4MA is the MAJCOM POC for ASIP. **(T-2)**

11.10.4.2. **(Added-AFGSC)** The MXG/CC or equivalent will ensure an effective ASIP is established and appoint a SNCO as the MXG ASIP Manager. **(T-2)**

11.10.4.3. **(Added-AFGSC)** ASIP Manager Will:

11.10.4.3.1. **(Added-AFGSC)** Develop effective measures to capture and report ASIP aircraft usage data (L/ESS and IAT) to achieve the required data capture rates. **(T-2)**

11.10.4.3.2. **(Added-AFGSC)** Develop procedures to collect and submit ASIP aircraft usage data (e.g., computer files downloaded from a flight data recorder, tapes obtained from a flight data recorder, "bubble sheets"). **(T-2)**

11.10.4.3.3. **(Added-AFGSC)** Coordinate with the MDS MAJCOM OPR to obtain feedback on data capture rates and to implement corrective actions as needed to achieve the required rates. **(T-2)**

11.10.4.3.4. **(Added-AFGSC)** Identify maintenance activities (ASIP Monitors) responsible for changing and submitting storage media. **(T-2)**

11.10.4.4. **(Added-AFGSC)** Maintenance activities (ASIP Monitors) responsible for ASIP aircraft usage data collection and evaluation will collect and submit ASIP aircraft usage data IAW local ASIP publications, TOs and this instruction. **(T-2)**

11.11. Identification Friend or Foe (IFF) Program.

11.11.1. MAJCOMs will establish an Identification Friend or Foe Program for aircraft in their command (if equipped).

11.11.1.1. MAJCOM programs will identify additional requirements necessary to ensure status of Identification Friend or Foe systems meets mission requirements.

11.11.1.1.1. **(Added-AFGSC)** IFF Mode V checks for contingency missions: Perform Mode V check on all applicable aircraft prior to first sortie of the day (or prior to placing on alert status). When an aircraft is found to have a malfunctioning IFF system, the Aircraft Commander will then determine course of action based on operational needs and requirements. **(T-2)**

11.11.1.1.2. **(Added-AFGSC)** IFF Mode V checks for non-CONUS and Transoceanic sorties: Perform Mode V checks on all applicable aircraft prior to aircraft leaving CONUS airspace to include transoceanic sorties. When an aircraft is identified as having a malfunctioning IFF system, the Aircraft Commander will then determine a course of action based on operational needs and requirements. **(T-2)**

11.11.2. DELETED.

11.11.3. Equipped aircraft will be checked prior to its first sortie of the day during contingency operations. **(T-2)**

11.12. Radar Warning Receiver/Radar Threat Warning Testing.

11.12.1. MAJCOMs will identify weapon systems with enhanced on-board diagnostics and internal testing capabilities which do not require external testing in their supplement to this instruction (if equipped).

11.12.1.1. MAJCOMs will determine non-contingency system functional check requirements necessary to ensure Radar Warning Receiver/Radar Threat Warning systems are maintained operationally ready to meet mission requirements IAW the MESL or MDS equivalent.

11.12.1.1.1. **(Added-AFGSC)** Aircraft with on-board diagnostic testing are exempt from non-contingency operations. **(T-2)**

11.12.2. DELETED.

11.12.2.1. The Radar Warning Receiver/Radar Threat Warning Manager if assigned, will coordinate test procedures with the Wing Electronic Warfare Officer and the MXS, if applicable. **(T-2)**

11.12.2.2. The Radar Warning Receiver/Radar Threat Warning Manager if assigned will ensure each unit accomplishes the required minimum number of checks as defined below. **(T-2)**

11.12.2.2.1. For contingency missions, the Radar Warning Receiver/Radar Threat Warning Manager will coordinate with the Electronic Warfare Officer/Electronic Combat Officer who will determine system check requirements and specific threats to be simulated. **(T-3)**

11.12.3. When an aircraft is found to have a malfunctioning Radar Warning Receiver/Radar Threat Warning system prior to flight, the Aircraft Commander (AC) determines the course of action based on operational needs and requirements.

11.13. Cannibalization Program.

11.13.1. General. CANN actions may be necessary when a condition prevents the accomplishment of a mission, and the required assets are not immediately available from supply. Prior to performing a CANN action, verify the required component cannot be sourced from LRS, TNB or back shop. When authorizing a CANN, the expenditure of man-hours and potential damage to equipment need to be weighed against the expected benefit. High risk CANNs should not be performed unless priority aircraft are involved, or lack of ready equipment will impede mission accomplishment. See **Table 1.2** (Reference AFTTP 3-4.21V1).

11.13.1.1. **(Added-AFGSC) [NC3]** CANN actions for NC3 assets will be decided by maintenance personnel. Maintenance personnel will document CANN actions on NC3 AFTO Form 781A.

11.13.1.2. **(Added-AFGSC) [NC3]** Once the CANN is validated by the Pro Super, DMS personnel will update applicable supply records when CANN actions are required.

11.13.2. Definition. CANN is the authorized removal of a specific assembly, subassembly, or part from one weapon system, system, support system, or equipment end item for installation on another end item to satisfy an existing supply requisition and to meet priority mission requirements with an obligation to replace the removed item. Weapon systems, support

systems, or equipment include aircraft, missiles, drones, RPA, uninstalled engines, uninstalled engine modules, aircrew and/or launch crew training devices, Communications-Electronics equipment, AGE, TMDE, serviceable uninstalled pods, and guns.

11.13.3. Responsibilities. CANN Authorities (CA) will be tracked in the MIS and SCR (see **Table 11.1**). **(T-2)**

11.13.3.1. CA will be SNCOs, officers or civilian equivalents. **(T-2)** These personnel are typically Pro Supers.

11.13.3.2. Those who are authorized to approve CANNs will not further delegate their responsibility. **(T-2)**

11.13.4. If an assembly is cannibalized to satisfy a condition caused by lack of bits and pieces (such as, washers, nuts, and bolts), the assembly is counted as a CANN, and the bits and pieces are considered transfer actions. Bits and pieces removed from an end item (without removing the assembly) for installation on another end item are considered individual CANN actions.

11.13.5. When a required part cannot be delivered and installed on time, the CA may approve the CANN of parts before the initiation of CANN documentation (such as, Red Ball maintenance). The CA will give this approval only after confirming the part is not readily available in LRS, TNB, forward supply points, or back shops. **(T-2)**

11.13.5.1. The CA will notify the appropriate supply activity to change the “mark-for” components in the document number. **(T-2)**

11.13.5.2. The CA will also ensure complete documentation is accomplished for each CANN action. **(T-2)**

11.13.6. When TCIs, serially controlled items, items affecting compliance of a TCTO, or other components with inspection requirements that align to specific hourly, calendar, or event limits are considered for CANN, the CA will coordinate with PS&D or EM to ensure adequate time remains on the item to justify the CANN and to ensure appropriate records are updated. **(T-2)**

11.13.6.1. If the CANN action takes place, the performing work center will update the MIS and notify PS&D or EM. **(T-2)**

11.13.7. Installed engines are not end items; installed engines are considered a LRU (similar to a radar component, gun, seat, canopy, radio, multifunction display unit).

11.13.7. **(AFGSC)** Uninstalled engines returning to CRF/depot for repair will not be cannibalized without approval from AFGSC/A4MA Engine Managers (EM).

11.13.7.1. If a functional LRU is removed from one end item to put on another end item to fill a “hole” which was caused by a supply requisition, (the requisition could be against the LRU), then this is considered a CANN.

11.13.7.2. **(Added-AFGSC)** Engines will be shipped to CRF/Depot repair activities with all parts installed unless approved by AFGSC/A4M Command Engine Manager.

11.13.8. Restrictions.

11.13.8.1. Egress system component CAD/PAD cannibalization actions are considered "High-Risk" and should not be performed unless priority aircraft are involved (example,

higher headquarters/alert status), or lack of ready equipment will impede mission accomplishment.

11.13.8.1.1. To ensure system integrity and validation of the explosive CAD/PAD listing, cannibalization of egress explosive and seat components require MXG approval. **(T-3)**

11.13.8.1.2. After cannibalization actions, Egress Red X discrepancies in the aircraft AFTO Form 781As will not be cleared until verification that CAD/PAD S/N content matches the S/N content entries in the MIS. **(T-2)**

11.13.8.1.3. Only (2A6X3) Egress personnel will accomplish this action. **(T-2)**

11.13.8.2. CANN actions involving parts from ABDR training aircraft, AF Museum Aircraft, Maintenance Training Devices, GITA, TAA, or DLADS will not be accomplished without authorization from the Program Office. **(T-2)**

11.13.8.2.1. Parts will not be removed from static display/AF Museum Aircraft except as authorized by AFI 84-103. **(T-2)**

11.13.8.2.2. If the part is approved for CANN, it must not be put into service until all necessary inspections (such as, NDI, pressure checks, operational checks, TCTOs) have been accomplished using specific guidance from the item manager to ensure proper serviceability. **(T-2)**

11.13.8.3. Units will not CANN parts from aircraft possessed by AFMC (B or D PIC) without first coordinating through the MAJCOM functional manager who will request approval from the applicable PM. **(T-2)**

11.13.8.4. An aircraft that has been extensively cannibalized will not be launched on an overseas or cross-country sortie/mission on the first flight following CANN rebuild without the owning MXG/CC or equivalent approval. **(T-2)**

11.14. Hangar Queen Aircraft.

11.14.1. General. The objective of this program is to ensure the entire fleet remains healthy and all possible management actions are carried out to ensure aircraft do not remain inoperative for extended periods. MAJCOMs will establish a Hangar Queen Management Program.

11.14.1. **(AFGSC)** Hangar Queen Aircraft reporting is a separate process from the No-Fly inspection requirements outlined in TO 00-20-1.

11.14.1.1. **(Added-AFGSC)** The MXG/CD (or MXG/CDs delegated individual) may delegate approval authority for Hangar Queen Aircraft Category 1. The MXG/CD (or MXG/CDs delegated individual) is the cannibalization approval authority for Hangar Queen Aircraft Category 2 and Category 3. **(T-2)**

11.14.2. Definitions. A “Hangar Queen” is a unit-possessed aircraft that has not flown for at least 30 calendar days. Aircraft are exempt from accruing Hangar Queen time for up to 10 days immediately following DFT/CFT repair or maintenance; however, if an aircraft is not flown after the 10th day, the 10 days are included in the total number of days since last fly date to determine the Hangar Queen category computation. Hangar Queen aircraft will be further defined by the following three categories:

11.14.2.1. Category 1: Aircraft that have not flown for 30 to 59 calendar days. **(T-2)**

11.14.2.1. **(AFGSC)** When an aircraft becomes Category 1 Hangar Queen, brief aircraft maintenance and supply status weekly to the MXG/CC. Category 1 aircraft are managed locally.

11.14.2.2. Category 2: Aircraft that have not flown for 60 to 89 calendar days. **(T-2)**

11.14.2.2. **(AFGSC)** When an aircraft becomes Category 2 Hangar Queen, they continue to brief aircraft maintenance and supply status daily to the MXG/CC. Category 2 aircraft are managed locally.

11.14.2.3. Category 3: Aircraft that have not flown for 90 or more calendar days. **(T-2)**

11.14.2.3. **(AFGSC)** When an aircraft becomes a Category 3 Hangar Queen, assign a SNCO or officer (or civilian equivalent) to manage the Hangar Queen Aircraft. Brief aircraft maintenance and supply status at the daily wing standup meeting and continue Category 2 Hangar Queen requirements. Units will report aircraft tail number(s) monthly to the applicable WST, AFGSC/A4A (B-1, B-2, B-52, and E-4) and AFGSC/A4B (UH-1 and MH-139) with the estimated delivery dates for top downtime driver (AWP) parts. **(T-2)**

11.14.2.3.1. **(Added-AFGSC)** Units will send reports to the applicable WST in AFGSC/A4A or AFGSC/A4B (see **paragraph 11.14.7** for Hangar Queen reporting). **(T-2)**

11.14.2.3.2. **(Added-AFGSC)** Cease all cannibalization, transfer, and diversion actions on Category 3 Hangar Queen aircraft. **(T-2)**

11.14.2.3.3. **(Added-AFGSC)** MXG/CC will determine if an OCF/FCF is needed for Hangar Queen Category 1 and 2 aircraft prior to release from Hangar Queen status (if not otherwise required by the aircraft specific TO). **(T-2)**

11.14.2.3.4. **(Added-AFGSC)** At a minimum, an OCF is mandatory for Hangar Queen Category 3 aircraft prior to release from hangar queen status. **(T-2)**

11.14.3. All aircraft placed on higher HHQ alert status are exempt from the Hangar Queen Management Program and reporting throughout the duration of alert status/posturing.

11.14.3. **(AFGSC)** Aircraft in “PJ” or “PR” possession identifier code are exempt from Hangar Queen reporting. Aircraft regained from possession code PJ or PR and aircraft being removed from alert or immediate response are authorized a 10-calendar day grace period for Hangar Queen reporting. **(T-2)**

11.14.4. An aircraft is released from Hangar Queen status after the first flight. The following examples are provided to clarify when an aircraft becomes a Hangar Queen:

11.14.4.1. A unit-possessed aircraft has not flown for 20 calendar days, enters depot status for 5 more calendar days, and then returns to unit possession on the 26th non-fly day; the unit has up to 10 calendar days to fly the aircraft to avoid Hangar Queen status. If this aircraft does not fly on the 10th calendar day (35th non-fly day), the aircraft will become 36-day Category 1 Hangar Queen on the next day.

11.14.4.2. A unit-possessed aircraft has not flown for 2 calendar days, then enters depot status for 1 calendar day and is returned to unit possession, the unit must fly the aircraft in the next 27 calendar days to avoid becoming a Category 1 Hangar Queen.

11.14.4.2.1. **(Added-AFGSC)** When an aircraft becomes identified as a Hangar Queen, management should intensify their efforts to alleviate the condition as soon as possible (e.g., mission impact letters, Lead Command and item manager assistance). An aircraft's last fly day should be accessible through the LIMS-EV Fleet Asset Status (FAS) view. **(T-2)**

11.14.5. **(Added-AFGSC)** Units will develop Hangar Queen Procedures that cover any local unit responsibilities. **(T-2)**

11.14.6. **(Added-AFGSC)** Hangar Queen Exceptions.

11.14.6.1. **(Added-AFGSC)** Aircraft permanently assigned and possessed in TX code or with a "G" prefix are exempt from Hangar Queen reporting. **(T-2)**

11.14.6.2. **(Added-AFGSC)** Aircraft regained from depot possessions which have not flown for 30 consecutive days and fall within the 10-calendar day grace period is still locally managed as Hangar Queens. **(T-2)**

11.14.7. **(Added-AFGSC)** Hangar Queen Reporting.

11.14.7.1. **(Added-AFGSC)** Report all Category 3 Hangar Queen aircraft within 24 hours of effective date of entering Hangar Queen Category 3 status. MO will provide Hangar Queen Reports to AFGSC/A4A (B-1, B-2, B-52, and E-4) or AFGSC/A4B (UH-1 and MH-139) appropriate WST via message/coordinated email. **(T-2)**

11.14.7.1.1. **(Added-AFGSC)** Subject of the message/coordinated email, with appropriate aircraft tail number information, will be Category 3 HANGAR QUEEN STATUS AIRCRAFT XX-XXXX. **(T-2)**

11.14.7.1.2. **(Added-AFGSC)** Include the following information in HQ reporting message:

11.14.7.1.2.1. **(Added-AFGSC)** Aircraft MDS. **(T-2)**

11.14.7.1.2.2. **(Added-AFGSC)** Aircraft tail number. **(T-2)**

11.14.7.1.2.3. **(Added-AFGSC)** Owning unit. **(T-2)**

11.14.7.1.2.4. **(Added-AFGSC)** Date last flown. **(T-2)**

11.14.7.1.2.5. **(Added-AFGSC)** Reason for potential Hangar Queen. **(T-2)**

11.14.7.1.2.6. **(Added-AFGSC)** Status. **(T-2)**

11.14.7.1.2.7. **(Added-AFGSC)** Pacing action. **(T-2)**

11.14.7.1.2.8. **(Added-AFGSC)** Parts required. **(T-2)**

11.14.7.1.2.9. **(Added-AFGSC)** Estimated fly date. **(T-2)**

11.14.7.1.2.10. **(Added-AFGSC)** Include the following Total Not Mission Capable Supply (TNMCS) information also: **(T-2)**

11.14.7.1.2.10.1. **(Added-AFGSC)** Estimated Delivery Date(s) **(**EDDs).

(T-2)

11.14.7.1.2.10.2. **(Added-AFGSC)** WUC(s). **(T-2)**

11.14.7.1.2.10.3. **(Added-AFGSC)** NSN(s). **(T-2)**

11.14.7.1.2.10.4. **(Added-AFGSC)** Document Number. **(T-2)**

11.14.7.1.2.10.5. **(Added-AFGSC)** Requisition Number. **(T-2)**

11.14.7.1.2.10.6. **(Added-AFGSC)** Off base requisition (s). **(T-2)**

11.14.7.1.2.11. **(Added-AFGSC)** Identify any assistance required from AFGSC/A4A (B-1, B-2, B-52, & E-4) and AFGSC/A4B (UH-1 and MH-139). **(T-2)**

11.14.7.1.2.12. **(Added-AFGSC)** A point of contact with telephone number. **(T-2)**

11.14.7.1.2.13. **(Added-AFGSC)** A plan for recovery. **(T-2)**

11.14.7.1.3. **(Added-AFGSC)** MO will send a message/coordinated email to the AFGSC/A4A or AFGSC/A4B appropriate WST when Category 3 aircraft have been released from Hangar Queen status. **(T-2)**

11.15. Ground Instructional Trainer Aircraft (GITA). GITA are permanently grounded aircraft declared excess to future operations or flying requirements by higher headquarters and will be re-designated by the addition of the prefix "G" to the basic MDS. GITA are not maintained in a flyable condition but maintain system/subsystem operational condition for purposes of maintenance training and will be carried in assignment/PIC outlined in DAFI 21-103 and AFI 16-402. This section does not apply to ABDR training aircraft. ABDR training aircraft are managed by AFSC/LZDB (ABDR Program Office (PO)). This **Chapter** does not apply to training equipment maintained by Contract Logistics Support contracts administered by commands other than AETC.

11.15.1. Only those items requested by the PM are considered for removal. If the item does not affect training and if approved by MXG/CC, the part will be removed and turned in as per the ALC MXG/CC's (or equivalent) instructions. **(T-2)**

11.15.1.1. Units are responsible for storing uninstalled or removed equipment that is not required for training. **(T-3)**

11.15.2. Training Aid Aircraft (TAA). TAA are permanently grounded aircraft that, at a minimum, require an aircraft fuselage that was previously in the AF inventory as an aircraft.

11.15.2.1. Assigned TAA are not maintained in airworthy condition, and only the system/subsystem required for the specific training requirements will be maintained in operational condition for purposes of required maintenance/organizational training. **(T-2)**

11.15.2.2. TAA used for training are not terminated from the AF inventory IAW AFI 16-402. TAA requests for use by non-maintenance AFSCs require coordination through AFMC/LCMC and the PM prior to approval of assignment via an AF Form 913. **(T-3)**

11.15.2.3. Questions about the designation of an aircraft used for training should be directed to the MAJCOM AVDO.

11.15.2.4. Permanently grounded missiles retain their original MDS without a prefix.

11.15.2.5. Upon assignment of a permanently grounded GITA/TAA, the MXG will contact the applicable MAJCOM to coordinate "save list" requirements identified by the applicable PM. **(T-2)**

11.15.2.5.1. “Save list” items removed will be turned into LRS for shipment. **(T-3)**

11.15.2.5.2. If an item on the “save list” is not removed, the reason for not removing it will be annotated and coordinated with the applicable MAJCOM. **(T-2)**

11.15.2.5.3. If items on the “save list” are required for training and an unserviceable item will suffice, units will coordinate with the applicable MAJCOM for receipt of the unserviceable item(s). **(T-2)**

11.15.2.5.4. All unserviceable items furnished by ALC will be marked/identified as “unserviceable” in a conspicuous manner (such as, Red X or Red dot system). **(T-2)**

11.15.3. MAJCOM Responsibilities. MAJCOMs will determine use of MIS for permanently grounded GITA records management.

11.15.3. **(AFGSC)** In addition to AFTO 781-series forms, all Job Data Documentation (JDD) maintenance actions will be documented in MIS for permanently grounded GITA. **(T-2)**

11.15.3.1. MAJCOMs will coordinate “save list” requirements/changes with the applicable PMs.

11.15.4. MXG/CC Responsibilities. MXG/CC or equivalent will:

11.15.4.1. - 11.15.4.2. DELETED.

11.15.4.2.1. GITA maintenance includes on- and off-equipment maintenance of active systems and subsystems and necessary actions to maintain the aircraft in a safe and presentable condition.

11.15.4.2.2. TAA require minimal maintenance on systems/subsystems used to meet training requirements and should be maintained in a safe and presentable condition.

11.15.4.2.3. Determine which system and subsystem are required to support the training. Consider present, future, and cross-utilization of systems when making determinations. These systems will be maintained in the same configuration as operational equipment. **(T-3)**

11.15.4.2.4. - 11.15.4.2.7. DELETED.

11.15.4.2.7.1. Prior-to-use inspections will be conducted by the using organization employing a tailored weapon system pre-/post-dock checklist. **(T-3)**

11.15.4.2.7.2. Conduct periodic maintenance inspections using a tailored work deck. **(T-3)**

11.15.4.2.8. DELETED.

11.15.4.2.8.1. When changes in requirements occur, initiate a new memorandum.

11.15.4.2.8.2. Ensures copies of all GITA/TAA memorandums to the MAJCOM AVDO. **(T-2)**

11.15.4.2.9. DELETED.

11.15.4.2.10. DELETED.

11.15.4.2.10.1. Owning units not having maintenance capability will establish MOAs or MOUs with organizations which can provide maintenance support. **(T-2)**

11.15.4.2.11. - 11.15.4.2.11.2. DELETED.

11.15.4.2.12. DELETED.

11.15.4.2.12.1. When an item is removed or replaced, supervisors will ensure this action is documented in the aircraft forms. **(T-2)** Include the authority for removal (such as, message number, telecon, letters, and dates) and condition of installed/replacement items.

11.15.4.2.12.2. When the limited save list actions have been done, a copy of the completed list will be forwarded to the appropriate PM and the local documentation function which will be added to the TAA historical record. **(T-2)**

11.15.4.2.12.3. W&B handbook requirements will be maintained IAW TO 1-1B-50 and applicable -5 series TOs. **(T-2)**

11.15.4.2.12.4. Operating and maintenance technical data will be readily accessible whenever the GITA/TAA is in use or undergoing inspection. **(T-2)**

11.15.4.2.12.5. DELETED.

11.15.4.2.12.5.1. The GITA/TAA Manager must be qualified to operate GITA/TAA systems and appropriate support equipment to conduct GITA/TAA maintenance. **(T-3)**

11.15.4.2.12.5.2. The GITA/TAA Manager will accomplish and/or coordinate maintenance actions for the GITA/TAA and ensure GITA/TAA documentation is accurate and complete. **(T-3)**

11.15.4.2.12.5.2. **(AFGSC)** The designated individual will:

11.15.4.2.12.5.3. **(Added-AFGSC)** Ensure their aircraft has a current set of AFTO Form 781-series maintained IAW TO 00-20-1. **(T-2)**

11.15.4.2.12.5.4. **(Added-AFGSC)** Perform thorough forms review a minimum of every 30 calendar days.

11.15.4.2.12.5.5. **(Added-AFGSC)** Ensure their aircraft is scheduled for and undergoes preventive maintenance requirements. **(T-2)**

11.15.4.2.12.5.6. **(Added-AFGSC)** Monitor the status of removed parts and parts on order. **(T-2)**

11.15.4.2.12.5.7. **(Added-AFGSC)** Maintain required -21 equipment. **(T-2)**

11.15.4.2.13. For equipment designated as trainers, only the systems required for technical training (or those required to ensure safety or system integrity) need to be maintained. **Note:** This does not apply to "temporarily" grounded aircraft or operational equipment or systems on loan from MAJCOMs or ALCs.

11.15.4.2.13. **(AFGSC)** Establish written minimum operational systems guidelines and general maintenance requirements (wash interval, paint interval, etc.) for group training aircraft. **(T-2)**

11.15.5. Technical Data Applicability.

11.15.5.1. Operational systems on GITA/TAA are maintained IAW applicable technical data. The specific policy governing the use and modification of technical data is contained in TO 00-5-1.

11.15.5.1.1. Some systems may be operated and maintained with original contractor data because formal technical data was never developed and/or the contractor data was never assigned a TO number.

11.15.5.2. Inspection and lubrication requirements may be adjusted to correspond with training requirements and equipment usage and to prevent over or under inspection.

11.15.5.3. When significant savings may be achieved, the commander or contract project manager must request deviations or changes to technical data requirements, including substitution of materiel from the weapon system program manager.

11.15.5.3.1. If deviations are approved, the unit will retain approved deviations/changes in the GITA historical records. **(T-3)** In all cases, safety or design function must not be compromised.

11.15.5.4. TCTOs. The QA function or other designated agency will be responsible for determining applicability of TCTOs for GITAs. **(T-2)** TCTO upgrades are not required on TAA.

11.15.5.4.1. Ensure timely completion of TCTOs on systems designated for configuration management and proper configuration status accounting is maintained.

11.15.5.4.2. Accomplish TCTOs on systems not designated for configuration management as required to ensure safety of operation or as directed by the PM.

11.15.4.2.11.2. DELETED.

11.16. Aircraft Inlet/Intake/Exhaust Certification.

11.16.1. MAJCOMs will determine the requirement to implement an Aircraft Inlet/Intake/Exhaust Certification program and certification frequency requirements.

11.16.1. **(AFGSC)** All units will have an installed and uninstalled aircraft/engine intake/inlet/exhaust training and certification program. MXGs will identify the frequency requirements for certification. The program is applicable to B-1s, B-2s, B-52s, E-4s, UH-1s and MH-139s. **(T-2)**

11.16.2. DELETED.

11.17. Engine Run Training and Certification Program.

11.17.1. A comprehensive engine run certification program will be developed and strictly enforced to prevent safety mishaps and potential loss of life. **(T-2)**

11.17.1.1. DELETED.

11.17.1.2. All maintenance personnel authorized to start and operate aircraft engines, APUs, and uninstalled engines and APUs will be trained and certified to operate engines at TO determined power settings. **(T-2)**

11.17.1.3. Aircraft engine motoring will only be performed by qualified engine run personnel. **(T-2)** Exception: Rotary wing maintenance personnel qualified through OJT may motor engines IAW prescribed TO.

11.17.1.4. The following minimum requirements will be used to certify engine run personnel:

11.17.1.4.1. The MT will serve as the OPR and focal point for the management and development of the engine run certification program, engine run certification test question bank, and written tests for their respective weapon system. **(T-2)**

11.17.1.4.2. Pre-run training will be conducted in the trainee's work center through OJT. **(T-2)** Pre-run training is designed to prepare the trainee for successful completion of initial engine-run training. As a minimum, pre-run training will include:

11.17.1.4.2.1. An evaluation by immediate supervisor or NCOIC/Flight Chief to determine the individual's level of maturity and experience prior to being selected for engine-run training. **(T-2)**

11.17.1.4.2.2. The trainee will review and become familiar with engine-run operations to include emergency procedures IAW the applicable aircraft general system type TO and engine run checklist. **(T-2)**

11.17.1.4.2.3. MTs may develop a handout to facilitate learning engine-run procedures, engine limitations, and emergency procedures.

11.17.2. Certifying Officials. Certifying official certification requirements are listed in **Table 11.1**.

11.17.2.1. Instructor Pilots (IP) can also be used as certifying officials during the practical engine-run demonstration.

11.17.2.2. Certifying officials must maintain proficiency in the same manner as other technicians; certifying officials must recertify each other. **(T-2)**

11.17.3. Instructors. Individuals selected as instructors will possess a 7-skill level or civilian equivalent, a qualified contractor, or AFETS/CETS personnel. **(T-2)**

11.17.3.1. AFMAN 11-218, *Aircraft Operations and Movement on the Ground*, aircraft and engine TOs, commercial aircraft/engine operating procedures, and special test project engineering procedures will be used to develop engine run certification training programs. **(T-2)**

11.17.4. Installed Engine Run Personnel. Prior to entering engine run training, personnel will meet the following requirements:

11.17.4.1. Personnel will be selected IAW criteria established in **Table 11.1**. **(T-2)** MXG/CCs may designate contractors in writing to run aircraft engines.

11.17.4.2. Qualified to operate the aircraft APU as applicable. **(T-2)**

11.17.4.3. Qualified as a brake operator. **(T-2)**

11.17.4.4. Qualified in basic radio and interphone systems operation. **(T-2)**

11.17.4.5. Qualified on marshalling signals. **(T-2)**

11.17.5. The initial engine run certification program will consist of following three phases, each of which will be successfully completed before progressing to the next phase:

11.17.5.1. Phase 1. **(T-2)** Phase 1 is formal classroom training. Classroom instruction will include:

11.17.5.1.1. General aircraft familiarization to include, as a minimum, basic MDS airframe characteristic, aircraft safe-for-maintenance procedures, cockpit configuration and systems, throttles and aircraft controls, egress, normal and emergency braking systems, and aircraft system/subsystems related to safe engine operation. **(T-2)**

11.17.5.1.1. **(AFGSC)** Installation and removal of aircraft restraining devices or ballast load (if applicable). **(T-2)**

11.17.5.1.2. A thorough review of TO procedures with emphasis on and notes, cautions, and warnings. **(T-2)**

11.17.5.1.3. Engine/APU operation, to include normal operational parameters and limitations. **(T-2)**

11.17.5.1.4. Ensuring aircraft, engine, and APU emergency procedures are memorized. **(T-2)**

11.17.5.1.5. UHF/VHF radio operation, Air Traffic Control tower procedures, and emergency radio transmissions. **(T-2)**

11.17.5.1.6. A two-part closed book examination (students will successfully complete **Part I** before taking **Part II**). **(T-2)** The examination will consist of the following:

11.17.5.1.6. **(AFGSC)** The examination may be hard copy or digital form. **(T-2)**

11.17.5.1.6.1. **Part I** - Students will be given a written/computer-based examination on all boldface emergency procedures or all emergency procedures identified in applicable technical data requiring a passing score of 100 percent. **(T-2)**

11.17.5.1.6.2. **Part II** - Students will be given a written examination covering normal engine run procedures and limitations requiring a minimum passing score of 90 percent, corrected to 100 percent. **(T-2)**

11.17.5.1.6.2.1. **(Added-AFGSC)** The part II exam will have a minimum of 25 questions covering all subject areas excluding bold faced emergency procedures. **(T-2)**

11.17.5.1.7. Personnel failing the written/computer-based examination will receive additional instruction before being re-tested. **(T-2)**

11.17.5.1.8. Students will not be given the same **Part II** test during re-testing efforts. **(T-2)**

11.17.5.1.9. After a second failure of the two-part closed book examination, the SQ/CC (or equivalent) will determine if personnel may retest and continue with the program. **(T-3)**

11.17.5.2. Phase 2. **(T-2)** Phase 2 is simulator training. All maintenance personnel requiring engine run certification will receive simulator training on each specific aircraft MDS and APU. **(T-2)**

11.17.5.2. **(AFGSC)** At least 3 engine starts are required to confirm individual capability to operate engines. **(T-2)**

11.17.5.2.1. Phase 2 simulator training will be accomplished in an Aircrew Training Device, Cockpit Trainer, flight simulator, Maintenance Training Device, or approved Technology Development Trainer. **(T-2) Note:** If any of the above are not available, a similar MD(S) simulator may be used if the procedures are the same or "dry run" procedures will be accomplished in an aircraft to ensure procedural knowledge.

11.17.5.2.1. **(AFGSC)** Use of Simulators. Maintenance Training Section (MT) notifies the wing simulator training officer of Aircrew Training Devices (ATD) requirements.

11.17.5.2.2. As a minimum, students will demonstrate knowledge and proficiency in the following areas:

11.17.5.2.2.1. Proper run clearance procedures. **(T-2)**

11.17.5.2.2.2. UHF/VHF radio operation, Air Traffic Control tower procedures, and emergency radio transmissions. **(T-2)**

11.17.5.2.2.3. Normal APU, engine start, run, and shutdown procedures. **(T-2)**

11.17.5.2.2.4. Augmenter or thrust reverser operation (as applicable). **(T-2)**

11.17.5.2.2.5. Applicable aircraft systems/subsystems normal operating parameters. **(T-2)**

11.17.5.2.2.6. Ensure TO emergency bold face items are memorized. **(T-2)**

11.17.5.2.2.6.1. Instructors will evaluate the student on response time and ability to handle emergency situations to include egress procedures. **(T-2)**

11.17.5.3. Phase 3. **(T-2)** Phase 3 is practical demonstration. Each individual will receive a practical engine run evaluation after successful completion of Phase 1 and Phase 2 training. **(T-2)** For fighter-type aircraft, it is preferable to conduct the evaluation in an NSS, or on a trim pad. As a minimum, the student will demonstrate successful completion of the following areas without any discrepancies based on a go/no-go standard:

11.17.5.3.1. Run clearance procedures. **(T-2)**

11.17.5.3.2. UHF/VHF radio operation, Air Traffic Control tower procedures, and emergency radio transmissions. **(T-2)**

11.17.5.3.3. Normal APU, engine start, run, and shutdown procedures, including notes, cautions, and warnings. **(T-2)**

11.17.5.3.4. Augmenter or thrust reverser operation as applicable, including notes, cautions, and warnings. **(T-2)**

11.17.5.3.5. Applicable aircraft systems/subsystems normal operating parameters, including notes, cautions, and warnings. **(T-2)**

11.17.5.3.6. Ensure TO emergency bold face items are memorized. **(T-2)** Instructors will evaluate the student on response time and ability to handle emergency situations. **(T-2)**

11.17.5.3.7. Egress procedures. MAJCOM/Lead Command, TO, and checklist procedures for the applicable MDS will be demonstrated without error. **(T-2)**

11.17.6. Annual recertification for certifying officials and engine run certified personnel will be accomplished by successfully completing the written test (**Part I** and **Part II**) administered by the MT and demonstrating proficiency of normal and emergency procedures to a certifying official by operating one of the following: Aircrew Training Device, Cockpit Trainer, authorized Technology Development Trainer (if assigned or available), or aircraft as appropriate. **(T-2)**

11.17.6.1. Personnel failing the written examination will receive additional instruction before being re-tested. **(T-2)**

11.17.6.2. Students will not be given the same **Part II** test during re-testing efforts. **(T-2)**

11.17.6.3. After a second failure of the two-part closed book examination, the individual will be decertified. **(T-2)**

11.17.6.3.1. The SQ/CC (or equivalent) will determine if personnel may retest and continue with the program, and whether they must attend all three phases of initial training prior to being recertified. **(T-2)**

11.17.6.4. Certified individuals who PCS to the same MDS, and engine type and model must be approved by the SQ/CC (or equivalent) and complete an initial evaluation by a certifying official prior to becoming run qualified at the gaining base. **(T-2) Note:** MAJCOMs will determine if additional training is required for the specific engine series.

11.17.6.4. **(AFGSC)** Initial Evaluation is comprised of a Phase 3 Practical Demonstration evaluated by a Certifying Official if individual still meets 90 calendar day proficiency requirements. **(T-2)**

11.17.6.4.1. The evaluation will include, as a minimum, familiarization of local procedures and requirements. **(T-2)**

11.17.6.4.2. Carry over the date of original class completion from previous documentation (certificate, training record, MIS printout).

11.17.7. Documentation. Qualifications of installed engine run certifying officials and engine run certified personnel, will be documented in the MIS and entered on the SCR. **(T-2)**

11.17.7. **(AFGSC)** Track the following in the MIS: **(T-2)**

11.17.7.1. **(Added-AFGSC)** Annual engine run certification by MDS and Engine Type. **(T-2)**

11.17.7.2. **(Added-AFGSC)** Engine Run Certifier by MDS and Engine Type. **(T-2)**

11.17.8. Proficiency. MAJCOMs will determine proficiency requirements for maintenance personnel authorized to operate installed engines.

11.17.8. **(AFGSC)** To maintain proficiency, personnel qualified to run installed engines will perform at least one engine run every 90 calendar days. Certifying officials must also meet the 90 calendar day proficiency requirements. **(T-2)**

11.17.8.1. Units will track run proficiency requirements in the MIS. **(T-2)**

11.17.8.2. Supervisors will ensure individuals who fail to maintain proficiency are decertified. **(T-2)**

11.17.8.2.1. Decertified individuals will recertify IAW **Paragraph 11.17.6**. **(T-2)**

11.17.9. Engine run certification tests are controlled items and will be handled IAW DAFMAN 36-2664, *Personnel Assessment Program*, and administered only by MT personnel or regional training centers. **(T-2)**

11.17.10. Aircraft APU Installed Operation Training. The following requirements and standards will apply to qualifying maintenance personnel on operating the aircraft APU:

11.17.10.1. When conducting initial operator qualification training for APU, use the applicable video or other training program. **(T-2)**

11.17.10.2. A two-part closed book examination consisting of the following: **Note:** MAJCOMs will determine examination applicability requirements for PMA only APU operations in their supplement/addendum to this DAFI.

11.17.10.2.1. **Part I** - Students will be given a written/computer-based examination on all boldface emergency procedures or all emergency procedures identified in applicable technical data requiring a passing score of 100 percent**. (T-2)**

11.17.10.2.2. Students will successfully complete **Part I** before taking **Part II. (T-2)**

11.17.10.2.3. **Part II** - Students will be given a written/computer-based examination covering normal APU run procedures and limitations requiring a minimum passing score of 90 percent, corrected to 100 percent. **(T-2)**

11.17.10.3. Personnel failing the examination will receive additional instruction before being re-tested. **(T-2)**

11.17.10.4. Students will not be given the same **Part II** test during re-testing efforts. **(T-2)**

11.17.10.5. After a second failure of the two-part closed book examination, the individual will be decertified. **(T-2)**

11.17.10.5.1. The SQ/CC (or equivalent) will determine if personnel may retest and continue with the program prior to being recertified. **(T-2)**

11.17.10.5.2. Individuals must attend all three phases of initial training prior to being recertified. **(T-2)**

11.17.10.6. **Part III** Personnel must then accomplish an on-equipment practical evaluation for certification completion. **(T-2)**

11.17.10.7. Personnel will be recertified annually using the initial certification procedures. The practical evaluation portion will be accomplished by operating one of the following: Aircrew Training Device, Cockpit Trainer, authorized Technology Development Trainer (if assigned or available), or aircraft as appropriate (or as determined by the certifying official). **(T-2) Note:** Recertification is not required if the individual is engine run certified and has maintained annual engine-run certification requirements.

11.17.11. Documentation. Qualifications of APU run certifying officials and APU run certified personnel, will be documented in the MIS and entered on the SCR. **(T-2)**

11.17.11.1. If applicable, MAJCOMs will define SCR applicability requirements for PMA only APU operations in their supplement/addendum to this instruction.

11.17.12. Proficiency. MAJCOMs will determine proficiency requirements for maintenance personnel authorized to operate APUs.

11.17.12. **(AFGSC)** Personnel qualified to run aircraft APU will perform at least one APU run every 180 calendar days. Certifying officials must also meet the 180-calendar day proficiency requirement. **(T-2)**

11.17.12.1. Units will track run proficiency requirements in the MIS. **(T-2)**

11.17.12.2. Supervisors will ensure individuals who fail to maintain proficiency are decertified. **(T-2)**

11.17.13. Certification tests are controlled items and will be handled IAW AFI 36-2605 and administered only by MT personnel. **(T-2)**

11.17.14. Uninstalled Engine Operation on Test Stands and Cells (includes Jet Fuel Starter /APU uninstalled operations). All personnel identified for uninstalled engine run qualification will complete an uninstalled engine run training program prior to certification. **(T-2)** The following minimum requirements will apply:

11.17.14.1. Certification Requirements. Individuals will be certified for each specific engine TMS authorized to run IAW criteria established in **Table 11.1**. **(T-2)**

11.17.14.2. Certifying Officials will be designated IAW criteria established in **Table 11.1**. **(T-2)**

11.17.14.3. Instructors. Individuals selected as instructors will be 7-skill level or civilian equivalent, a qualified contractor, or an AFETS/CETS representative, and be run certified on each TMS (if they are to be certifying officials). **(T-2)**

11.17.14.4. Training. Uninstalled engine run training will consist of the following three phases:

11.17.14.4.1. Phase 1. Phase 1 is formal training. Instruction will include, as a minimum, the following areas:

11.17.14.4.1.1. General engine familiarization to include, as a minimum, basic engine description, component location, and functions. **(T-2)**

11.17.14.4.1.1. **(AFGSC)** Functions include engine system operation. **(T-2)**

11.17.14.4.1.2. Thorough familiarization of control cabs, NSSs, ETSs, and T-9 fire

suppression control panels (if applicable). **(T-2)**

11.17.14.4.1.3. Thorough review of TO procedures with emphasis on notes, cautions, and warnings. **(T-2)**

11.17.14.4.1.4. Uninstalled engine operation to include normal operating parameters and limitations. **(T-2)**

11.17.14.4.1.5. Ensuring uninstalled engine emergency procedures are memorized. **(T-2)**

11.17.14.4.1.6. Local communication procedures. **(T-2)**

11.17.14.4.1.7. A two-part closed book examination (students will successfully complete **Part I** before taking **Part II**) consisting of the following:

11.17.14.4.1.7.1. **Part I** - Students will be given a written/computer-based examination on all boldface emergency procedures or all emergency procedures identified in applicable technical data requiring a passing score of 100 percent. **(T-2)**

11.17.14.4.1.7.2. **Part II** - Students will be given a written/computer-based examination covering normal engine run procedures and limitations requiring a minimum passing score of 90 percent, corrected to 100 percent. **(T-2)**

11.17.14.4.1.7.2. **(AFGSC)** The Part II exam will have a minimum of 25 questions covering all subject areas excluding boldface emergency procedures. **(T-2)**

11.17.14.4.1.8. Personnel failing the examination will receive additional instruction before being re-tested. **(T-2)**

11.17.14.4.1.9. Students will not be given the same **Part II** test during re-testing efforts. **(T-2)**

11.17.14.4.1.10. After a second failure of the two-part closed book examination, the individual will be decertified. **(T-2)**

11.17.14.4.1.10.1. The SQ/CC (or equivalent) will determine if personnel may retest and continue with the program prior to being recertified or be removed from program. **(T-2)**

11.17.14.4.1.10.1.1. Individuals must attend all three phases of initial training prior to being recertified. **(T-2)**

11.17.14.4.2. Phase 2. Phase 2 is the control cab evaluation. After successful completion of formal training, students will properly demonstrate the following minimum requirements to a certifying official without discrepancies using the go/no-go standard:

11.17.14.4.2.1. Proper uninstalled engine start, run, and shutdown procedures, including notes, cautions, and warnings (engine not operating). **(T-2)**

11.17.14.4.2.2. Proper uninstalled engine boldface emergency procedures, including notes, cautions, and warnings (engine not operating). **(T-2)**

11.17.14.4.2.3. Knowledge of normal uninstalled engine operating limits, including notes, cautions, and warnings. **(T-2)**

11.17.14.4.2.4. Augmenter or thrust reverser operation (as applicable), including notes, cautions, warnings, and emergency procedures. **(T-2)**

11.17.14.4.3. Phase 3. Phase 3 is the practical evaluation. Each individual will receive a practical uninstalled engine run evaluation after successful completion of classroom training and control cab evaluation from a certifier. **(T-2)** As a minimum, the student will demonstrate successful completion of the following areas without discrepancies based on a go/no-go standard:

11.17.14.4.3. **(AFGSC)** Phase 3 Practical Demonstration will be evaluated by a certifying official who did not teach Phase 1 or Phase 2 to the trainee. **(T-2)**

11.17.14.4.3.1. Run clearance procedures. **(T-2)**

11.17.14.4.3.2. Emergency communication procedures. **(T-2)**

11.17.14.4.3.3. Normal uninstalled engine start, run, and shutdown procedures, including notes, cautions, and warnings. **(T-2)**

11.17.14.4.3.4. Augmenter or thrust reverser operation (as applicable), including notes, cautions, and warnings. **(T-2)**

11.17.14.4.3.5. Proper emergency procedure corrective actions during all bold face uninstalled engine emergency conditions. **(T-2)**

11.17.14.4.3.6. **(Added-AFGSC)** Troubleshooting and leak check procedures. **(T-2)**

11.17.14.4.3.7. **(Added-AFGSC)** Test stand/engine preparation (including proper restraint). **(T-2)**

11.17.14.5. Recertification. Recertification for certifying officials and uninstalled engine run qualified personnel will be accomplished annually. **(T-2)**

11.17.14.5.1. The following three requirements must be met to obtain recertification:

11.17.14.5.1.1. Successfully completing the written test (**Part I** and **Part II**) administered by the MT. **(T-2)**

11.17.14.5.1.2. Passing a control cab evaluation demonstrating knowledge of normal and emergency procedures to a certifying official. **(T-2)**

11.17.14.5.1.3. Completing a practical engine run demonstration. **(T-2)**

11.17.14.5.2. Personnel failing the written examination will receive additional instruction before being re-tested. **(T-2)**

11.17.14.5.3. Students will not be given the same **Part II** test during re-testing efforts. **(T-2)**

11.17.14.5.4. After a second failure of the two-part closed book examination, the individual will be decertified. **(T-2)**

11.17.14.5.4.1. The SQ/CC (or equivalent) will determine if personnel may retest

and continue with the program prior to being recertified. **(T-2)**

11.17.14.5.4.2. Individuals must attend all three phases of initial training prior to being recertified. **(T-2)**

11.17.14.6. Proficiency. MAJCOMs will determine proficiency requirements.

11.17.14.6. **(AFGSC)** To maintain proficiency, personnel qualified to run uninstalled engines on test stands and cells will perform at least one uninstalled engine run on a test stand or cell every 90 calendar days. Certifying officials must also meet the 90 calendar day proficiency requirements. **(T-2)**

11.17.14.6.1. Supervisors will ensure individuals who fail to maintain proficiency are decertified. **(T-2)**

11.17.14.6.1.1. Decertified individuals will recertify IAW **Paragraph 11.17.14.5**. **(T-2)**

11.17.14.7. **(Added-AFGSC)** Track the following in MIS if test cell is operational:

11.17.14.7.1. **(Added-AFGSC)** Annual uninstalled engine run certification by Type Make Series Modification (TMSM). **(T-2)**

11.17.14.7.2. **(Added-AFGSC)** Uninstalled Engine Run Certifier by TMSM. **(T-2)**

11.17.14.7.3. **(Added-AFGSC)** 90 calendar day uninstalled engine run proficiency requirements. **(T-2)**

11.17.14.8. **(Added-AFGSC)** Crew Size. The minimum requirements for uninstalled engine run crew are:

11.17.14.8.1. **(Added-AFGSC)** Minimum crew size is 3 personnel, except for small gas test stand that requires a minimum of two personnel. **(T-2)**

11.17.14.8.1.1. **(Added-AFGSC)** One crew member must be engine run certified and will be responsible for engine operation/trim. **(T-2)**

11.17.14.8.1.2. **(Added-AFGSC)** One person, separate from the engine run certified individual, is qualified as a test stand operator and trained on the fire control panel. **(T-2)**

11.17.14.8.1.3. **(Added-AFGSC)** Others, if not test stand/small gas test stand qualified, are briefed by the engine run certified person. At a minimum, the briefing includes emergency procedures and hazardous areas such as intake, exhaust, turbine/starter plane of rotation, high voltages, etc. **(T-2)**

11.17.15. Fire Control Panel Operation in NSS. This section applies to all NSS designed for enclosed aircraft and uninstalled engine operation (such as, T-9, T-10, T-11, T-12, and T-20) with fire suppression systems. Only qualified personnel will be certified to use the NSS Fire Suppression Systems. **(T-2)** The following certification requirements will apply:

11.17.15.1. Meet criteria established in **Table 11.1**. **(T-2)**

11.17.15.2. Training will consist of formal training using TOs and hands on familiarization and will include the following minimum requirements:

11.17.15.2.1. NSS Fire Suppression System familiarization and operation. **(T-2)**

11.17.15.2.2. Emergency procedures, including local notification procedures. **(T-2)**

11.17.15.3. NSS supervisor, contractor, AFETS/CETS personnel or individual designated by the NSS supervisor will serve as certifying official(s). **(T-2)**

11.17.15.4. Annual recertification of NSS Fire Suppression System certified personnel will be accomplished utilizing the same criteria as initial certification. **(T-2)**

11.17.15.4. **(AFGSC)** Track hush house and T-9/T-10/T-11 fire control panel annual recertification in the MIS. **(T-2)**

11.17.16. **(Added-AFGSC)** Engine run procedures: Units will ensure the following:

11.17.16.1. **(Added-AFGSC)** Establish unit engine run guidance, at a minimum include maximum RPM limitations for parking areas and other high traffic/congested areas. Also include minimum fuel loads or any local restrictions for engine runs. **(T-2)**

11.17.16.2. **(Added-AFGSC)** The fire chief determines if a fire fighting vehicle stands by in the immediate vicinity when an aircraft is in an isolated area. **(T-2)**

11.17.16.3. **(Added-AFGSC)** During preserved engine runs a fire fighting vehicle will be standing by and will be released at the discretion of the Pro Super. When used, this vehicle remains in position until the integrity of the fuel/oil system is verified. A standby fire fighting vehicle is not required during external fuel tank leak and transfer checks. Ensure adequate lighting is used during nighttime engine runs to facilitate leak detection. **(T-2)**

11.17.16.4. **(Added-AFGSC)** Notify the control tower and fire department anytime cartridge starts are scheduled. **(T-2)**

11.17.16.5. **(Added-AFGSC) [B-52 units]** When running more than four engines above idle concurrently, a qualified aircrew member is required on board. **(T-2)**

11.17.17. **(Added-AFGSC)** Maintenance personnel are not authorized to taxi aircraft. **(T-2)**

11.18. Engine Blade Blending Training and Certification Program.

11.18.1. General. All units will have a comprehensive training program to ensure technical standards are met, and proficiency is maintained. **(T-2)** The number of individuals authorized to inspect and repair blades should be sufficient to meet mission requirements and production needs. Personnel will be selected for certification IAW criteria established in **Table 11.1**. **(T-2)** MXG/CCs may designate contractors in writing to complete blade blending certification.

11.18.2. Responsibilities and Management. The MT or TD will be responsible for management and development of the blade blending training program. **(T-2)**

11.18.2.1. At a minimum, the course will include care and handling of equipment, applicable technical data, fault isolation/damage assessment/defect size determination, techniques required to correctly inspect and repair blades and performance of an engine blade blend. **(T-2)**

11.18.2.2. Prior to placement on the SCR, members must complete formal blade blending training (MT or TD course) and initial engine blade blending certification will be mandatory. **(T-2)**

11.18.3. - 11.18.3.3. DELETED.

11.18.4. Certification Officials. Certifying officials will be selected IAW criteria established in **Table 11.1**.

11.19. Engine Flexible Borescope Inspection Training and Certification Program. The purpose of this program is to ensure individual knowledge and proficiency levels; proper care and use of equipment; and standardization of program requirements.

11.19.1. All units maintaining engines using flexible borescopes will establish a comprehensive training program. **(T-2)** Certification procedures described here are only for engine borescope certification.

11.19.1. **(AFGSC)** MXG/CC will select maintenance instructors or TD instructors to provide training, (AFETS/CETS may be used as alternate instructors). At a minimum, courses will include care and handling of the equipment, all borescope/port locations to include all inspection requirements and procedures, all applicable technical data, fault isolation/damage assessment/defect size determination, and performance of an actual engine borescope. **(T-2)** **Note:** If applicable, assigned AFETS/CETS should be used to certify other certifying officials.

11.19.1.1. Training will be annotated in training records. **(T-2)**

11.19.2. MAJCOMs will:

11.19.2.1. Ensure an engine flexible borescope formal training course is developed, tracked, and managed by MT/TD.

11.19.2.1. **(AFGSC)** After completing formal training, the instructor signs off the trainee's individual training plan within an electronic training record. Ensure that all borescope inspections are loaded against the engine and not the aircraft. **(T-2)**

11.19.2.1.1. **(Added-AFGSC)** MT will ensure the following course codes are tracked in the MIS: **(T-2)**

11.19.2.1.1.1. **(Added-AFGSC)** Formal training borescope course. **(T-2)**

11.19.2.1.1.2. **(Added-AFGSC)** Proficiency requirement. **(T-2)**

11.19.2.1.1.3. **(Added-AFGSC)** Annual recertification. **(T-2)**

11.19.2.2. Ensure engine flexible borescope proficiency and annual recertification (by a certifying official) requirements are established by course code.

11.19.2.2. **(AFGSC)** Borescope proficiency for personnel maintaining aircraft with event-driven inspections only is 180 calendar days. Work center supervisors ensure personnel who do not meet minimum requirements are decertified and must be recertified by completing annual recertification requirements. **(T-2)**

11.19.2.2.1. **(Added-AFGSC)** Annual Recertification. Only certifying officials may recertify borescope-qualified technicians. This is accomplished by having technicians demonstrate proper inspection requirements, as well as use and care of equipment. **(T-2)**

11.19.2.3. Ensure time, training and documentation currency requirements are established for engine flexible borescope certified personnel who PCS to the same MDS/engine.

11.19.2.3. **(AFGSC)** Certified individuals who are to PCS to the same MDS and engine TMSM may bypass the formal training course. These individuals must be re-certified by a certifier prior to being added to the SCR. Carry over the date of original class completion from previous documentation (certificate, training record, MIS printout). **(T-2)**

11.19.2.4. Determine training requirements for personnel using borescopes for non-engine type inspections (such as, behind ejection seats, wing boxes) to include, as a minimum, proper use, and care of borescopes.

11.19.2.4. **(AFGSC)** Personnel using borescopes for non-engine type inspections (behind ejection seats, wing boxes, etc.) are not required to follow Engine Flexible Borescope Inspection Training and Certification Program procedures, but at a minimum must be trained on the proper use, handling and care of borescopes. Training must be annotated in training records. **(T-2)**

11.19.2.5. **(Added-AFGSC)** Special attention must be given to current safety TCTO/risk mitigating borescope inspections. Address background, technical procedures, and potential failure modes. **(T-2)**

11.19.2.5.1. **(Added-AFGSC)** All current TCTO and risk mitigating borescope inspections will be task evaluated by the certifying official. **(T-2)**

11.20. Flying Crew Chief (FCC) Program. The purpose of the FCC Program is to enhance mission effectiveness by providing qualified maintenance support for aircraft at locations other than home station. The FCC flies in Mission Essential Personnel status. FCC's typically fly with the aircraft for the purpose of accomplishing ground maintenance at the TDY location. The duty period typically starts when the FCC shows at the aircraft prior to departure. FCCs are qualified in their duty AFSC and are required to obtain, maintain, and apply basic knowledge in several other aircraft maintenance AFSCs. They are responsible for launch, recovery, inspection, servicing, generation, and maintenance of aircraft in austere locations and locations where specific MDS maintenance capability may not be available.

11.20.1. MAJCOMs may authorize/develop an FCC Program under the direction of AF/A4LM for maintainers who are required to regularly fly and maintain aircraft.

11.20.1.1. FCCs will be selected per mission requirements as directed by MAJCOMs and qualify for Special Duty Assignment Pay (SDAP) IAW AFI 36-3017, *Assignment Incentive Pay and Special Duty Assignment Pay*.

11.20.2. The FCC program only applies to personnel assigned to positions on the Unit Manning Document with a "C" prefix for the Duty AFSC.

11.20.3. The following situations will not qualify the FCC for SDAP:

11.20.3.1. Occasional flights where the aircraft is used as transportation in lieu of commercial air.

11.20.3.2. Incentive or indoctrination flights.

11.20.3.3. Deployments where additional maintenance personnel are required at the designated location to supplement assigned maintainers.

11.20.4. Qualifying missions. A mission consists of one or more sorties with a mission number as entered on the AFTO Form 781, *Aircrew/Mission Flight Data Document*. The mission must meet at least one of the following criteria to qualify for this program:

11.20.4.1. The FCC is required to accomplish maintenance at locations other than home station to prepare the aircraft for its next departure. **(T-2)**

11.20.4.2. The FCC is required to perform in flight maintenance tasks, if required IAW MDS TO requirements or Special/Alert sorties assigned with a mission number with documented agreement between the Operations and Maintenance Squadron Commanders. **(T-2)**

11.20.5. FCC Program responsibilities.

11.20.5.1. AF/A1PA oversees the overall SDAP and provides guidance in AFI 36-3017.

11.20.5.2. AF/A4LM is the SDAP functional manager for FCCs.

11.20.5.2.1. AF/A4LM sets criteria for FCCs, validates MAJCOM FCC reports, and forecasts FCC SDAP budget needs.

11.20.5.2.2. AF/A4LM approves/disapproves FCC position increases/decreases in coordination with AF/A1PA.

11.20.5.3. MAJCOMs implement the FCC Program and will appoint in writing an FCC Program Manager to enforce standards and prepare the annual report.

11.20.5.3. **(AFGSC)** HQ AFGSC/A4MA manages the AFGSC FCC program. **(T-2)**

11.20.5.4. MAJCOM FCC Program Managers will determine which squadrons will participate in the FCC Program and will:

11.20.5.4.1. Validate and forward squadron FCC SDAP requests (**Attachment 5**) to AF/A4LM and AF/A1PA.

11.20.5.4.2. Annually validate FCC SDAP positions.

11.20.5.4.3. Assign FCC SDAP positions with an AFSC prefix of "C" and an appropriate SEI on command manpower documents.

11.20.5.4.4. Establish command unique training requirements and set additional qualification standards for their FCCs as needed.

11.20.5.4.5. Maintain quarterly and annual FCC reports (**Attachment 3** and **Attachment 4**).

11.20.5.4.6. Prepare and submit the command annual FCC report to AF/A4LM at **AF.A4LM.Workflow@us.af.mil** and AF/A1PA by 15 August each year. Submit the biennial FCC report to AF/A1PA upon request.

11.20.5.4.7. Review and approve/disapprove ACR for changes of the “C” prefix to an AFSC on the UMD.

11.20.5.4.8. Review and recommend approval/disapproval of ACRs for additions, deletions of the “C” prefix to an AFSC on the UMD.

11.20.5.5. MAJCOM (A1M) Command Manpower and Organization Responsibilities. A1M will:

11.20.5.5.1. Coordinate and obtain approval/disapproval from MAJCOM for Installation Manpower and Organization Office ACRs pertaining to validation of "C" prefix to AFSCs on the UMD.

11.20.5.5.2. Assign the "C" prefix to AFSCs upon approval from MAJCOM FCC Program Manager. This provides MAJCOM functional managers and unit senior maintenance managers the visibility of squadron FCC SDAP positions. **Note:** FCC SDAP positions do not affect a unit's manpower authorizations.

11.20.5.6. SQ/CC's will:

11.20.5.6.1. Administer the squadron FCC Program IAW AFI 36-3017, AFMAN 36-2100, *Military Utilization and Classification*, and this instruction.

11.20.5.6.2. Ensure FCCs fly only when required for the mission. **(T-2)**

11.20.5.6.3. Appoint and remove personnel from the FCC Program IAW AFMAN 36-2100.

11.20.5.6.3.1. Assign FCCs for a minimum of one year, unless removed for cause. **(T-2)**

11.20.5.6.4. Ensure only qualified FCCs and assistant FCCs who meet minimum requirements IAW AFI 36-3017 receive SDAP and fly a minimum of three qualifying missions per quarter. **(T-2)** An indicator of having too many FCCs may be reflected in a unit whose FCCs routinely do not meet minimum quarterly requirements.

11.20.5.6.5. Assign no more than two FCCs per aircraft (an FCC and assistant FCC) to each qualifying mission unless otherwise approved by MAJCOM. **(T-2) Exception**: SQ/CC may assign the minimum number of additional FCCs when required to maintain proper work-rest cycles or to meet TO requirements.

11.20.5.6.6. Appoint in writing a Unit FCC Program Manager. **(T-2)**

11.20.5.7. Unit FCC Program Managers will:

11.20.5.7.1. Track status and prepare unit reports. **(T-2)**

11.20.5.7.2. Ensure personnel possess the appropriate SEI for their MDS aircraft. **(T-2)**

11.20.5.7.3. Provide a letter to their Installation Manpower and Organization Office and an information copy to the MAJCOM FCC Program Manager to change, add, or delete a "C" prefix to the AFSC on the UMD. **(T-2)**

11.20.5.7.3.1. The letter will contain the unit designation, function account code, AFSC, position number, and a POC. **(T-2)**

11.20.5.7.4. Ensure FCCs and assistant FCCs are aligned in a duty position with a "C" prefix by initiating an DAF Form 2096, *Classification/On-the-Job Training Action*, or special order. **(T-2)**

11.20.5.7.5. Counsel FCCs and assistant FCCs on SDAP termination (AFI 36-3017, **Table 3** lists reasons for termination). **(T-2)**

11.20.5.7.5.1. SDAP stops on the dates listed in this table. As long as a "C" prefix is attached to an AFSC the member will receive SDAP. **(T-2)**

11.20.5.7.6. Review, update, and authenticate the monthly SDAP roster. **(T-2)** The SDAP roster is the only administrative tool used to start, stop, or continue the FCC pay entitlement.

11.20.5.7.6.1. If changes are made on the monthly SDAP roster, an DAF Form 2096 or special order must be submitted to the Military Personnel Section (MPS). **(T-2)**

11.20.5.7.6.2. Authentication of the monthly SDAP roster validates that each FCC is meeting the full intent of the program. **Note:** AFI 36-3017 provides commanders conditions concerning pay entitlements.

11.20.5.7.7. Submit SDAP position increase/decrease requests to MAJCOM FCC Program Manager by message, e-mail, or letter stating the number of positions to be increased/decreased with a brief justification. **(T-2)**

11.20.5.7.7.1. MAJCOMs will forward requests to AF/A4LM for final approval.

11.20.5.7.8. Provide information for processing DD Form 1610, *Request and Authorization for TDY Travel of DoD Personnel*, for FCCs. **(T-3)**

11.20.5.7.9. Ensure TDY orders authorize FCCs to travel in Mission Essential Personnel status. **(T-2) Note:** Aeronautical orders do not apply to this program, as FCCs are not aircrew members.

11.20.5.7.10. Monitor training qualifications and currency to ensure only qualified FCCs are scheduled for missions. **(T-2)**

11.20.5.7.10.1. As a minimum, maintain a folder for each FCC containing training qualifications, immunizations, military passport information, appointment letters, and FCC Mission Reports. **(T-2)** If the unit mobility section already maintains these source documents, either electronic or paper copies may be maintained.

11.20.5.7.11. Coordinate scheduling of FCCs through Flight CC/Chiefs and operations schedulers. **(T-2)**

11.20.5.7.12. Maintain a Unit FCC Program Manager's Continuity Book. **(T-2)** As a minimum the continuity book will include:

11.20.5.7.12.1. Lists of required instructions with web addresses (including AFI 36-3017, AFMAN 36-2108 and this instruction). **(T-2)**

11.20.5.7.12.2. Unit FCC Program Manager appointment letter, DAF Form 2096 or special orders. **(T-2)**

11.20.5.7.12.3. Manpower correspondence assigning "C" prefix AFSC. **(T-2)**

11.20.5.7.12.4. Quarterly and annual FCC status reports, SDAP position requests and miscellaneous FCC and SDAP correspondence. **(T-2)**

11.20.5.7.13. Report program status by Fiscal Year (FY) quarters to MAJCOM FCC Program Manager NLT the 15th day of the month following each FY quarter and report FY annual program status to the MAJCOM NLT 15 July each year. **(T-2)**

11.20.5.7.13.1. Annual report will consist of the previous FY 4th quarter and current FY 1st, 2nd, and 3rd quarters (1 Jul - 30 Jun). **(T-2)**

11.20.5.7.14. Submit funding requests for flight clothing, per diem, and other related expenses for the annual budget (for safety during flight, flight clothing is mandatory for FCCs and Assistant FCCs). **(T-2)**

11.20.5.8. Installation Manpower and Quality Office will:

11.20.5.8.1. Forward ACR to MAJCOM to add, delete, or change "C" prefixes on AFSCs existing on the UMD. **(T-2)**

11.20.5.9. Enroute supervisors will:

11.20.5.9.1. Not assign FCCs to work other enroute aircraft. **(T-2)** However, FCCs left at an enroute location and awaiting transportation may be assigned to work other enroute aircraft.

11.20.5.9.2. Brief FCCs on local safety precautions, maintenance practices, and limitations. **(T-2)**

11.20.5.9.3. Coordinate with the Pilot in Command (PIC) and FCC to obtain transportation to/from quarters. **(T-2)**

11.20.5.10. The FCC will:

11.20.5.10.1. Establish duty shifts and rest periods with the PIC and enroute supervisor based on maintenance and mission requirements. **(T-2) Note:** Consider the duration of the flight, the ability to rest during the flight, and the quality of the rest during the flight. FCCs do not automatically enter crew rest with the aircrew upon arrival at an enroute/transient location unless the duty day was exceeded.

11.20.5.10.1.1. If the FCC's safety is jeopardized by fatigue, the FCC's duty day must end. **(T-2)**

11.20.5.10.2. Upon arrival at enroute locations, determine their ability to perform duties safely and effectively. **(T-2) Note:** The FCC's primary job is preparing the aircraft (inspect, service, aircraft forms maintenance) for the next mission.

11.20.5.10.2.1. Notify Tanker Airlift Control Center/Logistics Cell of planned crew rest periods and or establish an alternate point of contact during scheduled rest periods to minimize rest cycle interpretations. **(T-2)**

11.20.5.10.3. Coordinate with the PIC to ensure crew integrity for quarters is maintained. **(T-2)**

11.20.5.10.4. Coordinate with the PIC to ensure the FCC Performance Feedback Form in **Attachment 2** is completed by the PIC and provided the Unit FCC Program Manager upon return to home station. **(T-2)**

11.20.6. FCC qualifications and responsibilities.

11.20.6.1. FCCs should be a 2AX AFSC 5- or 7-skill level.

11.20.6.2. As a minimum, the FCC must be qualified and certified on the following MDS applicable items:

11.20.6.2.1. Possess a SEI of the aircraft assigned to the FCC. **(T-2)**

11.20.6.2.2. Refuel/defuel member and supervisor; concurrent servicing supervisor (as applicable). **(T-2)**

11.20.6.2.3. Tow member, tow supervisor, and tow brake operator. **(T-2)**

11.20.6.2.4. LOX/GOX servicing, nitrogen, and tire servicing. **(T-2)**

11.20.6.2.5. Tire and brake change; launch; recovery; marshalling; pre-flight, thru-flight and post-flight inspection. **(T-2)**

11.20.6.2.6. APU operation/quick air start system. **(T-2)**

11.20.6.2.7. Engine run. **(T-2)**

11.20.6.2.8. Kneeling operation and cargo door/ramp/visor operation on applicable MDS. **(T-2)**

11.20.6.2.9. All applicable powered/non-powered AGE. **(T-2)**

11.20.6.2.10. Qualified to operate, troubleshoot, service, and perform maintenance on their aircraft's critical systems as required by the MAJCOM. **(T-2)**

11.20.6.3. Assistant FCC qualifications and responsibilities.

11.20.6.3.1. Assistant FCCs must be a 5-level A1C or above with at least a SEI on their assigned aircraft and must accompany a fully qualified FCC. **(T-2)**

11.20.6.3.2. As a minimum, the Assistant FCC will be qualified and certified on the following MDS applicable items:

11.20.6.3.2.1. Refuel/defuel member. **(T-2)**

11.20.6.3.2.2. Tow member and tow brake operator. **(T-2)**

11.20.6.3.2.3. LOX/GOX servicing, nitrogen, and tire servicing. **(T-2)**

11.20.6.3.2.4. Tire and brake change; launch; recovery; marshalling; pre-flight, thru-flight and post-flight inspection. **(T-2)**

11.20.6.3.2.5. APU operation/quick air start system. **(T-2)**

11.20.6.3.2.6. Cargo door/ramp/visor operation on applicable MDS. **(T-2)**

11.20.6.3.2.7. All applicable powered/non-powered AGE. **(T-2)**

11.20.7. Work/rest plan (see **Chapter 1**).

11.20.8. MAJCOM FCC Program reporting.

11.20.8.1. MAJCOMs will forward a yearly report to AF/A4LM by 15 August.

11.20.8.2. Use previous FY 4th quarter, and current FY 1st, 2nd, and 3rd quarters. Late reports may postpone FCC waiver requests. Refer to **Attachment 3** and **Attachment 4** for reporting criteria.

11.20.9. Waivers.

11.20.9.1. Forward unit waiver requests to the MAJCOM FCC Program Manager, who will either disapprove/return to unit, or recommend approval/forward to AF/A4LM for final approval IAW DAFMAN 90-161. **(T-2)**

11.20.9.1.1. All approved waivers are reviewed annually as part of the annual report unless otherwise stipulated by the approval authority.

11.20.9.1.2. Waiver renewals. Submit a brief justification for waivers requiring renewal.

11.21. Maintenance of Flash Blindness Protective Devices.

11.21.1. MAJCOMs will define responsibilities across maintenance for sustainment of flash blindness protective devices for assigned aircraft in a supplement to this instruction. As a minimum, MAJCOM supplements will assign responsibilities that ensure:

11.21.1.1. Units maintain aircraft thermal protective devices, shields, and associated hardware IAW aircraft TOs.

11.21.1.2. Units will establish a training program to qualify individuals to install, inspect, and when required, seal aircraft thermal protective devices and shields. **(T-2)**

11.21.2. **(Added-AFGSC) BGS/** Aircraft Maintenance Squadrons are responsible for the following: **Note:** This paragraph is not applicable to B-1 or B-2 aircraft.

11.21.2.1. **(Added-AFGSC)** Ensure aircraft thermal protective devices, shields, and associated hardware is maintained IAW aircraft TOs and this instruction. **(T-2)**

11.21.2.2. **(Added-AFGSC)** Establish a program to train and qualify individuals to install, inspect, and when required, seal aircraft thermal protective devices and shields. **(T-2)**

11.21.2.3. **(Added-AFGSC)** Ensure procedures are developed that address the following:

11.21.2.3.1. **(Added-AFGSC)** Management of condemned thermal curtains used for training. **(T-2)**

11.21.2.3.2. **(Added-AFGSC)** Pre-generation inspection of thermal-protective devices. **(T-2)**

11.21.2.3.3. **(Added-AFGSC)** Sealing and certification of thermal-protective devices. **(T-2)**

11.21.3. **(Added-AFGSC)** AFE Flights/Sections are responsible for the following: **Note:** This paragraph is only applicable to B-52 and E-4 aircraft.

11.21.3.1. **(Added-AFGSC)** Train and task qualify AFE technicians to inspect and repair thermal protective devices and shields. **(T-2)**

11.22. WRM External Nestable Fuel Tank Build-Up. MAJCOMs will ensure units sustain the capability to support assigned wartime taskings. External Nestable Fuel Tank Build-Up is a

wartime capability, supported/tasked through a UTC to provide a critical wartime skill that compensates for the expenditure of aircraft fuel tanks (refer to **Chapter 4**). With exception of the core 2A6X4 personnel, augmentees may come from any group or squadron within the wing. MAJCOMs, as applicable, will:

11.22.1. Ensure units adhere to the direction outlined in their Mission Capability statement and DOC statement IAW DAFI 10-401 governing the quantity, size, and composition of fuel tank build-up teams.

11.22.2. Provide guidance for UDMs to ensure personnel tasked/selected for WRM Nestable Fuel Tank Build-Up team augmentees are not tasked for other wartime UTCs.

11.22.2.1. MAJCOMs must ensure UDMs responsible for deploying 2A6X4 personnel are designated as the focal point for WRM Nestable Fuel Tank Build-Up team assembly and are required to develop/maintain a written plan. The plan must be kept current, reviewed annually, and contain the following:

11.22.2.1.1. Specific manning positions across the wing to be tasked as Nestable Fuel Tank Build-Up team augmentees. **Note:** The applicable independent Nestable Fuel Tank Build-Up UTC Manpower Force Packaging System will be used as a guide to construct the teams.

11.22.2.1.2. Guidelines for activation of the tank build-up teams are established.

11.23. Protective Aircraft Shelters (PAS). MAJCOMs that possess PAS will publish guidance for aircraft maintenance operations in a PAS environment. At a minimum, MAJCOM guidance and procedures will address:

11.23.1. PAS marking and floor plans.

11.23.2. Electrical Requirements.

11.23.3. Refueling/Defueling Operations.

11.23.4. Shelter Door Operations.

11.23.5. Aircraft Engine Operation.

11.23.6. Aircraft Positioning inside the PAS.

11.23.7. Aircraft Winching (Hot/Cold).

11.23.8. Placement and Storage of Munitions in the PAS.

11.23.9. Collocating Nuclear and Conventional Munitions (AF Munitions).

11.23.10. External Fuel Tank storage.

11.23.11. PAS maintenance and Inspection requirements not covered by existing publications (such as, grounding and ventilation, mods).

11.24. Combat Sortie Generation. Combat sortie generation is a process by which mission capable aircraft are generated in a minimum amount of time, during peacetime or wartime, through separate 2AXXX and 2WXXX tasks or by Concurrent Servicing Operations. Combat sortie generation may include fueling, munitions/ammunition loading/unloading, aircraft reconfiguration, -6 TO inspections, and other servicing requirements, IAW applicable MDS TOs, Technical Order Data (TOD), IETM, TO 11A-1-33, *Handling and Maintenance of Explosives-*

Loaded Aircraft, TO 00-25-172 and other applicable directives. Procedures can be compressed through pre-positioning resources and concurrent performance of tasks.

11.24. (AFGSC) Combat Sortie Generation. Combat units will develop/maintain Hot Pit Refuel or Concurrent Servicing capability to maximize combat turnaround times. **(T-2)**

11.24.1. Wings will determine when to exercise combat sortie generation procedures. Procedures may be used during actual contingencies, scheduled exercises, and daily flying operations.

11.24.1. **(AFGSC)** Coordinate updates or any new generation plans with the Joint Nuclear Operations Center (JNOC) for evaluation. JNOC will forward its recommendation(s) to AFGSC and other appropriate agencies for review/approval. Reference AFGSCI 13-520-SV3, *(U) Bomber Nuclear Generation and Regeneration*, for more guidance. **(T-2)**

11.24.2. **(Added-AFGSC)** MXG/CC and/or OG/CC will notify PS&D and Wing Plans when Aircraft Generation Flow Plans require modification. PS&D will coordinate for the unit generation flow plans to be evaluated annually and chaired by the MXG/CC and OG/CC. The review will ensure effective use of resources and planning. BGSs/AMXSs, MOC, QA, Wing Weapons Manager (WWM), OSS, OG/CC, MXG/CC and PS&D will be in attendance. Once the annual review is completed, PS&D will sign AF IMT 2411. If there are changes to the plans, PS&D will coordinate the generation flow plans to be signed by MXG/CC, OG/CC and Wing/CC. Generation flow plans will be filed at a minimum within PS&D, Wing Plans, and MOC and placed on the inventory of record within AFRIMS. **(T-2)**

11.25. Hot Refueling Procedures. For the purpose of this instruction hot refueling is the transfer of fuel into an aircraft having one or more engines running. The purpose of hot refueling is to reduce aircraft ground time, personnel and equipment support requirements and increase system reliability by eliminating system shut down and subsequent restart. Refer to the following sources for additional guidance: TO 00-25-172, TO 00-25-172 CL-4, *Checklist -- Aircraft Fuel Servicing with R-9, R-11, and Commercial Fuel Servicing Trucks and with Fuels Operational Readiness Capability Equipment (FORCE)*, TO 37A9-3-11-lCL-l, *Checklist, Operational and Organizational Maintenance Hot Refueling and Hot Integrated Combat Turnaround Procedures, Aircraft Fuel Servicing Unit Type GRU 17/E Pantograph PACAF Type IV Hydrant Servicing*, and DAFMAN 91-203. **Exception:** N/A for MAJCOMs/Mx units not tasked to maintain hot pit refueling capabilities.

11.25. (AFGSC) Hot Refueling Procedures. Units will initiate hot refueling certification process with the site's installation commander. Additionally, units will notify AFGSC/A4A (B-1, B-2, B-52, and E-4) and AFGSC/A4B (UH-1/MH-139) upon initiation of hot refueling certification process. **(T-2)**

11.25.1. Hot Refueling Site Types. In addition, the process for certifying a site on Foreign Nation is outlined in section **11.25.8**. Personnel will not perform hot refueling operations until the location, equipment requirements, and personnel qualifications are certified IAW this instruction and TO 00-25-172. **(T-2)**

11.25.1.1. Site Certification. MAJCOMs will develop hot refueling site certification requirements. **(T-2)** Site certification team composition will be at a minimum IAW TO 00-25-172, **paragraph 6.5**. **(T-2)**

11.25.1.1. **(AFGSC)** Site Certifications. Installation commanders responsible for the site may authorize a virtual, in lieu of in-person site survey to accomplish hot pit site certification, when individual/team travel is not feasible.

11.25.1.1.1. The following questions will be addressed as part of the site certification:

11.25.1.1.1.1. Has the aircraft been approved by System Safety Engineering Analysis (SSEA) for hot pit refueling? **(T-3)**

11.25.1.1.1.2. Is adequate area provided to position the aircraft safely (evaluate ability to reposition due to wind direction)? **(T-3)**

11.25.1.1.1.3. Is the ramp level to prevent drainage that could cause environmental impact? Request the fire department dump water to verify flow, if questionable. **(T-3)**

11.25.1.1.1.4. Is the location adequate for the number of aircraft to be serviced? **(T-3)**

11.25.1.1.1.5. Has a hot brake holding area been established? **(T-3)**

11.25.1.1.1.6. Is there proper clearance between the hot pit area and hot brake holding area to prevent conflict? **(T-3)**

11.25.1.1.1.7. Is there proper clearance between the hot pit and Explosive Clear Zone/Hot Cargo Pad/Airfield Clearance Zones to prevent violations of any area/zone? **(T-3)**

11.25.1.1.1.8. Is the hot pit adequately clear of the aircraft/vehicle traffic area? **(T-3)**

11.25.1.1.1.9. Is the hot pit and cursory check area of the ramp clear of FOD potential? **(T-3)**

11.25.1.1.1.10. Does the location provide for rapid access of emergency equipment and egress of aircraft/equipment? **(T-3)**

11.25.1.1.1.11. Are adequate grounding points available? **(T-3)**

11.25.1.1.2. QA or responsible unit will maintain site certification documentation and a master listing of hot pit refueling sites administered by the MXG. **(T-2)**

11.25.1.1.2.1. QA or responsible unit will coordinate with Fuels Base Support Manager to ensure Base Support and Expeditionary (BaS&E) Planning Tool is updated for hot pit site certification listing any time sites are added, changed, or deleted. **(T-2)**

11.25.1.1.3. Each unit hot refueling site will be certified by a unit certification team, and approved by Installation Commander, when one of the following occurs:

11.25.1.1.3. **(AFGSC)** When certifying airports or host-nation locations, follow procedures outlined in applicable MAJCOM DAFI 21-101 supplements (e.g., PACAF). If not defined, contact the applicable MAJCOM A4 to determine hot pit site certification approval authority.

11.25.1.1.3.1. Construction of new hot refueling sites. **(T-2)**

11.25.1.1.3.2. Change in the unit MDS, or when an additional MDS is acquired. **(T-2)**

11.25.1.1.3.3. Change in refueling equipment. **(T-2)**

11.25.1.1.3.4. Changes in the certified site areas which affect/change in the previous certification. **(T-2)**

11.25.1.1.3.5. **(Added-AFGSC)** QA will provide the following:

11.25.1.1.3.5.1. **(Added-AFGSC)** A Certification Approval Request memo from MXG/CC to the Installation Commander. **(T-2)** Ensure memo addresses requirement for affected MAJCOMs IAW TO 00-25-172. The memo will contain the following:

11.25.1.1.3.5.2. **(Added-AFGSC)** List of the certification team members that participated in the survey (see **sub-paragraphs** to **11.25.1.1**) **(T-2)**

11.25.1.1.3.5.3. **(Added-AFGSC)** Ensure each question listed in **sub-paragraph**s to **11.25.1.1.1** are addressed. **(T-2)**

11.25.1.1.3.5.4. **(Added-AFGSC)** A copy of the new consolidated Hot Pit site certification listing. The listing will address each item detailed in **sub-paragraphs** to **11.25.2**. **(T-2)**

11.25.1.1.3.5.5. **(Added-AFGSC)** Local Checklists (LCL) for approval. Checklists must contain maps of Hot Pit sites, with details for pit set-up. This map should mirror map in site certification plan. **(T-2)**

11.25.1.1.3.5.6. **(Added-AFGSC)** Address local published procedures and additional precautions, IAW **paragraph 11.25.4**. **(T-2)**

11.25.1.1.4. - 11.25.1.1.10.4. DELETED.

11.25.2. Hot refueling site master listing. This listing must contain the following information for all hot refueling sites established and/or sustained by an AF installation or equivalent:

11.25.2.1. All sites must be identified by coordinates on a map. **(T-3)**

11.25.2.1.1. Each facility within the distance identified in TO 00-25-172, must be identified as to its use/contents and its distance in feet from the refueling site/operation. **(T-3)**

11.25.2.1.2. Other refueling sites, aircraft parking areas, also need to be identified and all distances must be shown even if a violation exists. **(T-3)**

11.25.2.1.3. The request cover letter will state if there are no violations. **(T-3)**

11.25.2.1.4. Procedures such as aircraft taxi routes should also be shown. Use arrows or dotted lines to show taxi directions, both entry and exit. **(T-3)**

11.25.2.1.5. Address any restrictions to normal operations and actions required IAW with TO 00-25-172. **(T-3)**

11.25.2.2. State the type of equipment used for hot refueling at each site, (such as, hose carts, truck). **(T-3)**

11.25.2.2.1. Show the location of any fixed fuel pits and usual location of cart or truck if used. **(T-3)**

11.25.2.2.2. Unit-approved sites will be identified on the aircraft parking plan. **(T-3)**

11.25.2.2.3. OSS, CE, and QA and will maintain copies of hot refueling sites on file. **(T-3)**

11.25.2.2.4. **(Added-AFGSC)** Initiating units will forward copies of all hot refueling site certification to AFSTRAT/A4 **8AF.LG@us.af.mil**.

11.25.2.3. State whether or not all hot refueling areas comply with the quantity-distance separation requirements of DESR6055.09_AFMAN 91-201 in relation to surrounding exposed sites/potential explosion sites.

11.25.3. Hot refueling requires detailed procedures be published in appropriate TOs and unit-developed Local Checklists. Unit Local Checklists will be developed IAW **Chapter 6** and include detailed procedures, normal and emergency, to meet requirements of the local environment. **(T-3)**

11.25.3.1. Units will forward Local Checklists to their respective QA office for approval. **(T-3)**

11.25.4. Units will publish procedures to supplement this section and outline local requirements and additional precautions as necessary for hot refueling, including hot refueling with ordnance, when authorized, IAW TO 00-25-172. **(T-3)**

11.25.5. Units tasked to perform hot refueling operations will ensure hot refueling crews are available to meet mission requirements. **(T-3)** MXS maintenance personnel may be utilized.

11.25.6. Temporary Sites. Temporary sites allow site certification and use for specific exercises, contingencies, and bare base operations in support of Agile Combat Employment. Temporary sites will be approved by installation commander or appropriate host. **(T-2)**

11.25.6.1. Temporary Site Certification. MAJCOMs will develop site certification team requirements. **(T-2)**

11.25.6.1.1. and 11.25.6.1.2. DELETED.

11.25.6.2. The following questions will be addressed as part of the site certification:

11.25.6.2.1. Has the aircraft been approved by system safety engineering analysis (SSEA) for hot pit refueling?

11.25.6.2.2. Is adequate area provided to position the aircraft safely (evaluate ability to reposition due to wind direction)?

11.25.6.2.3. Is the ramp level to prevent drainage that could cause environmental impact? Request the fire department dump water to verify flow, if questionable.

11.25.6.2.4. Is the location adequate for the number of aircraft to be serviced?

11.25.6.2.5. Has a hot brake holding area been established?

11.25.6.2.6. Is there proper clearance between the hot pit area and hot brake holding area to prevent conflict?

11.25.6.2.7. Is there proper clearance between the hot pit and Explosive Clear Zone/Hot Cargo Pad/Airfield Clearance Zones to prevent violations of any area/zone?

11.25.6.2.8. Is the hot pit adequately clear of the aircraft/vehicle traffic area?

11.25.6.2.9. Is the hot pit and cursory check area of the ramp clear of FOD potential?

11.25.6.2.10. Does the location provide for rapid access of emergency equipment and egress of aircraft/equipment?

11.25.6.2.11. Are adequate grounding points available?

11.25.6.3. - 11.25.6.5. DELETED.

11.25.7. Units will develop a checklist addressing the following at a minimum:

11.25.7.1. Required conditions and materials **(T-2)**

11.25.7.2. Site certification procedures **(T-2)**

11.25.7.3. Preparation for operations. **(T-2)**

11.25.7.4. Map Overlays **(T-2)**

11.25.8. Foreign nation site certification. Provides maintenance units the capability to conduct hot refueling operations. The completion of the site certification assures by MDS that safe hot refueling can be accomplished at locations in support of operations or exercises.

11.25.8.1. Unit Responsibility. At a minimum, requesting unit will accomplish hot refueling site certification IAW this instruction and TO 00-25-172. Owning/Host MAJCOM/A4 should be included in site certification process to help facilitate and advocate for required resources.

11.25.8.2. MXG QA Responsibility. MXG QA review site certification package prior to approval. Develop and maintain completed and approved site certification package. Completed package will be sent to MAJCOM/A4 for their records.

11.25.8.3. MAJCOM/A4 with Unit responsibility (i.e., ACC, AFGSC, etc.). Facilitate and advocate for requesting unit for required resources, as needed.

11.25.8.4. Host MAJCOM/A4 (i.e., PACAF, USAFE, etc.). In coordination with owing MAJCOM, facilitate and advocate for requesting unit for required resources, as needed. Develop and maintain file of approved packages.

11.25.8.4.1. - 11.25.8.4.5. DELETED.

11.25.8.5. Approval Authority. The requesting unit WG/CC is the approving official for the final site certification package. **Exception:** For deployed unit(s)/Task Force, commander with operational command is the approving authority for the final site certification package.

11.25.8.5.1. - 11.25.8.6. DELETED.

11.25.9. Hot Refueling Team Members and Duties. MAJCOMs will determine team member's prerequisites for each position. **(T-2)**

11.25.9.1. Pad Supervisor. Responsible for overall supervision of hot refueling operations when two or more aircraft are simultaneously hot refueled on the same pad (multiple hot refueling). Maintains full view and control of multiple hot refueling operations.

11.25.9.1.1. - 11.25.9.1.2. DELETED.

11.25.9.2. Refuel supervisor "A" member. Individual will be refuel task qualified, capable of supervising hot refuel crew. **(T-2)**

11.25.9.3. Refuel crew "B" member. Individual will be task qualified. **(T-2)**

11.25.9.4. Fuels specialist with 2F0X1 AFSC, or equivalent, "C" member. Individual will be refuel task certified on the specific facility/equipment, and task qualified for aircraft hot refueling. **(T-2)**

11.25.9.5. Additional refuel crew “D” member. Individual will be task qualified. **(T-2)** Use “D” members as required by applicable aircraft technical data.

11.25.10. Hot refueling team members and QA/Unit certifying officials/evaluators may be multi- MDS qualified.

11.25.10.1. After initial certification on each MDS, personnel must update their hot refueling currency by performing hot refueling on each MDS. **(T-2) Exception:** Fuels specialist will maintain certification and proficiency IAW DAFI 23-201, *Fuels Management*.

11.25.10.2. Section NCOICs/Chiefs will ensure personnel maintain proficiency on each MDS. **(T-2)**

11.25.11. Conducting Hot Refueling Training, Certification and Documentation. [For additional information, refer to AFI 11-235, *Specialized Refueling Operations*]. **Note:** Fuels specialist training will be conducted IAW DAFI 23-201 and CFETP. Qualification training of hot refueling personnel will be conducted in three distinct phases. **(T-2)** The three hot refueling qualification training phases are as follows:

11.25.11.1. Phase 1. “Familiarization” phase. Designated instructors familiarize trainees with applicable technical data, procedures, and guidance for hot refueling. Place special emphasis on procedures for hot refueling with ordinance loaded, when authorized.

11.25.11.2. Phase 2. “Hands-on” phase. Apply information learned in Phase 1 to develop in-depth knowledge and proficiency in all facets of hot refueling. Training will include proper operation, preventive maintenance, use of hand signals and emergency procedures. **(T-2)** Simulate hot refueling by performing all hot refueling tasks without aircraft engines running (cold pit). Designated instructors will demonstrate tasks then require trainees to perform tasks, practice emergency procedures, critique performance and provide additional training as required. **(T-2)**

11.25.11.3. Phase 3. “Demonstration/Certification” phase. Trainees will demonstrate hot refueling under the supervision of designated certifying officials with aircraft engine(s) running. **(T-2)** The Squadron Certifying Officials will certify individuals upon successful demonstration of hot refueling. **(T-2)** If Phase 3 training has not been completed within 30 days of Phase 2 training, Phase 2 training must be repeated. **(T-2)**

11.25.11.4. Qualification training will:

11.25.11.4.1. Stress safety requirements, emergency procedures and equipment inspection in all three phases of training. **(T-2)**

11.25.11.4.2. Ensure procedures in TO 37A9-3-11-1CL-1, TO 00-25-172, and TO 00-25-172CL-4 are taught to all team supervisors and members. **(T-2)**

11.25.11.4.3. Allow Phase 2 and Phase 3 training to be conducted utilizing joint sessions including 2F0X1 AFSC personnel and all maintenance AFSCs. **(T-2)**

11.25.11.4.4. Utilize both fuels (2F0X1) and maintenance AFSC instructors for joint sessions (T-2)

11.25.11.4.5. Be conducted by MT (QA if MT not available). **(T-2)**

11.25.11.5. QA hot pit certifying officials and QA hot pit certifier augmentees (squadron certifying officials) will train, evaluate, and certify unit personnel. **(T-2)** QA hot pit certifying officials will ensure augmentees conduct evaluations using procedures outlined in this instruction, applicable aircraft TOs and local procedures. **(T-2)**

11.25.11.6. DELETED.

11.25.12. Document training for personnel performing, evaluating, supervising, or instructing hot refuel operations as follows:

11.25.12.1. Document all aircraft maintenance and 2F0X1 AFSC personnel Phases 1, 2, and 3 initial training in MyLearning. **(T-2)**

11.25.12.1.1. For AFSCs where "refuel aircraft with engines operating" is not contained in MyLearning, use DAF Form 797/MIS to document initial hot refuel training. **(T-2)**

11.25.12.1.2. Track recurring hot refueling certification in the MIS (initial and annual) IAW with TO 00-25-172 and this DAFI. **(T-2)**

11.25.12.2. 2F0X1 AFSC personnel will use MyLearning/DAF Form 1098, *Special Tasks Certification and Recurring Training*, to document Phases 1, 2, and 3 initial/recurring hot refuel training. **(T-2)** Fuels (2F0X1) certifying officials will be appointed by the LRS/CC IAW DAFMAN 36-2689. **(T-2)**

11.25.13. Track hot refueling members, by position, on the SCR. **(T-2)**

11.25.14. Unique proficiency, certifying, and decertifying actions for hot refuel team members will be outlined in MAJCOM supplements/addendums to this DAFI. **(T-2)**

11.25.15. **(Added-AFGSC)** Training and certification requirements for hot refuel team members are outlined in **Table 11.2**. **(T-2)**

11.25.15.1. **(Added-AFGSC)** Personnel are decertified if they miss any semi-annual proficiency requirement or annual special requirement. Personnel can also be decertified by any hot/aircraft- the owning supervision any time one of these individuals sees an unsafe act or demonstrated lack of proficiency on the part of any hot/aircraft-to-aircraft refueling team member. **(T-2)**

Table 11.2. (Added-AFGSC) Hot Aircraft Refueling Training/Certification Requests. (T-2)

Position	Required Qualification Training	Proficiency Requirements	Special Requirements
QA Hot Refueling	Phases I, II, III	N/A	One-time EPE by QA Chief Inspector.
Certifiers	Phases I, II, III		
Squadron Hot Refueling Certifiers	Phases I, II, III	Hot Refuel Semi-Annually	One time PE by QA Hot Refueling Certifier; Augmentee Squadron Certifiers will maintain currency and recertify annually by another hot refueling certifier for task qualification.
Pad Supervisor	Phases I, II, III	Hot Refuel Semi-Annually	Annual Evaluation by QA or Squadron Certifier.
Refuel A, B, C, D Member	Phases I, II, III	Hot Refuel Semi-Annually, "C" Annually	Annual Evaluation by QA or Squadron Certifier.
Decertified Squadron Certifier or Pad Supervisor	Repeat Phases II, III		Recertification must start within 90 calendar days, or Phase I will also be completed PE by QA Chief Inspector.
Decertified A, B, C, D	Repeat Phases II, III		Recertification must start within 90 calendar days, or Phase I will also be completed.

11.26. Aircraft Rapid/Hot Defueling.

11.26.1. Rapid defueling presents hazards which are not normally encountered in normal defueling operations. Owning MAJCOMs will develop and sustain a rapid defueling capability to meet routine and contingency mission requirements IAW TO 00-25-172 and MDS-specific TOs.

11.26.1.1. Rapid defueling operations are considered hot defueling operations whenever the provider/source aircraft has an engine running.

11.27. 406 MHz Emergency Locator Transmitter Systems Program.

11.27.1. Units will ensure procedures are established to update the Emergency Locator Transmitter registration database whenever 406 MHz Emergency Locator Transmitter–equipped aircraft are transferred to other commands/wings, Emergency Locator Transmitter that are taken out of service, removed for maintenance, or destroyed. **(T-0)**

11.27.2. Aircraft maintenance functions must register and track status of fixed-mounted aircraft 406 MHz Emergency Locator Transmitter systems. **(T-0)**

11.27.3. IAW DoDI 3002.02, *Personnel Recovery and 406 MHZ Search and Rescue (SAR) Emergency Beacons in the Department of Defense*, USAF 406 MHz Emergency Locator Transmitter systems must be registered in the DoD Joint Search and Rescue Satellite Aided Tracking Electronic Tracking System database. **(T-0)**

11.27.3.1. The POC for JSETS registration is the Personnel Recovery Mission Software Help Desk at **PRMSMail@jricp.osis.gov**.

11.27.3.2. The governing agencies are the Joint Personnel Recovery Agency and the Electronic Services Command at Hanscom AFB, MA. Refer to AFMAN 10-207, *Command Posts*, for Command Post or C2 function responsibilities regarding 406 MHz Emergency Locator Transmitter and Personal Locator Beacon systems.

11.28. Crashed, Damaged or Disabled Aircraft Recovery (CDDAR) Program.

11.28.1. Installation/WG/CCs responsible for active airfields/runways, and flying missions will implement a CDDAR Program IAW TO 00-80C-1, *Crashed, Damaged, Disabled Aircraft Recovery Manual*. **(T-2)** The program must be designed to provide a response and/or recovery capability of assigned host, tenant, and consider transient aircraft consistent with the following considerations: (1) urgency to open the runway for operational use; (2) prevention of secondary damage to the aircraft; and (3) preservation of evidence for mishap or accident investigations IAW DAFI 91-202 and DAFI 91-204.

11.28.2. Responsibilities:

11.28.2.1. MAJCOMs will:

11.28.2.1.1. Ensure flying units maintain a CDDAR capability IAW 00-80C-1.

11.28.2.1.2. Designate a MAJCOM CDDAR OPR. As a minimum, the CDDAR OPR will:

11.28.2.1.2.1. Standardize CDDAR equipment inventory accountability and reporting requirements by MDS for all on hand CDDAR equipment prescribed by TO 00-80C-1, allowance standard and applicable weapons system TOs across assigned units with active airfields/runways.

11.28.2.1.2.1.1. Review unit's annual CDDAR equipment inventories to identify and document equipment shortfalls.

11.28.2.1.2.1.2. Coordinate AS change request with the applicable AFMC AS activity IAW AFI 23-101.

11.28.2.1.2.1.3. Ensure excess CDDAR equipment is redistributed to fill internal shortfalls prior to units turning equipment into supply/DLADS as excess.

11.28.2.1.2.2. Participate as member of CDDAR Working Group. **(T-2)**

11.28.2.2. AETC will:

11.28.2.2.1. Develop, sustain, and administer the CDDAR training program.

11.28.2.3. AFMC will:

11.28.2.3.1. Utilize AFSC/LZDB to serve as AF CDDAR Program OPR (**AFSC.LZDB.CDDAROPR@us.af.mil**) with the following responsibilities:

11.28.2.3.1.1. Provide CDDAR Program guidance to MAJCOM CDDAR OPRs. **(T-2)**

11.28.2.3.1.2. Provide routine communication to MAJCOM CDDAR OPRs on relevant matters such as new technology, guidance changes, significant events, equipment recall notifications, and best practices. **(T-2)**

11.28.2.3.1.3. Coordinate and consolidate MAJCOM CDDAR OPR inputs on CDDAR policy, training, and technical data, and present this information to the appropriate agency as required. **(T-2)**

11.28.2.3.1.4. Develop, manage, and chair a CDDAR Working Group to address equipment requirements, priorities, and funding. The CDDAR Working Group members will consist of MAJCOM CDDAR OPRs. The CDDAR Working Group will make efforts to gain economy of scale when requesting new equipment. **(T-2)**

11.28.2.3.2. Provide approved tech-data outlining equipment procedures to safely respond and/or recover aircraft from a CDDAR event.

11.28.2.3.3. Provide timely engineering support to facilitate resolution of unique CDDAR events which cannot be resolved by existing tech-data.

11.28.2.3.4. Develop, manage, and maintain AS needed to sustain a weapon system for peacetime and wartime operations IAW AFI 23-101.

11.28.2.4. - 11.28.2.5.7. DELETED.

11.28.2.6. CDDAR Team Chief and alternate will:

11.28.2.6.1. Be designated as the unit's subject matter expert on aircraft recovery operations and equipment and will be thoroughly familiar with and perform their Team Chief duties IAW TO 00-80C-1. **(T-2)**

11.28.2.6.1. **(AFGSC)** CDDAR Team Chiefs will be assigned for a minimum of 24 months. **(T-2)**

11.28.2.6.2. **(Added-AFGSC)** Track individual team member training requirements using the following IMDS Course Codes: 310523, J3AAR2AXXX 048B Basic formal CDDAR training course, 016010, Aircraft CDDAR Team Member (initial), and 016044, CDDAR Team Member (annual). **(T-2)**

11.28.2.6.3. **(Added-AFGSC)** In addition to team member courses, Team Chiefs will use IMDS Course Codes: 003840: Aircraft CDDAR Team Chief Certification, and 022219: Aircraft CDDAR Team Chief Lift (three-year requirement per TO 00-80C-1). **(T-2)**

11.29. Aircraft Battle Damage Repair (ABDR). ABDR is an effective force multiplier contributing to wartime sortie production by assessing and repairing battle damaged aircraft rapidly to support flying operations. ABDR repairs will be accomplished during contingency or wartime only. However, weapons system program managers may approve ABDR repairs during peacetime on a case-by-case basis using trained ABDR Technicians.

11.29.1. Responsibilities:

11.29.1.1. The Directorate of Logistics (AF/A4L) will provide overall policy and guidance for the USAF ABDR Program.

11.29.1.2. AFMC will:

11.29.1.2.1. Assume management responsibility for USAF ABDR Programs.

11.29.1.2.2. Publish a MAJCOM instruction to implement the ABDR requirements contained in this instruction.

11.29.1.2.3. Develop and manage ABDR policy for pre-positioning of tools, materiel kits, related SE, and management of ABDR training aircraft.

11.29.1.2.4. Support development and publication of ABDR TOs for new weapon systems.

11.29.1.2.5. Maintain ABDR UTCs for AFMC organizations.

11.29.1.2.6. Plan for and develop capability to repair battle/crash damaged aircraft.

11.29.1.2.6.1. Ensure plans include procedures to add additional repair capabilities into operating locations and provide aircraft evacuation alternatives.

11.29.1.2.7. Plan, program, and submit ABDR funding requests.

11.29.1.2.8. Maintain an ABDR Technical Support Office to advocate and provide day-to-day management of tasks associated with development, implementation, maintenance, and support needed to enhance the USAF ABDR capability.

11.29.1.2.9. Provide support in determining technical requirements, repair techniques, repair materials, assessment aids and Research & Development (R&D) efforts.

11.29.1.2.10. Manage TO 1-1H-39, *Aircraft Battle Damage Repair General Technical Manual*, and the engineering handbook for ABDR engineers and support initiatives to develop, publish, and maintain weapon system-specific –39 TOs.

11.29.1.2.11. Ensure the status of aircraft permanently grounded for ABDR training is reported IAW DAFI 21-103.

11.29.1.2.12. Establish Aircraft Battle Damage Evaluator training program, manage course documentation and provide training to MT Instructors as required. **(T-2)**

11.29.1.3. MAJCOMs will:

11.29.1.3.1. Establish a command focal point to work ABDR issues with AFMC.

11.29.1.3.2. In conjunction with AFMC, develop a command ABDR Concept of Operations and ensure Concept of Operations covers unit plans for repair of battle/crash damaged aircraft during combat operations.

11.29.1.3.2.1. Address ABDR in mission need statements for new weapon systems that support or engage in combat operations.

11.29.1.3.2.2. Incorporate ABDR in command war planning documents.

11.29.1.3.2.3. Task AFMC ABDR UTCs to support OPLANs.

11.29.1.3.2.4. Develop plans for the reception and employment of AFMC ABDR teams at the onset of hostilities.

11.29.1.3.2.5. Formalize integration and bed down requirements in applicable BSP IAW AFI 10-404.

11.29.1.3.2.6. Provide unit level weapon-system-specific tools (other than common hand tools) and equipment needed to repair battle/crash damaged aircraft.

11.29.1.3.2.7. USAFE and Pacific Air Forces (PACAF) will store and maintain serviceability, accountability, and status reporting to include Financial Improvement and Audit Readiness reporting of AFMC owned and provided WRM ABDR trailers IAW established procedures. **(T-2)**

11.29.1.3.2.8. Provide technical support to the ABDR Technical Support Office for live fire or similar testing.

11.29.1.3.3. – 11.29.1.3.10. DELETED

11.29.1.4. Unit Responsibilities. Units will:

11.29.1.4.1. Utilize trained Aircraft Battle Damage Evaluators to evaluate aircraft battle damage and mishap damage sustained during combat or contingency operations. **(T-3)**

11.29.1.4.2. Ensure shelf-life items listed in TO 1-1H-39 and weapon system-specific –39 TOs are maintained at required levels to support ABDR requirements. **(T-3)**

11.29.1.4.3. Ensure aircraft battle damage is documented on an AFTO Form 97, *Aerospace Vehicle Battle Damage Incident Debrief/Assessment/Repair Record* or AFTO Form 97B, *Aircraft Battle Damage Evaluator Checklist* as required IAW TO 1-1H-39. Completed forms will be forwarded to the Aircraft Battle Damage Repair Program Office. **(T-2)** CLASSIFIED messages must be sent to SIPR: **usafsaf.wright-patt.afsc-lg.mbx.afsc-lzd-abdr-tso@mail.smil.mil** and UNCLASSIFIED messages must be sent to NIPR: **AFSC.LZD.ABDRTSO@us.af.mil** for filing in the historical archives. **(T-2)**

11.29.1.5. Aircraft Battle Damage Evaluator/Training:

11.29.1.5.1. Aircraft Battle Damage Evaluator training provides MXG/CC's with ABDR knowledgeable forces and prepares units to execute Air Tasking Orders in a denied airspace with potential heavy losses. Aircraft Battle Damage Evaluator roles and responsibilities are outlined in TO 1-1H-39.

11.29.1.5.2. Maintenance Supervision will determine the proper mixture of personnel to attend Aircraft Battle Damage Evaluator training. **(T-3)**

11.29.1.5.3. Aircraft Battle Damage Evaluator formal training will be IAW the approved ABDR course control documents. **(T-2)**

11.29.1.5.4. Aircraft Battle Damage Evaluators will complete unit provided refresher training every 24 months. **(T-2)**

11.29.1.5.5. Course documents and instructor training is provided by the ABDR Technical Support Office NIPR, and can be requested at: AFSC.LZD.ABDRTSO@us.af.mil

11.30. Egress/Cockpit Familiarization Training.

11.30.1. All non-egress personnel who access aircraft cockpits with egress systems maintained and managed by 2A6X3 Egress Systems personnel must complete initial and refresher familiarization training. **(T-2)**

11.30.1.1. As a minimum, initial and refresher egress/cockpit familiarization training will include location and installation procedures of egress system safety devices, cockpit entry/exit procedures, procedures for determining whether or not an egress component is expended, emergency procedures associated with an expended egress component, and local maintenance concerns identified by the egress work center supervisor. **(T-2)**

11.30.1.2. New personnel to the unit must receive initial familiarization training prior to accessing cockpits unless last duty position involved same mission design aircraft as current duty position. **(T-2)**

11.30.1.3. Personnel not requiring initial training will attend refresher training when they become due. **(T-2)**

11.30.1.4. Initial egress familiarization training will normally be hands-on using an aircraft. **(T-2)**

11.30.1.4.1. Due to the diverse egress systems across all weapon systems, units desiring to use an aircraft maintenance trainer in lieu of an aircraft must submit a request from the MXG/CC to the MAJCOM for approval/disapproval. Approving MAJCOM must coordinate with the MDS lead command to ensure no technical/other mitigating factors exist and to provide transparency. **(T-2)**

11.30.1.5. Refresher familiarization training will be conducted annually using an aircraft, maintenance trainer or media, which is approved and designated by the egress work center supervisor. **(T-2)**

11.30.1.5.1. Non-egress personnel may administer training media (slideshow/video) during refresher familiarization training.

11.30.1.5.2. Direct students to the egress section if technical assistance is required and/or questions are raised concerning course subject matter.

11.30.1.6. Only egress personnel, certified on assigned egress system(s), should instruct initial egress familiarization training. **(T-2)** MXG/CC may authorize MT personnel to instruct this training provided they are currently certified to perform egress maintenance.

11.30.1.7. Training media must meet approval of the 2A6X3 AFSC MAJCOM Functional Manager (MFM) or current media produced by the 367 Training Support Squadron listed on the Defense Imagery at **http://www.defenseimagery.mil. (T-2)**

11.30.1.8. Individuals overdue for annual egress familiarization training will not access aircraft cockpits until they complete familiarization training. **(T-2)**

11.30.1.9. Units with unique, experimental, or test aircraft requirements.

11.30.1.9.1. If training courses are not available through AETC, units must use interagency training before considering non-government training sources. **(T-2)**

11.30.1.9.1.1. If courses in both of these sources are not available, units will establish a documented training program that meets the intent of this instruction. **(T-2)**

11.30.1.9.1.2. Training will be conducted by the most qualified personnel and must be approved by the MFM prior to implementation. **(T-2)**

11.30.2. MAJCOMs in coordination with the applicable lead command will identify emergency aircraft egress/evacuation training and frequency requirements in their supplement to this DAFI for personnel assigned to weapon systems that do not have aircraft egress systems maintained and managed by 2A6X3 personnel.

11.31. Aircraft Defensive Systems Loading Program.

11.31.1. Aircraft Defensive Systems Loading Program provides instruction required to install/remove chaff/flare on unique mission aircraft in units where there are no 2W1 AFSC authorizations assigned.

11.31.2. Authorized units will establish a program to train and qualify personnel to perform these tasks IAW procedures outlined in DAFMAN 21-201 and this **Chapter**.

11.31.3. Units will work with the installation Weapon System Manager (WSM) and Airfield Operations Flight to develop written instructions for handling chaff/flare-loaded aircraft IAW DESR6055.09_AFMAN 91-201 and DAFI 91-202.

11.31.3.1. As a minimum, written instructions will include procedures for launch/recovery/parking of chaff/flare-loaded aircraft; chaff/flare storage and transportation; and partially ejected flares and minimum requirements outlined in DESR6055.09_AFMAN 91-201.

11.31.4. The MXG/CC will appoint 7-skill or 9-skill level individual with maintenance AFSC as the Weapons Task Qualification Manager (WTQM). **(T-2) Note:** Units with 2W1 AFSCs assigned will comply with training/qualification requirements in **Chapter 10**.

11.31.5. WTQM and Weapons Task Qualification Crew (WTQC) responsibilities. The WTQM/WTQC provide oversight of chaff/flare loading operations to ensure they are conducted safely by providing initial and recurring load training, serving as the focal point for all chaff/flare loading issues, and observing loading operations during training. The WTQM and WTQC will not participate in load operations during training. **(T-2)**

11.31.5.1. WTQM. The WTQM typically holds a 2A871X AFSC; however, other flightline personnel with the 2AX7X AFSC may perform this function. The WTQM develops and oversees the chaff/flare loading standardization program, sets standards, and develops local policies and procedures. The WTQM will be tracked on the SCR. **(T-2)** The WTQM will:

11.31.5.1.1. Receive initial and recurring load qualification training from a WTQC and maintain currency on chaff/flare loading tasks. **(T-2)**

11.31.5.1.2. Once trained and qualified, the WTQM will develop and administer the unit's chaff/ flare load training program and train/qualify home station WTQC

personnel. **(T-2) Note:** In the event a unit is initially tasked and has no qualified instructors, it will be necessary for the WTQM to become certified at a unit with qualified trainers. The WTQM will:

11.31.5.1.2.1. Ensure sufficient numbers of personnel are qualified to load chaff/flare to support the unit's mission requirements. **(T-2)**

11.31.5.1.2.1.1. A course code will be loaded in the MIS to identify trained personnel and qualification status. **(T-2)**

11.31.5.1.2.2. Establish time standards for initial and recurring loading tasks. **(T-2)**

11.31.5.1.2.2.1. Lead wings will develop time standards for each MDS for qualification purposes. **(T-2)**

11.31.5.1.2.2.2. The senior evaluator has the discretion to add to the time standard if inclement weather or equipment failure is the cause for exceeding the time standard.

11.31.5.1.2.3. As a minimum, the WTQM will identify the number of qualified personnel, names and employee numbers, MDS qualification, Defensive Systems, equipment type, qualification date, and date(s) recurring training is due. **(T-2)**

11.31.5.1.2.4. The WTQM will select, train, evaluate, and qualify a minimum of two personnel as the WTQC on safe and reliable munitions loading procedures. **(T-2)**

11.31.5.1.2.4.1. The WTQM will evaluate and re-certify WTQC members annually. **(T-2)** WTQC members will be tracked on the SCR. **(T-2)**

11.31.5.1.3. Review and approve/disapprove RCs that pertain to chaff/flare loading technical data. **(T-2)**

11.31.5.1.4. Develop a local Task Assignment List by utilizing lead wing-developed MDS-specific Task Assignment Lists for use during training for all chaff/flare loading operations. **(T-2)** A Task Assignment List is derived from applicable MDS munitions load checklist (TO 33-1-20-series) and identifies the load crew members' responsibilities by step.

11.31.5.1.5. Ensure chaff/flare loading CTKs are standardized to the maximum extent possible. **(T-2)**

11.31.5.1.5.1. Chaff/flare loading CTKs must include all tools and equipment necessary to support applicable MDSs and AME configurations. **(T-2)**

11.31.5.1.6. Coordinate the scheduling of personnel for chaff/flare load training. **(T-2)**

11.31.5.1.6.1. The WTQM may delegate this duty to the WTQC.

11.31.5.1.7. Coordinate with PS&D, or the Regional Training Center, if applicable, to obtain chaff/flare dispensing system-equipped aircraft for training purposes. **(T-2)**

11.31.5.1.8. Ensure training magazines match the characteristics and "feel" of live magazines (such as, weight, dimensions). **(T-2)**

11.31.5.2. WTQC. The WTQC assists the WTQM in managing the chaff/flare loading standardization program. The WTQC's primary purpose is to train and qualify personnel to load chaff/flares but may also perform chaff/flare load duties. The lead WTQC member is typically a 7-skill level technician with the 2AX7X AFSC. Initial training will be conducted using inert munitions. **(T-2)** The number of trained WTQC members should be based on current/anticipated workloads and their ability to maintain proficiency on all applicable MDSs. WTQC members are qualified by the WTQM. The WTQC members will:

11.31.5.2.1. Provide personnel with initial and recurring load qualification training. **(T-2)** One WTQC member will be required to conduct practical training. **(T-2)**

11.31.5.2.2. Monitor personnel qualifications to ensure required academic and practical training is complete. **(T-2)**

11.31.5.2.2.1. Disqualify individuals if recurring requirements are not met. **(T-2)**

11.31.5.2.3. Spot-check personnel to evaluate proficiency. **(T-2)**

11.31.5.2.3.1. The WTQC will disqualify personnel who violate safety, technical data, and reliability procedures, or fail to demonstrate proficiency. **(T-2)**

11.31.5.2.4. Develop/coordinate training schedules and provide to PS&D for inclusion in the appropriate schedule (monthly, weekly). **(T-2) Note:** Enroute WTQMs forward training requirements to the UTM, who coordinates for ground training aircraft with the Regional Training Center.

11.31.6. Training Requirements. Personnel are considered qualified upon successful completion of training provided by a qualified WTQC.

11.31.6.1. Initial qualification will be conducted using inert munitions. **(T-2)**

11.31.6.2. Live munitions may be used during annual qualification to maintain currency. Load qualification training consists of academic and practical training.

11.31.6.3. Document the initial and recurring load qualification training requirements in MyLearning or other approved training process if MyLearning is unavailable (i.e., 623A, *Individual Training Record*) **(T-2)**

11.31.6.4. Academic and practical training must be provided during initial and recurring load qualification training. **(T-2)**

11.31.6.4.1. Academic training is required before practical training is accomplished. **(T-2)**

11.31.6.4.2. Initial practical training must be completed within 14 days of successfully completing initial academic training. **(T-2)**

11.31.6.4.2.1. Practical training should duplicate operational conditions as closely as possible.

11.31.6.4.3. Recurring practical task qualification is administered at least annually. **(T-2)**

11.31.6.4.3.1. As a minimum, practical training will include chaff/flare module

serviceability criteria, actual chaff/flare loading, and operation of support equipment/AGE used during loading operations. **(T-2) Note:** Weapons task qualification academic training may fulfill the requirements for explosive safety training if the requirements of DAFI 91-202 are included.

11.31.6.5. Academic training is administered every 12 months. **(T-2)** As a minimum, academic training will include:

11.31.6.5.1. Familiarization with chaff/flare loading publications, including TO 11A-1-33, MAJCOM, and local procedures. **(T-2)**

11.31.6.5.2. Aircraft and munitions familiarization. **(T-2)**

11.31.6.5.3. Safety, security, and emergency procedures. **(T-2)**

11.31.6.5.4. Support, test, handling equipment, and special tools familiarization. **(T-2)**

11.31.6.5.5. Task Assignment Lists and aircraft specific 33-1-2 series TOs must be available at the load-training site. **(T-2) Note:** Training course control documents will be coordinated annually through the Wing Safety and MT. **(T-2)**

11.31.6.6. Personnel qualified on a specific task on a specific MDS are considered qualified to perform that task on all series of that MDS; however, the member must be familiar with differences within the MDS (such as, cockpit switch locations). **(T-2)**

11.31.6.6.1. The WTQM or WTQC will provide practical, on-aircraft training on these differences and document these qualifications for each dispensing system in the qualification status or equivalent system. **(T-2)**

11.31.7. Disqualifying Chaff/Flare Load Personnel. Disqualification will be documented in A - Changed to MyLearning, or other approved training process if MyLearning is unavailable (i.e., 623A), and the qualification status system. **(T-2)**

11.31.7.1. Although not all-inclusive, the following criteria constitute grounds for disqualifying personnel from chaff/flare loading duties:

11.31.7.1.1. Failing to complete recurring training.

11.31.7.1.2. Committing a safety or reliability error.

11.31.7.1.3. Lack of proficiency.

11.31.8. Transient Aircraft.

11.31.8.1. Apply the following when working transient aircraft:

11.31.8.1.1. Under no circumstances will personnel attempt chaff/flare load operations without current technical data. **(T-2)**

11.31.8.1.2. If current technical data is available, then qualified personnel may perform chaff/flare load operations. **(T-2)**

11.31.8.1.3. If current technical data is available but no one is qualified on the transient aircraft type, then the MXG/CC (or Air Mobility Squadron (AMS)/CC at enroute locations) may authorize the WTQC or WTQM to de-arm and/or unload the aircraft.

11.31.8.1.3.1. The WTQM will submit a written request to the MXG/CC (or

AMS/CC at enroute locations) identifying personnel selected to perform the task, aircraft type and (if applicable) number of aircraft to be de-armed and unloaded. **(T-2)**

11.31.8.1.3.1.1. Approved requests will be maintained for 90 days. **(T-2) Note:** This is a temporary, one-time authorization to facilitate required maintenance when qualified personnel are not available.

11.31.9. Identification of Chaff/Flare-Loaded Aircraft. Verify chaff/flare load status of aircraft by checking AFTO Form 781A/C before performing any maintenance.

11.31.9.1. Explosive placards are not required on AMC aircraft.

11.31.9.2. If an aircraft is loaded with chaff/flare, it will be safed IAW applicable technical data prior to performing any maintenance. **(T-2)**

11.31.9.3. Before loading chaff/flares, review the AFTO Form 781C, A*vionics Configuration and Load Status Document*, for defensive systems inspection status. **(T-2)**

11.31.9.3.1. If chaff/flare is loaded on aircraft, ensure/verify applicable MIS documentation requirements are completed. **Note:** Do not load chaff/flares if the aircraft is overdue a scheduled DS inspection.

11.31.10. Tracking and Reconciliation of Chaff/Flare-Loaded Aircraft.

11.31.10.1. Expenditure tracking and processing will be handled by Munitions Personnel (2W0X1) IAW DAFMAN 21-201, **Chapter 7**.

11.31.10.2. Munitions personnel will not use the direct input method to process flightline chaff/flare expenditures; all chaff/flare expenditures will be returned to the Munitions Storage Area (MSA) for verification by munitions personnel before processing expenditures in Theatre Integrated Combat Munitions Systems (TICMS). **(T-2)**

11.31.11. Additional Requirements (as applicable).

11.31.11.1. Document DS software version data and aircraft inspections (such as, 90-, 120-, or 180-day checks) on AFTO Form 781C. **(T-2)**

11.31.11.2. For software version data, enter the following information in the remarks section for each reprogrammable system: type system; installed Operational Flight Program (OFP) version; and/or Mission Data File (MDF) version (such as, ALE-47, OFP XXXX, MDF XXXX).

11.31.11.2.1. If a system contains multiple OFPs, list all applicable versions (such as, ALE-47, Programmer OFP XXXX, Sequencer OFP XXXX, MDF XXXX).

11.31.12. Chaff/Flare Build-up. Chaff/flare magazine build-up will only be accomplished by personnel with 2W0 AFSC or qualified contractors. **(T-2)**

11.31.12.1. Units will only perform chaff/flare build-up in facilities/locations approved by the installation WSM IAW DESR6055.09_AFMAN 91-201. **(T-2)**

11.31.12.2. Units must have an approved explosive site plan or explosives facility license on file with Wing Safety prior to initiating chaff/flare build-up or storage operations. **(T-2)**

11.32. Aircraft and Equipment Decontamination.

11.32.1. Maintenance organizations need to have the Ability to Survive and Operate in a Chemical, Biological, Radiological, Nuclear, and high-yield Explosives (CBRNE) environment and have the capability to decontaminate operational aircraft, vehicle, and SE.

11.32.2. Units will employ AF and locally developed TTPs IAW DAFI 10-2503, *Chemical Biological, Radiological, Nuclear, (CBRN) Defense Program*. **(T-2)**

11.32.2.1. TTPs provide the fundamental counter-chemical warfare (CCW) tools to survive to operate and maximize combat sortie generation capabilities in a CBRNE environment.

11.32.3. The following references in addition to MDS-specific technical data should be utilized when developing unit decontamination programs: DAFMAN 91-203, AFI 10- 2501, AFTTP 3-4, *Airman's Manual*, TO 00-110A-1, *Guidelines for Identification and Handling of Aircraft and Material Contaminated with Radioactive Debris*, TO 00-20-1, TO 11C15-1-3, *Chemical Warfare Decontamination, Detection and Disposal of Decontamination Agents*, TO 11D1-3-8-1, *Decontamination Apparatus, Power Driven, Portable Type A/E32U- 8, (Engineered Air).*

11.33. End-of-Runway (EOR) Inspection.

11.33.1. EOR is MDS specific, PM directed inspection of aircraft systems identified in the Dash 6 TO or equivalent and published in Dash 6 work cards IAW TO 00-20-1. (N/A to aircraft that do not have an EOR -6 TO requirement).

11.33.2. If local requirements dictate, publish additional guidance to TOs for EOR inspections IAW TO 00-20-1 and TO 00-5-1. **Note:** Safing, arming, and de-arming of live munitions will be accomplished by personnel qualified IAW Chapter **4**, **5**, and **10**.

11.33.3. The EOR team chief (identified by a reflective vest) will carry an EOR checklist and ensures each item is inspected as required. **(T-2)** On aircraft with a ground intercom system, units are only required to establish verbal communications with the pilot when communication beyond the standard EOR marshalling hand signals is required unless otherwise directed by MDS specific technical data.

11.34. Wing Avionics Manager (WAM).

11.34.1. WAM Duties and Responsibilities.

11.34.1.1. Will be in the minimum grade of MSGT, 7 Level or equivalent, and 2A Avionics AFSC. **(T-3)**

11.34.1.2. Act As the Wing Avionics Functional Manager. **(T-2)**

11.34.1.3. Serve as the maintenance group focal point for all avionics related interactions between PMs, MAJCOMs, Lead Commands, Wings, Operations and Maintenance or equivalent activities to discern and implement changes in avionics configuration requirements. **(T-2)**

11.34.1.4. Ensure RAMPOD updates are completed IAW DAFI 21-103.

11.34.1.5. Ensure classified pods/components and equipment are stored in authorized areas IAW AFI 16-1404. **(T-2)**

11.34.1.6. Ensure classified aircraft/Support/Test equipment are stored in authorized areas IAW AFI 16-1404. **(T-2)**

11.34.1.7. Meet quarterly with MXG SEL to review avionics manning status and ensure manning resources are strategically distributed to provide the greatest possibility for mission success. **(T-2)**

11.34.1.8. Serve as the MXG Identify Friend or Foe Program Manager IAW **Paragraph 11.11** of this publication. **(T-2)**

11.34.1.9. Serve as the MXG Radar Warning Receiver/Radar Threat Warning program manager IAW **Paragraph 11.12** of this publication. **(T-2)**

11.34.1.10. Serve as the MXG EW program manager and EW Integrated Reprogramming focal point. **(T-2)**

11.34.1.11. Serve as MXG focal point for external organizations 406 MHz Emergency Locator Transmitter Systems Program IAW **Paragraph 11.27**. **(T-2)**

11.34.1.12. Coordinate with the wing EW POC to ensure compliance with DAFMAN 10-703, *Electronic Warfare Integrated Reprogramming*. **(T-2)**

11.34.1.13. Track wing assigned ECM, electronic attack and sensor pods, and associated support equipment. **(T-2)**

11.34.1.14. Coordinate all pod shipments as directed by MAJCOM to/from base or operating location. **(T-2)**

11.34.1.15. Track all incoming and outgoing pod parts and SE until received or arrived at destination. **(T-2)**

11.34.1.16. Coordinate with Electronic Combat Pilot/Electronic Warfare Officer to ensure most current MDF to configure Radar Warning Receiver/Radar Threat Warning to meet mission requirements. **(T-2)**

11.34.1.17. Serve as the MXG focal point for external organizations on all cybersecurity matters pertaining to aircraft interface equipment. **(T-2)**

11.35. Fire Extinguisher Requirements.

11.35.1. Unit coordinate with Fire Emergency Services Flight and Airfield Operations Flight to ensure required number of portable fire extinguishers are available for on and off installation operational requirements. Refer to DAFMAN 91-203, TO 00-25-172, *Ground Servicing of Aircraft and Static Grounding/Bonding*.

11.36. Air Force Repair Enhancement Program (AFREP).

11.36.1. The AFREP optimizes AF resources and repair capability of aerospace parts and equipment by increasing the wing-level (referred also as field-level) participation with the appropriate Program Office. This is accomplished by field-level identification and recommendation of candidates for reparability consideration by the appropriate PO.

11.36.1.1. The AFREP is an optional program.

11.36.1.1. **(AFGSC)** The AFREP is an optional program but will be assigned to a group staff agency (e.g., QA) within the MXG for personnel and funding management.

11.36.1.1.1. **(Added-AFGSC)** AFREP Manager.

11.36.1.1.2. **(Added-AFGSC)** AFREP Manager Duties and Responsibilities.

11.36.1.1.2.1. **(Added-AFGSC)** Will be in the minimum grade of TSgt, 7-Level or civilian equivalent

11.36.1.1.2.2. **(Added-AFGSC)** Serves as the maintenance group focal point for all AFREP related interactions between PMs, MAJCOMs, Lead Commands, Wings, Operations and Maintenance or equivalent activities to discern and implement changes in repair requirements. **(T-2**)

11.36.1.2. Unit leadership must verify mission benefit outweighs the cost and obtain MAJCOM AFREP Manager Approval prior to program implementation.

11.36.2. AFREP is repairing consumable/expendable items (XF3 and XB3). Repair Network is repairing XD2 (recoverable) and XF3 (field level/condemnable). The concept is to make recommendations to the PM of consumable/expendable items which the field-level has identified as desirable candidates to be considered for conversion to field-level repair, limited repair or even full depot-level repair, contract or organic as directed by the Depot Source of Repair process in AFI 63-101/20-101, in addition, ensure repair cost/benefit analysis takes into consideration the total costs to the AF as outlined in Air Force TO 00-20-3, *Maintenance Processing of Reparable Property and Repair Cycle Asset Control System*.

11.36.2.1. The approval authority to change the SMR/ERRC codes, or select, use, arrange for, contract with, qualify sources of repair, or authorize the initiation of any local or other repair action rests solely with the PM.

11.36.2.2. Repair Approval. Personnel must coordinate any operational change to the system, end item, modified configuration, or maintenance procedure prior to implementation IAW AFI 63-101/20-101. For example, additional base-level repair or contract repair of any item beyond the provisions which already exist in field-level TOs. **(T-2)**

11.36.2.3. Field-level personnel, including AFREP work centers, will not contract out or arrange for repair services without prior written authorization by the PM and approval by the MAJCOM AFREP Manager. **(T-2)** The PM responsible for the system or end item will retain responsibility for making any decision stemming from such a recommendation. Field-level TOs do not give permission for local contract or off-base repair of any item, only on-base repair to the extent specified by the SMR code for a given item.

11.36.3. Operational Safety, Suitability & Effectiveness (OSS&E). OSS&E is an outcome of properly planned and applied systems engineering.

11.36.3.1. Organizations responsible for preserving OSS&E of AF systems or end items must ensure that operational use, configuration changes, maintenance repairs, aging, part substitutions, and similar activities and events do not degrade baselined characteristics of systems or end items over their operational life.

11.36.3.2. OSS&E is an integrated effort to ensure items are not allowed to degrade as a result of maintenance, repairs, parts substitutions, and similar activities.

11.36.3.2.1. The program manager is responsible for the assurance of OSS&E throughout the life cycle of each configuration of each component of each system. Only the PM may convert an item from non-repairable to reparable.

11.36.4. Requirements. Given authorized repair of a consumable/expendable item, the PM will determine the SMR/ERRC code validity. All resulting changes are linked with Supply Chain Manager Consideration for that item.

11.36.4.1. Supply Chain Management issues must be considered as a matter of law, given these issues affect Congressionally Authorized budget authority and funds allocated to accomplish specifically different supply chain functions (spares buys versus repairs).

11.36.4.1.1. Any personnel, organization, or AFREP work center may request SMR/ERRC code changes IAW TO 00-25-195 and AFH 23-123, Volume 2, **Part 2**, *Integrated Logistics System-Supply (ILS-S), Standard Base Supply System Operations*, **Chapter 8**.

11.36.4.2. Non-repairable (XB3) assets submitted to PM for repair approval will contain RC (SMR/ERRC change) IAW TO 00-25-195 and a MAJCOM published form for the AFREP Vendor Repair Approval that will include all supply data, full justification, and test/repair procedures. This document will be reviewed by the MAJCOM AFREP Manager IAW **Paragraph 11.36.8**.. **(T-2)**

11.36.4.3. Repairable (XF3) assets submitted to PM for vendor repair approval will be submitted on MAJCOM published form. The form must contain all current vendor certifications and governing technical procedures utilized for test/repair by vendor. This document will be reviewed by MAJCOM AFREP Manager and signed off.

11.36.5. Asset Turn-In. Items repaired IAW technical data will be turned in to the supply system following guidance in DAFMAN 23-122 and TO 00-20-3. **(T-2)**

11.36.6. AFREP Reporting Instructions: Wing AFREP Managers will provide quarterly updates to the MAJCOM AFREP Manager. **(T-2)**

11.36.6.1. MAJCOM AFREP Managers will report yearly activity updates from October 1 to September 30 and file their yearly report with AF/A4LM by 15 October. **(T-2)**

11.36.6.1.1. The quarterly/yearly updates will include at a minimum the nomenclature and total number of items repaired, total cost avoidance, and total cost savings. **(T-2)**

11.36.7. AF/A4L Roles and Responsibilities.

11.36.7.1. Prepares, publishes, and reviews AF-level policy and guidance for AFREP.

11.36.7.2. Perform annual program analysis to verify mission benefits outweigh costs.

11.36.8. MAJCOM AFREP Manager Responsibilities.

11.36.8.1. Administer/manage the MAJCOM AFREP in coordination with the applicable Program Office.

11.36.8.2. Perform annual analysis on program viability.

11.36.8.3. Mandate use of Program Office/selection authority criteria guidance and recommendations related to maintenance, supply, and repair sources.

11.36.8.4. Designate a focal point within the applicable Program Office for the MAJCOM and end users to contact regarding AFREP recommendations and OSS&E issues.

11.36.8.5. Establish a process to identify candidate items for submission to Program Office for consideration.

11.36.8.5.1. At a minimum, process will ensure base AFREP certifies the candidate item is beyond repair from all applicable on-base organic maintenance work centers/back shops. Certification must be documented (email, logbook). Parts coded direct NRTS are exempt from this requirement. **(T-2)**

11.36.8.6. Establish and maintain an AFREP Program Office submission and status tracking website.

11.36.8.7. Compile annual program cost benefit analysis information and forward to AF/A4L.

11.36.8.8. Provide Program Office repair recommendations for evaluation and track their status (**Part I** identification, initiation date, submittal date, closure date).

11.36.8.9. Maintain, update, and distribute a list of Wing/Unit AFREP POCs to include representatives from other agencies (such as, DLA, ALCs, MAJCOMs).

11.36.8.10. Review/Validate Wing/Unit SMR/ERCC requests IAW TO 00-25-195 and TO 00-20-3 prior to submission to the applicable Program Office for evaluation/approval.

11.36.8.11. Validate items are approved for contract repair for strategic sourcing opportunities.

11.36.8.12. Initiate the opportunity assessment of strategic sourcing candidates when deemed appropriate or when requested by the Program Office.

11.36.8.13. Provide quarterly MAJCOM cross-tell of AFREP repairs to Base/Center AFREP managers. The minimum data will include nomenclature, total cost, and total amount saved for each item across the MAJCOM.

11.36.8.14. **(Added-AFGSC)** Communicate process improvements to all wing/unit AFREP managers in the command. **(T-2)**

11.36.9. Wing/Unit Responsibilities:

11.36.9.1. Participate in AFREP when approved by the MAJCOM AFREP Manager. **(T-2)**

11.36.9.1.1. DELETED.

11.36.9.1.2. MXG SEL will ensure AFREP Manning Positions are categorized as an additional duty and not listed as positions on the MXG UMD. **(T-2)**

11.36.9.1.3. **(Added-AFGSC)** Ensure Project Fund Management Record (PFMR) account is established for financial accountability. All credit earned will be carefully managed and applied to mission-related requirements.

11.36.10. Wing/Unit AFREP Manager Responsibilities:

11.36.10.1. Submit SMR/ERRC change recommendations to the MAJCOM AFREP Manager for Program Office coordination. See TO 00-25-195, and this DAFI. **(T-2) Note:**

Field-level TOs do not give authorization for local contract repair of any item, only on-base repair to the extent specified by the SMR code for a given item. AFREP or any other field level personnel will not perform repairs not authorized by technical data. **(T-2)**

11.36.10.1.1. Workcenters participating in AFREP repairs will submit Critical Application Items (CAI) and Critical Safety Items (CSI) repair recommendations to the MAJCOM AFREP Manager for screening to determine appropriate PM for submission. **(T-2) Note:** CAIs, CSIs, or elements of a system which the PM has designated as a CAI system, or a CSI system are prohibited from consideration under the AFREP program unless otherwise approved by an authorized engineering authority.

11.36.10.1.1.1. All Electronic Warfare (EW) Systems are CAI-designated systems. Verify CAI and CSI items on the Joint Services Critical Item Data Viewer, located at: **https://remote3.amrdec.army.mil/csiviewer/**. See **Attachment 2**, CAI & CSI for additional information.

11.36.10.1.2. Contractor repairs of any item are not allowed without prior written authorization from the PM and approval by the MAJCOM AFREP Manager. **(T-2) Note:** AFREP work centers are prohibited from entering into repair source contractual/obligation relationships with contractors. DoD regulations exist to assign such actions (finding and qualifying repair sources) to the authorized engineering authority.

11.36.10.1.2.1. If contract repairs are authorized, contracts will be established IAW local contracting procedures. **(T-2)**

11.36.10.1.2.1.1. **(Added-AFGSC)** AFGSC Form 45, *AFREP Source of Approved Repair (SAR) Request and Reply*, is the standard format used to approve contractors. Completed AFGSC Form 45s will be submitted to the AFGSC AFREP manager for review and routing to the appropriate program office. **Note:** Items contract repaired prior to SAR requirement implementation are not subject to recall. **(T-2)**

11.36.10.1.3. The Wing/Unit AFREP Manager will ensure the SOW includes, as a minimum, the following items for contracted repairs:

11.36.10.1.3.1. Requirement for the contractor to perform/document receiving inspections. **(T-2)**

11.36.10.1.3.2. Requirement for the contractor to inspect/test the item following repair. **(T-2)**

11.36.10.1.3.3. Requirement for the contractor to provide a record of the repair and test results to the AFREP office and made available for the Government Inspector (such as, Defense Contract Management Agency (DCMA)). **(T-2)**

11.36.10.1.3.4. Contract will specify expected shipping, transportation, and repair-estimate completion dates. **(T-2)**

11.36.10.1.3.5. Repair items IAW Technical Data. **(T-2) Note:** Restricted use of systems will result from use of components which have been repaired as described immediately above, without prior written authorization from the program manager.

11.36.10.1.3.6. Enter data into the AFREP Recommendation Submittal site: AFREP - Home (dps.mil) The minimum data consists of a roll up AFREP repair total cost and will include:

11.36.10.1.3.6.1. Time expended coordinating PM approval for AFREP repair authorization. **(T-2)**

11.36.10.1.3.6.2. Man-hours to complete repair "labor hours". **(T-2)**

11.36.10.1.3.6.3. Nomenclature/Stock Number of part being repaired. **(T-2)**

11.36.10.1.3.6.4. Total cost of item if sourced from the supply chain. **(T-2)**

11.36.10.1.3.6.5. Total cost of tangible resources expended to complete AFREP repair (such as, wiring/consumables). **(T-2)**

11.36.10.1.3.7. Assist technicians by interfacing with engineering, Equipment Specialists (ES), QA, Air Force Engineering Technical Services, and other field-level agencies. **(T-2)**

11.36.10.1.3.8. Accumulate and forward data requested by MAJCOMs concerning AFREP. **(T-2)**

11.36.10.1.3.9. Provides repair authorizations to the MXG QA PIM IAW DAFI 21- 101.

11.36.10.1.3.10. Ensure individuals assigned AFREP extra duties are trained, qualified and maintains a minimum five-skill level in their AFSC IAW DAFMAN 36-2689.

11.36.10.1.3.11. Submit and monitors DR for deficiencies discovered during a Wing/Unit AFREP initiative, IAW TO 00-35D-54 or equivalent PM approved DR process.

11.36.10.1.3.12. Review daily Awaiting Parts (AWP) and MICAP lists from maintenance activities to determine if the AFREP office can recommend to the appropriate PO, items from those lists. **(T-2)**

11.36.10.1.3.12.1. **(Added-AFGSC)** DIFM Status Code ZCP is reserved for AFREP DIFM items IAW User Manual Appendix 12, located on the Integrated Logistics Systems-Supply (ILS-S) homepage IAW DAFMAN 23-300. **Note:** ZCP coded items are NOT to exceed 270 total DIFM days. **(T-2)**

11.36.10.1.3.13. Provided quarterly AFREP repair updates to MXG/CC. The repair updates at a minimum will include nomenclature, total cost, and total amount saved for each item. **(T-2)**

11.36.10.1.3.14. Establish collection points within unit supply sections for consumable/expendable items coded with ERRC XB3 to determine reparability of assets prior to permanent disposal.

11.36.10.1.3.15. **(Added-AFGSC)** Ensure supply system demand requirement exists prior to repairing DIFM items.

11.36.10.1.3.16. **(Added-AFGSC)** Ensure DIFM item repairs do not exceed the

Economic Retention Level within the local supply system per AFMAN 23-300. **Note:** Continued repairs on items with ample stock can negatively impact the supply cycle.

11.36.10.1.3.17. **(Added-AFGSC)** Screen asset availability through Defense Logistics Agency Disposition Services (DLADS) per DAFMAN 23-300. **(T-2)**

11.36.10.1.3.18. **(Added-AFGSC)** Circuit Card Repair (CCR) Technician is an optional program under AFREP that can be established by the unit AFREP manager. **(T-2)**

11.37. Calibration Limitation Approval Certification Program.

11.37.1. General. A limited TMDE calibration could seriously impact mission capability of weapon systems. All units will have a comprehensive training program to ensure authorized personnel can interpret TMDE calibration limitations to the specified requirement of the applicable weapon system. **(T-2)** Personnel will be certified IAW criteria established in **Table 11.1**. **(T-2)** MXG/CCs may designate contractors in writing to authorize calibration limitations.

11.37.2. Responsibilities and Management. The MT or TD will be responsible for management and development of the calibration limitation approval training program. **(T-2)**

11.37.2.1. As a minimum, the course will include when to consider a limited calibration, impact of using improperly calibrated equipment, and how to apply calibration specifications to weapon system requirements. **(T-2)**

11.37.2.2. Prior to placement on the SCR, the calibration limitation approval training (MT or TD course) will be mandatory. **(T-2)**

11.37.3. - 11.37.3.2. DELETED.

11.37.4. Certification Criteria. Certifying officials will be selected IAW criteria established in **Table 11.1**. **(T-2)**

11.38. Oil Analysis Program (OAP).

11.38.1. Program. Oil Analysis is the process of analyzing oil and other fluids used to lubricate or operate mechanical equipment, evaluating the condition of the fluid or the equipment from which the fluid originated, and recommending maintenance actions to the equipment operating activity. An OAP ensures timely and accurate oil analysis support through the strategic location of oil analysis laboratories and the standardization of procedures, data elements, analytical instrumentation, and diagnostic techniques. The Joint Oil Analysis Program (JOAP) is a combined effort of the Army, Navy and AF to set-up and maintain a standard program. Oil analysis requires a centrally managed program and the integration of AF OAP and JOAP plans.

11.38.2. Objectives. The overall objective of the AF OAP is to detect oil-wetted air and space equipment failures before serious malfunction or secondary damage occurs. The specific objectives of the AF OAP and JOAP programs are as follows:

11.38.2.1. Improve the operational safety, readiness, and economy of military equipment through the use of on-board and off-board oil analysis, a condition-monitoring concept that relies on the detection and measurement of wear-metals in the fluid.

11.38.2.2. Collect and analyze oil analysis data in order to increase the effectiveness of oil analysis techniques in the diagnosis of potential equipment failures and lubricant condition; to provide wear metal and lubricant physical property data to the various weapons system managers and others, as required.

11.38.2.3. Ensure oil analysis plans and operations are integrated (where practical) to provide:

11.38.2.3.1. Standard laboratory techniques, procedures, data, calibration standards, and analytical instruments.

11.38.2.3.2. Inter-service oil analysis support to all military departments.

11.38.2.3.3. The most cost–effective means of determining the condition of lubricants, fluids, and mechanical system through the use of various analytical techniques.

11.38.3. Guidance. The OAP helps aircraft technicians and supervisors to make informed, condition-based, preventive maintenance decisions, and can reduce equipment costs, increase equipment availability, and reduce in-flight risk. This is primarily achieved by monitoring the concentration of wear metals in fluids used to lubricate or power mechanical systems.

11.38.3.1. To monitor engine health, the OAP uses a variety of testing mechanisms. These include:

11.38.3.1.1. Atomic Emission spectrometric wear metal analysis.

11.38.3.1.2. Magnetic Chip Detectors/Magnetic Chip Detectors with on-board sensors.

11.38.3.1.3. Scanning Electron Microscope/Energy Dispersive X-ray system technology.

11.38.3.2. To the extent deemed cost effective, EOT will be used as the standard time interval between oil analysis sampling when in-service engines are equipped with an Engine Monitoring System or other operating time recorders.

11.38.3.2.1. For engines without Engine Monitoring System or other operating time recorders, oil analysis trending intervals will be standardized based upon Engine Flying Hours.

11.38.3.3. Analyze oil samples from transient aircraft IAW applicable technical data and owning activity requirements.

11.38.3.3.1. For transient aircraft with an EMS, at bases without the capability to download EOT data, Engine Flight Hours will be used to continue oil analysis trending.

11.38.3.4. Responsible activities must ensure the resultant data is accurate and given promptly to all customers so they can effectively monitor the condition of their equipment.

11.38.3.4.1. AF OAP laboratories will evaluate response times to optimize support of the customer. **(T-2)** Evaluation frequency is established by MAJCOM supplemental guidance.

11.38.3.5. Laboratory operation.

11.38.3.5.1. Each OAP laboratory must be certified IAW TOs 33-1-37-1/-2.

11.38.3.5.2. Seek to maximize inter-service use of existing laboratories through laboratory consolidation, workload sharing, and use of standardized instrumentation, techniques, and procedures. **(T-2)**

11.38.3.5.3. AF OAP laboratories must provide oil analysis services at no charge for all US Government, North Atlantic Treaty Organization (NATO) and friendly Foreign Military Sales aircraft. These services include analyzing oil samples from transient aircraft IAW applicable technical data within the AF OAP laboratory capabilities. **(T-2)**

11.38.4. Roles and Responsibilities

11.38.4.1. AF/A4L is the chief Air Staff agency with policy responsibility for the maintenance of air and space equipment.

11.38.4.1.1. Guidance. Prepares, publishes, and reviews AF-level policy and guidance for the AF OAP.

11.38.4.1.1.1. Coordinates with MAJCOMs to review and resolve guidance-related issues.

11.38.4.1.2. Management. Designates a POC for AF OAP. The representative will manage this publication while closely coordinating with functional experts.

11.38.4.1.2.1. Works with AF representative to the JOAP-Coordinating Group (CG) on policy issues.

11.38.4.2. Major Command. Each MAJCOM establishes a headquarters POC for complying with MAJCOM OAP responsibilities.

11.38.4.2.1. Establishes or relocates OAP laboratories to support MAJCOM mission. Coordinates establishment or relocation with the AF OAP Manager.

11.38.4.2.2. Ensures quality deficiency reports are submitted to the unit Product Improvement Manager IAW TO 00-35D-54. DRs must be submitted to engine program offices on all equipment requiring tear down or overhaul due to an OAP laboratory maintenance recommendation and on all oil-wetted component failures where no OAP laboratory maintenance recommendation was made.

11.38.4.2.3. Ensures laboratories provide the depot a computer-generated printout/record, for each engine undergoing scheduled maintenance or overhaul.

11.38.4.2.4. Ensures laboratories process and evaluate samples IAW TO 33-1-371/- 2.

11.38.4.2.5. Ensures proper training of AF OAP laboratory technicians. This includes identifying training requirements to the AETC.

11.38.4.2.6. Ensures assigned shop instrumentation and equipment is not modified or used for non-OAP applications without AF OAP Office approval.

11.38.4.2.7. Provides guidance necessary to execute the AF OAP and ensures all subordinate organizations understand and properly execute AF OAP and JOAP responsibilities. MAJCOMs/ANG may provide additional guidance in their supplements or addendums to this DAFI as required.

11.38.4.2.8. Ensures AF OAP and JOAP requirements are included in planning, programming, and budgeting process. This includes providing needed funds, personnel, facilities, and other resources to maintain an effective program.

11.38.4.2.9. Supports equipment evaluations and field surveys for the AF OAP Office.

11.38.4.3. Air Force Materiel Command (AFMC). AFMC is the lead MAJCOM for the AF OAP and AF participation in the JOAP. AFMC is also responsible for oil analysis Research, Development, Test and Evaluation (RDT&E). The Directorate of Logistics, Civil Engineering, Force Protection, and Nuclear Integration (AFMC/A4/10) is the headquarters office of primary responsibility for AF OAP guidance coordination and implementation within AFMC.

11.38.4.3.1. Propulsion Directorate.

11.38.4.3.1.1. Sustainment Chief Engineer represents the AF on the JOAP-Executive Committee.

11.38.4.3.1.1.1. Establishes, funds, staffs, and directs the AF OAP Office.

11.38.4.3.1.2. The Development Program Manager ensures specification guidance for oil analysis sampling provisions or other appropriate measures to detect oil-wetted failures, where applicable, are included during the design phase.

11.38.4.3.1.3. AF OAP Office, AFLCMC/LP. The AF OAP Office manages the AF OAP, and in coordination with the MAJCOMs and propulsion community, leads AF participation in the JOAP.

11.38.4.3.1.3.1. Certifies/decertifies AF OAP laboratories for participation in the JOAP.

11.38.4.3.1.3.2. Maintains a list of AF OAP laboratories, equipment, and customers.

11.38.4.3.1.3.3. Assists MAJCOM/Center managers in program execution. This includes recommending the establishment, location, and relocation of AF OAP laboratories.

11.38.4.3.1.3.3.1. Communicates AF OAP objectives, policies and procedures to the Director of Propulsion, Engine OAP Managers, equipment specialists and program managers.

11.38.4.3.1.3.3.2. Evaluates the need for and performs special studies, as requested by the MAJCOMs or depots.

11.38.4.3.1.3.3.3. The AF OAP Office should periodically conduct laboratory assistance/assessments to determine adequacy and effectiveness of the AF OAP. Identifies problems and recommends solutions.

11.38.4.3.1.3.4. Establishes and manages a data system, meeting tri-service requirements, to evaluate AF OAP participation and effectiveness and to provide engine program offices with historical data on oil sample analysis results.

11.38.4.3.1.3.5. Coordinates and consolidates AF/MAJCOM requirements

with Army/Navy to ensure, where practical, the procurement of common OAP equipment.

11.38.4.3.1.3.6. Represents the AF on the JOAP-CG.

11.38.4.3.1.3.7. Develops a comprehensive OAP laboratory certification and quality control program.

11.38.4.3.1.3.8. Maintains and provides AF inputs to TOs 33-1-37-1/-2/-3/-4, *JOAP Manual*.

11.38.4.3.1.3.9. Reviews and evaluates the JOAP school curriculum.

11.38.4.3.1.3.10. Assists the Engine OAP Manager and serves as an advisor for the engine Maintenance Planning Working Group (MPWG) for OAP issues.

11.38.4.3.2. Director of Propulsion (DOP). The DOP AFLCMC/LP in conjunction with Engine Single Managers at AFLCMC/LPS, AFLCMC/LPA and the AF OAP Office assess existing/potential oil analysis technologies. The DOP also ensures wear metal debris and oil analysis is an integral part of the Engine Health Management Program. The DOP appoints Engine OAP Managers for each AF managed engines.

11.38.4.3.2.1. Engine OAP Managers. The Engine OAP Manager is the engineer in charge of a particular engine and is solely responsible for the OAP related issues on that particular engine.

11.38.4.3.2.1.1. Serves as the focal point for the engine MPWG for OAP issues, provides the guidance necessary to accomplish engine-specific oil analysis.

11.38.4.3.2.1.2. Ensures expeditious handling of equipment returned for tear down or overhaul because of an OAP laboratory maintenance recommendation or where oil analysis results indicated a potential problem.

11.38.4.3.2.1.3. Provides guidance necessary to accomplish engine specific oil analysis. Provides updates for TOs 33-1-37-1/-2/-3/-4 to the OAP Office.

11.38.4.3.2.1.4. Provides accurate and timely feedback to the MPWG and field units on OAP-monitored equipment. This includes maintenance findings on equipment in for tear down or overhaul as a result of an OAP laboratory maintenance recommendation. It also includes failure reports and related wear metal and oil analysis data on oil-wetted components where no OAP laboratory maintenance recommendation was made.

11.38.4.3.2.1.5. Works with the MPWG to establish and maintain wear metal limits, diagnostic criteria, and other oil analysis parameters. This is based on a review of data from equipment tear-down and overhaul findings.

11.38.4.3.2.1.6. Maintains metrics on hits, misses, and escapes. Once oil analysis data is included in the Engine Health Management AF Enterprise Center with software capability to perform metric monitoring, the AF OAP will concurrently monitor metrics with the Engine OAP managers.

11.38.4.3.2.1.7. Works with the MPWG, MAJCOM customers and the AF

OAP Office to establish engine-specific technical and performance requirements for all wear metal debris and oil analysis equipment.

11.38.4.3.2.1.8. Utilizes the Component Improvement Program as needed to evaluate the cost effectiveness of existing and potential wear metal debris and oil analysis applications, establish test programs, and implement the most cost-effective method(s).

11.38.4.3.2.1.9. Sends updates of specific oil sampling intervals and wear metal limits (evaluate for new engines during the design phase; reconsider for existing engines when oil-wetted parts undergo any materiel or strength changes) to the MPWG.

11.38.4.3.3. SE and Vehicles Division (AFLCMC/WNZ) procures oil analysis equipment at the request of the AF OAP Office.

11.38.4.3.3.1. Maintains a contract for procurement of JOAP AE spectrometers used by the Army, Navy, and AF laboratories.

11.38.4.3.3.2. Provides technical order provisioning and support.

11.38.4.3.3.3. Establishes inter-service logistics support. This includes spare parts support, instrument repair and overhaul, procurement of common JOAP laboratory equipment and supplies, item management and equipment specialist activities, and funding status of existing contracts.

11.38.4.3.4. Air Force Research Laboratory. The Air Force Research Laboratory accomplishes RDT&E to improve wear metal and oil analysis instruments, materials, and techniques. **(T-2)**

11.38.4.3.4.1. Supports the AF OAP charter to conduct test and evaluation for the oil analysis programs, including the JOAP and the AF OAP, as applicable. **(T-2)**

11.38.4.3.4.2. Coordinates RDT&E activities with the MAJCOMs, DOP, and AF OAP Office as applicable. **(T-2)**

11.38.4.4. AETC. Provides initial oil analysis training for AFSC 2A7X2 through the Nondestructive Inspection course. The AF OAP Management Office and MAJCOMs may request additional training, as required.

11.38.4.4.1. Coordinates course materiel changes with the AF OAP Office and the MAJCOM POCs.

11.38.5. Reporting and Measurement. All MAJCOMs and laboratories must collect and report metrics to the AF OAP Manager IAW TOs 33-1-37-1/-2/-3/-4.

11.38.5.1. All laboratories must collect, and report hits, misses, and escapes as a minimum. **(T-2)**

11.38.5.2. **(Added-AFGSC)** AFGSC OAP Manager is A4MA. **(T-2)**

11.39. Air Force Engineering and Technical Services (AFETS).

11.39.1. General. The AF must maintain its weapons systems and equipment to meet worldwide mission requirements and operational needs at a reasonable cost. To accomplish

this, units need the capability to quickly resolve complex or unusual technical problems and provide enhanced system-specific technical training to AF technicians, contractors, and operators. Engineering and Technical Services (ETS) provides this expeditionary resource and is prepared to deploy AFETS and CETS as needed.

11.39.1.1. AFETS personnel are the primary source of Engineering and Technical Services support in the AF. AFETS field engineers are Emergency Essential DoD civilian employees, highly experienced and thoroughly trained technical specialists.

11.39.1.2. CETS can be an important element in developing an independent AF capability on new systems; however, units must develop their own organic capability and/or request AFETS support. **(T-2)** Organizations should normally terminate CETS within 12 months after obtaining self-sufficiency.

11.39.2. AFETS are DoD civilians who provide advantages of long-term continuity and decreased retraining costs provided by a civilian work force. AFETS field technicians will be used and retrained as necessary to meet technical needs and changing mission requirements. **(T-2)**

11.39.2.1. AFETS can design special test equipment, develop special maintenance procedures, develop, and conduct technical training for unit maintainers and operators, and recommend changes to maintenance processes.

11.39.2.2. AFETS also serve as the unit technical liaison and work with MAJCOM functional managers, depot technicians, engineers, item managers, and equipment manufacturers to resolve complex equipment problems.

11.39.2.3. AFETS will certify tasks IAW AFI 36-2650 and DAFMAN 36-2689 in USAF personnel training records when training is provided to the go/no-go level. **(T-2)**

11.39.3. AFETS personnel should be functionally aligned under the local ETS OPR (typically the MXG/CC or equivalent commander) and reside within the assigned organizations maintenance complex.

11.39.3.1. AFETS will not be authorized to overcome manning shortfalls or to perform duties considered organic to the unit's manning. **(T-2)**

11.39.3.2. When AFETS and contracted engineering support (example, CETS, Field Service Engineer or FSR) are assigned to a unit every effort will be made to co-locate these resources to maximize effectiveness of technical support within the organization. **(T-2)**

11.39.4. The AF may utilize CETS to provide on-site proficiency training, technical advice, and technical assistance for initial system bed-down or major modifications when AFETS are unavailable. Units desiring services of strategically assigned CETS will direct their requests to their MAJCOM OPR. **(T-2)**

11.39.4.1. When CETS and AFETS are assigned to the same unit, CETS will support and train AFETS personnel as required. **(T-2)**

11.39.4.2. CETS will certify tasks IAW DAFMAN 36-2689, and AFI 36-2650, in USAF personnel training records when training is provided to the go/no-go level. **(T-2)**

11.39.5. Exclusions. ETS covered in this DAFI excludes:

11.39.5.1. Engineering review and resolution of service-revealed deficiencies reported through normal maintenance information systems.

11.39.5.2. Materiel DR covered in TO 00-35D-54.

11.39.5.3. The engineering determination of materiel integrity.

11.39.5.4. The engineering or technical services used in 61-series instructions.

11.39.6. Limits: CETS are restricted to the duties and responsibilities outlined in this DAFI and specific tasks listed in the Task Work Specification. MAJCOM OPRs (with approval by the applicable MAJCOM Directorate) may grant exceptions to these limits only on a case-by-case basis based on mission need. Do not use CETS to avoid manpower ceilings or other personnel rules and regulations.

11.39.6.1. CETS will not:

11.39.6.1.1. Perform non-ETS duties or normal unit duties. **(T-3)**

11.39.6.1.2. Make policy or represent the using activity at meetings or conferences. **(T-3)**

11.39.6.1.3. Supervise or control AF personnel or personnel of other contractors. **(T-3)**

11.39.6.1.4. Hold engineering decision-making positions. **(T-3)**

11.39.6.1.5. Perform direct maintenance except in emergency situations. **(T-3)**

11.39.7. MAJCOM Responsibilities. MAJCOMs will:

11.39.7.1. Supplement this document as necessary to ensure standardization among subordinate units.

11.39.7.2. Designate a Lead ETS Program Office in a single MAJCOM to administer the activities of the member MAJCOMs merged by MOA/MOU.

11.39.7.3. Designate an ETS OPR in the appropriate Headquarters Directorate or Field Operating Unit (FOA) to serve as the MAJCOM ETS OPR for member MAJCOMs merged by MOA/MOU.

11.39.7.4. Ensure all applicable requirements of this DAFI are met by units authorized to decentralize management of their ETS programs to the using activities.

11.39.7.5. Program and defend MAJCOM ETS funds and manpower requirements over the Future Years Defense Program (FYDP) consistent with AF mission requirements.

11.39.7.6. Budget and fund AFETS PCS, TDY, and Developmental Training costs to support their MAJCOM requirements and submit Program Objective Memorandum (POM) for all ETS requirements.

11.39.7.7. Identify and ensure mobility statements are in AFETS Standard Core Personnel Document and designate positions as Emergency-Essential. Refer to DAFI 36-153, *Civilian Mobility*.

11.39.7.8. Ensure general personnel management records are maintained at the unit of assignment on all ETS personnel to assure proper management and administration of ETS resources.

11.39.7.9. Ensure training for AFETS receive proper priority in AF training plans.

11.39.7.10. Redistribute ETS resources between major activities when mission changes dictate such realignment. All redistribution efforts will be coordinated with losing and gaining organizations.

11.39.7.11. Provide government property support to CETS IAW Federal Acquisition Regulation (FAR), Subpart 45.3, Authorizing the Use and Rental of Government Property.

11.39.7.12. Coordinate CETS contract questions with the AFLCMC/Enterprise Acquisition Division (PZIEB) who performs all central acquisition contracting functions for CETS.

11.39.8. Lead ETS Program Office/Decentralized Management Activities Responsibilities (as applicable). Lead ETS Program Office/Decentralized Management Activities will:

11.39.8.1. Develop Task Work Specification and initiate procurement packages for each approved CETS requirement using appropriate Advisory & Assistance Service policies and procedures IAW FAR Subpart 37.2, *Advisory and Assistance Services*.

11.39.8.2. Oversee Contract Officer Representative (COR) activities.

11.39.8.3. Establish procedures to notify subordinate activities of CETS termination.

11.39.8.4. Develop and utilize assessment criteria to effectively manage, administer, and control ETS activities.

11.39.8.5. Conduct annual assessments of ETS Team performance at each field unit.

11.39.8.6. Validate manpower requirements at least every 24 months. Validation should be accomplished with inputs and recommendations from unit leadership and MAJCOM ETS OPR.

11.39.8.7. Realign AFETS manpower as needed when the mission, system, or equipment changes dictate.

11.39.8.8. Coordinate AFETS placement and Standard Core Personnel Documents with manpower and civilian personnel offices.

11.39.8.9. Maintain the knowledge, training abilities and skills of the AFETS workforce.

11.39.8.10. Update/train AFETS on new weapon systems, equipment conversions and major system modifications.

11.39.8.11. Coordinate with weapon system and equipment managers to program AETC Type I Training and other types of training for AFETS on a priority basis for current and new systems.

11.39.8.12. Provide AFETS instructor training.

11.39.8.13. Verify need for CETS personnel security clearances and take action to maintain access at the minimum level required IAW DoDMAN5200.02_AFMAN 16-1405, *Air Force Personnel Security Program*.

11.39.8.14. Include Personnel Reliability Program guidance in the Task Work Specification of contractors whose duties involve nuclear weapons.

11.39.8.15. Consolidate subordinate units' requirements and establish a validation process through the MAJCOM, FOA, or Direct Reporting Unit (DRU) ETS OPR (as applicable).

11.39.8.16. Establish, maintain, and manage MAJCOM ETS TDY and training budget to include planning and execution of funds.

11.39.9. Using Activity will:

11.39.9.1. Employ ETS resources effectively and efficiently to enhance mission capability IAW AF and MAJCOM guidance. **(T-2)**

11.39.9.2. Provide specific direction and guidance on maintenance activities requiring focused AFETS attention and/or technical support. **(T-2)**

11.39.9.3. Ensure AFETS personnel attend and participate in Group, Squadron, and unit maintenance meetings, as required. **(T-2)**

11.39.9.4. Ensure AFETS personnel are providing desired coverage on all shifts, as required, with a focus on shifts where the significant maintenance and repair activities are ongoing. **(T-3)**

11.39.9.5. Provide local access and oversight of Time and Attendance actions for assigned AFETS personnel.

11.39.9.6. AFETS assigned as tenants will be afforded command/base support by the host commensurate with other assigned DoD civilians to include eligibility for local awards, security clearance processing, annual physicals, passport/visa processing. **(T-2)**

11.39.9.7. Fund AFETS to attend conferences, Technical Interchange Meetings (TIM), and deployments as required. **(T-3)** In addition, fund training requirements to ensure AFETS remain current on assigned and emerging systems. **(T-3)**

11.39.9.8. Provide office supplies, special Information Technology (IT) equipment as necessary to support the unit's mission. **(T-3)**

11.39.9.9. Adhere to AF and ETS TDY/Deployment Policies and regulations. **(T-2)** Units are authorized and encouraged to deploy AFETS to support mission requirements worldwide. AFETS employees must be assigned UTC positions in mobility tasked units on the Deployment Manning Document (DMD) as required. **(T-2)** CETS representatives are typically not deployed but may be deployed on specific approval of the MAJCOM OPR if AFETS personnel are not available, subject to contract provisions and funding availability.

11.39.9.10. UDM/deployment functions/processes are the responsibility of assigned unit for AFETS personnel.

11.39.9.11. Adhere to Adverse Action, Appeal and Grievance Procedures. **(T-2)** Refer to DAFI 36-148, *Discipline and Adverse Actions of Civilian Employees*, issue based 36-Series AFIs, and Negotiated Labor Management (Union) Agreement as applicable, before proceeding.

11.39.9.12. Provide support through the local security manager to process AFETS personnel security periodic reviews and updates.

11.39.9.13. Provide AF Certifying Officer Support. **(T-2)** The using activity OPR will serve as or designate AF Certifying Officers for CETS personnel and provide the name, office symbol, signature, and telephone number of the Air Force Certifying Officer to the Administrative Contracting Officer, with a copy to the MAJCOM OPR, no later than 30 days after the CETS assignment or within five workdays of any AF Certifying Officer change. **(T-2)**

11.39.9.13.1. The CETS contract line items assigned to each certifying officer will be clearly identified in this designation.

11.39.9.13.2. The AF Certifying Officer is responsible for certifying the monthly Certificate of Service. It is recommended that the using activity delegate the AF Certifying Officer responsibilities to the Director of Operations of the squadron primarily using the individual CETS employee's services.

11.39.9.13.2.1. The designated certifying officer will be a commissioned officer. **(T-2)** When it is impractical to designate a commissioned officer or one is not available, requests for approval to appoint a senior NCO or AF civilian (GS-11 or above) as AF Certifying Officer will be submitted by the using activity OPR in writing to the MAJCOM OPR. Each request will be evaluated on an individual basis.

11.39.10. AFETS Responsibilities. AFETS personnel will:

11.39.10.1. Provide field service engineering, technical advice; and assistance to resolve system anomalies and equipment failures. **(T-2)**

11.39.10.2. Develop and teach specific technical training for maintaining and operating unit equipment and assigned weapons systems. **(T-2)**

11.39.10.3. Investigate equipment failures and mishaps and train personnel to help prevent recurrence. **(T-2)**

11.39.10.4. Develop contacts with contractor, depot, and AFLCMC engineers, technicians, and item managers to resolve maintenance problems, design deficiencies, and supply problems. **(T-2)**

11.39.10.5. Develop special test equipment and maintenance procedures to resolve complex system problems. **(T-2)**

11.39.10.6. Perform emergency maintenance (direct assistance) on equipment when temporary skill or manning shortages prevent accomplishment by other assigned personnel. **(T-2)**

11.39.10.7. Advise the ETS OPR on the best utilization and management of CETS. **(T-2)**

11.39.10.8. Document technical activates and provide stakeholders a written account of maintenance activities by the end of each month. **(T-2)**

11.39.10.9. Maintain mobility readiness and accomplish unit required ancillary training. Training must be kept current. **(T-2)**

11.39.11. CETS Contractor Responsibilities. CETS contractor will:

11.39.11.1. Provide ETS through CETS employees to perform the duties described in the Task Work Specification. **(T-2)**

11.39.11.2. Select, supervise, and exercise sole and autonomous control and direction over CETS employees. **(T-2)**

11.39.11.3. Comply with the administrative and security regulations of the using activities. **(T-2)**

11.39.11.4. Provide copies of the Task Work Specification to CETS employees. **(T-2)**

11.39.11.5. Provide CETS security clearance certification to the unit security office. **(T-2)**

11.40. Senior Leader Mission Generation (SLMG) Course.

11.40.1. The Senior Leader Mission Generation (SLMG) Course was developed in 2013 and focused on wing leadership teaming between maintenance, operations, and logistics support to achieve safe and effective mission generation. SLMG objectives are to 1) comprehend the organizational dynamics and responsibilities of operational, maintenance, logistics support, and medical functions for aircraft mission generation; 2) comprehend the necessary integration and teamwork between operational, maintenance, logistics support, and medical functions for aircraft mission generation.

11.40.2. Only Wing CCs/CVs, Operations Group Commander (OG/CCs), MXG/CCs, Mission Support Group (MSG/CCs), MDG/CCs and their equivalent to be stationed at wings with a flying or nuclear mission are required for attendance. **(T-2) Note:** MAJCOM/CV is the waiver authority for attendance. Officers in Space, Cyber, Intel, Air Base Wings or other "non-traditional" wings are not mandated to attend; however, officers desiring to attend from non-mandated wings can contact their Senior Leader Management office and be added to the course. Registration for SLMG will be accomplished during registration for Pre-Command Training. **Note:** The SLMG course is a unit funded TDY.

11.41. Condition Based Maintenance Plus (CBM+). CBM+ is the application and integration of appropriate processes, technologies, and knowledge-based capabilities to improve the reliability and maintenance effectiveness of USAF systems and components. CBM+ is maintenance performed based on evidence of need provided by RCM analysis and other enabling processes and technologies. The CBM+ Process has four distinct phases, including Component Selection, Enhanced Reliability Centered Maintenance (eRCM), Sensor-Based Algorithms (SBA), and CBM+ Deployment.

11.41.1. PREDICTIVE MAINTENANCE ALERT LOOP (PMAL). A six-step collaborative process that allows stakeholders to receive and act upon the results of eRCM analyses and/or sensor-based algorithms/modules. PMAL transforms eRCM forecasts and sensor-based algorithm alerts into Mx and supply chain actions and is a critical component in the integration of a successful USAF Predictive Mx culture.

11.41.2. GOVERANCE. A CBM+ Team is assigned per weapon system and includes representatives from AFLCMC/RO, the Program Office, the MAJCOM (including direct CBM+ support, WSMs/WSTs and field unit contacts), AFSC/LZRB, and 420 SCMS. For platforms managing many MOBs, a field representative may also serve as an optional member of the CBM+ Team to provide feedback on the execution of Mx. The CBM+ Team oversees the execution of the PMAL. The CBM+ Team meets on an as-needed basis to discuss the most

recently published forecast, the locations of affected aircraft, and the availability of supply to make informed, collaborative decisions and recommendations.

11.41.3. PLAN AND SCHEDULE MAINTENANCE. The PS&D Section will be the focal point for CBM+ management, including ordering parts, ensuring that CBM+ parts desired to be changed are scheduled on the weekly operations and maintenance schedule, and that all documentation is complied with IAW **Chapter 14** of this instruction. Refer to the respective MAJCOM guidance on how and when to schedule maintenance for assigned locations. When supply is limited or aircraft are deployed or preparing for mission deployment, the MAJCOM may prioritize Mx requirements or coordination with applicable supporting organizations.

11.42. (Added-AFGSC) Deicing/Anti-icing Training. Deicing/Anti-icing training will be conducted IAW TO 42C-1-2, *Anti-icing, Deicing and Defrosting of Parked Aircraft*, and aircraft-specific deicing TO guidance. Only licensed drivers can operate deicing trucks.

11.43. (Added-AFGSC) Maintenance Flash/QA Flash. MAJCOM and MXGs may use Maintenance Flash or QA Flash to clarify or bring attention to maintenance related issues/concerns. QA should be the POC for developing and disseminating Maintenance Flashes at the base level. If used, these flashes will be standardized within the MXGs, and at minimum should cover background, concern/condition, and corrective action regarding the maintenance issue. **Note:** Maintenance Flashes/QA Flashes are considered advisory in nature. If Maintenance Flashes/QA Flashes affect more than one unit, they will be coordinated through the appropriate WST for distribution. **(T-2)**

11.44. (Added-AFGSC) Hangar Door Program.

11.44.1. **(Added-AFGSC)** General. This section establishes supplemented procedures for management of powered hangar doors. Powered Hangar Doors as it applies to this program are any powered hangar/shelter/hush house/nose-dock type doors used for aircraft, engine or vehicle entry/exit. See DAFMAN 91-203 for hangar door operations and safety requirements.

11.44.2. **(Added-AFGSC)** MXG/CC is responsible for the Hangar Door Program and must ensure:

11.44.2.1. **(Added-AFGSC)** An assessment of all hangar doors is accomplished. Assessments must address hazards outlined in DAFMAN 91-203 and local/manufacturer peculiarities.

11.44.2.2. **(Added-AFGSC)** A hands-on OJT program is developed for all personnel who operate electric and manual hangar doors. At a minimum, training will include door operations, hazard awareness/abatement, and emergency procedures.

11.44.2.3. **(Added-AFGSC)** Detailed hangar door operating checklists are developed and posted at each hangar door control panel. The checklist will include step-by-step procedures and list the names of the building custodians. Exception: Do not post the checklist on Hush House doors. Post a sign at each door control panel stating, “Operate doors IAW TO 33D4-6-645.”

11.44.3. **(Added-AFGSC)** All areas that pose a potential pinch point or crush area are marked to ensure no one enters the area during door operation. Identify these pinch points, crush areas, and powered door movement areas IAW DAFMAN 91-203.

11.44.4. **(Added-AFGSC)** A policy is developed for cold weather hangar/PAS door closure procedures that adequately prevent fire suppression systems from freezing.

11.45. (Added-AFGSC) [B-52 units] Bomber Airborne Maintenance Support (BAMS) Program.

11.45.1. **(Added-AFGSC)** The AFGSC Bomber Airborne Maintenance Support (BAMS) program is like the FCC program, however, its purpose is to ensure mission readiness for OPLAN, BTF, and Agile Combat Employment (ACE) requirements, while developing mission ready Airmen.

11.45.2. **(Added-AFGSC)** As mission requirements dictate, BAMS personnel fly with the aircraft for the purpose of accomplishing ground maintenance at the TDY location.

11.45.3. **(Added-AFGSC)** BAMS mission requirements will be determined by the OG/CC to enable maintenance support at locations other than home stations to prepare the aircraft for its next departure.

11.45.4. **(Added-AFGSC)** BAMS personnel are qualified in their duty AFSC and are required to obtain, maintain, and apply basic knowledge in several other aircraft maintenance AFSCs. They are responsible for launch, recovery, inspection, servicing, generation, and maintenance of aircraft in austere locations and locations where specific MDS maintenance capability may not be available.

11.45.4.1. **(Added-AFGSC)** BAMS personnel must remain in a ready status and will maintain MDS specific requirements IAW DAFMAN 11-401, *Aviation Management*, and AFI 11-401*, AFGSC SUP*, *Aviation Management*. Expired currency or inability to maintain MDS specific flyer training requirements will be a disqualifier.

11.45.5. **(Added-AFGSC)** BAMS support decisions will be based on mission priority and approved by the BGS/CC or equivalent after coordination with the OSS/CC. OG/CC is the final approval authority for missions when BAMS personnel are requested.

11.45.6. **(Added-AFGSC)** BAMS personnel should accompany AFGSC aircraft to locations away from home station, where MDS specific maintenance capabilities do not exist, especially when the aircraft is expected to remain off station overnight.

11.45.7. **(Added-AFGSC)** Units will process orders as outlined in AFI 65-103, *Temporary Duty /Special Orders*. Ensure BAMS TDY orders specify the following:

11.45.8. **(Added-AFGSC)** BAMS personnel will be authorized billeting/quarters with aircrew. BAMS personnel will not share a room with aircrew members as they are subject to calls from home station (or responsible C2 element). This will ensure aircrew and BAMS personnel receive the required rest.

11.45.8.1. **(Added-AFGSC)** MEP approval authority statement is annotated on travel orders.

11.45.9. **(Added-AFGSC)** Coordinate with SARM (Squadron Aviation Resource Management) office to ensure BAMS personnel meet mission requirements and training resources.

11.45.10. **(Added-AFGSC)** BGS/CC or equivalent will:

11.45.10.1. **(Added-AFGSC)** Administer the squadron BAMS Program IAW DAFI 36-3012, *Military Entitlements.*

11.45.10.2. **(Added-AFGSC)** Appoint and remove personnel from the BAMS Program IAW DAFI 36-3012.

11.45.10.3. **(Added-AFGSC)** Assign BAMS personnel for a minimum of two years.

11.45.10.4. **(Added-AFGSC)** Appoint in writing a Unit BAMS Program Manager. Minimum NCO, or civilian equivalent.

11.45.11. **(Added-AFGSC)** Unit BAMS Program Managers will:

11.45.11.1. **(Added-AFGSC)** Coordinate/track BAMS aircrew training and ready status.

11.45.11.2. **(Added-AFGSC)** Ensure personnel possess the appropriate SEI for their MDS aircraft.

11.45.11.3. **(Added-AFGSC)** Provide information for processing DD Form 1610, *Request and Authorization for TDY Travel* of DoD Personnel, for BAMS personnel.

11.45.11.4. **(Added-AFGSC)** Ensure only qualified BAMS personnel are scheduled for missions.

11.45.11.5. **(Added-AFGSC)** At a minimum, maintain a folder for each BAMS containing training qualifications, immunizations, military passport information, appointment letters, and Mission Reports. If the unit mobility section already maintains these source documents, either electronic or paper copies may be maintained.

11.45.11.6. **(Added-AFGSC)** Coordinate scheduling of BAMS personnel through Flight CC/Chiefs or equivalent and operations schedulers.

11.45.11.7. **(Added-AFGSC)** Maintain a Unit BAMS Program Manager's Continuity Book. At a minimum the continuity book will include:

11.45.11.7.1. **(Added-AFGSC)** Lists of required instructions with web addresses (including DAFI 36-3012 and this instruction).

11.45.11.7.2. **(Added-AFGSC)** Unit BAMS Program Manager appointment letter, DAF Form 2096 or special orders.

11.45.11.8. **(Added-AFGSC)** Submit funding requests for flight clothing, per diem, and other related expenses for the annual budget (for safety during flight, flight clothing is mandatory for BAMS personnel).

11.45.11.9. **(Added-AFGSC)** **Units** will not exceed more than two BAMS personnel per aircraft.

11.45.12. **(Added-AFGSC)** BAMS qualifications and responsibilities.

11.45.12.1. **(Added-AFGSC)** BAMS personnel may be any 2AXXX AFSC, 5- or 7-skill level.

11.45.13. **(Added-AFGSC)** Units will identify minimum maintenance task qualifications. BAMS members must be qualified and certified on the following MDS applicable items:

11.45.13.1. **(Added-AFGSC)** Possess an SEI for B-52 aircraft.

11.45.13.2. **(Added-AFGSC)** Refuel/defuel member and supervisor; concurrent servicing supervisor (as applicable).

11.45.13.3. **(Added-AFGSC)** Tow member, tow supervisor, tow vehicle operator, and tow brake operator.

11.45.13.4. **(Added-AFGSC)** LOX servicing, nitrogen and tire servicing.

11.45.13.5. **(Added-AFGSC)** Tire/brake change, launch, recovery, marshalling, pre-flight, thru-flight, and post-flight inspections.

11.45.13.6. **(Added-AFGSC)** Air and cartridge start system.

11.45.13.7. **(Added-AFGSC)** Engine run.

11.45.13.8. **(Added-AFGSC)** All applicable powered/non-powered AGE.

11.45.13.9. **(Added-AFGSC)** Drag chute removal and installation.

11.45.13.10. **(Added-AFGSC)** Maintain SVA certification.

11.46. (Added-AFGSC) Egress Augmentees. Due to the extraordinary safety and training requirements of the ejection systems of the various aircraft, the Egress Augmentee program is established. This is like other types of cross-utilization training but considers the extra training requirements and all the sensitivity surrounding the ejection systems.

11.46.1. **(Added-AFGSC)** Egress Augmentees are any personnel who do not possess the 2A6X3 AFSC but have completed the training plan developed by the Egress NCOIC. They are certified by the Egress NCOIC via MFR, and remain current until their training expires, or a violation is detected. These members are intended to augment Egress manpower, not replace it.

11.46.2. **(Added-AFGSC)** The number of Egress Augmentees established will be limited at the discretion of the MXG/CC.

11.46.3. **(Added-AFGSC)** Once certified, Egress Augmentees will be granted access to Egress work center tasks in the MIS to document their work.

11.47. (Added-AFGSC) Software Analysis Section [B-1 units]. The Software Analysis Section processes and analyzes B-1 Central Integrated Test System (CITS) or CITS Deployable Diagnostic System (CDDS) data, as applicable, to provide timely and accurate information to aid the maintenance effort, identify software discrepancies to the appropriate OPRs, and identify trends to maintenance supervisors and assigned engineers. B-1 units address all software deficiencies/anomalies associated with aircraft diagnostics using the CDDS. A Software Analysis team comprised of maintenance technicians compares data extracted from the CITS via the CDDS to ensure accuracy and validity of the data in support of airframe availability. This section works closely with maintenance analysis functions to identify trends in system performance. Demonstrated knowledge and ability should be of primary importance in assigning personnel to this section; however, flightline avionics will be represented. All assigned personnel should have performed in their AFSC within the last 3 years.

11.47.1. **(Added-AFGSC)** At a minimum, the responsibilities of this section are to:

11.47.1.1. **(Added-AFGSC)** Analyze and establish the accurate status of all reported CITS Maintenance Codes (CMC) Reference Designator Indicators.

11.47.1.2. **(Added-AFGSC)** Identify adverse system/maintenance trends to appropriate maintenance supervisors and engineers.

11.47.1.3. **(Added-AFGSC)** Identify/Report CITS/CDDS software deficiencies via Product Quality Deficiency Reporting (PQDR) through the Joint Deficiency Reporting System (JDRS) web site.

11.47.1.4. **(Added-AFGSC)** Setup, maintain, repair, and update CDDS server network; update CPIN software when required; remove, repair or replace computers and components.

11.47.1.5. **(Added-AFGSC)** Assist maintenance technicians in identifying and reporting Ground Readiness Test (GRT) deficiencies.

11.47.1.6. **(Added-AFGSC)** Provide CITS/CDDS information products, as required, to support the production effort.

11.47.1.7. **(Added-AFGSC)** Assist/train maintenance technicians to use CITS/CDDS maintenance reports in troubleshooting malfunctions.

11.47.1.8. **(Added-AFGSC)** Maintain historical data for each assigned aircraft in accordance with the RDS.

11.47.1.9. **(Added-AFGSC)** Compile CDDS aircraft data and submit to appropriate system engineers via U. S. Army Aviation and Missile Research Development and Engineering Center (AMRDEC) or Aircraft Structural Integrity Management Information System (ASIMIS).

11.47.1.10. **(Added-AFGSC)** Retrieve and analyze the debrief report from the CDDS in support of each sortie debrief. Analyze new, analysis-coded and data-dependent maintenance codes to determine whether maintenance action is required. If required, notify applicable maintenance flight of the discrepancy. Provide the Debrief Section with a list of CITS/CDDS reported aircraft malfunctions/faults requiring a work center event (job control number) to be entered into MIS/AFTO Form 781A.

Chapter 12

MAINTAINING COMMERCIAL DERIVATIVE AIRCRAFT (CDA).

12.1. Background Information, Objective and Roles and Responsibilities. The USAF procures CDA for various missions. These aircraft are originally type certificated to Federal Aviation Administration (FAA) regulations/orders and have FAA-approved aircraft maintenance manuals. If the aircraft are civil registered (N number displayed) in lieu of military registration and military tail number, it may carry an FAA standard airworthiness certificate if operated and maintained in full compliance with civil regulations.

12.1.1. Civil registered aircraft owned and operated by the USAF IAW Title 10 U.S. Code are public use aircraft. When these aircraft are engaged in civil aircraft operations, such operations must be conducted IAW FAA and civil. When these aircraft are engaged in public aircraft operations, they are exempt from civil regulations and FAA oversight. Civil registered aircraft owned and operated by the USAF may be declared public use at any time and are then exempt from civil regulations and FAA oversight. If the aircraft are civil registered but do not have a civil airworthiness certificate or are operated by the USAF under a military registration and tail number, the aircraft are for public use and operate entirely under the authority of the USAF military technical airworthiness authority.

12.1.2. The FAA defines a Commercial Derivative Aircraft (CDA) as a commercial aircraft with an FAA type certificate (TC) and produced under an FAA Production Certificate (PC). Air Force Policy Directive (AFPD) 62-6, *USAF Airworthiness*, establishes policies for CDA to ensure that any USAF operated aircraft are airworthy over their entire life cycle and maintain high levels of safety. The directive also instructs the USAF to Meet the Intent (MTI) of applicable FAA regulations to the maximum extent practical.

12.1.3. All USAF-managed aircraft, and associated modifications, must meet the requirements of DAFI 62-601, *Airworthiness*, and AFI 63-101/20-101. **(T-2)** PMs are ultimately responsible for maintaining configuration control and ensuring flight safety of systems within their portfolio. When a military mission is compatible with a certified civil usage, the USAF will utilize FAA-type certified CDA to the maximum extent practicable. **(T-2)** To ensure safety and support, all modifications performed on CDA type certificated components or systems will be FAA certified (example, supplemental type certificate). Modifications to CDA military type certificated components or systems require approval of AF chief engineer, or delegated authority.

12.1.4. For maintenance and operations of CDA the AF will use AF-managed TOs or FAA-approved aircraft and component maintenance manuals and FAA regulations called out in Title 14 Code of Federal Regulation Parts **43**, **91**, **121,** and **145** as a guide. **(T-0)** FAA Advisory Circulars, Notices to Airmen, and other FAA information sources may also be used to satisfy all requirements of Title 14 Code of Federal Regulations Parts **43**, **91**, **121,** and **145.**

12.2. AF/A4L will:

12.2.1. Coordinate relevant policies and procedures with SAF/AQ and the FAA.

12.3. The Program Manager (PM) will:

12.3.1. Be responsible for all elements of life cycle management IAW AFI 63-101/20-101. **(T-2)**

12.3.1.1. Evaluate acquisition and sustainment strategies and determine requirements for Contractor Logistics Support (CLS) structure, Organically Managed support structure, and/or hybrid support structure.

12.3.2. When FAA manuals are used, issue technical data for configuration items and inspection requirements that are not approved by the FAA or supplied by the Original Equipment Manufacturer. **(T-2)**

12.3.3. Review evaluations from the Lead Commands concerning Airworthiness Directives (AD), Service Bulletins (SB), Customer Bulletins (CB), All Operator Letters, and Aircraft Service Changes (ASC) and will determine extensions for each, if required. **(T-2)**

12.3.4. For CDA which maintain an FAA Type Certified, ensure that the MAJCOM performs overhauls, rebuilding, major repairs, major alterations, minor repairs, and minor alterations in FAA-authorized repair facilities with appropriate ratings and authorizations or an AF-approved AFSC Military Repair Station depot facility, as directed by the PM. **(T-2)**

12.3.5. Establish a maintenance plan and Service Action Review process with the Lead Command for aircraft originally Type Certified by the FAA. **(T-2)**

12.3.6. Follow AFI 63-101/20-101 for modification requests and approvals. **(T-2)**

12.3.7. Obtain airworthiness approvals IAW DAFI 62-601. **(T-2)**

12.3.8. Coordinate with the FAA Military Certification Office for approval of modifications that affect commercial derivative aircraft configuration IAW USDOT/FAA Order 8110.101, *Type Certification Procedures for Military Commercial Derivative Aircraft*. **(T-0)**

12.3.9. Ensure FAA ADs and SBs are utilized in place of TCTOs, and commercial maintenance manuals are utilized in lieu of AF TOs to the greatest extent possible. **(T-2)**

12.3.10. For units possessing CDA that strictly utilize commercial manuals, may issue original FAA SBs, ADs or other FAA-approved modifications in-place of TCTOs. **(T-2)**

12.3.11. For units possessing CDA that strictly utilize USAF managed TOs, in order to implement ADs, SBs or other FAA-approved modifications, issue TCTOs IAW TO 00-5-1 and TO 00-5-15. Reference one of the following in each TCTO:

12.3.11.1. The AD and/or SB involved.

12.3.11.2. The Supplemental Type Certificate number.

12.3.11.3. Other FAA approval.

12.3.12. Develop a Maintenance Management Program Plan and ensure maintenance planning data is supplied to MAJCOMs, units, and/or contractors in order to operate and maintain airworthiness for the weapon system lifecycle. The program plan meets the intent of the guidance in FAA Advisory Circular 120-16, *Continuous Airworthiness Maintenance Program (CAMP)*.

12.3.12.1. The Maintenance Management Program Plan will outline the requirements to maintain the lifecycle of continued airworthiness of a weapon system in compliance with the intent of Title 14 Code of Federal Regulations (CFR) Parts 43, 65, 121 and 145 throughout its post-production, post-modification DD Form 250, *Material Inspection and Receiving Report* in-service lifecycle. The Maintenance Management Program Plan should include as a minimum:

12.3.12.1.1. Airworthiness Responsibility

12.3.12.1.2. Air Carrier Maintenance Manual

12.3.12.1.3. Maintenance Organization Structure and Function

12.3.12.1.4. Accomplishment and Approval of Maintenance and Alterations

12.3.12.1.5. Maintenance Schedule

12.3.12.1.6. Required Inspection Items

12.3.12.1.7. Maintenance Record Keeping

12.3.12.1.8. Contract Maintenance

12.3.12.1.9. Personnel Training

12.3.12.1.10. Maintenance Program Development

12.3.12.1.11. Configuration Management and Tracking

12.3.12.1.12. Engineering Services

12.3.12.1.13. Continuing Analysis and Surveillance System (CASS)

12.3.12.1.14. Depot Support Plan (if required)

12.4. Lead Commands will:

12.4.1. Ensure any new or modified configurations or maintenance conditions are coordinated with, and approved by, the designated Lead Command IAW AFPD 10-9 and the PM or equivalent responsible for the reliability, maintainability and availability of the systems and end-items prior to implementation. **(T-2)**

12.4.2. Assist ALC in determining additional inspection and component time-change requirements, intervals, documentation and publication update requirements. **(T-2)**

12.4.3. Review evaluations from their field units on ADs, SBs, CBs, All Operator Letters, or ASCs and make recommendations to the aircraft's PM. **(T-2)**

12.4.4. Ensure depot and contractor maintenance providers are furnished with lead command maintenance program and they meet AF approved FAA equivalent requirements or are a FAA approved repair station, as applicable. **(T-2)**

12.5. Units will:

12.5.1. Participate in the Service Action review process established by the PM. **(T-2)**

12.5.2. Assist Lead Commands and the PM to determine additional inspection intervals and requirements. **(T-2)**

12.5.3. Comply with FAA ADs as directed by the Chief Engineer or delegated authority. **(T-2)**

12.6. Maintenance Personnel Requirements. For AF-managed aircraft that maintain an FAA TC and airworthiness, maintenance personnel will meet the Lead Command and PM established requirements and procedures to maintain airworthiness. **(T-2)** AF maintenance technicians performing organic depot maintenance follow Air Force Sustainment Center Instruction (AFSCI) 62-603, Military Repair Station Program, Air Force Sustainment Center Manual (AFSCMAN) 62-602, Military Repair Station Manual.

12.6.1. For CDA that do and do not maintain a civil airworthiness certificate, maintenance is not required to be completed by an FAA-certificated mechanic. However, a Maintenance Management Program Plan detailing the maintenance personnel requirements will be established between the PM and the Lead Command. **(T-2)**

12.6.1.1. The plan will address as a minimum the training requirements, the level of effort allowed (such as, specific maintenance tasks as identified in the Original Equipment Manufacturer maintenance manuals), and tasks that will be performed by FAA-certified mechanics, repair stations, AFSC Military Repair Stations, or the Original Equipment Manufacturer. **(T-2)**

12.6.1.1.1. CDA Training courseware, as applicable, for unique CDA platform requirements, such as but not limited to; Extended Operations (ETOPS and Polar Operations), Materiel Management, Continuing Analysis Surveillance System (CASS), Maintenance Provider Program, Required Inspection Item (RII), Major/Minor Repair) will be addressed in lead command program training development and remain standardized across the entire weapon system. Individual Main Operating Base (MOB) units and depots may augment training as required.

12.6.1.2. The maintenance plan will be approved by the PM with coordination by the FAA Military Certification Office or Military Repair Station/Flight Standards Management Office as appropriate. **(T-2)**

12.7. Deviations/Changes to Inspection Requirements, Time Change Intervals, and Component/Aircraft Overhaul. Commercial derivative aircraft inspection requirements, time change, component and aircraft overhaul intervals are established and controlled by the Original Equipment Manufacturer and approved by the FAA. When deviation from the Original Equipment Manufacturer established maintenance standards/configuration is needed to meet AF mission requirements, units will send proposed changes to the PM through MAJCOM and for evaluation. **(T-2)**

12.8. Air Force Modifications to CDA and Components. AF modifications to CDA and components are developed following procedures outlined in AFI 63-101/20-101. All AF modification requests require coordination with the Chief Engineer or delegated authority who will provide assistance in determining applicable requirements, forms and coordination necessary to correctly disposition aircraft and component modification requests. **(T-2)**

12.9. Certification Basis for CDA. Elements of the certification basis for any CDA which are not met via FAA certification are satisfied by compliance with approved military airworthiness requirements derived from MIL-HDBK-516C, *DoD Handbook, Airworthiness Certification Criteria*. CDA whose primary mission is the transport of passengers are FAA Type Certified; FAA certification of these CDA passenger carrying aircraft is maintained for the life of the air system.

Chapter 13

CENTRALIZED REPAIR FACILITIES (CRF).

13.1. Introduction. CRFs consolidate off-equipment intermediate-level, and in some instances, depot-level tasks for commodities such as aircraft engines, electronic warfare pods, avionics line replaceable units, wheel and tire assemblies, and other aircraft components. CRFs focus on efficiently providing maintenance, repair, and/or overhaul capabilities, support RN efficiencies and will be fully integrated into the AF Supply Chain. CRFs are considered part of the repair network and exist to ensure responsiveness to MGN requirements to sustain operations both at home station and/or when deployed. Management and control procedures are outlined in AFI 20-117.

13.2. Organization. CRFs will be established within existing maintenance organizations (EMS, CMS, MXS), minimizing requirements for overhead and support. **(T-2)** Production oversight and monitoring of repair operations is the responsibility of the owning maintenance organization in which the CRF is established. Commanders with CRFs will manage the personnel, facilities, and processes for the CRF following the policies and procedures in this DAFI and DAFI 20-117. **(T-2)**

13.3. CRF Production Requirements. Maintenance Squadron (EMS, CMS, MXS) Director of Operations/MX SUPT will:

13.3.1. Ensure the Node Manager (NM) executes enterprise production duties as outlined in AFI 20-117. **(T-2)**

13.3.2. Ensure the NM identifies and up-channels repair constraints that affect CRF repair/RN CAP2 to the MFM and RNM as prescribed in DAFI 20-117.

13.3.3. Ensure the NM utilizes information management systems and participates in RNM collaboration calls to provide timely status reports, resolve repair constraints, and receive revised repair requirements/RN changes. **(T-2)**

13.3.4. Identify systemic distribution, transportation, and supply difficulties and coordinate with base LRS leadership and/or up-channel concerns to the RNM and MFM for resolution. **(T-2)**

13.3.5. Follow established procedures to ensure the rapid movement of retrograde and sustainment assets to support enterprise requirements.

13.4. MGN Support. Units supported by CRFs will maintain the level of intermediate-level repair capability necessary to sustain MGN operations. MAJCOMs must identify intermediate-level tasks and resources required to perform MGN maintenance tasks for assigned weapon systems (for example, repair of XF3 assets, hose/tube testing, functional checks, NRTS screening).

13.4.1. Rotable Pools. Customer Wait Time and transportation constraints may drive the establishment of a Centralized Rotable Pool for Class VII end items such as engines and pods to meet established weapons system availability goals. Use of a Centralized Rotable Pool can enhance mission capability by placing serviceable assets closer to the user when the repair capability is off installation. Centralized Rotable Pool size, compared to support unit spare levels, will be determined during deliberate planning between the appropriate RNM and MAJCOMs.

13.4.2. Cannibalization at supported units. When commodity LRU local retail stocks fall below mission requirements, retention of CRF-repaired end items as "CANN assets" may be necessary. However, this will be by exception and must be approved by the appropriate RNM in coordination with the supporting MAJCOM CRF Manager. **(T-2)** CRFs will document their cannibalization process and notify supporting unit of approval to retain CANN assets. **(T-2)**

13.4.3. Provide CRF node performance, CAP2, and commodity status reports and metrics as defined in DAFI 20-117. **(T-2)**

13.4.4. Ensure the NM utilizes information management systems to provide timely status reports and receive workload requirements/ changes for commodity group repairs supported by the CRF IAW with AFI 20-117. **(T-2)**

13.5. CRF Enterprise Information Management. Managers require accurate, timely, and enterprise repair data to make CRF command and control and production decisions. To facilitate this requirement, NMs will utilize systems, processes, and business rules prescribed by AFI 20-117 to provide repair data and ensure enterprise visibility. **(T-2)**

13.6. Documentation. The CRF and supported units will maintain all required status, inventory, and historical record documentation on CRF-repaired assets, IAW TO 00-20-1 and DAFI 21-103.

13.7. Metrics. CRFs will report performance against metrics IAW DAFI 20-117.

Chapter 14

MAINTENANCE PLANS, SCHEDULING AND DOCUMENTATION (PS&D).

14.1. Responsibilities:

14.1.1. and 14.1.1.1. DELETED.

14.1.2. MAJCOMs will:

14.1.2.1. Supplement this instruction to establish minimum requirements for the following:

14.1.2.1.1. TCTO folders and monthly/weekly utilization and maintenance schedules.

14.1.2.1.1. **(AFGSC)** See **paragraph 14.3.3.3.2.3** for MAJCOM procedures.

14.1.2.1.2. Publish MAJCOM procedures for verification of configuration items.

14.1.2.1.2. **(AFGSC)** See paragraphs **14.2.4.2.2**, **14.2.4.2.7**, **14.2.4.3.4** for MAJCOM procedures.

14.1.2.1.3. Determine whether to ship removed engines to depot or induct into CRF repair.

14.1.2.1.3. **(AFGSC)** See **paragraph 14.4.1.3.10** for MAJCOM procedures.

14.1.2.1.4. Determine routing and approval for AF Form 2407.

14.1.2.1.4. **(AFGSC)** See **paragraph 14.5.6.3.8.1** for MAJCOM procedures.

14.1.3. PS&D will:

14.1.3.1. Maintain historical documents and maintenance data essential for the development of wing plans, schedules, and analysis of historical maintenance events. **(T-2)**

14.1.3.1. **(AFGSC)** Units will automate new AFTO Form 95 and maintain them in the MIS. This approach eliminates duplication and provides a single source repository. If current AFTO Form 95 documents are partially automated, then complete automation is highly encouraged. When the AFTO Forms are completely automated and reconciled for 100% accuracy, destroy the duplicate hard copies. Units that choose to maintain the original hard copies, will document the hard copy with an entry that states, "History as of this date is automated and maintained in the MIS." Also, the first entry of the continuation/automated AFTO Form 95 will be documented with an informational entry, "Previous history as of this date is maintained in the aircraft jacket file or decentralized file." **(T-2)**

14.1.3.1.1. **(Added-AFGSC)** Notify the item manager when items are received and AFTO Form 95 is missing for proper disposition instructions.

14.1.3.2. Maintain historical maintenance data within the MIS. **(T-2)**

14.1.3.2. **(AFGSC)** In conjunction with Maintenance Management Analysis (MMA), MO PS&D will develop manual JCN block assignment and procedures. MIS-CDB uses year-event-identifiers instead of JCNs and uses an automatic JCN assignment feature. The

procedures need to be established only for manual input of JCNs during MIS-CDB downtime and deployment processing. **(T-2)**

14.1.3.3. Develop wing maintenance plans using MIS aircraft/system historical data input by all maintenance personnel. **(T-2)**

14.1.4. The PS&D Section NCOIC/Chief (or equivalent) will:

14.1.4.1. DELETED.

14.1.4.2. Establish and coordinate plans for rotating 2R1XX personnel through various duty positions to increase field knowledge and experience every 24 months, not to exceed 36 months. **(T-2)**

14.1.4.2.1. This rotation plan applies to TSgts and below as well as 3- or 5-skill level personnel of any rank. **(T-3)**

14.1.4.3. Evaluate quarterly the performance of workcenters performing scheduling functions to include TCTO, SI, and Job Standard Master Listing (JML) management (such as, AGE, Armament, Egress, Fuels, MXO, PS&D). **(T-2)**

14.1.4.3.1. During the visit, ensure historical documents are properly maintained and review and discuss the 2R1X1 training and rotation plan with each section NCOIC that have 2R1s assigned. **(T-2)**

14.1.4.3.2. Provide formal written reports of deficiencies found during the visits to the MXO DO/SUPT and applicable section NCOIC. **(T-2)**

14.1.4.3.2.1. Deficiencies will not be closed until validated by the MXO DO/SUPT. **(T-2)**

14.1.4.4. - 14.1.4.4.2. DELETED.

14.1.4.5. Provide SME on all maintenance scheduling issues and equipment historical document AFTO Form 95 management to QA during inspection/evaluations. **(T-2)**

14.1.4.6. Designate the MSM administrator from within PS&D (for units utilizing IMDS only). **(T-2)**

14.1.4.7. **(Added-AFGSC)** Ensure personnel performing scheduling functions in sections where 2R personnel are not assigned (e.g., armament, AGE) either permanently or temporarily are trained in day-to-day scheduling tasks. Ensure a DAF Form 797, or equivalent, is developed for each required area, and ensures training is provided. The unit 2R functional will establish training procedures and ensure coordination is accomplished with the respective work center section chief. **(T-2)**

14.1.4.8. **(Added-AFGSC)** Inventory of Records**.** Review MO PS&D and decentralized scheduling section(s) inventory of record (formally the file plan) annually. Ensure critical records are identified with appropriate disposition and updates are made within AFRIMS by the COR (e.g., official signed schedules, TCTO files/records, TCI files/records, Jacket Files, AVDO files/records, records requiring AF Form 2411, etc.) Keep the most current inventory of records on file. Document annual review on AF Form 2411. Electronic versions of records are acceptable for critical records. **(T-2)**

14.1.5. The Wing AVDO will:

14.1.5. **(AFGSC)** If decentralized, MO PS&D is responsible for the wing AVDO program. The primary AVDO will be assigned to MO PS&D. **(T-2)** BGS PS&D may be designated as an alternate AVDO.

14.1.5.1. Complete AVDO duties IAW DAFI 21-103 and maintain the inventory and utilization portion of the MIS Inventory, status, and utilization subsystem. **(T-2)**

14.1.5.2. Maintain a PDM schedule by tail/serial number for all assigned aircraft and equipment in support of AFMC and Lead Command plans and requirements. **(T-2)**

14.1.5.2. **(AFGSC)** PS&D will coordinate with the applicable AFGSC/A4A or AFGSC/A4B WST aircraft manager when developing PDM schedule/listing. **(T-2)**

14.1.6. Unit Dedicated Scheduler will:

14.1.6.1. Provide dedicated support to AMXS/AMU. **(T-2)**

14.1.6.2. Attend and actively participate in daily, weekly, and monthly scheduling, and quarterly and yearly planning programs and meetings. **(T-2)**

14.1.6.2.1. Inform Unit supervision of maintenance capabilities or limiting factors that could affect maintenance production. **(T-2)**

14.1.6.3. Coordinate with Unit supervision and Operational Squadron (OS) operations schedulers when scheduling Unit aircraft to meet flying requirements. **(T-2)**

14.1.6.4. Provide a listing of JCNs for following week's scheduled maintenance. **(T-2)**

14.1.6.4.1. This list will be used to track Maintenance Scheduling Effectiveness (MSE). **(T-2)**

14.1.6.4.2. PS&D will determine causes of missed maintenance for reporting MSE. **(T-2)**

14.1.6.5. Manage TCTOs, TCIs, and Sis (including installed engine inspections) for aircraft assigned to their appointed AMXS/AMU. **(T-2)**

14.1.6.5. **(AFGSC) [NC3]** Aircraft with NC3 platforms installed will have associated sub-system TCIs and SIs managed in IMDS for the NC3 platform, not the aircraft.

14.1.6.6. Generate AFTO Form 103, *Aircraft/Missile Condition Data*, to record certified maintenance needs for aircraft requiring depot maintenance IAW TO 00-25-4, *Depot Maintenance of Aerospace Vehicles and Training Equipment*, coordinate it with PS&D, QA, and AMXS maintenance supervision. **(T-2)**

14.2. Data Documentation.

14.2.1. Maintenance Historical Documentation.

14.2.1.1. Maintenance historical documentation will be accomplished IAW TO 00-20-1 which outlines the requirements to capture and record the significant maintenance actions on aerospace vehicles and equipment. **(T-2)**

14.2.1.2. Historical documentation will be entered and tracked in the authorized MDS MIS. **(T-2)** When the MIS is not available, historical documentation will be documented and tracked on the AFTO Form 95, or equivalent. **(T-2)**

14.2.1.2. **(AFGSC)** Annual inspections are required for hard copy/manually maintained items. Automated AFTO Form 95 items will be reconciled to ensure all required items are tracked and loaded with a historical header using MIS screen 390. Programs developed by database managers are recommended to identify missing AFTO Form 95 tracked items and/or missing Automated History Event (AHE) header record. **(T-2)**

14.2.1.2.1. **(Added-AFGSC)** Automated history is the primary method for maintaining individual historical documents. Aircraft and component MIS history will be saved to file/disk and placed into the jacket file only for permanent equipment transfer or when requested (e.g., accident/safety investigation board). Ensure history files are not corrupt prior to placing them into the jacket file. Maintain a back-up file until the gaining unit confirms receipt. Ensure AFTO Form 95s are printed and shipped with the item for overhaul. **(T-2)**

14.2.1.3. MAJCOMs should develop supplements to this instruction to identify aerospace vehicle and support equipment historical file content and retention requirements needed beyond the minimum requirements outlined in this instruction and TO 00-20-1.

14.2.2. Aircraft jacket files. Units will develop and maintain a standardized master aircraft jacket file for use throughout the wing following the requirements listed in this instruction, TO 00-20-1 and AFI 33-322.

14.2.2.1. MAJCOMs will standardize MDS-specific requirements not captured in this instruction in supplements and addendums to this instruction.

14.2.2.1. **(AFGSC)** Standardize MDS-specific aircraft jacket files IAW TO 00-20-1 and AFI 33-322.

14.2.2.2. Aircraft jacket files will be maintained in PS&D and standardized IAW the master aircraft historical file developed by the PS&D NCOIC. **(T-2)**

14.2.2.2.1. Off-equipment maintenance documents may be decentralized to sections maintaining installed-on equipment assets (examples include fuel cell records at fuel systems section, landing gear strut records at hydraulics section).

14.2.2.2.1.1. Decentralized records are filed by and are the responsibility of the owning work center.

14.2.2.2.2. PS&D will list all historical records, in their file plan or office of record. **(T-2)**

14.2.2.2.2.1. The DD Form 2861, *Cross-Reference*, will be used to cross-reference documents decentralized from PS&D to other sections and will be filed to cross reference AFTO Form 95 records that are maintained in the MIS. **(T-2)**

14.2.2.2.3. Wing-assigned aircraft jacket files may be maintained electronically; however, they must mirror the standardized master aircraft jacket file in organization and appearance. **(T-2) Note:** Slight variations in composition are allowed between different MDS weapons systems located within the same wing.

14.2.2.3. MXG/CC may identify additional local items for inclusion in aircraft jacket files. Aircraft jacket files as a minimum will include:

14.2.2.3.1. Packages for one complete inspection cycle. **(T-2)** Units may download paperless inspections to automated storage media from MIS for filing in aircraft jacket files.

14.2.2.3.2. Last FCF documentation (such as, FCF certification letter/FCF checklist). **(T-2)**

14.2.2.3.3. Last depot package. **(T-2)**

14.2.2.3.4. Transfer packages. **(T-2)**

14.2.2.3.5. Applicable weapon system -6 TO AFTO Form 95s. **(T-2)**

14.2.2.3.6. W&B records. **(T-2)**

14.2.2.3.7. Engine Records. **(T-2)**

14.2.2.3.8. Document review records/checklists. **(T-2)**

14.2.2.3.9. NDI records. **(T-2)**

14.2.2.3.10. AF Form 2411, Inspection Document (or equivalent). **(T-2)**

14.2.2.3.11. Annual aircraft jacket file review checklist. **(T-2)**

14.2.2.3.12. Authorized TO variances. **(T-2)**

14.2.2.3.13. Requests for assistance meeting the requirements for retention as historical records IAW TO 00-25-107, or equivalent/like MDS specific requirements for retention of documents as historical records. **(T-2) Note:** Contact the Lead Command as identified in AFPD 10-9 for guidance for meeting retention as historical records requirements outside the scope of TO 00-25-107.

14.2.2.3.14. Pulled AFTO Form 781-series aircraft forms. **(T-2)**

14.2.2.3.14. **(AFGSC)** Aircraft with NC3 equipment installed will also have 781-series forms (or equivalent) in the jacket file.

14.2.2.3.14.1. Pulled paper forms retained as part of the jacket file will be destroyed after 3 months if they do not contain historical information IAW AFRIMS. **(T-2)**

14.2.2.3.14.2. Fusing fully automated forms will maintain the last 7 copies of the pulled aircraft forms and destroy the earliest record when the 8th report is received IAW AFRIMS. **(T-2)**

14.2.2.3.14.3. Units not required to use a MIS will use aircraft forms and maintain the current and the last 3 months' worth of pulled aircraft forms. **(T-2)**

14.2.2.3.14.4. Pulled 781 forms will be filed in order by sets identified by the "From and To" date at the top of each 781-series form (see TO 00-20-1). **(T-2)**

14.2.2.3.14.5. Sets of forms may or may not include an AFTO Form 781J, *Aerospace Vehicle – Engine Flight Document* and AFTO Form 781K, *Aerospace Vehicle Inspection, Engine Data, Calendar Inspection and Delayed Discrepancy Document*. AFTO Forms 781J and K will be included in the set of forms they were pulled with and retained for the same period of time. **(T-2)**

14.2.2.3.14.6. When PS&D discovers the AFTO Form 781-series missing during a jacket file inspection, a missing-forms letter will be sent to the appropriate Maintenance Supervision of the maintenance unit responsible for pulling the forms with a 5 duty-day suspense. **(T-2)**

14.2.2.3.14.6.1. If a response is not returned within 5 duty days, notify the applicable maintenance unit supervision. **(T-2)**

14.2.2.3.14.6.2. If the forms cannot be located, file the missing forms letter, endorsed by the Maintenance Supervision in place of the missing forms. **(T-2)** See TO 00-20-1 for missing form procedures and AFI 33-322 for records management and disposition instructions.

14.2.2.4. Annual jacket file review. Review aircraft jacket files annually using a locally-developed PS&D checklist. **(T-2)**

14.2.2.4.1. The last completed checklist will be kept on file in each aircraft jacket file. **(T-2)**

14.2.2.4.1. **(AFGSC)** Annual jacket file completion will be documented on an AF Form 2411. **(T-2)**

14.2.3. Aircraft Document Reviews (ADR). ADRs validate and correct any errors on airframe and engine operating times and cycles, TCTO documentation, TCI component operating times, time remaining to the next inspection, backordered supply document numbers and open deferred discrepancies. The aircraft AFTO Form 781-series for possessed aircraft are reviewed by aircraft crew chiefs, flightline maintenance functions, PS&D, Engine Management (EM) and LRS personnel to ensure the accuracy and validity of entries.

14.2.3. **(AFGSC)** The NC3 AFTO Form 781-series (or equivalent) will be included in ADRs.

14.2.3.1. MAJCOMs will standardize the MIS/on-line products used to perform ADR on like-MDS weapons systems.

14.2.3.1. **(AFGSC)** IMDS units will use Automated Records Check (ARC) during ADR. **(T-2)**

14.2.3.1.1. Units using MDS-specific laptop forms (for example Integrated Maintenance Information System (IMIS), Autonomic Logistics Information System (ALIS)) must develop procedures to ensure intent of ADRs is implemented. **(T-2)**

14.2.3.2. An ADR will be accomplished at least every 60 days for units using the fully automated AFTO Form 781-series (AFTO Form 781A, AFTO Form 781J, *Aerospace Vehicle – Engine Flight Document*, AFTO Form 781K, *Aerospace Vehicle Inspection, Engine Data, Calendar Inspection, and Delayed Discrepancy Document*. **(T-2)**

14.2.3.2.1. Units without access to a MIS and authorized to use manual AFTO Form 781-series, must accomplish an ADR at least every 30 days. **(T-2)**

14.2.3.2.1.1. **(Added-AFGSC)** If the aircraft was away from home station and the last Aircraft Document Review (ADR) exceeds 60 calendar days; an ADR will be accomplished within 5 duty days after return to home station. A document review will be performed on aircraft prior to assuming alert/IR status. For aircraft on alert/IR status, document reviews may be done at the alert/IR facility. **(T-2)**

14.2.3.2.2. ADRs will also be accomplished when an aircraft is transferred, before and after scheduled inspections (PH or ISO), before and after storage and after fatigue tests. **(T-2)**

14.2.3.2.3. For CANN aircraft, conduct ADRs at least every 30 days. **(T-2)**

14.2.3.3. Units will develop and publish an ADR checklist for use by home station and deployed units. **(T-2)**

14.2.3.3.1. This checklist will identify who initiates the ADR, reviewing agencies (to include the OAP lab), AFTO Form 781-series entry requirements, agency responsible for completing the AFTO Form 781-series/MIS entry, and outline any configuration verification requirements. **(T-2)**

14.2.3.4. ADR Procedures.

14.2.3.4.1. PS&D will create a JST for ADRs on a red dash symbol and ensure it is loaded against all assigned aircraft. **(T-3)**

14.2.3.4.2. ADRs will be scheduled and added to the appropriate maintenance plan. **(T-2)** An ADR is a scheduled maintenance action and will be included in MSE computations. **(T-2)**

14.2.3.4.3. PS&D and EM will validate applicable inspection, TCI, TCTO data for correct due dates/time or expiration dates, airframe, and engine operating times (or flight times if applicable) and appropriate symbol entry IAW TO 00-20-1. **(T-2)**

14.2.3.4.4. Units will coordinate with /LRS to run a tail number inquiry to validate backorders and correct any discrepancies discovered. **(T-2)**

14.2.3.4.5. Maintenance personnel will correct all discrepancies discovered during the ADR, prior to signing off the ADR JCN. **(T-2)**

14.2.3.4.5.1. If an ADR discrepancy cannot be corrected immediately, document the ADR discrepancy in the AFTO Form 781A with a JCN and applicable symbol and retain it in the AFTO Form 781-series forms until corrected and signed off. **(T-2)** Once all the uncorrected discrepancies are documented in the AFTO Form 781- series the ADR can be signed off as complete.

14.2.3.4.5.2. **(Added-AFGSC)** Aircraft Section (DCC or Alternate), Section NCOIC and Flight Chiefs will reconcile the on-line Automated Records Check (ARC) with aircraft AFTO Form 781-series to ensure the forms and MIS match. DCC initiate actions to correct discrepancies, sign off the ADR JCN in the MIS and forward to PS&D for filing. Replace the old ADR package with the most current/recently completed ADR package in the Jacket File. **(T-2)**

14.2.3.4.5.3. **(Added-AFGSC)** Discrepancies with a scheduled start date and time greater than 10 calendar days after the date of discovery will be deferred if no action/work is being accomplished on the discrepancies/JCN. **Exception:** when major maintenance is scheduled, the JCN does not need to be deferred unless it is 10 duty days past its scheduled 'end date' per the current AF Form 2402, Weekly Equipment Utilization and Maintenance Schedule. An example being “A0001 scheduled for major maintenance from 1 October through 15 October” on AF Form

2402. The JCN would not need to be deferred until 25 October if there is a delay. If the major maintenance is still in work, there is no deferment needed as work is still being accomplished. If work is deferred, the appropriate code will be used. **(T-2)**

14.2.4. Pre-Dock Meetings. PS&D personnel will:

14.2.4.1. Review planned aircraft inspection schedules and initiate an AF Form 2410, *Inspection/TCTO Planning Checklist*, or locally developed product for each aircraft prior to the pre-inspection meeting. **(T-2)**

14.2.4.1.1. MAJCOMs may determine if the pre/post dock requirement for inspections with less than a 200-hourly or 200-calendar day cycle is required. If it is determined that a pre/post dock meeting is not required, initiation of an AF Form 2410 is not necessary.

14.2.4.2. Host meetings and notify the appropriate Maintenance Supervision and flight supervisors of any recurring problems with attendance. **(T-2)** Prior to the pre-dock meeting, PS&D will:

14.2.4.2.1. Determine pre-dock meeting attendees. **(T-2)**

14.2.4.2.1.1. The following personnel will attend the meeting as a minimum: PS&D, Pro Super, Inspection Dock NCOIC, aircraft crew chief, DMS/Supply representative, and EM representative. **(T-2)**

14.2.4.2.1.2. Include other agencies as required for performance of the work package.

14.2.4.2.2. Review and list all known aircraft and equipment TCTOs, TCIs, SIs, and other major requirements to be accomplished during the inspection on the AF Form 2410, or locally developed product. **(T-2)**

14.2.4.2.2. **(AFGSC)** Out-of-configuration Inspection/Time Change/TCTO items with established life limits will be resolved prior to post-docking the aircraft. Unresolved issues will be brought to AMXS/MXS/MO supervision immediately and resolved prior clearing the inspection suspense validation. **(T-2)**

14.2.4.2.3. Identify requirements for kits or parts. **(T-2)**

14.2.4.2.4. List all Delayed Discrepancies to be accomplished during the inspection on the AF Form 2410 keeping the original JCN. **(T-2)**

14.2.4.2.5. Incorporate all requirements against the aircraft into a work package. **(T-2)**

14.2.4.2.6. List specialist tasks required in addition to normal inspection needs. **(T-2)**

14.2.4.2.7. Develop a list of items identified as out-of-configuration for verification/correction during the inspection. **(T-2)**

14.2.4.2.7.1. For non-configuration tracked aircraft, compile a list of missing serially controlled items and coordinate/forward them to Inspection Dock NCOIC for verification. **(T-2)**

14.2.4.3. At the pre-dock meeting, PS&D will brief representatives of the inspection schedule and scope, including TCTOs, TCIs, SIs, DDs, and special requirements to be accomplished. **(T-2)**

14.2.4.3.1. Agency representatives will inform PS&D of limiting factors that might affect the schedule. **(T-2)**

14.2.4.3.2. PS&D will discuss aircraft configuration during all aircraft pre-dock meetings. **(T-2)**

14.2.4.3.3. Wings will use the AF Form 2410, or locally developed product to record additional information discussed during the pre-dock meeting. **(T-2)**

14.2.4.3.3.1. Maintain the original AF Form 2410, or locally developed product on file in the aircraft jacket file for use as a guide when conducting the post-dock meeting. **(T-2)**

14.2.4.3.3.2. Provide a copy to the Inspection Dock NCOIC or equivalent for use during the post-dock meeting. **(T-2)**

14.2.4.3.4. PS&D will provide a copy of the applicable "out of configuration" MIS products (such as, IMDS screen 810 and 990; FMxC2, screen 8110; serial number checklists) to Inspection Dock NCOIC in pre-dock package for verification/correction. **(T-2)**

14.2.4.3.4. **(AFGSC)** PS&D Sections with aircraft that do not have an established configuration table will provide the inspection dock chief with a serial number verification worksheet which, at a minimum, will include applicable MDS –6, AFTO Form 95, and TCI requirements. **(T-2)** The worksheet is a tool to verify the serial numbers of items that are accessible during the inspection.

14.2.4.3.4.1. The responsible work center will correct verified erroneous data and "out of configurations" in the MIS prior to post-dock. **(T-2)**

14.2.4.3.5. As a minimum, the following will also be discussed at the pre-dock meeting:

14.2.4.3.5.1. The type and number (if applicable) of the inspection to be performed. **(T-2)**

14.2.4.3.5.2. Validation of current aircraft and engine operating times. **(T-2)**

14.2.4.3.5.3. Parts in the TNB that require aircraft installation. **(T-2)**

14.2.4.3.5.4. Any known post inspection fuel cell work required. **(T-2)**

14.2.4.3.5.5. Date the aircraft is to be ready for the flightline to accept back. **(T-2)**

14.2.4.3.5.6. All known engines requiring replacement. **(T-2)**

14.2.4.3.5.7. Review of the aircraft forms open discrepancies including Delayed Discrepancies and develop a joint plan to work as many discrepancies as feasible/applicable. **(T-2)**

14.2.4.3.5.8. Any inspections that will require maintenance personnel to stop work (such as, NDI shop requirements) and when the maintenance dock needs to be clear

of personnel to perform the inspections. **(T-2)**

14.2.4.3.5.9. All meeting attendees will sign the AF Form 2410. **(T-2)**

14.2.5. Post-Dock Meetings. Units will hold a post-dock meeting as soon as possible after the inspection but no later than before the FCF or first flight. **(T-2)** PS&D will:

14.2.5.1. Lead a post-dock meeting for all inspections that required a pre-dock meeting. **(T-2)** As a minimum, discuss and validate the following information at the post-dock meeting:

14.2.5.1.1. PS&D, Pro Super, Inspection Dock NCOIC, Aircraft Section representative/crew chief and other locally determined attendees will discuss open discrepancies, review any significant inspection events, and identify any problems that may adversely affect future scheduling. **(T-2)**

14.2.5.1.2. The Inspection Dock NCOIC will provide the completed inspection work package to PS&D for filing until it is replaced by the next similar inspection work package. **(T-2)** For example, an HPO1 will be replaced by the next HPO1 and the HPO2 will be replaced with the next HPO2.

14.2.5.1.3. The Inspection Dock NCOIC will return the completed serial number verification sheet to the PS&D representative. **(T-2**

14.2.5.1.4. The Inspection Dock NCOIC or designated representative and the aircraft crew chief or equivalent will perform an aircraft documents review. **(T-2)**

14.2.5.1.5. PS&D personnel will validate TCTOs, TCIs, and SIs scheduled during the inspection were completed and signed off in the MIS prior to the post dock meeting. **(T-2)**

14.2.4.1.5.1. DELETED.

14.2.5.1.5.2. Validate that any TCTO/TCI/SI not complied with will not ground the aircraft before releasing the aircraft back to flightline maintenance personnel. **(T-2)**

14.2.5.1.6. Verify all parts placed on order during the inspection but not received have valid document numbers.

14.2.5.1.7. If maintenance actions previously identified for completion at the pre-dock meeting were not accomplished, establish agreements as to how these inspection requirements will be completed and documented on the AF Form 2410 or locally developed product with the reason why it was not performed. **(T-2)**

14.2.5.1.7.1. The Inspection Dock NCOIC and flightline maintenance supervisor (Pro Super or above) agree that all inspection requirements are completed and the flightline supervisor agrees to accept or “buy back” the aircraft. **(T-2)**

14.2.5.1.8. PS&D will file the completed AF Form 2410, or locally developed product, and completed/verified copies of the output products in the aircraft jacket file (PS&D retains completed package until the next scheduled PH/ISO inspection for that aircraft). **(T-2)** Electronic versions may be saved to digital media.

14.2.6. MIS (FMxC2/IMDS) extended downtime (more than 48 hours).

14.2.6.1. If the MIS is not available for more than 48 hours, maintenance organizations will use the most current data contained in MSM for IMDS units and "Global Reach" system products for FMxC2 units. The MSM database will be refreshed with new MIS products daily. **(T-2)**

14.2.6.1.1. MSM usage may continue in a digital format as long as updates can be made and retained.

14.2.6.2. Units will develop guidance to establish procedures to accurately manage Time Change Items, Special Inspections, and Time Compliance Technical Orders during Maintenance Information System (MIS) extended downtime, outage, or intermittent operability. These procedures are to ensure health of fleet and aircraft safety of flight. **(T-2)**

14.2.6.2.1. For PS&D and workcenters performing maintenance scheduling functions local guidance will address procedures to validate operating times (i.e., hours, cycles, starts, landings, rounds, due dates...etc.) affecting the accurate management of Time Change Items, Special Inspections, and Time Compliance Technical Orders weekly during extended or intermittent MIS outage or faulty operability. **(T-2)** Document completion on AF Form 2411, *Inspection Documentation*. **(T-2)**

14.2.6.2.2. MSM, Global Reach system products, or local tracking products may be used until the MIS is restored and backlog data has been loaded and verified in the system. If debriefed sorties are unable to be loaded into the MIS, the debrief section will provide a cumulative breakdown of sorties and hours completed daily to PS&D and MMA to ensure operating times reflect accordingly on locally tracked products and use to forecast scheduled maintenance actions. **(T-2)**

14.2.6.2.3. Munitions, Engine Management, AGE, and workcenters performing scheduling functions will provide operating times (i.e., hours, cycles, starts, rounds, due dates...etc.) as required by PS&D. **(T-2)**

14.2.6.3. If data cannot be retained by MSM or Global Reach, the use of AFTO Form 349, *Maintenance Data Collection Record*, or local developed form, will be initiated for use in data collection/completion. **(T-2)**

14.2.6.3.1. The most current paper or electronic version of MIS products will be used once AFTO Form 349 or electronic equivalent usage is initiated. **(T-2)**

14.2.6.3.2. The AFTO Form 349 or electronic equivalent, will be used to update applicable MIS products once brought back online. **(T-2)**

14.2.6.3.3. The AFTO Form 349 or electronic equivalent, will be maintained until the data listed on it has been verified as captured/loaded in the MIS. **(T-2)**

14.2.6.3.4. After all changes have been verified in the MIS, destroy the AFTO Form 349 or electronic equivalent.

14.2.6.4. If an aircraft is temporarily moved to an operating location away from the unit of assignment and connectivity to the MIS is unavailable, units will send only those documents necessary to ensure safety of flight and current aircraft status. **(T-2)**

14.2.7. Aerospace Vehicle and Equipment Mishap Response Procedures:

14.2.7.1. PS&D will coordinate with MMA or equivalent to ensure MIS lock out procedures to prevent further manipulation of data concerning the aerospace vehicle and/or equipment used during maintenance prior to the mishap event are completed IAW **Chapter 5**. **(T-2)**

14.2.7.2. At a minimum, produce, consolidate, and impound the following products: aircraft jacket file, aircraft AFTO Form 95s, TCTO history, debriefing records, pulled AFTO Form 781-series forms, SI/TCI data, maintenance history, automated records check. **(T-2)** Include any additional significant historical data, and other decentralized records. **(T-2)**

14.2.7.3. EM will download and impound engine records from the applicable MIS and CEMS. **(T-2)**

14.3. Configuration, TCTO, SI and TCI Management.

14.3.1. Responsibilities. MAJCOMs will establish PS&D requirements and responsibilities to support work centers whose duties require scheduling functions for the equipment they maintain (such as, Egress, Armament, Aerospace Ground Equipment, and Fuels) in a supplement to this instruction.

14.3.1.1. PS&D will provide work centers whose duties require scheduling functions (such as, Egress, Armament, and Aerospace Ground Equipment, Fuels) SME training support and oversight of scheduling products necessary to ensure configuration data integrity is maintained. **(T-2)** PS&D will:

14.3.1.1.1. Outline procedures for ordering hazardous materials for TCIs and TCTOs (such as, batteries). **(T-2)**

14.3.1.1.2. Units using a MIS will not delegate suspense validation processing for TCIs installed on aircraft to the performing work center unless the written procedures include the following: a list of work centers and specific technicians authorized to process suspenses; a list of the specific suspenses authorized to be cleared; and the method for notifying PS&D of the work completed (an audit trail) (IMDS units only). **(T-2)**

14.3.1.1.2. **(AFGSC) [B-52 & B-1 units]** The AFE Section is responsible for completing removal and installation tasks assigned in MIS for personnel parachutes and survival kits. AFE personnel will provide due dates for all Time Change Items, Special Inspections, and open Time Compliance Technical Orders to the unit scheduler. The unit (BGS, AMXS, etc.) scheduler will ensure all applicable MIS/JSTs are updated to reflect the correct due dates before the first flight. All other removal and installation tasks will be completed by the performing agency (e.g., Egress, Crew Chiefs). If decentralized, BGS PS&D will perform this function. **(T-2)**

14.3.1.1.2.1. Ensure EM processes all IMDS suspense validations for engines and engine components. **(T-2)**

14.3.1.1.3. Validate that data errors are corrected with appropriate personnel and updated in the MIS weekly. **(T-2)**

14.3.1.1.4. Submit MSM trouble tickets at **https://midtier.gunter.af.mil/**, call the Field Assistance Branch at DSN 596-5771, or e-mail **team4@gunter.af.mil** to correct program deficiencies. **(T-2)**

14.3.2. Configuration Management. Configuration management provides unit managers the capability to determine the actual versus approved configuration of an aircraft or equipment. The intent of configuration management is to ensure selected serially controlled and/or TCIs are properly loaded to the MIS database with accurate, approved part numbers, Quantity per Assembly and Next Higher Assembly items by WUC/LCN. PS&D has overall responsibility for the Equipment Configuration Management or Aircraft Configuration Management subsystem of the MIS and will provide assistance to maintenance personnel. **(T-2)** The performing work center supervisor and PS&D will validate configuration change, TCTO, SI and TCI events using MIS on-line capabilities. **(T-2)** Individual work centers accomplishing TCIs are responsible for changing configuration information in MIS. Unless otherwise specified in local procedures, schedulers will process all removal, installation, TCI, SI and TCTO compliance updates for aircraft and equipment in the applicable MIS and EM will process engines and engine components in applicable engine information system. **(T-2)**

14.3.2.1. Lead Commands will ensure procedures exist and are executed to provide system configuration tables which are updated, validated, and provided to field maintenance personnel as configurations change. **(T-2)**

14.3.2.1.1. Items not accessed or visible during field-level maintenance will be identified to Lead Command and AFSC managers for disposition. **(T-2)**

14.3.2.2. Maintenance personnel discovering an item with a missing data plate, or one which does not have a serial number, will contact PS&D who will coordinate with the Lead Command system functional manager and/or AFSC item manager for disposition. **(T-2)**

14.3.2.2. **(AFGSC)** Tracked items that have an established life limit will be highlighted to the MXG/CD if the issue cannot be resolved immediately for necessary actions. **(T-2)**

14.3.2.3. For those aircraft that do not currently have an established configuration table, the Lead Command will develop procedures to identify, track and validate installed configuration managed items against the data in the MIS.

14.3.2.3. **(AFGSC)** See **paragraph 14.2.4.3.4** for MAJCOM procedures.

14.3.2.4. PS&D will coordinate the daily resolution of IMDS configuration management notices with the appropriate maintenance section utilizing the applicable MIS screen. **(T-2)**

14.3.2.4.1. Uncorrected discrepancies will be briefed weekly at the daily production/scheduling meeting and forwarded to the appropriate maintenance supervision for corrective action. **(T-2)**

14.3.2.4.2. **(Added-AFGSC)** PS&D will notify the MXG/CC of ACM, TCI, and safety of flight issues that require immediate resolution. **(T-2)**

14.3.2.5. When out of configuration items or mismatched serially tracked items are discovered, establish a single DD for the “out-of-configuration” condition. **(T-2)**

14.3.2.5.1. Additionally, add a MIS WCE for each WUC/LCN and part/serial number item requiring verification to the single DD. **(T-2)**

14.3.2.6. **(Added-AFGSC)** Establish data cleansing procedures to ensure uninstalled time change items with associated JSTs are deleted from the database on a quarterly basis. **(T-2)**

14.3.3. TCTO Management. TCTOs are AF, MAJCOM/Lead Command or Numbered Air Force (NAF) directed modifications and inspections that provide units with instructions for doing a one-time change, modification, or inspection of equipment, (includes applicable FAA Airworthiness Directives, original equipment manufacturer service bulletins and service instructions, after concurrence by Lead Command). Lead Command, NAF and local inspections are considered OTIs. Use the MIS to process Lead Command and NAF OTIs or modifications in the same manner as TCTOs with compliance periods, remove from service dates and rescission dates IAW TO 00-5-15. TCTOs, with the exception of immediate and urgent action, are considered scheduled maintenance and integrated into maintenance planning cycles. **(T-2)** Consider concurrent accomplishment of TCTO work with other unscheduled or scheduled maintenance (such as, PH, ISO, HSC, HPO). Manage TCTOs using the MIS, TO 00-5-15 and specific MAJCOM instructions. **Note:** Communication of a grounding, or potential grounding event (TCTO, OTI, PM event) to weapon systems operating in a deployed environment and/or under the authority of an operational command must follow the grounding procedures outlined in DAFMAN 11-401 and 63-101/20-101. Units must not directly communicate home station requirements to its deployed forces but provide communication through their respective MAJCOM. **(T-2)**

14.3.3.1. PS&D is responsible for managing all assigned weapon system TCTO programs and will monitor/provide oversight of all AF owned aircraft, weapon system, AGE, and commodity TCTOs to ensure all compliance requirements are met. **(T-2)**

14.3.3.1.1. Munitions-related TCTOs will be managed by the munition's scheduler (if assigned) and engine-related TCTOs will be managed by EM schedulers. **(T-2)**

14.3.3.1.2. PMEL TCTOs will be managed by the owning agency with PS&D oversight. **(T-2)**

14.3.3.1.3. The parent technical training center manages and schedules all TCTOs for training equipment assigned to a TD or Mobile Training Team.

14.3.3.1.4. **(Added-AFGSC)** Armament, AGE, Munitions and Engine Management (EM) TCTO monitors will keep MO PS&D informed of problems. **(T-2)**

14.3.3.2. PS&D will review MIS products weekly to ensure proper documentation and management by owning and managing TCTO agencies. **(T-2)**

14.3.3.2.1. When an error is detected, PS&D will inform affected work centers and provide assistance to correct the discrepancy IAW TO 00-20-2.

14.3.3.2.2. Units will complete an annual TCTO status review between MIS and REMIS or equivalent systems. **(T-2)**

14.3.3.2.2. **(AFGSC)** All appointed TCTO monitors will have access to REMIS MIS. TCTO monitors will utilize REMIS, in addition to MIS, to manage their programs. **(T-2)**

14.3.3.2.2.1. Units will reconcile rescinded TCTOs using a REMIS Master TCTO report or equivalent annually (NLT 30 Sep) and before deleting/retiring TCTO

records from the appropriate MIS. **(T-2)**

14.3.3.2.2.2. If REMIS or equivalent access is not available, request a REMIS Master TCTO report or equivalent from the MAJCOM MDS Weapon Systems Team/Program Office identified in the subject TCTO. If TCTO status conflicts are identified, units will contact the applicable Lead Command to establish the process for resolving conflicts and facilitating status correction in REMIS or equivalent system. **(T-2)**

14.3.3.2.2.3. Once all status errors are corrected, and reconciliation is complete and verified, IMDS units can delete the TCTO from the MIS. FMxC2 automatically retires TCTOs 60 days after rescission, and all equipment shows as complete.

14.3.3.2.2.3.1. Document completion on AF Form 2411. **(T-2)**

14.3.3.2.3. PS&D will brief the MXG/CC (or equivalent) weekly on unaccomplished TCTOs that are within 60 days of grounding. **(T-2)**

14.3.3.2.3.1. Significant problems or potential delays in TCTO accomplishment will be brought to the immediate attention of the MXO DO/SUPT and MXG/CC (or equivalent). **(T-2)**

14.3.3.2.3.1.1. **(Added-AFGSC)** PS&D monitors the completion of commodity TCTOs and coordinates with performing work centers to ensure compliance within specified time limits. PS&D establishes schedules for completion of installed commodity TCTOs with companion aircraft TCTOs. PS&D schedules aircraft TCTOs. The EM Section schedules non-installed engine-related TCTOs and coordinates with PS&D on installed engine related TCTOs. The munitions squadron PS&D will manage TCTOs for all air-launched surface attack guided missiles and associated support equipment, munitions, nuclear ordnance commodity management items, guidance kits, air intercept/aerial guided missiles and air intercept/aerial rockets. **(T-2)**

14.3.3.2.4. PS&D will chair a TCTO review meeting attended by all TCTO owning and managing agencies after the monthly supply TCTO reconciliation meeting. **(T-2)** These meetings may be combined.

14.3.3.2.4.1. PS&D will discuss the supply reconciliation, supply status, scheduling factors, current TCTO status and anticipated problems for all active TCTOs. **(T-2)**

14.3.3.2.4.2. PS&D will produce meeting minutes on the AF Form 2410 and distribute to all affected agencies. **(T-3)**

14.3.3.2.5. Depot-level TCTOs, excluding commodities, will be loaded, and tracked in the MIS for auditing compliance and applicability. **(T-2)**

14.3.3.2.5.1. Depot-level engine TCTOs will be loaded in CEMS only. **(T-2)**

14.3.3.2.5.2. Units will ensure dual reporting of completed depot-level TCTOs is prevented. **(T-2)**

14.3.3.2.5.3. All field-level companion TCTOs for commodities must be loaded in the MIS. **(T-2)**

14.3.3.2.6. PS&D will monitor, track, and administer all applicable CPINS as commodity TCTOs for configuration management purposes IAW TO 00-5-15 and TO 00-5-16.

14.3.3.2.6.1. PS&D will coordinate reprogramming of all passive/active aircraft internal and external electronic warfare systems and equipment with the wing Electronic Warfare Officer or equivalent before implementing any CPIN changes. **(T-2)**

14.3.3.2.6.2. PS&D will coordinate with EM before issuing NSS/ETS CPINS. **(T-2)**

14.3.3.2.7. When TCTOs are directed for items without serial numbers, assign permanent serial numbers IAW TO 00-20-2 and AFI 23-101. **(T-2)**

14.3.3.2.7.1. For serial numbers that cannot be created IAW TO 00-20-2 or AFI 23-101, use the associated equipment serial number the item is assigned to (for example, an aircraft chock serial number would be 0000AXXXC1).

14.3.3.2.8. Control and Transfer of TCTO Kits. Units will transfer aircraft or equipment, with any TCTOs still pending completion, with their applicable TCTO kits. **(T-2)**

14.3.3.2.8.1. Retain engine TCTO kits for engines installed on aircraft at depot locations if the aircraft is returning to that unit for TCTO compliance. **(T-2)**

14.3.3.2.8.2. Transfer TCTO kits IAW AFI 23-101, TO 00-5-15 and TO 00-5-1.

14.3.3.3. Specific TCTO Responsibilities.

14.3.3.3.1. QA personnel will:

14.3.3.3.1.1. Review all new and revised technical data and TCTO's for completeness, accuracy, and applicability. **(T-2)** Inform applicable work centers of changes and up channel any problems discovered during this review. **(T-2)**

14.3.3.3.1.2. Determine if the TCTO impacts W&B. **(T-2)**

14.3.3.3.1.3. Distribute copies of TCTOs to the managing agency, performing work centers, and LRS. **(T-2)**

14.3.3.3.1.4. Provide a supply cover letter requesting the number of items in supply (including WRM) affected by the TCTO. **(T-2)**

14.3.3.3.1.5. Report all deficiencies in technical instructions and kit-proofing to the appropriate TCTO Manager IAW TOs 00-5-1 and 00-5-15. **(T-2)**

14.3.3.3.1.6. Attend TCTO planning meetings. **(T-2)**

14.3.3.3.1.7. Provide technical support to performing work centers. **(T-3)**

14.3.3.3.2. PS&D personnel will:

14.3.3.3.2.1. Determine the total number of end items applicable to the TCTO. **(T-2)**

14.3.3.3.2.1.1. Items that are assigned with the same Mission Design Series,

WUC, Part Number, but are not applicable to the TCTO will be loaded in "22" status. **(T-2)** This ensures accurate accountability that all equipment has been verified as being affected or not applicable to TCTO.

14.3.3.3.2.2. Chair a TCTO planning meeting with attendees from QA, owning and performing work centers and Flight Service Center/LRS IAW AFI 23-101, **Chapter 4**. **(T-2)**

14.3.3.3.2.2.1. Record meeting minutes on AF Form 2410, or locally developed product and provide an overall plan to implement the TCTO. **(T-2)**

14.3.3.3.2.2.2. Minutes will include TCTO applicability by ID number (or applicable part number or serial number for commodity TCTOs), purpose of the inspection/modification and clearly identify and document the performing work centers, training requirements, scheduling parameters, remove from service date, a review of the TCTO procedures, form entries and supply requirements prior to scheduling the TCTO for completion. **(T-2)**

14.3.3.3.2.2.3. All attendees sign the AF Form 2410, or locally developed product, at the conclusion of the planning meeting indicating agreement with the conditions. **(T-2)**

14.3.3.3.2.2.4. **(Added-AFGSC)** When validation/verification is completed on assigned aircraft or equipment; QA will provide a copy of the AFTO Form 82, to the TCTO monitor for filing in the TCTO folder.

14.3.3.3.2.3. Establish and maintain a TCTO folder for each active TCTO. **(T-2)**

14.3.3.3.2.3. **(AFGSC)** MO PS&D will develop a master TCTO folder to be used as the standard. **(T-2)**

14.3.3.3.2.3.1. TCTO folders will be standardized and include the basic TCTO and any supplements, completed AF Form 2410, or locally developed product, AF Form 2001, *Notification of TCTO Kit Requirements* (if required), messages and the supply cover letter from QA (if required). **(T-2)**

14.3.3.3.2.3.1. **(AFGSC)** The notes page will include important information and status updates for the overall TCTO. All TCTO reviews will be documented in the notes section (e.g., monthly, semi-annual, annual reviews). Important email traffic should be logged in and filed in the notes section. **Note:** Status updates are not necessarily referring to any one piece of equipment/aircraft/missile that is associated with the TCTO unless it is an important factor to note (e.g., delays, etc.). **(T-2)**

14.3.3.3.2.3.2. Once the TCTO has reached its rescission date, print a MIS product showing the current status of equipment and place it in the TCTO folder. **(T-2)**

14.3.3.3.2.3.2.1. Move the folder to an inactive TCTO file. **(T-2)**

14.3.3.3.2.3.2.2. The TCTO managing agency will maintain the folder until the TCTO is rescinded in the applicable MIS IAW TO 00-5-15. MIS TCTO records will be deleted (scheduled to retire for FMxC2 users) at that time.

(T- 2)

14.3.3.3.2.3.3. TCTOs will not be deleted from the MIS prior to the rescission date. **(T-2)**

14.3.3.3.2.3.4. Validate in REMIS that no additional requirements have been submitted or extensions applied. **(T-2)**

14.3.3.3.2.3.5. **(Added-AFGSC)** TCTO monitors will request a REMIS Master TCTO Record from the TCTO POC identified in the published TCTO and reconcile it with MIS prior to deleting Data Codes from MIS. If discrepancies are noted, forward a copy of the MIS product to the TCTO POC to update REMIS. Delete from MIS when MIS and REMIS match. **(T-2)**

14.3.3.3.2.4. If an initial TCTO load is not received from REMIS or equivalent, notify the single manager and/or equipment specialist IAW TO 00-5-15. **(T-2)**

14.3.3.3.2.4.1. **(Added-AFGSC)** If TCTOs are loaded in MIS manually; the TCTO monitor will contact the TCTO POC and request a REMIS Master TCTO Record. This record will be used to reconcile all data elements between MIS and REMIS to eliminate system interface errors during TCTO resync reporting to REMIS. **Note:** Units must not manually load TCTOs into the MIS without first contacting single manager and/or equipment specialist to let them know that TCTO was never loaded. **(T-2)**

14.3.3.3.2.5. Use the ILS-S to order required kits/parts/tools IAW MIS manuals. **(T-2)** Kits, parts, tools, and software will be ordered within 24 hours of the TCTO meeting and document numbers input on the AF Form 2001. **(T-2)** Locally manufactured and obtained parts will be documented on the AF 2001. **(T-2)**

14.3.3.3.2.5.1. When ILS-S is not available, initiate three copies of the AF Form 2001 and forward two copies of the Form with a copy of the TCTO to the supply TCTO monitor. **(T-2)**

14.3.3.3.2.5.2. For locally obtained parts, prepare an AF Form 2001 listing each item by NSN, noun and quantity required. **(T-2)**

14.3.3.3.2.6. Assign ID numbers to kits as they are received. **(T-2)**

14.3.3.3.2.6.1. Use **Part II** of the AF Form 2001 to manage kit/part assignment and track individual end items, date issued, document numbers and the number of kits remaining. **(T-2)**

14.3.3.3.2.6.2. The LRS/Flight Service Center TCTO monitor will ensure kits and/or parts are assembled prior to release. **(T-2)**

14.3.3.3.2.7. Control and release TCTO kits from LRS. **(T-2)**

14.3.3.3.2.8. Notify appropriate MAJCOM, by message, when local managers anticipate a problem with TCTO compliance within prescribed time limits. **(T-2)**

14.3.3.3.2.8.1. The message should include the TCTO number and narrative, total units affected, total units complete, kits on hand, kits on order, estimated delivery date, requisition number and a narrative of the problem.

14.3.3.3.2.8.2. The message will be endorsed by MXG/CC (or equivalent) prior to submission to MAJCOM. **(T-2)**

14.3.3.3.2.9. Report status of TCTOs that cannot be reported under "HOW MAL" codes 793, 797, 798, 801, 802, or 911 IAW the MIS, and 00-20 series TOs. **(T-2)**

14.3.3.3.2.10. Schedule, track and monitor TCTO accomplishment. **(T-2)**

14.3.3.3.2.10.1. Prepare a work order in the MIS for each affected end-item, including spares. Agencies owning installed on-equipment TCTOs will coordinate with PS&D prior to scheduling on-aircraft TCTOs. **(T-3)**

14.3.3.3.2.10.2. **(Added-AFGSC) [NC3]** Actions associated with the NC3 platform will be loaded in IMDS on the NC3 platform, not the aircraft.

14.3.3.3.2.11. Review suspense validation or equivalent inputs prior to processing TCTO suspenses and updating the MIS. **(T-2)**

14.3.3.3.2.12. Annotate back-up MIS products as changes occur. **(T-2)**

14.3.3.3.2.12.1. **(Added-AFGSC)** Annotations to the original MIS product and/or separate tracking sheet used to monitor TCTO status is sufficient. Repetitive printing/filing Screen #525 in the TCTO folder is not required. Upon completion of TCTO, run a part number listing to ensure no additional parts applicable to the TCTO were gained or loaded into the MIS. Print a new MIS product and file in TCTO folder. **(T-2)**

14.3.3.3.2.13. Ensure TCTOs are scheduled for completion prior to expiration or grounding date whichever comes first. **(T-2)**

14.3.3.3.2.14. Schedule all workable TCTOs for accomplishment prior to permanent equipment transfer or storage input. **(T-2)**

14.3.3.3.2.15. For TCTOs with compliance periods calculated in operating time (hours, cycles, starts, landings, or rounds) create a local JST and load the JST to the equipment, schedule for completion prior to expiration of the compliance period operating time. **(T-2) Note:** Once compliance period operating time has been reached remove equipment from service until the TCTO has been completed. **(T-2)**

14.3.3.3.2.15.1. Document the JST number in the TCTO notes.

14.3.4. SI and TCI Management:

14.3.4.1. Job Standard Master Listing (JML) Management.

14.3.4.1.1. PS&D will maintain (load, change, and delete) the JML for all inspections and time changes listed in the applicable aircraft/system -6 TO and commodity TOs. **(T-2)**

14.3.4.1.2. **(Added-AFGSC)** Schedulers will monitor -6 and associated technical orders, AGE owner's manuals and Air Force publications to ensure time change/inspection frequencies align and support the maintenance concept of the weapon system. Scheduled maintenance requirements that do not align with the established maintenance concept and affect aircraft availability will be identified and

forwarded to the Product Improvement Working Group (PIWG) for consideration and/or resolution.

14.3.4.2. Develop a matrix/chart depicting the total number of SIs and TCIs to be loaded in the MIS for each assigned aircraft/system. **(T-2)**

14.3.4.2. **(AFGSC)** If decentralized, MO PS&D will perform this function. Maintain the TCI and SI matrix using MSM (IMDS units). **(T-2)**

14.3.4.2.1. Maintain JMLs for off-equipment items in the OWC. PS&D will provide written guidance and training for JML management of off-equipment JSTs when PS&D authorizes OWCs to maintain it. **(T-3)**

14.3.4.2.2. For units using FMxC2, Lead Commands must maintain master inspection and time change requirements.

14.3.4.2.3. Once Master Job Standard Numbers are fielded for a weapon system, local PS&D will review TO 00-20-2 for Master Job Standard Numbers procedures. **(T-2)**

14.3.4.2.4. PS&D will load, change, and delete JSTs in the MIS as soon as possible after receipt of any -6 TOs, or other TO, TCI or inspection change and will promptly notify all affected PS&D sections for action. **(T-2)** PS&D will:

14.3.4.2.4.1. Load separate JSTs for all aircraft/systems -6 TOs special/scheduled inspections with frequencies greater than 30 days or 50 hours in the MIS. **(T-2)**

14.3.4.2.4.1.1. Load PE, PH, engine changes and other event type inspections (such as, hard landing) as a JST in the MIS as they occur. **(T-2)**

14.3.4.2.4.1.2. Provide training for maintaining JSTs as necessary. **(T-2)**

14.3.4.2.4.1.3. **(Added-AFGSC)** Units have the option to load JSTs with frequencies less than 30 calendar days/50 hours. **(T-2)**

14.3.4.2.4.2. Perform a semi-annual review of the JML and all JSTs for accuracy and currency to include off-equipment and decentralized activities. **(T-2)**

14.3.4.2.4.2.1. Review matrix/chart depicting the total number of SIs and TCI requirements to be loaded in the MIS for each assigned aircraft/system. **(T-2)**

14.3.4.2.4.2.2. Reconcile TCI and SI JSTs with the aircraft/systems -6 TOs and applicable commodity TOs and document the semi-annual review on AF Form 2411. **(T-2)**

14.3.4.2.4.2.3. Units may create JSTs in the MIS to automate required documentation of repetitive or complex tasks (such as engine change, tire change, phase inspection, flight control maintenance).

14.3.4.2.4.2.4. **(Added-AFGSC)** In conjunction with QA, develop a local JST for both installed/uninstalled engine blade blending which will include FOD prevention. **(T-2)**

14.3.4.2.4.3. Monitor the inspection and time change subsystems in the MIS. **(T-2)**

14.3.4.2.4.3.1. Perform a monthly review of all inspections, SIs, and TCI JSTs for each assigned aircraft. **(T-2)**

14.3.4.2.4.3.1. **(AFGSC)** Units will use MSM during quarterly reviews and ensure accurate data in the MIS (Only IMDS using units). **(T-2)**

14.3.4.2.4.3.2. Look for missing and/or excess inspections and TCIs loaded to the aircraft and ensure the accuracy of all due dates/times for TCIs and verify the Date of Manufacture (DOM) and Date of Installation (DOI). **(T-2)**

14.3.4.2.4.3.2.1. TCIs will be loaded in the MIS with a part number and serial number. **(T-2)**

14.3.4.2.4.3.3. Document the review and ensure corrections are made to the MIS. **(T-2)**

14.3.4.2.4.3.4. Maintain the report on file with corrective actions until the next review. **(T-2)** The use of automated verification tools is encouraged provided MIS data is the source for verification.

14.3.4.3. PS&D will manage the assigned weapon systems TCI program. **(T-2)** PS&D Personnel will:

14.3.4.3. **(AFGSC)** If decentralized, MO PS&D is responsible for the wing TCI program. EM is responsible for monitoring, projecting and including engine life limited component TCI requirements into aircraft maintenance plans. **(T-2)**

14.3.4.3.1. At least annually, meet with Egress and Aircrew Flight Equipment activities to verify each aircraft's egress data. **(T-2) Note:** MAJCOM/Units may direct more frequent verification of Egress and Aircrew Flight Equipment as required to maintain system integrity.

14.3.4.3.1.1. Document all verification of aircraft's egress data on the AF Form 2411 maintained in the aircraft jacket file. **(T-2)**

14.3.4.3.2. Identify, monitor, forecast and schedule only those selected items specifically identified in TO 00-20-9, *Forecasting Replacement Requirements for Selected Calendar and Hourly Time Change Items*; applicable commodity TOs; the aircraft -6 TO, DAFMAN 21-201 or identified as Federal Supply Group 13 and Materiel Management Code AQ Items. **(T-2)**

14.3.4.3.2. **(AFGSC)** If decentralized, MO PS&D will perform this function. **(T-2)**

14.3.4.3.2.1. TCIs will be loaded in the MIS with a part number and serial number. **(T-2)**

14.3.4.3.3. Establish a JST for both the DOM and DOI for Cartridge-Actuated Devices (CAD), Propellant Actuated Devices (PAD), life sustaining, and other TCI items listed in the aircraft -6 TO and applicable commodity TOs. **(T-2)**

14.3.4.3.3.1. Load only the DOI or DOM JST that comes due first, in the MIS against a specific part or serial number. **(T-2)**

14.3.4.3.3.2. As a minimum, when the DOI and DOM frequencies are identical, maintain the JST for the DOM. **(T-2)** (N/A for FMxC2 units).

14.3.4.3.3.3. Ensure component background information is provided by Egress to include a list of all components having multiple part numbers with a different

service life. **(T-2)**

14.3.4.3.3.3.1. Forecasting of CAD/PAD items for long-term CAD/PAD spare requirements will be accomplished by Ogden Air Logistics Complex through use of the Requirements Determination Module to extract installation and due dates from REMIS. **(T-2)**

14.3.4.3.3.3.2. When CAD/PAD items or forecast requirements are not visible within the maintenance data system (for example, Contract Logistics Support managed components), units will forecast for TCIs IAW TO 00-20-9 and DAFMAN 21-201.

14.3.4.3.3.3.3. Validate and consolidate TCI forecasts for items listed in TO 00-20-9, commodity TOs, and aircraft specific -6 TOs. **(T-2)**

14.3.4.3.3.3.4. Submit consolidated forecasts to the appropriate Lead Command representative with an info copy to munitions operations. **(T-2)**

14.3.4.3.3.3.5. Forward any quarterly updated forecasts to munitions operations. **(T-2)**

14.3.4.3.4. Initiate, validate, and submit TCI extension requests to the Air Force Sustainment Center item manager with an info copy to munitions operations. **(T-2)**

14.3.4.3.4. **(AFGSC)** If decentralized, Maintenance Management will perform this function, including physical placement and removal from aircraft forms. **(T-2)** Submit TCI extension requests NLT 30 days prior to the due date. Exception: Submit extensions for aircraft projected to deploy where TCIs will come due during the duration of the deployment plus one month NLT 60 days prior to projected departure**. (T-2)**

14.3.4.3.4.1. Ensure a copy of approved extension are placed in the affected aircraft's forms and removed when no longer required. **(T-2)**

14.3.4.3.4.2. Maintain and monitor a suspense copy of the extension request and follow up prior to the grounding date of the TCI. **(T-2)**

14.3.4.3.4.3. Refer to TO 00-20-1 and 00-20-9 for additional guidance on TCI extensions and maintain a copy of the Air Force Sustainment Center/System Program Director approved message until the item is replaced. **(T-2)**

14.3.4.3.4.4. EM will generate engine TCI extension requests and coordinate through the Command Engine Manager to the appropriate Engine Program Office in AFLCMC. **(T-2)**

14.3.4.3.5. Perform monthly reconciliation of all TCIs with LRS. **(T-2)**

14.3.4.3.5.1. The reconciliation will consist of 100 percent validation of existing due outs. **(T-2)**

14.3.4.3.5.2. Inform FSC of any "mark for" changes or items no longer required. **(T-2)**

14.3.4.3.6. Monitor and requisition TCI requirements based on projected equipment utilization. **(T-2)**

14.3.4.3.6.1. Order parts using MIS or coordinate with LRS/DMS to order parts using AF Form 2005, unless otherwise specified in -11, -14 and -6 TOs. **(T-2)**

14.3.4.3.6.2. Schedule TCIs for replacement to minimize aircraft downtime at the next applicable inspection IAW TO 00-20-1 (i.e., schedule a TCI at the next inspection interval, HPO, PH, PE, HSC, 60-month, letter check). **(T-2) Note:** Life sustaining, or CAD/PAD TCIs cannot exceed replacement interval in applicable -6 and commodity TOs without an approved extension/waiver from the Program Office/appropriate item manager.

14.3.4.3.6.3. Notify the Munitions Flight of the need to order munitions items IAW TO 00-20-9 and DAFMAN 21-201. **(T-2)**

14.3.4.3.6.3.1. Serviceable CAD/PAD TCIs components will not be turned into munitions operations until the remaining service life reaches 9-months or less. **(T-2)** Serviceable CAD/PAD TCIs components with less than 9-months service life remaining will not be reissued. **(T-2)**

14.3.4.3.6.3.1. **(AFGSC)** Careful consideration must be given when ordering CAD/PAD items 6 to 9 months early (e.g., if a cluster of TCIs that are due at the 9th month mark and additional TCIs are due on the 10th or 11th month, the aircraft will be scheduled for additional major maintenance closer to the time change items that are due in the 9th month period). Therefore, it may be more cost effective not to schedule TCIs too early. Instead, consider the most effective grouping of TCIs. This concept balances the 9-month rule with cost effectiveness. However, aircraft availability for deployments and contingency operations is the determining factor in deciding to group TCIs into a single down period. **(T-2)**

14.3.4.3.6.3.2. Maintenance plans must reflect replacement dates to coincide within the 9-month parameter. **(T-2)**

14.3.4.3.6.4. Order non-CAD/PAD or engine TCIs IAW AFI 23-101.

14.3.4.3.6.5. **(Added-AFGSC)** If a TCI is authorized an over-fly limit and part is received; then TCI will be considered due for replacement at the HPO, Phase, PE, HSC, or ISO inspection nearest to the replacement date without exceeding authorized over-fly limits in applicable technical orders. **(T-2)**

14.3.4.3.7. Schedule the time change in the MIS and incorporate it in the monthly/weekly/ quarterly maintenance schedule. **(T-2)**

14.3.4.3.8. Review the data (DOM, DOI, LOT number, JST, and Due Date) entered by the performing work center. Ensure the suspense validation is updated in the MIS when the time change is completed (Suspense validation N/A for FMxC2). **(T-2)**

14.3.4.3.8.1. **(Added-AFGSC)** Ensure the part number, serial number, position, reference designator, and lot number (as applicable) are loaded. For Calendar TCIs check the DOM, DOI, frequency and due dates to ensure they are accurate. For hourly, start, or cycle tracked TCIs, verify the DOI. To verify the time remaining, subtract current operating time /starts cycles, from the frequency. **(T-2)**

14.3.4.3.9. Coordinate management of respective TCIs with applicable maintenance and operation work centers. **(T-2)**

14.3.4.3.10. Schedule drogue chute TCIs, except chute harnesses, for replacement during the drogue chute repack before the expiration of the component service or shelf life. **(T-2)**

14.3.4.3.10.1. These components will not be over flown without an approved extension from the appropriate item manager. **(T-2)**

14.3.4.3.10.1.1. A copy of approved extensions must be maintained in the affected aircraft's forms and removed when no longer required. **(T-2)**

14.3.4.3.11. Prepare TCI forecasts IAW TO 00-20-9.

14.3.4.3.11.1. Provide squadron Maintenance Supervision a forecast for non-munitions items for their supply section. **(T-2)**

14.3.4.3.11.1. **(AFGSC)** Agencies requesting changes or updates to the need-date of any cartridge actuated device/propellant actuated device (CAD/PAD) item must coordinate with PS&D and Munitions Accountable System Officer (MASO) in sufficient time to preclude emergency issue requests. Refer to DAFMAN 21-201 for emergency issue and contingency issue requests. **(T-2)**

14.3.4.3.12. To facilitate quarterly requisitioning, P&S will submit the quarterly validated time-change AFTO Form 223, Spreadsheet, or IMDS/FMxC2 generated forecast to the Munitions Accountable System Officer. **(T-2)** This must be submitted between 45 and 60 calendar days Continental United States (CONUS) or between 90 and 120 calendar days Outside Continental United States (OCONUS) before the next calendar year quarter IAW DAFMAN 21-201 **Table 7.3**, OCONUS and CONUS Time Change Requisitioning Schedule. **(T-2)** If aircraft is scheduled to be in depot when time change will be required, home station P&S will coordinate with depot P&S to facilitate requisition of required assets by the depot munition's function IAW DAFMAN 21-201 **Table 7.3** time frames. **(T-2)**

14.3.4.3.12.1. Validate current requirements against the annual forecast and make corrections based on aircraft utilization. **(T-2)**

14.3.4.3.12.1. **(AFGSC)** PS&D will submit an updated quarterly forecast when the need date for parts is outside of the calendar quarter which the parts were forecasted for on the annual forecast. PS&D then forwards it with the adjusted totals to munitions operations for ordering of the additional assets. **(T-2)**

14.3.5. Major Maintenance Work Processing. PS&D will:

14.3.5.1. Coordinate on all TO 00-25-107 requests for DAFI 21-103 reporting. **(T-2)**

14.3.5.1.1. The work center discovering the discrepancy is responsible for drafting the TO 00-25-107 request and forwarding the request to QA for coordination and release.

14.3.5.1.2. PS&D will make the appropriate PIC changes in the MIS when the 00-25-107 request has been submitted and/or received. **(T-2)**

14.3.5.1.3. Depot-level assistance provided by contractor support will be accomplished IAW contract specifications. **(T-2)**

14.3.5.2. Develop procedures in conjunction with QA for routing all major maintenance requests to ensure all affected parties are informed. **(T-2)**

14.3.5.3. Conduct an initial meeting upon arrival of a DFT to validate maintenance support requirements are in place. **(T-2)**

14.3.5.3.1. The meeting will be documented on an AF Form 2410, or locally-developed product. **(T-2)**

14.3.5.3.2. PS&D will initiate/accomplish all PIC changes in the MIS. **(T-2)**

14.3.5.3.3. Once work is completed, PS&D will ensure appropriate PIC are changed and a completed copy of the work package is placed in the aircraft jacket file. **(T-2)**

14.3.5.3.3.1. PS&D will document significant historical data on the appropriate AFTO Form 95 IAW 00-20 series TOs. **(T-2)**

14.3.6. Transfer Inspections.

14.3.6.1. Units will perform gaining/losing transfer inspections IAW TO 00-20-1, MAJCOM guidance and this instruction. **(T-2)**

14.3.6.1.1. In conjunction with QA, develop a local JST for both gaining and losing aircraft and equipment transfer. **(T-2)**

14.3.6.1.1.1. This JST must meet all TO 00-20-1, 2J-1-18, *Preparation for Shipment and Storage of Gas Turbine Engines*, applicable aircraft -6 and -21 TOs, as well as DAFI 21-103 and MAJCOM specific transfer requirements. **(T-2)**

14.3.6.1.1.2. Include all historical records (example, NDI records, Egress records, W&B records, OAP records, strut records) and other applicable items. **(T-2)**

14.3.6.1.2. Losing PS&D ensures all actions are completed in the MIS prior to permanently transferring an aircraft to another unit. **(T-2)**

14.3.6.1.3. Losing PS&D conducts a transfer pre-dock meeting one duty day prior to start of the aircraft transfer inspection. **(T-2)**

14.3.6.1.4. All items to be accomplished during the transfer inspection will be documented on an AF Form 2410, or locally developed product, and scheduled in the MIS. **(T-2)**

14.3.6.1.5. **(Added-AFGSC)** Refer to DAFI 21-103 for additional information on "temporary loans." **(T-2)**

14.3.6.2. Losing PS&D will complete a total verification of all TCIs installed on the transferring aircraft. **(T-2)**

14.3.6.2.1. Verify the correct computation of all due dates/hour/cycles based on DOM, DOI, installed times, or equivalent factors. **(T-2)**

14.3.6.2.2. For IMDS units only:

14.3.6.2.2.1. Ensure the IMDS-REMIS synchronization programs are processed,

and errors are corrected prior to transfer. **(T-2)**

14.3.6.2.2.2. Ensure an up-to-date Transfer of Equipment report and an AFTO Form 95 with current engine trend and performance data are placed in the aircraft jacket file. **(T-2)**

14.3.6.2.2.3. Ensure a backup copy is maintained until receipt is verified by the gaining unit. **(T-2)**

14.3.6.2.2.4. **(Added-AFGSC)** Special MIS procedures are required to minimize loss of data associated with aircraft transfer/data migration. The Transfer Between Enterprise Location Code process is used for unit-to-unit transfers, 3WO process is used for PDM-to-unit transfers and unique MIS procedures are required when PDM visits result in an MDS/SRD change (e.g., B-52H to B-52J). Contact MIS DBM for support. **(T-2)**

14.3.6.3. Losing PS&D will ensure an ADR is performed and conduct a transfer post dock meeting to ensure all required actions have been completed, all forms are current/accurate, and the MXG/CC (or equivalent) has certified each aircraft ready to transfer aircraft IAW TO 00-20-1, AFI 16-402, and DAFI 21-103.

14.3.7. Acceptance Inspections. Units perform acceptance inspections IAW TO 00-20-1, MAJCOM guidance and this instruction.

14.3.7.1. **(Added-AFGSC)** 95 WG will ensure engine acceptance inspections are completed within 5 duty days of engine delivery.

14.4. ENGINE MANAGEMENT (EM).

14.4.1. Engine Management (EM). EM manages unit efforts to maintain adequate engine support for mission requirements. EM monitors engine removals and replacements, component tracking, engine TCTOs and TCIs, engine records in the MIS and CEMS and performs engine manager duties.

14.4.1.1. - 14.4.1.1.2. DELETED.

14.4.1.2. EM will:

14.4.1.2.1. Manage the MIS and CEMS by referencing applicable information in this instruction, AFI 23-101, TO 00-25-254-1, TO 00-20-5-1-3, *Instructions for Jet Engine Parts Tracking of OC-ALC/LPA Managed Engines*. Reference AFCSM 21-558, *Comprehensive Engine Management System* and applicable aircraft -6 TOs.

14.4.1.2.2. Coordinate with Propulsion Flight CC/SUPT and organization leadership to support WRE requirements. **(T-2)**

14.4.1.2.3. Ensure plans, schedules, and maintenance actions are documented on assigned engines. **(T-2)**

14.4.1.2.4. Perform quarterly inventory IAW TO 00-25-254-1. Coordinate with the PS&D AVDO or equivalent to ensure accurate aircraft accountability in support of engine quarterly inventory completion.

14.4.1.2.5. Review Engine Managers Data List and reconcile after review IAW 00-25-254-1.

14.4.1.2.6. Ensure IMDS suspense validations/FMxC2 Engine Managers Data List transactions are accomplished no later than the close of business of the next business day following the date/time of occurrence. All transactions must be reported and entered in the order of occurrence. **(T-2)** Note**:** **Paragraph 14.4.1.3.4.2** provides unit level procedures requirements to support EM execution of duties for **Paragraph 14.4.1.2.6**.

14.4.1.2.7. Perform a monthly reconciliation of total assigned assets between the local MIS and CEMS, document the completed reconciliation on AF Form 2411 and develop a file plan for historical purposes. (**T-2)** At a minimum the reconciliation will include SRAN location, total engines assigned (to include serial numbers), engine condition/status, installed engines, uninstalled engines.

14.4.1.2.7.1. Engine managers will take immediate action to correct all reporting errors along with the competed AF Form 2411. **(T-2)** Contact MAJCOM engine manager or CEMS PMO Help Desk, **cems.pmo.helpdesk@us.af.mil** to solve reporting problems requiring clarification for completion of monthly reconciliation

14.4.1.2.7.2. **Command e** ngine managers will develop a standard procedure to extract monthly reconciliation data from engines located at a contractor repair facility whom contractors' sites do not have access to CEMS or the MIS. **(T-2)** At a minimum, reconciliation data must include SRAN location, total engines assigned (to include serial numbers), engine condition/status, installed engines, and uninstalled engines.

14.4.1.2.8. Provide TCI information (cycles remaining, EOT) on serially controlled items to the Propulsion Flight and AMXS/AMU for engine and engine component CANN actions. **(T-2)**

14.4.1.2.9. Ensure all engine SIs are loaded in MIS against the engine, not against the aircraft. **(T-2)**

14.4.1.2.10. Ensure all engine/module inspections/TCIs tracked by EOT, Calculated Cycles (CCY), Total Accumulated Cycles (TAC), are loaded/tracked in the MIS and CEMS databases. **(T-2)**

14.4.1.2.11. Ensure serial numbers erroneously input into CEMS are followed by a Possessor Change (6D) Transaction Condition Code (TCC). **(T-2)**

14.4.1.2.11.1. After the TCC has successfully processed, notify the CEMS Program Management Office help desk stipulating the serial number was erroneously input and will be deleted from CEMS, **cems.pmo.helpdesk@us.af.mil**. **(T-2)**

14.4.1.2.11.2. Create a JCN for engine, module or component data plate changes, modifications, re-identifications and new etchings and document changes in CEMS automated history. **(T-2)**

14.4.1.2.11.3. A matrix by engine type will be developed to depict specific inspection and TCI quantities for each TMS. Inspections tracked by flight hours must be loaded in the MIS. **(T-2)**

14.4.1.2.11.4. **(Added-AFGSC)** Inspections tracked by flight hours must also be

loaded in CEMS. **(T-2)**

14.4.1.2.12. Items that are assigned with the same TMS, WUC, Part Number, but are not applicable to the TCTO will be loaded in "22" status (refer to TO 00-20-2). **(T-2)** This ensures accurate accountability that all equipment has been verified as being affected or not applicable to TCTO.

14.4.1.2.12.1. Comply with TCTO duties and responsibilities for engine items IAW this **Chapter**. **(T-2)**

14.4.1.2.13. Manage TCTOs on all assigned engines and engine components, installed and uninstalled, as well as manage TCTOs for support equipment to include engine trailers. **(T-2)**

14.4.1.2.14. Accomplish quarterly TCTO status reviews and reconciliations IAW TO 00-25-254-1. **(T-2)**

14.4.1.2.15. Maintain records on TCTO kits and status for all engines installed on aircraft sent to depot. **(T-2)**

14.4.1.2.16. Manage time changes on all engines and engine components. **(T-2)**

14.4.1.2.16.1. EM will forecast parts requests and ensure requests are submitted to LRS up to 60 days (but not less than 10 days) prior to the need date of the scheduled time change or JEIM/CRF induction (see sections 14.2. and 14.3.). **(T-2)**

14.4.1.2.17. Reconcile all TCIs during the monthly TCI meeting with PS&D and LRS. **(T-2)**

14.4.1.2.17.1. Reconciliation will consist of 100 percent validation of existing due-outs and a complete physical inventory of all issued TCIs. **(T-2)**

14.4.1.2.17.2. Inform FSC of any “mark for” changes or items no longer required. **(T-2)**

14.4.1.2.18. Maintain and update historical documents for all assigned engines, modules, and major assemblies that are not managed by a Performance Based Logistics or contractually by a Contract Logistics Support contract. **(T-2)**

14.4.1.2.19. Check life-limited components forecast for additional component changes, TCTOs and SIs on all removed engines. **(T-2)**

14.4.1.2.19.1. **(Added-AFGSC)** Document the semi-annual review on AF Form 2411. **(T-2)**

14.4.1.2.20. Coordinate with the propulsion Flight CC/SUPT to develop a detailed 6-month engine and module TCI removal forecast and publish the forecast in the monthly flying and maintenance schedule. **(T-2)**

14.4.1.2.20.1. This 6-month forecast must be accomplished monthly using CEMS product E373/MIS products and the projected unscheduled removals based on the Unscheduled Removal Rate. **(T-2)**

14.4.1.2.20.2. Removal rate formula (total number of unscheduled removals divided by flying hours, multiplied by 1000). Provide a copy of the forecast to

maintenance leaders, PS&D, unit, and the MAJCOM engine manager. **(T-2)**

14.4.1.2.21. Publish scheduled engine changes in the weekly and monthly maintenance schedule. **(T-2)**

14.4.1.2.22. Verify engine total time versus aircraft total time, flying hours and manual cycles with PS&D during aircraft document reviews. **(T-2)**

14.4.1.2.23. Maintain the portion of the JML for engine inspections and time changes. **(T-2)**

14.4.1.2.23.1. Maintain (load, delete, and change) and conduct a semi-annual review of the JML for engine inspections and time changes listed in the aircraft -6 TO. **(T-2)**

14.4.1.2.24. Establish a CEMS and MIS contingency plan for when either or both systems are down for more than 48 hours. **(T-2)**

14.4.1.2.24.1. The plan will include procedures for retaining data in date-time order for input when MIS/CEMS operation resumes. **(T-2)** The plan will also address both home station and deployed procedures. **(T-2)**

14.4.1.2.25. Develop local engine tracking procedures and documentation methods to be used at deployed locations. **(T-2)**

14.4.1.2.25.1. Procedures must include the method of communication (message, e-mail or FAX), documentation and shipping responsibilities with SRAN addresses, and reporting procedures for CANNs and engine removals. **(T-2)**

14.4.1.2.25.2. Procedures will ensure units take immediate action to correct all reporting errors between the base MIS and CEMS using the engine manager's data list. **(T-2)**

14.4.1.2.25.3. **(Added-AFGSC)** Experienced technicians will be appointed as engine monitors for both on-station and deployed locations. EMs will receive locally developed training annually and prior to any deployments. This training will be tracked/documented by the EM. Engine monitors will report engine status changes to the EMs no later than the end of each duty day.

14.4.1.2.26. Update CEMS to reflect the four letter GEOLOC for uninstalled engines in a deployed location and the Organization Code is showing "1" per TO 00-25-254-1.

14.4.1.2.27. Accomplish UEM duties IAW, AFI 23-101, AFPAM 63-129, TOs 00-25-254-1, 00-20-5-1-3, AFCSM 21-558, applicable aircraft -6 TOs and this instruction.

14.4.1.2.27.1. Act as liaison to the SRAN engine manager when part of a tenant unit is supported by the host base engine manager. **(T-2)**

14.4.1.2.27.2. Provide the primary SRAN engine manager all quarterly reporting information required for submission to higher headquarters. **(T-2)**

14.4.1.3. The SRAN engine manager will:

14.4.1.3. **(AFGSC)** Contractors appoint a primary and an alternate engine manager responsible for the engines assigned to the SRAN under the maintenance contract and to

ensure Base Engine Manager (BEM) duties and UEM duties outlined in current directives and technical orders are accomplished. **(T-2)**

14.4.1.3.1. Be selected from AFSC 2A or 2R, minimum 7-skill level (or civilian equivalent). **(T-2)**

14.4.1.3.1.1. The assistant will be a minimum 5-skill level from the same AFSCs or civilian equivalent. **(T-2)**

14.4.1.3.1.2. Both individuals will be aligned under EM. **(T-2)**

14.4.1.3.2. Advise CMS or MXS/CC and MXG/CC (or equivalent), on administration of the base EM Program, engine maintenance concepts, principles, policies, procedures, and techniques. **(T-2)**

14.4.1.3.3. Act as the single point of contact between the unit, MAJCOM, and MMA for EM questions. **(T-2)**

14.4.1.3.4. Establish written procedures to support EM responsibilities IAW TO 00-25-254-1 and this instruction. Unit procedures must:

14.4.1.3.4.1. Specify responsibilities of affected work centers for accurate and timely MIS/CEMS reporting of TCTO, SI, TCI, and other documentation requirements (such as, borescope inspections, blade blending, CANN actions). **(T-2)**

14.4.1.3.4.2. Ensure engine, module, and component operation and maintenance data is reported to EM no later than close of business the first duty day after the event (for example, part removal, installation, time update, TCTO status change, and EMS operational/performance data where applicable). **(T-2)**

14.4.1.3.4.2.1. Ensure Engine Monitoring System (EMS) operational/performance data is transferred to CEMS where applicable. **(T-2)**

14.4.1.3.4.3. Address tenant, transportation, maintenance, aircraft distribution, supply, and support personnel requirements and be coordinated with the MAJCOM EM prior to publication. **(T-2)**

14.4.1.3.5. Request Initialization Decks (I-Deck) for engines and major modules (cores, High Pressure Turbine (HPT), Low Pressure Turbine (LPT), fans), to include embedded parts, part number, serial number, EOT, inspections, active TCTOs and TCIs, from CEMS Central Database (CDB) and ensure data in the MIS matches the CEMS CDB. **(T-2)**

14.4.1.3.6. Ensure deployed engine monitors are identified and trained to perform duties while deployed. **(T-2)**

14.4.1.3.6.1. Designated engine monitors will ensure all deployed spare engines have a copy (paper or electronic) of CEMS product E407, option 1 and 4, included in the deployment package. **(T-2)**

14.4.1.3.7. Perform engine manager duties for shipment and receipt of all assigned engines. **(T-2)**

14.4.1.3.8. Perform periodic quality audits to monitor accuracy and timeliness of reporting. **(T-2)**

14.4.1.3.9. Perform annual EM training for all affected personnel (back shop, test cell, flightline, aircraft maintenance scheduler) who report engine status or are responsible for engine documentation and scheduling IAW AFCSM 21-558, TOs 00-25-254-1 and 00-20-1/-2.

14.4.1.3.10. Maintain a jacket file of engine shipping documents and receipts. **(T-2)**

14.4.1.3.10.1. Obtain MAJCOM EM approval prior to returning engines to CRF/depot. **(T-2)**

14.4.1.3.10.1. **(AFGSC)** Obtain AFGSC/A4MA EM approval prior to returning engines to depot or 2LM. **(T-2)**

14.4.1.3.10.2. **(Added-AFGSC)** Add Engine Control Number Procedures. Prior to returning engines to depot, the following procedures will be used to obtain control number approval from AFGSC/A4MA EM. The unit will send an e-mail to AFGSC/A4MA EM and functional manager. Request will include the following information: Unit, From (requestor's name), Phone Number, Date, Engine Type, Engine Serial Number, Current Engine Operating Time, Time Remaining, Detailed Discrepancy (provide detailed description of the discrepancy that requires depot repair). **(T-2)**

14.4.1.3.10.3. **(Added-AFGSC)** Obtain AFGSC/A4MA EM approval for parts cannibalization from uninstalled engines returning to CRF/depot for repair. Approval is required once the notification/decision to ship the engine has been made due to an unserviceable condition.

14.4.1.3.10.4. **(Added-AFGSC)** Engines deemed unserviceable requiring CRF/Depot level repair, or in a contested serviceable status that will potentially require CRF/Depot repair, must have AFGSC/A4M Command Engine Manager coordination and approval prior to all cannibalization actions.

14.4.1.3.11. Perform duties and requirements for engine shipments IAW TOs 00-25-254-1, 00-85-20, 2J-1-18, and 2-1-18.

14.4.1.3.11.1. Engines requiring off-base shipment must be delivered to transportation within 24 hours of notification/decision to ship the engine and/or the engine change is complete. **(T-2)** Notify MAJCOM EM and the owning SRAN EM if this time frame cannot be met.

14.4.1.3.12. The work folder will transfer with the engine. **(T-2)**

14.4.1.3.12.1. A copy will be maintained by the losing organization until verification of receipt by gaining unit. **(T-2)**

14.4.1.3.12.2. Gaining units will maintain the work folders and ship the documents with the engine to depot when appropriate. **(T-2)**

14.4.1.3.12.2.1. Gaining units will retrieve a copy of the previous EAWP from the Data Repository Center or equivalent data in the applicable MIS upon receipt of the engine. **(T-2)**

14.4.1.3.12.2.2. EAWP users are required to send completed EAWP files to the Data Repository Center or MIS equivalent within 3 duty days of EAWP close-out. **(T-2)**

14.4.1.3.13. The SRAN EM will report the following in CEMS:

14.4.1.3.13.1. Receipt transactions for engines as of the date and time engines are delivered from the transportation hold area and accepted at the JEIM facility. **(T-2)**

14.4.1.3.13.2. Shipment transactions with the "as of" date and time the engine(s) physically leave the base. **(T-2)**

14.4.1.3.13.2.1. Once engine is received at gaining unit, ensure trailer and adapter are transferred in MIS. **(T-2)**

14.4.1.3.13.3. All engine and tracked item removals, installations, and engine status changes. **(T-2)**

14.4.1.3.13.4. All engine status transaction removals, installations, gains, Engine-Not-Mission Capable for Supply (ENMCS), work completed, test cell rejects, work stopped, work started, change in level of maintenance, awaiting disposition, intra-AF receipt and intra-AF shipments, transfer, and HOW MAL codes IAW TO 00-25-254-1.

14.4.1.3.14. Verify all update transactions (such as, times, TCTO, part removal and installations) are input before reporting an engine removal or installation. **(T-2)**

14.4.1.3.15. **(Added-AFGSC)** EM or assistant EMs will monitor engine spares, monitor all CANN actions and coordinate CANN actions with AMXS and MXS Pro Super as appropriate. Additionally, the EM and assistant will monitor the shipment preparations, (e.g., pack and wrap for MXG). MO/MXOM will provide advice to the MXG/CC's ET&D program, as required. **Note:** AFSC 2A6X1 and 2R2X1 may be substituted for each other as required, IAW with Engine Management AF Manpower Standards Table. **(T-2)**

14.5. Maintenance and FHP Planning Cycle.

14.5.1. Responsibilities. MAJCOMs will develop procedures to ensure the intent of the maintenance and FHP planning cycle is met. The objective of the planning cycle is to execute the wing FHP consistent with operational requirements and maintenance capabilities. The maintenance and FHP planning cycle begins with the annual allocation of flying hours. Maintenance and operations schedulers propose an annual flying plan that balances both operational requirements and maintenance capabilities. Units should commit the fewest number of aircraft possible to meet programmed Utilization (UTE) rate standards and goals.

14.5.1. **(AFGSC)** Responsibilities. Wings/Groups will develop a supplement to **paragraph 14.5** to ensure standardizing scheduling practices for the wing and each assigned mission design series (MDS). Minimum topics will include standardized flying windows, specific surge rules, quiet hour policies, cross-country take-offs and returns, minimum turn times, crew ready times, etc. Supplements will include local schedule inputs, publishing deadlines, and any wing-specific requirements. Refer to AFI 11-102_AFGSCSUP, *Flying Hour Program Management* for further information. **(T-2)**

14.5.1.1. If applicable, MAJCOMs will develop scheduling procedures for units involved in Operational Test and Evaluation, Developmental Test and Evaluation, or Initial Operational Test and Evaluation to ensure the intent of the maintenance and FHP planning cycle is met.

14.5.1.2. AMC units tasked by the 618th Air and Space Operations Center will adhere to Commander, Air Force Forces (COMAFFOR) Apportionment and Allocation Process (CAAP) policies and procedures.

14.5.1.3. The annual plan, detailed by month, will evaluate the capability of maintenance to support the annual FHP.

14.5.1.4. When developing the annual plan, units will utilize the MDS specific sortie production model, or equivalent, if available.

14.5.1.5. Maintenance PS&D. PS&D builds, coordinates, publishes, and distributes an integrated aircraft/system annual and quarterly plan & monthly and weekly schedule to support maintenance and operational requirements.

14.5.1.5.1. Plans will be developed, coordinated, and consolidated jointly by the OSS's Current Operations Flight Scheduling, and PS&D. **(T-2)**

14.5.1.5.2. The printed wing plan will include an assessment of the wing's ability to execute the FHP and will be coordinated with the OG/CC and MXG/CC. **(T-2)**

14.5.1.5.3. Plans and schedules may be published via electronic means (such as, web pages, SharePoint®, or e-mail) provided operations security is not compromised. **Note:** TORQUE will be used as it becomes available.

14.5.1.5.4. Normal daily operations and training schedules are For Official Use Only (FOUO) and will not be restricted to classified systems. **(T-2)**

14.5.1.5.5. **(Added-AFGSC)** Airframe Capability and Scheduling. To ensure accurate projection of operations and maintenance capacity, units will compute airframe capabilities using only the number of Primary Aircraft Inventory (PAI) aircraft; do not include Backup Aircraft Inventory (BAI) or attrition reserve aircraft. Operational and training schedules will be based on the capability of PAI aircraft to execute the schedule. The OG/CC and MXG/CC will ensure BAI and attrition reserve aircraft are not computed when building the flying program. **(T-2)**

14.5.2. First Look Requirements. The First Look report is an internal wing document intended to highlight potential maintenance-capacity and operational-requirement disconnects in the upcoming year. Every year, NLT 15 March, PS&D will coordinate with MMA, flightline and backshop maintenance work centers to provide PS&D with historical attrition and projected manning production. **(T-2)** This assessment will take into account personnel, facilities, and airfield infrastructure for each aircraft maintenance organization.

14.5.2.1. In wings operating aircraft supported by a sortie production model, PS&D will coordinate with the Unit Maintenance Supervision to establish local requirements, responsibilities and procedures for utilizing the model to develop, sustain or reflow FHP/contingency requirements. **(T-2)**

14.5.2.2. The assessment will be provided to PS&D NLT the last workday of March. **(T- 2)** **Note:** AMC units tasked by the 618th Air and Space Operations Center will adhere to the CAAP policies and procedures.

14.5.2.3. PS&D will provide copies of the capability assessment to each OS scheduling section and maintenance supervision. **(T-2)**

14.5.2.3.1. The assessment will provide first look maintenance capability projections in a monthly format IAW MAJCOM guidance. **(T-2)**

14.5.2.3.2. The assessment will include operational requirements taking into consideration historical data that determines the average number of aircrews not available per month (DNIF, PME attendance, Leave, TDY, deployments), an assessment of maintenance ability to support the monthly requirement and an overall assessment of the unit's maintenance capability to meet the annual FHP (N/A for AMC units). **(T-2)**

14.5.2.4. OS and maintenance responses are sent to PS&D and OSS's Current Operations Flight Scheduling and will be consolidated into a comprehensive package that includes a breakdown of the following items by OS:

14.5.2.4.1. Sortie UTE Rates (N/A to AMC units). **(T-2)** Compute UTE rates by month for the entire FY for contracted (required) sorties and scheduled sorties using the formula: (number of sorties per month) divided by (number of Primary Aerospace Vehicle (Aircraft) Inventory (PAI) aircraft).

14.5.2.4.2. Sorties contracted/scheduled per day (N/A to AMC units). **(T-2)** Compute the number of sorties required per operations and maintenance (O&M) day to meet the operational requirement using the following formula: (Number of Sorties Required) divided by (Number of O&M days in a Given Month). Sorties per day need to be computed by month for the entire FY.

14.5.2.4.3. Monthly scheduled sorties (N/A to AMC units). **(T-2)** Compute monthly scheduled sortie requirements using the following formula: (Number of Sorties or Hours Required) divided by (1 Minus the Attrition Factor). For example, (1,000 sorties or hours required) divided by (1 minus 0.15) equals 1,177 sorties or hours to schedule. Round any part to the next whole sortie or hour.

14.5.2.4.4. Inspection dock capability. **(T-2)**

14.5.2.4.4.1. Compute the number of major inspections (i.e., PH/ISO) to be accomplished for each maintenance unit, by month, for the entire FY in order to meet operational requirements.

14.5.2.4.4.2. Compute dock capability using the following formula: (Number of O&M Days) divided by (Number of PH/ISO Days) multiplied by (Inspection Cycle) = Inspection Dock Capability. Inspection dock capability is provided at the wing level and provided by the squadron performing inspections.

14.5.2.5. Once compiled, first look packages will be presented to the OG and MXG/CCs before being presented to the WG/CC. **(T-2)**

14.5.3. Annual Maintenance Planning Cycle.

14.5.3.1. MAJCOMs will develop procedures to ensure the objectives of the annual maintenance planning cycle are met.

14.5.3.1.1. At a minimum, MAJCOM procedures will produce an annual flying and maintenance plan that allocates sorties and hours into quarters, is approved by the WG/CC, and published prior to the beginning of the FY.

14.5.3.1.1.1. **(Added-AFGSC)** Developing the Annual Plan. MO PS&D and OSS Current Ops will ensure the annual planning process is initiated NLT 15 March and their final FHP (proposed FHP response) message will be submitted through 8 AF/A3 and AFGSC/A3 to AFGSC/A4M NLT the proposed FHP message suspense date. **(T-2)**

14.5.3.1.1.2. **(Added-AFGSC)** MO PS&D and MO MMA will build and validate all capability studies that include airframe, personnel, and facilities. The studies will be reviewed and analyzed with AMXS and MXS supervision. Capability shortfalls will be noted and briefed to the MXG/CC. **(T-2)**

14.5.3.1.1.3. **(Added-AFGSC)** OSS Current Ops will validate their monthly breakdown of hours and sorties (based on RAP/contingency/curriculum requirements) in the baseline allocation message. **(T-2)**

14.5.3.1.1.4. **(Added-AFGSC) [B-1 units]** In order to prolong service life of critical components, AFGSC will publish NLT 15 Jul each year a B-1 Fleet Management Policy memorandum establishing a flying hour per aircraft annual cap for the B-1 fleet. B-1 scheduling entities will control annual accrual of flying hours per aircraft IAW the B-1 Fleet Management Policy memorandum.

14.5.3.1.2. Due to the unpredictable nature of most future AMC mission requirements, units tasked by 618th Air and Space Operations Center will prepare flying and maintenance plans with focus on supporting local operational training requirements based on historical data as well as all known future maintenance and operational requirements.

14.5.3.2. Flying Hour Allocation. Using the MAJCOM Baseline Allocation message, PS&D, the OS, and OSS's Operations Scheduling will provide affected work centers the following planning factors NLT 20 August each year, or within 10 working days after receipt of the flying hour allocations:

14.5.3.2.1. PS&D will provide updated capabilities which are computed by MMA and the PDM schedule. **(T-2)**

14.5.3.2.2. OSS will provide the:

14.5.3.2.2.1. Required flying hours and estimated sorties and missions in monthly increments. **(T-2)**

14.5.3.2.2.2. Flying days in each month. **(T-2)**

14.5.3.2.2.3. Aircraft and aircrew alert requirements. **(T-2)**

14.5.3.2.2.4. Known and projected TDYs and special mission requirements. **(T-2)**

14.5.3.2.2.5. Configuration and munitions requirements. **(T-2)**

14.5.3.3. NLT 1 September, or within 10 working days after receipt of the planning factors, maintenance supervision will provide PS&D, SQ/CCs, and OSS's Operations Scheduling the following planning factors:

14.5.3.3.1. Estimated number of aircraft available by month, taking into consideration aircraft required for training. **(T-2)**

14.5.3.3.2. A projected airframe capability statement. **(T-2)**

14.5.3.3.3. Forecasted personnel capability, taking into consideration required training for maintenance personnel. **(T-2)** (N/A to contract maintenance organizations).

14.5.3.3.4. The number of supportable sorties for each month. **(T-2)**

14.5.3.3.5. An estimated monthly attrition factor provided by MMA. **(T-2)**

14.5.3.3.5.1. The factor combines operations, weather, and materiel (maintenance and supply) factors.

14.5.3.3.5.2. Maintenance is responsible for adding the attrition factor to operational requirements.

14.5.3.3.6. A recommended block scheduling pattern. **(T-2)**

14.5.3.3.7. A statement of limitations. **(T-2)**

14.5.4. Quarterly Maintenance and FHP Planning. Quarterly planning starts with the operational requirement for flying hours, UTE rate, airframe availability, alert, and other related scheduling data.

14.5.4.1. MAJCOMs will develop procedures to ensure the objectives of the Quarterly Planning cycle are met.

14.5.4.1. **(AFGSC)** Quarterly scheduling starts with the operational requirement for flying hours, UTE, airframe availability, alert, and other scheduling related data. The OS Director of Operations will provide these requirements to the BGS/SGF and Pro Super, MUNS Control/Munitions OIC and PS&D NLT the first weekly scheduling meeting the month prior to the effective quarter. BGS supervision and the OS Director of Operations Officer discuss these requirements at the scheduling meeting before the quarter being scheduled. Launch/recovery blocks, sortie flow timing, etc., are established based on training ranges and air refueling allocations. **(T-2)**

14.5.4.2. The OS Director of Operations will provide these requirements to maintenance supervision and PS&D NLT 25 days before the beginning of the quarter. **(T-2)**

14.5.4.3. Maintenance supervision and the OS Director of Operations will discuss these requirements at the scheduling meeting before the quarter being planned. **(T-2)**

14.5.4.4. Schedulers will ensure quarterly plans are as detailed and accurate as possible. **(T-2)**

14.5.4.4.1. Plans should include known special missions, PDM schedules, HHQ commitments and lateral command support requirements.

14.5.4.4.2. All maintenance requirements will be consolidated into a single, quarterly plan using AF Form 2401, Equipment Utilization and Maintenance Schedule, or computer-generated form. **(T-2)**

14.5.4.4.2.1. Specific locally developed codes will be used to identify inspections, SI, TCI, and TCTO on the AF Form 2401. **(T-2)**

14.5.4.4.3. As a minimum, the quarterly plan will show the next 3 months planned sorties and known maintenance requirements. **(T-2)**

14.5.4.4.3.1. Known maintenance requirements include all maintenance events that impact aircraft availability and require management attention to ensure proper Time Distributed Index flow.

14.5.4.4.3.2. Consolidate as many scheduled maintenance events as practical, to reduce individual aircraft downtime, increase Aircraft availability, and minimize the number of times per month an aircraft is removed from the schedule due to scheduled maintenance requirements.

14.5.4.4.3.2.1. The intent is to reduce the number of times per month an aircraft is removed from the schedule for scheduled maintenance, thus increasing aircraft availability.

14.5.4.4.3.2.2. Unit/Wing/MAJCOM requests to change the frequency of -6 TO requirements to increase bundling opportunities will be submitted through the applicable Lead Command for consideration and/or resolution. **(T-2)**

14.5.4.4.3.3. To prevent operational utilization for that day(s) flying schedule, the quarterly plans will include, at a minimum, calendar inspections that hold an aircraft down, calendar TCIs, TCTOs in workable status, PDM schedules, training aircraft, cannibalization aircraft and aircraft ISO/PE/PH inspections. **(T-2)**

14.5.4.4.3.4. Other maintenance requirements, such as engine changes, hourly requirements, acceptance/transfer inspections, training aircraft and cannibalization aircraft will be posted as they become known or planned. **(T-2)**

14.5.4.4.3.5. Add AME inspections to the quarterly plan if the aircraft is scheduled to stay in that configuration to ensure the inspections are included in the monthly and weekly schedules. **(T-2)**

14.5.4.4.4. Revise weekly schedule and monthly plan to meet the quarterly plan objectives while staying within the maintenance capability. **(T-2)**

14.5.4.4.5. Use the following priority to determine which objectives to support if a lack of resources prevents meeting requirements:

14.5.4.4.5.1. Alert commitments. **(T-2)**

14.5.4.4.5.2. HHQ directed missions. **(T-2)**

14.5.4.4.5.3. Training. **(T-2)**

14.5.4.4.5.4. OSS's Current Operations Flight Scheduling will compile, coordinate, and brief the unit's quarterly plan and include operational requirements, support capability and any difficulties expected. **(T-2)**

14.5.4.4.5.5. Once an approved quarterly plan is established, OSS's Current Operations Flight, Scheduling will forward a copy to the OS, AMXS, OG/CC and MXG/CC along with all scheduling agencies. **(T-2)**

14.5.4.4.5.6. The plan will be posted so it may be viewed by both maintenance and operations. **(T-2)**

14.5.4.5. - 14.5.4.5.3. DELETED.

14.5.5. Monthly Maintenance and FHP Planning.

14.5.5. **(AFGSC)** The sortie/flying hour contract specifies the number of sorties and hours required to be flown. The contract is the final resolved product between operational requirements and maintenance capabilities. The total forecasted attrition factor will be considered and added to the required sorties to ensure fulfillment of the contract. The annual required sorties for the month, plus the historical attrition factor (**Note: paragraph A15.1**. AFGSC/A4M approved revised attrition is also permitted), is the basis for the development of the monthly flying and maintenance schedules. Attrition sorties are not substitutes for capability shortfalls; they are figured against the contract. The monthly flying schedule will reflect the number of sorties contracted, the number of attrition sorties added, and the number of sorties scheduled for each unit. **(T-2) Note:** The calendar in **Table 14.1** is an example month and represents when group and wing level quarterly, monthly, and weekly scheduling meetings should be held. The calendar also illustrates when maintenance and operations requirements must be met. Each unit may hold scheduling meetings at times during the week/month convenient to the organization, if the timelines in this instruction are met. **(T-2)**

14.5.5.1. Wings will develop procedures to ensure the objectives of the monthly planning cycle are met. **(T-2)**

14.5.5.1.1. Include predictable maintenance factors based on historical data along with other inputs, such as flow times for maintenance, turnaround times and parts replacement schedules.

14.5.5.1.1. **(AFGSC)** Long-range maintenance plans will be developed in as much detail as possible. All maintenance requirements will be consolidated into a single long-range plan using AF Form 2401, Equipment Utilization and Maintenance Schedule, or automated product. At a minimum, the long-range plan will show the current month and the next 2 months' known flying and maintenance requirements. Known maintenance requirements are defined as events that impact aircraft availability and/or require management attention to ensure smooth flow of scheduling/completion. Maintenance events should be consolidated during a single down period to the greatest extent possible. Specific locally developed codes may be used to identify each different special inspection, TCI, and TCTO on the AF Form 2401. Refine monthly and weekly schedules to ensure the quarterly plan objectives are met. **(T-2)**

14.5.5.1.2. MAJCOMs will develop maintenance scheduling effectiveness guidance in their supplements to this DAFI. **(T-2)**

14.5.5.1.2. **(AFGSC)** See **Attachment 6,** Maintenance Scheduling Effectiveness.

14.5.5.2. The monthly flying and maintenance plan schedule refines the quarterly plan by combining all aspects of aircraft utilization and will include:

14.5.5.2.1. A detailed monthly operations utilization calendar that specifies total aircraft flying hours, total sorties and missions, alert requirements, scheduled sortie or mission requirements and daily turn plans for each MDS by squadron, group, or wing. **(T-2)**

14.5.5.2.1.1. Do not assign attrition sorties to a specific aircrew/mission for the monthly planning process. **(T-2)**

14.5.5.2.2. Monthly maintenance requirements (as required). **(T-2)**

14.5.5.2.3. Transient work schedule, if applicable. **(T-2)**

14.5.5.2.4. Scheduled inspections, TCTOs, engine changes, time changes, DDs, contract or depot maintenance, washes, corrosion control, training aircraft and all other known maintenance requirements. **(T-2)**

14.5.5.2.4. **(AFGSC)** The letter "F" (F2, F3, etc.) will be printed on the AF Form 2401, or automated product, to reflect the number of sorties each aircraft is scheduled to fly and to facilitate TDI/Phase management. At a minimum, automated products must reflect all required entries and must be standardized for each MDS. **(T-2)**

14.5.5.2.5. SE scheduled inspections, contract, or depot maintenance, TCTOs, time changes, DDs, washes, and corrosion control. **(T-2)**

14.5.5.2.6. Avionics and other off-equipment maintenance scheduled inspections, TCTOs, assembly or repair operations. **(T-2)**

14.5.5.2.7. Engine/module 6-month removal forecast and in-shop inspection requirements. **(T-2)**

14.5.5.2.8. Munitions, ECM, and other mission loading or configuration requirements, including ammunition changes. **(T-2)**

14.5.5.2.9. Total ordnance requirements for aircraft support. **(T-2)**

14.5.5.2.9. **(AFGSC)** Total ordinance requirements for aircraft support listed by quantity and type. **(T-2)**

14.5.5.2.10. Tanks, Racks, Adapters and Pylons and WRM scheduled inspections, TCTOs, assembly or repair operations. **(T-2)**

14.5.5.2.11. Monthly training schedules, if not published separately. **(T-2)**

14.5.5.2.12. Detailed support requirements (such as, Petroleum, Oil, and Lubricants servicing, supply, food service, fire department, security, civil engineer, and airfield operations requirements). **(T-2)**

14.5.5.2.13. All known operational events (such as, exercises, deployments, surges) to determine maintenance capability to meet operational needs. **(T-2)**

14.5.5.2.14. **(Added-AFGSC)** Nuclear munitions maintenance schedule. **(T-2)**

14.5.5.2.15. **(Added-AFGSC)** Maintenance workload requirements. **(T-2)**

14.5.5.2.16. **(Added-AFGSC)** Quality Assurance (QA) scheduled inspections listed by type and quantity unless published separately by QA. **(T-2)**

14.5.5.3. Monthly planning cycle requirements.

14.5.5.3.1. NLT the first weekly scheduling meeting of the month, the OS Director of Operations will provide maintenance supervision and PS&D with the estimated operational needs for the following month in as much detail as possible. **(T-2)**

14.5.5.3.1.1. To optimize aircraft and munitions support, CMS, EMS, MUNS, MXS, AMXS, and OS will ensure the number of aircraft, and/or munitions configurations, are minimized and standardized. **(T-2)**

14.5.5.3.1.2. Include known takeoff times, landing times and flying hour windows. **(T-2) Note:** Landing times are not required if the unit has an established and constant average sortie duration.

14.5.5.3.2. The OS Director of Operations and maintenance supervision will review their applicable portion of the monthly maintenance plan and weekly schedule prior to submission to PS&D. **(T-2)**

14.5.5.3.3. NLT the second weekly scheduling meeting of the month, AMXS maintenance supervision will notify the OS Director of Operations whether requirements can be met or limitations exist and collectively make necessary adjustments to the proposed schedule to satisfy maintenance and operational requirements. **(T-2)**

14.5.5.3.4. MXG/CC and OG/CC will formalize the next month's flying and maintenance plan prior to presenting it to the WG/CC for approval NLT the third scheduling meeting of the preceding month. **(T-2)**

14.5.5.4. WG/CC's monthly scheduling meeting.

14.5.5.4.1. OS scheduling will outline past accomplishments, status of flying goals, problems encountered and detailed needs for the next month. **(T-2)**

14.5.5.4.2. PS&D will outline projected maintenance capability and aircraft/equipment availability. **(T-2)**

14.5.5.4.3. DELETED.

14.5.5.5. When the WG/CC approves/signs the proposed monthly flying plan, PS&D will include it as a portion of the monthly flying and maintenance plan. **(T-2)** Monthly plans may be published electronically provided local security requirements are met.

14.5.5.5. **(AFGSC)** The monthly flying and maintenance schedule is published/distributed NLT 5 duty days prior to the beginning of the effective month. All agencies will submit their monthly plan inputs to MO PS&D before presentation to the WG/CC. **(T-2)**

14.5.6. Weekly Scheduling. The weekly schedule is the final refinement to the monthly plan and results in the weekly flying and maintenance schedule.

14.5.6. **(AFGSC)** MO PS&D reviews the schedules for adequate utilization of aircraft and proper scheduling of maintenance requirements.

14.5.6.1. Wings will develop procedures to ensure the objectives of the weekly scheduling process are met. **(T-2)**

14.5.6.1.1. PS&D will review matrix/chart depicting the total number of SI and TCI requirements to be loaded in the MIS for each assigned aircraft/system and verify against the MIS totals weekly. **(T-2)** Overdue and uncorrected discrepancies will be briefed weekly during a daily production/scheduling meeting chaired by the MXG/CD (or equivalent). **(T-2)**

14.5.6.2. NLT 2 workdays before the weekly scheduling meeting, the OS Director of Operations will provide maintenance supervision the following information (as required for missile units):

14.5.6.2.1. Aircraft takeoff and landing times. **(T-2)**

14.5.6.2.2. Configuration requirements. **(T-2)**

14.5.6.2.3. Munitions requirements. **(T-2)**

14.5.6.2.4. Fuel loads. **(T-2)**

14.5.6.2.5. Special or peculiar mission support requirements. **(T-2)**

14.5.6.2.6. Alert requirements. **(T-2)**

14.5.6.2.7. Exercise vulnerability. **(T-2)**

14.5.6.2.8. Deployments. **(T-2)**

14.5.6.2.9. Off-base sorties. **(T-2)**

14.5.6.2.10. On-equipment training requirements. **(T-2)**

14.5.6.2.11. Other special requirements. **(T-2)**

14.5.6.2.12. All mission unique requirements are annotated by OS Director of Operations on the weekly and daily flying schedule. **(T-2)**

14.5.6.2.13. **(Added-AFGSC)** Targeting Pod requirements. **(T-2)**

14.5.6.3. Home and deployed units will publish a weekly schedule. **(T-2)** Include the following in the weekly flying and maintenance schedule:

14.5.6.3.1. Sortie sequence numbers, aircraft tail numbers (primary and spares), scheduled takeoff and landing times, aircraft or equipment scheduled use times, configurations, fuel loads, and special equipment requirements. **(T-2)** Units that fly a published and constant average sortie duration need not publish land times.

14.5.6.3.1. **(AFGSC)** Units will publish landing times. **(T-2)**

14.5.6.3.2. Spare aircraft requirements. **(T-2)** Spare requirements are printed by day for each maintenance unit. Generate only the absolute minimum of spare aircraft.

14.5.6.3.3. Scheduled maintenance actions, by aircraft and equipment serial number, to include inspections, TCTOs, time changes, contract and depot inputs, engine changes, washes or corrosion control, document reviews and DDs. **(T-2)**

14.5.6.3.4. Required pre-inspection and other maintenance/scheduling meetings. **(T-2)**

14.5.6.3.5. Wash rack use. **(T-2)**

14.5.6.3.6. On-equipment training requirements. **(T-2)**

14.5.6.3.7. AGE inspections or maintenance schedule by type and ID number. **(T-2)**

14.5.6.3.7. **(AFGSC)** AGE monthly maintenance schedule meets the intent of this requirement.

14.5.6.3.8. MAJCOMs will develop standardized procedures to record and coordinate changes to the weekly schedule using an AF Form 2407 or electronic equivalent. Include minimum approval levels for approving changes to the weekly schedule.

14.5.6.3.8. **(AFGSC)** Pen-and-ink changes are not authorized in AFGSC units.

14.5.6.3.8.1. **(Added-AFGSC) Procedures.** The agency requesting the change initiates the AF Form 2407, Weekly/Daily Flying Schedule Coordination, and coordinates it through the relevant approving authorities (e.g., Pro Super, MOC, PS&D, etc.) as applicable for approval. Changes affecting munitions will be coordinated through the appropriate munitions management channels to ensure proposed changes can be met. Requested changes should be coordinated prior to the daily maintenance production meeting to allow sufficient time to determine the supportability of the change. All AF Form 2407 changes will include a specific reason for each change.

14.5.6.3.8.2. **(Added-AFGSC)** AF Form 2407, Approval Authority. Both the OG and MXG commander (or group level representative, designated in writing by group commander) will approve all AF Form 2407 changes adding aircraft and/or sorties or increase the flying window. Squadron commander(s) (or designated representative) will approve all other AF Form 2407 changes that affect them. The MOC will coordinate higher headquarters directed taskings that require immediate execution. Electronic coordination is acceptable provided receipt is acknowledged, and the sender enters the name of the person notified and the date/time on the AF Form 2407. **Note:** 582 HG SQ/CC or designated representative is the approval authority for Off Base Movement (Convoy) mission add lines and flying window extensions.

14.5.6.3.8.3. **(Added-AFGSC)** After coordination, a copy of the AF Form 2407 is filed in the MOC and in PS&D with the weekly schedule. The MOC will ensure MO MMA receives all AF Form 2407s for deviation accounting. AF Forms 2407 will be disposed of IAW RDS. **(T-2)**

14.5.6.3.8.4. **(Added-AFGSC)** After the end-of-week daily maintenance production meeting MOC will input all changes, maintenance debrief will input utilization data for all sorties considered "flown as scheduled" (e.g., FCF/OCF, cross-country returns, surge, second and subsequent goes).

14.5.6.3.8.5. **(Added-AFGSC)** MO MMA will review all AF Form 2407s daily for deviation accounting. **Note:** Use of the AF Form 2407 does not negate the recording of deviations. **(T-2)**

14.5.6.3.9. Any change to the printed schedule will require an AF Form 2407 with the following exceptions: a change to the original printed takeoff or landing time of 15 minutes or less; a change of aircrew names, ranges, or airspace; or a change arising

after the first crew ready time for the squadron's current day's scheduled flying window. **(T-2)**

14.5.6.3.9.1. Changes made during the daily scheduling meeting also require an AF Form 2407. **(T-2)**

14.5.6.3.9.2. The agency requesting the change initiates the AF Form 2407 and coordinates it IAW MAJCOM procedures. **(T-2)**

14.5.6.3.9.3. **(Added-AFGSC)** Changes to the original printed take-off or landing time of 30 minutes or less. **(T-2)**

14.5.6.3.9.4. **(Added-AFGSC)** Changes of aircrew names, call signs, ranges, minor configuration changes such as AME configuration locations (e.g., forward weapons bay, mid weapons bay, aft weapons bay) or airspace. **(T-2)**

14.5.6.3.9.5. **(Added-AFGSC)** Changes arising after the first crew ready time for the remainder of the flying day (e.g., tail number swaps) do not require an AF Form 2407; however, these changes will be coordinated by telephone or radio with all affected agencies. **(T-2)**

14.5.6.4. The OS Director of Operations and Maintenance Supervision will review and coordinate on the proposed weekly flying and maintenance schedule with OS, AMXS, MXS, CMS, and EMS prior to presenting it to the OG/CC and MXG/CC (or equivalent). **(T-2)**

14.5.6.4. **(AFGSC)** The OG/CC and MXG/CC, or their designated representatives, will chair the group meeting to consolidate and review proposed flying and maintenance plans. **(T-2)**

14.5.6.4.1. **(Added-AFGSC)** The WG/CC (or equivalent) will chair a weekly scheduling meeting at which the groups (OG/MXG/MSG) will present the flying and maintenance plan for approval. MO PS&D ensures a completed (paper or electronic) copy is submitted to the WG/CC (or equivalent) at the weekly scheduling meeting. **(T-2)**

14.5.6.5. The approved schedule will be submitted to PS&D for compilation and a complete copy provided to the WG/CC. **(T-3)**

14.5.6.6. At the weekly scheduling meeting wings will evaluate the past week's accomplishments (to include flying and MSE) and negotiate/approve refinements to the coming week's schedule. **(T-2)**

14.5.6.6.1. The AF Form 2402, *Weekly Equipment Utilization and Maintenance Schedule*, or locally developed product, will be used to summarize the upcoming week's schedule. **(T-2)**

14.5.6.6.2. The AF Form 2403, *Weekly Aircraft Utilization/Maintenance Schedule*, or locally developed equivalent product that contains all requirements and creates a finite depiction of aircraft utilization and maintenance. **(T-2)**

14.5.6.7. Once the weekly schedule is reviewed and signed by the OG/CC, MXG/CC (or equivalent), and WG/CC it becomes the final planning guide for both operations and maintenance and the basis for deviation reporting. **(T-2)**

14.5.6.7. **(AFGSC)** The OG/CC and MXG/CC present the proposed flying schedule to the WG/CC for approval. If an agreement cannot be reached before the weekly scheduling meeting, the problem is referred to the WG/CC for decision. Once approved and signed by the OG/CC, MXG/CC, and WG/CC the flying schedule is the final planning guide for both operations and maintenance, and every effort will be made to execute the schedule as printed. The weekly schedule will be signed NLT 1500L Friday. **(T-2)**

14.5.6.7.1. The schedule will be followed as printed or as amended by coordinated changes. **(T-2)**

14.5.6.7.2. Coordinated changes do not negate reporting deviations IAW MAJCOM guidance.

14.5.6.7.3. **(Added-AFGSC)** 582 HG/CC is approval authority for the proposed flying schedule. **(T-2)**

14.5.6.7.4. **(Added-AFGSC)** 95 WG/CC is approval authority for the proposed flying schedule. **(T-2)**

14.5.6.8. PS&D will distribute the schedule to each appropriate activity and work center NLT time determined in MAJCOM supplements to this DAFI. **(T-2)**

14.5.6.8. **(AFGSC)** MO PS&D ensures distribution of the schedule to each appropriate activity and work center NLT 1600L on Friday. Automated methods are acceptable (ensure security requirements are met). Once printed in the weekly flying and maintenance schedule, the aircraft or equipment is made available to meet that schedule. MO PS&D records maintenance scheduling deviations and forwards computations to MMA weekly for publication in the monthly maintenance summary as outlined in **Attachment 6** Maintenance Scheduling Effectiveness. The maintenance operations center (MOC) reports flying scheduling deviations. **(T-2)**

14.5.6.8.1. Weekly schedules may be published electronically provided local security requirements are met.

14.6. Contingency and Expeditionary Responsibilities.

14.6.1. Responsibilities of Contingency/Expeditionary (Cont/Exp) units, for example, maintaining non-assigned aircraft. **Note:** This does not include AMC-established enroute stations.

14.6.1.1. Most planning and scheduling is the responsibility of units with assigned aircraft and is provided through reach back support to home stations. Contingency units have fewer responsibilities as described below. Commanders of expeditionary units will ensure the intent of the guidance is met when the dynamic nature of a Cont/Exp organization make strict adherence impossible. **(T-2)**

14.6.1.2. Cont/Exp PS&D will conduct the following programs as outlined below:

14.6.1.2.1. ADR, pre- and post-dock meetings, acceptance inspections (from DFT/CFTs) and the major work program. **(T-2)**

14.6.1.2.1.1. Cont/Exp PS&D will use the procedures developed by the aircraft-owning organizations. **(T-2)**

14.6.1.2.1.2. If aircraft from multiple bases/units are supported, procedures do not have to be standardized.

14.6.1.3. Ensure discrepancies noted by the aircraft-owning PS&D for the Aircraft Configuration Management, TCI and SI programs are corrected. **(T-2)** Cont/Exp PS&D will not develop programs independent of the aircraft-owning organization. **(T-2)**

14.6.1.4. Develop local coordination procedures for contingency aircraft affected by Immediate and Urgent Action (I/UA) TCTOs. **(T-2)**

14.6.1.5. When notified by the aircraft-owning organization of an I/UA TCTO, the Cont/Exp PS&D will host a TCTO meeting. **(T-2)**

14.6.1.5.1. The purpose of the meeting is to determine if the Cont/Exp unit has the maintenance capability to perform the TCTO.

14.6.1.5.1.1. Invite AMU, QA and affected work centers. Cont/Exp will notify the Commander of the unit's capability to perform the TCTO. **(T-2)**

14.6.1.5.1.2. Develop and implement local tracking methodology to track TCTO completion. **(T-2)**

14.6.1.5.1.3. Update MIS when the aircraft owning Cont/Exp PS&D loads the requisite JST/JCNS. **(T-2)**

14.6.1.5.1.4. If the Cont/Exp unit does not have the maintenance capability to perform the TCTO, Cont/Exp PS&D will notify the owning organization of that inability. **(T-2)**

14.6.1.5.2. Cont/Exp PS&D will only maintain aircraft I/UA TCTO files while active. **(T-2)**

14.6.1.5.2.1. Once TCTOs are completed and loaded in MIS, records will be sent to home station for filing. **(T-2)**

14.6.1.5.2.2. A TCTO meeting is not necessary for Routine Action aircraft TCTOs.

14.6.1.5.3. A full TCTO program IAW this **Chapter** is required for AGE and other special equipment which is assigned to the contingency unit. **(T-2)** This is intended to cover equipment that does not rotate with aviation packages.

14.6.1.5.4. Monthly and weekly maintenance planning. Cont/Exp PS&D will produce maintenance plans detailing all known maintenance requirements for the upcoming month/week. **(T-2)**

14.6.1.5.4.1. This plan will detail by tail number, due date, JST and a description of the scheduled maintenance required for the time period. **(T-2)**

14.6.1.5.4.1.1. Use of the AF Form 2401 is not required.

14.6.1.5.4.1.2. The list will be published 2-days prior to the covered time period, coordinated through maintenance supervision, and approved by the Commander. **(T-3)**

14.6.1.5.4.2. The weekly schedule will additionally identify those actions which will be deferred. **(T-2)**

14.6.1.5.4.2.1. It will specifically identify if the action is deferred for mission requirements or due to a lack of capability. **(T-2)**

14.6.1.5.4.2.2. Actions which are not identified as "pre-deferred" are expected to be accomplished during the upcoming week.

14.6.1.5.4.3. MSE will not be calculated for Cont/Exp units. **(T-2)** It is anticipated that Cont/Exp units require a great deal of flexibility to meet mission requirements.

14.6.1.5.4.3. **(AFGSC)** Use **Attachment 6**, Maintenance Scheduling Effectiveness for computing MSE.

14.6.1.6. Cont/Exp organizations are not responsible for Aircraft Generation Planning, Transfer Inspections, Flying/Maintenance Planning Cycle, First Look, Annual/Quarterly Mx Planning, AVDO and 2R1 functional management responsibilities.

14.6.1.7. Cont/Exp PS&D will develop procedures with home station AVDOs to communicate and ensure AVDO responsibilities are performed. **(T-2)**

Chapter 15

AIRCRAFT SUNSHADE MANAGEMENT

15.1. Purpose: This **Chapter** outlines overall management responsibilities for aircraft sunshades, crew shelters and portable/inflatable shelters. Additionally, it provides guidance and a standardized approach to procure and sustain these equipment items.

15.2. Scope: Applies to all AF units possessing or procuring these equipment items to support logistics operations and flight line or maintenance areas. This includes conventional force logistics units; nuclear and nuclear support units; cyber and space; special operations; wholesale-level procurement, sustainment, and maintenance; aerial port squadrons; logistics readiness squadrons; research, test, and development units. It does not include medical logistics, civil engineering logistics, security forces units and communications units.

15.2.1. Aircraft sunshades and other shelter types as defined below and addressed in this **Chapter** are considered equipment items for accountability purposes and will be tracked and accounted for IAW DAFI 23-101 and DAFMAN 23-122.

15.2.1.1. These assets are not listed on unit authorized equipment tables of allowance because authorizations are ***not required*** support equipment for weapons systems. These assets are the responsibility of the owning organization.

15.2.1.2. Commanders will ensure all other applicable organizations with appropriate subject matter expertise are involved in the procurement, installation, repair, sustainment, and replacement of these assets. **(T-2)**

15.2.1.3. Aircraft sunshades are not considered as temporary or relocatable facilities associated with Military Construction (MILCON) projects. Procedures for temporary or relocatable facilities associated with MILCON projects are contained in DAFI 32-1020, *Planning and Programming Built Infrastructure Projects*. Relocatable buildings are designed to be readily erected, disassembled, stored, moved, and reused to meet a short-term requirement for facilities due to either transitory peak requirements or urgent requirements pending approval, such as construction of facilities via normal military construction programs. According to DAFI 32-1020, **Chapter 8**, Relocatable and Temporary Facilities, the terms temporary and relocatable are interchangeable. Furthermore, DAFI 32-1020 provides guidance on satisfying interim facility requirements using relocatable or temporary facilities. Aircraft sunshades are not incident or interim to a MILCON project, nor are they in place to meet a temporary requirement; therefore, the terms temporary or relocatable as used in DAFI 32-1020 do not apply to aircraft sunshades.

15.2.1.4. Aircraft sunshades are not intended to replace aircraft maintenance hangars and as such there is no requirement associated with aircraft specifications or square footage allowances contained in DAFMAN 32-1084.

15.3. Definitions.

15.3.1. Aircraft Sunshades: Structure with the sole purpose of providing minimal protection for personnel from the elements (sun, wind, rain, snow, excluding lightning) with a roof and a maximum of two sides.

15.3.2. Crew Shelters: Any portable or prefabricated structure placed inside, under or erected to support activities within an aircraft sunshade, hangar, hardened aircraft shelter or protective aircraft shelter. These should not be confused with other shelters that are designed for personnel protection only (such as, End-of-Runway shacks).

15.3.3. Portable/Inflatable shelters: A structure constructed using layers of membrane connected together using pressurized air to produce a structure which covers limited areas (such as, cargo aircraft engine, open fuel tanks) of an aircraft or equipment.

15.3.4. Allied support: Utilities (electrical, water, air, communications) provided up to a stub at each aircraft sunshade. Utilities are real property assets. Installation of new utility services carries a work classification of Construction. See **Paragraph 15.11**.

15.4. Headquarters Air Force.

15.4.1. AF/A4L will:

15.4.1.1. Develop, articulate, and clarify all AF aircraft sunshade policies.

15.4.2. The Directorate of Civil Engineers (AF/A4C) will:

15.4.2.1. Provide input for development and clarification of aircraft sunshade policies.

15.4.2.2. Determine appropriate A4C agencies responsible for procurement consultation to the field.

15.4.2.3. Develop allied support guidance in relation to aircraft sunshades.

15.5. MAJCOM A4s will:

15.5.1. Provide input to AF/A4L on AF aircraft sunshade policies.

15.5.2. Review all plans for procurement, installation, and sustainment of aircraft sunshades with assistance from MAJCOM/A3, A4, Safety, AF Installation and Mission Support Center (AFIMSC) or Primary Subordinate Unit (PSU) Air Force Civil Engineer Center (AFCEC) as outlined in Paragraphs **15.7.1.11** and **15.8**, prior to approving the procurement or installation.

15.5.3. Develop weather event baseline criteria if not previously developed so an organization can procure an acceptable aircraft sunshade suitable to its specific location. Consider annual days of sun, average wet bulb globe temperature, annual rainfall, and annual snowfall, UV index, snow load, snow removal capability, wind sustainment requirements and temperatures that may affect work-rest cycles and overall productivity.

15.5.4. DELETED.

15.5.5. Approve/disapprove submitted request(s) based on information contained under the owning organization responsibilities section of this **Chapter**.

15.5.6. Provide field operating and sustaining organizations direction on the specific types and sizes of aircraft sunshades to use for each application.

15.6. Owning Organization.

15.6.1. The owning organization is the group level or equivalent organization responsible for the planning, funding, procurement, installation, maintenance, and lifetime sustainment of the aircraft sunshade including any installed utilities (lighting, obstructions in front of lighting,

electrical, communications included in the project scope as defined in Paragraphs **15.3.4** and **15.8.8**. **(T-2)**

15.6.1.1. Owning organizations may install aircraft sunshades, upon MAJCOM/A4 concurrence, to provide protection from the sun or other weather events such as: rain, sleet, snow. **(T-2)**

15.6.2. Owning organizations are responsible for the aircraft sunshade grounding system beginning at the single point service ground. Owning organizations will test the aircraft sunshade grounding system IAW AFMAN 32-1065, *Grounding & Electrical Systems*, Chapter 10, *Testing and Inspecting Static and Lightning Protection Systems and Grounding*. **(T-2)**
Note: These responsibilities can be contracted as outlined in **Paragraph 15.8.8**.

15.6.2.1. Owning organizations will ensure that Base Civil Engineer accepts the Lightning Protection Systems prior to accepting the facility, ensuring the lightning protection system is compliant and that the facility is immediately usable IAW AFMAN 32-1065. **(T-2)**

15.6.3. The owning organization is responsible for maintaining and storing manufacturer design drawings and specifications and providing ready access to installation agencies as necessary. **(T-2)**

15.6.4. For each procurement, and each aircraft sunshade related contracting effort (such as inspection and sustainment contracts) referenced in **Paragraph 15.10.3** of this publication, the owning organization will provide and appoint a Contracting Officer Representative (COR) who reports to the contracting officer on all aspects of implementation of the contract. **(T-2)**

15.6.4.1. The COR will coordinate agreement with local Civil Engineering organization request a Civil Engineering representative to advise on technical requirements of the procurement and sustainment. **(T-2)**

15.6.4.2. The CE advisor will assist the COR in:

15.6.4.2.1. Enforcing established engineering standards or inspection criteria as defined and incorporated in the procurement/sustainment contract in order to address safety and integrity of the structure. **(T-2)**

15.6.4.2.2. Providing quality oversight authority for any technical/serviceability inspections performed on the structure by the contractor. **(T-2)**

15.7. New Procurements. To minimize diversity of types of aircraft sunshades, the AF utilizes strategic sourcing to establish efficiencies in procurement and long-term sustainment. For additional guidance, contact the MAJCOM A4 on aircraft sunshade standardization.

15.7.1. The owning organization will:

15.7.1.1. Develop plans for purchase, installation, acceptance, and sustainment then submit information to the MAJCOM/A4 for concurrence. **(T-2)** If the owning organization intends to request allied support, the owning organization will include these costs in the forecast. If allied support is required, submit an AF Form 332, *Base Civil Engineer Work Request*, or service/work request to Civil Engineering Customer Service prior to solicitations, purchases, or procurements. **(T-2)**

15.7.1.2. Refer to AFI 65-601, Volume 1, *Budget Guidance and Procedures*, and AFI 65-601, Volume 2, *Budget Management for Operations* to determine correct appropriation for

procurement and installation of aircraft sunshades or crew shelters described in this publication. Plan and fund current equipment sustainment IAW **Paragraph 15.10**.

15.7.1.3. Use local contracting office for strategic sourcing, if available, to standardize and leverage buying power from an enterprise perspective. (T-2)

15.7.1.4. Ensure all facets of aircraft sunshade sustainment are considered; all applicable installation functional areas (CE community planner, Airfield Management, Comm, Safety, Medical) are involved in the siting and selection process and is approved by the installation's facility board prior to solicitation and procurement. **(T-2)**

15.7.1.4.1. If expertise is not available in the owning organization, contact the appropriate MAJCOM representative for further guidance. All new sunshades will be compliant with current applicable structural, environmental and safety standards. **(T-2)** Ensure compliance with criteria and design as outlined in **Paragraph 15.8**.

15.7.1.5. Submit planning materials to include drawings, dimensions, cost estimates and statements of work, as well as ramp work striping and support equipment requirements to their applicable MAJCOM/A4. **(T-2) Note:** This must be completed as early as possible in the planning phase to facilitate a smooth execution phase.

15.7.1.6. Ensure use of reflective markings on corner structural supports regardless of lighting used. **(T-2)**

15.7.1.7. Ensure use of retro reflective beads for all apron, taxiway, and taxi lane markings near aircraft sunshades. **(T-2)** Reference Engineering Technical Letter 04-2, *Standard Airfield Pavement Marking Schemes* and Unified Facilities Guide Specifications 32-17-23, *Pavement Markings* and AFMAN 32-1040, *Civil Engineering Airfield Infrastructure Systems*.

15.7.1.8. Perform an evaluation of all proposed sunshade installation plans to ensure requirements in Unified Facilities Criteria (UFC) 3-260-01, *Airfield and Heliport Planning and Design* are met. If waivers are required, those waivers must be approved prior to contract award of the sunshade. **(T-2)**

15.7.1.8.1. Ensure waiver authorities do not undermine contract requirements or federal regulations (example Federal Acquisition Regulation, Department of Defense Federal Acquisition Regulation Supplement). **(T-0)**

15.7.1.9. Ensure aircraft sunshades that penetrate an airfield imaginary surface defined in UFC 3-260-01 have obstruction lights installed IAW UFC 3-535-01, *Visual Air Navigation Facilities*, and conform to requirements contained in AFMAN 32-1040.

15.7.1.10. Ensure compliance with fuel servicing safety requirements IAW TO 00-25-172.

15.7.1.11. Address the following items below and those in **Paragraph 15.8** as a minimum in installation plans submitted to applicable MAJCOM/A4 for approval. **(T-2)**

15.7.1.11.1. Aircraft sunshade protection characteristics such as hail size, snow, ice, and water accumulation (weight and/or inches, consider water runoff, ice mitigation), maximum winds (sustained and gusts), aircraft tie down and lightning/grounding protection determined in conjunction with proper local authorities or AFIMSC/PSU AFCEC. **(T-2)**

15.7.1.11.2. Ensure sunshades are designed IAW UFC 3-301-01, *Structural Engineering*. **Note:** Consider jet blast potential in aircraft sunshade design and siting.

15.7.1.11.3. Number of spots to be covered. Consider ramp space capacity for both peacetime and contingency requirements (reception and bed down). **(T-2)**

15.7.1.11.4. Number of parking spaces lost due to aircraft sunshade placement. Consider ramp requirements, future mission changes, and impact on overall aircraft parking plan. **(T-2)**

15.7.1.11.5. Design life expectancy and warranty information. **(T-2)**

15.7.1.11.6. Expected costs including procurement, installation, and projected annual sustainment costs, to include inspection services. **Note:** Ensure adequate resources are established to maintain aircraft sunshade serviceability and mission accomplishment.

15.7.1.11.7. **Sustainment methodology (owning organization supported, manufacturer supported, supplemental contractor).** Ensure minimum requirements outlined in **Paragraph 15.10.3** are addressed. **(T-2)** Pre-posture sustainment through end-of-year.

15.7.1.11.7.1. DELETED.

15.7.1.11.8. Foreign Object Damage (FOD) mitigation and prevention. **(T-2)**

15.7.1.11.9. Planned storage of Aerospace Ground Equipment (AGE) and other related support equipment in aircraft sunshades within the maintenance area. **(T-2)**

15.7.1.11.10. Provisions for electrical power units or powered AGE placement and protection from equipment exhaust and aircraft jet blast while operating in/near aircraft sunshades. **(T-2)**

15.7.1.11.11. Environmental impacts and mitigation plans. Ensure the host Environmental Planning Function reviews proposals for installation of aircraft sunshades and associated utilities as early in the planning process as possible. The Environmental Planning Function is responsible for determining the level of environmental impact analysis required. Environmental impact analysis must be completed prior to contract award or implementation. **(T-0)**

15.7.1.11.12. Conduct and include a Risk Management (RM) assessment IAW AFPD 90-8, *Environment, Safety, and Occupational Health Management and Risk Management*, and AFI 90-802, to determine potential impact to personnel, environmental, safety, occupational health and airfield operations before procurement and installation activities begin. **(T-2)**

15.7.1.11.13. Mitigate any issues affecting control tower visibility or security to include security lighting and illumination and any issues affecting navigational aids. **(T-2)**

15.7.1.11.14. Mitigate obstructions to airspace and file FAA Form 7460-1, *Notice of Proposed Construction or Alteration*, with the FAA for new construction. **(T-0)**

15.7.1.11.15. Communications requirements. If communication (Local Area Network (LAN), wireless communications) is placed in aircraft sunshades, provide explanation

of how communications will be procured, installed, and sustained. Include in procurement, installation, and sustainment cost estimates. **(T-2)**

15.7.1.11.16. Mitigate any limitations on emergency and maintenance vehicle access to aircraft. **(T-2)**

15.7.1.11.17. Fall protection for personnel working above 4’ off the ground IAW DAFMAN 91-203. **(T-2)**

15.8. Design Criteria/Standards of Aircraft Sunshades.

15.8.1. Current aircraft sunshades that don't meet these requirements of current design standardization are authorized for use until time of replacement. If repairs become significant or not cost effective, owning organizations should consider replacement to the new standard or removal of the aircraft sunshade.

15.8.1.1. Coordinate with Air Traffic Control, Base/Unit Terminal Instrument Procedures specialist (SEI 357), to evaluate plans for potential impacts on aircraft approach/departure procedures. **(T-2)**

15.8.1.2. **&**

15.8.1.3. DELETED.

15.8.2. **Type of materiel used.** Select materiel as appropriate for location, type of aircraft sunshade, and the mission being served. The aircraft sunshade and side materiel will be fabric, reinforced aramid fiber, carbon fiber, galvanized steel or shop/factory painted steel. The frame materiel should be galvanized steel or other suitable newly designed building materiel with strength and durability characteristics that replicate or exceed that of galvanized steel.

15.8.3. **Aircraft sunshade height and width.** Aircraft sunshades must meet minimum clearance requirements for interior aircraft movement, as well as entrances and exit points including taxi lanes or taxiways in close proximity to the exterior of the structure. Refer to UFC 3-260-01, **Chapters 6** and **8** for these dimensions. (**T-2)**

15.8.4. Consider AGE transport and maintenance/emergency vehicle height requirements. Also, consider exhaust blast from jet engines and auxiliary power units, and future mission changes that may impact aircraft sunshade height and width requirements.

15.8.5. Wing tip and tail height clearances will meet the requirements outlined in DAFMAN 91-203 and UFC 03-260-01.

15.8.6. Bird nesting/roosting mitigation. Ensure no bird roosting or nesting locations are present, all holes in support structure and beneath roof must be covered or screened. **(T-2)**

15.8.6.1. The metal structure should minimize potential nesting sites for birds.

15.8.6.2. Anti-perching devices will be installed to deter birds from perching on or under the structure. **(T-2)**

15.8.7. Airfield waivers. The owning organization will make every effort to prevent submission of new airfield waivers. **(T-2)**

15.8.8. Lighting requirements. If lighting is placed in or on the aircraft sun shades, provide explanation of how electricity will be provided to and within the aircraft sunshade. Ensure

lighting provides sufficient illumination for security but does not interfere with flightline visual references. The procurement of lighting, installation, maintenance, and sustainment will be included in aircraft sunshade cost estimates. **(T-2)**

15.8.8.1. Lighting designs and fixture specifications will be IAW UFC 3-530-01, *Interior and Exterior Lighting Systems*.

15.8.8.2. Light mounts will be designed to handle wind loads on the light fixtures without damaging the lights and without compromising the structural integrity of the aircraft sunshade. **(T-2)**

15.8.9. Electrical requirements. If electrical power is to be placed in aircraft sunshades, provide explanation of how electricity will be provided to and within the aircraft sunshade. Procurement, installation, maintenance, and sustainment of electrical requirements on the load side of the power supply point/stub will be included in aircraft sunshade cost estimates. **(T-2)**

15.8.9.1. Electrical power system design will be IAW AFMAN 32-1062, *Electric Systems, Power Plants and Generators*, AFMAN 32-1065. Reference UFC 3-501-01, *Electrical Engineering*, UFC 3-520-01, *Interior Electrical Systems*, UFC 3-530-01, and UFC 3-550-01, *Exterior Electrical Power Distribution*, UFC 3-600-01, *Fire Protection Engineering for Facilities*, and Engineering Technical Letter 02-15, F*ire Protection Engineering Criteria - New Aircraft Facilities*.

15.8.10. The cost of running power (such as, lighting, and electrical) from prime or temporary power sources to the sunshades will be included in the cost estimate and will be borne by the owning unit. **(T-2)**

15.8.11. In no case will the loss of parking spots resulting from the purchase or installation of aircraft sunshades be a primary factor used to propose or construct additional aircraft parking spots or upgrade existing pavements to support aircraft. Procedures on construction of additional parking spots or pavement upgrades will be IAW AFI 32-1020, *Planning and Programming Built Infrastructure Projects* and DAFI 32-1020.

15.8.11.1. Whenever possible, aircraft sunshades will be installed on existing pavement without driving a requirement to expand or upgrade the underlying features. When the addition of pavement is necessary to make the sunshade complete and usable, the cost of the structure must be included with the cost to installation of the pavement for a total sunshade construction project cost. **(T-2)**

15.8.12. Aircraft sunshades are airfield fixed-structure obstructions and will meet MIL-STD-3007, *Department of Defense Standard Practice for Unified Facilities Criteria and Unified Facilities Guide Specifications* and AF criteria included in referenced UFCs and AFIs, as well as, local and national fire, safety, and electrical standards and codes as applicable. **(T-2)**

15.8.13. Consider location specific design requirements (snow load, maximum wind ratings). In addition to the requirements in UFC 3-301-01, for adjacent sunshades which share bracing frames, each fourth frame will provide twice the required lateral bracing strength. **(T-2)**

15.8.13.1. Particular attention will be focused on the design of lateral bracing for wind and jet blast loads, fatigue strength of steel lateral bracing members, and the design and location of anchor bolts near joints in runway aprons. **(T-2)**

15.8.14. Aircraft sunshades must meet ventilation and exhaust air requirements referenced in the International Mechanical Code, UFC 1-200-01, *DoD Building Code*. **(T-0) Note:** Achieve minimum exhaust and/or ventilation air requirements utilizing either mechanical or natural systems.

15.9. Current Aircraft Sunshades.

15.9.1. To replace currently installed aircraft sunshades, select materiel as appropriate for location, type of aircraft sunshade, and the mission being served. The aircraft sunshade and side materiel will be fabric, reinforced aramid fiber, carbon fiber, galvanized steel or shop/factory painted steel. **(T-2)**

15.9.1.1. The frame materiel will be galvanized steel or other suitable newly designed building materiel with strength and durability characteristics that replicate or exceed that of galvanized steel. **(T-2)**

15.9.1.2. Current aircraft sunshades that don't meet these requirements of current design standardization are authorized for use until time of replacement. **(T-2)**

15.9.1.3. If repairs become significant or not cost effective, owning organizations will consider replacement to the new standard or removal of the aircraft sunshade. **(T-2)**

15.9.1.4. To minimize diversity of types of aircraft sunshades across the enterprise and to establish better efficiencies in procurement and long-term sustainment, use strategic sourcing, if available. **(T-2)**

15.9.1.5. If strategic sourcing is not available, seek guidance from higher headquarters on aircraft sunshade standardization. **(T-2)**

15.9.2. Owning organizations will sustain aircraft sunshades and other shelter types described in this publication IAW AFI 65-601, Volume 2, *Financial Management*, to ensure no degradation of safety to personnel or mission accomplishment occurs. **(T-2)**

15.9.3. Owning organizations will conduct a risk management assessment IAW AFI 90-802 in conjunction with proper local authorities on current aircraft sunshades for FOD mitigation, markings, bird roosting mitigation, sustainability, safety, structural integrity, wind-load capacity, snow-load capacity, and ability to withstand hail. **(T-2)**

15.9.3.1. The owning organization is responsible for repairing any deficient areas identified during the risk management assessment. **(T-2)**

15.9.4. There is no requirement to upgrade current aircraft sunshades to meet the full requirements outlined in Paragraphs **15.7.1** through **15.7.1.11.16** and **15.8.1** through **15.8.13** except where codes apply and are mandatory. However, any replacement or significant repair of current aircraft sunshades will meet requirements as outlined in Paragraphs **15.7.1** through **15.7.1.11.16** and **15.8.1** through **15.8.13** **(T-2)**

15.9.5. Alterations can significantly impact loading on the structure. Conduct a structural analysis certified by a licensed professional engineer or government structural engineer to ensure the alterations do not compromise the structural integrity of the sunshade structure. Sunshades will not be altered to have more than two total walls or bay(s).

15.10. Sustainment and Accountability. Owning organization Group Commander or equivalent will:

15.10.1. Appoint a primary and alternate aircraft sunshade managers.

15.10.2. Develop local procedures establishing management and maintenance of sunshades.

15.10.3. Ensure assets are tracked as equipment items on the appropriate documents IAW DAFI 23-101 and DAFMAN 23-122.

15.10.4. Ensure appropriate authorities (Maintenance Group (MXG), Contracting, Comm, CE, Safety, Airfield Management) at the installation level accept installation of aircraft sunshades and allied support IAW manufacturer specifications, contract specifications, and AFIs. **(T-2)**

15.10.5. Develop an organically supported or contractor supported replacement/sustainment plan that will be included in the 10-year facility plan IAW this DAFI. **(T-2) Note:** This statement does not limit the plan from exceeding the minimum 10-year requirement.

15.10.5.1. Sustainment plan at a minimum will address the following as appropriate:

15.10.5.1.1. Certification and acceptance of installation as needed. **(T-2)**

15.10.5.1.2. Routine maintenance/sustainment and inspection criteria/services which meet manufacturer or qualified engineering authority (such as, personnel officially trained to inspect or provide technical guidance on that specific Sunshade) guidance as needed and appropriate. **(T-2) Note:** Ensure manufacture warranty is not voided.

15.10.5.1.3. Periodic and recurring in-depth inspections with prescribed interval/frequency and items to be inspected to determine structural integrity as appropriately defined for each type of structure by the manufacturer or qualified engineering authority as needed and appropriate. **(T-2)**

15.10.5.1.4. Non-routine maintenance/sustainment and inspection services as needed and appropriate. **(T-2)**

15.10.6. Develop local guidance that establishes periodic inspection criteria as recommended by original manufacturer (interval not to exceed 6 months) approved by a qualified engineering authority for aircraft sunshades and document on AFTO Form 244, or equivalent. **(T-2)**

15.10.6.1. Required inspections will be tracked in MIS. **(T-2)**

15.10.6.2. As a minimum, the owning organization will ensure inspection of:

15.10.6.2.1. Structural Supports for signs of corrosion, excessive movement, cracking, or damage; lateral bracing for signs of corrosion, loosening, cracking, missing hardware, or fatigue damage, particularly at the connections; structural anchorage for signs of loosening and cracking around anchorage points on apron. **(T-2)**

15.10.6.2.2. Foreign Object, cleanliness, and serviceability of installed safety markings. **(T-2)**

15.10.6.2.3. Lighting (if installed) for security and serviceability. **(T-2)**

15.10.6.2.4. Electrical system equipment, including electrical panels, receptacles, lighting systems, solar panels, and conduit (if installed) for security and serviceability. **(T-2)**

15.10.6.2.5. Following extreme/unique weather events (i.e., microburst, flooding).

15.10.7. Any discrepancy identified during routine, non-routine maintenance or other visual inspection will be documented on the AFTO Form 244 or equivalent; appropriate condition symbol will be used IAW TO 00-20-1.

15.10.7.1. Additionally, all discrepancies will be annotated in the MIS. **(T-2)**

15.10.7.2. If a discrepancy is discovered which could affect safety or structural integrity this information will immediately be directed to the owning organization group commander or equivalent. **(T-2)**

15.10.7.3. The owning organization group commander or equivalent with advisement from the qualified engineering authority and safety personnel will decide whether the sunshade is in an acceptable condition to continue performing its intended purpose or whether the sunshade will be removed from service and all assets and personnel vacated from the sunshade until repair is completed. **(T-2)**

15.10.8. Establish an emergency evacuation plan to protect both personnel and equipment from inclement/severe weather that may compromise the integrity of the aircraft sunshade roof or support structure. **(T-2)**

15.10.8.1. During inclement/severe weather situations including but not limited to high winds, thunderstorms, lightning, hail, tornadoes, hurricanes or other adverse weather warning situation, personnel will be evacuated from the aircraft sunshade, not to the aircraft sunshade. **(T-2)**

15.10.8.1.1. The aircraft sunshade is not intended to be used as a protective shelter in these situations.

15.11. Allied Support (Electricity, Water, Communications, Lighting).

15.11.1. If elected, electrical power will be provided to a connection point at the aircraft sunshade IAW UFC 3-550-01, *Exterior Electrical Power Distribution* and will be installed and maintained by Civil Engineering as real property IAW DAFI 32-9005, *Real Property Accountability and Reporting*. **(T-2)**

15.11.1.1. Allied support funding requirements will be prioritized along with other facility and infrastructure requirements through the Facilities Board process or applicable installation facility project prioritization process. **(T-2)**

15.11.2. If elected, water lines can be installed to a stub at the aircraft sunshade site and will be installed and maintained by Civil Engineering as real property IAW DAFI 32-9005. Water stubs and/or connections must be appropriately protected from frost/freeze and other environmental conditions. **(T-2)**

15.11.2.1. These stubs and/or connections must be prominently marked to prevent hazards and accidents. **(T-2)**

15.11.2.2. Allied support funding requirements will be prioritized along with other facility and infrastructure requirements through the facilities board process or applicable installation facility project prioritization process. **(T-2)**

15.11.3. If elected, communications will be provided to the aircraft sunshade IAW UFC 3-580-01, *Telecommunications Interior Infrastructure Planning and Design*, and will be installed and maintained by qualified communications personnel.

15.11.3.1. Allied support funding requirements for the communication real property elements of a project (example, conduit, manholes, duct banks) will be prioritized along with other facility and infrastructure requirements through the facilities board process or applicable installation facility project prioritization process. **(T-2)**

15.11.4. Lighting installation will be considered during procurement and/or sustainment phases and will be purchased and maintained by the owning organization from the light to the power stub. **(T-2)**

15.11.4.1. If lighting is to be included in an aircraft sunshade, the owning organization will include this in the procurement, installation, and sustainment plan. **(T-2)**

15.11.4.2. Owning organizations will use criteria and consultation as outlined in Paragraphs **15.7** through **15.9**. Energy efficient lighting will be considered where allowable. **(T-2)**

15.11.5. Power receptacles will be considered during the procurement and/or sustainment phases and will be purchased and maintained by the owning organization from the power receptacles to the power stub. **(T-2)**

15.11.5.1. If power is to be included, the owning organization will include this in the procurement, installation, and sustainment plan. **(T-2)** Owning organizations will use criteria and consultation as outlined in Paragraphs **15.7** through **15.9**. **(T-2)**

15.12. Crew Shelters and Portable/Inflatable Shelters.

15.12.1. Owning organizations will address the following items as a minimum in installation plans submitted to applicable MAJCOM/A4 for approval:

15.12.1.1. Annual procurement and sustainment costs, including allied support infrastructure costs. See **Paragraph 15.11** for allied support procedures. **(T-2)**

15.12.1.2. Ensure shelter meets all standards and codes as applicable. Crew shelters and inflatable or fabric structures must comply with the minimum Antiterrorism Standard requirements of UFC 4-010-01, *DoD Minimum Antiterrorism Standards for Buildings*. **(T-0)**

15.12.1.3. Ensure a FOD mitigation plan is implemented. **(T-2)**

15.12.1.4. Warranty information. **(T-2)**

15.12.1.5. Wing tip and tail height clearances will meet the requirements outlined in DAFMAN 91-203 and UFC 03-260-01. **(T-0)**

15.12.1.6. Appoint a shelter manager and establish a shelter user and operations plan. Ensure assets are tracked as equipment items on the appropriate documents on the CA/CRL IAW DAFMAN 23-122. **(T-2)**

15.12.2. Crew shelters will be configured to minimum ventilation standards referenced in the International Mechanical Code when occupied. **(T-0)**

TOM D. MILLER

Lieutenant General, USAF
DCS/Logistics, Engineering and Force Protection

(AFGSC)

JAMES M. MILLER, GS-15, DAF
Executive Director, Logistics and Engineering

Attachment 1

GLOSSARY OF REFERENCES AND SUPPORTING INFORMATION

References

PUBLIC LAW 99-661, Sec 2638, *National Defense Authorization Act for Fiscal Year 1987*, 14 Nov 1986

PUBLIC LAW 108-136, Sec 802, *Quality Control in Procurement of Aviation Critical Safety Items and Related Services*, 24 Nov 2003

FAA Order 8110.101A, *Type Certification Procedures for Military Commercial Derivative Aircraft*, 25 Feb 2015

FAR Part 1.602-2(d), Part 42, *Contract Administration and Audit Services*, 16 Nov 2017

FAR Subpart 37.2, *Advisory and Assistance Services,* 16 May 2016

FAR, Subpart 45.3, *Authorizing the Use and Rental of Government Property*, 2 Apr 2012

Title 14 *Code of Federal Regulation, Aeronautics and Space*, 3 Jan 2019

Title 29 *Code of Federal Regulation 1910.1200(f), Occupational Safety and Health Standards, Toxic and Hazardous Substances*, 26 Mar 2012

DoDI 3002.02, *406 MHz Emergency Beacons and Other Emergency Reporting Devices in Support of Personnel Recovery and Search and Rescue*, 9 Feb 2023

DoDD 3150.02, *DoD Nuclear Weapons Surety Progra*m, 15 Jul 2022

DoD 7000.14-R, *DoD Financial Management Regulation, Vol 12, **Chapter 7**, Financial Liability for Government Property Lost, Damaged, Destroyed or Stol*en, Feb 2023

DoDD 8100.02, *Use of Commercial Wireless Devices, Services, and Technologies in the Department of Defense (DoD) Global Information Grid (GIG)*, 14 Apr 2004

DoDI 8500.01, *Cybersecurity*, 14 Mar 2014

DoDM 5200.01 – V3, *DoD Information Security Program; Protection of Classified Information*, 24 Feb 2012

DoD 8570, *Information Assurance Workforce Improvement Program,* 19 Dec 2005

Engineering Technical Letter 02-15, *Fire Protection Engineering Criteria - New Aircraft Facilities*, 3 Dec 2002

Engineering Technical Letter 04-2, *Standard Airfield Pavement Marking Schemes*, 19 Jul 2004

(Added-AFGSC) TO 42C-1-2, *Anti-icing, Deicing and Defrosting of Parked Aircraft,* 15 January 2024

Unified Facilities Criteria 3-260-01, *Airfield and Heliport Planning and Design*, 4 Feb 2019

Unified Facilities Criteria 3-301-01, *Structural Engineering*, 11 Apr 2023

Unified Facilities Criteria 3-501-01, *Electrical Engineering*, 6 Oct 2015

Unified Facilities Criteria 3-520-01, *Interior Electrical Systems*, 6 Oct 2015

Unified Facilities Criteria 3-530-01, *Interior and Exterior Lighting Systems*, 9 Feb 2023

Unified Facilities Criteria 3-535-01, *Visual Air Navigation Facilities*, 11 Apr 2017

Unified Facilities Criteria 3-550-01, *Exterior Electrical Power Distribution*, 1 Sep 2016

Unified Facilities Criteria 3-600-01, *Fire Protection Engineering for Facilities*, 8 Aug 2016

Unified Facilities Criteria 4-010-01, *DoD Minimum Antiterrorism Standards for Buildings*, 12 Dec 2018

Unified Facilities Guide Specifications 3-580-01, *Telecommunications Interior Infrastructure Planning and Design*, 1 Jun 2016

JP 1-02, *Department of Defense Dictionary of Military and Associated Terms*, 15 Feb 2016

NIST SP 800-53A Revision 4, *Assessing Security and Privacy Controls in Federal Information Systems and Organizations: Building Effective Security Assessment Plans*, 18 Dec 2014

ODM 4140.01, *DoD Supply Chain Materiel Management* V1-V10, 10 Feb 2014

(Added-AFGSC) AFGSCI 13-520-SV3, (U) *Bomber Nuclear Generation and Regeneration,* 27 March 2023

(Added-AFGSC) AFGSCI 21-105, *Corrosion Prevention and Control Programs,* 17 June 2022

(Added-AFGSC) AFI 11-102, *Flying Hour Program Management,* 8 December 2020

(Added-AFGSC) AFI 11-102_AFGSCSUP, *Flying Hour Program Management,* 30 January 2018

(Added-AFGSC) AFI 11-401_AFGSCSUP, *Aviation Management,* 04 October 2019

(Added-AFGSC) AFMAN 21-200_AFGSCSUP, *Munitions and Missile Maintenance Management,* 26 January 2024

(Added-AFGSC) AFMAN 21-204, *Nuclear Weapons Maintenance,* 13 January 2023

(Added-AFGSC) DAFI 36-3012, *Military Entitlements,* 06 April 2023

(Added-AFGSC) DAFMAN 91-118, *Air Force Nuclear Safety Design Certification Program,* 17 July 2025

DAFPD 10-9, *Lead Command Designation and Responsibilities for Weapon Systems*, 25 May 2021

AFPD 21-1, *Maintenance of Military Materiel*, 1 Aug 2018

AFPD 90-8, *Environment, Safety, Occupational Health Management and Risk Management*, 23 Dec 2019

AFI 1-1, *Air Force Standards*, 18 Aug 2023

AFI 10-201, *Force Readiness Reporting*, 22 Dec 2020

DAFI 10-401, *Operations Planning and Execution*, 13 Jan 2021

AFI 10-403, *Deployment Planning and Execution*, 17 Apr 2020

AFI 10-404, *Base Support and Expeditionary (BAS&E) Site Planning*, 24 Jul 2019

DAFMAN 10-703, *Electromagnetic Warfare Integrated Reprogramming*, 2 Jun 2021

DAFI 10-2501, *Emergency Management Program*, 16 Oct 2023

AFMAN 11-202 V3, *Flight Operations*, 10 Jan 2022

AFMAN 11-218, *Aircraft Operations and Movement on the Ground*, 5 Apr 2019

AFI 11-235, *Specialized Refueling Operations*, 31 May 2019

DAFMAN 11-401, *Aviation Management*, 27 Oct 2020

DAFMAN 13-201, *Airspace Management*, 10 Dec 2020

DAFI 13-213, *Airfield Driving,* 4 Feb 2020

AFI 16-402, *Aerospace Vehicle Programming, Assignment, Distribution, Accounting, and Termination,* 27 Sep 2019

DODM 5200.01V1_AFMAN 16-1404, *Information Security Program: Overview, Classification and Declassification*, 6 Apr 2022

AFI 17-130, *Cybersecurity Program Managemen*t, 13 Feb 2020

AFI 17-210, *Radio Management*, 31 Jul 2023

DAFI 17-220, *Spectrum Management*, 8 Jun 2021

AFI 20-110, *Nuclear Weapons-Related Materiel Management*, 4 Jun 2018

DAFI 20-117, *Repair Network Management*, 19 Jan 2021

DAFI 21-103, *Equipment Inventory, Status, and Utilization Reporting*, 1 Nov 2022

AFMAN 21-113, *Air Force Metrology and Calibration (AFMETCAL) Program Management,* 29 Jan 2020

AFI 21-131, *Joint Oil Analysis Program*, 26 Mar 2014

AFMAN 21-203, *Nuclear Accountability Procedures*, 29 Sep 2021

AFMAN 21-206, *Aircraft Armament Systems Management,* 4 Nov 2022

AFI 23-101, *Air Force Materiel Management*, 22 Oct 2020

DAFI 23-201, *Fuels Management*, 23 Aug 2023

AFI 24-302, *Vehicle Management*, 21 Feb 2020

DAFI 24-602V2, *Preparation and Movement of Air Force Cargo*, 12 Jun 2019

AFI 25-201, *Intra-Service, Intra-Agency, and Inter-Agency Support Agreements Procedures*, 18 Oct 2013

DAFI 31-101, *Integrated Defense (ID)*, 25 Mar 2020

AFI 32-1020, *Planning and Programming Built Infrastructure Projects*, 18 Dec 2019

AFMAN 32-1062, *Electric Systems, Power Plants and Generators*, 20 Oct 2020

AFMAN 32-1065, *Grounding Systems*, 17 Jul 2020

AFI 32-7001, *Environmental Management*, 23 Aug 2019

DAFI 32-9005, *Real Property Accountability*, 14 Sep 2022

AFI 33-322, *Records Management and Information Governance Program,* 28 Jul 2021

DAFI 34-101, Department of the *Air Force Morale, Welfare, and Recreation (MWR) Programs and Use Eligibility*, 7 Mar 2022

AFI 36-128, *Pay Settings and Allowances*, 17 May 2019

DAFI 36-153, *Civilian Mobility*, 28 Nov 2023

AFMAN 36-2100, *Military Utilization and Classification*, 7 Apr 2021

AFI 36-2650, *Maintenance Training*, 22 Jun 2022

DAFMAN 36-2689, *Training Program,* 31 Mar 2023

DAFI 36-3802, *Force Support Readiness Programs*, 21 Nov 2021

DAFI 36-148, *Discipline and Adverse Actions of Civilian Employees*, 27 Sep 2022

AFI 38-101, *Air Force Organization*, 29 Aug 2019

AFI 48-109, *Electromagnetic Field Radiation Occupational & Environmental Health Program*, 1 Aug 2014

AFI 48-127, *Occupational Noise and Hearing Conservation Program*, 26 Feb 2016

AFI 48-137, *Respiratory Protection Program*, 12 Sep 2018

DAFI 62-601, *Airworthiness*, 10 Jun 2022

AFI 63-101/20-101, *Integrated Life Cycle Management*, 30 Jun 2020

AFI 63-125, *Nuclear Certification Program*, 16 Jan 2020

AFI 63-138, *Acquisition of Services*, 30 Sep 2019

DAFI 63-140, *Aircraft Structural Integrity Program and Air and Space Equipment Structural Management*, 6 Aug 2020

AFI 84-103, *Department of the Air Force Heritage Program*, 12 May 2021

AFI 90-802, *Risk Management*, 1 Apr 2019

AFI 90-821, *Hazard Communication (HAZCOM) Program*, 13 May 2019

DAFI 91-101, *Air Force Nuclear Weapons Surety Program*, 26 Mar 2020

DAFI 91-202, *The US Air Force Mishap Prevention Program*, 12 Mar 2020

DAFI 91-204, *Safety Investigation and Hazard Reporting*, 10 Mar 2021

DAFI 91-205, *Non-Nuclear Munitions Safety Board*, 30 Mar 2023

DAFMAN 91- 223, *Aviation Safety Investigation and Reports*, 20 Sep 2022

AFCSM 21-558, *Comprehensive Engine Management System*, 1 Jun 2019

AFCSM 21-564 V2, *Status and Inventory Reporting Software User Manual*, 25 Feb 2019

DAFPAM 90-803, *Risk Management (RM) Guidelines and Tools*, 23 Mar 2022

AFMAN 10-206, *Operational Reporting (OPREP)*, 18 Jun 2018

AFMAN 10-207, *Command Posts*, 11 Apr 2018

AFMAN 10-409-O, *Support to Adaptive Planning*, 19 Apr 2016

DAFI 10-2503, *Chemical Biological, Radiological, Nuclear, (CBRN) Defense Program*, 6 Oct 2023

DoDMAN5200.02_AFMAN 16-1405, *Air Force Personnel Security Program*, 1 Aug 2018

DAFMAN 17-1203, *Information Technology (IT) Asset Management (ITAM)*, 13 Sep 2022

AFMAN 17-1301, *Computer Security (COMPUSEC)*, 12 Feb 2020

AFMAN 17-1302-O, *Communications Security (COMSEC) Operations*, 9 Apr 2020

AFMAN 20-116, *Propulsion Life Cycle Management for Aerial Vehicles*, 13 Apr 2022

AFMAN 21-111, *Advanced Maintenance and Munitions Operations School*, 6 Mar 2019

AFMAN 21-200, *Munitions and Missile Maintenance Management*, 9 Aug 2018

DAFMAN 21-201, *Munitions Management*, 3 May 2022

AFMAN 21-204, *Nuclear Weapons Maintenance*, 13 Jan 2023

DAFMAN 23-122, *Materiel Management Procedures*, 27 Oct 2020

DAFMAN 24-604, *Preparing Hazardous Materials for Military Air Shipments*, 9 Oct 2020

AFMAN 32-1040, *Civil Engineering Airfield Infrastructure Systems*, 23 Aug 2019

DAFMAN 32-1084, *Standard Facility Requirements*, 15 Jan 2020

AFMAN 32-7002, *Environmental Compliance and Pollution Prevention*, 4 Feb 2020

DAFMAN 48-125, *Personnel Ionizing Radiation Dosimetry*, 27 Oct 2020

DESR6055.09_AFMAN 91-201, *Explosives Safety Standards*, 28 May 2020

DAFMAN 91-203, *Air Force Occupational Safety, Fire, and Health Standards*, 25 Mar 2022

AFMAN 91-221, *Weapons Safety Investigations and Reports*, 26 Mar 2020

DAFMAN 91-223, *Aviation Safety Investigations and Reports*, 20 Sep 2022

DAFMAN 90-161, *Publishing Processes and Procedures*, 18 Oct 2023

AFH 23-123V1, *Materiel Management Reference Information*, 8 Aug 2013

AFH 23-123V2PT2, *Integrated Logistics System-Supply (ILS-S), Standard Base Supply System Operations,* 8 Aug 2013

AFH 23-123V3, *Air Force Equipment Management*, 8 Aug 2013

AFTTP 3-4, *Airman's Manual*, 26 Sep 2022

AFTTP 3-4.21V1, *Aircraft Maintenance*, 9 Feb 2022

DAF *Strategic Plan for Control Systems,* March 2021

MIL-STD-3007, *Department of Defense Standard Practice for Unified Facilities Criteria*, 13 Dec 2006

MIL-HDBK-516C, *DoD Handbook, Airworthiness Certification Criteria*, 12 Dec 2014

TO 00-5-1, *AF Technical Order System*, 111 Sep 20235 Feb 2019

TO 00-20-5-1-3, *Instructions for Jet Engine Parts Tracking of OC-ALC/LPA Managed Engines*, 1 Mar 2007

TO 00-5-15, *Air Force Time Compliance Technical Order Process*, 28 Jul 2023

TO 00-5-16, *Computer Program Identification Number (CPIN) Management*, 1 Sep 2023

TO 00-20-1, *Aerospace Equipment Maintenance Inspection, Documentation, Policies, and Procedures*, 26 Sep 2022

TO 00-20-2, *Maintenance Data Documentation*, 22 Jul 2021

TO 00-20-3, *Maintenance Processing of Reparable Property and the Repair Cycle Asset Control System*, 17 Dec 2021

TO 00-20-9, *Forecasting Replacement Requirements for Selected Calendar and Hourly Time Change Items*, 9 Dec 2020

TO 00-25-4, *Depot Maintenance of Aerospace Vehicles and Training Equipment*, 15 Sep 2022

TO 00-20-14, *AF Metrology and Calibration Program*, 30 Nov 2023

TO 00-25-107, *Maintenance Assistance*, 15 Aug 2022

TO 00-25-113, *Conservation and Segregation of Critical Alloy and Precious Metal Bearing Parts and Scrap*, 15 Sep 2013

TO 00-25-172, *Ground Servicing of Aircraft and Static Grounding/Bonding*, 12 Jul 2023

TO 00-25-172CL-4, *Checklist -- Aircraft Fuel Servicing with R-9, R-11 and Commercial Fuel Servicing Trucks and with Fuels Operational Readiness Capability Equipment (FORCE)*, 22 Jun 2023

TO 00-25-195, *AF Technical Order System Source, Maintenance and Recoverability Coding of Air Force Weapons Systems, and Equipment*, 1 Sep 2023

TO 00-25-240, *Uniform Repair/Replacement Criteria for USAF Support Equipment (SE)*, 1 Aug 2003

TO 00-25-252, *Intermediate Maintenance and Depot Level Maintenance Instructions-Aeronautical Welding*, 29 Sep 2023

TO 00-25-254-1, *Comprehensive Engine Management System (CEMS) (D042) Engine Status, Configuration, and TCTO Reporting Procedure*s, 1 Feb 2022

TO 00-33A-1001, *Methods and Procedures, General Cyber Defense Operations Activities Management Procedures and Practice Requirements*, 11 May 2023

TO 00-35D-54, *USAF Deficiency Reporting, Investigation and Resolution*, 15 Aug 2022

TO 00-80C-1, *Crash, Damaged, Disabled Aircraft Recovery Manual*, 21 Jun 2023

TO 00-85-20, *Engine Shipping Instructions*, 1 Jul 2022

TO 00-105E-9, *Aerospace Emergency Rescue and Mishap Response Information*, 6 Jul 2023

TO 00-110A-1 *Guidelines for Identification and Handling of Aircraft and Material Contaminated with Radioactive Debris*, 4 Aug 2021

TO 1-1-3, *Inspection and Repair of Aircraft Integral Tanks and Fuel Cells*, 28 Mar 2022

TO 1-1-8, *Application and Removal of Organic Coatings, Aerospace and Non-Aerospace Equipment*, 24 Sep 2023

TO 1-1B-50, *Basic Technical Order for USAF Aircraft Weight and Balance*, 12 Sep 2023

TO 1-1H-39, *Aircraft Battle Damage Repair General Technical Manual*, 15 May 2023

TO 1-1-300, *Maintenance Operational Checks and Check Flights*, 15 Aug 2023

TO 1-1-691, *Cleaning and Corrosion Prevention and Control, Aerospace and Non-Aerospace Equipment*, 22 Jul 2022

TO 2-1-18, *Aircraft Engine Operating Limits and Factors*, 1 Jan 2023

TO 2J-1-18, *Preparation for Shipment and Storage of Gas Turbine Engines*, 1 Nov 2022

TO 4W-1-61, *Maintenance and Overhaul Instruction - All Types Aircraft Wheels*, 27 Nov 2023

TO 11A-1-33, *Handling and Maintenance of Explosives-Loaded Aircraft*, 26 Oct 2022

TO 11A-1-10, *Air Force Munitions Surveillance Program and Serviceability Procedures*, 5 Apr 2023

TO 11A-1-60, *General Instructions Inspection of Reusable Munitions Containers and Scrap Material Generated from Items Exposed to or Containing Explosives*, 27 Feb 2023

TO 11A-1-63, *Munitions Assembly Procedures—Inspection and Assembly of Conventional Munitions*, 5 Jul 2023

TO 11C15-1-3, *Chemical Warfare Decontamination Detection and Disposal of Decontamination Agents,* 28 Feb 04

TO 11D1-3-8-1, *Decontamination Apparatus, Power Driven, Portable Type A/E32U-8, (Engineered Air)*, 20 Sep 2019

TO 11N-3150-8-1, *USAF DIAMONDS Policy and Procedures*, 31 May 2013

TO 31R2-1-251, *General Instructions Transmission of False Distress Signals on Emergency Frequencies*, 11 Sept 05

TO 31S5-4-*ETOOL-1, eTool Set Up and Management*, 1 Sep 2023

TO 32-1-101, *Use and Care of Hand Tools and Measuring Tools*, 19 Aug 2023

TO 33-1-37-1, *Joint Oil Analysis Program Laboratory Manual, Volume I*, 15 Sep 2014

TO 33-1-37-2, *Joint Oil Analysis Program Laboratory Manual, Volume II*, 15 Jun 2022

TO 33-1-37-3, *Joint Oil Analysis Program Laboratory Manual, Volume III*, 15 Jun 2022

TO 33-1-37-4, *Joint Analysis Program Manual, Volume IV*, 1 Jul 2022

TO 33-1-38, *Cybersecurity for Automatic Test Systems and Automatic Test Equipment in FSC*, 19 Aug 2022

TO 33B-1-1, *Nondestructive Inspection Methods Basic Theory*, 1 Jul 2022

TO 33B-1-2, *Nondestructive Inspection General Procedures and Process Controls*, 15 May 2021

TO 33K-1-100-1, *Calibration Procedure for Maintenance Data Collection Codes and Calibration Measurement Summaries*, 30 Nov 2023TO 34-1-3, *Machinery and Shop Equipment*, 23 Aug 2019

TO 35-1-3, *Corrosion Prevention and Control, Cleaning, Painting, and Marking of USAF Support Equipment*, 26 Jan 2022

TO 35-1-4, *Processing and Inspection of Support Equipment for Storage and Shipment*, 8 Jun 2013

TO 35-1-24, *Air Force Economic Repair/Replacement Criteria for Selected Warner Robins Logistics Complex (ALC) Managed Support Equipment (SE)*, 20 Sep 2023

TO 35D-1-2, *Technical Manual –Munitions Materiel Handling Equipment Miscellaneous and Locally Manufactured (Munitions Related)*, 1 Nov 2023

TO 35D-2-2, *Munitions Materiel Handling Equipment Miscellaneous and Locally Manufactured Armament Related*, 15 Oct 2023

TO 37A9-3-11-lCL-l, *Checklist, Operational and Organizational Maintenance Hot Refueling and Hot Integrated Combat Turn-Around Procedures, Aircraft Fuel Servicing Unit Type GRU 17/E Pantograph PACAF Type IV Hydrant Servicing*, 15 Apr 2017

TO 42B1-1-18, *General Procedures, Handling of H-70 (Hydrazine–Water Fuel)*, 1 Jun 2020

TO 44B-1-15, *General Instructions - Jet Engine Anti-friction Bearing Handling, Removal, Cleaning, Inspecting, and Installation at Jet Engine Base Maintenance Facilities*, 29 Sep 2023

TO 42E1-1-1, *Organizational, Intermediate and Depot Maintenance; Aviation Hoses and Tube Manual*, 15 Apr 2022

Prescribed Forms

AF Form 596, *Quick Engine Change Kit Inventory*

AF Form 861, *Base/Transient Job Control Number Register*

AF Form 864, *Daily Requirement and Dispatch Record*

AF Form 2001, *Notification of TCTO Kit Requirements*

AF Form 2400, *Functional Check Flight Log*

AF Form 2401, *Equipment Utilization and Maintenance Schedule*

AF Form 2402, *Weekly Equipment Utilization and Maintenance Schedule*

AF Form 2403, *Weekly Aircraft Utilization/Maintenance Schedule*

AF Form 2407, *Weekly/Daily Flying Schedule Coordination*

AF Form 2410, *Inspection/TCTO Planning Checklist*

AF Form 2411, *Inspection Document*

AF Form 2426, *Training Request and Completion*

(**Added-AFGSC**) AFGSC Form 122, *Abort /IFE Record*

(**Added-AFGSC**) AFGSC Form 140, *CTK Inventory and Control Log*

(**Added-AFGSC**) AFGSC Form 145, *Lost Tool/ Object Report*

(**Added-AFGSC**) AFGSC Form 147, *Quality Assurance Impoundment Record*

AF Form 2408, Generation Maintenance Plan

(**Added-AFGSC**) AFGSC Form 45, *AFREP Source of Approval Repair (SAR) Request*

(**Added-AFGSC**) AFGSC Form 64, *Request for Special Certification*

AF Form 2409, Generation Sequence Action Schedule

Adopted Forms

(**Added-AFGSC**) AF Form 4366, *Aircraft Inspection Flow Chart*

AF Form 55, Employee Safety and Health Record

AF Form 332, *Base Civil Engineer Work Request*

AF Form 623, *Individual Training Record*

(**Added-AFGSC**) AFTO Form 367, *Aircraft Discrepancy Gig Sheet*

DAF Form 797, *Job Qualification Standard Continuation/Command JQS*

DAF Form 847, *Recommendation for Change of Publication*

AF Form 1067, *Modification Proposal*

DAF Form 1098, *Special Tasks Certification and Recurring Training*

AF Form 1297, *Temporary Issue Receipt*

AF Form 1492, *Warning Tag*

AF Form 2005, *Issue/Turn-In Request*

DAF Form 2096, *Classification/On the Job Training Action*

AF Form 3580, *USAF Museum Aerospace Vehicle Static Display Egress and Safety Certificate*

AFTO Form 20, *Caution and Inspection Record*

AFTO Form 66, *TMDE Bar Codes (Polyester Film)*

AFTO Form 82, *TCTO Verification Certificate*

AFTO Form 95, *Significant Historical Data*

AFTO Form 97, *Aerospace Vehicle Battle Damage Incident Debrief/Assessment/Repair Record*

AFTO Form 97B, *Aircraft Battle Damage Evaluator Checklist*

AFTO Form 103, *Aircraft/Missile Condition Data*

AFTO Form 242, *Nondestructive Inspection Data*

AFTO Form 244, *Industrial/Support Equipment Record*

AFTO Form 252, *Technical Order Publications Change Request*

AFTO Form 345, *Aerospace Vehicle Transfer Inspection Checklist and Certification*

AFTO Form 349, *Maintenance Data Collection Record*

AFTO Form 350, *Reparable Item Processing Tag*

AFTO Form 492, *Maintenance Warning Tag*

AFTO Form 726, *Transient Aircraft Service Record*

AFTO Form 781, *Arms Aircrew/Mission Flight Data Document*

AFTO Form 781A, *Maintenance Discrepancy and Work Document*

AFTO Form 781C, *Avionics Configuration and Load Status Document*

AFTO Form 781H, *Aerospace Vehicle Flight Status and Maintenance*

AFTO Form 781J, *Aerospace Vehicle - Engine Flight Document*

AFTO Form 781K, *Aerospace Vehicle Inspection, Engine Data, Calendar Inspection and Delayed Discrepancy Document*

DD Form 250, *Material Inspection and Receiving Report*

DD Form 1348-6, *DoD Single Line Item Requisition System Document*

DD Form 1610, *Request and Authorization for TDY Travel of DoD Personnel*

(**Added-AFGSC**) DD Form 2757, *Welding Examination Record*

DD Form 2861, *Cross-Reference*

FAA Form 7460-1, *Notice of Proposed Construction or Alteration*

Abbreviations and Acronyms

(Added-AFGSC) 2LM—Two Level Maintenance

ABDR—Aircraft Battle Damage Repair

AC—Aircraft Commander

ACC—Air Combat Command

(Added-AFGSC) ACE—Agile Combat Employment

ACR—Authorization Change Requests

AD—Airworthiness Directives

ADR—Aircraft Document Review

AETC—Air Education and Training Command

(Added-AFGSC) AF—Air Force

AFCSM—Air Force Computer Systems Manual

(Added-AFGSC) AFERMS—Aircrew Flight Equipment Records Management

AFETS—Air Force Engineering and Technical Service

AFI—Air Force Instruction

AFLCMC—Air Force Life Cycle Management Center

AFMAN—Air Force Manual

AFMC—Air Force Materiel Command

AFPAM—Air Force Pamphlet

AFPD—Air Force Policy Directive

AFR—Air Force Reserve Command

AFREP—Air Force Repair and Enhancement Program

AFRIMS—Air Force Records Information Management System

AFSC—Air Force Specialty Code

AFSCI—Air Force Sustainment Center Instruction

AFTO—Air Force Technical Order

AGE—Aerospace Ground Equipment

(Added-AFGSC) AIMS—Air Identification Mark XII System

AIRCAT—Automated Inspection, Repair, Corrosion, and Aircraft Tracking

ALC—Air Logistics Complex

ALIS—Autonomic Logistics Information System

AMC—Air Mobility Command

AME—Alternate Mission Equipment

(Added-AFGSC) AMIC—Acquisition Management & Integration Center

AMU—Aircraft Maintenance Unit

AMS—Air Mobility Squadron

AMXS—Aircraft Maintenance Squadron

(Added-AFGSC) AMXS/CC—Aircraft Maintenance Squadron Commander

ANG—Air National Guard

APU—Auxiliary Power Unit

AQL—Acceptable Quality Level

ARC—Air Reserve Component

AS—Allowance Standard

ASC—Aircraft Service Changes

(Added-AFGSC) ASC—Allowance Source Codes

ASIP—Aircraft Structural Integrity Program

ASM—Aircraft Structural Maintenance

AVDO—Aerospace Vehicle Distribution Office

AWM—Awaiting Maintenance

AWP—Awaiting Parts

(Added-AFGSC) BAMS—Bomber Airborne Maintenance Support

BCS—Bench Check Serviceable

(Added-AFGSC) BEM—Base Engine Manager

(Added-AFGSC) BGS—Bomber Generation Squadron

BSL—Basic Systems Listing

BSP—Base Support Plan

(Added-AFGSC) BTF—Bomber Task Force

(Added-AFGSC) C2—Command and Control

CA—Cannibalization Authority

CAAP—COMAFFOR Apportionment and Allocation Process

CA/CRL—Custodian Authorization/Custody Receipt Listing

CAD/PAD—Cartridge Actuated Device/Propellant Actuated Device

CAI—Critical Application Items

CANN—Cannibalization

CAT I—Category I

CAT II—Category II

CB—Customer Bulletins

CBM+—Condition-Based Maintenance Plus

CBRNE—Chemical, Biological, Radiological, Nuclear, and high-yield Explosive

CBU—Cluster Bomb Unit

CCY—Calculated Cycles

CD—Deputy Commander (MXG/CD)

CDA—Commercial Derivative Aircraft

CDB—Central Database

CDDAR—Crashed, Damaged or Disabled Aircraft Recovery

(Added-AFGSC) CDDS—CITS Deployable Diagnostic System

CE—Civil Engineer

CEMS—Comprehensive Engine Management System

(Added-AFGSC) CEP—Continuous Evaluation Program

CETS—Contractor Engineering and Technical Services

CFETP—Career Field Education and Training Plan

CFT—Contract Field Team

CM—Configuration Management

CMD—Commercial Mobile Device

CMS—Component Maintenance Squadron

CND—Can Not Duplicate

(Added-AFGSC) CNMS—Communication, Navigation, and Mission Systems

(Added-AFGSC) CO—Contracting Officer

COMAFFOR—Commander, Air Force Forces

Cont/Exp—Contingency/Expeditionary

COMSEC—Communications Security

CONUS—Continental United States

CPINS—Computer Program Identification Numbering System

CRF—Centralized Repair Facility

CSI—Critical Safety Items

CTK—Composite Tool Kit

CCW—Counter Chemical Warfare

DAFI—Department of Air Force Instruction

DBM—Database Manager

DCA—Design Control Activity

DCC—Dedicated Crew Chief

DCMA—Defense Contract Management Agency

DDR—Daily Demand Rate

(Added-AFGSC) DDR—Data Detailed Record

DEV—Deviation

DFT—Depot Field Team

DIAMONDS—Defense Integration and Management of Nuclear Data Services

DIFM—Due-in From Maintenance

DISA—Defense Information System Agency

DIT—Data Integrity Team

DLA—Defense Logistics Agency

DMS—Decentralized Materiel Support

D23—Repair Cycle Asset Management Listing

DOC—Designed Operational Capability

DoD—Department of Defense

DoDI—Department of Defense Instruction

DoDD—Department of Defense Directive

DOI—Date of Installation

DOM—Date of Manufacture / Director of Maintenance

DOP—Dropped Object Prevention / Director of Propulsion

DR—Deficiency Report

DLADS—Defense Logistics Agency Disposition Service

DRU—Direct Report Unit

DSV—Detected Safety Violations

(Added-AFGSC) ECS—Environmental Control System

(Added-AFGSC) ELC—Enterprise Location Code defines a unique MIS database for each base

(Added-AFGSC) ELMS—Enterprise Logistics Management System

(Added-AFGSC) ERCC—Engine Running Crew Change

(Added-AFGSC) eRCM—enhanced Reliability Centered Maintenance

eTools—Electronic Tools

E&E—Electrical & Environmental

EAWP—Engine Automated Work Package

ECM—Electronic Countermeasures

ED—Incapacitated

EHM+—Engine Health Management

EHR—Event History Recorder

E&I—Evaluation and Inspection

EID—Event Identification Description / Equipment Identification Designator

EM—Engine Management/Emergency Management

EMS—Equipment Maintenance Squadron

EMXG/CC—Expeditionary Maintenance Group Commander

ENMCS—Engine Not Mission Capable for Supply

EOD—Explosive Ordnance Disposal

EOR—End of Runway

EOT—Engine Operating Time

EPE—Evaluator Proficiency Evaluation

ER—Exceptional Release

ERRC—Expendability, Recoverability, Reparability Code

ES—Equipment Specialist

ESOH—Environment Safety and Occupational Health

ESOHMS—Environment, Safety, and Occupational Health Management System

ESP—Expeditionary Site Plan

ESS—Environmental Stress Screening

ETIC—Estimated Time in Commission

ETIMS—Enhanced Technical Information Management System

ET&D—Engine Trending and Diagnostics

ETS—Engineering and Technical Services/Engine Test Stand

EW—Electronic Warfare

EWS—Electronic Warfare System

EX—Exercises/Contingencies

FAA—Federal Aviation Administration

(Added-AFGSC) FAC—Functional Activity Code

FAR—Federal Acquisition Regulation

FCC—Flying Crew Chief

FCF—Functional Check Flight

FHP—Flying Hour Program

FMxC2—Field Maintenance Command and Control

FO—Foreign Object

FOA—Field Operating Unit

FOD—Foreign Object Damage

FOM—Facilitate Other Maintenance

FOUO—For Official Use Only

(Added-AFGSC) FRAG—Fragmentary Operations Order

(Added-AFGSC) FSE—Flying Schedule Effectiveness

FSL—Full Systems Listing

FSR—Field Service Representatives

FY—Fiscal Year

GBU—Guided Bomb Unit

GEOLOC—Geographical Location

GITA—Ground Instructional Trainer Aircraft

(Added-AFGSC) GM—Guidance Memorandum

GOX—Gaseous Oxygen

GP—Group

GSU—Geographically Separated Units

HAF—Headquarters, US Air Force

HAZMAT—Hazardous Material

HF—High Frequency

(Added-AFGSC) HG—Helicopter Group

HHQ—Higher Headquarters

HPO—Hourly Post-flight

HPT—High Pressure Turbine

HQ—Headquarters

HSC—Home Station Check

IAW—In Accordance With

ID—Identification / Integrated Defense

I-Deck—Initialization Deck

IETM—Interactive Electronic Technical Manuals

IFCS—Instrument and Flight Control Systems

IFE—In-Flight Emergency

IFR—In Flight Refueling

ILS-S—Integrated Logistics Systems-Supply

IMDS—Integrated Maintenance Data System

IMIS—Integrated Maintenance Information System

IP—Instructor Pilot

IPCOT—In-Place Consecutive Overseas Tour

IPI—In-Process Inspection

ISO—Isochronal Inspection

I/UA—Immediate and Urgent Action

ISU/DOR—Issue/Due-Out Release

JCN—Job Control Number

JDD—Job Data Documentation

JDRS—Joint Deficiency Reporting System

JEDMICS—Joint Engineering Data Management Information and Control System

JEIM—Jet Engine Intermediate Maintenance

JML—Job Standard Master Listing

JOAP—Joint Oil Analysis Program

JST—Job Standard

KTL—Key Task List

LAN—Local Area Network

LCN—Logistics Control Number

LEAP—Logistics Evaluation Assurance Program

LM—Limited-use Munition

LME—Locally Manufactured Equipment

LMR—Land Mobile Radio

LO—Low Observable

LOX—Liquid Oxygen

LPT—Low Pressure Turbine

LRS—Logistics Readiness Squadron

LRU—Line Replaceable Unit

LSC—Load Standardization Crew

LV—Emergency Leave

MAJCOM—Major Command

MC—Mission Capable

(Added-AFGSC) MCL—Master Course Listing

MDF—Mission Data File

MDS—Mission Design Series

MEL—Minimum Equipment Level

(Added-AFGSC) MEP—Mission Essential Personnel

MESL—Minimum Essential Subsystems List

MFG—Munitions Family Group

MFM—MAJCOM Functional Manager

MGN—Mission Generation Networks

MI—Management Inspection

MICAP—Mission Impaired Capability Awaiting Parts

MIL—Master Inventory List

MILSPEC—Military Specification

MIL-STD—Military Standard

MIS—Maintenance Information Systems

MMA—Maintenance Management Analysis

MMHE—Munitions Materiel Handling Equipment

MOA—Memorandum of Agreement

MOC—Maintenance Operations Center

MOU—Memorandum of Understanding

MPS—Military Personnel Section

(Added-AFGSC) MRM—Maintenance Risk Management

MRPL—Minimum Required Proficiency Load

MRSP—Mobility Readiness Spares Package

(Added-AFGSC) MRT—Maintenance Recovery Team

MSA—Munitions Storage Area

MSE—Maintenance Scheduling Effectiveness

MSEP—Maintenance Standardization & Evaluation Program

MSG—Mission Support Group

MT—Maintenance Training

MSM—DS Maintenance Scheduling Module

MUNS—Munitions Squadron

(Added-AFGSC) MW—Missile Wing

MX—Maintenance

MXG—Maintenance Group

MXG/CC—Maintenance Group Commander

MXG/CD—Maintenance Group Deputy Commander

MXO—Maintenance Operations

MXS—Maintenance Squadron

MX SUPT—Maintenance Superintendent

NAF—Numbered Air Force

NATO—North Atlantic Treaty Organization

NCE—Nuclear Certified Equipment

(Added-AFGSC) NCO—Noncommissioned Officer

NCOIC—Non-Commissioned Officer in Charge

NDI—Nondestructive Inspection

NIE—Normally Installed Equipment

NLT—Not Later Than

NMC—Non Mission Capable

NPA—Non-Powered AGE

NORAD—North American Aerospace Defense Command

NRTS—Not Repairable This Station

NSN—National Stock Number

NSS—Noise Suppression System

NWRM—Nuclear Weapons-Related Materiel

O&M—Operations and Maintenance

OAP—Oil Analysis Program

OBIGGS—On-Board Inert Gas Generating Systems

OBOGS—On-Board Oxygen Generating Systems

(Added-AFGSC) OBTS—On-Board Test System

OCF—Operational Check Flight

OCONUS—Outside Continental U.S.

OFP—Operations Flight Program

OG—Operations Group

G/CC—Operations Group Commander

(Added-AFGSC) OGP—OBTS Ground Processor

OI—Operating Instruction

OIC—Operations-in-Charge

OJT—On-the-Job Training

OPLAN—Operational Plan

OPR—Office of Primary Responsibility

ORE—Operational Readiness Exercises

OS—Operational Squadron

OSS—Operations Support Squadron

OSS&E—Operational Safety Suitability and Effectiveness

(Added-AFGSC) OSS/CC—Operations Support Squadron Commander

OTI—One Time Inspection

OWC—Owning Work Center

P&R—Programs and Resources

PAA—Primary Aerospace Vehicle (Aircraft) Authorized

PACAF—Pacific Air Forces

PAFSC—Primary AFSC

PAI—Primary Aerospace Vehicle (Aircraft) Inventory

PAS—Protective Aircraft Shelter / Personnel Assignment Symbol (Code)

PBR—Percent of Base Repair

PCS—Permanent Change of Station

PDM—Programmed Depot Maintenance

PE—Personnel Evaluation/Periodic Inspection

PED—Portable Electronic Device

PH—Phase

PIC—Purpose Identifier Code / Pilot in Command

PIM—Product Improvement Manager

PIP—Product Improvement Program

PIT—Platform Information Technology

PM—Primary Munition/Program Manager

PMA—Portable Maintenance Aids

PMC—Partially Mission Capable

PME—Precision Measurement Equipment

PMEL—Precision Measurement Equipment Laboratory

PMO—Program Management Office

PO—Program Office

POC—Point of Contact

PPE—Personal Protective Equipment

PRP—Personnel Reliability Program

PRS—Performance Requirements Statement

PS&D—Plans, Scheduling, and Documentation

PWS—Performance Work Statement

QA—Quality Assurance

(Added-AFGSC) QAA—Quality Assurance Application

QASP—Quality Assurance Surveillance Plan

QE—Quarterly Evaluation

QEC—Quick Engine Change

(Added-AFGSC) QLP—Query Language Processor

QRL—Quick Reference List

QVI—Quality Verification Inspections

RAMPOD—Reliability, Availability, Maintainability for Pods

RC—Recommended Change

(Added-AFGSC) RCP—Repair Cycle Processing

(Added-AFGSC) RDS—Records Disposition Schedule

RegAF—Regular Air Force

REMIS—Reliability and Maintainability Information System

RIL—Routine Inspection List

RN—Repair Network

RNM—Repair Network Manager

RPA—Remotely Piloted Aircraft

(Added-AFGSC) RSP—Readiness Spares Package

(Added-AFGSC) S/N—Serial Number

(Added-AFGSC) SARM—Squadron Aviation Resource Management

SB—Service Bulletins

SCR—Special Certification Roster

(Added-AFGSC) SD—Signature Diagnostics

SDAP—Special Duty Assignment Pay

SE—Support Equipment

SEI—Special Experience Identifier

SI—Special Inspection

SIPRNET—Secret Internet Protocol Router Network

SM—Support Munitions

SME—Subject Matter Expert

SMR—Source of Maintenance and Recoverability

SNCO—Senior Non-Commissioned Officer

SOW—Statement of Work

SPRAM—Special Purpose Recoverable Authorized Maintenance

SQ—Squadron

SQ/CC—Squadron Commander

SRAN—Stock Record Account Number

SRU—Shop Replaceable Unit

SEL—Senior Enlisted Leader (Enlisted Duties)

(Added-AFGSC) ST—Special Tools

(Added-AFGSC) SVA—Sole Vouching Authority

TA—Transient Alert

TAA—Training Aid Aircraft

TAC—Total Accumulated Cycles

TBA—Training Business Area

TCC—Transaction Condition Code

TCI—Time Change Item

TCTO—Time Compliance Technical Order

TD—Training Detachment

TDV—Technical Data Violation

TDY—Temporary Duty

TFI—Total Force Integration

TMDE—Test Measurement and Diagnostic Equipment

TMS—Type Model Series

TNB—Tail Number Bin

(Added-AFGSC) TNMCS—Total Not Mission Capable Supply

TO—Technical Order

TODA—Technical Order Distribution Account

TODO—Technical Order Distribution Office

TTML—Test/Training Munitions List

TTP—Tactics, Techniques & Procedures

UCML—Unit Committed Munitions List

UCR—Unsatisfactory Condition Report

UEM—Unit Engine Manager

UFC—Unified Facilities Criteria

UHF—Ultra High Frequency

UII—Unique Item Identifier

UMD—Unit Manpower Document

UPMR—Unit Personnel Management Roster

USAF—United States Air Force

USAFE—United States Air Forces in Europe

UTC—Unit Type Code

UTE—Utilization (rate)

UTM—Unit Training Manager

VHF—Very High Frequency

W&B—Weight and Balance

WASP—Web Applications Software Product

WCE—Work Center Event

WG—Wing

WG/CC—Wing Commander

WG/CD—Vice Wing Commander

WJQS—Work Center Job Qualification Standard

WLCMT—Weapons Load Crew Management Tool

WLCTP—Weapons Load Crew Training Program

WLT—Weapons Load Training

WRE—War Readiness Engine

WRM—War Reserve Materiel

WS—Weapons Standardization

WSM—Weapon System Manager

TQC—Weapons Task Qualification Crew

WTQM—Weapons Task Qualification Training Manager

(Added-AFGSC) WTR—Work center Training Requirement

WWID—Worldwide Identification (code for TCMax®)

WWM—Wing Weapons Manager

WX—Weather

WUC—Work Unit Code

(Added-AFGSC) X/C—Cross-Country

Office Symbols

(Added-AFGSC) AFGSC/A3—AFGSC Operations Directorate

(Added-AFGSC) AFGSC/A4—AFGSC Logistics and Engineering Directorate

(Added-AFGSC) AFGSC/A4A—AFGSC Combat Aircraft Weapons System Team Division

(Added-AFGSC) AFGSC/A4B—AFGSC ICBM/ Helo Maintenance Division

(Added-AFGSC) AFGSC/A4M—AFGSC Maintenance Division

(Added-AFGSC) AFGSC/A4MQ—AFGSC Maintenance Management Branch

(Added-AFGSC) AFGSC/A4N—AFGSC Nuclear Command and Control Communications

(Added-AFGSC) AFGSC/A5/8—AFGSC Strategic Plans, Programs, & Requirements Directorate

(Added-AFGSC) AFGSC/A6—AFGSC Warfighter Communications and Cyber Systems Directorate

Terms

(Added-AFGSC) Active Associate—ARC/ANG component unit retains principal responsibility for weapon system or systems; shares with one or more AD units.

(Added-AFGSC) Addition—A sortie or aircraft added to the printed weekly flying schedule.

(Added-AFGSC) Aerospace Equipment—refers to weapon systems and equipment such as aerospace vehicles, equipment, missiles, nuclear weapons, Test Measurement and Diagnostic Equipment (TMDE), trainers, training equipment, engines, Flight Support Equipment (FSE), industrial plant equipment, all related Support Equipment (SE).

(Added-AFGSC) Air Abort—An airborne aircraft that cannot complete its primary or alternate mission.

(Added-AFGSC) Air Deviation Code—A deviation from the scheduled sortie flight plan occurring after aircraft take-off.

Aircraft and Equipment Impoundment—Isolation of an aircraft or equipment due to an unknown malfunction or condition making it unsafe for use or flight.

Aircraft Purpose Identifier Codes (PIC)—specified in DAFI 21-103, PIC are applied to assigned aerospace vehicles to facilitate standardization of reporting. Examples of PIC are: CC=Combat, BQ=major maintenance awaiting AFMC decision or action; DJ=awaiting depot level maintenance work. Refer to DAFI 21-103 for a listing of all specific PIC.

Air Reserve Component—The Air National Guard and Air Force Reserve together form the ARC.

(Added-AFGSC) Alert Sorties—Sorties flown from alert because of a higher headquarters exercise, active air or practice scramble, or committed to fly from alert on the printed weekly schedule will be considered sorties scheduled and flown as scheduled.

Allowance Standard (AS)—Authorized document that identifies the amount and type of equipment for an organization.

Alternate Mission Equipment (AME)—Equipment identified to a higher end-item, not listed in the table of allowance. Normally, -21 equipment.

(Added-AFGSC) Appoint—To select an individual to fill a position/create a position, all instances when the word “appoint” will require written documentation e.g., an appointment letter.

(Added-AFGSC) Attrition—Losses expected based on historical data. Sorties added by maintenance scheduling to a unit's sortie contract to allow for expected losses due to maintenance, operations, supply, air traffic control, sympathy, HHQ, other, and weather cancellations. If attrition is less or more than planned, adjustments to the schedule should be made to prevent overextending maintenance and/or to stay within the unit's sortie flying hour program. Attrition programmed sorties are not substitutes for capability shortfalls; they are additive to the contract to ensure mission goals are met. A programmed sortie lost will normally be flown in the week/month the loss occurred. If at the end of a quarter losses exceed attrition figures, the OG/MXG CCs will come to an agreement on how the shortfall will be corrected.

(Added-AFGSC) Attrition Reserve—Attrition reserve aircraft are those aircraft required to replace primary aircraft inventory losses each year projected over the life span of the weapons system. These aircraft are distributed to operational and training units to evenly spread life cycle fatigue and ensure all aircraft receive periodic systems upgrades and modifications. Assigned attrition reserves are occasionally realigned to maintain fleet balance. Reference: AFI 16-402.

Automated Inspection, Repair, Corrosion, and Aircraft Tracking (AIRCAT)—is the Individual Aircraft Tracking Program (IATP) of record for the C-130 as mandated by the USAF Aircraft Structural Integrity Program (ASIP). This effort includes development and maintenance of an extensive Oracle database and a wide variety of both client, server, and web-based applications to provide data entry, reporting, and analysis.

Awaiting Maintenance (AWM)—Designation for a deferred discrepancy on an aircraft awaiting maintenance.

Awaiting Parts (AWP)—Designation for a deferred discrepancy on an aircraft awaiting parts.

(Added-AFGSC) Backup Aircraft Inventory (BAI)—Aircraft above the PMAI to permit scheduled and unscheduled maintenance, modifications, inspections and repair without reduction of aircraft available for operational missions.

Bench Stocks—Stores of expendability, recoverability, reparability coded (ERRC) XB3 items kept on-hand in a work center to enhance maintenance productivity.

(Added-AFGSC) Cancel—A deviation to the flying schedule where a scheduled line is deleted/removed prior to crew show. After crew show a ground abort deviation is used.

(Added-AFGSC) Cancellation—A sortie line removed from the printed schedule for any reason. This includes both cancel (CX) and unspared ground abort (GA) deviations.

Cannibalization—Authorized removals of a specific assembly, subassembly, or part from one weapons system, system, support system, or equipment end-item for installation on another end-item to meet priority mission requirements with an obligation to replace the removed item.

Centralized Repair Facility—A facility that performs repairs for a specified region or bases.

Certified Load Crew Member—A load crew member trained and certified by position according to **Chapter 10**.

(Added-AFGSC) Change—A recompilation of a unit's month-by-month flying hour plan, this is required when the unit's flying hour allocation changes.

(Added-AFGSC) Chargeable Aircraft (CHRG ACFT)—The number of aircraft against which units should build their programs. Except in cases where possessed aircraft is forecast to be significantly different from the PMAI such as in building or down-sizing units, chargeable aircraft will normally equal the unit's PMAI, PTAI, or PDAI, as applicable. In these cases, HQ ACC/A3 will assign a chargeable aircraft accountability for the unit in the ACC Flying Hour First Look and Baseline Messages.

(Added-AFGSC) Classic Associate—AD component unit retains principal responsibility for weapon system or systems; shares with one or more ARC/ANG units.

Classified Processing Area (CPA)—Areas identified by the unit which have had an Emission Security assessment and have been approved by the by the wing Information Assurance office to be utilized to discuss or process classified information IAW AFI 16-1404.

Code 1, Code 2, Code 3, Code 4, Code 5—Landing status codes used by aircrew to inform maintenance of their inbound aircraft's condition. A Code 1 aircraft has no additional discrepancies other than those it had when it last departed; a code 2 aircraft has minor discrepancies, but is capable of further mission assignments; a code 3 aircraft has major discrepancies in mission-essential equipment that may require repair or replacement prior to further mission tasking; a code 4 indicates suspected or known nuclear, biological, or chemical contamination; and a code 5 indicates battle damage. Codes 4 and 5 are entered into the MIS as code 8.

(Added-AFGSC) Combat Sortie Generation—A process by which aircraft are generated in a minimum time, during peacetime or wartime, through concurrent operations that may include refueling, munitions loading/unloading, aircraft reconfiguration, and -6 inspection and other servicing requirements. These exercises test a wing's ability to meet current war plans and contingency operations.

Commercial Derivative Aircraft (CDA)—Any fixed or rotary-wing aircraft procured as a commercial Type Certified off-the-shelf aircraft, and whose serial number is listed on an FAA-approved Type Certified Data Sheet.

Commodity Time Compliance Technical Order—TCTO concerning a designated item, subsystem, or system that is not identified as a weapon or military system.

Composite Tool Kit (CTK)—A controlled area or container used to store tools or equipment and maintain order, positive control, and ease of inventory. CTKs are assembled as a kit and designed to provide quick, easy visual inventory and accountability of all tools and equipment. CTKs may be in the form of a toolbox, a shadow board, shelves, system of drawers (Stanley Vidmar®, Lista®), cabinets, or other similar areas or containers. The CTK contains tools and equipment necessary to accomplish maintenance tasks, troubleshooting, and repair.

Condition—Based Maintenance Plus—A set of maintenance processes and capabilities derived from real-time assessment of weapon system condition obtained from embedded sensors, external tests and measurements using portable equipment. The goal of CBM+ is to perform maintenance only when internal and/or external sensors indicate the need instead of performing maintenance on a periodic basis. **Consumable Items**—Also known as "Consumption" or "Expendable" Items designated XB3. Items which are consumed in use, or which lose their original identity during periods of use by incorporation into or attachments upon another assembly. Issued on an as required basis and consist of such supplies as maintenance parts or office supplies.

(Added-AFGSC) Continuation Sortie—A scheduled sortie containing scheduled operation stops. When a crew completes their training/mission and performs an operation stop, the engines/APU remains running, and maintenance does not service the aircraft. The aircraft can subsequently be launched without the participation of maintenance personnel, except for a fire/safety observer. The primary purpose is to on/off load crew members. **Exception:** UH-1 and MH-139 aircraft do not have APUs, therefore the aircrew is authorized to shut down completely.

Contracting Officer Representative (COR)—A COR is an individual designated IAW Department of Defense Federal Acquisition Regulation Supplement subsection 201.602-2 and authorized in writing by the contracting officer to perform specific technical or administrative functions.

Crashed, Damaged or Disabled Aircraft Recovery (CDDAR)—The ability to move damaged or disabled aircraft using specialized equipment.

(Added-AFGSC) Crew Ready—An aircraft that has been properly inspected, fueled, required weapons loaded, necessary maintenance actions completed, the exceptional release signed off (for the first flight of the day) and the tail number passed to operations. **Note:** Units will develop and publish specific crew ready times for each assigned MDS as agreed upon by the OG/CC and MXG/CC.

(Added-AFGSC) Crew Show—The time that the aircrew arrives at the aircraft.

Critical Application Item (CAI)—An item that is essential to weapon system performance or operation, or the preservation of life or safety of operating personnel, as determined by the military services. The subset of CAI whose failure could have catastrophic or critical safety consequences is called CSIs. Refer to **Attachment 7**.

Critical Safety Item (CSI)—A part, assembly, installation equipment, launch equipment, recovery equipment, or support equipment for an aircraft or aviation weapons system that contains a characteristic any failure, malfunction, or absence of which could cause a catastrophic or critical failure resulting in the loss or serious damage to the aircraft or weapons system, an unacceptable risk of personal injury or loss of life, or an uncommanded engine shutdown that jeopardizes safety. Damage is considered serious or substantial when sufficient to cause a 'Class A' mishap. The determining factor in CSIs is the consequence of failure, not the probability that the failure or consequence may occur. For the purpose of this instruction "Critical Safety Item", "Flight Safety Critical Aircraft Part", "Flight Safety Part", "Safety of Flight Item", and similar terms are synonymous.

Cross-tell—Cross-tells are used to highlight trends, benchmarks or safety conditions relating to maintenance equipment, personnel, training, or processes. A cross-tell is initiated to assist other maintenance or logistics personnel with similar equipment to do their jobs more safely and/or efficiently. Typically, a cross-tell will be initiated when a condition or trend is discovered regarding but not limited to, a weapon system or common components that should be shared with other users or potential users. This information should be transmitted using signed and encrypted e-mail to ensure widest dissemination and ensure it is brought to the attention of unit commanders in order to prevent or mitigate mishaps, injury or damage to AF personnel, equipment or property. Typically, cross-tells will provide relevant background information and history and can include such information as NSNs, part numbers, specific location of problem areas.

Customer Wait Time—Customer Wait Time for LRUs is the total elapsed time between the issuance of a customer order and satisfaction of that order, regardless of source (immediate issues or backorders), and can include issues from wholesale and/or retail stocks as well as various other arrangements. Customer Wait Time for end items (engines and pods) includes time for the retrograde and serviceable transportation legs.

(Added-AFGSC) Daily Maintenance Production Meeting—Meeting required by DAFI 21-101 to review the previous day’s accomplishments, verify aircraft and equipment utilization and scheduled maintenance requirements for the current and next day, establish work priorities, and coordinate schedule changes.

Debriefing—Program designed to ensure malfunctions identified by aircrews are properly reported and documented.

Decertification—The removal of certification status from a person for a specific task

Dedicated Crew Chief—DCCs are first-level supervisors in the flightline management structure who manage and supervise all maintenance on their aircraft, and are selected on the basis of initiative, management and leadership ability, and technical knowledge.

Delayed or Deferred Discrepancies—Malfunctions or discrepancies not creating NMC or PMC status that are not immediately corrected.

Delayed Release—Munition or store that fails to eject from an aircraft upon firing of impulse cartridge, but releases sometime afterwards. Release times qualifying “delayed” bombs are outlined in MDS-specific technical orders.

Demand Response Team—Two-member team where one person reads technical order steps and the other person performs the task and responds when each step is completed.

Depot Level Maintenance—Provides the capability to maintain materiel coded for organizational, intermediate and depot levels of maintenance. Includes maintenance requiring the overhaul, upgrading, or rebuilding of parts, assemblies, or subassemblies, and the testing and reclamation of equipment as necessary IAW AFPD 21-1

(Added-AFGSC) Designate—To select and set aside for a specific duty, position or purpose. Designation will not require documentation.

(Added-AFGSC) Deviation—A departure from the printed weekly flying schedule.

Dispatchable CTK—CTK issued out and is designed to be used outside the work center.

(Added-AFGSC) Early Landing—Scheduled sorties landing more than 30 minutes prior to scheduled landing time. Early landing deviations are not included in FSE calculations.

(Added-AFGSC) Early Take-off—Scheduled sorties launched more than 30 minutes prior to scheduled take-off.

Equipment Custodian—Individual responsible for all in-use equipment at the organizational level whose duties include requisitioning, receiving, and controlling of all equipment assets.

Equipment Identification Designator (EID)—A number assigned to a piece of shop equipment, used to track status and accountability.

Equipment Items—Item authorized in the allowance standard within an organization.

(Added-AFGSC) eTool—electronic Tool; Mobile workstation (laptop) used to view electronic TOs.

Evaluated Load—A loading task that is assessed according to **Chapter 10**.

(Added-AFGSC) Exercise—A unit or higher headquarters event designed to test or evaluate an organization's plans, procedures, and operational/maintenance capabilities. Exercises are a planned sortie surge, a combat sortie generation, or unscheduled tasking. Operational readiness inspections and wing directed operational readiness evaluations are combat sortie generations.

Expendability, Recoverability, Reparability, Category (ERRC)—Used to categorize Air Force inventory into various management groupings. The grouping determines the type of management used throughout the logistics cycle, designates the process to be used in computing requirements and are used in the correction and reporting of asset and usage data. (such as, XB3, XF3, XD2, NF2, NF4).

(Added-AFGSC) Extended Sortie—Scheduled sorties that land more than 15 minutes past the scheduled landing time. If the extended sortie originated on time, record the subsequent late take-off or deletion against the agency that caused the late landing. If the extended sortie did not originate on time, record the subsequent sortie deviation against the agency that caused the original delay.

(Added-AFGSC) F118-100—The General Electric F118 is a non-afterburning turbofan engine derived from the GE F110 afterburning turbofan specially developed for the B-2 Spirit stealth bomber.

(Added-AFGSC) Ferry Sortie—Those sorties flown to transfer an aircraft to or from a maintenance facility or to a new assignment, including inter-command, inter-unit transfers.

Flight Chief—NCO responsible to the maintenance officer or superintendent for management, supervision, and training of assigned personnel.

FK or FV—Prefix used to identify the munitions supply account. FV denotes units utilizing the TICMS and FK denotes units utilizing ILS-S or manual records supply point within a munitions'' operations unit for conventional munitions.

(Added-AFGSC) Flown as Scheduled Sortie—A sortie flown by a specific aircraft on the date and time indicated on the printed weekly schedule, and those aircraft that are defined as "flown as scheduled" elsewhere in this instruction.

(Added-AFGSC) Flying Scheduling Effectiveness (FSE) Rate—The FSE rate is the percentage of sorties flown as scheduled. This rate determines how efficiently the planned/printed flying schedule was executed. It also indicates unit turmoil caused by flying schedule deviations.

(Added-AFGSC) Functional Check Flight (FCF)—The flight of an aircraft, in accordance with the applicable -6 manual, to verify the airworthy condition of the aircraft.

Functional Checklist—locally developed checklists used to identify the steps required to react to specific events. Functional checklists are required for use by functional area(s) during actions such as aircraft crash, mass loads, severe weather warning or evacuation, self-inspections.

(Added-AFGSC) Geographically Separated Unit (GSU)—A unit separated from or without a parent Maintenance Group. Units not aligned under a maintenance group.

(Added-AFGSC) Ground Abort—Event after crew show time that prevents a "crew ready" aircraft from becoming airborne. Ground aborts are categorized as maintenance (GAA, GAB, GAC), operations, HHQ, weather, sympathy, other, etc. The difference between a ground abort and a cancel is after crew show it is a ground abort, before crew show it is a cancel. A ground abort by itself is not a deviation but can cause a deviation such as lost sortie or late take-off.

(Added-AFGSC) Hangar Queen—An aircraft that has not flown for more than 30 consecutive days.

(Added-AFGSC) Higher Headquarters—A controlling agency above wing level.

(Added-AFGSC) Home Station Sortie—Sorties launched from the home base or deployed locations where parent unit maintenance is provided.

Hung Ordnance—Any item attached to the aircraft for the purpose of dropping or firing which has malfunctioned or failed to release. In addition, hung ordnance includes the following items: (1) External fuel tanks after unsuccessful jettison attempt; (2) Remaining ordnance after an inadvertent release; (3) 20/30 mm ammunition after a gun malfunction (no fire, unplanned cease fire, runaway gun, or gun unsafe indication); (4) Any stores determined to be in an unsafe condition.

(Added-AFGSC) Immediate Response Aircraft—Mission capable aircraft postured to meet short-notice taskings which allow flexibility in meeting required Designed Operational Capability (DOC) timing.

Inadvertent Release—Uncommanded launch or release of a store or ordnance or launch or release of a store or ordnance other than those selected when a launch or release command was generated (system malfunction); does not include an unintentional release. If commanding a single release,

do not consider a double bomb release as an inadvertent release if the releases occur from a practice bomb dispenser.

Individual Tools and Equipment—Tools and equipment that are available for individual sign-out but stored in the tool room in storage bins, cabinets, shelves with every item having an assigned location (example, flashlights, ladders). **Integrated Logistics System-Supply (ILS-S)**—is the overarching term used to describe the system(s) used by base retail materiel management operations. ILS-S is comprised of the Enterprise Solution–Supply. In many cases the term ILS-S is used to identify system related functions and/or references.

(Added-AFGSC) In-Flight Emergency (IFE)—An airborne aircraft that encounters a situation or emergency that results in an IFE being declared by the aircrew. (Not a deviation but will be recorded IAW **Attachment 14**).

Intermediate-Level Maintenance—Maintenance consisting of those off-equipment tasks normally performed using the resources of the operating command at an operating location or at a centralized intermediate repair facility.

In Process Inspection (IPI)—Inspection performed during the assembly or reassembly of systems, subsystems, or components with applicable technical orders. An IPI is accomplished and documented by an authorized IPI inspector other than the technician performing the specific step of a task that requires the IPI.

"Knock It Off"—"Knock it Off" empowers all Airman regardless of rank to terminate an operation or situation which they perceive is unsafe or too dangerous. "Knock it Off" includes using a recognizable "audible" (capable of being heard) from anyone in an effort to prevent a potential mishap.

(Added-AFGSC) Joint Nuclear Operations Center (JNOC)—Is Global Strike/USSTRATCOM JFACC's nuclear command center responsible for the day-to-day capability provided by ICBMs bombers, Nuclear Command and Control (NC2), and (Reconnaissance in Support of Nuclear Operations) RISNO assets.

(Added-AFGSC) Late Landing—Aircraft landing 30 minutes past its scheduled landing time, does not apply to continuation sorties. If the sortie originated on time, record the subsequent late take-off or cancellation against the agency that caused the late landing. If the extended sortie did not originate on time, record the subsequent sortie deviation against the agency that caused the original delay. Late landings are not included in FSE calculations.

(Added-AFGSC) Late Take-off—Scheduled sortie launched more than 30 minutes after scheduled take-off time.

Lead Crews—A load crew certified by the load standardization crew (LSC), which is assigned to WS to assist in conducting the weapons standardization program. **Levels**—Computed and authorized requirements for a quantity of assets.

Loading Standardization Crew (LSC)—A load crew designated by the WWM and the WS superintendent to administer the weapons standardization program. LSC members have certification and decertification authority.

Loading Task—The actions required by one crew member, in a designated position, to accomplish a munitions load.

Local Commander—The group commander with responsibility for maintenance (as applicable to loading technical data).

Maintenance Capability—Unit's ability to generate and sustain weapon systems to support the mission. It is composed of personnel, capacity (facilities, support equipment, and parts), and weapons systems and is affected by policies and business practices.

Maintenance Cyber Discipline—A focus on daily cyber hygiene activities which requires continuous attention in order to mitigate daily threats by creating a culture of cyber awareness, discipline, and strict compliance.

(Added-AFGSC) Maintenance Scheduling Effectiveness (MSE)—A measurement used to determine what percent of the scheduled maintenance actions were completed as scheduled in the weekly flying schedule.

Maintenance Training—Any proficiency, qualification, or certification tasking required by a technician to perform duties in their primary AFSC.

Master Inventory List (MIL)—Primary source document for inventory of CTKs. The MIL indicates the total number of items in each drawer or section of the tool kit. MIL may be automated.

Mission Design Series (MDS)—Alpha and numeric characters denoting primary mission and model of a military weapons system.

Mission Generation Network—The MGN supports all Organizational-level, on-equipment and off-equipment maintenance and is optimized at the Wing-level across the USAF. MGN consists of the cumulative effort required to generate and sustain sortie and mission production to meet assigned mission requirements.

Minimum Required Proficiency Load (MRPL)—Recurring loading of munitions for which a person is certified.

(Added-AFGSC) Monthly, Bi-Monthly, Semiannual, or Annual Intervals—Requirements will be accomplished by the last day of the scheduled month.

Munitions Decertification—Removal of the certification status of a person that precludes them from loading a specific type of munitions or MFG.

(Added-AFGSC) Night Operations—Flight time logged between the end of evening civil twilight and the beginning of morning civil twilight.

Normally Installed Equipment (NIE)—launchers, and pylons normally installed on an aircraft.

No-Lone Zone—Area where the two-person concept must be enforced because it contains nuclear weapons, nuclear weapons systems, or certified critical components.

Non-Consumable Item—Also referred to as a "non-expendable" or "equipment" item. Durable items that are capable of continuing or repetitive use by an individual or organization.

Non-Release—System malfunction in which a weapon does not release from the delivery system.

(Added-AFGSC) Off—Station Sorties—Sorties flown away from home base (cross-country) and parent unit maintenance is not provided. This includes aircraft that divert or break off-station and parent unit maintenance is sent to repair and launch the aircraft. **Note:** Off-station sorties are

considered flown as scheduled. Deviations incurred are not used in scheduling effectiveness or abort rate computations.

Off-Equipment Maintenance—Maintenance tasks that are not or cannot be effectively accomplished on or at the weapon system or end-item of equipment but require the removal of the component to a shop or facility for repair.

On-Equipment Maintenance—Maintenance tasks that are or can be effectively performed on or at the weapon system or end-item of equipment.

Operating Stock—The bits and pieces needed to support a maintenance work center that does not meet the criteria of bench stock. It includes reusable items such as dust covers, hydraulic line covers, caps, items leftover from work orders, TCTOs. Items deleted from bench stock that are less than a full Unit of Issue (UI) are not considered operating stock but may be retained as work order residue.

(Added-AFGSC) Operational Check Flight (OCF)—The first flight of an aircraft that has had extended downtime or extensive maintenance which does not require an FCF.

Operational Safety, Suitability & Effectiveness (OSS&E)—OSS&E is an outcome of properly applied systems engineering principles, processes, and practices. Well-integrated configuration management and control, deficiency reporting and response, reliability, maintainability, integrity, and other engineering practices ensure that base-lined engineering characteristics of systems and end items are not allowed to degrade as a result of maintenance, repairs, parts substitutions, and similar activities. The PM is responsible for the assurance OSS&E throughout the life cycle of each configuration of each component of each system.

(Added-AFGSC) Operations and Maintenance (O&M) Day—Any day, Monday through Friday, not including federal holidays or command directed family days.

Organizational Level Maintenance—Maintenance consisting of those on-equipment tasks normally performed using the resources of an operating command at an operating location.

PACER WARE—is the unclassified term for an actual change or notification of a deficiency to an Electronic Warfare system.

Personnel Protective Equipment (PPE)—Equipment required to do a job or task in a safe manner.

(Added-AFGSC) Pilot Reported Discrepancy—Any maintenance event recorded against a sortie or ground abort (Cap codes 2,3,4,5,9). Does not include red ball maintenance.

Plan—A forecasted scheme of sequenced and timed events for accomplishing broad objectives. The plan is the product of annual, quarterly, and monthly planning of scalable operations and maintenance activities necessary to achieve long term mission requirements.

(Added-AFGSC) Planned Sortie Surge—A scheduling option where a unit may plan to produce sorties at a higher-than-normal rate. To qualify as a surge, the number of planned sorties will exceed the normal daily sortie rate by at least 50 percent. This will be based on the monthly daily sortie rate as determined by MO PS&D.

Preload—A complete munition and suspension equipment package ready for loading.

Primary Aerospace Vehicle Authorization (PAA)—The number of aircraft authorized to a unit for performance of its operational mission. The primary authorization forms the basis for the allocation of operating resources to include manpower, support equipment, and flying-hour funds.

Primary Aerospace Vehicle Inventory (PAI)—The aircraft assigned to meet the primary aircraft authorization. Includes PMAI, PTAI, PDAI and POAI.

(Added-AFGSC) Primary Development/Test Aircraft Inventory (PDAI)—Formerly CB or Test. Aircraft assigned primarily for the test of the aircraft or its components for purposes of research, development, test and evaluation, operational test and evaluation, or support for testing programs.

(Added-AFGSC) Primary Mission Aircraft Inventory (PMAI)—Formerly CC/CA PAA Coded Aircraft. Aircraft assigned to a unit for the performance of its wartime mission.

(Added-AFGSC) Primary Other Aircraft Inventory (POAI)—Formerly ZA, ZB. Aircraft required for special missions not elsewhere classified.

(Added-AFGSC) Primary Training Aircraft Inventory (PTAI)—Formerly TF. Aircraft required primarily for technical and specialized training for crew personnel or leading to aircrew qualification.

Production Superintendent (Pro Super)—Senior NCO responsible for squadron maintenance production. Directs the maintenance repair effort.

(Added-AFGSC) Program Element (PE)—The PE is the smallest unit of military output controlled at the DOD level. It is identified by a six-digit alphanumeric program element code (PEC). The sixth character, “F", identifies the PE with the Air Force.

(Added-AFGSC) Program Element Code (PEC)—The six-digit alphanumeric code used to identify the Program Element (see definition above).

Program Manager (PM)—The designated individual with responsibility for and authority to accomplish program objectives for development, production, and sustainment to meet the user's operational needs. The PM will be accountable for credible cost, schedule, and performance reporting to the Milestone Decision Authority.

Programmed Depot Maintenance (PDM)—Maintenance activities requiring skills, equipment, or facilities not normally possessed by operating locations.

Project Funds Management Records—a record maintained in the material accounting system to provide for control over that portion of each responsibility center manager operating budget programmed for purchase of expense materiel from the Defense Business Operations Funds stock activity fund. It is used to record available expense authority, current month and fiscal year-to-date sales, sales returns, and due outs for both supplies and expense equipment.

Quality Assurance (QA)—Office or individual who monitors maintenance (organic or contractor) on a daily basis.

Quarterly Evaluation (QE)—Recurring calendar task evaluations required by munitions and weapons personnel.

Quick Reference List (QRL)—Listing of fast moving, high use items required for primary mission aircraft. The basic purpose of the QRL is to provide maintenance personnel with a speedy way to place a demand on the supply system.

Rag—A remnant of cloth purchased in bulk or a standardized, commercial quality, vendor-supplied shop cloth (uniform size and color) or similar material used in general industrial, shop, and flightline operations.

(Added-AFGSC) Ready Aircrew Program (RAP)—Continuation training regulated under the AFI 11-2 MDS specific series for training of aircrews assigned to units primarily flying fighter, bomber, and LDHD PMAI. The AFGSC flying hour program centers around unit RAP tasking orders and the associated flying hours derived using the flying hour program models.

Reclama—A request to a duly constituted authority to re-consider its decision or its proposed action (see JP 1-02).

Recoverability Code—A one position code assigned to end items and support items to indicate the recoverability intention and the level of maintenance authorized disposition action on unserviceable support items; and for reparable items, it is used to indicate the lowest maintenance level responsible for repair, disposition, or condemnation of the item.

Recurring Discrepancy—A recurring discrepancy is one that occurs on the second through fourth sortie or attempted sortie after corrective action has been taken and the system or sub- system indicates the same malfunction when operated.

Reliability-Centered Maintenance—A logical discipline for developing a scheduled-maintenance program that will realize the inherent reliability levels of complex equipment at minimum cost.

Remote Split Operations—Occurs when the ground control stations, the Unmanned Aerial Vehicle (UAV) launch and recovery functions, and the satellite uplink are geographically separated.

Repair Cycle Asset—Any recoverable item with an expendability, recoverability, reparability code (ERRC) category of XD or XF.

Repair Recommendation—An idea or proposal to repair an item that is not currently repaired or is beyond the capability of the work center. An AFREP initiative is generated when an asset has a demand level of "greater than three" per calendar year. All new AFREP initiatives will be staffed through the applicable organizations.

Repairable—Unserviceable items that can be economically repaired and restored to a serviceable condition.

Repeat Discrepancy—A repeat discrepancy is a pilot reported discrepancy (PRD) occurring on the same system or subsystem on the first sortie or sortie attempt after that PRD has been signed off.

Retrograde—Returning assets (reparable assets) from the field to their source of repair.

(Added-AFGSC) Risk—The probability and severity of loss or adverse impact from exposure to various hazards.

(Added-AFGSC) Risk Assessment—The process of detecting/prioritizing hazards and their causes and systematically assessing the associated risks to mission or activity success.

(Added-AFGSC) Risk Management—The systematic process of identifying hazards, assessing risk, analyzing risk control options and measures, making control decisions, implementing control decisions, accepting residual risks, and supervising/reviewing the activity for effectiveness.

Schedule—Planned events that result in final review and agreement of how to execute a proposed plan of sequenced and timed events. Results in a binding commitment captured in writing and approved by signature between operations and maintenance to complete activities required to accomplish agreed upon objectives. Refers to the execution phase of weekly and daily operations and maintenance activities.

(Added-AFGSC) Scheduled Maintenance Action—A maintenance requirement printed in the weekly schedule.

(Added-AFGSC) Scheduled Sortie—An aircraft scheduled for flight by tail number on the weekly flying schedule and confirmed on the daily flying schedule. Incentive flights are considered scheduled sorties and published in the weekly schedule. FCFs and OCFs are excluded.

SEEK EAGLE—The Air Force certification program for determining safe carriage, employment and jettison limits, safe escape, and ballistics accuracy, when applicable, for all stores in specified loading configurations on USAF aircraft.

SERENE BYTE—is the unclassified term for an exercise change or deficiency notification to an Electronic Warfare system.

Shop CTK—Tool kits (not dispatched) used by work center personnel during a shift, provided a single person is responsible for the tool kit.

Shop Stock—Includes items such as sheet metal, electrical wire, fabric, and metal stock, used and stored within a maintenance work center to facilitate maintenance.

(Added-AFGSC) Sortie—A sortie begins when an aircraft becomes airborne or takes off vertically from rest at any point of support. It ends after an airborne flight when the aircraft returns to the surface except for continuation sorties.

(Added-AFGSC) Sortie Contract—A written agreement between operations and maintenance and approved by the WG/CC. It specifies the number of sorties and hours to be flown.

Source Code—Codes assigned to end items and support items to indicate the manner of acquiring items for the maintenance, repair, or overhaul of end items.

Source, Maintenance, Recoverability (SMR) Code—A code assigned to parts and assemblies that provides maintenance activities with repair level responsibilities, support method and disposition instructions. The SMR codes are also input into the supply and maintenance automated data system. The uniform SMR code is composed of three parts, consisting of a two-position source code, a two-position maintenance code, and one position recoverability code.

(Added-AFGSC) Spare Aircraft—An aircraft specifically designated on the flying schedule to replace aircraft that cannot fly its sortie. Spares can include aircraft that have been cancelled, aborted, flown an earlier sortie, scheduled in a later sortie, or an aircraft that has been released after FCF/OCF. Do not count "Printed Spares" used as deviations when computing FSE.

(Added-AFGSC) Spare Ground Abort—Event after crew show time that prevents a "crew ready" aircraft from becoming airborne but is replaced by a spare that meets the mission requirement. Spare ground aborts are categorized as maintenance (GAA, GAB, GAC). The difference between a ground abort and a spare ground abort is the scheduled line is accomplished, where the ground abort is not. A spare ground abort is not a deviation but can cause a deviation such as late take-off. Spare ground aborts do not count towards FSE.

Spares—Serviceable assets that are available for future use, and in the logistics pipeline. The term spare carries the assumption that there are already enough assets in the AF inventory to satisfy end item or quantity per aircraft requirements.

Special Certification Roster (SCR)—Management tool that provides supervisors a listing of personnel authorized to perform, evaluate, and inspect critical work.

Special Purpose CTK—Small individually issued tool kits that because of the nature of contents or type of container could preclude shadowing or silhouetting (example, launch kits, recovery kits, cartridge cleaning kits, oxygen servicing kits).

Subcrew—Two or more certified and/or qualified personnel who may perform specific tasks.

Supply Point—Forward warehouse located within or near the maintenance work center.

Supply Reports—There are many examples of “Supply Reports” used to record supply transactions. The Daily Document Register (D04) provides a means for organizations to review all document numbers processed during the day by the SBSS. The Project Funds Management Records and Organization Cost Center Record Update and Reconciliation (D11) show the current status and internal balance of the Project Funds Management Record by supplies and equipment. The Repair Cycle Asset Management Listing (D23) is used to monitor repair cycle assets and as a management product to monitor the stock position and repair cycle status of repairable (DIFM) assets. It may be produced in several sequences and is provided to the customer daily.

Sub-Pool—A parking area designated by the Airfield Operations Flight that provides authorized pooling of serviceable AGE to enhance close proximity support to using organizations.

(Added-AFGSC) T-9—Phase hangar at Whiteman AFB.

Tactical/Theater Airborne Reconnaissance System (TARS)—is a sensor package offers improved timeliness, reduced support costs, and improved operational capability over film systems. Once fielded, this system will provide the tactical commander with an organic system capable of responding in Near Real-Time (NRT) (in time) to battlefield requirements.

Tail Number Bins (TNB)—Locations established and controlled to store issued parts awaiting installation and parts removed to FOM. Holding bins are set up by tail number, serial number, or identification number.

(Added-AFGSC) Tail Swap—Tail number swaps made to the daily flying schedule IAW **Attachment 14** Aircraft tail swaps are swaps between printed aircraft on the same day, between printed aircraft and spare aircraft on the same day or between printed aircraft and aircraft that have previously flown that day (cross-country return, OCF, FCF, etc.). The term is synonymous with the previously used term “Interchange.”

Task Assignment List—Functional grouping of procedural steps from applicable -33 series TOs, by crew position, to be accomplished in sequence by each crew member during an operation.

Technical Administrative Function—Function responsible for ordering and posting instructions, processing all orders, enlisted performance ratings, and general administrative tasks for the section.

Technical Data—Information (regardless of the form or method of the recording) of a scientific or technical nature, including computer software documentation. As applied in this publication, it includes information required for the design, development, production, manufacture, assembly, operation, training, testing, repair, maintenance, or modification of defense articles.

Technical Order Distribution Office (TODO)—Function required to maintain records on TOs received and distributed.

Time Compliance Technical Order (TCTO)—Authorized method of directing and providing instructions for modifying equipment and performing or initially establishing one-time inspections.

Tool Storage Facility/Tool Room—A controlled area within a work center designated for storage and issue of tools and equipment.

(Added-AFGSC) Total Active Inventory (TAI)—Aircraft assigned to operating forces for mission, training, test, or maintenance functions (including primary aircraft inventory, backup aircraft inventory, attrition, and reconstitution reserve).

Total Asset Visibility—The capability to provide users with timely and accurate information on the location, movement, status, and identity of units, personnel, equipment, materiel, and supplies. It also includes the capability to act upon that information to improve overall performance of the Department of Defense's logistic practices.

(Added-AFGSC) Training Goal—The unit's completion of a formal course training syllabus and/or phase of instruction (TF coded units only).

Unintentional Release—Store or ordnance launched or released through pilot error.

Unique Item Identifier (UII)—The set of data elements marked on items that are globally unique, unambiguous, and robust enough to ensure data information quality throughout life, and to support multi-faceted business applications and users.

Unit Committed Munitions List (UCML)/Test/Training Munitions List (TTML)—The UCML/TTML is a list of primary munitions (PM), support munitions (SM), and limited-use munitions (LM) necessary to meet unit operational and training requirements.

(Added-AFGSC) Unit Training Assembly (UTA)—A planned period when guard or reserve personnel participate in training duty, instruction, or test alert. For the purposes of this instruction, one UTA is considered a single Saturday through Sunday weekend.

Unmanned Aerial Vehicle (UAV)—An unmanned aircraft that is either remotely piloted (such as, Predator) or programmed (such as, Global Hawk).

(Added-AFGSC) Unscheduled Tasking—Tasking in which initial notification occurs after publication of the weekly schedule.

Urgency Justification Code—Two-digit code used to reflect the impact and type of need. The Urgency of Need Designator fills the first position of the Urgency Justification Code. Use of Urgency of Need Designator 1, A and J is restricted and is verified by designated personnel.

Utilization Rate (UTE Rate)—Average number of sorties or hours flown per primary assigned aircraft per period. Usually, time period is based on a monthly rate.

War Readiness Engine (WRE) Levels—The quantity of net serviceable engines required to support the Air Force war tasking and to sustain operational units' war efforts until pipelines are filled and repair capabilities are available. These engines are to be available to support a weapon system from the start of the war until re-supply (via base, intermediate, CRF or depot repair) is established.

War Reserve Materiel (WRM)—Consists of enterprise managed, dynamically positioned equipment and consumables that contribute to initial operations and provide initial support cross the full range of military operations. It enhances Agile Combat Support capability to reduce the time required to achieve an operational capability and/or produce an operational effect.

Weapons Certification—The act of verifying and documenting a person's ability to load a particular type of aircraft, and munition or MFG within established standards.

Weapons Locally-Manufactured Equipment (LME)—All equipment that measures, tests, or verifies system, subsystem, component, or item integrity. It also includes equipment such as handling dollies, storage racks (except storage shelves), maintenance stands, or transport adapters. It does not include simple adapter cables and plugs constructed as troubleshooting aids to replace pin-to-pin jumper wires specified in TOs.

Weapons Standardization (WS)—Organization comprised of the WWM, a Superintendent, the Load Standardization Crew, an academic instructor, and lead crews.

Weapons Task Qualification—A munitions related task not requiring certification.

(Added-AFGSC) Weekly Flying and Maintenance Schedule—The schedule, agreed to by operations and maintenance, and signed by the OG/MXG/WG/CCs, to support the unit's flying and maintenance requirements. In this publication it is referred to as the "flying schedule."

Weight and Balance (W&B) Program—Program used in calculating, verifying, updating, and computing weight and balance on a weapon system.

(Added-AFGSC) Zulu (time)—More commonly known as "GMT" (Greenwich Mean Time).

Attachment 2

AIRCRAFT COMMANDER FEEDBACK ON FCC

Figure A2.1. Aircraft Commander Feedback on FCC.

MEMORANDUM FOR <Unit Designation/Office Symbol> *Date*
<Street>
<Base, State, and Zip Code>
FROM: <Aircraft Commander>
<Street>
<Base, State, and Zip Code>
SUBJECT: Aircraft Commander Feedback of the Flying Crew Chief
(FCC) Was the FCC knowledgeable of the aircraft and the systems?
a - Extremely knowledgeable c - Lacks knowledge
b - Sufficient knowledge d - Not observed
Did the FCC know the status of PMC and NMC discrepancies?
a - Always c - Rarely
b - Most of the time d - Never
Did the FCC perform duties willingly and enthusiastically?
a - Always c - Never b
- Sometimes d - Not
Observed
What type of working relationship did the FCC have with the aircrew?
a - Outstanding c - Fair
b - Good d - Poor
Rate the overall maintenance support provided by the FCC:
a - Outstanding c - Fair
b - Good d - Poor
This FCC was:
a - An asset to the FCC program c - Just getting by b - A hard
worker, but needs more experience d - Detriment to the FCC program
Remarks:
POC is <FCC Program Manager's Name, office symbol, duty phone number>.<signed>
Aircraft Commander

Note*:* Please fold and return to the squadron FCC Program Manager upon return to home station.

Attachment 3

QUARTERLY FCC REPORT FORMAT

Figure A3.1. Quarterly FCC Report Format.

MEMORANDUM FOR MAJCOM/A4L *Date*
FROM: <Unit Designation/Office Symbol>
<Street>
<Base and Zip Code>
SUBJECT: <State fiscal quarter (FY20/1)> Quarterly Flying Crew Chief Report (RCS: AF/A4L(Q&A)0011)

IAW AFI 21-101 <unit designations> report is submitted.
Number of C-coded FCC positions on the Unit Manpower Document entitled to be filled. Include approved changes (losses/increases):
Number of people filling C-coded positions:
Number of qualifying missions flown per quarter by C-coded crew chiefs. Include the number of TO directed missions:
Number of qualifying missions flown by personnel without C-coded prefix. Include TO directed missions flown by non-C-coded prefix personnel:
Number of all missions away from home station that required FCCs:
Total number of days TDY for all C-coded crew chiefs on qualifying missions:
Total number of days TDY for all non-C-coded crew chiefs on qualifying missions:
Unit and MAJCOM remarks and overall program assessment. Include remarks to justify vacant positions: FCC Program Manager is <rank, name>, office symbol, DSN number.
<Sign>
Commander, <Unit Designation>

Attachment 4

ANNUAL FCC REPORT

Figure A4.1. Annual FCC Report.

MEMORANDUM FOR MAJCOM/A4L or DOM *Date*

FROM: <Unit designation/Office Symbol>
<Street>
<Base and Zip Code>
SUBJECT:<state fiscal year (FY20)> Annual Flying Crew Chief Report RCS: AF/A4L(Q&A)0011) IAW AFI 21-101<unit designations> report is submitted.
Number of C-coded FCC positions on the Unit Manpower Document entitled to be filled. Include approved changes (losses/increases):
Number of people filling C-coded positions:
Number of qualifying missions flown per quarter by C-coded crew chiefs. Include the number of TO directed missions:
Number of qualifying missions flown by personnel without C-coded prefix. Include TO directed missions flown by non-C-coded prefix personnel:
Number of all missions away from home station that required FCCs:
Total number of days TDY for all C-coded crew chiefs on qualifying missions:
Total number of days TDY for all non-C-coded crew chiefs on qualifying missions:
Unit and MAJCOM remarks and overall program assessment. Include remarks to justify vacant positions: FCC Program Manager is <rank, name>, office symbol, DSN number.
<Sign>
Commander, <Unit Designation>

Attachment 5

FCC SDAP REQUEST

Figure A5.1. FCC SDAP Request.

MEMORANDUM FOR MAJCOM/A4L or DOM *Date*

FROM: <Unit Designation/Office Symbol>
<Street>
<Base and Zip Code>

SUBJECT: Flying Crew Chief (FCC) SDAP Positions <Increase/Decrease> Request

IAW <unit designations> requests <increase or decrease> of <state quantity of positions>. Provide brief justification; include comments about force structure changes, additional mission requirements. FCC Program Manager is <rank, name>, office symbol, DSN number.
<Sign>
Commander, <Unit Designation>

Attachment 6

FOREIGN OBJECT DAMAGE (FOD) REPORT

Figure A6.1. Foreign Object Damage (FOD) Report.

MEMORANDUM FOR *Date*

FROM:<Unit Designation/Office Symbol> <Street> <Base and Zip Code>
SUBJECT: <Foreign Object Report>. FOD program report number (unit, year, and month, followed by sequence number -- example, 301FW-060501).

Type of report: Initial/Formal Update/Final FOD Report
Date and Time of Incident:
Unit and Base of Incident:
Origin of Sortie:
When discovered (Preflight, Postflight, In-Coming, ETS)
Owning Unit, Base and MAJCOM
MDS and Tail Number (N/A for ETS incidents)
Engine Type, Model, Series (TMS):
Engine S/N:
Engine Position (If Applicable):
Time Since Overhaul:
Description of Incident:
Material Failure: (Yes or No)
Tech Data Deficiency: (Yes/No) Preventable/Non-Preventable:
Investigation Findings:
Action Taken to Prevent Recurrence:
Parts Cost: Labor Cost: Total Cost:
Additional Comments (if necessary):

<Sign>
FOD Monitor, <Unit Designation>

Attachment 7

CRITICAL APPLICATION ITEMS & CRITICAL SAFETY ITEMS

A7.1. CRITICAL APPLICATION ITEMS (CAIs). For the purpose of this instruction, it is an item that is essential to weapon system performance or operation, or the operating personnel as determined by AFI 20-106IP, *Management of Aviation Critical Safety Items*.

A7.1.1. Includes flight safety items, life support, critical safety items (CSI), and nuclear hardened items. For systems including radar, avionics, munitions, contact the PO for the system to obtain the CAI designation.

A7.1.2. The management of CAIs (contains unique repair and manufacturing qualifications; material and manufacturing process requirements; and extensive testing requirements after repair) is a complex process. These specified procedures rest with the program manager.

A7.1.3. Other than TO and PO approved repairs, Electronic Warfare (EW) Systems are Critical Application Items and prohibited from consideration under the AFREP program. Performing repairs on EW system components may render the entire EW system degraded. Environmental Stress Screening (ESS) of repaired EW components is mandatory. Many EW components cannot be repaired due to electrical characteristics that are not visible or evident without special test facilities and procedures, none of which are available to field personnel or unqualified contractors.

A7.2. CRITICAL SAFETY ITEMS (CSIs). For the purpose of this instruction, CSIs are items whose failure may cause loss of life, permanent physical disability or major injury, loss of a system, or significant damage to equipment.

A7.2.1. Special attention is placed on CSIs due to potential catastrophic or critical consequences of failure; Public Law 108-136, section 802, *Quality Control in Procurement of Aviation Critical Safety Items and Related Services*, was enacted to address aviation CSIs. The public law addresses three concerns:

A7.2.1.1. The Design Control Activity (DCA) is responsible for processes related to identification and management of CSIs used in procurement, modification, repair, and overhaul of aviation systems. The DCA is defined as the systems command of a military Service responsible for the airworthiness certification of the system in which a CSI is used.

A7.2.1.2. For contracts involving CSIs, DoD is restricted to DCA approved sources.

A7.2.1.3. The law requires that CSI deliveries and services meet the technical and quality requirements established by the DCA.

A7.2.2. ODM 4140.01, *DoD Supply Chain Materiel Management Procedures*, establishes procedures for the management of aviation CSIs. AFI 20-106IP, *Management of Aviation Critical Safety Items*, addresses requirements for identification, acquisition, quality assurance, management, repair, and disposition of aviation CSIs.

Attachment 8 (Added-AFGSC)

MAINTENANCE RECOVERY TEAM (MRT) TASKING CHECKLIST

Table A8.1. (AFGSC) Maintenance Recovery Team (MRT) Tasking Checklist.

Maintenance Recovery Team (MRT) Tasking Checklist.
1. The MRT POC will: 1.1. Record the following: 1.1.1. Aircraft MDS and tail number. 1.1.2. Location. 1.1.3. Point of contact (POC) and phone number. 1.1.4. All discrepancies requiring support. 1.1.5. Type of and desired skill level of needed technician. 1.1.6. Parts requirements. 1.1.7. Equipment requirements (including tools, testers, etc.) 1.1.8. Mode of transportation and projected date/time of departure. Evaluate capabilities and determine the best mode of transportation (military airlift, commercial, or government vehicle). 1.1.9. Passport/Visa/Immunization requirements for personnel. 1.1.10. Country/Diplomatic clearance requirements for personnel. 1.2. Contact the applicable maintenance supervision to review requirements and request support from the responsible units to assemble an MRT. 1.3. Brief MRT personnel concerning their duties and responsibilities. Ensure the MRT chief understands the responsibilities Emphasize the following: 1.3.1. The MRT is required to call the home station MOC upon arrival to provide a phone number where they can be contacted. 1.3.2. The MRT is responsible for their equipment and parts: 1.3.2.1. Verify necessary parts are available. Open each container to ensure the right part(s) are in the box prior to departure. 1.3.2.2. Check special tools, support and test equipment for serviceability prior to departure. 1.4. Ensure TDY orders are generated for MRT. Consider the following authorizations and provide as required: 1.4.1. Mission Route Support (MRS) or Mission Essential Personnel (MEP). 1.4.1.1. MRS permits the bumping of cargo to allow space for the MRT and their equipment. 1.4.2. Advance per diem. 1.4.3. Commercial travel. 1.4.4. Rental 1.4.5. Variations: 1.5. Direct the responsible shop to order the required parts and the applicable unit to select the required equipment items. If requirements are not known, contact the AC/flight engineer/ crew chief to determine what items are required. 1.5.1. Items too large or heavy will be processed by the responsible shop and given to the TMF for shipment. (If required, coordinate with applicable WST for additional assistance) 1.5.2. If parts cannot be sourced locally, consider directing cannibalization. 1.6. Commercial transportation of an MRT and equipment is, in many cases, the most expeditious method. Consider the following: 1.6.1. Airline:

Maintenance Recovery Team (MRT) Tasking Checklist.
1.6.2. Surface (bus, rail, and limousine). 1.6.3. Air Express Small Package Service. 1.7. Coordinate transportation requirements with TMF. Review the following: 1.7.1. Destination, and priority. 1.7.2. Selected mode of transportation and itinerary. 1.7.3. Names for MRT personnel and nomenclature of equipment items and parts. 1.7.4. Authorization for excess baggage allowance if necessary. 1.7.4. Record TCNs, government bills of lading (GBL), and any applicable billing or shipment numbers. **Note:** Shipment of large or heavy items by commercial airline mandates prior coordination with airline personnel by MOC or the MRT. To maintain control of parts/equipment, they must be hand-carried or checked as baggage. If an item is not accepted as carry-on luggage or checked as baggage, purchase of an extra seat to accommodate it must be considered and is recommended. (Airline policies apply) Advance coordination with the airline is the key to a successful movement without unnecessary delays. 1.8. Maintain contact with the MRT or the unit responsible for the parts/equipment shipment to ensure that all resources arrive in time to make the scheduled departure.

Attachment 9 (Added-AFGSC)

MAINTENANCE RECOVERY TEAM (MRT) CHIEF RESPONSIBILITIES

Table A9.1. (AFGSC) Maintenance Recovery Team (MRT) Chief Responsibilities.

Maintenance Recovery Team (MRT) Chief Responsibilities
1. Prior to Departure. The MRT chief will: 1.1. Receive complete MRT briefing. 1.2. Read and understand all MRT chief responsibilities. 1.3. Ensure all personnel on the MRT are prepared and aware of their part in recovery actions. 1.4. Ensure all equipment/parts/tool kits/technical orders are properly prepared for shipment. 1.4.1. Verify necessary parts are available. Open containers to ensure the right part(s) are in the box. 1.4.2. Check special tools, support and test equipment for serviceability. 2. Upon Arrival. The MRT chief will: 2.1. Contact home station MRT POC. 2.2. Report to the mission commander and/or MOC. 2.3. If possible, debrief aircrew and make initial determination of discrepancy. 2.4. Compute MRT duty day: 2.4.1. Emphasize safety. 2.4.2. Your initial duty day begins at the time you reported to work prior to MRT tasking. The total duty day (home station duty, travel, and recovery site duty) will not exceed 12 hours without approval from owning MXG/CC and/or the group commander at the deployment site. These MXG/CCs may also grant duty time extensions allowing up to a 16 hour duty day for any team member. Technicians are entitled to at least eight hours of uninterrupted rest. 2.4.3. MRT work starts immediately upon arrival unless duty day has expired enroute. 2.4.4. Normal work/rest period at recovery site is 12 hours of work, followed by 12 hours of rest. The 12-hour work period may be extended with concurrence of the Owning MXG/CC and/or the group commander at the deployment site. Do not overwork your team and compromise safety. You are responsible for their care. 2.4.5. If any questions arise consult the AC, group commanders, and senior maintenance representative. 2.5. Report to home station MRT POC with the following information. 2.5.1. Specific discrepancies. 2.5.2. Estimated time in-commission (ETIC). 2.5.3. Billeting room/phone (if applicable). 2.5.4. Expiration time of MRT duty day. 3. During recovery, report to the MRT POC to the following schedule: 3.1. Upon initial assessment of actual discrepancy. 3.2. If maintenance/supply status changes. 3.3. As additional requirements become known (parts, equipment, expertise, etc. 3.4. At the end of shift or upon job completion. 4. Upon completion of recovery. The MRT chief will: 4.1. Assemble all parts/equipment/tools and prepare them for return shipment. Reparable assets brought with you or shipped to you from your home unit must be returned to your unit.

Maintenance Recovery Team (MRT) Chief Responsibilities
Reparable assets issued at the recovery location will require turn-in at the recovery location. If in doubt about disposition, contact the home station MRT POC. 5. Upon return to home station. The MRT chief will notify MRT POC of return.

Attachment 10 (Added-AFGSC)

MAINTENANCE RECOVERY TEAM (MRT) CHIEF TASKING CHECKLIST

Table A10.1. (AFGSC) Maintenance Recovery Team (MRT) Chief Tasking Checklist.

Maintenance Recovery Team (MRT) Chief Tasking Checklist
1. Team Chief: Name- Rank- AFSC- 2. Other Personnel: Name- Rank- AFSC- 3. (AFGSC) Recovery Location: 4. Aircraft Type: 5. Tail Number: 6. Mission Number: 7. Next Destination: 8. Mission Commander: Room# Phone: 9. Director of Operations/MX SUPT: 10. Communications at Recovery Site: 11. Specific Discrepancies: 12. Equipment Required: Item: TCN: 13. Part(s) Required: NSN: TCN: a. Nomenclature: b. Have the required parts been bench checked before packing? Y / N / NA 14. Tool Kits Required: Kit Number: TCN: 15. Support Acft Tail No: 16. Mission Number: 17. Show Time: 18. Orders Prepared? Y / N 19. ETD: 20. Passport/Visa required? Y / N 21. Required Clothing/Money/Shot Records/etc.: 22. Military Travel Request (MTR) prepared? Y / N

Attachment 11 (Added-AFGSC)

MAINTENANCE SCHEDULING EFFECTIVENESS

A11.1. (AFGSC) MAINTENANCE SCHEDULING EFFECTIVENESS.

A11.1.1. **(AFGSC) Purpose.** MSE is a leading indicator that measures the unit's ability to plan and complete scheduled maintenance events (inspections, periodic maintenance, etc.) and scheduled use of maintenance resources (static/Immediate Response (IR)/training aircraft, etc.) on time per the maintenance plan. The AFGSC goal for MSE is 95 percent for aircraft maintenance. A low MSE rate may indicate a unit is experiencing a high rate of turbulence on the flight line, field or back shops. MSE is primarily used as a reliability indicator for maintenance managers assessing the unit's capacity to execute the scheduled maintenance plan.

A11.1.2.2. **(AFGSC)** The MXG/CC may select additional areas for local scheduling effectiveness tracking. The unit will establish standards for these programs. When reported to HHQ, these locally selected areas will not be included in MSE rates. The standards requirement is not applicable for WSA/MSA maintenance schedules; however, MUNS/CC may elect to create MSE requirements for internal tracking. If WSA/MSA units create an MSE requirement they must create a local policy with assigned weighted points for all maintenance actions.

A11.1.2.3. **(AFGSC)** When a unit is tasked with a combat sortie generation, unscheduled tasking, unannounced exercise/real world contingency, or HHQ exercise that impacts the printed weekly maintenance schedule, the plan may be revised or reprinted without incurring deviations with MXG/CC approval. Utilizing **Table A11.1** (for aircraft) normal deviation reporting procedures will be followed once the revised or reprinted plan is finalized. The unaccomplished portion of the original maintenance schedule will not be included in the scheduling effectiveness formula.

Table A11.1. (AFGSC) Aircraft MSE Deviations and Functions. (T-2)

DEVIATION	FUNCTION
Maintenance (MX)	Actions cancelled due to adding aircraft to the flying schedule, lack of manpower, equipment or because of mismanagement.
Operations (OP)	Actions cancelled or not completed on time for operational considerations or because of adding aircraft to the flying and maintenance schedule to meet operations requirements. This also includes maintenance events not completed due to operations group actions, e.g., Aircrew Flight Equipment Section not completing scheduled maintenance as published in the wing weekly flying and maintenance schedule.
Higher headquarters (HHQ)	Actions cancelled or not completed because of higher headquarters tasking from outside of the wing.

DEVIATION	FUNCTION
Weather (WX)	Actions cancelled or not completed because of weather conditions.
Supply (SU)	Deviations that result from verified parts back-order condition.
	Aircraft impounded after publication of the weekly schedule, unscheduled major maintenance where the scheduled maintenance action cannot be accomplished because of tech data restrictions, aircraft off base and unable to return or because of productivity/utilization goal days.
Exception: Any scheduled maintenance for an aircraft that is possessed by depot/PDM/Contract Field Team (CFT), that is not complied with because the aircraft is not released for possession as scheduled to the owning unit does not count toward MSE computations.	

A11.1.2.5. **(AFGSC)** Units may revise or reprint the following days or remainder of that week's maintenance schedule to compensate for adverse weather. This adjustment should be used only in extreme cases and recorded on AF Form 2407. Once changed, normal deviation reporting procedures will apply. **(T-2)**

A11.1.2.6. **(AFGSC)** MO PS&D will coordinate with BGS Lead Pro Super to cancel and reschedule maintenance actions to coincide with the portion of the flying schedule that was cancelled after the unit or OS has achieved the UTE goal for the month. These cancelled maintenance actions will not be included in MSE computations. **(T-2)**

A11.1.2.6.1. **(AFGSC)** To obtain only the aircraft OPs/MX MSE rate, treat events with deviations in categories other than OPs or MX as if they were not missed.

A11.1.3. **(AFGSC) Overall Maintenance Scheduling Effectiveness Rate Formula:** Total Points Earned / Total Points Possible x 100

Table A11.2. (AFGSC) Maintenance Scheduling Effectiveness Computation.

SCHEDULED EVENT	A WEIGHTED POINTS	B NUMBER OF SCHEDULED EVENTS	C POSSIBLE POINTS (A x B)	D COMPLETED AS SCHEDULED	E POINTS EARNED (A x D)
Phase Inspections	6				
Hourly Post Flights	5				
464 System Checkout	5				
Engine Changes	5				

Time Changes	4		
TCTOs	4		
Corrosion Control/ Paint/Wash	4		
Training	3		
Aircraft Static/IR/Alert Prep	3		
Special Inspections	3		
Delayed Discrepancies	3		
Document Reviews	2		
		Total Points Possible:	Total Points Earned:

Attachment 12 (Added-AFGSC)

DEPLOYED OPERATIONS AND OFF-STATION SORTIES

A12.1. (AFGSC) DEPLOYED OPERATIONS AND OFF-STATION SORTIES.

A12.1.1. **(AFGSC) Purpose.** This Chapter establishes rules and procedures used in planning, executing, evaluating, and reporting of unit flying and maintenance schedules at deployed locations where unit maintenance is provided. Sorties flown at deployed locations where no parent unit maintenance is provided are considered off-station sorties. If parent unit support is deployed, this is considered the same as home station support and normal deviation reporting applies. Limited launch support is not considered parent unit maintenance.

A12.1.2. **(AFGSC) General.** Normal deviation reporting applies to deployed operations except as noted in this Chapter. Data from deployed operations will be transmitted or forwarded back to home station to be included in unit totals IAW TO 00-20-2.

A12.1.3. **(AFGSC) Scheduling.** In addition to the procedures for home station scheduling and reporting, deployed units will use the following procedures when developing a weekly flying schedule and reporting deviations:

A12.1.3.1. **(AFGSC)** Separate block(s) of sortie sequence numbers will be assigned for deployment location(s).

A12.1.3.2. **(AFGSC)** Additions and cancellations at deployed locations, which are required to accomplish specific aircrew training requirements and make optimum use of available range time, are considered flown as scheduled. This does not relieve operations and maintenance from developing a viable and realistic flying schedule at the deployed location. The primary purpose of this flexibility is to allow the unit to make up non-effective sorties to ensure the accomplishment of the deployment training plan. Procedures for changing the weekly schedule in **Chapter 14** apply to deployment location flying and maintenance schedules. Additions and cancellations caused by ineffective planning are recorded.

A12.1.3.3. **(AFGSC)** When operating at a deployed location using a daily ATO, follow procedures outlined in **paragraph A14.10** of this instruction.

A12.1.4. **(AFGSC) Aircraft Rotation Planning.**

A12.1.4.1. **(AFGSC)** A Nonstandard Aircraft Rotation Justification memorandum is required only when planning aircraft rotations, which do not maximize the allowable tarry time at the alternate location.

A12.1.4.2. **(AFGSC)** Aircraft rotation planning maximizes fleet aircraft availability by keeping aircraft at the alternate location as long as necessary for the mission and as long as allowable per applicable technical guidance (currently 6 months). When fleet health can be demonstrably improved by a nonstandard aircraft rotation, the MXG/CC will submit a Nonstandard Aircraft Rotation Justification memorandum to the WG/CC for approval. The memorandum should summarize the following:

A12.1.4.2.1. **(AFGSC)** The problem being solved by the nonstandard aircraft rotation(s).

A12.1.4.2.2. **(AFGSC)** The course of action (COAs) considered.

A12.1.4.2.3. **(AFGSC)** The operational benefits analysis, especially for the selected COA.

A12.1.4.3. **(AFGSC)** Notify AFGSC/A4A and 8 AF/A4 once the Nonstandard Aircraft Rotation Justification memorandum is approved by the WG/CC.

A12.1.4.3.1. **(AFGSC)** See **Attachment 13** for Nonstandard Aircraft Rotation Justification memorandum template.

A12.1.5. **(AFGSC)** Deployed Daily Activity Report. Required information for deployed AFGSC units will be transmitted to home station IAW applicable unit deployment plans. See TO 00-20-2 for required data. **(T-2)**

A12.1.6. **(AFGSC) Off-Station Sorties.** Off-station sorties are those sorties flown from other than home station and parent unit maintenance is not provided (e.g., cross-country sorties). Units will publish sorties planned while off-station. Take-off and landing times may be TBD when supporting another unit and the specific times are unknown at the time of publishing. The following paragraphs outline the rules that apply to higher headquarters alert or off-station sorties:

A12.1.6.1. **(AFGSC)** When a spare is launched to the off-station/cross-country location in place of the originally intended aircraft, or for a scheduled deployment to a Forward Operating Location (FOL), one of the following options applies to the home and off-station location flying and maintenance schedules:

A12.1.6.1.1. **(AFGSC)** Option 1. The originally scheduled prime aircraft, which remained on base, may fly the sorties of the departed aircraft for the remainder of the week without recording FSE deviations. MSE is based on the published weekly schedule. **(T-2)**

A12.1.6.1.2. **(AFGSC)** Option 2. The sorties may be tail swapped with a printed spare aircraft on each day's schedule. **(T-2)**

A12.1.6.2. **(AFGSC)** When an aircraft is off-station and cannot return to home station for its scheduled sortie, a deviation will be recorded for the reason the aircraft was unable to return. The reasons will be specific, (e.g., maintenance, operations, weather, etc.). **Note:** If the off-station aircraft can fly its scheduled mission from its location, no deviation is recorded. **(T-2)**

A12.1.7. **(AFGSC)** Deployed MO PS&D Support Operations.

A12.1.7.1. **(AFGSC)** NLT 7 days after a new unit's arrival, MO Superintendent will visit all decentralized scheduling activities and provide technical assistance as needed. **(T-2)**

A12.1.7.2. **(AFGSC)** Units will follow home station guidance. **(T-2)**

A12.1.7.3. **(AFGSC)** Home stations will perform Aerospace Vehicle Distribution Office (AVDO) duties on deployed aircraft unless the possession changes to the deployed location. With home station AVDO approval, deployed MO PS&D will make MIS inventory/status transactions and coordinate message requirements with home station AVDOs. If possession changes, deployed MO PS&D will perform all AVDO duties. **(T-2)**

Attachment 13 (Added-AFGSC)

NONSTANDARD AIRCRAFT ROTATION JUSTIFICATION TEMPLATE

Table A13.1. (AFGSC) Nonstandard Aircraft Rotation Justification Template.

Nonstandard Aircraft Rotation Justification Template
Letterhead DATE MEMORANDUM FOR HQ AFGSC/A4 FROM: X MXG/CC 123 Main Street XXX, AFB EG xxxxx-xxxx SUBJECT: Nonstandard Aircraft Rotation 1. The X Bomb Wing is requesting consideration for a Nonstandard Aircraft Rotation for the next rotation, xx Mon xx, to X……. AFB IAW DAFI 21-101 AFGSC SUP Attachment 12. AFGSC) An analysis of the X wing's capability to support the standard tour indicates associated benefits of shortening the normal 180-day duration for x of the x deployed aircraft. Recommended Courses of Action (COAs) with expected risk associated to meet assigned objects are listed as follows: 1. COA 1 2. COA 2 3. COA 3 3. Describe the operational benefits of the selected COA. 4. My POC for this request is Xxx Xxx, X MXG/MXOS, DSN xxx-xxxx.   JOHN H. DOE, Colonel, USAF Commander cc: 8AF/CC AFGSC/A3 1st Ind, AFGSC/A4, Nonstandard Aircraft Rotation MEMORANDUM FOR X MXG/CC I have reviewed your request for BTF Nonstandard Aircraft Rotation and concur / non-concur with the proposed plan to manage your fleet.

JANE S. DOE, SES, DAF
Director, Logistics and Engineering

Attachment 14 (Added-AFGSC)

FLYING SCHEDULING EFFECTIVENESS

A14.1. (AFGSC) Purpose. This Chapter provides formulas for computing Flying Scheduling Effectiveness and defines flying schedule deviations. Flying Scheduling Effectiveness is a tool to identify those processes within the wing's control that can be improved to help drive down turbulence for both the operator and maintainer. The flying schedule must be loaded in the MIS to track scheduling and deviation data.

A14.1.1. **(AFGSC)** The OS Director of Operations and maintenance leadership, along with MXO, will monitor deviations to ensure they meet the criteria in this publication. **(T-2)** When conflicts arise, leadership of units involved will resolve them at the lowest level. All deviations will be recorded as prescribed in this publication**. (T-2)**

A14.1.2. **(AFGSC)** There are two aircraft FSE standards developed by AFGSC/A4MQ and approved by HQ AFGSC/A4, the overall FSE rate and the maintenance/operations FSE rate. These metrics and their computations are explained in **paragraph A14.16** of this attachment.

A14.2. (AFGSC) Responsibilities.

A14.2.1. **(AFGSC)** The Debrief Section will load aborts, early and late take-offs/landings, and in-flight emergency incidents in the MIS during the MIS automated debriefing process.

A14.2.2. **(AFGSC)** The MOC will review MIS debriefing and deviation reports (e.g., IMDS screens 174 and 181) to ensure accuracy of aircraft debriefing inputs. **(T-2)** MOC will also review MIS utilization and uncompleted operational event reports (e.g., IMDS screens 365 and 719) daily to ensure uncomplete sortie lines are resolved after coordination with the Debrief Section and MO PS&D. **(T-2)** MOC will also load additions, cancels before crew show, and tail swaps in MIS as deviations occur.

A14.2.3. **(AFGSC)** The wing will develop a listing for sortie sequence numbers. **(T-2)**

A14.3. (AFGSC) Flying Schedule Deviations.

A14.3.1. **(AFGSC)** Schedule deviations apply to the printed weekly flying and maintenance schedule, even when a coordinated change is accomplished using an AF Form 2407. Multiple deviations against a single line entry will not count towards FSE except for additions that result in a cancellation or additions that take-off early/late. **(T-2)**

A14.3.1.1. **(AFGSC)** The AFTO Form 781, *ARMS Aircrew Mission Flight Data Document*, is the official source document for take-off and landing data.

A14.3.1.2. **(AFGSC)** For all deviations, MOC or debriefing personnel recording the deviations in the MIS will provide a detailed explanation in the remarks section and a maintenance event ID for all maintenance cancellations, ground/air aborts, and in-flight emergencies. **(T-2)**

A14.3.2. **(AFGSC)** All deviations will be recorded with the following codes from **Table A14.1** to indicate whether the deviation is chargeable to FSE.

Table A14.1. (AFGSC) Category Codes and Functions. (T-2)

CODE	**FUNCTION**

C	Chargeable Deviations for FSE (all deviations are recorded, but not all are chargeable against FSE, **see paragraph A14.1.**
N	Non-chargeable Deviation for FSE, includes any deviation not captured in **paragraph A14.5.**

A14.4. (AFGSC) Ground Deviations. Events occurring before aircraft take-off. All ground deviations are recorded in MIS and used in FSE calculations unless otherwise noted.

A14.4.1. **(AFGSC)** When documenting ground deviations in the MIS use one of the codes in **Table A14.2**. Deviation codes are defined in the following paragraphs.

Table A14.2. (AFGSC) Ground Deviation Codes and Functions. (T-2)

CODE	**FUNCTION**
AD	Addition
CX	Cancel
ET	Early Take-off
GA	Ground Abort
LT	Late Take-off
SP	Ground Abort (Spared)
TS	Tail Number Swap

A14.4.2. **(AFGSC)** Ground Abort (GA). A ground abort is an event after crew show time preventing a "crew ready" aircraft from becoming airborne. A ground abort by itself is not a deviation from the flying schedule but can cause a deviation such as lost sortie or late take-off. Ground aborts will be recorded to the responsible agency or condition that caused the aircraft to abort. **(T-2)** Ground aborts are categorized as GAA, GAB, GAC, operations, HHQ, weather, sympathy, other, etc. For maintenance ground aborts, do not use cause code MTx, only use GAA, GAB, or GAC. For example, if an aircraft ground aborts and the sortie is not replaced by a spare, the lost sortie is a deviation towards FSE.

A14.4.2.1. **(AFGSC)** Grounds aborts for maintenance use one of the following cause codes:

A14.4.2.1.1. **(AFGSC)** GAA – Ground abort, before engine start, maintenance.

A14.4.2.1.2. **(AFGSC)** GAB – Ground abort, after engine start, before taxi, maintenance.

A14.4.2.1.3. **(AFGSC)** GAC – Ground abort, after taxi, maintenance.

A14.4.2.2. **(AFGSC)** Ground aborts on FCFs/OCFs will be included when computing FSE, unless the ground abort is related to the system being checked.

A14.4.2.3. **(AFGSC)** If the original aborted aircraft is launched on the original scheduled mission, but exceeds the 30-minute late take-off criteria, the sortie will be recorded as a late take-off.

A14.4.2.4. **(AFGSC)** If the aircraft lands, takes fuel via the hot pits, incurs an NMC condition after completion of hot pit refueling (receptacle disconnected) and can no longer continue, a ground abort is recorded.

A14.4.2.5. **(AFGSC)** A ground abort that is not spared will be included in attrition calculations as a lost/cancelled sortie.

A14.4.2.6. **(AFGSC)** Spare Ground Abort (SP). A spare is a designated aircraft on the printed schedule to be used in case a scheduled primary aircraft cannot fly its scheduled sortie. Spare aircraft can also include aircraft that are scheduled to fly in sorties later in the day, have aborted from an earlier sortie, have flown earlier or are released after FCF/OCF. If a ground aborted aircraft is replaced by a spare, and the spare can meet the mission requirements, the original aircraft will be coded as a "spare ground abort". **Note:** Do not count printed spares flown in scheduled lines as deviations when computing FSE.

A14.4.2.6.1. **(AFGSC)** If an aircraft ground aborts and is replaced by a spare, and the spare ground abort causes the sortie not to be flown; both ground aborts will be counted in the overall ground abort rate; and the lost sortie will be considered cancelled and included as the deviation in FSE. The first ground abort would not be used in computing FSE.

A14.4.3. **(AFGSC)** Addition (AD). A sortie or aircraft added to the schedule not previously printed on the weekly schedule will be recorded against the agency/cause (OP, MX, HQ, WX, etc.) **(T-2)** Sorties added to the schedule will be used in total sorties scheduled for FSE computation. **(T-2)** Aircraft added to the schedule will not be used as a part of the Total Sorties Scheduled for FSE computation; however, aircraft adds (e.g., added spares) will be captured in the FSE calculated-deviations computation. **(T-2)**

A14.4.3.1. **(AFGSC)** Functional Check Flights (FCF) or Operational Check Flights (OCF) whose primary purpose is to perform maintenance checks are not addition deviations; however, will be coordinated using the AF Form 2407. **(T-2)** FCF/OCF sorties and sorties originating off-station without home-unit support will be considered "flown as scheduled" without recording deviations. **Note:** All additions will be coordinated using the AF Form 2407 and approved **IAW Chapter 14. (T-2)**

A14.4.4. **(AFGSC)** Cancel (CX). An aircraft or sortie removed from the printed schedule for any reason prior to crew show.

A14.4.4.1. **(AFGSC)** A cancel deviation is not the same thing as a cancelled sortie. A sortie that is cancelled before crew show results in a cancel deviation. A sortie that is cancelled after crew show is a ground abort deviation. Both are cancellations with respect to the sortie line.

A14.4.5. **(AFGSC)** Early Take-off (ET). An early take-off is a scheduled sortie launching more than 30 minutes prior to the published take-off time. Exception: Do not record early take-off deviations for ERCC, hot pit, or quick turn sorties. **(T-2)**

A14.4.6. **(AFGSC)** Late Take-off (LT). A late take-off occurs when a scheduled sortie becomes airborne more than 30 minutes after the scheduled take-off time. If the printed tail number is a ground abort and is replaced with a spare that takes off late, only the late take-off is computed in FSE. Another example is an aircraft landing late and subsequently takes off late due to insufficient time to turn the aircraft; the late take-off deviation will then be recorded to the original cause of the late landing, such as operations.

A14.4.7. **(AFGSC)** Tail Swap (TS). Tail swaps are changes to the printed flying schedule involving aircraft tail numbers printed on that day's schedule. Tail swaps may be made up to crew show time. Tail swaps made after crew show are recorded as spare. Production will notify MOC of all tail swaps and MOC will record all tail swaps in MIS. **(T-2)** Do not count tail swaps as deviations when computing FSE. Below are specific examples of tail swaps:

A14.4.7.1. **(AFGSC)** Changing aircraft in printed line numbers with printed spare aircraft.

A14.4.7.2. **(AFGSC)** Changing aircraft in printed line numbers to different printed line numbers.

A14.4.6.3. **(AFGSC)** Changing aircraft in printed line numbers to any previously flown aircraft. For example, tail swaps are allowed for aircraft after release from OCF/FCF or Cross-Country (XC) return aircraft.

A14.5. (AFGSC) Air Deviations. Air deviations are events occurring after take-off. They are recorded in MIS but are not included in FSE calculations. **(T-2)** Ground deviations take precedence over air deviations.

A14.5.1. **(AFGSC)** When documenting air deviations in the MIS use one of the codes in **Table A14.3**. Deviation codes are defined in the following paragraphs.

Table A14.3. (AFGSC) Air Deviation Codes and Functions. (T-2)

CODE	**FUNCTION**
AA	Air Abort
AI	Air Abort, IFE
EL	Early Landing
FE	IFE
FI	In-flight Incident
LL	Late landing

A14.5.2. **(AFGSC)** Air Abort (AA). An air abort is an aircraft/sortie that cannot complete its mission. Air aborts will be coded to the agency or condition that caused the aborted mission. **(T-2) Note:** Effective mission decisions will be made by operations; however, a non-effective mission decision by operations does not necessarily mean an air abort occurred as defined in TO 00-20-2 *Maintenance Data Documentation*. For example, if one planned mission task out of a planned 5 tasks is not completed or operations flies an alternate mission (close air support, reconnaissance, etc.) and does not return the aircraft immediately to maintenance, the sortie should not be coded as an air abort if operations later determine, based on the original mission profile, the sortie was non-effective. The air abort rate is used as a maintenance reliability indicator and as a measure of re-work (sorties re-flown).

A14.5.3. **(AFGSC)** Air Abort, IFE (AI). An air aborted aircraft/sortie with a situation resulting in an in-flight emergency declared by the aircrew.

A14.5.4. **(AFGSC)** Early Landing (EL). An early landing is an aircraft/sortie landing more than 30 minutes before the scheduled landing time. Early landings deviations are not used when computing FSE.

A14.5.5. **(AFGSC)** IFE (FE). An aircraft/sortie with a situation resulting in an in-flight emergency declared by the aircrew after the mission is accomplished.

A14.5.6. **(AFGSC)** Late Landing (LL). A late landing is an aircraft/sortie landing more than 30 minutes after the scheduled landing time. If the sortie originated on time, record any subsequent late take-off or cancellation against the agency that caused the late landing. If the extended sortie did not originate on time, record any subsequent sortie deviation against the agency that caused the original delay. Late landings are not included in FSE calculations.

A14.6. (AFGSC) Deviation Causes. Deviations must be coordinated with the appropriate squadrons to assign a primary cause. If multiple causes exist, then the earliest cause from a sequence of events will be made the primary cause. Enter one of the codes from **Table A14.4** to indicate the primary cause for the deviation. **(T-2)**. Cause codes are defined below.

Table A14.4. (AFGSC) Cause Codes and Functions. (T-2)

CODE	FUNCTION	CODE	FUNCTION
ATx	Air Traffic	**HQT**	Higher Headquarters, MAJCOM (Non-exercise)
GAA	Ground Abort, before engine start, maintenance	**HQN**	Higher Headquarters, NAF (Non-exercise)
GAB	Ground Abort, after engine start, before taxi, maintenance	**HQP**	Higher Headquarters, other (non-exercise)
GAC	Ground Abort, after taxi, maintenance	**MTx**	Maintenance
OPx	Operations	**OTx**	Other
SUx	Supply	**SYx**	Sympathy
XUT	UTE Cancel	**WXx**	Weather
EXH	Exercise, HHQ	**EXL**	Exercise, Local
x at the end of codes may be replaced with another letter to denote locally determined variations.			

A14.6.1. **(AFGSC)** Maintenance (MTx). Deviations resulting from aircraft discrepancies, maintenance non-delivery due to no available mission capable aircraft, unscheduled maintenance, unplanned overages of scheduled maintenance, or for actions taken for maintenance consideration. Maintenance ground aborts (GA and SP) will only use the cause codes described in **paragraph A14.4.2.1**.

A14.6.2. **(AFGSC)** Operations (OPx). Deviations resulting from operations/aircrew actions, mission changes causing an early/late take-off, or cancellation including substitution/aircrew illness (including short notice aircrew physical/mental disqualification), and over-stressing the aircraft. OPx are also deviations resulting from unit-controlled operations factors including those caused by mission/load planning, life support, intelligence, base operations, range scheduling, and passengers.

A14.6.3. **(AFGSC)** Supply (SUx). Deviations resulting from a Partially Mission Capable Supply or Not Mission Capable Supply condition as well as for late Supply or POL delivery. Note: The actual time required for installation will be considered.

A14.6.4. **(AFGSC)** Higher Headquarters (HHQ). Deviations resulting from a higher headquarters tasking including closing of low-level routes/ranges or external customer-driven

mission change. When an aircraft that was scheduled for a higher headquarters directed alert or off-base mission is replaced by a spare refer to this attachment for unit options.

A14.6.5. **(AFGSC)** Weather (WXx). Deviations resulting from weather conditions such as sorties cancelled because of severe weather conditions. For example, if an aircraft taxied to the end of runway and the wing commander cancels all flying due to weather, the deviation is a weather abort. Sorties/aircraft cancelled prior to crew show are weather cancels.

A14.6.6. **(AFGSC)** Sympathy (SYx). Deviations occurring when a flight of two or more aircraft, under the command of a flight leader or instructor pilot are cancelled, aborted, or late due to a cancellation, abort, or delay of one of the aircraft in the flight or a supporting flight. Sorties, which are to replace sympathy aborts or cancellations on the same day, will be recorded as sympathy additions. Sorties lost caused by the aircraft's scheduled mated tanker/receiver/mission event will be recorded as sympathy. Note: Deviations caused by aircraft/missions from earlier scheduled lines will be assigned to the cause of the earlier deviation, not SY.

A14.6.7. **(AFGSC)** Air Traffic Control (ATx). Deviations resulting from air traffic control problems. For example, flight clearance delays, tower communication failure, conflicting air traffic, runway change, or runway closure.

A14.6.8. **(AFGSC)** Other (OTx). Deviations resulting from unusual circumstances not covered by other causes listed. OT may include:

A14.6.8.1. **(AFGSC)** Malfunctions, failures, or necessary adjustments to equipment undergoing tests or evaluations.

A14.6.8.2. **(AFGSC)** Unusual circumstances such as bird strikes, damage during air refueling, and unscheduled alert swap out.

A14.6.9. **(AFGSC)** Utilization Day (UTE). Commander's authorized management deletions **IAW** paragraph **A14.8.3** and **A14.8.4**.

A14.6.10. **(AFGSC)** Exercise, Higher Headquarters (EXH). Deviations resulting from higher headquarters directed exercises, including alarm/force protection conditions.

A14.6.11. **(AFGSC)** Exercise, Local (EXL). Deviations resulting from wing/unit directed exercises, including alarm/force protection conditions.

A14.7. (AFGSC) Deviation Considerations.

A14.7.1. **(AFGSC) Use Table A14.5.** to determine FSE Deviation reporting.

Table A14.5. (AFGSC) Common Flying Scheduling Effectiveness Deviation Determination Matrix. (T-2)

Event	Recorded in MIS?	Calculated in FSE?	Remarks
A sortie is added to the flying schedule (excluding OCFs/FCFs and XC returns).	Yes	Yes	**Paragraph A14.4.3.**

A sortie is added for an OCF/FCF.	No	No	These are considered flown as scheduled. **Paragraph A14.4.3.1.**
A sortie is cancelled.	Yes	Yes	Once the decision is made to cancel the sortie, it is a cancel. If a decision is made after the cancel to go ahead and fly the sortie, it becomes an added line. **Paragraph A11.4.4.**
A sortie is determined to be non-effective.	No	No	Not a deviation. The determination is made by operations and has no bearing on FSE. **Paragraph A14.5.2.**
A take-off is determined to be late.	Yes	Yes	**Paragraph A14.4.6.**
A take-off is determined to be early.	Yes	Yes	**Paragraph A14.4.5.**
A landing is determined to be early or late.	Yes	No	A late landing may result in a late take-off on a subsequent sortie. See paragraph **A14.4.5.** and **A14.4.6.** to determine the cause of the subsequent late take-off.
During a surge, more sorties are flown than were printed and the statement "Sortie Surge" is NOT printed in the remarks section of the affected day's flying schedule.	Yes	Yes	Sorties printed in the weekly schedule will be flown as printed. Additional sorties not printed will be considered added lines. **Paragraph A14.13.**
During a surge, more sorties are flown than were printed and the weekly schedule contains "Sortie Surge" in the remarks section of the affected day.	No	No	During planned and printed surges and combat sortie generations, additional lines are considered flown as scheduled. **Paragraph A14.13.**
During a surge, an aircraft turn sortie takes off early or late.	No	No	Units should track late take-offs of turn sorties locally during surges to prevent their reoccurrence. Late take-offs are recorded for surge first go sorties only. **Paragraph A14.4.5.** and **A14.4.6.**
Maintenance is performed during a stop in a continuation sortie and the mission continues.	Yes	Yes	An "add" is recorded for the subsequent sortie. Be sure the added line is designated as a continuation sortie to prevent further deviations for other scheduled stops. **Paragraph A14.14.**

A sortie is added to the schedule for weather attrition.	Yes	No	**Paragraph A15.2.**
A sortie is cancelled at any time due to weather.	Yes	Yes	Prior to crew show, it is a cancel. After crew show, it is a weather abort. **Paragraph A14.4.** and **A14.6.5.**
A spare aircraft printed on the flying schedule is used in a printed line.	Yes	No	Before crew show it is a tail swap, otherwise record a spare deviation. **Paragraph A14.4.**
An aircraft on the printed schedule is swapped with an aircraft in another printed line.	Yes	No	**Paragraph A14.4.7.**
An aircraft not printed on the flying schedule is used in a printed line. (Excluding aircraft already flown that day such as OCF/FCF, XC returns).	Yes	Yes	One deviation is recorded for the added aircraft and one for the tail swap or spare. The result is the same as adding an aircraft as a spare, then tail swapping it into a printed line. **Paragraph A14.4.**
An aircraft not on the printed flying schedule is added as a spare.	No	Yes	Counts as an FSE deviation even if the aircraft does not fly. MIS currently lacks the capability to capture this so MMA must manually input data. **Paragraph A14.4.2.6.**
An aircraft not printed on the flying schedule that has flown that day is flown/used in a printed line.	Yes	No	Examples include previously flown FCF/OCF aircraft as well as cross-country returns. **Paragraph A14.4.6.3.**
A ground abort is replaced with another aircraft/spare on the printed schedule.	Yes	No	Both the ground abort and spare action will be recorded in MIS. If the replacement aircraft takes off on time, no additional deviation is recorded. **Paragraph A14.4.2.6.**
A printed aircraft (original aircraft) ground aborts and is replaced with a spare, however, the spare also ground aborts, but the original aircraft is fixed and flies the sortie.	The MIS will not allow the same aircraft to have duplicate lines against the same sortie. Debrief will have to delete the original aircraft from the sequence in the MIS and only document the second aircraft's spare ground abort to the first aircraft. The spare deviation is recorded in the MIS but is not chargeable to FSE. If the sortie takes off late then record a late take-off in the MIS, chargeable to FSE. If the second aircraft is NOT on the printed schedule record an addition in the MIS to the sortie, chargeable to FSE.		

A14.8. (AFGSC) Scheduling Exceptions.

A14.8.1. **(AFGSC)** Limited Number of Possessed Aircraft. BGSs, with 40% of their possessed aircraft deployed, are authorized to schedule tail numbers daily. Units will print aircraft tail numbers in the weekly flying schedule. **(T-2)** Aircraft tail numbers may be changed at the daily maintenance production meeting using AF Form 2407 without recording deviations (sorties added or cancelled are chargeable). Immediately following the daily maintenance production meeting, the selected aircraft tail numbers for the next day's flying schedule will be entered in IMDS/MIS. **(T-2)** Aircraft tail number changes will be chargeable against FSE after being confirmed during the daily maintenance production meeting. **Note:** No additional sorties may be added under this scheduling option without addition deviation rules being applied as applicable in **paragraph A14.4**.

A14.8.2. **(AFGSC)** Adverse Weather. Units may add sorties to the flying schedule to make up for weather losses. Sorties will only be added to the schedule when the planned weather attrition for the month, prorated daily, has been exceeded for that month. The number of sorties added will not exceed the difference between the planned weather attrition and actual weather losses. See **Attachment 15** for prorated weather computations.

A14.8.3. **(AFGSC)** Achievement of Utilization. Utilization management is accomplished throughout the month. Attrition should be closely monitored and a determination to adjust the number of sorties required should be made before each weekly schedule is developed. This practice ensures an even sortie flow, eliminates excessive maintenance actions and limits the number of sorties cancelled. The OG/CC is responsible for the flying program and will coordinate with the MXG/CC to cancel sorties anytime during the month. FSE will be recorded when changing the weekly schedule. The OG/CC in coordination with MXG/CC and MSG/CC is encouraged to modify or cancel all or part of the schedule when they are reasonably assured the UTE goal for the month will be met. Sorties may be cancelled for UTE management during the last 5 O&M days of the month and will be recorded as "UTE". Sorties cancelled for UTE are not included in the FSE rate computation.

A14.8.4. **(AFGSC)** Year End Closeout. During the last 15 O&M days of the fiscal year, units are permitted to selectively cancel scheduled sorties to manage the end-of-year flying hour close-out. These cancellations will be recorded as "UTE". Sorties added to meet utilization requirements are charged to the agency responsible. (T-2) This provision is intended to help units gradually close out end-of-year flying without creating hangar queen aircraft and unintentionally exceeding the UTE. Sorties cancelled for UTE are not included in FSE rate computation. Sorties requiring munitions support should be evenly distributed throughout the fiscal year to preclude a high demand for munitions support during the month of September. Semi-annual inventories must be started and finished in March and September IAW AFMAN 21-201, *Munitions Management*.

A14.9. (AFGSC) Combat/Contingency Sortie Generation. Combat/contingency sortie generations are conducted to exercise the wing's ability to meet to the unit's combat or contingency sortie generation tasking under current war plans or contingency operations.

A14.9.1. **(AFGSC)** For scheduled combat/contingency sortie generations, publish the weekly flying schedule as a normal schedule. On the days the unit plans to exercise, annotate scheduled exercise on the flying schedule and AF Form 2402, AF Form 2403 or electronic product. If an

unannounced exercise is initiated, the remainder of the printed weekly schedule will be cancelled.

A14.9.2. **(AFGSC)** Combat sortie generation will include operations using ATOs. **See paragraph A14.10** for procedures.

A14.9.3. **(AFGSC)** When a scramble launch scenario is used, a launch "window" will be established for each line number or block of line numbers. Normal deviations will be assessed against all sorties.

A14.9.4. **(AFGSC)** Sorties lost due to required scenario responses such as chemical warfare condition “black,” airfield attacks, etc., will be recorded as "EXH or EXL."

A14.9.5. **(AFGSC)** If more sorties are flown than line numbers printed, those sorties will be considered flown as scheduled.

A14.9.6. **(AFGSC)** Once the objectives established by higher headquarters or the commander have been met, the remainder of that day's schedule will be cancelled in the MIS.

A14.9.7. **(AFGSC)** At the termination of the combat sortie generation, the units originally printed weekly flying schedule may be revised, cancelled, or replaced with a new weekly schedule without recording deviations. Normal deviation reporting procedures will apply once they are finalized.

A14.10. (AFGSC) Air Tasking Order. The Air Tasking Order (ATO) can contain mission numbers, on-status time/time on target and configurations. A daily flying schedule, including aircraft tail numbers for the first lines and spares, will be finalized and confirmed to operations and the MOC no later than 2 hours prior to the first on-status/take-off time. **(T-2)** The new published schedule derived from the ATO is applicable to all affected organizations and no AF Form 2407 is required to implement the new schedule. All changes after the new schedule have been published, up to the first unit crew show time, will be documented and coordinated on an AF Form 2407. **(T-2)** Unlike a planned sortie surge, early and late take-offs are recorded on second and subsequent sorties, unless an operations change is made to the ATO. Normal deviations will be recorded against all sorties using the new published schedule derived from the ATO. **(T-2) Note:** All sorties launched under “Classified ATOs” will be considered flown as scheduled. Classified ATO lines that are missed will be recorded as cancels in the MIS. **(T-2)** Cancellations will be loaded into the MIS once the sortie is declared cancelled regardless of actual scheduled take-off time and ground aborts will be recorded in the MIS. **(T-2)**

A14.10.1. **(AFGSC) Alert Sorties.** Sorties flown from alert because of a higher headquarters exercise, active air or practice scramble, or committed to fly from alert on the printed weekly schedule will be considered sorties flown as scheduled. **(T-2)** Ground aborts will be recorded in the MIS; however, no deviation is recorded against FSE. **(T-2) Note:** Alert sorties are considered unscheduled and will not be entered as a scheduled event in the MIS. These sorties (take-off/land times) will be entered into the MIS during the debrief process.

A14.11. (AFGSC) Unscheduled Tasking. When a unit is tasked with an unscheduled higher headquarters tasking, self-initiated tasking (mobility exercises or weather evacuations), or other services tasking which significantly impacts the printed weekly flying schedule, MO PS&D may revise or delete the printed schedule from the MIS and replace with a new weekly schedule without

recording any deviations. For weather evacuations, the schedule will be cancelled in the MIS, not deleted, so the data is available for historical attrition.

A14.11.1. **(AFGSC)** If the schedule is revised or cancelled/reprinted, the following procedures will be used:

A14.11.1.1. **(AFGSC)** The revised schedule will be finalized a minimum of 2 hours before the first scheduled take-off**. (T-2)**

A14.11.1.2. **(AFGSC)** Once the tasking terminates, the original schedule may be used or it may be revised/reprinted for the tasking period. Normal deviation reporting is used once the revised/reprinted schedule is finalized. **(T-2)**

A14.11.1.3. **(AFGSC)** Normal deviation reporting procedures will be followed after a take-off time is established to a tasking by higher headquarters or other services.

A14.11.2. **(AFGSC)** If the unscheduled tasking has an adverse impact on the monthly UTE goal, the commander has the option to adjust the monthly sortie UTE goal.

A14.11.3. **(AFGSC)** An unscheduled tasking or actual combat operations may include use of an ATO. Deviations for all aircraft will be recorded IAW this instruction.

A14.13. (AFGSC) Planned Sortie Surge.

A14.13.1. **(AFGSC)** Units may plan to produce sorties at a higher-than-normal rate. A unit may also use a planned sortie surge when the rest of the unit is deployed to a different location. A planned sortie surge is not considered a combat sortie generation or an unscheduled tasking. The number of sorties will be determined by training objectives and established by the OS Director of Operations and BGS Supervision. Printed sortie surge rates will exceed the daily sortie rate (average contracted sortie per O&M Day based on the applicable monthly sortie/flying hour contract) of the unit by at least 50%, but not less than the contract required sorties scheduled on the monthly contract/plan. For example, if a unit normally flies 6 sorties in a day, to qualify for a surge, that same unit would schedule at least 9 sorties for the surge day. The statement "Sortie Surge" must be printed in the remarks section of the affected day's flying schedule to add sorties without incurring deviations.

A14.13.1.1. **(AFGSC)** Aircraft tail numbers, take-off times, land times, line numbers, and configurations will be printed on the weekly schedule for each aircraft's first sorties of each day. **(T-2)** Include the statement "sortie surge" in the remarks section for each affected day. Only line numbers are required on the weekly schedule for subsequent sorties (i.e., the total number of sorties/line numbers the unit intends to fly). **(T-2)** Other data such as take-off times, configurations, and missions may be printed as required by the unit.

A14.13.1.3. **(AFGSC)** Units will confirm subsequent sorties NLT the daily maintenance production meeting on the day prior. **(T-2)**

A14.13.1.4. **(AFGSC)** Early and late take-offs are not recorded on second and subsequent sorties. For all other deviations, normal deviation reporting applies.

A14.13.1.5. **(AFGSC)** If more sorties are flown than what was intended (e.g., line numbers printed), these sorties will be considered flown as scheduled.

A14.14. (AFGSC) Continuation Sortie. A continuation sortie is a sortie containing scheduled operations stops. This scheduling option is intended to allow the exchange of aircrew while the

aircraft engines/Auxiliary Power Unit (APU) remains running. Aircraft possession does not return to maintenance; therefore, maintenance support is limited to chocking the aircraft and fire/safety observer. **Exception:** On B-52 aircraft, engines may be shut down to re-pack drag chutes while crew change occurs. The UH-1/MH-139 aircraft do not have an APU, therefore engine shutdown is allowed during a continuation sortie. All other requirements in this paragraph apply. **Note:** Returning the aircraft to maintenance terminates the continuation sortie. Continuation sorties will be clearly identified in the published weekly flying schedule. **(T-2)** The initial crew on the sortie will brief the follow-on crew at the aircraft. **(T-2)** A continuation sortie ends when the later mod is debriefed since both are assigned the same sortie number. Units may add continuation mods onto scheduled sorties to make up for sorties lost earlier in the same week without recording deviations. Do not include these added continuation mods in FSE unless there were no lost sorties earlier in the week. If no sorties were lost in the same week, the added continuation mod will be an "add" deviation in FSE. **(T-2)**

A14.15. (AFGSC) Engine Running Crew Change (ERCC). The ERCC sortie is used to optimize aircraft use. It involves the turnaround of an aircraft incorporating partial or full crew change between two separate sorties. The difference between ERCC and continuation sorties is minor maintenance, and servicing can be performed between sorties and since each is a separate sortie, deviations apply to each sortie. Aircraft scheduled to fly an ERCC sortie will be published in the weekly schedule. Upon landing, aircrew members are exchanged at the aircraft with at least one engine running. **Exception:** On B-52 aircraft, engines may be shutdown to re-pack drag chutes while crew change occurs. Minimum ground time should be scheduled between sorties. The aircrew of the first sortie must brief the aircrew of the second sortie at the aircraft. **(T-2)** Other aircraft on the published flying schedule or previously flown aircraft not on the flying schedule (OCF, FCF, adds) can be tail swapped into the second sortie. For example, if two aircraft are scheduled to land at approximately the same time, either aircraft could ERCC to the later sortie.

A14.16. (AFGSC) Overall FSE Rate. This leading indicator is a measure of how well the unit planned and executed the weekly flying schedule. Deviations that decrease the FSE from 100% include: scheduled sorties not flown because of maintenance, supply, operation adds, deletes, and ground aborts; scheduled sorties that take-off more than 30 minutes prior to scheduled take-off; and scheduled sorties that take-off more than 30 minutes after their scheduled take-off time. Disruptions to the flying schedule can cause turmoil on the flight line, sending a ripple effect throughout other agencies, and adversely impact scheduled maintenance actions.

A14.16.1. **(AFGSC)** Maintenance/Operations FSE Rate. Also referred to as the O&M or maintenance/operations rate, this leading indicator is a subset of FSE that focuses on only the effects of maintenance and operations in executing the weekly flying schedule. The chargeable deviations that increase the maintenance/operations rate from 0% are the same that reduce FSE, however, only the maintenance, maintenance ground abort, and operations cause codes for **Table 14.4** are used.

A14.16.2. **(AFGSC)** Compute monthly flying scheduling effectiveness rates by aircraft mission and design using the formulas in **Table A14.6**.

Table A14.6. (AFGSC) Flying Scheduling Effectiveness Computations.

Flying Scheduling Effectiveness Computations

Total sorties scheduled = Total sorties flown + cancellations (GA and CX deviations) – Additions (added sorties only).
Adjusted sorties scheduled = Sum of total sorties scheduled (home base, off station or deployed) – UTE cancellations.
Calculated deviations = Sum of all deviations (including added aircraft) – [air deviations, tail swaps, printed spare actions, late and early lands, ground aborted sorties flown by spare aircraft (on-time), and UTE cancellations/additions].
OP/MX deviations = Sum of all calculated deviations recorded using OPx or MTx as the deviation cause code (include GAA, GAB and GAC).
Overall FSE rate = Adjusted sorties scheduled – calculated deviations / adjusted sorties scheduled × 100.
Maintenance/Operations FSE rate = OP+MX deviations / adjusted sorties scheduled × 100.

Attachment 15 (Added-AFGSC)

ATTRITION AND SPARE FACTOR

A15.1. (AFGSC) Attrition. Attrition represents a historical percentage of scheduled sorties lost. Maintenance and operations schedulers will add attrition sorties to monthly contracts to ensure mission goals are met. Units will request HQ AFGSC/A4M approval before using different attrition factors from statistical attrition rates calculated by MO MMA. **(T-2)**

A15.1.1. **(AFGSC)** Attrition sorties are not substitutes for unit capability shortfalls; they are added to the contract to mitigate scheduling turbulence to ensure that mission goals are met. The monthly flying and maintenance plan will clearly identify attrition sorties for planning purposes. If attrition is less or more than planned, adjustments to the weekly flying and maintenance schedule will be made to prevent over-extending maintenance or exceeding the unit's contract. A programmed sortie lost will normally be flown in the same month the loss occurred. If at the end of a quarter combined losses exceed attrition figures, the OG and MXG/CCs will negotiate a resolution to the shortfall.

A15.1.2. **(AFGSC)** Attrition will be computed for and applied to each flying squadron. Monthly statistical attrition anomalies should be identified, documented and factored out of attrition calculations, if necessary. BGS and squadron analysts will compute attrition factors monthly for their flying squadron and provide results to the BGS and flying squadron schedulers. MO MMA will compile attrition factors from squadron analysts and provide the results to MO PS&D and OG or OSS flight schedulers. During the annual Flying Hour Program Coordination MO MMA will provide attrition factors by month for the entire next fiscal year to MO PS&D and the OG.

A15.1.3. **(AFGSC)** Attrition Factor Computation. The attrition factor will be calculated based on no less than 4 years of similar flying months. Exclude months that have significant outliers. If 4 years of data does not exist, then the unit will data for the same weapon system in a similar location or will use the data that is available until 4 years is achievable.

A15.1.3.1. **(AFGSC)** The formula that will be used for the attrition factor is total historical sorties lost divided by total historical sorties scheduled. Total sorties scheduled will use the same formula found in **Attachment 14**. Sorties lost will include both cancels (CX) and unspared ground abort (GA) deviations. The attrition factor itself is commonly presented as either a percentage or decimal.

A15.1.3.2. **(AFGSC)** Total attrition used for calculating attrition sorties will include losses for MTx/GAx, OPx, SUx, WXx, ATx, SYx, OTx, EXH/EXL, and HQx. Weather attrition used for prorated weather additions will only include losses for WXx. Maintenance attrition used to measure the impact of maintenance impacts to the flying schedule will include only losses for MTx, GAA, GAB, or GAC. Other variation of attrition may be used for local use.

A15.1.4. **(AFGSC) Attrition Factor Application.** Examples for computing and using the attrition can be found in **Table A15.1** and **Table A15.2**.

A15.1.4.1. **(AFGSC) Table A15.1.** shows 4 years of scheduled sorties and losses. To calculate the total attrition factor, take the sum of the historical losses (10+8+4+8=30) and

divide by the historical sorties scheduled (67+63+57+63=250). The total attrition factor then 30/250 = 0.12 or 12%. The weather attrition is 8 divided by 250, or 3.2%.

A15.1.4.1. **(AFGSC) Table A15.2.** shows an example for using the attrition calculated in **A15.1.4.1** to determine the number of attrition sorties needed to meet mission requirements. In the scenario to meet the 238-sortie requirement with a 12% total attrition factor the unit will need to schedule an additional 33 attrition sorties.

Table A15.1. (AFGSC) Attrition Computation Example.

JULY	2021	2022	2023	2024	Total
Total Sorties Scheduled	67	63	57	63	250
Maintenance Losses	3	2	2	3	10
Weather Losses	1	2	3	2	8
Operations Losses	1	2	1	0	4
Sympathy Losses	3	2	2	1	8

Table A15.2. (AFGSC) Sample Application of Calculating Total Attrition Sorties.

Sample Application of Calculating Total Attrition Sorties	
Sorties Required	238
Subtract attrition factor from 1:	(1 - 0.12) = 0.88
Divide 238 by 0.88	
Required sorties to schedule 270.45, round up to 271.	
Based on historical attrition of 12%, the unit can expect to lose 33 sorties to meet the required 238 sorties.	

A15.2. (AFGSC) Prorated Weather Additions. Prorated weather adds are tool for units when the number of sorties lost in a month due to weather exceeds what was projected using weather attrition. Weather attrition sorties will not be carried over into another month. BGS and squadron analysts will evaluate the month's weather attrition daily and inform production when weather attrition sorties become available.

A15.2.1. **(AFGSC)** From the example in **Table A15.3**, a unit would expect 0.35 sorties lost each O&M Day in the month for weather. Thus, a total of 7 sortie losses (0.35 sorties x 20 O&M days) is expected for that month. Whenever weather losses exceed the total projected weather losses (number of O&M days to date x 0.35, round up to the next whole number), a unit may add sorties not to exceed the difference between the sorties lost due to weather and the total projected weather losses. For example, on the 11th O&M Day of the month, a unit

lost a total of 14 sorties to date due to the weather. The expected prorated weather sorties lost to-date is 4 (0.35 times 11 equal 3.85, round up). The unit also added 2 weather sorties earlier in the month. The unit could add up to 8 sorties (14 sorties lost to date due to weather minus 4 prorated losses minus 2 weather adds equals 8 weather adds available).

Table A15.3. (AFGSC) Sample Application of Prorated Weather Attrition Factor.

Sample Application of Prorated Weather Attrition Factor	
Sorties Required	238
Subtract the weather attrition factor from 1	(1-0.032) = 0.968
Divide 1000 by 0.97	238/0.968
Equals Required Sorties to Schedule	246
Minus Sorties Required	246-238
Expected Weather Losses	7
Divide 31 by O&M Days (20 for this exercise)	31/20
Expected Sortie Losses per O&M Day	0.35

A15.3. (AFGSC) Spare Requirement. The spare requirements will not exceed 50 percent of aircraft committed to the flying schedule, rounded up to the next whole aircraft. **Note:** During planned sortie surges, the MXG/CC determines the number of spares that will be committed. Units should be cognizant of their historical break rates and spare constraints when scheduling surges. Spares are used quickly during surges and once spares are exhausted the capability to meet surge goals is severely limited. **(T-2)**

A15.3.1. **(AFGSC)** MO MMA computes annual spare aircraft requirements by month, using historical aircraft first sortie losses for maintenance and supply and provides this information to the MO PS&D for use in computing spare aircraft requirements. Spare computation is based on unit historical data from previous similar flying months using 4 years of data while excluding outlier months. For example, when computing spares for Jan 25, use historical data for Jan 24, Jan 23, Jan 22, and Jan 21. The formula for computing spare factor is Historical First Sortie Cancellations (CX + GA) divided by historical first sorties scheduled. See **Table A15.4**.

A15.3.1.1. **(AFGSC)** A first sortie is defined as a sortie flown by an aircraft that has not previously flown for the day (flying period between 0001-2400). For example, if 4 aircraft are committed to the schedule and there are 6 total sorties scheduled, the first 4 sortie line numbers (e.g., 101-104) should reflect all 4 committed aircraft tail numbers before they are re-scheduled (turned) against the last 2 (e.g., 105-106).

A15.3.1.1.1. **(AFGSC)** Operations may define first sorties or turns by mission profile and take-off times, but for the purposes of this instruction the sortie turn pattern is

defined against initial aircraft flown and scheduled turns of the same or a portion of the same aircraft.

A15.3.2. **(AFGSC)** The computed spare requirement may be adjusted to compensate for multiple configurations and syllabus constraints. When additional spares are added for multiple configurations, units will not exceed one spare per configuration.

A15.3.2.1. **(AFGSC)** Additional spares are authorized to support higher headquarters tasks and special missions (if required by the tasking).

A15.3.2.2. **(AFGSC)** At least one spare aircraft is authorized per MDS for each flying day.

A15.3.3. **(AFGSC) Spare Factor Application.** Examples for computing and using attrition can be found in **Table A15.4** and **Table A15.5**.

A15.3.3.1. **(AFGSC) Table A15.4.** shows 4 years of first sorties and first sortie losses across 4 years. To calculate the spare factor for July 2025, take the sum of the losses and divide by total sorties scheduled or 15 (6+5+4) divided by 131 which results in a spare factor of 0.115 or 11.5%

A15.3.3.2. **(AFGSC) Table A15.5.** shows how to derive the number of spare aircraft required using the spare factor. In the scenario 6 first sorties are scheduled. Multiplying this by an 11.5% spare factor results in 0.69, or when rounded up leaves a requirement for 1 spare aircraft.

Table A15.4. (AFGSC) Sample Computation of Spare Factors.

JULY	2021	2022	2023	2024	Total
Total 1st Sorties Scheduled	32	34	32	33	131
Maintenance CXs	2	1	1	2	6
Maintenance GAs	1	1	2	1	5
Supply CXs	1	2	1	0	4

Table A15.5. (AFGSC) Sample Application of Spare Factor.

Sample Application of Spare Factor	
First Sorties Scheduled	6
Compute Spare Factor	(6+5+4) / 131 = 11.5%
Multiply Spare Factor by First Sorties Scheduled, round up	6*.115 = 0.69, rounded to 1
Required spare aircraft	1

Attachment 16 (Added-AFGSC)

A4 EXECUTIVE REPORTING PROCEDURES

A16.1. (AFGSC) Monthly Reporting. Executive reporting consists of two products: the A4 Executive Summary and the A4 Executive Workbook. Both reports are required to be submitted by aircraft units to the AFGSC/A4 each month. Requirements for any non-aircraft weapon system will be identified by the applicable AFGSC/A4 division. The OPR for the overall executive reporting process is the AFGSC/A4MQ Analysis Team which can be contacted for assistance via DSN or email: **AFGSC.A4M.Workflow@us.af.mil**.

A16.2. (AFGSC) Responsibility. Wing, maintenance groups, and subordinate commanders are responsible for ensuring compliance with the procedures outlined in this attachment. Commanders are responsible for the accuracy of data required by this instruction and take action to improve deficiencies. At a minimum, the MXO SEL, or equivalent, will have overall responsibility for ensuring both reports are properly filled out prior to submission to HQ AFGSC. The preparing agency and wing OPR for report submission will be the maintenance management analysis section, or analysis team if consolidated with another section.

A16.3. (AFGSC) Report Transmission. A4 Executive Reports must be uploaded to the HQ AFGSC/A4MQ Maintenance Analysis SharePoint site (**https://usaf.dps.mil/sites/AFGSC-HQ/hq/A4/a4m/a4bx/mma/alx**) under the respective wing or weapon system document library. Upload the reports into the corresponding Year and Month folder in the library.

A16.3.1. **(AFGSC)** If for any reason the SharePoint is unavailable the reports will be emailed to the AFGSC/A4M Workflow: **AFGSC.A4M.Workflow@us.af.mil**.

A16.4. (AFGSC) A4 Executive Summary Report. The purpose of the A4 Executive Summary is to provide Weapon System Teams and AFGSC leadership with a summary of current initiatives and efforts, areas requiring assistance, and items impacting fleet health and readiness. Aircraft Wings will submit one Executive Summary for each MDS under their control regardless of the number of subordinate units. Requirements for non-aircraft weapon systems will be identified by the applicable AFGSC/A4 division.

A16.4.1. **(AFGSC)** Frequency of Reporting. The A4 Executive Summary is submitted to the AFGSC/A4 monthly. Upload the document to the AFGSC/A4MQ Analysis SharePoint IAW **paragraph A16.3**. NLT 1400 CST on the 10th calendar day following the month being reported. AFGSC/A4MQ is the authorizing authority for any extensions. Exercises, down-days, and inspections are not valid reasons for late submittals.

A16.4.2. **(AFGSC)** Report Template. The A4 Executive Summary templates can be found on the AFGSC/A4MQ Analysis SharePoint under a Templates button. Templates will include "Executive Summary Template" in the document's name. Wings will not modify templates. If changes are required, contact the AFGSC/A4MQ Analysis Team who will route the changes through the applicable AFGSC/A4 division.

A16.4.3. **(AFGSC)** Classified Reporting. Certain weapon systems require Executive Summary inputs to be classified. Classified Executive Summary reports or an addendum to the unclassified report will be submitted through Microsoft Teams on SIPR using the same frequency as the unclassified reports. AFGSC/A4MQ can be contacted to get access to the Teams site.

A16.5. (AFGSC) A4 Executive Workbook. Aircraft wings will submit one workbook summarizing data for each MDS under their scope of responsibility regardless of the number of subordinate units. Requirements for non-aircraft weapon systems will be identified by the applicable AFGSC/A4 division.

A16.5.1. **(AFGSC)** Frequency of Reporting. The A4 Executive Workbook is submitted to the AFGSC/A4 Branch monthly. Upload the Executive Workbook Excel to the AFGSC/A4MQ Analysis SharePoint IAW **paragraph A16.3**. NLT 1400 CST on the 8th calendar day following the month being reported. AFGSC/A4MQ is the authorizing agency for any extensions. Exercises, down-days, and inspections are not valid reasons for late submittals.

A16.5.2. **(AFGSC)** Report Template. Workbook templates can be found on the AFGSC/A4MQ Analysis SharePoint. Aircraft templates will include "000000-0901-MMM-YYYY" in their name. Wing-specific templates will be identified by the Wing's designation replacing the "000000" in the name (e.g., 2nd Bomb Wing would be 0002BW). Weapon system specific templates will identify the weapon system. All other weapon systems will have templates established by the relevant AFGSC/A4 division. Wings will not modify templates. If changes are required, contact the AFGSC/A4MQ Analysis Team who will route the changes through the applicable AFGSC/A4 division.

A16.6. (AFGSC) Coordination and Correction Procedures. After the A4 Executive Reports have been uploaded to the AFGSC/A4MQ Analysis SharePoint site any corrections to reports must be submitted via the same SharePoint with a notification email sent to AFGSC/A4MQ Analysis (**AFGSC.A4M.Workflow@us.af.mil**) with reference to the original reported data as well as the corrected data. A master file of monthly reports will be maintained for the current and previous fiscal years. If there are any reporting errors identified after the reports are provided to HQ AFGSC/A4, AFGSC/A4MQ will contact the unit OPR who will notify the appropriate base agency to correct the erroneous data in the MIS.

Attachment 17 (Added-AFGSC)

MAINTENANCE RISK MANAGEMENT (MRM) ASSESSMENT

Table 17.1. (AFGSC) Maintenance Risk Management (MRM) Assessment.

Maintenance Risk Management (MRM) Assessment
NOTE: This form does NOT grant waiver authority for regulatory guidance. Risks identified below do not allow for the violation of prescribed regulations and waivers must be approved at the appropriate authority level. This Maintenance Risk Management (MRM) Assessment is mandatory prior to elevated risk task operations as prescribed by the implementation guidance. Further use of this form is at the discretion of the applicable MXG/CC or equivalent.
INSTRUCTIONS:
The MRM assessment is intended to be a conversation between Team Supervisor and Team Members to help identify and mitigate risks. Complete MRM Assessment prior to the tasks. The Team Supervisor will brief all identified risk factors, and focus on how risks will be mitigated.
Personnel Factors
1. Are all team members current and qualified to perform the task?
a. If "**Yes**", **GO**
b. If "**No**", will a qualified trainer be supervising the non-current/qualified personnel?
i. If "**Yes**", **GO** - If "**No**", **NOGO**
2. Is Training being conducted during task?
a. If "**No**", **GO**
b. If "**Yes**", will a qualified trainer be supervising the trainee during the task?
i. If "**Yes**", **GO - If "No", NOGO**
3. Have all members of the team had enough rest to safely perform the task? (Consider things like recent shift changes within 72 hours and consecutive workdays)
a. If "**Yes**", **GO - If "No", NOGO**
4. Are there any concerns about your team members? (e.g., Experience Level, Qualifications, Physical or Mental Fitness)?
a. If "No", **GO**
b. If "Yes", can the risk factors be mitigated?
i. If "Yes" **GO - If "No", NOGO**
Tasks Factors
1. Do you have the required quantity of personnel to conduct the task as defined by Technical Data?
a. If "**Yes**", **GO - If "No", NOGO**
2. Are there any concerns from any team members about the task to be performed? (e.g. Support Equipment Serviceability, Unusual Configuration not captured in T.O, T.O. Accuracy/Suitability)
a. If "**No**", **GO**
b. If "**Yes**", are the appropriate Tactics, Techniques, Procedures (TTP's) sufficient to mitigate the risks associated with the concerns?
i. If "**Yes**", **GO - If "No", NOGO**

Maintenance Risk Management (MRM) Assessment
3. Do all team members have sufficient task experience to deal with all associated complexities?
a. If "**Yes**", **GO - If "No", NOGO**
4. Are all applicable Tools, Equipment, Materials available for use per Technical Data/Instructions?
a. If "**Yes**", **GO - If "No", NOGO**
Environmental Factors
1. Will concurrent maintenance actions be in the immediate work area?
a. If "**No**", **GO**
b. If "**Yes**", are appropriate steps to mitigate associated hazards being conducted?
i. If "**Yes**", **GO - If "No", NOGO**
2. Is the current weather (Temperature/Winds/Precipitation) and lighting (Night/Poor Illumination) providing additional hazards to the situation?
a. If "**No**", **GO**
b. If "**Yes**", are appropriate TTP's sufficient to mitigate the hazards?
i. If "**Yes**", **GO - If "No", NOGO**
DECISION
If ANY answer leads to "**NOGO**", **STOP!** Do NOT continue with task. If risk factors can be mitigated, inform Leadership or Production prior to task performance. If they cannot be mitigated, inform Leadership to make the appropriate final determination.
Completed By: **Date:** **Task Performed:**