# Car Connectivity Consortium MirrorLink™

# **Network Information Data Service**

Version 1.2.0 (CCC-TS-052)



Copyright © 2011-2013 Car Connectivity Consortium LLC

All rights reserved

Confidential


# **VERSION HISTORY**

2

Version	Date	Comment
1.2.0	25 September 2013	Approved Version

# LIST OF CONTRIBUTORS

4	Brakensiek, Jörg	Nokia Corporation
5	Kim, Jungwoo	LG Electronics
6	Kim, Mingoo (Editor)	LG Electronics



#### LEGAL NOTICE

1

- The copyright in this Specification is owned by the Car Connectivity Consortium LLC ("CCC LLC"), Use 2
- 3 of this Specification and any related intellectual property (collectively, the "Specification"), is governed
- 4 by these license terms and the CCC LLC Limited Liability Company Agreement (the "Agreement").
- 5 Use of the Specification by anyone who is not a member of CCC LLC (each such person or party, a
- "Member") is prohibited. The legal rights and obligations of each Member are governed by the Agree-6
- ment and their applicable Membership Agreement, including without limitation those contained in Arti-7
- 8 cle 10 of the LLC Agreement.
- 9 CCC LLC hereby grants each Member a right to use and to make verbatim copies of the Specification
- 10 for the purposes of implementing the technologies specified in the Specification to their products ("Im-
- plementing Products") under the terms of the Agreement (the "Purpose"). Members are not permitted 11
- 12 to make available or distribute this Specification or any copies thereof to non-Members other than to
- 13 their Affiliates (as defined in the Agreement) and subcontractors but only to the extent that such Affili-
- 14 ates and subcontractors have a need to know for carrying out the Purpose and provided that such Affil-
- 15 iates and subcontractors accept confidentiality obligations similar to those contained in the Agreement.
- 16 Each Member shall be responsible for the observance and proper performance by such of its Affiliates
- and subcontractors of the terms and conditions of this Legal Notice and the Agreement. No other li-17
- cense, express or implied, by estoppel or otherwise, to any intellectual property rights are granted 18
- 19 herein.
- 20 Any use of the Specification not in compliance with the terms of this Legal Notice, the Agreement and
- 21 Membership Agreement is prohibited and any such prohibited use may result in termination of the ap-
- 22 plicable Membership Agreement and other liability permitted by the applicable Agreement or by appli-
- 23 cable law to CCC LLC or any of its members for patent, copyright and/or trademark infringement.
- THE SPECIFICATION IS PROVIDED "AS IS" WITH NO WARRANTIES. EXPRESS OR IMPLIED. 24
- 25 INCLUDING WITHOUT LIMITATION ANY WARRANTY OF MERCHANTABILITY. FITNESS FOR A
- 26 PARTICULAR PURPOSE, NONINFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL
- 27 PROPERTY RIGHTS. AND COMPLIANCE WITH APPLICABLE LAWS.
- 28 Each Member hereby acknowledges that its Implementing Products may be subject to various regula-
- 29 tory controls under the laws and regulations of various jurisdictions worldwide. Such laws and regulato-
- 30 ry controls may govern, among other things, the combination, operation, use, implementation and dis-
- 31 tribution of Implementing Products. Examples of such laws and regulatory controls include, but are not
- 32 limited to, road safety regulations, telecommunications regulations, technology transfer controls and 33
- health and safety regulations. Each Member is solely responsible for the compliance by their Imple-
- 34 menting Products with any such laws and regulations and for obtaining any and all required authoriza-
- 35 tions, permits, or licenses for their Implementing Products related to such regulations within the appli-
- 36 cable jurisdictions.
- 37 Each Member acknowledges that nothing in the Specification provides any information or assistance in
- 38 connection with securing such compliance, authorizations or licenses.
- 39 NOTHING IN THE SPECIFICATION CREATES ANY WARRANTIES, EITHER EXPRESS OR
- 40 IMPLIED, REGARDING SUCH LAWS OR REGULATIONS. ALL LIABILITY, INCLUDING LIABILITY
- 41 FOR INFRINGEMENT OF ANY INTELLECTUAL PROPERTYRIGHTS OR FOR NONCOMPLIANCE WITH LAWS, RELATING TO USE OF THE SPECIFICATION IS EXPRESSLY DISCLAIMED. BY 42
- USE OF THE SPECIFICATION, EACH MEMBER EXPRESSLY WAIVES ANY CLAIM AGAINST 43
- CCC LLC AND ITS MEMBERS RELATED TO USE OF THE SPECIFICATION. 44
- 45 CCC LLC reserve the right to adopt any changes or alterations to the Specification as it deems neces-
- 46 sary or appropriate.
- 47 Copyright © 2011-2013. CCC LLC.

# **TABLE OF CONTENTS**

2	VEF	RSION HISTORY	2
3	LIS	T OF CONTRIBUTORS	2
4	LEG	GAL NOTICE	3
5		BLE OF CONTENTS	
6		RMS AND ABBREVIATIONS	
7		ABOUT	
		INTRODUCTION	
9		NETWORKINFO OBJECT	
10	_		
11		REFERENCES	
	_		

18

# TERMS AND ABBREVIATIONS

2	AP	Access Point
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16	MirrorLink is a t	rademark of the Car Connectivity Consortium LLC.
17	UPnP is a registe	ered trademark of UPnP Implementers Corporation.

Other names or abbreviations used in this document may be trademarks of their respective owners.

#### 1 ABOUT

- 2 This document specifies Network Information Data Service based on SBP (Service Binary Protocol)
- 3 framework [3]. The service is used to provide network capabilities and status information of Access Point
- 4 to Client.
- 5

14

15

16

17

18

19 20

21 22

23 24

25

26

27

28

29

30

- The specification lists a series of requirements, either explicitly or within the text, which are mandatory el-
- 7 ements for a compliant solutions. Recommendations are given, to ensure optimal usage and to provide suit-
- 8 able performance. All recommendations are optional.
- 9 The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD",
- 10 "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are following the
- notation as described in RFC 2119 [1].
- 12 1. MUST: This word, or the terms "REQUIRED" or "SHALL", mean that the definition is an absolute requirement of the specification.
  - 2. MUST NOT: This phrase, or the phrase "SHALL NOT", mean that the definition is an absolute prohibition of the specification.
  - 3. SHOULD: This word, or the adjective "RECOMMENDED", mean that there may exist valid reasons in particular circumstances to ignore a particular item, but the full implications must be understood and carefully weighed before choosing a different course.
  - 4. SHOULD NOT: This phrase, or the phrase "NOT RECOMMENDED" mean that there may exist valid reasons in particular circumstances when the particular behavior is acceptable or even useful, but the full implications should be understood and the case carefully weighed before implementing any behavior described with this label.
  - 5. MAY: This word, or the adjective "OPTIONAL", means that an item is truly optional. One vendor may choose to include the item because a particular marketplace requires it or because the vendor feels that it enhances the product while another vendor may omit the same item. An implementation which does not include a particular option MUST be prepared to interoperate with another implementation which does include the option, though perhaps with reduced functionality. In the same vein an implementation which does include a particular option MUST be prepared to interoperate with another implementation which does not include the option (except, of course, for the feature the option provides.)

#### 2 Introduction

- 2 The purpose of Network Information service is to provide network capabilities and status of the Access
- 3 Point to Client.

1

13

17

18

19

20 21

- 4 When MirrorLink Server and Client are connected though Wi-Fi technology of Wi-Fi Alliance, both the
- 5 ML Server and the Client can be either an Access Point (AP) or Client. In-vehicle setting, it is important for
- 6 Client to know network status information of the AP, as network delay on AP may cause poor response
- 7 time of applications requiring Internet connectivity on Client. MirrorLink Client can select the "best" net-
- 8 work interface to be used for the Internet access with regard to network capabilities and the status infor-
- 9 mation of AP. The algorithm for a selection of the network interface for the Internet access on Client is out
- 10 of scope of this document. Wi-Fi connection established between the ML Server and the Client MUST be
- 11 maintained while the Client configures its network interfaces to access the Internet.
- 12 The following code shows the definition of service:

```
/* com.mirrorlink.networkinfo service, v1.0 */
/** NetworkSupport Object carrying network capabilities of Access Point
    @mandatory
    @UID: to be calculated */
Object NetworkSupport {
    LONG supportedNetworkType; /// @UID: to be calculated
};
/** NetworkStatus Object carrying current network status of Access Point
    @mandatory
    @UID: to be calculated */
Object NetworkStatus {
                                /// @UID: to be calculated
   LONG activeNetworkType;
                                /// @UID: to be calculated
    BYTE connectivityStatus;
                                /// @UID: to be calculated
    INT signalStrength;
};
/** DataBalanceStatus Object carrying current data balance status of
    Access Point
    @optional
    @UID: to be calculated */
Object DataBalanceStatus {
                                /// @UID: to be calculated
    BOOL dataRoamingStatus;
    LONG mobileDataLimit;
                                /// @UID: to be calculated
    LONG mobileDataUsage;
                                /// @UID: to be calculated
};
```

- This service uses the name of "com.mirrorlink.networkinfo" to uniquely identify this service on CDB layer [2].
- 16 The service is composed of following Objects:
  - **NetworkInfo Object**: This is a network type that Access Point supports. Supporting of this Object is mandatory.
  - **NetworkStatus Object**: This Object allows accessing current network status of the Access Point. This Object MUST be supported.
  - **DataBalanceStatus Object**: This Object provides current data balance status of the Access Point. Supporting this Object is optional.

### 3 NETWORKINFO OBJECT

- 2 NetworkSupport Object returns network types that Access Point supports.
- 3 Following table gives further explanation about member variables defined:

Name	Data type	Description
supportedNetworkType	LONG	Bit wise OR of all supported Network Types
supportediverwork rype	LOING	• 0x0000 0000 0000 0001: GSM • 0x0000 0000 0000 0002: GPRS • 0x0000 0000 0000 0004: EDGE • 0x0000 0000 0000 0100: UMTS • 0x0000 0000 0000 0200: HSDPA • 0x0000 0000 0000 0400: HSUPA • 0x0000 0000 0000 0800: HSPA+ • 0x0000 0000 0001 0000: EV-DO • 0x0000 0000 0001 0000: EV-DO • 0x0000 0001 0000 0000: LTE • 0x0000 0002 0000 0000: WiMAX • 0x0001 0000 0000 0000: Others
		A zero value indicates that there is no network support for head-unit connectivity.

NetworkStatus Object returns the current network status information directly. If the current network information is not available. Server MUST return "Not available" error code. This applies to the case when the NetworkInfo Object is subscribed. Following table gives further explanation about member variables defined:

Name	Data type	Description
activeNetworkType	LONG	Current network type being used. Value defined in the table above.
connectivityStatus	ВУТЕ	High-level status information of the active network. The value should be one among  • 0x01: active and tethering enabled  • 0x02: active but tethering disabled  • 0x03: inactive, and  • 0x04: disabled
signalStrength	INT	Signal strength of the active network. The value should be one among  • 0: No signal • 1: Weakest signal • 2: Weak signal • 3: Medium signal • 4: Strong signal • 5: Strongest signal

8

- NetworkStatus Object can be accessed by using Subscribe or Get command. In case of changing any variables of the Object, Server MUST send a new notification.
- 4 DataBalanceStatus Object returns the current data balance information of the Access Point. Data-
- 5 BalanceStatus composes of member variables described in the table as follows:

Name	Data type	Description
dataRoamingStatus	BOOLEAN	Roaming status of Access Point.
		<ul><li>True: Access Point is in roaming mode.</li><li>False: Access Point is not in roaming mode.</li></ul>
mobileDataLimit	LONG	Mobile data limit. The unit is Byte.  • A zero value indicates mobile data is unlimited.
mobileDataUsage	LONG	Amount of mobile data used during the data usage cycle. The unit is Byte.

# **4 IMPLEMENTATION CONFIGURATIONS**

- 2 The Client SHOULD first Get NetworkSupport Object, and then it SHOULD subscribe Network-
- 3 Status Object. The server MUST NOT provide DataBalanceStatus Object if required information
- 4 is not available or not accurate. For instance, data balance or data usage information is valid only if a user
- 5 inputs a billing cycle of the data plan on the Server device.



# 5 REFERENCES

1

4

5

2	[1]	IETF, RFC 2119, Keys words for use in RFCs to Indicate Requirement Levels, March 1997.
3		http://www.ietf.org/rfc/rfc2119.txt

- [2] Car Connectivity Consortium, "MirrorLink Device Attestation", Version 1.1, CCC-TS-014
- [3] Car Connectivity Consortium, "MirrorLink Service Binary Protocol", Version 1.1; CCC-TS-