

Intralabcm:

```
GNU nano 5.4 /etc/mysql/mariadb.conf.d/50-server.cnf
#
# These groups are read by MariaDB server.
# Use it for options that only the server (but not clients) should see
#
# this is read by the standalone daemon and embedded servers
[server]
#
# this is only for the mysqld standalone daemon
[mysqld]
server-id=1
log_bin=binlog
relay_log=relay-bin
log_slave_updates=1
auto_increment_increment=2
auto_increment_offset=1
expire_logs_days=10
max_binlog_size=100M
master-retry-count=20
replicate-do-db=gsb_frais

bind-address = 172.18.
#
# * Basic Settings
#
user                        = mysql
pid-file                    = /run/mysqld/mysqld.pid
basedir                     = /usr
datadir                     = /var/lib/mysql
tmpdir                      = /tmp
lc-messages-dir             = /usr/share/mysql
lc-messages                  = en_US
skip-external-locking

# Broken reverse DNS slows down connections considerably and name resolve is
# safe to skip if there are no "host by domain name" access grants
#skip-name-resolve

# Instead of skip-networking the default is now to listen only on
# localhost which is more compatible and is not less secure.
bind-address                = 172.18.
#
# * Fine Tuning
```

Résultat de la commande SHOW SLAVE STATUS\G

```

MariaDB [(none)]> SHOW SLAVE STATUS\G
***** 1. row *****
      Slave_IO_State: Waiting for master to send event
        Master_Host: 172.18.
        Master_User: replica
        Master_Port: 3306
        Connect_Retry: 60
        Master_Log_File: binlog.000003
        Read_Master_Log_Pos: 339
        Relay_Log_File: relay-bin.000010
        Relay_Log_Pos: 635
        Relay_Master_Log_File: binlog.000003
        Slave_IO_Running: Yes
        Slave_SQL_Running: Yes
        Replicate_Do_DB: gsb_frais
        Replicate_Ignore_DB:
        Replicate_Do_Table:
        Replicate_Ignore_Table:
        Replicate_Wild_Do_Table:
        Replicate_Wild_Ignore_Table:
            Last_Errno: 0
            Last_Error:
            Skip_Counter: 0
        Exec_Master_Log_Pos: 339
        Relay_Log_Space: 1234
        Until_Condition: None
        Until_Log_File:
        Until_Log_Pos: 0
        Master_SSL_Allowed: No
        Master_SSL_CA_File:
        Master_SSL_CA_Path:
        Master_SSL_Cert:
        Master_SSL_Cipher:
        Master_SSL_Key:
        Seconds_Behind_Master: 0
Master_SSL_Verify_Server_Cert: No
            Last_IO_Errno: 0
            Last_IO_Error:
            Last_SQL_Errno: 0
            Last_SQL_Error:
        Replicate_Ignore_Server_Ids:
            Master_Server_Id: 2
            Master_SSL_Crl:
            Master_SSL_Crlpath:
                Using_Gtid: No
                Gtid_IO_Pos:
        Replicate_Do_Domain_Ids:
        Replicate_Ignore_Domain_Ids:
            Parallel_Mode: optimistic
            SQL_Delay: 0
            SQL_Remaining_Delay: NULL
        Slave_SQL_Running_State: Slave has read all relay log; waiting for more updates
        Slave_DDL_Groups: 0
Slave_Non_Transactional_Groups: 0
        Slave_Transactional_Groups: 0
1 row in set (0,000 sec)

```

Hdintralab:

```

#
# These groups are read by MariaDB server.
# Use it for options that only the server (but not clients) should see

# this is read by the standalone daemon and embedded servers
[server]

# this is only for the mysqld standalone daemon
[mysqld]
server-id=2
log_bin=binlog
relay_log=relay-bin
log_slave_updates=1
auto_increment_increment=2
auto_increment_offset=2
expire_logs_days=10
max_binlog_size=100M
master-retry-count=20
replicate-do-db=gsb_frais

bind-address = 172.18.

#
# * Basic Settings
#

user                = mysql
pid-file             = /run/mysqld/mysqld.pid
basedir              = /usr
datadir              = /var/lib/mysql
tmpdir               = /tmp
lc-messages-dir      = /usr/share/mysql
lc-messages          = en_US
skip-external-locking

# Broken reverse DNS slows down connections considerably and name resolve is
# safe to skip if there are no "host by domain name" access grants
#skip-name-resolve

# Instead of skip-networking the default is now to listen only on
# localhost which is more compatible and is not less secure.
bind-address         = 172.18.

```

Résultat de la commande SHOW SLAVE STATUS\G:

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> SHOW SLAVE STATUS\G

```
***** 1. row *****
Slave_IO_State: Waiting for master to send event
Master_Host: 172.18.
Master_User: replica
Master_Port: 3306
Connect_Retry: 60
Master_Log_File: binlog.000013
Read_Master_Log_Pos: 339
Relay_Log_File: relay-bin.000011
Relay_Log_Pos: 552
Relay_Master_Log_File: binlog.000013
Slave_IO_Running: Yes
Slave_SQL_Running: Yes
Replicate_Do_DB: gsb_frais
Replicate_Ignore_DB:
Replicate_Do_Table:
Replicate_Ignore_Table:
Replicate_Wild_Do_Table:
Replicate_Wild_Ignore_Table:
Last_Errno: 0
Last_Error:
Skip_Counter: 0
Exec_Master_Log_Pos: 339
Relay_Log_Space: 1234
Until_Condition: None
Until_Log_File:
Until_Log_Pos: 0
Master_SSL_Allowed: No
Master_SSL_CA_File:
Master_SSL_CA_Path:
Master_SSL_Cert:
Master_SSL_Cipher:
Master_SSL_Key:
Seconds_Behind_Master: 0
Master_SSL_Verify_Server_Cert: No
Last_IO_Errno: 0
Last_IO_Error:
Last_SQL_Errno: 0
Last_SQL_Error:
Replicate_Ignore_Server_Ids:
Master_Server_Id: 1
Master_SSL_Crl:
Master_SSL_Crlpath:
Using_Gtid: No
Gtid_IO_Pos:
Replicate_Do_Domain_Ids:
Replicate_Ignore_Domain_Ids:
Parallel_Mode: optimistic
SQL_Delay: 0
SQL_Remaining_Delay: NULL
Slave_SQL_Running_State: Slave has read all relay log; waiting for more updates
Slave_DDL_Groups: 0
Slave_Non_Transactional_Groups: 0
Slave_Transactional_Groups: 0
1 row in set (0,000 sec)
```