ExampleSet Filter Examples

Role				■
	Name	Туре	Statistics	Range
gular	sIP	nominal	mode = 236.196.32.152 (9064), least =	(236.196.32.152 (9064), 0.0.27.166 (0), 0.0.27.171 (0), 0.0.27.179 (0), 0.0.27
ular	dIP	nominal	mode = 171.34.21.158 (2), least = 171.1	171.169.70.182 (2), 171.202.34.171 (2), 171.210.240.128 (2), 171.34.21.158
ılar	sPort	nominal	mode = 80 (9064), least = 20000 (0)	80 (9064), 0 (0), 1 (0), 10000 (0), 10001 (0), 10002 (0), 10003 (0), 10004 (0),
ılar	dPort	nominal	mode = 3072 (4653), least = 10320 (0)	3072 (4653), 1024 (4411), 0 (0), 1 (0), 10000 (0), 10001 (0), 10002 (0), 10002
lar	protocol	nominal	mode = 6 (9064), least = 17 (0)	17 (0), 6 (9064), 1 (0), 41 (0), 47 (0)
lar	flags	nominal	mode = SA (9064), least = S (0)	SA (9064), A (0), AC (0), AE (0), AEC (0), AU (0), AUC (0), AUEC (0), C (0), E (0),
lar	ttl	numeric	avg = 106.354 +/- 3.141	[50.000; 107.000]
ılar	bytes	numeric	avg = 40 +/- 0	[40.000; 40.000]