

WonderWall™

Description:

The WonderWall™ is a heavy duty, enhanced Barrier system. The robust Barrier gives stability in high winds without the need for extra ballast. It creates a safer working environment when Barrier is deployed near the road side, or excavations on site. Can be moved with ease by one person, and can be moved via Fork-lift truck when the Bases are stacked.

Features:

- Pedestrian & Plant WonderDoor™ can be used.
- The WonderDoor™ system can be created using the Melba Swintex S-Clip, as well as connection to existing Barrier systems.
- A separately moulded peg that is securely fixed allows a quick & easy connection to the next Barrier.
- Embossing with corporate branding on both the Base and Top.
- Tops and Bases can be coloured coded for corporate identity .
- Holes in base for Fork lift entry.
- Location holes for a 600 x 450 Courtesy Sign, & Lamp bracket.
- Bases can stack with one another.
- Compatible with existing systems.
- Facility to take a double decked system.
- 21 pieces each to a pallet.



Connection WonderDoor™ Embossing

Standards:

- Reflectivity requirements of **BSEN12899-1**
- Chapter 8 - The Traffic Signs Manual
- Traffic Signs Regulations & General Directions



Height:	1000 mm
Width:	1140 mm
Barrier Depth:	50 mm
Base Depth:	500 mm
Weight:	25 kg

**All weights are approximate*

The information given on these sheets is typical of the product depicted it must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice. All measurements are in millimetres (mm)

REMA



FM 673547