

04 – The bonus shebang

CS 2043: Unix Tools and Scripting, Spring 2019 [1]

Matthew Milano

January 30, 2019

Cornell University

Table of Contents

Caution About Shebang

- The shebang **must** be the first line.
- Generally speaking, best approach is to use `env`:

```
#!/usr/bin/env bash
#!/usr/bin/env python
```
- Generally, it is “wrong” to hard-code say `#!/bin/bash`
 - If I have a custom installation of **bash** that I want to use, your script will ignore me and use the default system **bash**.
- There times **ARE** you do this, but they are very uncommon.
 - Example: program that interfaces with the operating system.
 - Then you **do** want to hard-code paths to `/bin` or `/usr/bin`.
- Not a `#` commentable language?
 - Official answer: just don’t use a shebang.
 - Unofficial answer: technically it doesn’t matter, since the shebang is a hack on the first 8 bits, but this would render the file useless except for when it is executed by a shell.

Shebang Case Study: System Tool Counterexample

- Consider the tool **gnome-tweak-tool**. It's purpose is to alter system configurations of the desktop manager Gnome.
- Their shebang:

```
#!/usr/bin/env python
```

- This is “wrong”. My operating system uses **/usr/bin/python** behind the scenes for displaying windows etc.
- I have a *custom* python installation that I use for daily hacking.
 - **gnome-tweak-tool** uses my *custom* python, instead of using the *system* python.
 - Should be using **/usr/bin/python**.
- Why is it “wrong”? The **gi.repository** library imported refers to my *custom* python, not the *system* python.
- This “bug” has been around for years with no change. There has to be a reason?

Shebang Details

- The Shebang does not need a space, but can have it if you want. The following all work:

```
#!/usr/bin/env bash
#! /usr/bin/env bash
#!      /usr/bin/env bash
#!      /usr/bin/env bash
```

- The **#!** is the *magic* (yes, that is the technical term):
 - The **#!** **must** be the very first two characters, and
 - the executable separated by whitespace *on the same line*.
- Recall that starts **#** is a comment in **bash**.
 - Technically this line is never “executed” *by the script*.
 - The **shell** *launching the script* to determine *how* to launch.
- In general, you will see either one space or no spaces.
 - Best to stick with one of those for consistency ;)

Shebang Limitations

- Generally, only *safe* to use **two** arguments in shebang:
 1. The interpreter.
 2. An optional set of arguments.
- So when you do `/usr/bin/env`, technically
 1. `/usr/bin/env` is the “interpreter”
 2. `bash` is the argument.
- This means that if you want to use `perl` or `awk` or something, you are limited to single letter flags. E.g. if you want `-a`, `-b`, `-c`, you would have to do `/usr/bin/perl -abc`.
 - `/usr/bin/env` cannot be used!
 - [Interesting mail thread][04_env_mail].
- [Amusing hacks available][04_shebang_hacks].

References

- [1] Stephen McDowell, Bruno Abrahao, Hussam Abu-Libdeh, Nicolas Savva, David Slater, and others over the years. “Previous Cornell CS 2043 Course Slides”.