

Azure ESLZ: Naming Standard

Instruction: Follow the below and update any new items as approved

Sample
Format: [region]-[Abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-Abbreviation-prod-std-demo-001
Notes:
Management Groups
Format: [COUNTRY]-MG-[SCOPE]
Example: AUS-MG-PLATFORM, AUS-MG-CONNECTIVITY, AUS-MG-IDENTITY, AUS-MG-SECURITY, AUS-MG-MANAGEMENT, AUS-MG-PROD-CONTROLLED, AUS-MG-DEV-STANDARD
Notes: All Capital.
Subscriptions
Format: [country]-[sub]-[environment]-[apm security domain]-[instance identifier]
Example: aus-sub-prod-controlled-01, aus-sub-uat-standard-01
Notes: All Small. APM Security Domain as Full Word for example: controlled and standard .
Resource Groups
Format: [region]-[rg]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Examples: - Connectivity: auea-rg-connectivity-palo-001 - Identity: auea-rg-identity-adds-001 - Management: auea-rg-management-monitoring-001 - Security: auea-rg-security-logs-001 - Workload (Prod/Dev/SIT/UAT): auea-rg-prod-ctrl-[appname]-001, auea-rg-prod-std-[appname]-001 - Backup RGs: [region]-rg-[env]-[ctrl/std]-backup-[instance identifier]: auea-rg-prod-std-backup-001
Notes: For Palo Alto, (palo) must always be in the RG name.
Virtual Networks
Format: [region]-[vnet]-[environment]-[apm security domain]-[instance identifier]
Example: auea-vnet-connectivity-001, ause-vnet-prod-std-001, auea-vnet-prod-std-001, auea-vnet-avd-ctrl-001
Notes: All VNets peered into Hub (Connectivity) except for Sandbox and Acquisition.
Subnets
Format: [region]-[snet]-[descriptor]- [instance identifier]
Example: auea-snet-app-001, ause-snet-db-001
Notes: Subnet does not need <i>environment</i> and <i>apm security domain</i> . These are linked to specific VNets that belongs to specific <i>environment</i> and <i>apm security domain</i> .
Route Tables
Format: [region]-[rt]-[environment]-[apm security domain]-[descriptor]- [instance identifier]
Example: auea-rt-connectivity-001, auea-rt-prod-crtl-001, ause-rt-dev-std-001
Firewalls (Palo Alto)
Format: [region:shortform]-[fw]-[environment:shortform]-[descriptor]-[instance identifier]
Example: aefwppalo001, aefwppalo002, asfwppalo001
OS Disk Format for Palo Alto: [region:shortform]-osdisk-[vmname]
Example: ae-osdisk-aefwppalo001
Data Disk Format for Palo Alto: [region:shortform]-datadisk-[vmname]-[instance identifier]
Example: ae-datadisk- aefwppalo001-001, ae-datadisk-aefwppalo001-002

NIC Format for Palo Alto: [region:shortform]-nic-[vmname]-[instance identifier]

Example: ae-nic-aefwppalo001-001

Internal Load Balancer (Palo Alto)

Format: [region:shortform]-[resource type abbreviation]-[environment:shortform]-[descriptor]-[instance identifier]

Example: aelbippalo001, aslbippalo001

Associated resources with Internal Load Balancer (Palo Alto):

Public IP: auea-pip-prod-[descriptor]-[instance identifier]

Frontend: auea-fe-prod-[descriptor]-[instance identifier]

Backend Pool: auea-bepool-prod-[descriptor]-[instance identifier]

LB Rule: auea-lbrule-prod-[descriptor]-https-[instance identifier]

Probe: auea-probe-prod-[descriptor]-https-[instance identifier]

Note:

- Internal Load Balancer: lbi
- External Load Balancer: lbe
- Public IP: pip
- Frontend: fe
- Backend Pool: bepool
- Load Balancer Rule: lbrule
- Probe: probe

Public IP

Format: [region]-[resource type abbreviation]-[environment]-[descriptor]-[instance identifier]

Example: auea-pip-conn-s2sgateway-001, ause-pip-conn-s2sgateway-001

Application Gateway

Format: [region]-[resource type abbreviation]-[environment]-[apm security domain]-[optional descriptor]-[instance identifier]

Example: auea-appgw-conn-001, auea-appgw-prod-ctrl-001, ause-appgw-prod-ctrl-001

Public IP: ae-pip-p-appgw-001, as-pip-p-appgw-001

Notes: In connectivity subscription, use same RG style as Palo: ‘[region]-rg-connectivity-appgw-001’

Azure Front Door (v2) [INCORRECT]

Format: global-[resource type abbreviation]-[instance identifier]

Example: global-afd-001

Notes: Always global service, put in ‘global-rg-connectivity-frontdoor-001’

Active Directory Domain Services (ADDS)

Format: [region:shortform]-[vm]-[environment:shortform]-[apm security domain:shortform]-[descriptor]-[instance identifier]

Example: aevmpadds001, asvmpadds001

OS Disk: [region:shortform]-osdisk-[vmname]

Data Disk: [region:shortform]-datadisk-[vmname]-[instance identifier]

NIC: [region:shortform]-nic-[vmname]-[instance identifier]

RG: [region]-rg-identity-adds-001

Key Vaults

Format: [region]-[kv]-[environment]-[apm security domain]-[descriptor]-[instance identifier]

Examples: auea-kv-management-001, ause-kv-security-001, ause-kv-prod-ctrl-001, auea-kv-prod-std-001

RG: Management → [region]-rg-management-shareservices-001

Storage Accounts

[region:shortform]-[st]-[environment:shortform]-[apm security domain:shortform]-[descriptor]-[instance identifier]

Example: aestmopslog001, aestpcappname001, asstpsappname001

Security flow logs: [region:shortform]stxflowlog[instance identifier]

Example: aestxflowlog001

Security diagnostic: [region:shortform]stxsecdiag[instance identifier]	
Example: aestxsecdiag001	
Backup Vaults (Recovery Services Vaults)	
Format: [rsv]-[environment]-[apm security domain]-[descriptor]-[region]-[instance identifier]	
Examples: auea-rsv-connectivity-001, auea-rsv-prod-ctrl-001	
Notes: All controlled/standard subscriptions now also get '[region]-rg-[environment]-[ctrl/std]-backup-001' for these.	
Log Analytics	
Format: [region]-law-[environment]-[descriptor]-[instance identifier]	
Examples: auea-law-mgmt-operation-001, auea-law-sec-001	
RG: Management → <region>-rg-management-monitoring-001	
RG: Security → <region>-rg-security-logs-001	
Network Watcher (Revised)	
Format: NetworkWatcherRG_[region]	
Examples: NetworkWatcher_australiaeast, NetworkWatcher_australiasoutheast	
RG: default → NetworkWatcherRG	
Notes: One per subscription per region.	
Private DNS Zones	
Format: [region]-[pdz]-[descriptor]-[instance identifier]	
Examples:	
Blob: auea-pdz-blob-001	
File: ause-pdz-file-001	
SQL: auea-pdz-sqldb-001	
App Service: ause-pdz-appsvc-001	
Azure VM Server Host	
Format: [region:shortform]-[vm]-[environment:shortform]-[apm security domain:shortform]-[descriptor]-[instance identifier]	
Example: aevmpscrm01, aevmpcsp01,	
OS Disk: [region:shortform]-osdisk-[vmname]	
Data Disk: [region:shortform]-datadisk-[vmname]-[instance identifier]	
NIC: [region:shortform]-nic-[vmname]-[instance identifier]	
Private Endpoint	
Format: [region]-[resource type abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]	
Example: auea-pep-prod-ctrl-kvsecrets-001, auea-pep-sit-std-aestpcblob001-001	
Backup Policy	
Format: [region]-[resource type abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]	
Example: (VM)	auea-rsvp-prod-ctrl-backup-basic-001, auea-rsvp-prod-ctrl-backup-standard-001
Example: (VM with SQL)	auea-rsvp-prod-ctrl-vmsqlbackup-basic-001, auea-rsvp-prod-ctrl-vmsqlbackup-standard-001, auea-rsvp-prod-ctrl-vmsqlbackup-standard-002, auea-rsvp-prod-ctrl-vmsqlbackup-enhanced-001
Network Security Group	
Format: [region]-[nsg]-[environment]-[apm security domain]-[descriptor]-[instance identifier]	
Example: ause-nsg-dev-ctrl-web-001, ause-nsg-dev-ctrl-db-001, ause-nsg-prod-std-web-001, ause-nsg-prod-std-db-001, auea-nsg-connectivity-001, auea-nsg-appgw-001, auea-nsg-identity-001, auea-nsg-mgmt-jumphost-001	
Network Security Rules (New Addition)	
Format: [allow/deny]-[ob/ib]-[source]-to-[destination]-[optional:descriptor]-[instance identifier]	
Example: deny-ib-vnet-to-vnet-https-01, allow-ob-azmoniror-to-law-https-01	
ib: Inbound,	
ob: Outbound	
Updated Date: 17 July 2026	
Availability Set (New Addition)	

Format: [region]-[resource type abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-avail-conn-palo-01
IP Config Name (New Addition)
Format: [region]-[resource type abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-ipconfig-aefwppalo001-001
Databases (Azure SQL Database server)
Format: [region]-[sql]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-sql-prod-std-demo-001, Example: auea-sql-nonprod-ctrl-demo-001
Notes: 128 Character limit
Databases (Azure SQL database)
Format: [region]-[sqldb]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-sqldb-prod-std-demo-001
Notes: 116 Character limit
Databases (Azure SQL Elastic Pool)
Format: [region]-[sqlep]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-sqlep-prod-std-demo-001
Notes:
Databases (SQL Managed Instance)
Format: [region]-[sqlmi]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-sqlmi-prod-std-demo-001
Notes:
App Service environment
Format: [region]-[ase]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-ase-prod-std-demo-001
Notes:
App Service plan
Format: [region]-[asp]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-asp-prod-std-demo-001
Notes:
Load Balancer (External - Frontend Public IP)
Format: [region]-[lb]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-lbe-prod-std-demofepip-001
Notes:
Load Balancer (External - Public IP)
Format: [region]-[lb]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-lb-prod-std-demofeip-001
Notes:
Function App
Format: [region]-[Abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-func-prod-std-demo-001
Notes:
Application Insights
Format: [region]-[Abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-aapi-prod-std-demo-001
Notes:
Azure Front Door (Standard/Premium) Profile [Names must be Globally unique, 5-64 characters]

Format: [apm]-[Abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: apm-adf-prod-std-demo-001
Notes: Global Service always.
Azure Front Door (Standard/Premium) Endpoint
Format: [apm]-[Abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: apm-fde-prod-std-demo-001
Notes:
Azure Front Door firewall policy
Format: [apm]-[Abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: apm-fdfp-prod-std-demo-001
Notes:
Azure Data Factory
Format: [region]-[Abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-adf-prod-ctrl-demo-001
Notes:
Azure Web App
Format: [region]-[Abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-app-prod-ctrl-demo-001
Notes: Character limit of 2 to 60 characters. Must be globally unique.
Managed Identity
Format: [region]-[Abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-Abbreviation-prod-std-demo-001, auea-uami-management-demo-001, auea-sami-management-demo-001
Notes: User Assigned: 'u'; System Assigned: 's'.
Logic App
Format: [region]-[Abbreviation]-[environment]-[apm security domain]-[descriptor]-[instance identifier]
Example: auea-logic-prod-std-demo-001
Notes: