

Designing Visualization Widgets for Tangible Data Exploration: A Systematic Review

Haonan Yao * Lingyun Yu † Lijie Yao ‡

Department of Computing, School of Advanced Technology, Xi'an Jiaotong-Liverpool University




Fig. 1: An illustration of the dimensions and their sub-categories in our systematic review. A detailed version is in Appendix A.

ABSTRACT

We present a systematic review on tasks, interactions, and visualization widgets (refer to tangible entities that are used to accomplish data exploration tasks through specific interactions) in the context of tangible data exploration. Tangible widgets have been shown to reduce cognitive load, enable more natural interactions, and support the completion of complex data exploration tasks. Yet, the field lacks a structured understanding of how task types, interaction methods, and widget designs are coordinated, limiting the ability to identify recurring design patterns and opportunities for innovation. To address this gap, we conduct a systematic review to analyze existing work and characterize the current design of data exploration tasks, interactions, and tangible visualization widgets. We next reflect based on our findings and propose a research agenda to inform the development of a future widget design toolkit for tangible data exploration. Our systematic review and supplemental materials are available at physicalviswidget.github.io and osf.io/vjw5e/.

Index Terms: Visualization widget, Tangible interaction, Data exploration.

1 INTRODUCTION

Exploring data requires users to complete specific tasks through interactions with visual representations [6]. A wide range of interaction paradigms have been proposed, including tactile and pen-based input [13, 29], mid-air gestures [17, 5], and hybrid approaches combining voice or multi-modal input [25, 10]. Among these, tangible interaction—where users manipulate physical objects to control virtual counterparts—has shown particular promise by leveraging users' natural motor skills and spatial reasoning [1]. Specifically, in data exploration, visualization widgets, such as sliders, cutting planes, and data probes, have been widely used as interactive tools to control how data is displayed and interpreted [27, 19, 24].

Despite the wide interest in tangible interactions, we still lack a structured understanding of how task types, interaction techniques, and visualization widgets are coordinated in data exploration. In the

absence of such an overview, it remains challenging to identify recurring design patterns or extract fruitful insights for future widget toolkit development. While prior work has explored individual visualization widgets or specific interaction methods, no studies have synthesized this knowledge to examine how tangible widgets, user interactions, and visualization tasks are interlinked.

To fill in this gap, we conduct a systematic review of 71 papers, resulting in 171 instances of data exploration tasks involving tangible visualization widgets and corresponding user interactions. We analyze these instances across four dimensions: **Tasks**, **User Interactions**, **Visualization Widgets**, and their **Relative Position**. We further reflect on the findings and propose a research agenda that moves from current practices toward the creation of a tangible widget toolkit. Our research agenda highlights the need to define reusable functional shapes of widgets, leverage material properties for interaction, and establish deeper coordination between tasks, visualization widgets, and user interactions in data exploration.

2 RELATED WORK

As our review lies in the tasks and interactions in data exploration, focusing on the tangible visualization widgets, we first introduce the related work on visualization widgets, followed by visualization tasks and interaction techniques.

2.1 Visualization Widgets

Visualization widgets support interaction by being manipulated by users to control how data is visualized [1]. It can be virtual or tangible entities. For example, adjusting the transparency of bar charts through a virtual slider on a 2D screen [27], viewing the interior of a volume rendering by using a virtual cutting plane on a 2D screen [2, 16, 21], cutting a volume rendering to intercept slices with a paper above the tabletop [23], or replacing the representation of spatio-temporal data via cubes assembly on the table [11]. However, how the physical properties of a tangible widget can be used to benefit the data exploration tasks has not been systematically investigated. A most relevant work to ours is from Gong et al. [9], highlighting that features like affordances could be leveraged in tangible surface interactions.

2.2 Visualization Tasks

In the visualization community and broader human-computer interaction (HCI), data exploration tasks have been classified according to different aspects, such as data characteristics (e.g., graph data

*e-mail: haonanyao0622@gmail.com

†e-mail: lingyun.yu@xjtlu.edu.cn

‡Corresponding author, e-mail: yaolijie0219@gmail.com

tasks [18, 15] in information visualization (InfoVis) and spatial 3D data tasks [1, 14] scientific vis), interaction tasks (i. e., tasks of controlling virtual entities through actions [4, 12, 22]), and high-level tasks (i. e., abstract tasks oriented by user intent [1, 3]) and low-level tasks (i. e., concrete tasks for accomplishing high-level data visualization and exploration tasks [14]). In our work, instead of proposing a new classification, we categorize the tasks according to the environment in which they occur, their content, and the representation of the task entity to help clarify relationships between tasks, interactions, and widgets.

2.3 Interaction Techniques

Interaction is a goal-oriented activity [6] and widely exists in data exploration to help users explore and get insights from data. Yi et al. [28] proposed general categories of interaction techniques widely used in Infovis. Specifically, Gomez et al. [8] used a cube that can be held by one hand to manipulate data rendering; Ens et al. [7] designed building models that could be placed on a tabletop interface to visualize energy usage inside the building. More recently, He et al. [11] proposed a set of flexible cubes that allow users to browse datasets by holding, comparing them by overlaying, or merging them through side-by-side placement. Previous work illustrates the diverse roles of tangible widgets in supporting interaction, which our review systematically analyzes to uncover broader design patterns and inform future widget-based data exploration.

3 APPROACHES

In this section, we first introduce how we conducted our systematic review, and next, how we analyzed the results.

3.1 Literature Selection and Screening

Selection: We selected papers from major visualization-related and HCI venues, including VIS, EuroVis, CHI, UIST, ISMAR, VR, VRST, DIS, ISS, TEI, SUI, 3DUI, TVCG, CGF, and CG&A. Our initial search used the keywords “tangible & interaction” and “widget”, yielding 611 papers. We later expanded to include “3D interaction” after observing that many relevant works in 3D environments employed visualization widgets for data exploration without explicitly referencing the two keywords above, and also included “physical interaction” to ensure broader coverage of related papers, resulting in 466 papers. We in total selected 1,077 publications, spanned from 2010 to 2024.

Screening: We excluded papers that lacked a tangible widget (e.g., gesture-only interactions, and virtual visualization widgets), did not involve interaction with a task entity (e.g., annotation without task engagement), or used objects as proxies without further manipulation (e.g., simple pointing). We then examined the remaining papers to confirm they clearly described their data exploration tasks, the interactions to complete the tasks, and the (tangible) visualization widgets used. Papers lacking this information were excluded. In total, we retained 71 papers that met our criteria, including 50 from keywords on “tangible & interaction”, 3 from “widget”, and 18 with “3D interaction”.

3.2 Review and Categorization Process

We analyzed the 71 retained papers through a three-phase process:

Dimension Initialization: We defined an initial set of three dimensions aligned with our research scope: *Tasks*, *User Interactions*, and *Visualization Widgets*. Based on our observations during the literature screening phase, that much relevant work had been conducted in an immersive or 3D environment, we thus included *Relative Position* as a fourth dimension to capture the spatial relationships among the user, widget, and task entity. Two authors collaboratively reviewed a sample of approximately 15 papers to define sub-categories for each dimension. One author then applied the resulting categorization scheme to all 71 papers.

Dimension Iteration: During categorization, if new potential categories emerged, the coding author brought them to the group discussion. All authors jointly evaluated whether to incorporate the new category and clarified its scope. We refer to this as an iterative process. After each iteration, the categorizing author reapplied the updated scheme to the full paper set. Iteration concluded once no additional subcategories emerged.

Categorization Checking: To ensure clarity and consistency, a second author—independent from the initial coder—reviewed the full categorization to identify ambiguous cases. The two authors resolved disagreements through discussion, and any unresolved cases were brought to the full author group for final decision. The final version of our categorization can be found on OSF (osf.io/vjw5e/).

As one paper may involve multiple tasks (and thus multiple interactions and widgets), we collected and categorized 171 instances of tasks from 71 papers in the end.

4 RESULTS

In this section, we describe the results of our systematic review, per dimension and its sub-categories (illustration in Fig. 1). We use in-line visualization as a visual indicator for major counts.

 **Tasks** describe in which environment the data exploration tasks have been conducted (*Task environment*), what the task content is (*Task content*), and in which representation the task entity has been perceived by users (*Task entity's representation*).

Task environment: Most data exploration tasks were conducted on 2D displays , followed by immersive environments such as AR and VR . In contrast, stereoscopic screens were rarely used; one possible reason is that there have been no dedicated design guidelines on how to show data effectively on such screens.

Task content: Our collected instances included general tasks such as adjusting , modulating , translating/rotating/scaling , looking up, clipping, replacing, navigating, browsing, and locating. We did not identify other tasks beyond the known types.

Task entity's representation: 3D  and 2D  are both common representations of task entities; each accounts for almost half of the whole. Other formats, such as audio, system, artifact, are rare. We provided a full version in the Appendix B, demonstrating the detailed representations included in these three types.

 **User Interactions** describe how users operate tangible entities to complete a data exploration task (*Manipulation method*), what interactions users perform (*Interaction type*), and where interactions take place (*Where the interaction happens*).

Manipulation method: In current practices, one-handed manipulation is mainstream . For two-handed manipulation, symmetric interaction appears approximately twice as often as asymmetric.

Interaction type: We categorized the actions users performed into six types:  positioning ,  rotating ,  shaking ,  casting (pointing an object toward a target),  shaping (modifying an object's geometry or structure), and  tracing (drawing a motion trajectory). In addition to individual interactions, combination also appeared, and there are quite a few, such as  positioning +  rotating .

Where the interaction happens: Interactions typically took place above horizontal surfaces  (e.g., a tabletop), or on the horizontal surfaces . Some interactions happened in a room space that does not necessarily require a tabletop . A few interactions occurred on vertical and inclined surfaces.

 **Visualization Widgets** refer to tangible entities that are used to accomplish data exploration tasks through specific interactions. Widget examples include a VR pointer for selecting points via ray-casting, a physical dial/button for adjusting visual-

ization scale, and a pen for positioning. Here we discuss how big a widget is (*Size*), how many widgets are used (*Quantity*), the shape in which the widget acts (*Functional shape*), and the material properties of the widget (*Material properties*).

Size: Small widgets—those that fit within a user’s palm—were the most commonly used [10]. Medium widgets, which exceed palm size but can still be held in one hand, appeared less frequently [11]. Large widgets, which cannot be grasped by hand, were rarely used.

Quantity: Most instances involved a single tangible widget to perform a task [12], with occasional use of more than one. In some cases (mainly the clipping task), combined setups were used—either integrating virtual and tangible widgets (e.g., a virtual cutting plane controlled by a slider is used to slice a volume rendering accurately, and multiple tops of columns are used for forming a non-planar surface to slice a volume rendering flexibly.)

Functional shape: While widgets may exhibit diverse physical forms, the shape that makes sense might be the same (e.g., one corner of a tablet is used as point input to select a virtual object, and a distal end of a slender body is used as point input to locate a position in space.). The most common functional shape was a planar surface [13], followed by a body-shaped form [14], a straight edge, a point, and a non-planar surface.

Material properties: Material Properties influenced by the materials from which the widgets are constructed, including [15] bendable, [16] assembleable, [17] elastic, [18] foldable, [19] malleable, [20] stretchable, and [21] twistable. In our review, most visualization widgets did not leverage material properties [22]. Only a small number incorporated material-dependent behaviors, such as stretchability, elasticity, or foldability.

Relative Position indicates the Accessible distance between user and task entity, the Accessible distance between user and visualization widget(s), and the Spatial integration between task entity and visualization widget(s).

Accessible distance between user and task entity: Reachable distance—where the task entity lies within arm’s reach—was the most common configuration in our review [23]. Less frequent were unreachable distances, flexible distances (with a variable user–entity relationship), and cases where distance could not be determined, such as when the task entity was formless.

Accessible distance between user and visualization widget(s): Similar to above, reachable distance—where the widget is within the user’s arm’s length—was the most common configuration [24]. In a few cases, widgets were used in an embodied manner (e.g., a bracelet is worn on the wrist to manipulate a 3D virtual object directly).

Spatial integration between task entity and visualization widget(s): The most frequent configuration was [25] discrete [26], meaning the widget is completely separated from the task entity; and aligned [27], indicating side-by-side placement. Less common were [28] crossed, where the widget partially overlaps with the task entity, and [29] embedded, where one is fully contained within the other. “Other” denotes cases where the relative position was unmeasurable, such as when the task entity was formless.

In summary, we investigate tangible data exploration across four dimensions. We found that most tasks are performed in 2D or immersive environments, with positioning and rotating as the most common interaction types. Interactions are typically one-handed and occur above or on horizontal surfaces. Widgets are generally small, used individually, and without using material properties—most often shaped as planar or body-like forms. Interaction tends to take place within arm’s reach, with task entities and widgets commonly arranged in discrete or aligned spatial integration.




Fig. 2: A mapping relationship between the widgets’ physical form and functional shape. The definitions of the physical form and functional shape can be found in Appendix C.

5 REFLECTIONS AND A RESEARCH AGENDA

Based on the findings of our systematic review, here we discuss our reflections on the current design and outline research opportunities in tangible data exploration.

5.1 Reflections

Our reflections go from a low level to a high level. As our goal is to inform tangible visualization widget design, we first reflect on the widget design. We next reflect on how the widgets function in interactions to complete concrete tasks.

Widget Design:

The role of shape: In our systematic review, we introduce *functional shape* of a widget, referring to the geometry relevant to its interactive role. Here, we examine how a widget’s physical form relates to its functional shape (Fig. 2). This relationship is not one-to-one: multiple physical forms, such as polyhedrons or slender bodies, may serve the same functional role, and a single form may support multiple functions. These patterns suggest that designers often repurpose different geometries to achieve similar interaction goals. This raises the question: could a general-purpose widget or a toolkit covering key functional shapes streamline the design of tangible tools for data exploration?

Utilization of material properties: A key distinction between tangible and non-tangible widgets lies in their material-based properties, such as bendability, stretchability, and twistability. Yet, our review reveals that these properties are rarely leveraged in data exploration contexts. For example, although paper is commonly used for straight-line cuts, practitioners often rely on external right-angled objects rather than folding the paper itself to achieve a precise corner. This underuse may stem from a lack of understanding about how such physical properties can be effectively exploited—and to what extent they support specific data exploration tasks.

Task-Interaction-Widget as A Whole:

Tasks summarization: As we introduced in related work, visualization tasks have been well classified according to different aspects, such as low-level and high-level tasks. In contrast to creating a new task classification, we summarize the low-level tasks categorization presented in our systematic review under a framework with the high-level tasks that they belong to, referring to Munzner’s [20] and Besançon’s [1] classifications. They are: *changing*, including replacing a visual representation or adjusting a visual parameter; *manipulating*, including translating/rotating/scaling a visualization or navigating; *searching*, including looking up, browsing, and locating; and *modulating and clipping*.

Our task summarization focuses specifically on tangible visualization widgets, and as such, differs in scope and granularity from prior task classifications in visualization [28, 1, 20]. We see value in providing this tailored summary, as a lack of existing guidance on which tasks, under which context, have been practically supported

SUPPLEMENTAL MATERIALS

An interactive website of our systematic review is accessible at physicalviswidget.github.io. The supplemental materials for our study are available on OSF at osf.io/vjw5e/. In particular, we share our (a) systematic review material, (b) coding co-occurrences derived from our analysis, and (c) definitions of the physical form and functional shape with examples from our review.

ACKNOWLEDGMENTS

Lijie Yao is partially funded by the XJTLU RDF, grant № RDF-24-01-062. Lingyun Yu was partially supported by the National Natural Science Foundation of China, grant № 62272396.

REFERENCES

- [1] L. Besançon, A. Ynnerman, D. F. Keefe, L. Yu, and T. Isenberg. The state of the art of spatial interfaces for 3D visualization. *Computer Graphics Forum*, 40(1):293–326, 2021. doi: 10.1111/cgf.14189 1, 2, 3
- [2] J. Beyer, M. Hadwiger, S. Wolfsberger, and K. Bühler. High-quality multimodal volume rendering for preoperative planning of neurosurgical interventions. *IEEE Transactions on Visualization and Computer Graphics*, 13(6):1696–1703, 2007. doi: 10.1109/TVCG.2007.705601
- [3] M. Brehmer and T. Munzner. A multi-level typology of abstract visualization tasks. *IEEE Transactions on Visualization and Computer Graphics*, 19(12):2376–2385, 2013. doi: 10.1109/TVCG.2013.124 2
- [4] F. Brudy, C. Holz, R. Rädle, C.-J. Wu, S. Houben, C. N. Klokmoose, and N. Marquardt. Cross-device taxonomy: Survey, opportunities and challenges of interactions spanning across multiple devices. In *Proceedings of the Conference on Human Factors in Computing Systems*, p. 1–28. ACM, New York, 2019. doi: 10.1145/3290605.3300792 2
- [5] M. Cavallo, M. Dholakia, M. Havlena, K. Ocheltree, and M. Podlaseck. Dataspace: A reconfigurable hybrid reality environment for collaborative information analysis. In *Proceedings of the Conference on Virtual Reality and 3D User Interfaces*, pp. 145–153. IEEE, New York, 2019. doi: 10.1109/VR.2019.8797733 1
- [6] E. Dimara and C. Perin. What is interaction for data visualization? *IEEE Transactions on Visualization and Computer Graphics*, 26(1):119–129, 2019. doi: 10.1109/TVCG.2019.2934283 1, 2
- [7] B. Ens, S. Goodwin, A. Prouzeau, F. Anderson, F. Y. Wang, S. Gratzl, Z. Lucarelli, B. Moyle, J. Smiley, and T. Dwyer. Uplift: A tangible and immersive tabletop system for casual collaborative visual analytics. *IEEE Transactions on Visualization and Computer Graphics*, 27(2):1193–1203, 2020. doi: 10.1109/TVCG.2020.3030334 2
- [8] S. R. Gomez, R. Jianu, and D. H. Laidlaw. A fiducial-based tangible user interface for white matter tractography. In *Advances in Visual Computing: International Symposium*, pp. 373–381. Springer, Berlin, Heidelberg, 2010. doi: 10.1007/978-3-642-17274-8_37 2
- [9] W. Gong, S. Santosa, T. Grossman, M. Glueck, D. Clarke, and F. Lai. Affordance-based and user-defined gestures for spatial tangible interaction. In *Proceedings of the Designing Interactive Systems Conference*, pp. 1500–1514. ACM, New York, 2023. doi: 10.1145/3563657.3596032 1
- [10] B. D. Hall, L. Bartram, and M. Brehmer. Augmented chironomia for presenting data to remote audiences. In *Proceedings of the Symposium on User Interface Software and Technology*. ACM, New York, 2022. doi: 10.1145/3526113.3545614 1
- [11] S. He, H. Yao, L. Jiang, K. Li, N. Xiang, Y. Li, H.-N. Liang, and L. Yu. Data cubes in hand: A design space of tangible cubes for visualizing 3D spatio-temporal data in mixed reality. In *Proceedings of the Conference on Human Factors in Computing Systems*, pp. 1–21. ACM, New York, 2024. doi: 10.1145/3613904.3642740 1, 2
- [12] J. Hertel, S. Karaosmanoglu, S. Schmidt, J. Bräker, M. Semmann, and F. Steinicke. A taxonomy of interaction techniques for immersive augmented reality based on an iterative literature review. In *Proceedings of the International Symposium on Mixed and Augmented Reality*, pp. 431–440. IEEE, New York, 2021. doi: 10.1109/ISMAR52148.2021.00060 2
- [13] J. Jo, S. L’Yi, B. Lee, and J. Seo. Touchpivot: Blending wimp & post-wimp interfaces for data exploration on tablet devices. In *Proceedings of the Conference on Human Factors in Computing Systems*, p. 2660–2671. ACM, New York, 2017. doi: 10.1145/3025453.3025752 1
- [14] D. F. Keefe and T. Isenberg. Reimagining the scientific visualization interaction paradigm. *Computer*, 46(5):51–57, 2013. doi: 10.1109/MC.2013.178 2
- [15] N. Kerracher, J. Kennedy, and K. Chalmers. A task taxonomy for temporal graph visualisation. *IEEE Transactions on Visualization and Computer Graphics*, 21(10):1160–1172, 2015. doi: 10.1109/TVCG.2015.2424889 2
- [16] T. Klein, F. Guénat, L. Pastur, F. Vernier, and T. Isenberg. A design study of direct-touch interaction for exploratory 3D scientific visualization. In *Computer Graphics Forum*, vol. 31, pp. 1225–1234, 2012. doi: 10.1111/j.1467-8659.2012.03115.x 1
- [17] Z. Kostic, C. Dumas, S. Pratt, and J. Beyer. Exploring mid-air hand interaction in data visualization. *IEEE Transactions on Visualization and Computer Graphics*, 30(9):6347–6364, 2024. doi: 10.1109/TVCG.2023.3332647 1
- [18] B. Lee, C. Plaisant, C. S. Parr, J.-D. Fekete, and N. Henry. Task taxonomy for graph visualization. In *Proceedings of the AVI Workshop on Beyond Time and Errors: Novel Evaluation Methods for Information Visualization*, pp. 1–5. ACM, New York, 2006. doi: 10.1145/1168149.1168168 2
- [19] D. Leithinger, S. Follmer, A. Olwal, S. Luescher, A. Hogge, J. Lee, and H. Ishii. Sublimate: State-changing virtual and physical rendering to augment interaction with shape displays. In *Proceedings of the Conference on Human Factors in Computing Systems*, p. 1441–1450. ACM, New York, 2013. doi: 10.1145/2470654.2466191 1
- [20] T. Munzner. *Visualization analysis and design*. CRC press, 2014. 3
- [21] C. Rieder, F. Ritter, M. Raspe, and H.-O. Peitgen. Interactive visualization of multimodal volume data for neurosurgical tumor treatment. In *Computer Graphics Forum*, vol. 27, pp. 1055–1062, 2008. doi: 10.1111/j.1467-8659.2008.01242.x 1
- [22] A. Scoditti, R. Blanch, and J. Coutaz. A novel taxonomy for gestural interaction techniques based on accelerometers. In *Proceedings of the International Conference on Intelligent User Interfaces*, p. 63–72. ACM, New York, 2011. doi: 10.1145/1943403.1943414 2
- [23] M. Spindler, S. Stellmach, and R. Dachselt. Paperlens: Advanced magic lens interaction above the tabletop. In *Proceedings of the International Conference on Interactive Tabletops and Surfaces*, p. 69–76. ACM, New York, 2009. doi: 10.1145/1731903.1731920 1
- [24] D. A. Steinman. Simulated pathline visualization of computed periodic blood flow patterns. *Journal of Biomechanics*, 33(5):623–628, 2000. doi: 10.1016/S0021-9290(99)00205-5 1
- [25] M. Tsang, G. W. Fitzmaurice, G. Kurtenbach, A. Khan, and B. Buxton. Boom chameleon: Simultaneous capture of 3D viewpoint, voice and gesture annotations on a spatially-aware display. In *Proceedings of the Symposium on User Interface Software and Technology*, pp. 111–120. ACM, New York, 2002. doi: 10.1145/571985.572001 1
- [26] B. Ullmer, H. Ishii, and R. J. K. Jacob. Token+constraint systems for tangible interaction with digital information. *ACM Transactions on Computer-Human Interactions*, 12(1):81–118, Mar. 2005. doi: 10.1145/1057237.1057242 6
- [27] W. Willett, J. Heer, and M. Agrawala. Scented widgets: Improving navigation cues with embedded visualizations. *IEEE Transactions on Visualization and Computer Graphics*, 13(6):1129–1136, 2007. doi: 10.1109/TVCG.2007.70589 1
- [28] J. S. Yi, Y. ah Kang, J. Stasko, and J. A. Jacko. Toward a deeper understanding of the role of interaction in information visualization. *IEEE Transactions on Visualization and Computer Graphics*, 13(6):1224–1231, 2007. doi: 10.1109/TVCG.2007.70515 2, 3
- [29] L. Yu, K. Efstathiou, P. Isenberg, and T. Isenberg. Efficient structure-aware selection techniques for 3D point cloud visualizations with 2DOF input. *IEEE Transactions on Visualization and Computer Graphics*, 18(12):2245–2254, 2012. doi: 10.1109/TVCG.2012.217 1