

Changing `textContent`, `innerHTML`, `value`, and `style` in JavaScript

In this section, you'll learn how to dynamically change content and appearance on a webpage using JavaScript.

1. `textContent`

The `textContent` property sets or returns the text content of a node and its descendants. It ignores any HTML tags.

```
<p id="demo">Hello <strong>World</strong></p>
```

```
const para = document.getElementById("demo");  
console.log(para.textContent); // Hello World  
para.textContent = "New text content";
```

2. `innerHTML`

The `innerHTML` property sets or returns the HTML content of an element.

```
<p id="demo">Hello</p>
```

```
const para = document.getElementById("demo");  
para.innerHTML = "<strong>Bold Text</strong>";
```

Use `innerHTML` carefully to avoid XSS vulnerabilities when inserting user-provided data.

3. `value`

The `value` property is used to get or set the value of form elements such as `<input>`, `<textarea>`, and `<select>`.

```
<input type="text" id="username" value="John">
```

```
const input = document.getElementById("username");
console.log(input.value); // John
input.value = "Harry";
```

4. `style`

You can change the inline style of an element using the `style` property.

```
<p id="demo">This is a paragraph.</p>
```

```
const para = document.getElementById("demo");
para.style.color = "red";
para.style.fontSize = "20px";
para.style.backgroundColor = "#f0f0f0";
```

Note: CSS property names with dashes (e.g., `background-color`) become camelCase (`backgroundColor`) in JavaScript.

Summary

Property	Purpose
textContent	Changes plain text (ignores HTML)
innerHTML	Changes or inserts HTML content
value	Reads or sets form input values
style	Dynamically changes inline CSS