

Creating, Appending, and Removing Elements in JavaScript

JavaScript allows you to dynamically create, insert, and remove elements from the DOM, enabling highly interactive web applications.

1. Creating Elements

Use `document.createElement()` to create a new HTML element in memory (not yet in the DOM).

Example:

```
const newDiv = document.createElement("div");
newDiv.textContent = "Hello, I was created dynamically!";
```

You can also set attributes or classes:

```
newDiv.setAttribute("id", "dynamicDiv");
newDiv.classList.add("box", "highlight");
```

2. Appending Elements

Use methods like `appendChild()` or `append()` to insert an element into the DOM.

Example:

```
<div id="container"></div>
```

```
const container = document.getElementById("container");  
container.appendChild(newDiv); // Adds the newDiv as the last child
```

Or using `append()` which allows multiple nodes or strings:

```
container.append("Another text node", document.createElement("hr"));
```

3. Prepending Elements

Use `prepend()` to insert an element at the beginning of the parent.

```
const heading = document.createElement("h2");  
heading.textContent = "Welcome!";  
container.prepend(heading);
```

4. Removing Elements

To remove an element, you can use:

a) `removeChild()` (from parent)

```
container.removeChild(newDiv);
```

b) `element.remove()` (directly on the element)

```
heading.remove(); // Removes the heading element directly
```

Note: `element.remove()` is widely supported but not in very old browsers.

Summary

Task	Method
Create element	<code>document.createElement()</code>
Set text content	<code>element.textContent</code>
Add attribute or class	<code>setAttribute()</code> , <code>classList.add()</code>
Append to parent	<code>appendChild()</code> , <code>append()</code>
Prepend to parent	<code>prepend()</code>
Remove from parent	<code>parent.removeChild(child)</code>
Remove element directly	<code>element.remove()</code>