

BCI2000-Compatible Audio-Visual P3 Task

Jennia Hizver, Jürgen Mellinger, Dennis McFarland, Gerwin Schalk

December 2, 2005

Contents

1	Functionality	2
1.1	Stimulus Definition	2
1.2	Stimulus Sequence	3
1.2.1	Deterministic Sequence:	3
1.2.2	Random Sequence:	4
1.3	Stimulus Delivery	4
2	Processing of Classification Results	5
2.1	Free Mode	6
2.2	Copy Mode	6
3	Parameters	6
4	States	9
5	Time line	9

Abstract

The main purpose of this task is to present a series of (auditory or visual) stimuli sequentially to the user of the BCI system. The sequence and nature of the stimuli can be defined by the investigator. In addition to stimulus delivery, the task can optionally be used in conjunction with BCI2000's P300 Signal Processing module (P3SignalProcessing.exe) to provide feedback to a selected stimulus in either a copy or a free mode.

1 Functionality

1.1 Stimulus Definition

Stimuli are set up through a parameter defined by the application module. This implicitly defines the total number of stimuli as well as the details of each stimulus. Each stimulus is defined by the following properties:

1. Caption
2. Icon file
3. Audio file
4. optionally, an individual Stimulus duration ("on time")

In addition to stimuli that are part of the actual stimulation sequence, the **FocusOn** and **Result** parameters contain definitions for a stimulus that announces what to focus on, and a stimulus that announces the result. These stimuli are only used when the task is set to copy or free mode.

The following table contains an example definition of two stimuli; for clarity, the parameter line defining the associated parameter is also given: ¹

¹The line's parameter format contains two newly introduced extensions:

- In the place of a dimension value there may be a list of string labels that may be used instead of numerical indices, delimited by a matching pair of any of `{`, `[]`, `()`.
- A `%` character followed by up to two hexadecimal digits represents a byte value in hexadecimal notation, thus `%20` represents a space character, and `%`, `%0`, and `%00` all represent an empty string value; `%%` represents the `%` character itself.

	focuson	result	stimulus1	stimulus2
caption	Please focus on	The result was	Donkey	
icon	icons\focus on.bmp	icons\result.bmp	icons\donkey.bmp	icons\elefant.bmp
audio	wav\focus on.wav	wav\result.wav	wav\snicker.wav	wav\trumpet.wav

```
"P3AV matrix Matrix= "
    "{caption icon audio OnTime} " // row labels
    "{stimulus1 stimulus2} "      // column labels

    // stimulus1
    "Donkey icons\\donkey.bmp wav\\snicker.wav 10 "
    // stimulus2
    "% icons\\elefant.bmp wav\\trumpet.wav 30 "
```

Comments: In order to specify individual stimulus durations, a row labelled `OnTime` may be added to the `Matrix` parameter. In this case, the global `OnTime` parameter will be ignored, and a duration for each stimulus must be given in the `OnTime` row.

The stimulus properties might contain white spaces. A caption/icon/audio file are not being presented, if they are not defined (e.g., see caption in stimulus2). The stimulus definition parameter does *not* contain a description on how the stimuli are presented. Stimulus numbers start at 1. Relative paths are interpreted relative to the application module's executable location.²

1.2 Stimulus Sequence

Stimuli are presented in a certain sequence. This sequence can either be deterministic, i.e., defined by the investigator, or random.

1.2.1 Deterministic Sequence:

The investigator defines the order by entering a list of stimulus IDs to be presented. As an example:

```
1 5 3 4 2
```

defines a sequence in which stimulus 1 is first presented, followed by stimulus 5, etc.

²Which, in general, is not the application module's working directory at runtime but the path portion of the first argument to `main()`.

1.2.2 Random Sequence:

The investigator defines absolute stimulus frequencies for each stimulus, with the sum N of those values equaling the total number of stimulus presentations in the final sequence. The resulting random sequence is obtained by applying a random permutation to an arbitrary sequence that reproduces the given frequencies, with all $N!$ index permutations being equally probable (Block Randomization).³

As an example:

6 2 3

defines a sequence of 11 stimulus presentations with stimulus 1 being presented 6 times, stimulus 2 2 times, and stimulus 3 3 times. The resulting sequence S_1 will be a permutation of $S_0 = [1, 1, 1, 1, 1, 1, 2, 2, 3, 3, 3]$, and the probability for S_1 to equal S_0 will be $\frac{6! \times 2! \times 3!}{(6+2+3)!} = 1/4620$.

Multiple sequences can be generated from the given frequencies. The investigator can define how many sequences are generated and played.

1.3 Stimulus Delivery

For any stimulus, delivery occurs simultaneously for caption⁴, icon, and audio. (A computer can only execute commands in sequence, but the time difference between start of presentation of caption, icon, and audio, is negligible). *Comment:* A knowledgeable investigator has to understand the implications of audio files that are of unequal length !

An investigator can specify:

- Size and position of the target window (using the same scheme/parameters as used by the RJB task, Oddball paradigm, or P3 speller).
- Width and height of caption and icon in percent of screen width/height⁵
- Whether captions, icons, or audio files will be presented (i.e., a global switch). There are no individual switches for each stimulus. However, captions/icons/wave files will not be presented for individual stimuli if they are not defined (i.e., their respective entries are blank).

³Block randomization routines, as well as a pseudo random generator better than the one available via `rand()`, are available in the P3 Speller module.

⁴A caption, if defined, always appears in front on an icon.

⁵Using, e.g., the `TImage::Stretch` property for scaling.

- The volume for audio playback as a float value between 0 and 1
- Window background color in RGB⁶
- Caption color in RGB
- The duration during which a stimulus is presented (in units of SampleBlocks)⁷
- The duration of an inter-stimulus interval following stimulus presentation (in units of SampleBlocks)⁸
- A minimum and maximum time (in units of SampleBlocks) that will be added randomly to the inter-stimulus interval, with probability distributed uniformly over time intervals. If these variables are both set to 0, the actual inter-stimulus interval will always be exactly as defined above. If these variables are set to, for example, 0 and 3, inter-stimulus intervals will randomly be longer by between 0 and 3 units, with a probability of 1/4 for the occurrence of any one of the four time intervals possible.
- A Comment. A user can enter comments to the specific run in a string parameter.

2 Processing of Classification Results

The task can be configured to interpret results communicated to it by the P3 Signal Processing module. These results represent a judgment on which of the stimuli was most likely selected. Handling of these results is identical to the P3 Spelling Task.

When it transmits a classification result, Signal Processing sets the state *StimulusCodeRes* to the stimulus code that was originally transmitted to it by the user application. For example, when it sets *StimulusCodeRes* to 3, it indicates that it transmits classification results for stimulus 3. In addition, it sets *StimulusTypeRes* to reflect the type of the stimulus (0=non-target,

⁶For convenience, RGB values may be entered in hexadecimal notation, e.g. 0xff0000 for red.

⁷Playback of audio extending above the specified duration will be muted.

⁸During the inter-stimulus interval, the screen is blank and audio is turned off.

1=target) when the system is in copy mode. Signal Processing transmits the classification result as one number (i.e., the first control signal).

2.1 Free Mode

The task can be configured to operate in free mode. In this case, the sequence of stimulus delivery is followed by a time period, in which the result of Signal Processing's classification is announced. The final classification result is the stimulus with the highest classification result.

In order to deliver this announcement, the system uses the stimulus defined in the **result** column of the stimuli parameter. This announcement is followed by delivery of the determined stimulus. In other words, after a sequence of stimulus delivery, the system might play a .wav file that says: "the result is," followed by a .wav file that says "yes." (assuming "yes" represents the stimulus that produced the highest classification result).

Finally, the task sends this result to the operator module as an ASCII text message so that it appears in a log window.

Free mode does not terminate until the investigator suspends operation.

2.2 Copy Mode

Copy mode is similar to free mode. In copy mode, the investigator can define a list of stimuli to be copied (e.g., "3 5 4"). In this example, the user has to attend to stimulus 3 for the first sequence, 5 for the second sequence, etc.

In addition to an announcement of the result, in copy mode the delivery of stimuli is preceded by an announcement that describes which stimulus the user has to attend to. This announcement uses the stimulus that is defined in the **focuson** column of the stimuli parameter. This announcement is followed by delivery of the desired target stimulus. As an example, the system might say "Please focus now on" ... "yes," before it starts with the sequence of stimulus delivery.

Copy mode terminates (i.e., the task suspends) when the user finished copying all stimuli specified by the investigator.

3 Parameters

The following parameters configure this task:

- **WinXpos, WinYpos, WinWidth, WinHeight:** Size and position of the target window (using the same scheme/parameters as used by the RJB task, Oddball paradigm, or P3 speller).
- **WinBackgroundColor:** Window background color in RGB⁹
- **StimulusWidth:** Width of stimulus in percent of screen. Height is deduced based on the respective icon's aspect ratio.
- **AudioSwitch:** Whether audio files will be presented (i.e., a global switch). There are no individual switches for each stimulus. However, wave files will not be presented for individual stimuli if they are not defined. The values can be: 0(off) and 1(on).
- **VideoSwitch:** Whether video files will be presented (i.e., a global switch). There are no individual switches for each stimulus. However, icons files will not be presented for individual stimuli if they are not defined. The values can be: 0(off) and 1(on).
- **CaptionSwitch:** Whether captions will be presented (i.e., a global switch). There are no individual switches for each stimulus. However, captions will not be presented for individual stimuli if they are not defined. The values can be: 0(off) and 1(on).
- **AudioVolume:** The volume for audio playback as a float value between 0 and 1
- **CaptionColor:** Color of stimulus caption text in hex (0x00BBGGRR).
- **CaptionHeight:** Height of stimulus caption text in percent of screen.
- **OnTime:** The duration during which a stimulus is presented (in units of SampleBlocks)¹⁰ The way it translates to seconds is **OnTime** multiplied by **SampleBlockSize** (samples transmitted per time) divided by **SamplingRate**(samples per one second). When individual stimulus durations are given in the **Matrix** parameter, the value of the **OnTime** parameter is ignored.

⁹For convenience, RGB values may be entered in hexadecimal notation, e.g. 0xff0000 for red.

¹⁰Playback of audio extending above the specified duration will be muted.

- **OffTime**: The duration of an inter-stimulus interval following stimulus presentation (in units of SampleBlocks)¹¹
- **MinInterTime**, **MaxInterTime**: A minimum and maximum time (in units of SampleBlocks) that will be added randomly to the inter-stimulus interval, with probability distributed uniformly over time intervals. If these variables are both set to 0, the actual inter-stimulus interval will always be exactly as defined above. If these variables are set to, for example, 0 and 3, inter-stimulus intervals will randomly be longer by between 0 and 3 units, with a probability of 1/4 for the occurrence of any one of the four time intervals possible.
- **PreSequenceTime**: The duration(in SampleBlocks) before a sequence is presented. During this time the following is going to happen. In Copy Mode: “Please, focus on ...” message will be played followed by the actual stimulus that the subject needs to focus on. In Free Mode and No-Interpretation Mode: during this time nothing will be presented, just a plain blank screen.
- **PostSequenceTime**: The duration(in SampleBlocks) after a sequence is presented. During this time the following is going to happen. In Copy Mode and Free Mode: “The result was ...” message will be played followed by the predicted stimulus. In No-Interpretation Mode: during this time nothing will be presented, just a plain blank screen.
- **Matrix**: Defines all the possible stimuli which can be presented on the screen. See description in 1.1 section.
- **FocusOn**: Defines a stimulus that is used to announce “please, focus on ..” message.
- **Result**: Defines a stimulus that is used to announce “the result is ..” message.
- **Sequence**: Sequence of stimuli that is presented to the user (deterministic type) / Frequencies for for each stimulus (random sequence). Stimuli are defined as column indices into the **Matrix** parameter.

¹¹During the inter-stimulus interval, the screen is blank and audio is turned off.

- **SequenceType**: Specifies whether the sequence is deterministic (value 0) or random (value 1).
- **NumberOfSeq**: Number of sequences being presented to the user in a single run.
- **InterpretMode**: None(value 0, no interpretation)/Free(value 1)/Copy(value 2) mode. If interpretation mode is set to none, the task does not rely on presence of **StimulusCodeRes** and **StimulusTypeRes** states and thus can be used with other signal processing modules.
- **ToBeCopied**: A list of stimuli that user needs to copy (only in copy mode).
- **UserComment**: A Comment. A user can enter comments to the specific run in a string parameter.

The following conditions need to be satisfied:

- Sound card has to be present if wave files are defined and global audio switch is on.
- All the parameters have to be present.
- **MinInterTime** has to be less than **MaxInterTime**.
- **PreSequenceTime** and **PostSequenceTime** have to be at least 2 times larger than **OnTime**. This follows from the fact that during presequence and postsequence there will be 2 stimuli presented: one is for “please, focus on ..”/“the result is ..” and the other for the actual name of the stimulus.
- The time defined by **PostSequenceTime** multiplied by **SampleBlockSize** has to be larger than the value defined by **NumSamplesInERP**.

4 States

The time line of stimulus delivery is encoded in state variables as defined in Table 1.

5 Time line

State Name	Bits	Description
SelectedStimulus	7	stimulus ID of finally selected stimulus only >0 when determining selected stimulus
PhaseInSequence	2	0 in inter-stimulus interval 1 period prior to stimulus sequence (if any) 2 stimulus sequence period 3 period after stimulus sequence (if any)
StimulusTime	16	time in ms as calculated in P3 Speller
StimulusCode	7	stimulus ID of currently visible stimulus or 0 if no stimulus visible
StimulusType	1	0 in free mode; copy mode : 1 when current stimulus equals target stimulus 0 otherwise
Flashing	1	1 during stimulus presentation, 0 otherwise

Table 1: Encoding scheme for this task.




Figure 1: Time line.