


Minimisation of (history-)deterministic generalised (co-)Büchi automata

joint work with Antonio Casares, Denis Kuperberg, Olivier Idir and Aditya Prakash


Minimisation of (history-)deterministic generalised (co-)Büchi automata

joint work with Antonio Casares, Denis Kuperberg, Olivier Idir and Aditya Prakash

Büchi automaton




Büchi automaton



$$L(\mathcal{A}) = \{\text{words that contain infinitely many } aab\} = (\Sigma^* aab)^\omega$$


Büchi automaton




$$L(\mathcal{A}) = \{\text{words that contain infinitely many } aab\} = (\Sigma^* aab)^\omega$$

Deterministic Büchi automata recognise *Büchi languages*.

Co-Büchi automaton




Co-Büchi automaton



$$L(\mathcal{A}) = \{\text{words that contain finitely many } aab\} = \Sigma^* a^\omega \cup \Sigma^* (ab^+)^{\omega}$$

Co-Büchi automaton



$$L(\mathcal{A}) = \{\text{words that contain finitely many } aab\} = \Sigma^* a^\omega \cup \Sigma^* (ab^+)^{\omega}$$


Deterministic co-Büchi automata recognise *co-Büchi languages*.
= complements of Büchi languages.

History-determinism [Henzinger, Piterman 2006]

\mathcal{A} is **history-deterministic** if there is a *resolver* $\sigma : \Delta^* \times \Sigma \rightarrow \Delta$ such that for all $w \in L(\mathcal{A})$, applying σ while reading w yields an accepting run.

History-determinism [Henzinger, Piterman 2006]

\mathcal{A} is **history-deterministic** if there is a *resolver* $\sigma : \Delta^* \times \Sigma \rightarrow \Delta$ such that for all $w \in L(\mathcal{A})$, applying σ while reading w yields an accepting run.




History-deterministic co-Büchi automaton.

Finitely many b or finitely many c .


History-determinism [Henzinger, Piterman 2006]

\mathcal{A} is **history-deterministic** if there is a *resolver* $\sigma : \Delta^* \times \Sigma \rightarrow \Delta$ such that for all $w \in L(\mathcal{A})$, applying σ while reading w yields an accepting run.



History-deterministic co-Büchi automaton.

Finitely many b or finitely many c .




Büchi automaton,
NOT history-deterministic.

Infinitely many b or infinitely many c .


History-determinism [Henzinger, Piterman 2006]

\mathcal{A} is **history-deterministic** if there is a *resolver* $\sigma : \Delta^* \times \Sigma \rightarrow \Delta$ such that for all $w \in L(\mathcal{A})$, applying σ while reading w yields an accepting run.



History-deterministic co-Büchi automaton.

Finitely many b or finitely many c .



Büchi automaton,
NOT history-deterministic.

Infinitely many b or infinitely many c .

[Kuperberg, Skrzypczak 2015]

History-determinism can be tested in PTIME for Büchi and co-Büchi automata.

Minimisation

Minimise \mathcal{A} = find \mathcal{B} of the same type, the same language and with as few states as possible.

Minimisation

Minimise \mathcal{A} = find \mathcal{B} of the same type, the same language and with as few states as possible.

Remark : Minimising deterministic Büchi and co-Büchi automata is the same problem.

Minimisation

Minimise \mathcal{A} = find \mathcal{B} of the same type, the same language and with as few states as possible.

Remark : Minimising deterministic Büchi and co-Büchi automata is the same problem.

But history-deterministic Büchi and co-Büchi are very different!

[Kuperberg, Skrzypczak 2015]

- ▶ History-deterministic co-Büchi automata can be exponentially smaller than deterministic ones,
- ▶ Every history-deterministic Büchi automata has an equivalent deterministic one of size $O(n^2)$.

[Schewe 2010]

It is NP-complete to minimise
deterministic (co-)Büchi
automata.

[Schewe 2010]

It is NP-complete to minimise
deterministic (co-)Büchi
automata **when the acceptance
condition is on the states.**

[Schewe 2010]

It is NP-complete to minimise deterministic (co-)Büchi automata **when the acceptance condition is on the states.**

[Abu Radi, Kupferman 2019]

We can minimise history-deterministic co-Büchi automata in polynomial time **when the acceptance condition is on the transitions.**

[Schewe 2010]

It is NP-complete to minimise deterministic (co-)Büchi automata **when the acceptance condition is on the states.**

[Schewe 2020]

It is NP-complete to minimise history-deterministic (co-)Büchi automata **when the acceptance condition is on the states.**

[Abu Radi, Kupferman 2019]

We can minimise history-deterministic co-Büchi automata in polynomial time **when the acceptance condition is on the transitions.**

State-based

[Schewe 2010]

It is NP-complete to minimise deterministic (co-)Büchi automata **when the acceptance condition is on the states.**

[Schewe 2020]

It is NP-complete to minimise history-deterministic (co-)Büchi automata **when the acceptance condition is on the states.**

Transition-based

[Abu Radi, Kupferman 2019]

We can minimise history-deterministic co-Büchi automata in polynomial time **when the acceptance condition is on the transitions.**

State-based

[Schewe 2010]

It is NP-complete to minimise deterministic (co-)Büchi automata **when the acceptance condition is on the states.**

[Schewe 2020]

It is NP-complete to minimise history-deterministic (co-)Büchi automata **when the acceptance condition is on the states.**

Transition-based

[Abu Radi, Kupferman 2019]

We can minimise history-deterministic co-Büchi automata in polynomial time **when the acceptance condition is on the transitions.**

*Can we minimise
(history-)deterministic (co-)Büchi
automata in polynomial time?*

In the transition-based world

	Büchi	Co-Büchi
Deterministic	???	???
History-deterministic	???	PTIME

In the transition-based world

	Büchi	Co-Büchi
Deterministic	???	???
History-deterministic	???	PTIME

When you encounter a difficult problem, switch to a different (related) problem.

-George Pólya (sort of)

In the transition-based world

	Büchi	Co-Büchi
Deterministic	???	???
History-deterministic	???	PTIME

When you encounter a difficult problem, switch to a different (related) problem.

-George Pólya (sort of)

This work: We study **generalised** (co-)Büchi automata:

In the transition-based world

	Büchi	Co-Büchi
Deterministic	???	???
History-deterministic	???	PTIME

When you encounter a difficult problem, switch to a different (related) problem.

-George Pólya (sort of)

This work: We study **generalised** (co-)Büchi automata:

	Generalised Büchi	Generalised co-Büchi
Deterministic	NP-complete	NP-complete
History-deterministic	NP-complete	PTIME


Generalised Büchi automaton

Set of colours $C = \{\bullet, \bullet, \bullet, \dots\}$, colouring function $col : \Delta \rightarrow 2^C$

Generalised Büchi automaton

Set of colours $C = \{\bullet, \bullet, \bullet, \dots\}$, colouring function $col : \Delta \rightarrow 2^C$

Generalised Büchi: See every colour infinitely many times.




Infinitely many aab or infinitely many
 ab and b^2

Generalised Büchi automaton


Set of colours $C = \{\bullet, \bullet, \bullet, \dots\}$, colouring function $col : \Delta \rightarrow 2^C$

Generalised Büchi: See every colour infinitely many times.





Infinitely many aab or infinitely many ab and b^2

Generalised co-Büchi: avoid some colour indefinitely after some point.



Finitely many aab and finitely many ab or b^2



From GBA to BA



Generalised Büchi with n states
and k colours.

Büchi with nk states.

From GBA to BA



Generalised Büchi with n states
and k colours.

Büchi with nk states.

Preserves history-determinism!

Minimisation of gen. HD co-Büchi in polynomial time

Step 1: Apply Abu Radi-Kupferman

Given a generalised history-deterministic co-Büchi recognising L ,

- Compute an equivalent history-deterministic co-Büchi


Step 1: Apply Abu Radi-Kupferman

Given a generalised history-deterministic co-Büchi recognising L ,

- ▶ Compute an equivalent history-deterministic co-Büchi
- ▶ We can minimise it $\rightarrow \mathcal{A}_{min}^L$ using Abu Radi and Kupferman's algorithm


Step 2: Merge safe components

Suppose the language is *prefix-independent*, i.e., all states have the same residual.
(= the language is stable under prefix modification)



Step 2: Merge safe components


Suppose the language is *prefix-independent*



Accepted = stay in a safe component eventually


Step 2: Merge safe components

Suppose the language is *prefix-independent*





Step 2: Merge safe components

Suppose the language is *prefix-independent*





Step 2: Merge safe components

Suppose the language is *prefix-independent*





Step 2: Merge safe components

Suppose the language is *prefix-independent*





Step 2: Merge safe components

Suppose the language is *prefix-independent*



Step 2: Merge safe components

Suppose the language is *prefix-independent*



- + all other transitions, with **X X X**

Why it is minimal

[Abu Radi, Kupferman 2019]

For all equivalent HD co-Büchi automaton \mathcal{C} there is an injection $\eta : \text{SafeComp}(\mathcal{A}_{min}^L) \rightarrow \text{SafeComp}(\mathcal{C})$ such that $|\eta(S)| \geq |S|$ for all $S \in \text{SafeComp}(\mathcal{C})$.

Why it is minimal

[Abu Radi, Kupferman 2019]

For all equivalent HD co-Büchi automaton \mathcal{C} there is an injection $\eta : \text{SafeComp}(\mathcal{A}_{min}^L) \rightarrow \text{SafeComp}(\mathcal{C})$ such that $|\eta(S)| \geq |S|$ for all $S \in \text{SafeComp}(\mathcal{C})$.

- We have an HD gen. co-Büchi of size $m = \text{size of the largest safe component of } \mathcal{A}_{min}^L$

Why it is minimal

[Abu Radi, Kupferman 2019]

For all equivalent HD co-Büchi automaton \mathcal{C} there is an injection $\eta : \text{SafeComp}(\mathcal{A}_{min}^L) \rightarrow \text{SafeComp}(\mathcal{C})$ such that $|\eta(S)| \geq |S|$ for all $S \in \text{SafeComp}(\mathcal{C})$.

- ▶ We have an HD gen. co-Büchi of size $m = \text{size of the largest safe component of } \mathcal{A}_{min}^L$
- ▶ Every equivalent HD co-Büchi has a safe component of size $\geq m$

Why it is minimal

[Abu Radi, Kupferman 2019]

For all equivalent HD co-Büchi automaton \mathcal{C} there is an injection $\eta : \text{SafeComp}(\mathcal{A}_{min}^L) \rightarrow \text{SafeComp}(\mathcal{C})$ such that $|\eta(S)| \geq |S|$ for all $S \in \text{SafeComp}(\mathcal{C})$.

- ▶ We have an HD gen. co-Büchi of size $m = \text{size of the largest safe component of } \mathcal{A}_{min}^L$
- ▶ Every equivalent HD co-Büchi has a safe component of size $\geq m$

If we had a smaller HD gen. co-Büchi we could unfold it to get an HD co-Büchi where all components have size $< m$.

This work

We can minimize generalised HD co-Büchi automata in polynomial time.

Why it is minimal

[Abu Radi, Kupferman 2019]

For all equivalent HD co-Büchi automaton \mathcal{C} there is an injection $\eta : \text{SafeComp}(\mathcal{A}_{min}^L) \rightarrow \text{SafeComp}(\mathcal{C})$ such that $|\eta(S)| \geq |S|$ for all $S \in \text{SafeComp}(\mathcal{C})$.

- ▶ We have an HD gen. co-Büchi of size $m = \text{size of the largest safe component of } \mathcal{A}_{min}^L$
- ▶ Every equivalent HD co-Büchi has a safe component of size $\geq m$

If we had a smaller HD gen. co-Büchi we could unfold it to get an HD co-Büchi where all components have size $< m$.

This work

We can minimize generalised HD co-Büchi automata in polynomial time.

If not prefix-independent $\rightarrow \sim$ apply the procedure for each residual.

A sketch of NP-completeness

NP upper bound

\mathcal{A} a (history-)deterministic gen. (co-)Büchi automaton with n states and k colours.
Is there an automaton of the same type with $\leq m$ states equivalent to \mathcal{A} ?

NP upper bound

\mathcal{A} a (history-)deterministic gen. (co-)Büchi automaton with n states and k colours.

Is there an automaton of the same type with $\leq m$ states equivalent to \mathcal{A} ?

- ▶ Guess an automaton \mathcal{B} with $\leq m$ states
- ▶ Check equivalence between \mathcal{A} and \mathcal{B}

NP upper bound

\mathcal{A} a (history-)deterministic gen. (co-)Büchi automaton with n states and k colours.
Is there an automaton of the same type with $\leq m$ states equivalent to \mathcal{A} ?

- ▶ Guess an automaton \mathcal{B} with $\leq m$ states
- ▶ Check equivalence between \mathcal{A} and \mathcal{B} ✓

Folklore

Equivalence is decidable in PTIME between all those kinds of automata.

NP upper bound

\mathcal{A} a (history-)deterministic gen. (co-)Büchi automaton with n states and k colours.
Is there an automaton of the same type with $\leq m$ states equivalent to \mathcal{A} ?

- ▶ Guess an automaton \mathcal{B} with $\leq m$ states
- ▶ Check equivalence between \mathcal{A} and \mathcal{B} ✓

Folklore

Equivalence is decidable in PTIME between all those kinds of automata.

But \mathcal{B} could have exponentially many colours!

NP upper bound

\mathcal{A} a (history-)deterministic gen. (co-)Büchi automaton with n states and k colours.
Is there an automaton of the same type with $\leq m$ states equivalent to \mathcal{A} ?

- ▶ Guess an automaton \mathcal{B} with $\leq m$ states ✓
- ▶ Check equivalence between \mathcal{A} and \mathcal{B} ✓

Folklore

Equivalence is decidable in PTIME between all those kinds of automata.

But \mathcal{B} could have exponentially many colours!



This work

If \mathcal{B} exists then it can be recoloured to use $\leq \mathcal{O}(|\mathcal{A}|km)$ colours.

NP lower bound

From graph 3-colouring.

Suitable language: $L_G = \bigcap_{v \in V} (V^*vv)^\omega \cup V^*(V \setminus N(v))^\omega$.



NP lower bound

- ▶ Every k -colouring of G induces a det. gen. Büchi automaton with k states for L_G .
- ▶ A 3-state gen. Büchi automaton for L_G induces a 3-colouring of G .

NP lower bound

- ▶ Every k -colouring of G induces a det. gen. Büchi automaton with k states for L_G .
- ▶ A 3-state gen. Büchi automaton for L_G induces a 3-colouring of G .

This work

This problem is NP-complete:

Given a (history-)deterministic Büchi automaton \mathcal{A} and $k \in \mathbb{N}$,
is there an equivalent one with $\leq k$ states?

NP lower bound

- ▶ Every k -colouring of G induces a det. gen. Büchi automaton with k states for L_G .
- ▶ A 3-state gen. Büchi automaton for L_G induces a 3-colouring of G .

This work

This problem is NP-complete:

Given a (history-)deterministic Büchi automaton \mathcal{A} with 4 states, is there an equivalent one with ≤ 3 states?

Minimising colours

This work

It is NP-complete to minimise both the number of states and colours for (history-)deterministic gen. (co-)Büchi automata.

Minimising colours

This work

It is NP-complete to minimise both the number of states and colours for (history-)deterministic gen. (co-)Büchi automata.

Proof idea:

Minimising colours

This work

It is NP-complete to minimise both the number of states and colours for (history-)deterministic gen. (co-)Büchi automata.

[Casares, M. 2024] \rightarrow study of the complexity of simplifying conditions on ω -automata.

What is left to do

- ▶ Minimisation of Büchi, parity automata
- ▶ Are HD gen. Büchi automata more succinct than deterministic ones?
- ▶ (In-)approximability of minimisation?

What is left to do

- ▶ Minimisation of Büchi, parity automata
- ▶ Are HD gen. Büchi automata more succinct than deterministic ones?
- ▶ (In-)approximability of minimisation?

Thanks !