Vietnam Cambodia Laos vACC – VVDN Pilot Briefing

Da Nang International Airport (IATA: DAD, ICAO: VVDN) is an international airport serving the area of Central Vietnam and the region's largest city Da Nang.

Two parallel Runways 35R/17L and 35L/17R at Da Nang International Airport are operated dependently and considered as **one Runway** for flight operations.

Runway 35L is mainly used for landing and Runway 35R is mainly used for take-off.

Runway 17R is mainly used for landing and Runway 17L is mainly used for take-off.

Departure Procedures

Aircraft departing Runway 35R will be assigned a RNAV SID ending in “G”.

Aircraft departing Runway 17L will be assigned a conventional SID ending in “A”.

Pushback

Aircraft code D/E to be pushed to Taxiway E.

Aircraft up to code C operating on taxilane D.

Initial Climb

The initial climb for all departures out of Da Nang is **5000 feet**, regardless of SID.

Transition Altitude

The transition altitude is 9000 feet.

ATC frequency list

Callsign	Frequency
VVDN_GND (Da Nang Ground)	121.600
VVDN_TWR (Da Nang Tower)	118.350
VVDN_APP (Da Nang Approach)	120.450
DNA_APP (Da Nang Control)	125.300
VVHM_CTR (Ho Chi Minh Control)	132.350
VVDN_ATIS	128.525

Arrival Procedures

Runway 35L

The standard STAR expected is Kilo (LATOM2K/PAPRA2K/CAHEO2K/BUNTA2K/CQ 2K) arrivals for ILS V runway 35L.

Runway 17R

Conventional STAR to be expected for VOR DME approach runway 17R (DME arc or over the station)

Transition Level

The transition level is FL100.

Taxiing procedures

All aircraft after runway vacated should taxi on Taxiway E into stand.

Charts

Charts for Da Nang International Airport (VVDN) can be found here

Available Scenery

MSFS: VVDN By Dominic Design Team

Enhancement Package by Yoshino

X-Plane: 105290 by Julian Lockwood