USB_C_Receptacle_PowerOnly_6P CC1= A5 CC2= B5 VBU\$WR_FLAG GND 🕂 16 D GND VBUS_FET_EN FLIP CC1 CC2 VCCD R3 2.2k 1_k R4 H_{4.7u} +3.3V R8 5.1k Q1 DMP3098LSD-13 VDDD \$1 61 \$2 62 C3 C4 C5 R2 20k § ♦ 01_2 8 01_1 7 01_1 6 02_2 5 R10 5.1k R11 10k PWR_FLAG +3.3V X CYPD3177-24LQXI1 N R E N R VDC_0UT 11 P HPI_SDA 12 A HPI_SDA 12 VBUS_MAX HPI_SCL 13 $\begin{array}{c|c} DNU2 & 21 \\ HPI_INT & 7 \\ GPIO_1 & 8 \end{array}$ HPI_SDA 12 DNU1 20 R13 R12 5.1k Q2 2N7002K R1442 20k € 4 ÷3.3v D1 1k V_out














O H4 MountingHole



Headphone Output





+15V

R26 2.2k

U3A NE5532

R29 10

VBIAS_LEFT

SN 4

S ♦

GND

U3B NE5532

R30 10 + U3C C15

C16 10u

R27 2.2k

