

Exploration and Presentation - Assignment 3

Anders Jacobsen, Dima Karaush

April 14, 2021

Contents

1	Task 1	3
1.1	Find a point in your program that can be optimized	3
1.2	Make a measurement of the point to optimize	3
1.3	Make it at least 50% faster	4

Intro

We are using the project Letter Frequencies downloaded from <https://github.com/CPHBusinessSoftUFO/letterfrequencies> in this paper.

System Information

Computer specs used to optimize: OS Name: Microsoft Windows 10 Pro OS Version: 10.0.19042 N/A Build 19042 System Type: x64-based PC Processor(s): 1 Processor(s) Installed. [01]: Intel64 Family 6 Model 165 Stepping 5 GenuineIntel 3792 Mhz BIOS Version: American Megatrends Inc. 1.10, 21-05-2020 Total Physical Memory: 32.688 MB

1 Task 1

1. Find a point in your program that can be optimized (for speed), for example by using a profiler
2. Make a measurement of the point to optimize, for example by running a number of times, and calculating the mean and standard deviation (see the paper from Sestoft)
3. If you work on the letter frequencies program, make it at least 50% faster

1.1 Find a point in your program that can be optimized

We did not use a profiler. The reason is that we could not get the profiler to run in Visual Studio Code. We have however located multiple points in the program that can be optimized. Since we are reading a relatively big text-file, we believe it is here we can optimize the most. We took multiple steps to make the program faster as shown in the list below:

1. Upgrading the FileReader to a BufferedReader.
2. Replacing the “HashMap<Integer, Long>” with a “int[]”
3. Limiting the while loop to only saving letters A-Z

We’ve decided to measure the two methods in the program “tallyChars()” and “print_tally()”. We measure them together as a sequence to see the difference execution time on all our optimizations.

1.2 Make a measurement of the point to optimize

To make measurements we first had to create a timer that supports our measurements. The timer class can be found in “letterfrequencies/src/main/java/cph-business/ufo/letterfrequencies/Timer.java”.

Procedure

We've decided to make multiple measurements in order to create a realistic image of the run-times of both the optimized and non-optimized classes. The way we do this is by creating a loop and then run the two methods for a specified amount of iterations and writing each iterations run-time to a CSV file for the analysis.


We've chosen to use 500 continuous measurements to calculate the statistics afterwards.

1.3 Make it at least 50% faster


The task was to make the program 50% faster, and that has been achieved. Below are some tables and statistics along with a box-plot describing our results.

	Normal	Optimized
Mean	46,562ms	23,232ms
Std. dev	3,351510293	0,571690178
Min	40ms	23ms
1. Quatile	46ms	23ms
Median	47ms	23ms
3. Quartile	47ms	23ms
Max	99ms	26ms

From this data it is possible to create a box-plot to visualize the difference.



As it can be seen in the box-plot, there is a few outliers that could be removed. Especially from the Normal plot. With the outliers removed, the new boxplot looks like the plot below:



It is now possible to see that not only did we improve a whole lot on the execution-time, but we have also stabilized the system a whole lot. This is visible from observing the whiskers on each entry in the box-plot. As it is visible from the results table, the results have improved by a whole lot, but how much exactly? This depends on what you are measuring, we've decided that two of the numbers we can use to illustrate the improvements are the Mean and the Median. Therefore we have calculated how much the run-times have improved in percent. The results can be seen below:

Mean improvement	50,11%
Median improvement	51,06%

Results

In conclusion we have improved the program by approx. 50%-51%. But what is also worth noticing is the stabilization of the execution-times with our optimized solution.