

BUILT — Faster transport + a Performance toggle (v0.46.0)

Two RPS finishers: gzip + keep-alive on the wire, and a Modern/Lite/Legacy switch in Settings. Both additive; data, search and the 104th sheet are untouched.

1 · gzip + KEEP-ALIVE (every page load, automatically)

Keep-alive (HTTP/1.1)

one TCP connection reused
across every request
(Content-Length on all
responses) — less handshake
latency on slow links

gzip (Accept-Encoding aware)

compresses JSON / HTML / JS / SVG
when the browser sends gzip
skips < 512 B (overhead) and
already-compressed PNG / PDF
sets Vary: Accept-Encoding

Verified (curl)

- 2 KB JSON → 45 B gzipped (Content-Encoding: gzip)
- two requests served on ONE connection (keep-alive)
- small JSON (<512 B) left uncompressed
- image/png left uncompressed even when gzip offered
- no Accept-Encoding → full uncompressed body

Biggest win for the large home page + JSON results on a slow connection or an old box; zero UI change — it's in `_send()`.

2 · PERFORMANCE TOGGLE IN SETTINGS (manual override)

⚙ Settings → Performance (Retroactive Post-Support)

Auto

match this PC (the probe decides) — the default

Modern

full effects, server hi-fi loupe

Lite

effects off, lighter rendering

Legacy

Win 7 / Vista friendly

How it works:

- the choice is saved per-browser (localStorage 'rps.mode'); rps.js reads it and re-applies live — no reload
- it asks `/api/rps?mode=...` for that mode's flags, then toggles lite-effects + default DPI on the client
- the SERVER's mode (SQLite tuning + page cache) stays auto-picked from the real hardware — you can't mis-tune the DB by choosing a UI mode
- force the whole server at launch instead with `viewer_app.py --mode legacy` (or `?mode=` in the URL)