

Machine Learning Assignment – 02

Team:

BL.EN.U4AIE22118 - Ishvarya G

BL.EN.U4AIE22121 - Kavya Sree Kammari

BL.EN.U4AIE22151 - Sharanya V Thambi

Kavya Sree Kammari

Question – 1:

The code defines the functions `euclidean_distance`, `manhattan_distance`. that calculates the Euclidean distance between two vectors. Euclidean distance, also known as L2 norm, is a measure of the straight-line distance between two points in n-dimensional space. The function checks if the dimensions of the input vectors are the same, and if not, it raises a `ValueError`. The `Manhattan_distance` computes the sum of squares of the differences between corresponding elements of the vectors, takes the square root of this sum, and returns the Euclidean distance. Calculates the sum of absolute differences between corresponding elements of the vectors.

- Returns the sum of absolute differences, which represents the Manhattan distance.

Pseudocode:

Function euclidean_distance(vector1, vector2):

Find the length of the vectors

if length_1 \neq length_2:

Raise ValueError

sum_of_squares = 0

for i = 0 to length_1 - 1:

sum_of_squares += (vector1[i] - vector2[i])²

euclidean_dist = square root of sum_of_squares

return euclidean_dist

function manhattan_distance(vector1, vector2):

Find the length of the vectorsd

if length_1 \neq length_2:

Raise ValueError

```

sum_of_differences = 0
for i = 0 to length_1 - 1:
    sum_of_differences += absolute value of (vector1[i] - vector2[i])

return sum_of_differences

```

Question – 2:

In the code function named `knn_classify`, which implements the k-nearest neighbors (KNN) classification algorithm. This function takes three parameters: the training data set (`training_data`), a single test instance (`test_instance`), and the value of `k` (`k`) representing the number of nearest neighbors to consider for classification. It computes the Euclidean distance between the test instance and each data point in the training set, sorts the distances in ascending order, selects the `k` nearest neighbors, and then tallies the votes for each class label among these neighbors. Finally, it returns the class label that received the highest number of votes as the predicted label for the test instance.

Pseudocode:

```

Procedure knn_classify(training_data, test_instance, k):

    distances = empty list # List to save distance between each point

    for each row in training_data:

        Compute the Euclidean distance between the current training data point and
        the test instance

        Append a tuple containing the training data point and its distance to the
        distances list

    Sort the distances list based on the distance in ascending order

    Select the k nearest neighbors from the sorted distances list

    class_votes = empty dictionary # Dictionary to store votes for each class label

    for each neighbor in the k nearest neighbors:

```

Extract the class label of the neighbor

If the label is already in class_votes:

Increment its vote count

Else:

Initialize its vote count to 1

Return the class label with the maximum number of votes

Question – 3:

In this code, The function encodes categorical variables in the input DataFrame using label encoding. It replaces each unique categorical value in the DataFrame columns with a corresponding integer label. It returns the encoded DataFrame along with a dictionary containing label encoders for each column.

Pseudocode:

Procedure label_encoding(data):

encoded_data = make a copy of data # Avoid modifying the original data directly

label_encoders = empty dictionary

for each column in encoded_data:

if data type of column is 'object': # Check if the column contains categorical values

unique_labels = unique values in column

label_encoder = create a label encoder mapping each label to a unique integer

map labels in column to integer values using label_encoder

store label_encoder in label_encoders dictionary

return encoded_data, label_encoders

Question – 4:

This function performs one-hot encoding on categorical variables in the input DataFrame. It creates binary columns for each unique value in the categorical columns, indicating the presence or absence of that value in the original column. It returns the encoded DataFrame with one-hot encoded columns and a list of the names of these new columns.

Pseudocode:

Procedure one_hot_encoding(data):

encoded_data = make a copy of data # Avoid modifying the original data directly

one_hot_encoded_columns = empty list

for each column in encoded_data:

if data type of column is 'object': # Check if the column contains categorical values

unique_values = unique values in column

for each value in unique_values:

new_column_name = column_name + '_' + value # Create a new column name

create a new binary column indicating presence of value

append new_column_name to one_hot_encoded_columns

drop the original column from encoded_data

return encoded_data, one_hot_encoded_columns

Ishvarya G

In this program for questions 1,3 and 4, I have made the code modularized specific to each question's functionality. The main function provides the functionality of taking input from the user's end for each function and a call is made to the respective function to perform the operation, the result of which is displayed using the main function. However, for implementation of the K-NN classifier (Question 2) there is no main function. The code uses custom fit(), predict() functions without using any external ML libraries (except pandas that is used to load in the train and test csv files) for its implementation.

Question 1:

To calculate the Euclidean and Manhattan distance between 2 vectors whose dimensions are variable :

Explanation:

The code uses 2 For loops to loop through the range of numbers from 0 till the length of the vector. Using the formula of taking the sum of the squares of differences of elements of the 2 given vectors Euclidean distance is calculated. Similarly, for finding the Manhattan distance, the sum of the absolute differences of the vector elements is taken. Finally the calculated values are returned.

Pseudocode:

Function findEuclidean(INPUT vec1,vec2):

 SET euclidean=0

 FOR i in the range of length of vec2:

 #since the length of both the vectors must be equal : length of vec1 = length of vec2

 SET euclidean = euclidean + (vec2[i] - vec1[i]) ** 2

 REPEAT until i reaches the length of vec2

 RETURN sqrt(euclidean)

```

Function findManhattan( INPUT vec1,vec2):
    SET manhattan=0

    FOR j in the range of length of vec2:
        #since the length of both the vectors must be equal : length of vec1 = length of vec2
        SET manhattan= manhattan + abs(vec2[j] – vec1[j])

    REPEAT until i reaches the length of vec2

    RETURN sqrt(manhattan)

```

Question 2:

To implement K-NN classifier using a function :

Explanation:

The code defines a KNNclassifier class that initializes k (no.of neighbours to check for), fit() that just stores the train and test data to be used during predictions and the predict() function that has the function to calculate the Euclidean distances between each feature of the training and test samples and returns distances_for_test_point list, which is further sorted in ascending order. Then, we extract the indices of the first ‘k’ closest test points and also extract its corresponding labels. Among these, we find the majority of all the labels (taking the max()) and add it to the predictions_list for the test set.

Pseudocode :

```

class KNNclassifier:

    Function __init__(INPUT k):
        Initialize k

    Function fit(INPUT X_train, y_train):
        Store X_train and y_train as instance variables

```

Function predict(INPUT X_test,X_train):

 Function findEuclidean(vec1, vec2):

 #same as in Question 1

 Convert train and test set to NumPy arrays

 SET predictions_list to []

 FOR test_point in test_features:

 SET distances_for_test_point to []

 FOR train_point in train_features:

 SET distance to the result of the Euclidean distance between train
 and test points

 Append to the distances_for_test_point list

 SET sorted_indices to indices sorted in test_features according to
 the distances

 SET k_nearest_indices to the first k closest indices

 SET unique_labels = set(k_nearest_neighbours)

 SET prediction = max(unique_labels, count of k_nearest_labels as
 the key)

 Append predictions to predictions_list

 RETURN predictions_list

Load the data

Create the KNN classifier object

Call fit() method on X_train and y_train

Call the predict() method on X_test and X_train

DISPLAY the returned predictions

DISPLAY the accuracy

Question 3:

To convert categorical variables to numeric using label encoding :

Explanation:

This function aims to encode the categorical inputs to numeric values by converting assigning a unique number to each unique label in the data. It first finds the unique_labels by using the set() method and uses For loop to iterate through the unique labels and sets the corresponding index as its value.

Pseudocode :

Function encodeLabel (INPUT categ):

 SET label_mapping = {}

SET unique_labels to the unique labels in categ using set()

FOR index ,label in enumerate(unique_labels):

 SET label_mapping[label] to index

SET encoded_labels to [label_mapping[label] for label in categ]

 RETURN encoded_labels

Question 4:

To convert categorical variables to numeric using One-hot encoding :

Explanation:

This function aims to encode the categorical inputs to numeric values by converting assigning a binary value to each unique label in the data. It first finds the unique_labels by using the set() method then creates a list of lists that is filled with 0s whose row length is equal to the number of categorical variables and the column length is equal to the number of unique variables. We set the label_mapping to be equal to the corresponding index value. Then using 2 For loops we check if the value of j (iterable) matches the index of the label for current element in categ (categ[i]) , if so it sets the element in position i, j to 1. Finally it returns the encoded_labels.

Pseudocode:

Function encodeOneHot (INPUT categ):

 SET unique_labels to the unique labels in categ using set()

 SET encoded_labels to 0 where the rows is the length of items in categ and columns is the length of items in unique_labels

 SET label_mapping to {}

 FOR index ,label in enumerate(unique_labels):

 SET label_mapping[label] to index

 FOR i in range of length of categ:

 FOR j in range of length of unique_labels:

 Check if j matches the index of the label for the current element in categ:

 SET encoded_labels[i][j] = 1

RETURN encoded_labels

Sharanya VT

Question 1:

Pseudo code:

def euclidean(vector1,vector2,n):

sum initialised to 0

 loop i from 0 to n:

 Assign sum as sum+power of 2 of corresponding values of vectors
 subtracted

 Return square root of sum

def manhattan(vector1,vector2,n):

sum initialised to 0

 loop i from 0 to n:

 Assign sum as sum+absolute value of corresponding values of
 vectors subtracted

 Return sum

Question 2:

Pseudo code:

Def knnclassifier_sharanya():

Initialise a map for label encoding of target column ob BMI index

Change index column to the numerical values that was encoded

Create column for male and female and initialise it to 0

One hot encode it according to the gender value for each instance

Drop gender column

Reorder the columns and bring male and female to the beginning

Take a test vector to test the model

Create a distance column and initialise it to 0

Loop through the dataframe by calling indexes from 0 to length of dataframe:

Call the euclidean() and find distance between testvector and
instance_vector

Sort the data frame according to distance

Loop i through all values in map:

Loop j through 0 to k:

if (i==Index value of that instance):

sum=sum+1

save sum in a list sum_list

Max value of sum_list is found and then then position is stored

predicted target is the key corresponding to the position as value in map

Predicted target is returned

Question 3:

Pesudo code: