

Argumentation among Agents: Review and Commentary

Grigore Costin-Teodor
Vasiliu Florin

Radu Ștefan-Octavian
Vintilă Eduard

Introduction

- Reference: Iyad Rahwan's *Argumentation among Agents*, Chapter 5 in *Multiagent Systems*, by G. Weiss.

Introduction

- Reference: Iyad Rahwan's *Argumentation among Agents*, Chapter 5 in *Multiagent Systems*, by G. Weiss.
- Our contribution: several new examples, and proofs for some merely stated claims.

Introduction

- Reference: Iyad Rahwan's *Argumentation among Agents*, Chapter 5 in *Multiagent Systems*, by G. Weiss.
- Our contribution: several new examples, and proofs for some merely stated claims.
- What is the author attempting to formalize?

Introduction

- Reference: Iyad Rahwan's *Argumentation among Agents*, Chapter 5 in *Multiagent Systems*, by G. Weiss.
- Our contribution: several new examples, and proofs for some merely stated claims.
- What is the author attempting to formalize?
- The philosopher's view of argumentation: the giving of claims in favor or against a statement that is open for debate.

Prakken's framework, briefly

- Idea: generalize common logics by admitting two kinds of inference rules – *strict* and *defeasible*.

Prakken's framework, briefly

- Idea: generalize common logics by admitting two kinds of inference rules – *strict* and *defeasible*.
- An *argumentation system* is a tuple $(\mathcal{L}, cont, S, D)$.

Prakken's framework, briefly

- Idea: generalize common logics by admitting two kinds of inference rules – *strict* and *defeasible*.
- An *argumentation system* is a tuple $(\mathcal{L}, cont, S, D)$.
- \mathcal{L} is some “logical language” (must contain \neg).

Prakken's framework, briefly

- Idea: generalize common logics by admitting two kinds of inference rules – *strict* and *defeasible*.
- An *argumentation system* is a tuple $(\mathcal{L}, cont, S, D)$.
- \mathcal{L} is some “logical language” (must contain \neg).
- The function

$$cont : \mathcal{L} \rightarrow \mathcal{P}(\mathcal{L})$$

generalizes negation.

Prakken's framework, briefly

- Idea: generalize common logics by admitting two kinds of inference rules – *strict* and *defeasible*.
- An *argumentation system* is a tuple $(\mathcal{L}, cont, S, D)$.
- \mathcal{L} is some “logical language” (must contain \neg).
- The function

$$cont : \mathcal{L} \rightarrow \mathcal{P}(\mathcal{L})$$

generalizes negation.

- S, D are respectively the sets of strict/defeasible inference rules.

Prakken's framework, briefly

- How does the *cont* function generalize negation?

Prakken's framework, briefly

- How does the *cont* function generalize negation?
- If $\varphi \in \text{cont}(\psi)$, then
 - if $\psi \notin \text{cont}(\varphi)$, then φ is a *contrary* of ψ ;
 - if $\psi \in \text{cont}(\varphi)$, then φ and ψ are *contradictory*.

Prakken's framework, briefly

- How does the *cont* function generalize negation?
- If $\varphi \in \text{cont}(\psi)$, then
 - if $\psi \notin \text{cont}(\varphi)$, then φ is a *contrary* of ψ ;
 - if $\psi \in \text{cont}(\varphi)$, then φ and ψ are *contradictory*.
- It is mandatory that

$$\neg\varphi \in \text{cont}(\varphi) \quad \text{and} \quad \varphi \in \text{cont}(\neg\varphi)$$

for any formula φ .

Prakken's framework, briefly

- An *argument* from a knowledge base \mathcal{K} is defined similarly to a deduction in propositional logic. (The members of \mathcal{K} play the role of the hypotheses.)

Prakken's framework, briefly

- An *argument* from a knowledge base \mathcal{K} is defined similarly to a deduction in propositional logic. (The members of \mathcal{K} play the role of the hypotheses.)
- Major difference: incorporation of the used inference rules.

Prakken's framework, briefly

- An *argument* from a knowledge base \mathcal{K} is defined similarly to a deduction in propositional logic. (The members of \mathcal{K} play the role of the hypotheses.)
- Major difference: incorporation of the used inference rules.
- The complete framework contains a partial order on defeasible rules. Using it, arguments may be compared.

Dung's model

- Henceforth, an *argumentation framework* will mean a finite directed graph $(\mathcal{A}, \rightarrow)$, whose nodes are called “arguments”. The adjacency relation is pronounced “defeats”.

Dung's model

- Henceforth, an *argumentation framework* will mean a finite directed graph $(\mathcal{A}, \rightarrow)$, whose nodes are called “arguments”. The adjacency relation is pronounced “defeats”.
- Hence, for arguments p, q , “ $p \rightarrow q$ ” means “ p defeats q ”.

Dung's model

- Henceforth, an *argumentation framework* will mean a finite directed graph $(\mathcal{A}, \rightarrow)$, whose nodes are called “arguments”. The adjacency relation is pronounced “defeats”.
- Hence, for arguments p, q , “ $p \rightarrow q$ ” means “ p defeats q ”.
- Note how the structure of arguments is not taken into account anymore.

Dung's model

- Henceforth, an *argumentation framework* will mean a finite directed graph $(\mathcal{A}, \rightarrow)$, whose nodes are called “arguments”. The adjacency relation is pronounced “defeats”.
- Hence, for arguments p, q , “ $p \rightarrow q$ ” means “ p defeats q ”.
- Note how the structure of arguments is not taken into account anymore.
- Objective: define an “acceptable” argument.

Dung's model




Figure: Our argumentation framework.

- $S^+ =$ the set of arguments defeated by some member of S .

Dung's model




Figure: Our argumentation framework.

- S^+ = the set of arguments defeated by some member of S .
- In the figure, $\{p, q\}^+ = \{q, s, t\}$.

Dung's model




Figure: Our argumentation framework.

- a^- = the set of arguments which defeat a .

Dung's model




Figure: Our argumentation framework.

- a^- = the set of arguments which defeat a .
- In the figure, $s^- = \{p, s\}$.

Dung's model




Figure: Our argumentation framework.

- A set S of arguments is *conflict-free* if no argument in S defeats another also in S .

Dung's model




Figure: Our argumentation framework.

- A set S of arguments is *conflict-free* if no argument in S defeats another also in S .
- In the figure, $\{p, t\}$ and $\{r, t\}$ are conflict-free.

Dung's model




Figure: Our argumentation framework.

- A set S of arguments *defends* argument a if every argument which defeats a is defeated by S (i.e., is in S^+).

Dung's model




Figure: Our argumentation framework.

- A set S of arguments *defends* argument a if every argument which defeats a is defeated by S (i.e., is in S^+).
- In the figure, $\{p, t\}$ defends p .

Dung's model




Figure: Our argumentation framework.

- The *characteristic function* \mathcal{F} is defined thus:
 $\mathcal{F}(S) =$ the set of arguments defended by S .

Dung's model




Figure: Our argumentation framework.

- The *characteristic function* \mathcal{F} is defined thus:
 $\mathcal{F}(S)$ = the set of arguments defended by S .
- In the figure, $\mathcal{F}(\{p, q, r\}) = \{p, r, t\}$ and $\mathcal{F}(\{r, t\}) = \{r, t\}$.

Dung's model




Figure: Our argumentation framework.

- A *complete extension* is a set S of arguments which is conflict-free and such that $\mathcal{F}(S) = S$ (i.e., it defends its own members and nothing else).

Dung's model




Figure: Our argumentation framework.

- A *complete extension* is a set S of arguments which is conflict-free and such that $\mathcal{F}(S) = S$ (i.e., it defends its own members and nothing else).
- By the remarks on previous slides, $\{r, t\}$ is a complete extension.

Dung's model

- The author exhibits an equivalent characterization of complete extensions via *labellings*.

Dung's model

- The author exhibits an equivalent characterization of complete extensions via *labellings*.
- An argument p is:
 - *skeptically accepted* iff p belongs to every extension;
 - *credulously accepted* iff p belongs to some extension;
 - *rejected* iff p doesn't belong to any extension.

The Argument Interchange Format

- Stems from a need for standardized representations of arguments.

The Argument Interchange Format

- Stems from a need for standardized representations of arguments.
- Previous attempts unsuitable:

The Argument Interchange Format

- Stems from a need for standardized representations of arguments.
- Previous attempts unsuitable:
 - designed to be used with specific tools

The Argument Interchange Format

- Stems from a need for standardized representations of arguments.
- Previous attempts unsuitable:
 - designed to be used with specific tools
 - strong link between language and tool

The Argument Interchange Format

- Stems from a need for standardized representations of arguments.
- Previous attempts unsuitable:
 - designed to be used with specific tools
 - strong link between language and tool
 - neglected formal logic due to user experience focus

The Argument Interchange Format

- Objectives:

The Argument Interchange Format

- Objectives:
 - standardize communication between reasoning-based multi-agent systems

The Argument Interchange Format

- Objectives:
 - standardize communication between reasoning-based multi-agent systems
 - facilitate the creation of such systems

The Argument Interchange Format

- Objectives:
 - standardize communication between reasoning-based multi-agent systems
 - facilitate the creation of such systems
 - design an efficient and abstract format for exchanging data

The Argument Interchange Format

- Objectives:
 - standardize communication between reasoning-based multi-agent systems
 - facilitate the creation of such systems
 - design an efficient and abstract format for exchanging data
 - facilitate argument manipulation and visual representation

Foundational concepts of the AIF

- Arguments are composed of networks of interlinked nodes.

Foundational concepts of the AIF

- Arguments are composed of networks of interlinked nodes.
- Two types of nodes:

Foundational concepts of the AIF

- Arguments are composed of networks of interlinked nodes.
- Two types of nodes:
 - $\mathcal{N}_I \subset \mathcal{N}$, information nodes (I-nodes)

Foundational concepts of the AIF

- Arguments are composed of networks of interlinked nodes.
- Two types of nodes:
 - $\mathcal{N}_I \subset \mathcal{N}$, information nodes (I-nodes)
 - $\mathcal{N}_S \subset \mathcal{N}$, scheme nodes (S-nodes)
- Schemes are classes of reasoning patterns.

Foundational concepts of the AIF

- Arguments are composed of networks of interlinked nodes.
- Two types of nodes:
 - $\mathcal{N}_I \subset \mathcal{N}$, information nodes (I-nodes)
 - $\mathcal{N}_S \subset \mathcal{N}$, scheme nodes (S-nodes)
- Schemes are classes of reasoning patterns.
- Schemes are divided into:

Foundational concepts of the AIF

- Arguments are composed of networks of interlinked nodes.
- Two types of nodes:
 - $\mathcal{N}_I \subset \mathcal{N}$, information nodes (I-nodes)
 - $\mathcal{N}_S \subset \mathcal{N}$, scheme nodes (S-nodes)
- Schemes are classes of reasoning patterns.
- Schemes are divided into:
 - $\mathcal{S}^R \subset \mathcal{S}$, *rule of inference* schemes

Foundational concepts of the AIF

- Arguments are composed of networks of interlinked nodes.
- Two types of nodes:
 - $\mathcal{N}_I \subset \mathcal{N}$, information nodes (I-nodes)
 - $\mathcal{N}_S \subset \mathcal{N}$, scheme nodes (S-nodes)
- Schemes are classes of reasoning patterns.
- Schemes are divided into:
 - $\mathcal{S}^R \subset \mathcal{S}$, *rule of inference* schemes
 - $\mathcal{S}^C \subset \mathcal{S}$, *conflict* schemes

Foundational concepts of the AIF

- Arguments are composed of networks of interlinked nodes.
- Two types of nodes:
 - $\mathcal{N}_I \subset \mathcal{N}$, information nodes (I-nodes)
 - $\mathcal{N}_S \subset \mathcal{N}$, scheme nodes (S-nodes)
- Schemes are classes of reasoning patterns.
- Schemes are divided into:
 - $\mathcal{S}^R \subset \mathcal{S}$, *rule of inference* schemes
 - $\mathcal{S}^C \subset \mathcal{S}$, *conflict* schemes
 - $\mathcal{S}^P \subset \mathcal{S}$, *preference* schemes

Foundational concepts of the AIF

- S-nodes are actual *applications* of a scheme.

Foundational concepts of the AIF

- S-nodes are actual *applications* of a scheme.
- S-nodes are of three types, for each scheme class:

Foundational concepts of the AIF

- S-nodes are actual *applications* of a scheme.
- S-nodes are of three types, for each scheme class:
 - $\mathcal{N}_S^{RA} \subset \mathcal{N}_S$, rule of inference *application* nodes (*RA-nodes*)

Foundational concepts of the AIF

- S-nodes are actual *applications* of a scheme.
- S-nodes are of three types, for each scheme class:
 - $\mathcal{N}_S^{RA} \subset \mathcal{N}_S$, rule of inference *application* nodes (*RA-nodes*)
 - $\mathcal{N}_S^{CA} \subset \mathcal{N}_S$, conflict *application* nodes (*CA-nodes*)

Foundational concepts of the AIF

- S-nodes are actual *applications* of a scheme.
- S-nodes are of three types, for each scheme class:
 - $\mathcal{N}_S^{RA} \subset \mathcal{N}_S$, rule of inference *application* nodes (*RA-nodes*)
 - $\mathcal{N}_S^{CA} \subset \mathcal{N}_S$, conflict *application* nodes (*CA-nodes*)
 - $\mathcal{N}_S^{PA} \subset \mathcal{N}_S$, preference *application* nodes (*PA-nodes*)

Foundational concepts of the AIF

- S-nodes are actual *applications* of a scheme.
- S-nodes are of three types, for each scheme class:
 - $\mathcal{N}_S^{RA} \subset \mathcal{N}_S$, rule of inference *application* nodes (*RA-nodes*)
 - $\mathcal{N}_S^{CA} \subset \mathcal{N}_S$, conflict *application* nodes (*CA-nodes*)
 - $\mathcal{N}_S^{PA} \subset \mathcal{N}_S$, preference *application* nodes (*PA-nodes*)
- Example: $MP_1 \in \mathcal{N}_S^{RA}$, an RA-node implementing the modus ponens *rule of inference scheme* from propositional logic.

Argument network

- An argument network Φ is a graph, consisting of:

Argument network

- An argument network Φ is a graph, consisting of:
 - a set $\mathcal{N} = \mathcal{N}_I \cup \mathcal{N}_S$ of vertices

Argument network

- An argument network Φ is a graph, consisting of:
 - a set $\mathcal{N} = \mathcal{N}_I \cup \mathcal{N}_S$ of vertices
 - a binary relation $\xrightarrow{\text{edge}}: \mathcal{N} \times \mathcal{N}$, representing edges, with the restriction that $\forall i \in \mathcal{N}_I, \forall j \in \mathcal{N}_I, \nexists(i, j) \in \xrightarrow{\text{edge}}$

A simple argument

- A simple argument, in a network Φ and schemes \mathcal{S} is a tuple $\langle P, \tau, c \rangle$, where:

A simple argument

- A simple argument, in a network Φ and schemes \mathcal{S} is a tuple $\langle P, \tau, c \rangle$, where:
 - $P \subseteq \mathcal{N}_I$ is a set of I-nodes, constituting the premises

A simple argument

- A simple argument, in a network Φ and schemes \mathcal{S} is a tuple $\langle P, \tau, c \rangle$, where:
 - $P \subseteq \mathcal{N}_I$ is a set of I-nodes, constituting the premises
 - $\tau \in \mathcal{N}_S^{RA}$ is an *RA-node*

A simple argument

- A simple argument, in a network Φ and schemes \mathcal{S} is a tuple $\langle P, \tau, c \rangle$, where:
 - $P \subseteq \mathcal{N}_I$ is a set of I-nodes, constituting the premises
 - $\tau \in \mathcal{N}_S^{RA}$ is an *RA-node*
 - $c \in \mathcal{N}_I$ is an I-node representing the conclusion, with the condition that $\tau \xrightarrow{\text{edge}} c$, $\text{uses}(\tau, s)$, $s \in \mathcal{S}$ and $\forall p \in P$ there is $p \xrightarrow{\text{edge}} \tau$

Natural language arguments to AIF

- The argument:

Natural language arguments to AIF

- The argument:
(P_1) The sun's UV helps produce Vitamin D in your body

Natural language arguments to AIF

- The argument:
 - (P_1) The sun's UV helps produce Vitamin D in your body
 - (P_2) Vitamin D is good for your health

Natural language arguments to AIF

- The argument:
 - (P_1) The sun's UV helps produce Vitamin D in your body
 - (P_2) Vitamin D is good for your health
 - (C_1) Therefore, the sun's UV is good for your health

Natural language arguments to AIF

- The argument:
 - (P_1) The sun's UV helps produce Vitamin D in your body
 - (P_2) Vitamin D is good for your health
 - (C_1) Therefore, the sun's UV is good for your health
- We construct the tuple $A_1 = \langle \{P_1, P_2\}, HS_1, C_1 \rangle$, a simple argument in natural language, where $P_1, P_2 \in \mathcal{N}_I$ are premises and $C_1 \in \mathcal{N}_I$ is the conclusion. $HS_1 \in \mathcal{N}_S^{RA}$ is an RA-node, that uses the hypothetical syllogism scheme from propositional logic.

Natural language arguments to AIF




Figure: Argument network using natural language

Natural language arguments to AIF

- Coming up with a rebuttal:

Natural language arguments to AIF

- Coming up with a rebuttal:
(P_3) The sun's UV causes skin cancer

Natural language arguments to AIF

- Coming up with a rebuttal:
 - (P_3) The sun's UV causes skin cancer
 - (P_4) Skin cancer is bad for your health

Natural language arguments to AIF

- Coming up with a rebuttal:
 - (P_3) The sun's UV causes skin cancer
 - (P_4) Skin cancer is bad for your health
 - (C_2) Therefore, the sun's UV is bad for your health

Natural language arguments to AIF

- Coming up with a rebuttal:
 - (P_3) The sun's UV causes skin cancer
 - (P_4) Skin cancer is bad for your health
 - (C_2) Therefore, the sun's UV is bad for your health
- We use the previous simple argument
 $A_1 = \langle \{P_1, P_2\}, HS_1, C_1 \rangle$ and similarly define another simple argument $A_2 = \langle \{P_3, P_4\}, HS_2, C_2 \rangle$, where $P_3, P_4 \in \mathcal{N}_I$ are premises and $C_2 \in \mathcal{N}_I$ is the conclusion. $HS_2 \in \mathcal{N}_S^{RA}$ is an RA-node, that uses the hypothetical syllogism scheme from propositional logic. Conflict is displayed with CA-nodes NEG_1 and NEG_2 , instantiations of a conflict scheme based on propositional contraries.

Natural language arguments to AIF




Figure: Argument network containing a rebuttal in natural language