

Argumentation among Agents: Review and Commentary

Grigore Costin-Teodor
Vasiliu Florin

Radu Ștefan-Octavian
Vintilă Eduard

Introduction

- Reference: Iyad Rahwan's *Argumentation among Agents*, Chapter 5 in *Multiagent Systems*, by G. Weiss.

Introduction

- Reference: Iyad Rahwan's *Argumentation among Agents*, Chapter 5 in *Multiagent Systems*, by G. Weiss.
- Our contribution: several new examples, and proofs for some merely stated claims.

Introduction

- Reference: Iyad Rahwan's *Argumentation among Agents*, Chapter 5 in *Multiagent Systems*, by G. Weiss.
- Our contribution: several new examples, and proofs for some merely stated claims.
- What is the author attempting to formalize?

Introduction

- Reference: Iyad Rahwan's *Argumentation among Agents*, Chapter 5 in *Multiagent Systems*, by G. Weiss.
- Our contribution: several new examples, and proofs for some merely stated claims.
- What is the author attempting to formalize?
- The philosopher's view of argumentation: the giving of claims in favor or against a statement that is open for debate.

Prakken's framework, briefly

- Idea: generalize common logics by admitting two kinds of inference rules – *strict* and *defeasible*.

Prakken's framework, briefly

- Idea: generalize common logics by admitting two kinds of inference rules – *strict* and *defeasible*.
- An *argumentation system* is a tuple $(\mathcal{L}, cont, S, D)$.

Prakken's framework, briefly

- Idea: generalize common logics by admitting two kinds of inference rules – *strict* and *defeasible*.
- An *argumentation system* is a tuple $(\mathcal{L}, cont, S, D)$.
- \mathcal{L} is some “logical language” (must contain \neg).

Prakken's framework, briefly

- Idea: generalize common logics by admitting two kinds of inference rules – *strict* and *defeasible*.
- An *argumentation system* is a tuple $(\mathcal{L}, cont, S, D)$.
- \mathcal{L} is some “logical language” (must contain \neg).
- The function

$$cont : \mathcal{L} \rightarrow \mathcal{P}(\mathcal{L})$$

generalizes negation.

Prakken's framework, briefly

- Idea: generalize common logics by admitting two kinds of inference rules – *strict* and *defeasible*.
- An *argumentation system* is a tuple $(\mathcal{L}, cont, S, D)$.
- \mathcal{L} is some “logical language” (must contain \neg).
- The function

$$cont : \mathcal{L} \rightarrow \mathcal{P}(\mathcal{L})$$

generalizes negation.

- S, D are respectively the sets of strict/defeasible inference rules.

Prakken's framework, briefly

- How does the *cont* function generalize negation?

Prakken's framework, briefly

- How does the *cont* function generalize negation?
- If $\varphi \in \text{cont}(\psi)$, then
 - if $\psi \notin \text{cont}(\varphi)$, then φ is a *contrary* of ψ ;
 - if $\psi \in \text{cont}(\varphi)$, then φ and ψ are *contradictory*.

Prakken's framework, briefly

- How does the *cont* function generalize negation?
- If $\varphi \in \text{cont}(\psi)$, then
 - if $\psi \notin \text{cont}(\varphi)$, then φ is a *contrary* of ψ ;
 - if $\psi \in \text{cont}(\varphi)$, then φ and ψ are *contradictory*.
- It is mandatory that

$$\neg\varphi \in \text{cont}(\varphi) \quad \text{and} \quad \varphi \in \text{cont}(\neg\varphi)$$

for any formula φ .

Prakken's framework, briefly

- An *argument* from a knowledge base \mathcal{K} is defined similarly to a deduction in propositional logic. (The members of \mathcal{K} play the role of the hypotheses.)

Prakken's framework, briefly

- An *argument* from a knowledge base \mathcal{K} is defined similarly to a deduction in propositional logic. (The members of \mathcal{K} play the role of the hypotheses.)
- Major difference: incorporation of the used inference rules.

Prakken's framework, briefly

- An *argument* from a knowledge base \mathcal{K} is defined similarly to a deduction in propositional logic. (The members of \mathcal{K} play the role of the hypotheses.)
- Major difference: incorporation of the used inference rules.
- The complete framework contains a partial order on defeasible rules. Using it, arguments may be compared.

Dung's model

- Henceforth, an *argumentation framework* will mean a finite directed graph $(\mathcal{A}, \rightarrow)$, whose nodes are called “arguments”. The adjacency relation is pronounced “defeats”.

Dung's model

- Henceforth, an *argumentation framework* will mean a finite directed graph $(\mathcal{A}, \rightarrow)$, whose nodes are called “arguments”. The adjacency relation is pronounced “defeats”.
- Hence, for arguments p, q , “ $p \rightarrow q$ ” means “ p defeats q ”.

Dung's model

- Henceforth, an *argumentation framework* will mean a finite directed graph $(\mathcal{A}, \rightarrow)$, whose nodes are called “arguments”. The adjacency relation is pronounced “defeats”.
- Hence, for arguments p, q , “ $p \rightarrow q$ ” means “ p defeats q ”.
- Note how the structure of arguments is not taken into account anymore.

Dung's model

- Henceforth, an *argumentation framework* will mean a finite directed graph $(\mathcal{A}, \rightarrow)$, whose nodes are called “arguments”. The adjacency relation is pronounced “defeats”.
- Hence, for arguments p, q , “ $p \rightarrow q$ ” means “ p defeats q ”.
- Note how the structure of arguments is not taken into account anymore.
- Objective: define an “acceptable” argument.

Dung's model




Figure: Our argumentation framework.

- $S^+ =$ the set of arguments defeated by some member of S .

Dung's model




Figure: Our argumentation framework.

- $S^+ =$ the set of arguments defeated by some member of S .
- In the figure, $\{p, q\}^+ = \{q, s, t\}$.

Dung's model




Figure: Our argumentation framework.

- a^- = the set of arguments which defeat a .

Dung's model




Figure: Our argumentation framework.

- a^- = the set of arguments which defeat a .
- In the figure, $s^- = \{p, s\}$.

Dung's model




Figure: Our argumentation framework.

- A set S of arguments is *conflict-free* if no argument in S defeats another also in S .

Dung's model




Figure: Our argumentation framework.

- A set S of arguments is *conflict-free* if no argument in S defeats another also in S .
- In the figure, $\{p, t\}$ and $\{r, t\}$ are conflict-free.

Dung's model




Figure: Our argumentation framework.

- A set S of arguments *defends* argument a if every argument which defeats a is defeated by S (i.e., is in S^+).

Dung's model




Figure: Our argumentation framework.

- A set S of arguments *defends* argument a if every argument which defeats a is defeated by S (i.e., is in S^+).
- In the figure, $\{p, t\}$ defends p .

Dung's model




Figure: Our argumentation framework.

- The *characteristic function* \mathcal{F} is defined thus:
 $\mathcal{F}(S) =$ the set of arguments defended by S .

Dung's model




Figure: Our argumentation framework.

- The *characteristic function* \mathcal{F} is defined thus:
 $\mathcal{F}(S)$ = the set of arguments defended by S .
- In the figure, $\mathcal{F}(\{p, q, r\}) = \{p, r, t\}$ and $\mathcal{F}(\{r, t\}) = \{r, t\}$.

Dung's model




Figure: Our argumentation framework.

- A *complete extension* is a set S of arguments which is conflict-free and such that $\mathcal{F}(S) = S$ (i.e., it defends its own members and nothing else).

Dung's model




Figure: Our argumentation framework.

- A *complete extension* is a set S of arguments which is conflict-free and such that $\mathcal{F}(S) = S$ (i.e., it defends its own members and nothing else).
- By the remarks on previous slides, $\{r, t\}$ is a complete extension.

Dung's model

- The author exhibits an equivalent characterization of complete extensions via *labellings*.

Dung's model

- The author exhibits an equivalent characterization of complete extensions via *labellings*.
- An argument p is:
 - *skeptically accepted* iff p belongs to every extension;
 - *credulously accepted* iff p belongs to some extension;
 - *rejected* iff p doesn't belong to any extension.