



Ministry
of Defence



Defence Fire and Rescue Tactics Techniques Procedure

| | |
|-----------------------------|---|
| Document No: | ATTP-A034-V1.2 |
| Title: | Augusta 109 |
| Date Issued: | 22 01 2025 |
| Supersedes: | 04 01 2023 |
| Review Date: | 01 01 2030 |
| Stakeholders: | DFR HQ ✓ Capita Fire and Rescue ✓ RN Aircraft Handler ¹ ✓ RAF Fire and Rescue ✓ DFRS LEC ✓ Other FRS Providers ² DFRS (DFSR, DIO, RN) ³ ✓ DFRS (USVF) |
| Technical Author(s): | Fire Station SMEs |
| Approved Authority: | DFR Sponsored Ops Policy Committee |

Sponsor Details: Strategic Lead Operational Capability & Development
Defence Fire & Rescue (DFR) Headquarters
Sedgemoor Building, Marlborough Lines,
Monxton Road,
Andover,
Hampshire,
SP11 8HT

Contact: dfr-hqocd@mod.gov.uk

Conditions of Release

1. This information is Crown Copyright and the intellectual property rights for this publication belong exclusively to the Ministry of Defence (MOD). No material or information contained in this publication should be reproduced, stored in a retrieval system or transmitted in any form outside MOD establishments except as authorised by both the sponsor and the MOD where appropriate.
2. This information is released by the United Kingdom Government to a recipient Government for defence purposes only. It may be disclosed only within the Defence Department of a recipient Government, except as otherwise authorised by the MOD.
3. This information may be subject to privately owned rights.
4. This ATTP has been subject to a DFR HQ Equality Impact Assessment.
5. On initial release a publication will be reviewed at the 12-month point, following which reviews will be 5 yearly or where changes in circumstances warrant a review.

¹ RN (AH) stakeholders are the Operational Responders based at the Culdrose, Predannack, Yeovilton and Merryfield aerodromes

² Other FRS Providers include Babcock, Mitie and QinetiQ Fire Services. In addition, this publication will also be shared with AWE and QinetiQ FRS for information purposes only.

³ For the purposes of this ATTP, DFRS Fire Officers employed within DFRS, DIO & RN, are included for information purposes only.

VERSION CONTROL HISTORY

| Version | Date | Amended by | Role | Change | Status |
|---------|------------|---------------|--------------------------|--|-------------|
| V1.0 | 21/10/2022 | Sgt Patterson | F.S. Trng Mngr | | draft |
| V1.1 | 22/11/2022 | C Freeborn | FSM | Minor Amendments | Final Draft |
| V1.1 | 06/01/2023 | P McGuinness | Hd of Response | | Issued |
| V1.2 | 16/10/2024 | P McGuinness | Hd of Response | 1. New Cover and layout. 2. Change of Sponsor. 3. Combined Engine / External Fire ATTP | For review |
| V1.2 | 19/12/2024 | C Smith | (Sgt) Fftr RAF Odiham | Station reviewer | Reviewed |
| V1.2 | 22/01/2025 | Shane Cook | AM for DFR HQ | Stakeholder Review | For issue |
| V1.2 | 22/01/2025 | P McGuinness | Hd of Response | Re-issued | Re-issued |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |




AIRCRAFT TACTICS TECHNIQUES PROCEDURES

1 x MPRV⁴

| | |
|-----------------------------------|--------|
| Version Control | Page 2 |
| TTP 1 - Engine Fire/External Fire | Page 3 |
| TTP 2 - Wheel Assembly Incidents | Page 6 |
| TTP 3 - Internal Fire | Page 9 |

TTP 1 – Engine/External Fire

Event Plan - Initial Deployment



Incident Commander Considerations:

- Conduct and complete DRA
- Order BA Team to don BA using Rapid Deployment procedures
- Declare Tactical Mode
- Consider required agencies and resources
- Consider implementing Major Incident Plan
- Direct firefighting actions to create survivable conditions
- Consider mass discharge from monitor
- Consider use of secondary media
- Consider contacting aircraft commander via ATC or 121.6 if available
- Be aware of PAX exiting aircraft
- Direct BA rescue crew
- Direct Medical Teams
- Direct all operational control and implement ICS
- Provide M/ETHANE report
- Maintain safe operations and ensure scene safety
- Direct other agencies
- Consider media run-off and water courses on scene.
- Consider preservation of evidence

⁴H1 Response: Consisting of single MPRV (or RRV), c/w a crew of 4.

- Instigate JESIP for multi-agency incident.

Crash 1 - MPRV Actions:

- Deploy vehicle to aircraft nose
- Be aware of PAX and assist them exiting the aircraft
- Direct personnel away from the airframe
- Consider use of monitor to extinguish fire
- Consider use of secondary agents.
- Consider method of entry if PAX remain onboard
- Don BA and instigate Rapid Deployment Procedures if required
- Deploy media with sufficient lengths of 45mm hose/hose reel as determined by IC
- DRA and prepare for entry into aircraft
- BA team access aircraft and create survivable conditions if required
- Confirm/make safe aircraft systems
- Utilise Medics to triage casualties on board if survivable conditions are present
- Aid Medics in extricating casualties
- Consider use of auxiliary equipment such as TIC
- Carry out external airframe cooling as required
- Provide scene safety.
- **No internal entry to airframe should take place until all external fires are extinguished or declared as under control.**

Specific Aircraft Hazards: (Make use of AQRC):

- Rotors
- Flammable liquids
- Flammable/pressurised gases
- Composite aircraft materials

Further Considerations:

- Aircraft position and wreckage
- Leaking fuel
- Aircrew
- Other agencies.

Supporting Information:

- DFR-OG 009 - Aircraft Fires
- Op Instruction 001 - Aircraft Incidents
- Op Instruction 002 - CFR HSE Policy
- Op Instruction 005 - Low Speed Manoeuvring
- Op Instruction 006 - MPRV ARFF Positioning Deployment & Task
- Op Instruction 007 - MPRV Vehicle Operations
- Op Instruction 033 - BA Operations
- Op Instruction 066 - Fire Contaminants
- Op Instruction 069 - Polymer-Composites-and-MMMF
- Op Guidance 001 - Aircraft Incidents
- Op Guidance 002 - Incidents Involving Rotary Wing Aircraft
- Op Guidance 005 - Incidents Involving Small Aircraft


- Op Guidance 007 - Aircraft Engine Fire
- MOD Aircraft Crash Hazards Document Set
- NATO STANAG / TO 00-105E-9-Chapter 13 (revision 16)
- DSA 1000m assessments
- DSA Water assessments
- DSA Response assessments

Training:

- Aircraft familiarisation
- Deployment exercise(s)
- Redkite CMS
- Aircraft lecture - 6 monthly lesson / familiarisation presentation

TTP 2 – Wheel Assembly Incidents

Event Plan - Initial Deployment



Incident Commander Considerations:

- Conduct and complete DRA
- Order BA Team to don BA using Rapid Deployment
- Declare Tactical Mode
- Consider required agencies and resources
- Consider implementing Major Incident Plan
- Direct firefighting actions to create survivable conditions
- Consider mass discharge from monitor
- Consider use of secondary media

- Consider contacting aircraft commander via ATC or 121.6 if available
- Be aware of PAX exiting aircraft
- Direct BA rescue crew
- Direct Medical Teams
- Direct all operational control and implement ICS
- Provide M/ETHANE report
- Maintain safe operations and ensure scene safety
- Direct other agencies
- Consider media run-off and water courses on scene.
- Consider preservation of evidence
- Instigate JESIP for multi-agency incident.

Crash 1 - MPRV Actions:

- Crash 1 to deploy on the relevant affected undercarriage area, taking into consideration wind direction, gradient, and passengers exiting.
- Direct personnel away from the airframe
- Consider use of monitor and extinguish fire
- Consider use of secondary agents
- Consider use of in-situ airfield FAFAs
- Consider method of entry if PAX remain onboard
- Don BA and instigate Rapid Deployment Procedures if required
- Deploy media with sufficient lengths of 45mm hose/hose reel as determined by IC DRA and prepare for entry into aircraft
- BA team access aircraft and create survivable conditions if required
- Confirm/make safe aircraft systems
- Utilise Medics to triage casualties on board if survivable conditions are present
- Aid Medics in extricating casualties
- Consider use of auxiliary equipment such as Raytec
- Carry out external airframe cooling as required.
- Maintain contact with IC
- Provide scene safety.
- **Note: No internal entry to airframe should take place until all external fires are extinguished or declared as under control.**

Specific Aircraft Hazards

- Rotors
- Weapons / Pyrotechnics
- Flammable liquids
- Flammable/pressurised gases
- Composite Materials
- Oleo Leg Collapsing

Further Considerations

- The actions during this incident will be dependent on the following conditions:
 - Is the wheel assembly on fire?
 - Is the fire confined to one area or is escalation likely upon undercarriage collapse
- Dependent on the severity of the fire, crew commander may request use handheld extinguishers
- Aircrew will commence shutting down of A/C systems and self-extract if possible

Training:


- Aircraft familiarization – Sqn personnel
- Endorsed PPT
- Redkite CMS.

Supporting Information:

- DFR-OG 009 - Aircraft Fires
- Op Instruction 001 - Aircraft Incidents
- Op Instruction 002 - CFR HSE Policy
- Op Instruction 005 - Low Speed Manoeuvring
- Op Instruction 006 - MPRV ARFF Positioning Deployment & Task
- Op Instruction 007 - MPRV Vehicle Operations
- Op Instruction 033 - BA Operations
- Op Instruction 066 - Fire Contaminants
- Op Instruction 069 - Polymer-Composites-and-MMMF
- Op Guidance 001 - Aircraft Incidents
- Op Guidance 002 - Incidents Involving Rotary Wing Aircraft
- Op Guidance 005 - Incidents Involving Small Aircraft
- Op Guidance 007 - Aircraft Engine Fire
- Op Guidance 008 - Aircraft Undercarriage Incidents
- MOD Aircraft Crash Hazards Document Set
- NATO STANAG / TO 00-105E-9-Chapter 13 (revision 16)
- DSA 1000m assessments
- DSA Water assessments
- DSA Response assessments

TTP 3 – Internal fire Incidents

Event Plan - Initial Deployment



Incident Commander Considerations:

- Emergency declared
- Location of A/C
- POB
- Wind Direction
- Confirm with all crew's nature of incident and location
- Evacuating PAX
- DRA followed by M/ETHANE
- Inform ATC of Tactical Mode & request external resources
- Consider contacting aircraft commander via ATC or 121.6 if available
- Repeat DRA as appropriate to the incident
- Prepare for ARA
- Declare state of Airfield and ICAO category

- Consider use of secondary media.
- Direct evacuated passengers / crew to safe holding area prior to designated casualty clearance set up by Medics.
- Direct Medics to SUV location (if resourced)
- SENG/Sqn Support
- LAFRS
- Ensure safe handover of incident when declared safe to relevant authority
- Debrief all crew's post-incident and identify any further support required.

Crash 1 - MPRV Actions

- Crash 1 to deploy on the port side of the A/C, this will give easy access if a BA team is needed to make entry
- Designated BA wearers will don BA sets but remain off air until instruction from Incident Commander
- Initially crew will respond and assist evacuating passengers/crew who will be directed towards the SUV and away from danger area (if resourced)
- Vehicle Commander will identify entry points to aircraft if required
- Deploy sufficient lengths of hose (45mm) or hose reel dependent upon the IC's DRA, for preparation for entry into airframe if required
- If BA entry is required instruction will be given by Incident Commander. BA Team will deploy according to current SOP with 45mm sideline or hose reel as appropriate to the incident
- BA team should consider use of thermal image camera to identify internal hot spots
- BA team aim will be to ensure survivable conditions therefore ventilation should be considered at the earliest opportunity and reported to Incident Commander
- Remove any casualties as appropriate and according to SOP.
- **No internal entry to airframe should take place until all external fires are extinguished or declared as under control.**

Specific Aircraft Hazards – (Make use of AQRC):

- Propellers
- Flammable liquids
- Pressurised gases
- Mk 9 oxygen masks are kept onboard for aircrew to use in the case of being trapped in a smoke-filled environment. They will last between 15-20mins depending on activity levels.

Further Considerations:

- Ventilation priority
- BA teams
- Mark 9 oxygen masks are kept onboard for aircrew to use in the case of being

trapped in a smoke-filled environment. They will last between 15- 30 mins depending on activity levels

- BA Teams are to note that access to rescue the occupants is very tight
- Due to irrespirable atmosphere, should crew be trapped but are under A/C system oxygen prior to ventilation, then consideration should be given to a DRA being carried out to leave the casualties in situ until medical personnel can access the A/C to assess them
- As part of 14 SQN SOP's the aircraft will be shut down prior to evacuation.
- Aircrew SOPs require evacuation via the main front port side exit in the event of an emergency
- Shut down aircraft i.a.w SQN SOP.

Training:

- Aircraft familiarization – Sqn personnel
- Endorsed PPT
- Redkite CMS.

Supporting Information:

- DFR-OG 009 - Aircraft Fires
- Op Instruction 001 – Aircraft Incidents
- Op Instruction 002 – CFR HSE Policy
- Op Instruction 005 – Low Speed Manoeuvring
- Op Instruction 006 – MPRV ARFF Positioning Deployment & Task
- Op Instruction 007 – MPRV Vehicle Operations
- Op Instruction 018 – SUV positioning Deployment & Task
- Op Instruction 033 – BA Operations
- Op Instruction 066 – Fire Contaminants
- Op Instruction 069 – Polymer-Composites-and-MMMF
- Op Guidance 001 – Aircraft Incidents
- Op Guidance 003 – Aircraft Fuel Fires and Foam Application
- Op Guidance 005 – Incidents Involving Small Aircraft
- Op Guidance 006 – Aircraft Internal Fires
- Op Guidance 008 – Aircraft Undercarriage Incidents
- MOD Aircraft Crash Hazards Document Set
- NATO STANAG/TO 00-105E-9-Chapter 13 (revision 16).
- www.fast-air.co.uk
- www.flightglobal.com MOD Aircraft Crash Hazards Document Set.