A-7679-PGE-LR1 THREE PHASE RECLOSER CONTROL AND CABINET
Part Number: **A-7679-PGE-LR1** consists of:

M-7679 – RECLOSER CONTROL
SMART MODEL NUMBER: M-7679-V6L1LL6ELV2CC26X

Consists of the following:
M-7679-
V - VERTICAL MOUNTING
6 - 60Hz FREQUENCY
L - LOW VOLT, 18-60VDC
1 - 1A PHASE CURRENT INPUTS (3)
L - 10mA SEF IG CURRENT INPUT (REQUIRED FOR DCD FUNCTION)
L6 - (6) 12 VAC MAX VOLTAGE INPUTS
EL - EXPANDED I/O(STD+8) LV(18-60VDC)
V - RECLOSER + SWITCH/SECTIONALIZER THREE PHASE GANGED
2 - PORT 1 TIA-232 COMM PORT
CC - PORT 2 & 3 RJ-45 10/100 MBPS ETHERNET
2 - TIA-232 PORT 4 SERIAL
6 - IEC61850 PROTOCOL
X - CUSTOMER REQUIREMENTS (CSR-7679-PGELR1) (Custom settings, custom DNP map, custom buttons and labels, firmware lock)

M-2979 – RECLOSER CONTROL CABINET
SMART MODEL NUMBER: M-2979-A42B0133Q20SUTYX

Consists of the following:
M-2979-
A - ALUMINUM, POWDER COATED GRAY
42B - 42-PIN MULTI RECLOSER INTERFACE (REQUIRES EXP. IO OPTION IN CONTROL)
0 - VOLTAGE SENSING INTERFACE: NONE
1 - POWER INPUT TO CABINET 120 VAC
33Q - 2X3-PIN SOCKETS (QUICK LOCK 2 SRC) W/ATS
20 - 2 x 12VDC 20AH BATTERY
S - UNIVERSAL RADIO SHELF
U - US TYPE OUTLET
T - 50W HEATER / THERMOSTAT
Y - FACTORY INSTALLED ACCESSORIES:
☐ N-2979-IDS – INTRUSION DETECTION
☐ N-2979-LTT - DOOR MOUNTED FOLDING LAPTOP TRAY

X - CUSTOMER SPECIFIC REQUIREMENTS: CSR-2979-PGELR1 which includes:
☐ **B-1794** –QTY 1 *CONNECTOR LOCK FOR 42 PIN CABINET CONNECTOR*
☐ **B-1816** –QTY 2 *SECURITY SLEEVE FOR 3 PIN CABINET CONNECTORS*
☐ *B-1904* –QTY 1 4" STANDOFF KIT FOR CABINET (bracket is made of 6063/T6 Aluminum & the hardware is 18-8 Stainless Steel) 2 brackets per kit