

# DSC 190

DATA STRUCTURES & ALGORITHMS

## Abstract Data Types

# Python's `list`

- ▶ You can go a long time without ever knowing how `list` is **implemented**.
- ▶ But you knew its **interface**.
  - ▶ supports `.append`, random access, is ordered, etc.

# Abstract vs. Concrete

- ▶ An **abstract data type** (ADT) is a formal description of a type's **interface**.
- ▶ A **data structure** is a concrete strategy for implementing an abstract data type.
  - ▶ Describes how data is stored in memory.
  - ▶ How to access the data.

# Example: Stacks

- ▶ A **stack** is an ADT which supports two operations:
  - ▶ push: put a new object on to the “top”
  - ▶ pop: remove and return item at the “top”
- ▶ Most often implemented using **linked lists**.
- ▶ But can also be implement with **(dynamic) arrays**.

## Main Idea

A given abstract data type can be implemented in several ways, but some data structures are more natural choices than others.

## Main Idea

The data structure (not the abstract data type) determines the time complexity of operations.

# Building Blocks

- ▶ Data structures are used to implement ADTs.
- ▶ But they are also used to implement more advanced data structures.
  - ▶ Example: arrays used to implement dynamic arrays.
- ▶ Arrays, linked lists are basic building blocks.

# DSC 190

DATA STRUCTURES & ALGORITHMS

## Priority Queues



# Priority Queues

- ▶ A **priority queue** is an abstract data type representing a collection.
- ▶ Each element has a **priority**.
- ▶ Supports operations<sup>1</sup>:
  - ▶ `.pop_highest_priority()`
  - ▶ `.insert(value, priority)`
  - ▶ `.is_empty()`

---

<sup>1</sup>and possibly more, like `.increase_priority`

# Example

```
>>> er = PriorityQueue()
>>> er.insert('flu', priority=1)
>>> er.insert('heart attack', priority=20)
>>> er.insert('broken hand', priority=10)
>>> er.pop_highest_priority()
'heart attack'
>>> er.pop_highest_priority()
'broken hand'
```

# Applications

- ▶ Scheduling.
- ▶ Simulations of future events.
- ▶ Useful in algorithms.
  - ▶ Example: Prim's MST algorithm

# Array Implementation

- ▶ We *can* implement a priority queue with a **(dynamic) array**.
- ▶ `.insert(k, p)`
  - ▶ append (value, priority) pair:  $\Theta(1)$  time
- ▶ `.pop_highest_priority()`
  - ▶ find entry with highest priority:  $\Theta(n)$  time
  - ▶ remove it:  $O(n)$  time

# Array Implementation (Variant)

- ▶ Alternatively, maintain dynamic array in sorted order of priority.
- ▶ `.insert(k, p)`
  - ▶ find place in sorted order:  $\Theta(\log n)$  time worst case
  - ▶ actually insert:  $\Theta(n)$  time worst case
- ▶ `.pop_highest_priority()`
  - ▶ remove/return last entry:  $\Theta(1)$  time

## Main Idea

If we made no insertions/deletions, a sorted array would be great. But we want a data structure with quick remove/return even after being modified.

# DSC 190

DATA STRUCTURES & ALGORITHMS

## Binary Heaps


# Binary Heaps

- ▶ A **binary heap** is a **binary tree** data structure often used to implement **priority queues**.




# Binary Trees


- Each node has **at most** two children (left, right).



# Example




# Example




# Complete Binary Trees

- ▶ A binary tree is **complete** if every level is filled, except for possibly the last (which fills from left to right).




# Node Height

- ▶ The **height** of node in a tree is the largest number of edges along any path to a leaf.
- ▶ The **height** of a tree is the height of the root.



# Complete Tree Height

- The height of a complete binary tree with  $n$  nodes is  $\Theta(\log n)$ .



# Binary Heap Properties


- ▶ A **binary max heap**<sup>2</sup> is a binary tree with three additional properties:
  1. Each node has a **key**.
  2. **Shape**: the tree is complete.
  3. **Max-Heap**: the key of a node is  $\geq$  the key of each of its children.

---

<sup>2</sup>There's also a min heap, of course.

# Example


- This is a binary max-heap.





# Example


- This is **not** a binary max-heap.




# Representation

- ▶ One representation: nodes are objects with pointers to children.
- ▶ But due to completeness property, we can store a binary heap in a (dynamic) array.

# Array Representation




- ▶ `.left_child(i)`
- ▶ `.right_child(i)`
- ▶ `.parent(i)`



# Operations

- ▶ `.max()`
  - ▶ Return (but do not remove) the max key
- ▶ `.increase_key(i, new_key)`
  - ▶ Increase key of node  $i$ , maintaining heap
- ▶ `.insert(key)`
  - ▶ Insert new node, maintaining heap
- ▶ `.pop_max()`
  - ▶ Remove max-key node, return key

.max



80	53	40	35	30	37	31	10	17	15	29	5
0	1	2	3	4	5	6	7	8	9	10	11

.max

```
class MaxHeap:
```

```
    def __init__(self, keys=None):  
        if keys is None:  
            keys = []  
        self.keys = keys
```


```
    def max(self):  
        return self.keys[0]
```

**.max**

- ▶ Takes  $\Theta(1)$  time.

# .increase\_key

.increase\_key(9, key=60)





## .increase\_key


```
def increase_key(self, ix, key):  
    if key < self.keys[ix]:  
        raise ValueError('New key is smaller.')  
  
    self.keys[ix] = key  
    while (  
        parent(ix) >= 0  
        and  
        self.keys[parent(ix)] < key  
    ):  
        self._swap(ix, parent(ix))  
        ix = parent(ix)
```

**.increase\_key**

- ▶ Takes  $O(\log n)$  time.

# .insert

.insert(key=60)



80	53	40	35	30	37	31	10	17	15	29	5
----	----	----	----	----	----	----	----	----	----	----	---

0 1 2 3 4 5 6 7 8 9 10 11

## .insert

```
def insert(self, key):  
    self.keys.append(key)  
    self.increase_key(  
        len(self.keys)-1, key  
    )
```


## **.insert**

- ▶ Takes  $O(\log n)$  time (amortized)<sup>3</sup>.

---

<sup>3</sup>If we use a static array the worst case is  $\Theta(\log n)$

# • pop\_max\_key



## • pop\_max\_key

```
def pop_max_key(self):  
    if len(self.keys) == 0:  
        raise IndexError('Heap is empty.')  
    highest = self.max()  
    self.keys[0] = self.keys[-1]  
    self.keys.pop()  
    self._push_down(0)  
    return highest
```

## • `_push_down(i)`

- ▶ Assume that left and right subtrees of node  $i$  are max heaps, but key of  $i$  is possibly too small.
- ▶ Push it down until heap property satisfied.
  - ▶ Recursively swap with largest of left and right child.



## • `_push_down()`

```
def _push_down(self, i):
    left = left_child(i)
    right = right_child(i)
    if (
        left < len(self.keys)
        and
        self.keys[left] > self.keys[i]
    ):
        largest = left
    else:
        largest = i

    if (
        right < len(self.keys)
        and
        self.keys[right] > self.keys[largest]
    ):
        largest = right

    if largest != i:
        self._swap(i, largest)
        self._push_down(largest)
```

## • `pop_max_key`

- ▶ `._push_down(i)` takes  $O(h)$  where  $h$  is  $i$ 's height
- ▶ Since  $h = O(\log n)$ , `pop_max_key` takes  $O(\log n)$  time.

# Summary

For a binary heap<sup>4</sup>:

.max	$\Theta(1)$
.increase_key	$O(\log n)$
.insert	$O(\log n)$
.pop_max_key	$O(h) = O(\log n)$

---

<sup>4</sup>There are other heap data structures. Fibonacci heaps have  $\Theta(1)$  insert and increase key, but slower for small  $n$ .

# Implementing Priority Queues

- ▶ Can use max heaps to implement priority queues.
- ▶ But a priority queue has values *and* keys.

```
pq.insert('heart attack', priority=20)
```

# Trick

- ▶ Heap keys need not be integers.
- ▶ Need only be comparable.
- ▶ Can store key and value with a **tuple**.

# Tuple Comparison

- ▶ In Python, tuple comparison is lexicographical.
  - ▶ Compare first entry; if tie, compare second, etc.

```
>>> (10, 'test') > (5, 'zzz')
```

```
True
```

```
>>> (10, 'test') > (10, 'zzz')
```

```
False
```

# Trick

- ▶ Use 2-tuples: priority in 1st spot, value in 2nd.

```
class PriorityQueue:

    def __init__(self):
        self._heap = MaxHeap()

    def insert(self, value, priority):
        self._heap.insert((priority, value))

    def pop_highest_priority(self):
        return self._heap.pop_max()

    def max(self):
        return self._heap.max()

    def is_empty(self):
        return not bool(self._heap.keys)
```



# DSC 190

DATA STRUCTURES & ALGORITHMS

**Example: Online Median**

# Online Median

- ▶ **Given:** a stream of numbers, one at a time.
- ▶ **Compute:** the median of all numbers seen so far.
- ▶ **Design:** a data structure with the following operations:
  - ▶ `.insert(number)`: in  $\Theta(\log n)$  time
  - ▶ `.median()`: in  $\Theta(1)$  time

# Review

- ▶ Given an array, we can compute the median in:
  - ▶  $\Theta(n \log n)$  time by sorting
  - ▶  $\Theta(n)$  (expected) time with quickselect
- ▶ But modifying the array and repeating is costly.

# Idea

- ▶ Median is the:
  - ▶ **maximum** of the smallest  $\approx n/2$  numbers.
  - ▶ **minimum** of the largest  $\approx n/2$  numbers.
- ▶ Keep a max heap for the smallest half.
- ▶ Keep a min heap for the largest half.
- ▶ May become unbalanced.
  - ▶ Move elements between them to balance.

# Example

- ▶ Given 5, 1, 9, 8, 10, 7, 3, 6, 2, 4