

北京邮电大学 2009—2010 学年第 2 学期

《数据库系统原理》期中考试试题

考 试 注 意 事 项	一、学生参加考试须带学生证或学院证明，未带者不准进入考场。学生必须按照监考教师指定座位就座。										
	二、书本、参考资料、书包等物品一律放到考场指定位置。										
	三、学生不得另行携带、使用稿纸，要遵守《北京邮电大学考场规则》，有考场违纪或作弊行为者，按相应规定严肃处理。										
	四、学生必须将答题内容做在试题答卷上，做在试题及草稿纸上一律无效。										
	五、填空题用英文答，中文答对得一半分。										
考试课程	考试时间 2010 年 5 月 6 日										
题号	一	二	三	四	五	六	七	八	九	十	总分
满分											
得分											
阅卷教师											

1. Fill in blanks. (3×3 points)

- (1) DDL is the language for specifying the database schema and as well as other properties of the data.
- (2) With respect to integrity mechanisms in DBS, trigger defines actions to be executed automatically when some events occur and corresponding conditions are satisfied.
- (3) An entity set that does not have sufficient attributes to form a primary key is termed a weak entity set.

惠佳快印 (原学五) 1

2. Choice (7×3 points)

- (1) With respect to DBS design, the index is designed at the BD phase.

A. requirement analysis      B. conceptual design  
C. logical design                D. physical design

- (2) For the E-R diagram given below, the mapping cardinality from A to B is C.



A. one-to-many    B. one-to-one    C. many-to-one  
D. many-to-many

- (3) The following SQL statement corresponds to the expression C.

Select \*

From r, s

A.  $r \cap s$     B.  $r \in s$     C.  $r \times s$     D.  $r - s$

- (4) Given the schema R(A, B, C, D, E, F) and the functional dependencies  $F = \{AB \rightarrow D, BC \rightarrow E, D \rightarrow F\}$ ,

13718407947 (微信同号)

$AB \rightarrow E, CE \rightarrow B$  holding on it, D is a transitive functional dependency.

- A.  $AB \rightarrow D$    B.  $BC \rightarrow E$    C.  $D \rightarrow F$    D.  $AB \rightarrow F$   
E.  $CE \rightarrow B$

(5) Given a relation  $r(R)$ , which one of the following functional dependencies is satisfied by  $r$ . C

- A.  $A \rightarrow B$    B.  $AC \rightarrow B$    C.  $BC \rightarrow A$   
D.  $B \rightarrow C$    E. none

A	B	C
1	6	2
4	5	6
4	6	6
7	3	8
9	1	0

(6) In a *Select* statement, C can be used to take out repetition tuples.

- A. unique   B. count   C. distinct   D. union

(7) All information except D belong to meta-data and

are stored in the data dictionary.


- A. names of the relations  
B. names of the authorized users  
C. attributes on which the index is defined  
D. tuples in the relations

3. Here is the schema diagram for CAP database. Some definitions for the attributes in the table *customer*, *agents*(代理商), *products*, and *orders*(订单) are also given in the following list. The *customers* order *products* from the *agents*. Each time an *order* is placed, a new row is inserted into the *orders* table. (28 points).

惠佳快印 (原学五) 2

13718407947 (微信同号)





attributes	data types	definitions
<u>c_id</u>	int	unique identifier for the customer; similar definitions for <u>a_id</u> , <u>p_id</u> , <u>ord_no</u>
c_name	varchar(10)	name of the customer; similar definitions for a_name and p_name
c_city	varchar(10)	city where the customer is located; similar definitions for a_city and

		p_city
discount	real	each customer has a negotiated discount (折扣) on prices
quantity	real	quantity of the product on hand for sale, in standard units
price	real	price of each unit product
o_date	date	the year and month the order was placed
qty	real	the total quantity ordered for the product
dollars	real	the cost for the ordered product in this order

Use the SQL statements to implement the following operations:

- (1) Define the table orders, it is assumed that the null value is inappropriate for the attribute qty and the attribute dollars ranges from 100 to 10,000. (7 points)

```

create table orders
(
  o_date date,
  c_id int,
  a_id int,
  p_id int,
  qty real not null,
  dollars real
)
  
```

check(dollars >= 100 and dollars <= 10000)

惠佳快印 (原学五) 3

13718407947 (微信同号)

6

- (2) Find out the name of each customer who orders all his products through only one agent. (7 points)

```

select c.name
from customer
where c.id in (select c.id
               from order
               group by c.id
               having count(distinct a.id)=1)

```

- (3) Give every customer, who places some orders and the total cost (in dollars) of all these orders is more than \$2000, a 10% increase in the discount he receives. (7 points)

```

update customer
set discount = (1+10%)*discount
where c.id in (select c.id
              from orders
              group by c.id
              having sum(dollar) > 2000)

```

- (4) Create a new table called Huabei\_customers, and add into it all customers who purchase the product "TV" and are located in Beijing, Tianjing and Shijz. (7 points)

```

create table Huabei_customer
(
  c_id int,
  c_name varchar(10),
  c_city varchar(10),
  discount real,
  primary key (c_id)
)

insert into Huabei_customer
select customer *
from customer, products, orders
where (c.customer.c_id = orders.c_id) and
      (products.p_id = orders.p_id) and
      (p.name = 'TV') and ((c.city = 'Beijing') or (c.city = 'Tianjing') or (c.city = 'Shijz'))

```

4. (20 points) The functional dependency set  $F = \{ A \rightarrow B, B \rightarrow C, C \rightarrow D, D \rightarrow E, E \rightarrow F, F \rightarrow G, G \rightarrow H, H \rightarrow I, I \rightarrow J \}$  holds on the relation

惠佳快印 (原学五) 4 13718407947 (微信同号)



$$F = \{A \rightarrow C, A \rightarrow DEI, B \rightarrow H\}$$

schema  $R = (A, B, C, D, E, F, G, H, I, J)$ ,

a. Compute  $(AF)^+$

(5 points)

1. result =  $(AF)^+$
2. result =  $ADEFI$  ( $A \rightarrow DEI$ )
3. result =  $ADEFIJ$  ( $D \rightarrow IJ$ )
4. result =  $ADEFCHI$  ( $F \rightarrow GH$ )
5.  $(AF)^+ = ADEFCHI$

b. List all the candidate keys of R.

AB

$\{A, B\}$

(5 points)

c. Compute the canonical cover  $F_c$

(5 points)

$AB \rightarrow C$  and  $A \rightarrow DEI$  with  $AB \rightarrow CDEI$   
 $AB \rightarrow C$  and  $B \rightarrow FH$  with  $AB \rightarrow CFH$   
 $AB \rightarrow CDEI$  and  $AB \rightarrow CFH$  with  $AB \rightarrow CDEFIH$

①  $AB \rightarrow C$ ,  $(A)^+$  不包含  $C$ ,  $(B)^+$  不包含  $C$ ,  
 $A, B$  均与  $C$  无关性。

②  $A \rightarrow DEI$ ,  $(A)^+$  包含  $I$ , 1 条无关属性

③  $B \rightarrow FH$ ,  $(B)^+$  包含  $H$ ,  $H$  与  $F$  无关性

④  $F \rightarrow GH$ ,  $D \rightarrow IJ$  无关性

$F_c = \{A \rightarrow C, A \rightarrow DEI, B \rightarrow F, F \rightarrow GH, D \rightarrow IJ\}$

d. Give a lossless and dependency-preserving

decomposition of R into 3NF. (5 points)

$A \rightarrow DEI$ ,  $D \rightarrow IJ$  1 条 1 条  
 $B \rightarrow FH$ ,  $F \rightarrow GH$  1 条 1 条

$A \rightarrow D$ ,  $D \rightarrow IJ$

$P_1(A, B, C)$

$P_2(A, D, E)$

$P_3(B, F)$

$P_4(F, G, H)$

$P_5(D, I, J)$

5. (22 points) Notown Records company needs to store

information about songs, albums and musicians who perform on its albums in a database. Consider the following information:


- Each musicians that records at company has an Id (which is unique), a name, an address, and a phone number.
- Each instrument used in company has a name and an ID, ID is unique.

13718407947 (微信同号)

- Each album recorded on the Notown label has a title, a copyright date, a format, and an album identifier.
- Each song recorded at Notown has a title and an author, and each song can be identified by title.
- Each musician may play several instruments, and a given instruments may be played by several musicians.
- Each album has a number of songs on it, but no song may appear on more than one album.
- Each song is performed by one or more musicians, and a musician may perform a number of songs.
- Each album has exactly one musician who acts as its producer. A musician may produce several albums, of course.

(1) Design the E/R diagram for hospital database on basis of the information mentioned above. (11 points)

Note: mapping cardinality of each relationship and participation of each entity to the relationship should be described in the diagram.



(2) Convert the E-R diagram to the proper relational schemas, and give the primary keys of each relation schemas by underlines. (11 points)

Musician (M-id, name, address, phone-number)

Instrument (I-id, I-name)

Album (a-identifier, title, format, copyright-date, m-id)

Song (S-title, author, a-identifier)

Play (m-id, I-id)

惠佳快印 (原学五) 6

13718407947 (微信同号)

(1)

(2)