Bayes Net Structure Learning

Andrew W. Moore

Associate Professor

School of Computer Science

Carnegie Mellon University

www.cs.cmu.edu/~awm

awm@cs.cmu.edu

412-268-7599

Oct 29th, 2001

Reminder: A Bayes Net



Estimating Probability Tables



J	L	R	S	T
True	False	False	True	False
True	True	False	True	True
True	False	False	True	False
False	True	True	False	False
True	True	False	True	True
:	:	:	:	:

Estimating Probability Tables



Dataset....

J	L	R	S	T
True	False	False	True	False
True	True	False	True	True
True	False	False	True	False
False	True	True	False	False
True	True	False	True	True
:	:	:	:	:

Scoring a structure



(Which of these fits the data best?)

N. Friedman and Z. Yakhini, On the sample complexity of learning Bayesian networks, Proceedings of the 12th conference on Uncertainty in Artificial Intelligence, Morgan Kaufmann, 1996

$$\text{Score} = -\frac{N_{\text{params}}}{2}\log R + R\sum_{j=1}^{m}\left(\begin{array}{c}\text{num combinations}\\ \text{of parent values}\end{array}\right)(\text{arity of } X_j)\sum_{k=1}^{}\sum_{v=1}^{}P(V_k)P(X_j=v\,|\,V_k)\log P(X_j=v\,|\,V_k)$$

Scoring a structure



Number of non-redundant parameters defining the net

#Attributes

#Records

Sums over all the rows in the prob-ability table for X_j

The parent values in the k'th row of X_j's probability table

$$\text{Score} = -\frac{N_{\text{parameters}}}{2}\log R + R\sum_{j=1}^{m}\left(\begin{array}{c}\text{num combinations}\\ \text{of parent values}\end{array}\right)(\text{arity of } X_j)\sum_{k=1}^{}\sum_{v=1}^{}P(V_k)P(X_j=v\,|\,V_k)\log P(X_j=v\,|\,V_k)$$

All these values estimated from data

Scoring a structure



This is called a BIC (Bayes Information Criterion) estimate

This part is a penalty for too many parameters

This part is the training set log-likelihood

BIC asymptotically tries to get the structure right. (There's a lot of heavy emotional debate about whether this is the best scoring criterion)

$$\text{Score} = -\frac{N_{\text{params}}}{2}\log R + R\sum_{j=1}^{m}\left(\begin{array}{c}\text{num combinations}\\ \text{of parent values}\end{array}\right)(\text{arity of } X_j)\sum_{k=1}^{\text{(arity of } X_j)} P(V_k)P(X_j = v \mid V_k)\log P(X_j = v \mid V_k)$$

All these values estimated from data

Searching for structure with best score



Simulated annealing with random restarts.

Each change requires re-evaluation of one or more contingency tables.

Learning Methods until today

	Dec Tree, Sigmoid Perceptron, Sigmoid N.Net, Gauss/Joint BC, Gauss Naïve BC, N.Neigh
	Joint DE, Naïve DE, Gauss/Joint DE, Gauss Naïve DE
	Linear Regression, Quadratic Regression, Perceptron, Neural Net, N.Neigh, Kernel, LWR

Learning Methods added today

	Dec Tree, Sigmoid Perceptron, Sigmoid N.Net, Gauss/Joint BC, Gauss Naïve BC, N.Neigh
	Joint DE, Naïve DE, Gauss/Joint DE, Gauss Naïve DE, Bayes Net Structure Learning (Note, can be extended to permit mixed categorical/real values)
	Linear Regression, Quadratic Regression, Perceptron, Neural Net, N.Neigh, Kernel, LWR

But also, for free…

	Dec Tree, Sigmoid Perceptron, Sigmoid N.Net, Gauss/Joint BC, Gauss Naïve BC, N.Neigh, Bayes Net Based BC
	Joint DE, Naïve DE, Gauss/Joint DE, Gauss Naïve DE, Bayes Net Structure Learning
	Linear Regression, Quadratic Regression, Perceptron, Neural Net, N.Neigh, Kernel, LWR

And a new operation…



Joint DE, Bayes Net Structure Learning



Dec Tree, Sigmoid Perceptron, Sigmoid N.Net, Gauss/Joint BC, Gauss Naïve BC, N.Neigh, Bayes Net Based BC



Joint DE, Naïve DE, Gauss/Joint DE, Gauss Naïve DE, Bayes Net Structure Learning



Linear Regression, Quadratic Regression, Perceptron, Neural Net, N.Neigh, Kernel, LWR