





Can `set_value` Actually Throw?

Robert Leahy
Core Developer
rleahy@rleahy.ca





What if You



std::execution in Asio Codebases


Adopting Senders Without a Rewrite

ROBERT LEAHY



20
25





`std::execution` in Asio Codebases


Adopting Senders Without a Rewrite

ROBERT LEAHY



20
25





std::execution in Asio Codebases

Adopting Senders Without a Rewrite

ROBERT LEAHY



```
/root/stdexec/include/stdexec/__detail/__debug.hpp:152:38: warning: 'void
stdexec::__debug::_ATTENTION_() [with _Warning =
stdexec::_WARNING_<_COMPLETION_SIGNATURES_MISMATCH_,
_COMPLETION_SIGNATURE_<stdexec::__rcvrs::set_value_t(const
std::error_code&)>,
_IS_NOT_ONE_OF_<stdexec::__rcvrs::set_value_t(std::error_code),
stdexec::__rcvrs::set_error_t(std::__exception_ptr::exception_ptr),
stdexec::__rcvrs::set_stopped_t()>,
_SIGNAL_SENT_BY_SENDER_<sender<stdexec::completion_signatures<stdexec::__rcvr
s::set_value_t(std::error_code),
stdexec::__rcvrs::set_error_t(std::__exception_ptr::exception_ptr),
stdexec::__rcvrs::set_stopped_t()>, asio::async_result<completion_token_t,
void(std::error_code)>::initiate<asio::basic_waitable_timer<std::chrono::_V2:
system_clock>::initiate_async_wait>(asio::basic_waitable_timer<std::chrono::_V2:
system_clock>::initiate_async_wait, const
completion_token_t&):<lambda(this auto:82&&, auto:83)>> > >
>]' is deprecated: The sender claims to send a particular set of
completions, but in actual fact it completes with a result that is not one of
the declared
completion signatures. [-Wdeprecated-declarations]
152 |         __debug::_ATTENTION_<_What>();
    |         ^~~~~~
```

```

/root/stdexec/include/stdexec/__detail/__debug.hpp:152:38: warning: 'void
stdexec::__debug::__ATTENTION_() [with _Warning =
stdexec::__WARNING_<COMPLETION_SIGNATURES_MISMATCH_,
COMPLETION_SIGNATURE_<stdexec::__rcvrs::set_value_t(const std::error_code&)>,
IS_NOT_ONE_OF_<stdexec::__rcvrs::set_value_t(std::error_code),
stdexec::__rcvrs::set_error_t(std::__exception_ptr::exception_ptr),
stdexec::__rcvrs::set_stopped_t()>,
SIGNAL_SENT_BY_SENDER_<sender<stdexec::completion_signatures<stdexec::__rcvrs::set_val
ue_t(std::error_code),
stdexec::__rcvrs::set_error_t(std::__exception_ptr::exception_ptr),
stdexec::__rcvrs::set_stopped_t()>, asio::async_result<completion_token_t,
void(std::error_code)>::initiate<asio::basic_waitable_timer<std::chrono::_V2::system_cl
ock>::initiate_async_wait>(asio::basic_waitable_timer<std::chrono::_V2::system_clock>::
initiate_async_wait, const completion_token_t&)::<lambda(this auto:82&&, auto:83)> > >
>]' is deprecated: The sender claims to send a particular set of completions, but in
actual fact it completes with a result that is not one of the declared
completion signatures. [-Wdeprecated-declarations]
152 |         __debug::__ATTENTION_<_What>();
    |         ~~~~~^~

```

```
stdexec::__rcvrs::set_value_t(const std::error_code&>,  
_IS_NOT_ONE_OF_<stdexec::__rcvrs::set_value_t(std::error_code)
```

```
std::invoke(  
    std::move(init_),  
    [this](auto&&... args) noexcept {  
        std::execution::set_value(  
            std::move(r_),  
            std::forward<decltype(args)>(args)...);  
    });
```



```
struct receiver {  
    using receiver_concept = std::exception::receiver_t;  
    void set_value(std::string) && noexcept;  
};
```

```
std::execution::completion_signatures<  
    std::execution::set_value_t(std::string),  
    /* ... */>;
```

```
const std::string str("...");
```

```
std::execution::set_value(std::move(rcvr), str);
```

```
const std::string str("...");  
std::move(rcvr).set_value(str);
```

```
const std::string str("...");
```

```
std::move(rcvr).set_value(std::string(str));
```

From the Standard

“set_value is a value completion function. [...] The expression `set_value(rcvr, vs...)` for a subexpression `rcvr` and pack of subexpressions `vs` is [...] expression-equivalent to `MANDATE-NOT_THROW(rcvr.set_value(vs...))`.”

“For a subexpression `expr`, let `MANDATE-NOT_THROW(expr)` be expression-equivalent to `expr`.

“*Mandates*: `noexcept(expr)` is true.”



```
struct receiver {  
    using receiver_concept = std::exception::receiver_t;  
    void set_value(std::string) && noexcept;  
};
```

```
struct receiver {  
    using receiver_concept = std::exception::receiver_t;  
    void set_value(std::string) && noexcept;  
};
```



```
struct receiver {  
    using receiver_concept = std::exception::receiver_t;  
    void set_value(std::string&&) && noexcept;  
};
```

```
template <typename T, typename U>
    requires
        std::is_convertible_v<U&&, T&&>
constexpr T&& convert(U&& u) noexcept {

    return std::forward<U>(u);

}
```

```
template <typename T, typename U>
constexpr std::remove_cvref_t<T> convert(U&& u) {

    return std::forward<U>(u);

}
```

```
static_assert(!noexcept(convert<std::string>("foo")));
```

```
template <typename T, typename U>
    requires
        std::is_convertible_v<U&&, T&&>
constexpr T&& convert(U&& u) noexcept {

    return std::forward<U>(u);

}
```

```
template <typename T, typename U>
    requires
        std::is_convertible_v<U&&, T&&>
constexpr T&& convert(U&& u) noexcept {

    return std::forward<U>(u);

}
```

```
template <typename T, typename U>
    requires (
        std::is_convertible_v<U&&, T&&> &&
        !std::reference_converts_from_temporary_v<T&&, U&&>)
constexpr T&& convert(U&& u) noexcept {

    return std::forward<U>(u);

}
```

```
template <
    typename Tuple,
    typename Receiver,
    std::size_t... Ns,
    typename... Args>
constexpr void set_value_impl(
    Receiver&& r,
    std::index_sequence<Ns...>,
    Args&&... args)
{

    std::execution::set_value(
        std::forward<Receiver>(r),
        ::convert<
            std::tuple_element_t<Ns, Tuple>>(
                std::forward<Args>(args))...);

}
```

```
template <
    typename Tuple,
    typename Receiver,
    std::size_t... Ns,
    typename... Args>
constexpr void set_value_impl(
    Receiver&& r,
    std::index_sequence<Ns...>,
    Args&&... args)
{

    std::execution::set_value(
        std::forward<Receiver>(r),
        ::convert<
            std::tuple_element_t<Ns, Tuple>>(
                std::forward<Args>(args))...);

}
```



```
template <typename>
struct has_function_call_operator {

    struct type {};

    static std::tuple<> operator()(type);

};

template <typename... Args>
struct has_function_call_operator<std::execution::set_value_t(Args...)> {

    static std::tuple<Args...> operator()(Args...);

};
```

```
template <typename>
struct overload_set;

template <typename... Signatures>
struct overload_set<
    std::execution::completion_signatures<Signatures...>>
    : has_function_call_operator<Signatures>...
{

    using has_function_call_operator<Signatures>::operator()...;

};
```

```
template <typename Signatures, typename Receiver, typename... Args>
constexpr void set_value(Receiver&& r, Args&&... args) {

    using tuple = decltype(
        overload_set<Signatures>{}(
            std::declval<Args>()...));

    ::set_value_impl<tuple>(
        std::forward<Receiver>(r),
        std::make_index_sequence<std::tuple_size_v<tuple>>{},
        std::forward<Args>(args)...);

}
```

```
std::invoke(  
    std::move(init_),  
    [this](auto&&... args) noexcept {  
        std::execution::set_value(  
            std::move(r_),  
            std::forward<decltype(args)>(args)...);  
    });
```

```
std::invoke(  
    std::move(init_),  
    [this](auto&&... args) noexcept {  
        std::execution::set_value(  
            std::move(r_),  
            std::forward<decltype(args)>(args)...);  
    });
```

```
std::invoke(  
    std::move(init_),  
    [this](auto&&... args) noexcept {  
        try {  
            ::set_value(  
                std::move(r_),  
                std::forward<decltype(args)>(args)...);  
        } catch (...) {  
            std::execution::set_error(  
                std::move(r_),  
                std::current_exception());  
        }  
    });
```

Thank you!

