GeeksforGeeks A computer science portal for geeks Placements Practice GATECS IDE Q&A GeeksQuiz Login/Register

Maximum Path Sum in a Binary Tree

Given a binary tree, find the maximum path sum. The path may start and end at any node in the tree.


Example:

Input: Root of below tree
 1
 / \

Output: 6

See below diagram for another example.

1+2+3



We strongly recommend you to minimize your browser and try this yourself first.

For each node there can be four ways that the max path goes through the node:

- 1. Node only
- 2. Max path through Left Child + Node
- 3. Max path through Right Child + Node

4. Max path through Left Child + Node + Max path through Right Child

The idea is to keep trace of four paths and pick up the max one in the end. An important thing to note is, root of every subtree need to return maximum path sum such that at most one child of root is involved. This is needed for parent function call. In below code, this sum is stored in 'max_single' and returned by the recursive function.

C++

```
// C/C++ program to find maximum path sum in Binary Tree
#include<bits/stdc++.h>
using namespace std;
// A binary tree node
struct Node
{
    int data;
    struct Node* left, *right;
};
// A utility function to allocate a new node
struct Node* newNode(int data)
    struct Node* newNode = new Node;
    newNode->data = data;
    newNode->left = newNode->right = NULL;
    return (newNode);
}
// This function returns overall maximum path sum in 'res'
// And returns max path sum going through root.
int findMaxUtil(Node* root, int &res)
{
    //Base Case
    if (root == NULL)
        return 0;
    // l and r store maximum path sum going through left and
    // right child of root respectively
    int 1 = findMaxUtil(root->left,res);
    int r = findMaxUtil(root->right,res);
    // Max path for parent call of root. This path must
    // include at-most one child of root
    int max_single = max(max(1, r) + root->data, root->data);
    // Max Top represents the sum when the Node under
    // consideration is the root of the maxsum path and no
    // ancestors of root are there in max sum path
    int max_top = max(max_single, l + r + root->data);
    res = max(res, max_top); // Store the Maximum Result.
```

```
return max_single;
}
// Returns maximum path sum in tree with given root
int findMaxSum(Node *root)
{
    // Initialize result
    int res = INT_MIN;
    // Compute and return result
    findMaxUtil(root, res);
   return res;
}
// Driver program
int main(void)
{
    struct Node *root = newNode(10);
    root->left
                     = newNode(2);
   root->right
                     = newNode(10);
   root->left->left = newNode(20);
   root->left->right = newNode(1);
    root->right->right = newNode(-25);
    root->right->right->left = newNode(3);
    root->right->right = newNode(4);
    cout << "Max path sum is " << findMaxSum(root);</pre>
   return 0;
}
```

Java

```
// Java program to find maximum path sum in Binary Tree
/* Class containing left and right child of current
 node and key value*/
class Node {
    int data;
    Node left, right;
    public Node(int item) {
        data = item;
        left = right = null;
    }
}
// An object of Res is passed around so that the
// same value can be used by multiple recursive calls.
class Res {
    public int val;
}
class BinaryTree {
```


```
// Root of the Binary Tree
Node root;
// This function returns overall maximum path sum in 'res'
// And returns max path sum going through root.
int findMaxUtil(Node node, Res res)
{
    // Base Case
    if (node == null)
        return 0;
    // l and r store maximum path sum going through left and
    // right child of root respectively
    int 1 = findMaxUtil(node.left, res);
    int r = findMaxUtil(node.right, res);
    // Max path for parent call of root. This path must
    // include at-most one child of root
    int max_single = Math.max(Math.max(1, r) + node.data,
                              node.data);
    // Max Top represents the sum when the Node under
    // consideration is the root of the maxsum path and no
    // ancestors of root are there in max sum path
    int max_top = Math.max(max_single, 1 + r + node.data);
    // Store the Maximum Result.
    res.val = Math.max(res.val, max_top);
    return max_single;
}
int findMaxSum() {
    return findMaxSum(root);
}
// Returns maximum path sum in tree with given root
int findMaxSum(Node node) {
    // Initialize result
    // int res2 = Integer.MIN_VALUE;
    Res res = new Res();
    res.val = Integer.MIN VALUE;
    // Compute and return result
    findMaxUtil(node, res);
    return res.val;
}
/* Driver program to test above functions */
public static void main(String args[]) {
```

Output:

```
Max path sum is 42
```

Time Complexity: O(n) where n is number of nodes in Binary Tree.

This article is contributed by **Anmol Varshney** (FB Profile: https://www.facebook.com/anmolvarshney695). Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



Company Wise Coding Practice Topic Wise Coding Practice

54 Comments Category: Trees

Related Posts:

· Convert a Binary Tree to a Circular Doubly Link List

- Find height of a special binary tree whose leaf nodes are connected
- Find a number in minimum steps
- Evaluation of Expression Tree
- · Print extreme nodes of each level of Binary Tree in alternate order
- Print cousins of a given node in Binary Tree
- Iterative function to check if two trees are identical
- Find largest subtree having identical left and right subtrees

(Login to Rate and Mark) 3.7 Average Difficulty: 3.7/5.0 Based on 74 vote(s)	Add to TODO List Mark as DONE
Writing code in comment? Please use code.geeksforgeeks.org, generate link and share the link here.	

@geeksforgeeks, Some rights reserved

Contact Us!

About Us!

Advertise with us!