


University of Sheffield

# Understanding Failure Modes in Multi-Agent LLM Reasoning Under Controlled Compute Budgets

Youheng Xie

A dissertation submitted in partial fulfilment of the requirements for the degree of

**MSc Artificial Intelligence**

School of Computer Science
University of Sheffield

Supervisor: Robert Loftin

September 2026

Reported word count: approximately 17,100 words

# Declaration

All sentences or passages quoted in this report from other people's work have been specifically acknowledged by clear cross-referencing to author, work and page(s). Any illustrations that are not the work of the author of this report have been used with the explicit permission of the originator and are specifically acknowledged. I understand that failure to do this amounts to plagiarism and will be considered grounds for failure in this project and the degree examination as a whole.

Signed: _____ Date: _____

# Acknowledgements

I thank my supervisor, Robert Loftin, for guidance on the framing, evaluation design, and interpretation of this project. I also acknowledge the University of Sheffield research computing facilities used to run the experiments. The University of Sheffield logo on the title page is reproduced from the official COM dissertation template supplied for this submission. Any remaining errors are my own.

# Abstract

Multi-agent language-model systems are often justified by an intuitive division-of-labour argument: several agents can explore more candidate answers than one agent, after which communication and aggregation should select the best result. Final-answer accuracy alone cannot test this mechanism. It conflates failure to discover the answer with failure to retain, endorse, or select an answer that was already present. This dissertation therefore evaluates multi-agent reasoning as a sequence of state transitions from answer discovery to final endorsement.

The study analyses Qwen3-4B in a frozen form and after supervised fine-tuning on MuSiQue and 2WikiMultiHopQA. A single-agent baseline is compared with five multi-agent architectures under matched thinking-token budgets of 1,000 and 2,000 tokens. The primary benchmark contains 9,600 item-configurations, including 8,000 multi-agent configurations and 26,873 intermediate stages. Lexical accuracy is supplemented by a stage-level semantic screen and a preregistered-style blind human audit focused on the two clearest temporal architectures, Debate and Sequential. The audit covers 160 distinct audited item-configurations drawn from 160 distinct benchmark question identifiers, 400 non-repeat stage records, and 20 hidden repeats. It separates whether a stage contains sufficient support for the reference answer (Discovery) from whether the stage commits to that answer (Endorsement).

The principal result is that exploration and decision quality separate. Multi-agent systems often expose a correct answer in at least one intermediate output, but later revision, communication, and aggregation can erase that advantage. In the human audit, the weighted harmful transition rate from a correct source endorsement to a wrong final endorsement was 5.45% for Debate and 0.59% for Sequential, a difference of 4.86 percentage points. Conversely, beneficial wrong-to-correct transitions were 0.00% for Debate and 5.82% for Sequential. A calibrated Mistral judge agreed with human stage labels at 82.5% for Discovery and 80.5% for Endorsement, but targeted transition reliability was too weak for it to serve as ground truth. Machine labels are consequently used only for full-trace screening, while the human audit supports the central transition claims.

Increasing the nominal thinking budget also failed to improve aggregate semantic outcomes: discovery fell from 84.19% to 82.84%, final accuracy fell from 74.08% to 72.82%, and mean wall time increased by 4.83 seconds per item. These results show that additional computation is not equivalent to useful reasoning when architectures repeatedly regenerate, revise, or compress information. The dissertation contributes an auditable evaluation framework, architecture-specific failure localisation, and evidence that multi-agent reasoning should be assessed by both candidate generation and answer preservation rather than final accuracy alone.

# Contents

**Declaration** i

**Acknowledgements** ii

**Abstract** iii

**1 Introduction** 1

1.1 Motivation . . . . . 1

1.2 Prior work in brief . . . . . 3

1.3 Problem statement . . . . . 4

1.4 Research questions . . . . . 5

1.5 Contributions . . . . . 5

1.6 Dissertation structure . . . . . 6

**2 Related Work** 7

2.1 Reasoning with a single language model . . . . . 7

2.2 Multi-agent language-model systems . . . . . 8

2.3 Multi-hop question answering . . . . . 11

2.3.1 Multi-hop questions and multi-step processes . . . . . 12

2.4 Process evaluation and failure localisation . . . . . 13

2.5 Language models as evaluators . . . . . 13

2.6 Positioning of this dissertation . . . . . 14

**3 Research Questions and Analytical Framework** 15

3.1 From a final prediction to a state trajectory . . . . . 15

3.2 Architecture-specific source states . . . . . 17

3.3 Outcome and transition metrics . . . . . 17

3.4 Weighting the human audit . . . . . 18

3.5 Reliability thresholds and evidence hierarchy . . . . . 19
3.6 Interpretive hypotheses . . . . . 19

**4 Experimental Design** **21**
4.1 Overview . . . . . 21
4.1.1 Units, keys, and data hierarchy . . . . . 21
4.2 Systems . . . . . 22
4.2.1 Single-agent system . . . . . 22
4.2.2 Sequential . . . . . 23
4.2.3 Subtask Parallel . . . . . 23
4.2.4 Parallel Roles . . . . . 23
4.2.5 Debate . . . . . 23
4.2.6 Ensemble . . . . . 23
4.3 Datasets . . . . . 24
4.4 Model variants . . . . . 24
4.5 Budget controller and resource measurement . . . . . 25
4.6 Trace capture and reproducibility . . . . . 26

**5 Evaluation and Human Audit Methodology** **27**
5.1 Lexical evaluation . . . . . 27
5.2 Semantic stage screen . . . . . 29
5.3 Calibration and the need for a targeted audit . . . . . 30
5.4 Human audit scope and sampling . . . . . 31
5.5 Item-level audit schema and the “15 fields” . . . . . 31
5.6 Codebook and annotation procedure . . . . . 32
5.7 Unblinding and quality checks . . . . . 34
5.8 Agreement analysis . . . . . 34
5.9 Transition estimation and uncertainty handling . . . . . 35
5.10 Budget and resource statistics . . . . . 35
5.11 Ethical and data-management considerations . . . . . 35

**6 Benchmark, Fine-Tuning, and Budget Results** **37**
6.1 Final-answer benchmark . . . . . 37
6.1.1 Error rates relative to the single-agent baseline . . . . . 38
6.1.2 Fine-tuning as an attempted intervention . . . . . 39

6.2 Budget effects . . . . . 40
6.3 Chapter summary . . . . . 41

**7 Machine-Screened Failure Analysis 42**
7.1 Semantic discovery, oracle coverage, and aggregation regret . . . . . 42
7.2 Machine-screened failure localisation . . . . . 43
7.3 Resource associations and truncation . . . . . 44
7.4 Why human validation is required . . . . . 45

**8 Human Audit and Transition Results 46**
8.1 Human audit reliability . . . . . 46
8.2 Raw audit composition across all 15 fields . . . . . 47
8.3 Human transition estimates . . . . . 47
8.4 Sensitivity to uncertain labels . . . . . 49
8.5 Scope of the human comparison . . . . . 49
8.6 Chapter summary . . . . . 49

**9 Discussion 51**
9.1 The central finding: exploration and decision separate . . . . . 51
9.2 Why Debate can lose correct answers . . . . . 52
9.3 Why Sequential aggregation can recover . . . . . 52
9.4 More computation is not necessarily more reasoning . . . . . 53
9.5 Implications for evaluation . . . . . 54
9.6 Implications for system design . . . . . 54
9.7 Relationship to prior findings . . . . . 55
9.8 Recommended next experiment . . . . . 55

**10 Limitations 57**
10.1 Model and task scope . . . . . 57
10.2 Fine-tuning scope . . . . . 57
10.3 Semantic judge validity . . . . . 58
10.4 Human audit limitations . . . . . 58
10.5 Compute measurement . . . . . 58
10.6 Metric limitations . . . . . 59

**11 Conclusion 60**

**A Abbreviations and Notation** **62**

A.1 Abbreviations . . . . . 62

A.2 Notation and label values . . . . . 63

**B Human Audit Codebook Summary** **64**

B.1 Blind record fields . . . . . 64

B.2 Discovery rules . . . . . 64

B.3 Endorsement rules . . . . . 64

B.4 Primary audit counts . . . . . 65

**C Frozen Mistral Screening Materials** **66**

C.1 Inference settings and provenance . . . . . 66

C.2 System prompt . . . . . 66

C.3 Complete screening-output example . . . . . 67

**D Reproducibility and Evidence Map** **70**

D.1 Core configurations . . . . . 70

D.2 Figure generation . . . . . 70

D.3 Derived evidence files . . . . . 70

D.4 Reproduction sequence . . . . . 72

D.5 Scope exclusions . . . . . 72

# List of Figures

2.1 Six architectures applied to one example . . . . . 10

3.1 Three evidence layers over the recorded runs . . . . . 16

6.1 Matched budget outcomes . . . . . 40

7.1 Candidate-oracle and final semantic accuracy . . . . . 43

7.2 Resource exposure and semantic outcomes . . . . . 45

8.1 Population-weighted human transition rates . . . . . 48

# List of Tables


2.1 Architecture overview . . . . . 11

4.1 Factorial benchmark design . . . . . 22

5.1 Concrete final-answer scoring examples . . . . . 28
5.2 Interpretation of the 15 audit fields . . . . . 33

6.1 MuSiQue final normalised accuracy . . . . . 38
6.2 Sensitivity of the benchmark to the lexical rule . . . . . 38
6.3 Final-answer error rates, SAS versus each MAS . . . . . 39

7.1 Machine-screened first-error rates . . . . . 44

8.1 Human audit reliability . . . . . 47
8.2 Trace-integrity fields in the audit sample . . . . . 47
8.3 Human fields in the audit sample . . . . . 48
8.4 Machine fields in the audit sample . . . . . 48

# Chapter 1

# Introduction

## 1.1 Motivation

Large language models (LLMs) can solve many reasoning tasks through a single generated chain of thought, but an increasingly common alternative is to organise several model calls as a multi-agent system (MAS). One agent may decompose a question, several agents may work on subproblems or adopt different roles, and a final component may revise or aggregate their outputs. This design is attractive because it resembles familiar forms of collaborative problem solving. Independent proposals may increase coverage, debate may expose errors, and a dedicated aggregator may separate exploration from decision making. Frameworks such as AutoGen have made these structures straightforward to implement, while work on multi-agent debate reports gains in factuality and reasoning under some settings [1–3].

This dissertation uses an operational rather than universal boundary between a single-agent system (SAS) and an MAS. An MAS is a computational graph with multiple separately invoked role instances that retain distinct local generation states and whose outputs are exchanged, selected, or aggregated by an explicit coordination procedure. The SAS baseline instead uses one solver invocation and one continuous local state, even when that trajectory contains several reasoning steps; Section 2.3.1 separates this process property from the multi-hop property of the questions themselves. Under this definition, Ensemble is an MAS because four separately sampled candidate states are passed to a separate aggregator. The five evaluated MAS architectures are Sequential, Subtask Parallel, Parallel Roles, Debate, and Ensemble.

Two of them carry most of the analysis and are introduced here, because the research questions and the human audit both refer to them directly. *Sequential* decomposes the question with a planner, passes the accumulated findings along an ordered chain of workers,

and forms the answer with a final aggregator; the last worker is therefore the state that the aggregator either preserves or loses. *Debate* has two agents produce independent proposals, exposes each agent to the opposing proposal so that it can issue a revision, and then has a separate picker choose between the two revised answers; the revised pair is the state the picker either exploits or discards. These two receive greater human-audited depth because they expose interpretable final coordination boundaries; all five remain in the broad benchmark and machine screen. Table 2.1 and Figure 2.1 set out all six systems side by side, and Chapter 4 gives the implementation detail.

The same decomposition also introduces new failure surfaces. A correct answer may be present in an early proposal but removed during revision. A final picker may prefer a polished but incorrect alternative. A sequential worker may correctly resolve a subproblem and then lose the answer when new context is appended. An aggregator may ignore a correct candidate in favour of a majority of correlated errors. These are not failures of initial answer discovery. They are failures of preservation, endorsement, and selection. A final exact-match score cannot distinguish them from cases in which no component ever produced useful evidence.

This distinction matters for both scientific and engineering reasons. Scientifically, claims that "agents reason better together" concern a mechanism, not only an endpoint. If several agents discover more correct candidates but the system cannot preserve them, the architecture has generated information without converting it into a reliable decision. Engineering decisions are also different under these two diagnoses. A discovery problem may call for better retrieval, more diverse prompts, or a stronger base model. A preservation problem instead calls for provenance-aware aggregation, protected evidence, calibrated confidence, or a less destructive revision policy. Treating both as final-answer error hides the intervention point.

Compute matching creates a second difficulty. A multi-agent graph naturally uses more model invocations than a single-agent baseline. Comparing systems without controlling computation can therefore reward the architecture that simply spends more. Conversely, assigning the same nominal token budget does not guarantee equal effective reasoning: agents can repeat context, emit boilerplate, terminate early, or spend tokens reconciling redundant outputs. Recent work by Tran and Kiela [4] directly challenges the assumption that multi-agent decomposition improves multi-hop reasoning when thinking-token budgets are matched. That work establishes *that* the multi-agent systems it evaluates fail to beat a compute-matched single-agent baseline, but it scores only the final answer. It therefore identifies the failure without explaining it: the reader cannot tell whether no component ever produced a correct answer, or whether one was produced and then discarded at a

later coordination step. Those two diagnoses call for different remedies, and a final-answer metric cannot separate them. The present dissertation reproduces that comparison with an open 4-billion-parameter model and supplies the missing explanation by measuring discovery, preservation, and endorsement at each architecture stage.

## 1.2 Prior work in brief

This section summarises the research the dissertation builds on and states the gap it addresses. Chapter 2 develops each strand in full.

Work on reasoning with a single model established the premise that intermediate steps matter. Chain-of-thought prompting showed that eliciting those steps improves performance and that the trajectory, not only the final string, carries information [5]. Self-consistency samples several trajectories and aggregates them [6]; Self-Refine and Reflexion add feedback and revision loops [7, 8]; Tree of Thoughts searches over partial reasoning states and ReAct grounds steps in external actions [9, 10]. These methods keep one model and one control flow, and they share a risk that becomes central below: later text can overwrite a correct earlier state.

Multi-agent systems distribute inference across separately invoked roles instead. AutoGen provides a general conversational framework [1], CAMEL assigns cooperating agents complementary personas [11], and MetaGPT constrains their exchange to structured artefacts [12]; surveys of the area observe that designs have multiplied faster than the practice for evaluating them [13]. Multi-agent debate is the most studied family, with reported gains in factuality and reasoning [2, 3], although later work finds those gains sensitive to the debate protocol and to the strength of the single-agent comparison [14, 15]. Decomposition is in any case not an exclusively multi-agent property, since a single model can generate and answer its own subquestions [16, 17].

Two recent results motivate this project directly. Tran and Kiela [4] show that the multi-agent advantage can disappear once thinking-token budgets are matched, and Cemri et al. [18] catalogue failures across several multi-agent frameworks, arguing that many are organisational rather than deficiencies of the underlying model. Neither traces the loss of a particular correct answer to a particular coordination step.

The evaluation literature supplies both the task and the instruments. Multi-hop question answering provides questions intended to require combining facts, from HotpotQA [19] to the stricter constructions of MuSiQue and 2WikiMultiHopQA [20, 21], with the caveat that compositional questions can often be answered without the intended reasoning [22]. Process supervision argues for evaluating intermediate steps rather than endpoints

[23, 24]. Language models used as judges make stage-level labelling feasible at scale [25, 26], but carry documented biases of position and self-preference [27, 28], so their validity on a new label definition cannot be assumed.

Taken together, this work motivates both the promise and the cost of decomposition, but stops either at outcome measurement or at framework-level taxonomy. What is missing is a compute-matched, architecture-aware account of where a correct answer is lost between its first appearance and the system's final commitment, with human rather than machine labels at the points where machine error would be most damaging. That is the gap this dissertation addresses.

## 1.3 Problem statement

The central problem is to determine what happens between the first appearance of a defensible answer and the system's final commitment. In this dissertation, an intermediate output is evaluated along two separate axes. *Discovery* asks whether the output contains enough content to support the reference answer, even when the answer is embedded in a longer discussion. *Endorsement* asks whether the output itself commits to that answer rather than merely mentioning it as one possibility. This separation is necessary because a debate transcript may contain the gold answer while explicitly rejecting it, and an aggregator may copy relevant evidence yet conclude with the wrong entity.

Let the source state be the last architecture-specific point at which the system has a meaningful opportunity to preserve a correct answer. For Debate this is the oracle over the two revised candidates; for Sequential it is the final worker output. The target is the final picker or aggregator. A harmful transition occurs when the source endorses the correct answer and the target endorses a wrong answer ($\mathrm{C}\rightarrow\mathrm{W}$). A beneficial transition occurs when the source is wrong and the target becomes correct ($\mathrm{W}\rightarrow\mathrm{C}$). These transition rates provide a direct measure of the value or damage added by the final coordination operation.

Automated semantic judges make this analysis scalable, but their errors can be especially consequential in deliberately difficult transition strata. A judge that is accurate on ordinary correct and incorrect answers may still confuse mention with endorsement, over-credit partial evidence, or behave inconsistently on truncated outputs. The project therefore adopts a hierarchy of evidence. Lexical metrics provide reproducible benchmark-level outcomes. A calibrated Mistral judge supplies a screen over all recorded stages. A blind human audit is the primary basis for the most important Debate and Sequential transition claims. This hierarchy prevents the scale of machine annotation from being mistaken for validity.

## 1.4 Research questions

The study addresses three research questions.

**RQ1** Under matched thinking-token budgets, how do single-agent and multi-agent architectures differ in final-answer performance, answer discovery, and answer preservation on multi-hop question answering?

**RQ2** When a correct answer is available before the final decision, where do Debate and Sequential architectures lose or recover it, and are these transitions supported by human annotation?

**RQ3** Do larger nominal thinking budgets and higher observed resource use improve semantic outcomes, or can additional computation coincide with lower discovery and higher post-discovery loss?

The questions deliberately move from broad comparison to causal diagnosis without claiming a causal experiment where none exists. RQ1 is a benchmark comparison. RQ2 localises state changes at known architecture boundaries. RQ3 combines matched-budget tests with observational resource associations; the latter are interpreted as descriptive rather than causal.

## 1.5 Contributions

This dissertation makes five contributions.

1. It implements a controlled comparison of a single-agent baseline and five multi-agent architectures – Sequential, Subtask Parallel, Parallel Roles, Debate, and Ensemble – using the same Qwen3-4B base family, fixed evaluation subsets, and matched nominal thinking-token budgets.

2. It reframes multi-agent performance as a transition process. Discovery, oracle availability, preservation, aggregation regret, and final endorsement are measured separately, making it possible to distinguish generation failures from coordination failures.

3. It develops a blind audit protocol that labels both Discovery and Endorsement, includes hidden repeated records for intra-rater consistency, freezes the sampling strata before unblinding, and reports finite-population weighted estimates for the target benchmark population.

4. It shows an architecture-specific asymmetry in the audited data. Debate's final decision is predominantly destructive: the weighted harmful C $\rightarrow$ W rate is 5.45% and the beneficial W $\rightarrow$ C rate is 0.00%. Sequential aggregation is less often harmful and sometimes corrective: 0.59% harmful and 5.82% beneficial.

5. It demonstrates that nominally larger budgets are not automatically useful. Across 4,000 matched multi-agent pairs, moving from 1,000 to 2,000 thinking tokens increases mean wall time by 4.83 seconds while reducing both semantic discovery and final semantic accuracy.

The numerical contributions should be read with their stated scope. The human audit supports population-weighted claims for the population defined by the frozen machine-screening and sampling snapshot. The full 26,873-stage semantic analysis is valuable for locating candidate failure mechanisms, but the Mistral labels do not meet the reliability standard required to convert every screened transition into ground truth.

## 1.6 Dissertation structure

Chapter 2 positions the work in research on multi-agent reasoning, multi-hop QA, process evaluation, and automated judging. Chapter 3 defines the state-transition framework and the metrics used throughout. Chapter 4 describes models, datasets, architectures, budgets, and the execution protocol, while Chapter 5 explains lexical scoring, semantic screening, calibration, blind human annotation, and statistical analysis. The results then follow the progression of the research. Chapter 6 first reports the matched-budget benchmark, the completed fine-tuning intervention, and the budget comparison. Chapter 7 asks why the outcome pattern occurs by using the full-trace Mistral screen to examine discovery, preservation, and failure location. Chapter 8 evaluates judge reliability and reports the human-audited transition estimates. Chapter 9 interprets the combined evidence and derives design implications. Chapter 10 bounds the claims, and Chapter 11 answers the research questions and identifies the most defensible next steps.

# Chapter 2

# Related Work

## 2.1 Reasoning with a single language model

Modern language-model reasoning systems often begin with chain-of-thought prompting, which elicits intermediate natural-language steps before an answer [5]. The important methodological insight is that reasoning quality depends not only on the final string but on the trajectory that produces it. Self-consistency extends this idea by sampling multiple reasoning paths and selecting the most consistent answer, thereby separating candidate generation from aggregation without requiring persistent agent identities [6]. Iterative approaches such as Self-Refine and Reflexion add feedback and revision loops to a single model [7, 8]. Search-based extensions push the idea further: Tree of Thoughts maintains several partial reasoning states and explores among them before committing [9], while ReAct interleaves reasoning with external actions so that intermediate steps can be grounded rather than merely asserted [10]. Both remain single-model procedures, because the branching happens inside one system's control flow rather than across separately invoked agents, and both therefore fall on the SAS side of the boundary drawn in Chapter 1. These methods demonstrate that repeated computation can help, but they also expose a general risk shared with multi-agent systems: later text can overwrite a correct earlier state.

This dissertation uses a single-agent system (SAS) as the primary baseline because architecture comparisons are only meaningful relative to a strong, compute-aware alternative. A weak one-shot baseline would confound decomposition with additional inference. The SAS receives the same question and oracle context as the multi-agent systems and is evaluated at the same nominal thinking-token levels. This follows the matched-compute emphasis of Tran and Kiela [4], who argue that the apparent benefit of multi-agent reasoning can diminish or reverse once the comparison controls for thinking tokens.

Single-agent self-consistency is related to the Ensemble architecture studied here, but

the decision rules differ. Self-consistency normally aggregates answers by agreement, while this implementation exposes several candidate generations to a final language-model aggregator. The latter can in principle use evidence quality rather than frequency, but it can also introduce selection error. This distinction motivates the oracle-final gap used later: the gap measures how often an answer was available among candidates but was not converted into a correct final prediction.

## 2.2 Multi-agent language-model systems

Multi-agent LLM systems distribute inference across interacting calls that are described as agents. The distinction from a single-agent system is taken here to be structural rather than rhetorical, in the operational sense fixed in Chapter 1: an MAS has multiple separately invoked role instances that hold distinct local generation states and whose outputs are exchanged, selected, or aggregated by an explicit coordination procedure, whereas an SAS has one solver invocation and one continuous local state. What makes a system multi-agent is therefore the computational graph, not the use of role names in a prompt. Within that definition the term still covers substantially different graphs. Some systems use independent roles to diversify viewpoints, some use planners and workers to decompose tasks, and others use adversarial critique. AutoGen provides a general conversation-based framework in which specialised agents exchange messages and invoke tools [1]. Such flexibility is useful for applications, but it makes scientific comparison difficult: changing the number of calls, prompts, stopping conditions, and aggregation logic can change both compute and behaviour. Surveys of the area describe the same heterogeneity and note that evaluation practice has not kept pace with the proliferation of designs [13]. Role-based frameworks illustrate the range. CAMEL assigns cooperating agents complementary personas and lets them converse towards a task [11], whereas MetaGPT encodes standard operating procedures so that agents exchange structured artefacts instead of free text [12]. The contrast is directly relevant here, because one candidate explanation for the losses reported later is that coordination passes prose summaries where it should pass evidence.

Multi-agent debate is one prominent family. Du et al. [2] report that multiple model instances proposing and debating answers can improve factuality and reasoning. Liang et al. [3] similarly motivate debate as a mechanism for divergent thinking and mitigation of degenerate consensus. At a high level, debate has two expected benefits. First, independent proposals increase the probability that at least one agent finds a correct answer. Second, revision after observing another proposal may correct mistakes. However, debate also adds two decision points: revisions may turn correct proposals into wrong ones, and a final

picker may choose the wrong revised answer. The present study measures both points rather than treating debate as a single black box.

The evidence for debate is not uniform. Smit et al. [14] find that reported gains are sensitive to the debate protocol and to the strength of the single-agent comparison, and that several configurations do not beat a well-prompted single agent. Wang et al. [15] reach a similar conclusion, arguing that much of the apparent benefit of multi-agent discussion can be recovered by one agent given a comparable prompt. Debate has also been repurposed as an evaluation mechanism rather than a solver [29], and consensus among heterogeneous models has been proposed as a way to avoid the correlated errors that arise when every agent shares one base model [30]. That last point bears on the present study, whose agents deliberately share one base model and one prompt family; the consequences are taken up in Chapter 9.

Planner-worker architectures make a different promise. A planner decomposes a multi-hop question into subquestions; workers solve these steps either sequentially or in parallel; and an aggregator forms the final answer. Sequential execution can propagate useful evidence from one worker to the next, but later workers inherit earlier errors and may displace previously correct content. Parallel execution reduces error propagation and latency but deprives workers of intermediate findings. Role-based parallelism seeks diversity by asking several agents to analyse the same evidence from different perspectives. An ensemble samples multiple answers with stochastic decoding. These architectures should not be treated as interchangeable instances of "more agents" because they create different source states and different opportunities for loss.

Decomposition is not by itself a multi-agent property. Least-to-most prompting solves a hard question by generating and answering progressively harder subquestions inside one model [16], and Decomposed Prompting routes subtasks to specialised handlers [17]. The multi-agent versions differ mainly in that each subtask is issued as a separate invocation with its own local state, which is exactly the condition that creates the preservation problem studied here.

Closest in spirit to this dissertation is recent work that treats multi-agent failure itself as the object of study. Cemri et al. [18] analyse traces from several multi-agent frameworks and derive a taxonomy of failure modes spanning specification, inter-agent misalignment, and task verification, arguing that many failures are organisational rather than a deficiency of the underlying model. The present study is narrower and more quantitative. Rather than cataloguing failure types across frameworks, it fixes the base model, the budget, and the task, and measures how often one specific failure occurs at a named boundary: a correct answer that is available before the final decision and is then not selected.





**Figure 2.1:** The SAS and five MAS computational graphs applied to the same illustrative question and oracle context, one architecture per row. Reading down the left edge shows the structural contrast directly: the SAS is a single invocation, while each MAS splits the same work across separately invoked roles. The line beneath each row names the source and final states used for the preservation analysis in Chapter 3. The short labels describe information flow, not observed experimental outputs.

**Table 2.1:** Operational overview of the SAS baseline and five MAS architectures. A candidate/source state is the last observable state used for preservation analysis; human-audit scope refers to the completed audit, not to benchmark inclusion.

| System | Roles/components | Information flow | Source and final decision | Completed human audit |
|---|---|---|---|---|
| SAS | One solver invocation | Question and oracle context remain in one continuous local state | Pre-final reasoning; direct prediction | None at process level |
| Sequential | Planner, ordered workers, aggregator | Plan and accumulated findings pass serially between workers | Last worker; aggregator | Source–final boundary |
| Subtask Parallel | Planner, independent subtask workers, aggregator | Planned subquestions fan out; partial findings reunite | Partial findings; aggregator | None |
| Parallel Roles | Solver, fact extractor, verifier, skeptic, aggregator | Distinct views of the same input run in parallel | Candidate oracle; aggregator | None |
| Debate | Two proposers, two cross-critics, picker | Independent proposals are exchanged and revised | Revised-candidate oracle; picker | Source–final boundary |
| Ensemble | Four sampled candidates, aggregator | Independent stochastic samples form a candidate set | Candidate oracle; aggregator | None |

The dissertation therefore treats architecture as a temporal data-generating process. Debate is proposal → revision → picker. Sequential is plan → worker chain → aggregator. Parallel Roles and Ensemble are candidate set → aggregator. Subtask Parallel is plan → partial findings → aggregator. The source-stage semantics differ: a subtask finding is not necessarily expected to answer the full question, whereas a revised debate answer is. This is why the strongest human transition comparison is restricted to Debate and Sequential, where the source and target states are interpretable and the final boundary is explicit.

## 2.3 Multi-hop question answering

Multi-hop QA is a natural test bed for decomposition because the answer is intended to require combining facts. MuSiQue was constructed by composing single-hop questions while applying filters designed to reduce shortcut solutions [20]. 2WikiMultiHopQA provides questions requiring reasoning over evidence from multiple Wikipedia pages and includes supporting facts intended to expose reasoning steps [21]. The datasets differ in difficulty and construction, which makes their joint use valuable: an architectural pattern that appears on only one dataset may reflect dataset-specific answer forms or shortcut opportunities. Both descend from HotpotQA, which established the format and supplied supporting-fact annotations [19] but was subsequently shown to admit shortcut

solutions, a finding that motivated MuSiQue's stricter construction. Methods built for these datasets also decompose explicitly: Self-Ask has a model pose and answer its own follow-up questions before committing [31], and IRCoT interleaves retrieval with chain-of-thought so that each hop retrieves its own evidence [32]. Because the present experiment supplies oracle context, it removes the retrieval half of that loop and isolates the reasoning and coordination half.

### 2.3.1 Multi-hop questions and multi-step processes

The terms *multi-hop* and *multi-step* are not synonyms here. Multi-hop describes a task property: the question requires connecting more than one fact or relation. Multi-step describes a process property: the system performs several sequential computations or role calls. For example, the illustrative question in Figure 2.1 is multi-hop because answering it requires retrieving the release date of each film and comparing the dates. An SAS may solve those hops within one continuous generation, whereas Sequential makes them explicit as planner, worker, and aggregation steps. Conversely, a multi-step process does not guarantee that the intended evidence hops were followed.

At the same time, benchmark labels do not prove that a model used the intended reasoning chain. Min et al. [22] showed that compositional questions can often be answered without the expected multi-hop process. For this reason, the present dissertation does not claim to verify latent reasoning. It evaluates observable text states: whether an answer-equivalent claim appears, whether the system endorses it, and whether later components preserve it. Oracle context is supplied so that the experiment focuses on reasoning and coordination rather than retrieval. This narrows the claim but improves internal interpretability: absence of the answer cannot be attributed to a failed document retriever.

Exact match and token-level F1 remain useful because they are transparent and reproducible, but they are brittle for semantically equivalent answers. An output may include the correct entity with explanatory text, an alias, a date format, or a harmless modifier and still fail strict matching. Conversely, substring matching can over-credit an answer mentioned only to reject it. These limitations are amplified at intermediate stages, whose outputs are not written in final-answer format. The project consequently reports lexical final accuracy for continuity with standard QA evaluation and uses a separate semantic protocol for stage localisation.

## 2.4 Process evaluation and failure localisation

Outcome supervision assigns a label to a completed response. Process supervision evaluates intermediate steps, potentially detecting where an otherwise promising trajectory goes wrong. Work such as Lightman et al. [23] demonstrates the value of step-level feedback for mathematical reasoning, and Uesato et al. [24] make the comparison explicit, reporting that process-based and outcome-based feedback yield different error profiles even at comparable final accuracy. That finding is the methodological premise of this dissertation, transposed from mathematical derivations to the outputs of architectural roles. The setting here is related but not identical. Intermediate stages are not individual mathematical derivations; they are messages produced by different architectural roles. A useful label must therefore be role-aware and must distinguish informational presence from the system's decision.

The dissertation introduces two observable variables for every relevant stage. Discovery records whether the reference answer is substantively available in the text. Endorsement records whether the text's answer-bearing statement commits to it. Consider a revised debate output stating that "Paris is plausible, but the evidence instead supports Lyon." Paris has been mentioned but is not endorsed. A presence-only judge may call this correct even though the revision would direct a final picker towards Lyon. Conversely, a worker may provide the exact supporting relationship without formatting a final answer; this can count as discovery even when endorsement is not applicable or remains uncertain. Explicit decision rules are therefore necessary for reproducible transition labels.

The closest quantitative concept is oracle accuracy over a candidate set. If any candidate is correct, an oracle selector would succeed. The difference between oracle and final accuracy is often described as aggregation regret. This project extends the idea temporally. It asks not only whether a correct candidate exists, but whether it survives revision, worker propagation, and final selection. Harmful and beneficial transitions then measure the net behaviour of a coordination step, rather than assuming that aggregation is beneficial whenever candidate coverage is high.

## 2.5 Language models as evaluators

LLM-based evaluation can approximate human preferences and semantic judgements at a scale that manual annotation cannot match. MT-Bench and Chatbot Arena helped establish the practical use of strong models as judges while documenting biases such as position sensitivity and self-preference [25]. G-Eval uses structured criteria and chain-of-thought evaluation to improve alignment with human judgements on generation tasks [26]. These results support machine-assisted evaluation, but they do not justify assuming validity

on a new label definition or a deliberately difficult subpopulation. Two documented failure modes bear directly on the design used here. Judgements are sensitive to presentation: Wang et al. [27] show that candidate order alone can change a judge's verdict, which is why the screen in this project labels each stage independently rather than asking a judge to compare stages against one another. Judges also favour text produced by their own model family [28]; the screening judge here is therefore drawn from a different family than the systems under evaluation, although that choice reduces rather than removes the concern.

Reliability is especially important for transition analysis. Suppose a source stage is falsely marked correct and the destination is correctly marked wrong. The resulting C→W transition is entirely artificial. Two individually plausible labels can also form the wrong transition class when one error occurs. General calibration accuracy therefore does not guarantee transition-level accuracy. The present project first calibrated a Mistral judge on ordinary final-answer correctness examples, then conducted a targeted human audit on transition-enriched strata. The targeted result was materially worse than the general result, so the dissertation does not use the machine judge as the primary estimator for Debate and Sequential transitions.

Cohen's kappa is reported alongside exact agreement because it adjusts for chance agreement under the observed marginal distributions [33]. Bootstrap confidence intervals describe uncertainty in agreement estimates [34]. Neither statistic establishes construct validity by itself. Hidden repeats measure one annotator's internal consistency, not independent inter-annotator agreement, and high consistency would not correct a systematically wrong codebook. The audit is therefore designed around explicit evidence checks, blind identifiers, frozen strata, and unblinding only after labels are complete.

## 2.6 Positioning of this dissertation

Existing work provides strong reasons to test both the promise and the cost of multi-agent decomposition. Debate and ensemble methods motivate diverse candidate generation; matched-compute studies question whether that diversity is worth its inference cost; process evaluation motivates inspection of intermediate states; and LLM-as-judge research offers scale with known validity risks. The gap is a controlled, architecture-aware analysis connecting these strands. This dissertation fills that gap by comparing multiple architectures under common budgets, measuring discovery and final correctness separately, localising loss at specific boundaries, and using human labels to support the claims for which machine errors would be most damaging.

# Chapter 3

# Research Questions and Analytical Framework

## 3.1 From a final prediction to a state trajectory

For item $i$, let an architecture produce a sequence of observable stage texts

$$T_i = (s_{i1}, s_{i2}, \ldots, s_{ik}, f_i)\,, \tag{3.1}$$

where $f_i$ is the final output and the preceding stages depend on the architecture. Each stage is mapped to two labels: discovery $D(s) \in \{\mathrm{C}, \mathrm{W}, \mathrm{U}\}$ and endorsement $E(s) \in \{\mathrm{C}, \mathrm{W}, \mathrm{U}\}$. The labels are defined relative to the reference answer and accepted aliases.

Discovery is C when the stage contains an answer-equivalent statement or enough explicit relational content to identify the answer. It is W when this support is absent or supports a different answer. Endorsement is C when the answer-bearing statement commits to the reference answer, and W when it commits elsewhere or explicitly rejects the reference answer. U is reserved for genuinely unresolvable cases, principally truncation inside the answer-bearing statement. The distinction is asymmetric: endorsement implies an answer decision, while discovery may be present in text that does not make a final commitment.

Figure 3.1 summarises three evidence layers derived from the recorded runs. Deterministic final-output evaluation produces benchmark results. Full-trace Mistral screening independently produces breadth and failure-location results. The targeted blind human audit both validates selected machine labels and supplies the primary transition estimates. The audit is therefore not merely the last transformation in a single scoring pipeline.





**Figure 3.1:** Three evidence layers derived from the recorded benchmark runs. Deterministic final-output evaluation produces benchmark results; full-trace machine labels support breadth screening; and the blind human audit validates selected labels while independently supporting the primary Debate and Sequential transition estimates.

## 3.2 Architecture-specific source states

A universal definition of "the previous stage" would obscure the semantics of different computational graphs. Source states are therefore defined by the last point before the final coordination decision at which correctness can be meaningfully preserved.

For Debate, two agents first produce proposals and then revised answers after exposure to the opposing position. Let $r_{iA}$ and $r_{iB}$ be the revised outputs. The source endorsement is an oracle over these revisions:

$$E_i^{\text{src}} = \max\left(E(r_{iA}), E(r_{iB})\right), \tag{3.2}$$

where the ordering is C > U > W for availability. The target is the final picker. This boundary measures whether the picker converts a correct revised option into the final answer. A separate machine-screened analysis examines proposal-to-revision changes, but the primary human transition estimate concerns the revision oracle to picker boundary.

For Sequential, workers receive the accumulated state in order. The source is the last worker output and the target is the final aggregator. This captures whether the aggregator preserves the chain's final answer state. Earlier worker transitions are useful diagnostics but are harder to interpret as homogeneous trials because workers may be assigned different subquestions.

For Parallel Roles and Ensemble, the natural source is the oracle over the candidate set and the target is the aggregator. For Subtask Parallel, candidate outputs are partial findings rather than complete answers, so oracle accuracy is not directly comparable with full-answer candidates. These three architectures remain in the benchmark and semantic screen, but are not included in the primary human transition audit.

## 3.3 Outcome and transition metrics

Final lexical performance is scored against the benchmark's own gold answer and its supplied aliases. The normalisation removes articles, punctuation, and redundant whitespace before comparison. Three comparison rules are used and are kept distinct throughout: normalised exact match, token-level F1, and normalised containment. Section 5.1 defines all three formally and Table 5.1 gives worked examples of predictions that do and do not match under each. The headline benchmark figures in Chapter 6 use normalised containment and are named *final normalised accuracy* there. Semantic metrics use the stage labels defined above.

For $N$ evaluated items, semantic discovery rate is

$$\text{DiscoveryRate} = \frac{1}{N}\sum_{i=1}^{N} \mathbb{I}\left[\exists s \in T_i : D(s) = \text{C}\right]. \tag{3.3}$$

Candidate-oracle accuracy restricts the maximum to the architecture's designated candidate stages. Final semantic accuracy is the proportion for which $D(f_i) = \text{C}$ under the screening protocol. Among items with a correct discovered state, preservation rate is

$$\text{Preservation} = P\left(D(f_i) = \text{C} \mid \exists s \in T_i : D(s) = \text{C}\right), \tag{3.4}$$

and drop rate is its complement. Aggregation regret measures the difference between what the candidate set made available and what the system finally delivered,

$$\text{Regret} = \text{OracleAccuracy} - \text{FinalAccuracy}, \tag{3.5}$$

where OracleAccuracy is the candidate-oracle accuracy defined above and FinalAccuracy is final semantic accuracy, both computed over the same $N$ items. A positive value indicates that the final decision failed to exploit available candidates. A negative value can occur for architectures such as Sequential or Subtask Parallel when aggregation synthesises partial evidence not individually sufficient for an oracle candidate label.

For the human analysis, the primary harmful and beneficial transition indicators are

$$H_i = \mathbb{I}\left[E_i^{\text{src}} = \text{C} \wedge E_i^{\text{final}} = \text{W}\right], \tag{3.6}$$

$$B_i = \mathbb{I}\left[E_i^{\text{src}} = \text{W} \wedge E_i^{\text{final}} = \text{C}\right]. \tag{3.7}$$

The rates $P(H_i = 1)$ and $P(B_i = 1)$ quantify damage and recovery at the final coordination boundary. Reporting both prevents a system with many destructive and many corrective changes from appearing equivalent to a stable system.

## 3.4 Weighting the human audit

The audit deliberately oversamples transitions that are rare in the full machine-screened population. Raw sample proportions therefore do not estimate population prevalence. Let $h$ index the frozen sampling strata, $N_h$ be the number of eligible items in a stratum, $n_h$ the audited sample, and $\bar{y}_h$ the audited transition rate. The finite-population weighted estimate is

$$\hat{p} = \sum_h W_h \bar{y}_h, \qquad W_h = \frac{N_h}{\sum_h N_h}. \tag{3.8}$$

An approximate stratified variance is

$$\widehat{\mathrm{Var}}(\hat{p}) = \sum_h W_h^2 \left(1 - \frac{n_h}{N_h}\right) \frac{s_h^2}{n_h}, \tag{3.9}$$

where $s_h^2$ is the within-stratum sample variance. Intervals use $\hat{p} \pm 1.96\sqrt{\widehat{\mathrm{Var}}(\hat{p})}$ with bounds clipped to $[0, 1]$. Because the final within-stratum selection also pursued coverage and balance, these intervals are descriptive approximations rather than confirmatory probability-sample intervals. The weighted point estimates are the primary summaries.

## 3.5 Reliability thresholds and evidence hierarchy

The project distinguishes three levels of evidence.

1. **Direct benchmark evidence**: exact match, F1, token use, truncation flags, and wall time are computed deterministically from recorded outputs and traces.
2. **Machine-screened semantic evidence**: a Mistral judge labels all relevant stages. These data support broad patterns, candidate selection for audit, and descriptive failure localisation.
3. **Human-audited transition evidence**: blinded human labels, hidden repeats, and frozen weights support the primary Debate and Sequential transition rates.

This hierarchy follows from observed transfer failure. The judge performed strongly on a broad calibration set but materially worse on difficult transition-enriched examples. A second, stronger Qwen2.5-72B judge improved agreement but still failed the predetermined acceptance thresholds. Rather than selecting whichever machine result best supports a narrative, the analysis retains the human audit as controlling evidence and presents machine outputs with explicit caveats.

## 3.6 Interpretive hypotheses

The framework yields testable expectations without requiring a single global claim that MAS is good or bad. Architectures with independent candidates should have high discovery and oracle coverage. If their final accuracy is lower, the gap points to aggregation rather than exploration. Debate should show beneficial proposal-to-revision changes if cross-critique works as intended, but harmful changes if social conformity or persuasive errors dominate. Sequential workers should be vulnerable to state loss across the chain, while

the final aggregator may recover from incomplete worker formulations. Larger budgets should improve outcomes if additional reasoning is productive; if they instead lengthen outputs, repeat information, or increase revision opportunities, discovery and preservation may stagnate or decline.

These hypotheses structure the results chapter. They are not all evaluated with the same evidential strength. Full-trace patterns generate architecture-level diagnoses, whereas the audited final-boundary estimates determine the main claim about Debate and Sequential preservation.

# Chapter 4

# Experimental Design

## 4.1 Overview

The experiment is a factorial comparison over dataset, model variant, architecture, and nominal thinking-token budget. Two multi-hop QA datasets are used: MuSiQue and 2WikiMultiHopQA. Two model variants are evaluated: the frozen Qwen3-4B checkpoint and a project fine-tuned variant labelled `v3b`. Six systems are compared: one single-agent baseline and five multi-agent architectures. Each system is run at budgets of 1,000 and 2,000 thinking tokens on fixed 200-item validation subsets per dataset. Temperature is zero except for the explicitly stochastic candidate generation used by Ensemble.

The complete benchmark therefore contains

$$2 \text{ datasets} \times 2 \text{ models} \times 6 \text{ systems} \times 2 \text{ budgets} \times 200 \text{ items} = 9{,}600 \tag{4.1}$$

item-configurations. Removing the single-agent baseline leaves 8,000 MAS configurations, from which 26,873 intermediate stage outputs are available for semantic screening. The design uses the validation split and a fixed random seed of zero. Oracle context is supplied for each question, so retrieval quality is held outside the scope of the comparison.

### 4.1.1 Units, keys, and data hierarchy

A *benchmark question* is identified by dataset and the dataset's original question identifier. An *experimental condition* is one dataset × model variant × system × budget combination; there are 48 such conditions. An *item-configuration* is one benchmark question executed under one condition and the fixed seed. Its complete recorded execution is a *trace*. A *stage record* is one observable architecture-level text associated with a named role or saved output position; it is not an individual latent reasoning step or a token. A *repeat* is a

blinded duplicate of an existing stage record used only for intra-rater quality control, not a new question, run, or stage.

The 9,600 total therefore count item-configurations, not distinct questions or stages: 1,600 belong to SAS and 8,000 to the five MAS architectures. Different architectures expose different numbers of stage records, which is why the MAS traces contain 26,873 screened intermediate stages rather than a constant multiple of 8,000. Within an SAS raw record, pre-final `trace.thinking` and the returned `prediction` originate from the same invocation but are stored as distinguishable observable texts. They would form the source and final records in a future architecture-neutral process audit.

**Table 4.1:** Factorial benchmark design.

| Factor | Levels and implementation |
|---|---|
| Dataset | MuSiQue and 2WikiMultiHopQA; 200 validation items each |
| Model | Qwen3-4B frozen; Qwen3-4B SFT checkpoint `v3b` |
| System | SAS, Sequential, Subtask Parallel, Parallel Roles, Debate, Ensemble |
| Budget | 1,000 and 2,000 nominal thinking tokens |
| Context | Oracle evidence passages supplied to every system |
| Decoding | Temperature 0.0, except Ensemble candidates at temperature 0.7 |
| Seed | 0 |

## 4.2 Systems

This section is placed before the datasets and model variants because the architectures are referred to throughout the earlier chapters. It expands the operational summary in Table 2.1 and the worked example in Figure 2.1 with the implementation detail actually used in the experiment, including the limits on plan length and parallel task count.

### 4.2.1 Single-agent system

The SAS receives the question and oracle context and produces one reasoning trajectory followed by a final answer. It is not an unreasoned one-shot control; it can use its entire thinking allowance within one coherent state. This is important because distributing the same nominal budget across multiple agents may reduce the amount of context-aware reasoning available to each individual call.

### 4.2.2 Sequential

The Sequential architecture uses a planner, an ordered chain of workers, and a final aggregator. The planner can produce at most five plan steps. Workers receive accumulated findings so that later steps can build on earlier results. This structure is well suited to genuinely compositional questions, but it creates serial dependence: an early error can propagate, and a later worker can overwrite or omit a useful previous finding. The final aggregator sees the worker chain and produces the answer. For human transition analysis, the last worker is the source and the aggregator is the target.

### 4.2.3 Subtask Parallel

Subtask Parallel also begins with a plan, but up to four tasks are executed independently before aggregation. Parallel workers cannot condition on one another's findings. The design reduces critical-path latency and propagation of early mistakes, but each output is a partial answer to a subtask rather than a full candidate for the original question. Candidate-oracle measures are therefore reported with a warning: a "wrong" partial output may still be useful evidence for synthesis.

### 4.2.4 Parallel Roles

Parallel Roles assigns several agents different analytical perspectives on the same question and context, with at most four parallel tasks. The intended benefit is diversity of interpretation rather than decomposition into ordered hops. A final aggregator selects or synthesises the answer. High candidate diversity is useful only if the aggregator can recognise which perspective is supported.

### 4.2.5 Debate

Two agents produce initial proposals, observe the opposing proposal, and issue revisions. A final picker chooses between the revised positions. Debate therefore contains two potential correction mechanisms and two potential loss mechanisms. Cross-exposure can turn a wrong proposal into a correct revision, or turn a correct proposal into a wrong revision. The picker can exploit a surviving correct revision, or discard it. The implementation retains both proposal and revision texts so these boundaries can be inspected separately.

### 4.2.6 Ensemble

The Ensemble produces four candidate answers using a sampling temperature of 0.7 and passes them to an aggregator. This is the most direct candidate-coverage architecture.

It is expected to yield a high oracle accuracy because several stochastic samples explore different answer paths. Its main weakness should therefore appear as aggregation regret when the final component fails to use an available correct candidate.

## 4.3 Datasets

MuSiQue constructs multi-hop questions from connected single-hop components and applies checks intended to prevent models from answering through only one component [20]. It is the harder dataset for the evaluated 4B model and therefore offers room for differences in discovery and aggregation. 2WikiMultiHopQA uses evidence from multiple Wikipedia pages and supplies supporting-fact annotations [21]. It produces substantially higher final accuracy in this experiment and helps reveal whether coordination losses persist when the underlying questions are easier for the model.

The use of oracle context narrows the experimental claim. The systems are not evaluated as end-to-end retrieval-augmented QA pipelines. Instead, they receive the passages needed to answer and are tested on their ability to combine evidence and maintain a correct answer through the computational graph. This improves comparability across architectures because one system cannot gain merely from a different retrieval query, but it also means the results do not estimate performance under realistic retrieval noise.

All systems use the same selected items within a dataset. This pairing is essential for the budget comparison: for a given model, dataset, and architecture, the 1,000- and 2,000-token runs can be compared on the identical question. Three Subtask Parallel records lacked a resolved semantic discovery label in the paired screen, leaving 3,997 discovery pairs rather than 4,000; final semantic accuracy retains all 4,000 MAS pairs.

## 4.4 Model variants

The base model is Qwen3-4B [35]. The frozen condition uses the public checkpoint without task-specific parameter updates. The `v3b` condition uses a merged supervised fine-tuning checkpoint developed within the project. It was trained through a low-rank adaptation workflow, a parameter-efficient approach derived from LoRA [36], and then merged for inference. The fine-tuning data were designed to preserve the single-agent reasoning format rather than directly train every multi-agent role.

The `v3b` objective is completion-only causal language modelling on naturally terminated, correct SAS trajectories. Training data were constructed from 1,175 four-hop MuSiQue training questions with oracle context. For each question the frozen model sampled up to

four reasoning traces at temperature 0.7 and top-$p$ 0.95 with a 1,536-token thinking cap; cap-truncated candidates were discarded. A deterministic answer phase was then checked against the gold answer and aliases using the project's normalised-containment filter, and the earliest correct sample was retained. This produced 833 examples (70.9% question coverage); 599 sampled candidates were discarded for reaching the cap. Retained reasoning lengths had mean 616 tokens and 10th/50th/90th percentiles of 219/514/1,228 tokens. This rejection design preferentially retains questions the frozen model can already solve and is consequently an adaptation experiment rather than evidence of new knowledge.

The prompt tokens were masked from the loss, while the completion, naturally positioned `</think>` marker, final answer, and end-of-sequence token were supervised. Sequences were capped at 4,096 tokens. LoRA used rank 16, scaling factor 32, dropout 0.05, and targeted the query, key, value, output, gate, up, and down projection modules. Training used bfloat16, learning rate $10^{-4}$, two epochs, per-device batch size 2, gradient accumulation 8 (effective batch size 16 on one device), gradient checkpointing, and seed 0. The final adapter was merged into the Qwen3-4B base weights for inference. These settings are recorded in the construction and training scripts cited in Appendix D.

This choice creates a controlled but limited contrast. It tests whether the observed architecture patterns survive a project-specific adaptation of the same base family; it does not establish generality across unrelated model families or parameter scales. The later `v4` role-conditioned experiments described in project notes are intentionally excluded from the main dissertation because they were not part of the completed, audited evidence chain. Including incomplete fine-tuning arms would expand the narrative without a correspondingly validated result.

For both variants, the configured maximum model length is 16,384 tokens, tensor parallel size is one, and the main benchmark uses deterministic decoding. The experiment records actual thinking tokens and truncation indicators at stage level, allowing the analysis to distinguish nominal limits from realised use.

## 4.5 Budget controller and resource measurement

The token controller applies nominal thinking budgets of 1,000 and 2,000 tokens. These levels refer to reasoning-token allowances within the architecture rather than a guarantee that every system emits exactly the limit. The controller records thinking tokens per item and flags stage truncation when generation reaches its assigned cap. Architecture overhead, final answers, and prompt tokens are not interpreted as interchangeable with productive reasoning tokens.

Wall time is observed end-to-end elapsed time for an item. For parallel architectures it approximates the critical path rather than the sum of all device work. Consequently, total recorded item wall time is not GPU-seconds, and exact energy or cost comparisons cannot be reconstructed without scheduler telemetry. The dissertation reports mean and distributional wall times to describe latency, not total hardware consumption.

Budget comparisons use paired items. For each system, model, and dataset cell, semantic outcomes at 1,000 and 2,000 tokens are compared with an exact McNemar test. This design asks whether increasing the cap changes correctness on the same questions. Resource association models separately compare observations above and below the median wall time or token use within dataset $\times$ model $\times$ budget $\times$ system strata. Those associations control for the design cells but remain observational because actual resource use is partly determined by the generated trajectory.

## 4.6 Trace capture and reproducibility

Every run stores the question identifier, gold answers and aliases, final prediction, stage texts, architecture metadata, budget, thinking-token count, wall time, and truncation status. Stage records are normalised into a common analysis format while retaining role names such as proposal, revision, worker, picker, and aggregator. The fixed configuration files specify models, systems, budgets, context mode, and seed. Analysis scripts then generate per-item lexical metrics, stage-level semantic files, transition tables, budget-pair tests, and audit workbooks.

The main source files are listed in Appendix D. This provenance is important because the human audit was constructed from frozen machine-defined strata. Re-running a judge with a different prompt could change the screen, but it does not retroactively change the audited sample or its population weights. The final report therefore keeps generated outputs and codebook revisions alongside the analysis rather than presenting only aggregate numbers.

# Chapter 5

# Evaluation and Human Audit Methodology

## 5.1 Lexical evaluation

The first evaluation layer scores final answers deterministically against the benchmark's own gold answer and its supplied aliases, under three comparison rules: normalised exact match (EM), token-level F1, and normalised containment. Let $n(x)$ lowercase a string, remove ASCII punctuation and the articles *a*, *an*, and *the*, collapse whitespace, and split the result into tokens. For prediction $p$ and accepted reference set $G$ (gold answer plus supplied aliases),

$$\mathrm{EM}(p, G) = \max_{g \in G} \mathbb{I}[n(p) = n(g)]. \tag{5.1}$$

For each $g$, the token multiset overlap is $m_g = |n(p) \cap n(g)|$. Precision is $P_g = m_g/|n(p)|$, recall is $R_g = m_g/|n(g)|$, and

$$\mathrm{F1}(p, G) = \max_{g \in G} \frac{2P_g R_g}{P_g + R_g}, \tag{5.2}$$

with a score of zero when no tokens overlap. Taking the maximum over aliases prevents a harmless accepted name or date form from being penalised merely because it differs from the canonical gold string.

Normalised containment relaxes the equality test to a substring test on the same normalised strings,

$$\mathrm{Contain}(p, G) = \max_{g \in G} \mathbb{I}\left[n(g) \neq \varnothing \ \wedge \ n(g) \subseteq_{\mathrm{sub}} n(p)\right], \tag{5.3}$$

where $\subseteq_{\mathrm{sub}}$ denotes substring inclusion. A prediction therefore counts as correct under

containment whenever an accepted answer string appears anywhere in the normalised output, regardless of the surrounding sentence.

**Table 5.1:** Concrete examples of final-answer scoring under the three lexical rules of Section 5.1. F1 is shown against the best accepted alias. The third row shows containment crediting an answer the output rejects; the fourth is a real Debate final output from the frozen 2WikiMultiHopQA run [21], and shows why exact match is uninformative for architectures that answer in a sentence.

| Gold/accepted alias | Model prediction | EM | Cont. | F1 | Interpretation |
|---|---|---|---|---|---|
| Little Buddha | Little Buddha | 1 | 1 | 1.00 | Exact normalised match; all three rules agree. |
| 22 February 1981; February 22, 1981 | Curtis Bernhardt died on February 22, 1981. | 0 | 1 | 0.60 | The accepted date is present, but explanatory tokens prevent EM. |
| Paris | Paris is plausible, but the evidence supports Lyon. | 0 | 1 | 0.25 | Containment finds "Paris" in an output that rejects it. This is the case that motivates separating Discovery from Endorsement. |
| Course For Collision | Course for Collision was released earlier. It aired in 1967, while Little Buddha was released in 1993. Therefore, **Course for Collision** predates **Little Buddha** by over two decades. | 0 | 1 | 0.19 | A substantively correct answer. EM scores it zero and F1 scores it 0.19 because the answer is embedded in a full sentence with markup. |

The choice among these rules is consequential, and the dissertation follows the reproduction protocol of Tran and Kiela [4] in reporting *normalised containment* as the headline benchmark figure. The fourth row of Table 5.1 shows why. Several of the architectures evaluated here, Debate most of all, answer in a full sentence rather than an answer span, so strict EM records almost none of their correct answers: across the frozen MuSiQue runs at 1,000 tokens, Debate scores 0.030 under EM and 0.510 under containment. An EM-only benchmark would therefore measure output formatting at least as much as reasoning, and would not be comparable across architectures.

Containment buys that comparability at a known cost. It credits any output in which an accepted string appears, including one that mentions the answer and then rejects it, as the third row of Table 5.1 shows. The headline accuracies in Chapter 6 are therefore upper bounds on final-answer correctness, and Table 6.2 reports EM and F1 alongside containment so that the size of the gap is visible for every system. This limitation is also a direct motivation for the rest of the evaluation: a metric that cannot distinguish an endorsed answer from a rejected mention is exactly the metric that cannot locate a

coordination failure. The pipeline additionally records an LLM final-answer judgement using the fixed rubric inherited from the reproduction protocol; it is semantically flexible but model-dependent and can abstain or misparse, and is reported only as a continuity measure. Human labels are reserved for the targeted process claims where the distinction between informational presence and commitment is decisive.

These lexical metrics do not reliably locate intermediate correctness. A worker may express the answer in a sentence rather than an answer field; an agent may use a valid semantic equivalent absent from the alias list; and debate outputs may mention both correct and incorrect candidates. Lexical scores are consequently interpreted as final-output evidence, not as evidence of when the system first reached a correct state.

## 5.2 Semantic stage screen

Human annotation cannot be applied to the whole trace population, which is why a machine screen exists at all. The five multi-agent architectures produce 26,873 intermediate stage records across 8,000 item-configurations, and each record has to be read in full and labelled on two axes against the question and the accepted answers; that is far beyond what a single annotator can complete. Uniform random sampling is not a workable substitute either, because the events this dissertation is about are rare. Harmful and beneficial final-boundary transitions together account for a low single-digit percentage of items, so a random sample small enough to annotate by hand would contain too few of them to estimate their rates with any precision.

The screen resolves both problems at once. It supplies a complete, if imperfect, labelling of every stage, which is what makes the breadth analysis in Chapter 7 possible; and it partitions the population into transition strata from which rare cases can be deliberately oversampled for human review and then reweighted back to population rates by Equation (3.8). The screen is therefore a sampling instrument as much as a measurement in its own right. Because the audit's population estimates depend on the strata it defines, its reliability is tested rather than assumed (Section 5.3 and Chapter 8).

A Mistral instruction model was prompted to label intermediate and final stage texts using the reference answer, aliases, question, and numbered stage statements. The frozen judge was Mistral-Small-3.2-24B-Instruct-2506, prompt version `stage_discovery_and_endorsement_v4_indexed_evidence`, with temperature 0 and JSON-object output. The final prompt revision applied the same semantic-discovery rule across stages and required evidence-statement identifiers for every correct Discovery label. For each stage, the judge returned both semantic labels, grounded evidence identifiers, an extracted endorsed answer,

and reason codes. Outputs that did not parse or lacked a resolvable basis were marked uncertain or parse error rather than silently coerced to correct or wrong. The complete prompt is reproduced in Appendix C, together with a full worked example showing the numbered statements a judge receives for one reasoning trace and the JSON it returns.

The full screen covers all 8,000 MAS item-configurations and 26,873 intermediate stages. When the final output text was identical to a recorded stage, its label was reused to avoid unnecessary stochastic re-judging; 2,297 final labels were reused and 5,703 were judged separately. Six uncertain intermediate labels were excluded pairwise from affected transition calculations.

The screen produces four families of descriptive outputs:

1. final semantic accuracy, discovery rate, candidate-oracle accuracy, preservation, and aggregation regret for each dataset, model, architecture, and budget;
2. the first stage at which a terminally incorrect trajectory becomes wrong, using architecture-specific stage order;
3. transitions from Debate proposals to revisions and from revisions to the picker, together with Sequential worker and aggregator transitions;
4. associations between wall time, realised thinking tokens, truncation, discovery, and post-discovery loss.

The machine screen is explicitly not treated as error-free annotation. It is used to summarise all traces and to create informative sampling strata for human review.

## 5.3 Calibration and the need for a targeted audit

Against human correctness labels, the judge initially achieved 91.9% accuracy and Cohen's $\kappa = 0.829$ on a general calibration set. Coverage and the false-positive/false-negative directions were inspected separately rather than folded into one ambiguously named statistic. Those results suggested that large-scale semantic screening was feasible. Performance was not uniform, however: cases involving Debate beneficial flips and Sequential losses were weaker. A targeted sensitivity audit of difficult transitions later found only 73.9% exact agreement across 199 resolved stage labels ($\kappa = 0.478$) and 50.5% exact agreement across 99 resolved transition pairs (multiclass $\kappa = 0.364$).

This difference is not paradoxical. General calibration is dominated by ordinary correct and wrong outputs. Transition-enriched cases place the decision boundary precisely where a judge is most likely to fail: partial evidence, answer mentions without commitment,

disagreement between proposals, and truncated conclusions. Because a transition is a compound of two labels, one stage error can change the transition class. The targeted result therefore supersedes the broad calibration result for transition-level inference.

A Qwen2.5-72B-Instruct judge was also evaluated as a stronger alternative. It reached 87.0% stage accuracy ($\kappa = 0.723$) and 79.0% exact transition accuracy (multiclass $\kappa = 0.701$) on the targeted set, with no parse or grounding failures. Although better, it did not pass the fixed acceptance thresholds. It is not used to relabel the full trace population. The decision to retain human labels was made from the reliability criteria rather than from whether machine estimates supported the desired hypothesis.

## 5.4 Human audit scope and sampling

The definitive audit focuses on Debate and Sequential because their final coordination boundaries are well defined and because the machine screen indicated substantively different transition patterns. The frozen machine-labelled population was divided into architecture and transition strata. Rare candidate transitions were oversampled so the audit would include enough difficult cases to diagnose judge direction and component behaviour. Within-stratum selection was fixed before human labels were unblinded.

The final sample contains 160 distinct audited item-configurations drawn from 160 distinct benchmark question identifiers: 80 Debate runs and 80 Sequential runs. Each Debate item-configuration contributes two revised candidates and one final picker output; each Sequential item-configuration contributes the last worker and final aggregator output. This gives 400 non-repeat stage records. Twenty stage records were duplicated under new blind identifiers and inserted as hidden repeats, giving 420 annotation rows in total. The repeat positions and item identities were not visible during annotation.

The audit is a single-annotator study. Hidden repeats therefore measure intra-rater repeatability, not agreement between independent annotators. The sampling design estimates transition rates for the population defined by the frozen machine-screening and sampling snapshot only after stratum weighting; the raw 80-item architecture counts are diagnostic and are not direct prevalence estimates.

## 5.5 Item-level audit schema and the “15 fields”

During supervision, the item-level audit columns were described informally as “15 labels.” The precise description is *15 item-level audit fields*. They are not fifteen independently annotated error indicators and are not all binary. Four fields are Boolean truncation

descriptors, eight are semantic state labels, and three are derived categorical transitions. Consequently, the fields should not be given fifteen separate prevalence interpretations.

At the architecture-aligned source boundary, the Debate source state pools the two revised candidates using an any-correct candidate rule, whereas the Sequential source state is the last worker output. The destination state is the final Debate picker or Sequential aggregator output. Table 5.2 records the role and scale of each field group.

The primary population comparison is therefore based on the weighted categories of `human_endorsement_transition_raw`. The cross-axis human transition is reported as a secondary diagnostic; truncation fields are covariates or sensitivity descriptors; and the five machine fields support sampling and human–machine validation. This hierarchy prevents derived or machine-generated columns from being counted as additional human outcomes.

## 5.6 Codebook and annotation procedure

The codebook was iterated through four revisions during pilot review and frozen before the final unblind analysis. Each record showed the question, accepted gold answer and aliases, evidence context, stage role, and stage text, but concealed architecture, run condition, transition stratum, and whether the row was a repeat. The annotator assigned Discovery and Endorsement independently.

Discovery used the following decision rule:

- C if the stage states the accepted answer or supplies an unambiguous answer-equivalent relationship grounded in the provided evidence;
- W if no sufficient answer-equivalent content appears, if the relation is wrong, or if only an unsupported option reference is present;
- U only when the available text prevents a defensible decision, particularly when truncation cuts through the answer-bearing claim.

Endorsement used a stricter commitment rule:

- C if the stage's answer-bearing statement selects the accepted answer;
- W if it selects a different answer, rejects the accepted answer, or ends without endorsing answer-equivalent content;
- U if the commitment itself is missing because the answer-bearing sentence is truncated.

**Table 5.2:** Interpretation of the 15 named item-level audit fields. The fields are grouped by measurement role rather than treated as fifteen independent outcomes.

| Group | Fields | Scale and analytical role |
|---|---|---|
| Truncation descriptors (4) | `question_any_truncated`, `source_truncated`, `final_truncated`, `any_truncated` | Boolean/NA flags for any truncated call in the item-configuration trace, the audited source boundary, the final destination, and their three-valued union. The final-stage metadata are unavailable in this audit snapshot; the union is derived rather than an independent error. |
| Human semantic states (4) | `human_source_discovery`, `human_source_endorsement`, `human_final_discovery`, `human_final_endorsement` | Human C/W/U judgements at the source and final stages on the two semantic axes. |
| Human derived transitions (2) | `human_endorsement_transition_raw`, `human_discovery_to_final_endorsement_raw` | Categorical source-to-final paths. The first is the primary within-axis transition; the second is a cross-axis diagnostic of discovery surviving to final endorsement. |
| Machine semantic states (4) | `machine_source_discovery`, `machine_source_endorsement`, `machine_final_discovery`, `machine_final_endorsement` | Frozen Mistral screen labels aligned to the human fields; used for sampling and agreement analysis, not as ground truth. |
| Machine derived transition (1) | `machine_transition` | Categorical source-Endorsement-to-final-Endorsement transition used to define the frozen sampling strata. |

The distinction prevents a common evaluator error: crediting a stage merely because the gold string appears somewhere. Evidence fields were checked for every C label in the final audit. Reason codes were harmonised after unblinding for three records, but the C/W/U labels did not change.

## 5.7 Unblinding and quality checks

Unblinding occurred after all 420 rows had complete labels. The 20 hidden pairs matched exactly on both axes. Across all rows, Discovery counts were 240 C, 180 W, and zero U; Endorsement counts were 225 C, 192 W, and three U. Fourteen rows had Discovery C but Endorsement W, directly confirming that presence and commitment are empirically distinct. No row had Endorsement C while Discovery was not C.

Completeness checks confirmed that all 105 rows labelled Discovery C in the final audited round contained verbatim or answer-equivalent evidence in the corresponding stage output. The unblind process also corrected a spreadsheet wildcard-count display defect affecting static truncation summary cells. The audited labels and derived transition results were unchanged.

## 5.8 Agreement analysis

Exact agreement and Cohen's kappa are computed separately for Discovery and Endorsement [33]. For hidden repeats, the two blind copies of the same stage are compared. For human-machine agreement, the 400 non-repeat human labels are aligned to the frozen Mistral labels. Percentile bootstrap intervals with resampling at the stage-record level describe uncertainty in kappa [34]. Agreement direction is also retained: human C/machine W indicates an over-strict machine judgement, while human W/machine C indicates an over-broad judgement.

Transition agreement is more demanding than stage agreement and is reported separately in the targeted sensitivity analysis. A pair is exactly correct only when both source and destination produce the same transition class under human and machine labels. This is why an approximately 80% stage agreement cannot be interpreted as 80% reliable transition counts.

## 5.9 Transition estimation and uncertainty handling

For each audited item, the source and final Endorsement states form one of four primary transitions: C→C, C→W, W→C, or W→W. The three U stage labels are handled under a conservative primary rule that maps U to W. Two sensitivity rules are also reported: exclude any item containing U, and map U to C. The substantive Debate-Sequential harmful-rate ordering is required to remain stable under all three rules.

Population estimates use the frozen stratum sizes as described in Chapter 3. A weighted contrast subtracts the Sequential harmful rate from the Debate harmful rate. Approximate 95% confidence intervals use the finite-population stratified variance. Because sample selection included greedy balancing rather than pure random sampling inside every stratum, intervals are treated as descriptive. No claim of conventional randomised-treatment causality is made.

## 5.10 Budget and resource statistics

Budget outcomes are compared within matched items using two-sided exact McNemar tests. Discordant counts identify questions that change from wrong to correct and from correct to wrong when the cap rises from 1,000 to 2,000. Mean paired changes in wall time and realised thinking tokens are reported alongside accuracy differences.

Resource associations use fixed-effect stratification over dataset, model variant, budget, and system. Exposure is defined relative to the within-stratum median for wall time or thinking-token use. Adjusted odds ratios compare semantic discovery and post-discovery drop between high- and low-exposure observations. A separate model tests whether truncation at a destination stage is associated with a $C \rightarrow W$ transition conditional on a correct source. These analyses are diagnostic. Slower or longer outputs may be consequences of difficult items or unstable trajectories rather than causes of error.

## 5.11 Ethical and data-management considerations

The experiments use public QA benchmark content and model-generated text; they do not involve recruitment of human participants or collection of personal data. The human annotation is the researcher's analysis of model outputs. The study nevertheless retains an auditable data trail: codebook revisions, blind sheets, round-level completions, the frozen key, and the unblind report are stored separately from the main benchmark outputs. Model-generated statements are not treated as factual sources beyond the supplied benchmark evidence. The analysis reports uncertainty and failed judge acceptance tests

rather than concealing them, because evaluator limitations materially affect the validity of the conclusions.

# Chapter 6

# Benchmark, Fine-Tuning, and Budget Results

## 6.1 Final-answer benchmark

The lexical benchmark establishes the outcome pattern before intermediate states are considered. The metric reported throughout this chapter, and referred to as *final normalised accuracy*, is the normalised containment of Equation (5.3): after lowercasing, punctuation removal, article removal and whitespace collapse, a prediction counts as correct when the gold answer or one of the benchmark's accepted aliases appears as a substring of it. Table 5.1 shows worked examples of predictions that do and do not match. Containment rather than exact match is used because it follows the reproduction protocol and because several architectures answer in a sentence rather than an answer span, which strict exact match barely credits; Table 6.2 quantifies that difference for every system. The corresponding cost is that containment credits an output that mentions an accepted answer and then rejects it, so the accuracies below are upper bounds on final-answer correctness. On the harder MuSiQue subset, the frozen SAS achieves final normalised accuracy of 0.560 at the 1,000-token budget and 0.525 at 2,000. Debate is the strongest MAS in this condition, at 0.510 and 0.535 respectively. Sequential is substantially lower, at 0.335 and 0.340. Fine-tuning does not reverse the broad ranking: at 1,000 tokens the `v3b` SAS scores 0.545, Debate 0.505, and Sequential 0.380.

On 2WikiMultiHopQA, absolute performance is much higher. In the frozen condition, Debate reaches 0.935 and 0.930 at the two budgets, compared with SAS at 0.860 and 0.845. This is an important counterexample to any universal statement that a single agent always wins: an MAS can outperform the SAS on a particular dataset and condition. The dissertation's claim is narrower. Multi-agent decomposition often increases candidate

**Table 6.1:** MuSiQue final normalised accuracy by model, architecture, and thinking-token budget ($n = 200$ per cell). The metric is normalised containment (Equation (5.3)); Table 6.2 gives the same cells under exact match and F1.

| Model | System | 1,000 | 2,000 |
|---|---|---|---|
| Frozen | SAS | **0.560** | 0.525 |
| | Debate | 0.510 | **0.535** |
| | Ensemble | 0.520 | 0.505 |
| | Parallel Roles | 0.425 | 0.390 |
| | Sequential | 0.335 | 0.340 |
| | Subtask Parallel | 0.425 | 0.425 |
| v3b | SAS | **0.545** | **0.530** |
| | Debate | 0.505 | **0.530** |
| | Ensemble | 0.515 | 0.510 |
| | Parallel Roles | 0.415 | 0.445 |
| | Sequential | 0.380 | 0.340 |
| | Subtask Parallel | 0.410 | 0.390 |

availability, but that gain is inconsistent and can be lost at later coordination stages. Relative performance depends on dataset difficulty, model variant, architecture, and budget.

**Table 6.2:** Final-answer accuracy for the frozen model at the 1,000-token budget under each of the three lexical rules of Section 5.1 ($n = 200$ per cell). Containment is the headline metric used elsewhere in this chapter. The EM column shows why: architectures that answer in a sentence rather than an answer span are barely credited by exact match, so an EM-only ranking would largely measure output format.

| | MuSiQue | | | 2WikiMultiHopQA | | |
|---|---|---|---|---|---|---|
| System | Contain. | EM | F1 | Contain. | EM | F1 |
| SAS | 0.560 | 0.290 | 0.371 | 0.860 | 0.200 | 0.431 |
| Sequential | 0.335 | 0.125 | 0.204 | 0.825 | 0.055 | 0.302 |
| Subtask Parallel | 0.425 | 0.155 | 0.220 | 0.830 | 0.060 | 0.294 |
| Parallel Roles | 0.425 | 0.225 | 0.314 | 0.870 | 0.290 | 0.526 |
| Debate | 0.510 | 0.030 | 0.075 | 0.935 | 0.005 | 0.123 |
| Ensemble | 0.520 | 0.420 | 0.511 | 0.870 | 0.335 | 0.518 |

### 6.1.1 Error rates relative to the single-agent baseline

The comparison that matters for RQ1 is between the single-agent baseline and each architecture separately, rather than between SAS and a pooled multi-agent average. Table 6.3 reports the final-answer error rate for every system alongside its difference from the SAS error rate in the same dataset, budget and model cell.

**Table 6.3:** Final-answer error rate (1 − containment) for the single-agent baseline and each multi-agent architecture, frozen model, $n = 200$ per cell. Values in parentheses are the difference from the SAS error rate in the same cell, in percentage points; positive means the architecture makes more final-answer errors than the single-agent baseline. The sign is not constant across datasets: on MuSiQue every architecture except Debate at the larger budget is worse than SAS, whereas on 2WikiMultiHopQA Debate, Ensemble and Parallel Roles are all better than SAS.

| | MuSiQue | | 2WikiMultiHopQA | |
|---|---|---|---|---|
| System | 1,000 | 2,000 | 1,000 | 2,000 |
| SAS (baseline) | 0.440 | 0.475 | 0.140 | 0.155 |
| Sequential | 0.665 (+22.5) | 0.660 (+18.5) | 0.175 (+3.5) | 0.210 (+5.5) |
| Subtask Parallel | 0.575 (+13.5) | 0.575 (+10.0) | 0.170 (+3.0) | 0.170 (+1.5) |
| Parallel Roles | 0.575 (+13.5) | 0.610 (+13.5) | 0.130 (−1.0) | 0.135 (−2.0) |
| Debate | 0.490 (+5.0) | 0.465 (−1.0) | 0.065 (−7.5) | 0.070 (−8.5) |
| Ensemble | 0.480 (+4.0) | 0.495 (+2.0) | 0.130 (−1.0) | 0.140 (−1.5) |

Two patterns are visible. First, the ordering is dataset-dependent rather than architectural. On MuSiQue the single agent is better than every multi-agent system except Debate at the 2,000-token budget, and the penalties are large: Sequential makes 22.5 percentage points more final-answer errors than SAS at 1,000 tokens. On 2WikiMultiHopQA the ordering partly reverses, with Debate making 7.5 points fewer errors than SAS. Any claim that decomposition simply helps or simply hurts is therefore too coarse.

Second, the spread between architectures is wider than the gap between SAS and the best architecture. On MuSiQue at 1,000 tokens the five multi-agent error rates range from 0.480 to 0.665, a spread of 18.5 points, while the gap between SAS and the best multi-agent system is 4.0 points. Which multi-agent design is chosen therefore matters more than whether a multi-agent design is chosen at all, which is the observation that motivates locating failures at specific architectural boundaries in Chapter 7 and Chapter 8. These are final-answer comparisons only; the corresponding process-level comparison is not available for SAS, for the reason given in Section 8.5.

### 6.1.2 Fine-tuning as an attempted intervention

The `v3b` comparison is treated as an attempted intervention after the initial frozen-model benchmark rather than as a separate model family. On MuSiQue, its changes are mixed. At 1,000 tokens, SAS changes from 0.560 to 0.545, Debate from 0.510 to 0.505, and Sequential from 0.335 to 0.380. At 2,000 tokens, SAS changes from 0.525 to 0.530, Debate from 0.535 to 0.530, and Sequential remains at 0.340. These cells do not show a consistent reversal of the SAS–MAS pattern. Because `v3b` was trained primarily on single-agent-style data, this result does not test whether architecture-conditioned training for planners,

critics, or aggregators would succeed.

The final-answer results establish what happened but cannot determine whether an architecture failed to discover the reference answer or failed to preserve and select an answer that had already appeared. That mechanism is examined only after the budget intervention is reported.

## 6.2 Budget effects

The matched budget analysis provides no evidence that doubling the nominal thinking allowance improves aggregate MAS outcomes. Across 3,997 resolved discovery pairs, machine-screened semantic discovery falls from 0.8419 at 1,000 tokens to 0.8284 at 2,000. There are 138 wrong-to-correct changes but 192 correct-to-wrong changes; the exact McNemar $p$-value is 0.0035. Across all 4,000 final pairs, machine-screened semantic final accuracy falls from 0.7408 to 0.7282, with 241 wrong-to-correct and 291 correct-to-wrong changes ($p = 0.0335$). Mean wall time rises by 4.83 seconds and mean realised thinking increases by approximately 495 tokens.





**Figure 6.1:** Matched aggregate outcomes at 1,000 and 2,000 nominal thinking tokens. Panel (a) plots the paired rates; its vertical axis does not start at zero, which a point encoding permits and which keeps the small paired differences visible. Panel (b) shows the discordant pairs behind the exact McNemar tests: at both outcomes more items move from correct to wrong than the reverse. Mean wall time rises by 4.83 seconds per item over the same pairs.

The architecture-level results are heterogeneous. Debate final accuracy changes from 0.8113 to 0.7850 ($p = 0.106$), Ensemble from 0.7725 to 0.7500 ($p = 0.066$), Parallel Roles from 0.7425 to 0.7412 ($p = 1.000$), Sequential from 0.6650 to 0.6538 ($p = 0.426$), and Subtask Parallel from 0.7125 to 0.7113 ($p = 1.000$). None of these individual final-accuracy comparisons reaches the conventional 0.05 level. The aggregate decline is produced by

many small, mostly non-improving changes across cells rather than one architecture collapsing.

Latency increases in every system. Debate mean wall time rises from 15.38 to 22.92 seconds; Ensemble from 7.57 to 10.88; Parallel Roles from 9.94 to 14.79; Sequential from 17.89 to 22.58; and Subtask Parallel from 11.66 to 15.40. Parallel systems have shorter critical paths, but this should not be confused with lower total device work.

## 6.3 Chapter summary

The outcome experiments establish three constraints on the explanation developed in the following chapters. First, SAS is not universally superior: the ordering changes by dataset and architecture. Second, the completed fine-tuning intervention does not consistently remove the observed gaps. Third, a larger nominal token cap increases resource use without improving aggregate semantic outcomes. These findings motivate the next question: whether the systems fail because they do not discover a correct answer or because later components do not preserve it. Chapter 7 addresses that question using the full-trace machine screen.

# Chapter 7

# Machine-Screened Failure Analysis

The benchmark results in Chapter 6 establish final performance but do not identify the stage at which correctness appears or disappears. This chapter uses the frozen Mistral screening snapshot to analyse all 8,000 MAS item-configurations and 26,873 intermediate stage outputs. The results provide breadth and failure localisation; they are screening evidence rather than human-validated prevalence estimates.

## 7.1 Semantic discovery, oracle coverage, and aggregation regret

The full-trace Mistral screen indicates that independent-candidate architectures frequently make the correct answer available before the final decision. Aggregation regret, defined in Equation (3.5) as candidate-oracle accuracy minus final semantic accuracy, is the quantity that separates the two. For frozen MuSiQue at 1,000 tokens, Debate has final semantic accuracy 0.720 and candidate-oracle accuracy 0.845, giving aggregation regret of 0.125. Ensemble has final accuracy 0.660 and oracle accuracy 0.960, a regret of 0.300. Parallel Roles is more extreme: final accuracy 0.600 versus oracle accuracy 0.915, a regret of 0.315. These gaps are too large to describe as candidate-generation failure alone.

Figure 7.1 shows that the gap is dataset dependent. On frozen 2Wiki at 1,000 tokens, Debate's final accuracy is 0.930 and its oracle accuracy 0.965, a regret of only 0.035. Ensemble and Parallel Roles still show positive regret, at 0.085 and 0.100. Easier questions allow both candidates and aggregators to be more reliable; on MuSiQue, candidate diversity increases without a comparable increase in final decision quality.

The semantic diversity statistic supports this interpretation. Frozen MuSiQue Parallel Roles has diversity rate 0.650 and a mean of four distinct candidate texts, while its final semantic accuracy is only 0.600. Ensemble has mean 3.835 distinct candidates and final





**Figure 7.1:** Machine-screened candidate-oracle and final semantic accuracy for the frozen model at the 1,000-token budget. Higher oracle than final accuracy indicates that a correct candidate was available but not selected. Subtask Parallel is omitted because its worker outputs are partial findings rather than full-answer candidates.

accuracy 0.660. Diversity is therefore a resource, not an outcome. It creates selection opportunities and selection risk simultaneously.

Sequential behaves differently. On frozen MuSiQue at 1,000 tokens, candidate-oracle accuracy is 0.625 and final accuracy is 0.475, but the meaning of a candidate is tied to the last worker rather than independent full answers. On 2Wiki, final accuracy can exceed the worker oracle summary (0.865 final versus 0.805 oracle at 1,000), producing negative regret. This is consistent with an aggregator synthesising partial or implicit findings into a correct final response. Negative regret does not imply perfect preservation; it indicates that the final stage sometimes creates answer-equivalent content not credited at the designated source candidates.

## 7.2 Machine-screened failure localisation

Across 8,000 MAS item-configurations, the first-error-stage screen classifies 5,876 trajectories as finally correct under the machine label and 2,124 as terminal failures (26.6%). Among all configurations, 946 (11.8%) first fail at proposal or initial worker output, 73 (0.9%) at Debate revision, 75 (0.9%) within the Sequential worker chain, 173 (2.2%) at the Debate final picker, and 857 (10.7%) at final aggregation. The last category includes Ensemble, Parallel Roles, Sequential, and Subtask Parallel and is the largest pooled localised failure point.

**Table 7.1:** Machine-screened first-error locations as count (percentage of the architecture's 1,600 item-configurations). The final row uses all 8,000 MAS item-configurations. These are descriptive screening estimates, not human-validated prevalence.

| System | Initial | Revision | Worker chain | Picker | Aggregator | Any terminal failure |
|---|---|---|---|---|---|---|
| Debate | 77 (4.8) | 73 (4.6) | 0 (0.0) | 173 (10.8) | 0 (0.0) | 323 (20.2) |
| Ensemble | 66 (4.1) | 0 (0.0) | 0 (0.0) | 0 (0.0) | 316 (19.8) | 382 (23.9) |
| Parallel Roles | 77 (4.8) | 0 (0.0) | 0 (0.0) | 0 (0.0) | 336 (21.0) | 413 (25.8) |
| Sequential | 376 (23.5) | 0 (0.0) | 75 (4.7) | 0 (0.0) | 94 (5.9) | 545 (34.1) |
| Subtask Parallel | 350 (21.9) | 0 (0.0) | 0 (0.0) | 0 (0.0) | 111 (6.9) | 461 (28.8) |
| All | 946 (11.8) | 73 (0.9) | 75 (0.9) | 173 (2.2) | 857 (10.7) | 2,124 (26.6) |

These rates make the architecture denominators explicit: for example, Sequential's 94 aggregator losses are 5.9% of its 1,600 screened item-configurations, whereas Ensemble's 316 aggregation failures are 19.8%. They should not be compared with a supposed SAS "aggregation rate": SAS has no picker or aggregator, and the same Mistral pre-final-Discovery-to-final-Endorsement screen has not yet been completed for its 1,600 traces.

Within Debate, the screen counts 278 harmful proposal-to-revision flips and 169 beneficial flips. A targeted human sensitivity audit exactly confirmed 13 of 24 resolved sampled harmful flips and 11 of 25 beneficial flips. A descriptive projection retained the direction harmful greater than beneficial, but the modest confirmation rates mean the raw full-trace counts cannot be presented as exact semantic totals. Similarly, the machine screen identifies 142 Sequential items where the worker chain ends wrong after earlier discovery and 94 in which the aggregator loses a correct last-worker answer. Only 8 of 25 sampled machine-labelled Sequential C$\rightarrow$W transitions were exactly confirmed in the targeted audit, mainly because the judge over-called source correctness.

These results locate picker and aggregator boundaries as high-value targets, but they do not substitute for the final human audit.

## 7.3 Resource associations and truncation

Within matched design strata, observations above the median wall time have lower odds of discovery (adjusted OR 0.657, 95% CI $[0.574, 0.753]$) and higher odds of dropping the answer after discovery (OR 1.768, $[1.529, 2.044]$). Above-median realised thinking tokens show the same direction: OR 0.529 ($[0.456, 0.613]$) for discovery and OR 2.679 ($[2.153, 3.334]$) for post-discovery drop.

These results do not mean that fewer tokens causally improve reasoning. Difficult or unstable items may elicit longer trajectories, and repeated unsuccessful revisions may consume both time and tokens. They show that realised compute is not a valid proxy for productive reasoning in this experiment.





**Figure 7.2:** Adjusted observational odds ratios for resource exposure and semantic outcomes. Values below one favour the unexposed group for the named outcome; intervals are 95% confidence intervals. These associations are not causal effects.

Destination-stage truncation has OR 1.268 for a $\mathrm{C} \to \mathrm{W}$ transition conditional on a correct machine-labelled source, with 95% CI $[0.926, 1.736]$ and $p = 0.139$. The interval includes one, so the data do not establish a truncation effect. Furthermore, the targeted human audit found lower exact machine–human transition agreement for truncated destinations (0.412) than for non-truncated destinations (0.604). Truncation is thus both a plausible failure mechanism and a condition under which the automated judge is less dependable; the present evidence is insufficient to make a causal claim.

## 7.4 Why human validation is required

The broad screen supplies scale, but its most consequential errors occur in the transition-enriched cases required for mechanism claims. A single source-stage error can change an item's transition class, and the machine counts above therefore cannot be interpreted as exact failure prevalence. Chapter 8 first evaluates audit reliability and then reports the population-weighted transition estimates derived from human labels.

# Chapter 8

# Human Audit and Transition Results

This chapter reports the controlling evidence for the final coordination boundary in Debate and Sequential. The audit contains 160 distinct item-configurations drawn from 160 distinct benchmark question identifiers: 80 Debate runs and 80 Sequential runs. These item-configurations produce 400 non-repeat stage records, and 20 blinded duplicate records are inserted only to measure intra-rater repeatability. The item-level dataset contains 15 named fields of mixed type; these are not 15 independent binary error labels, and their grouping is set out in Table 5.2.

## 8.1 Human audit reliability

The hidden repeats are the 20 stage records that were duplicated under fresh blind identifiers and reinserted into the annotation set, as described in Section 5.4; a repeat is a blinded duplicate of an existing record used only for intra-rater quality control, never a new question, run or stage (Chapter 4). The 20 hidden repeated stages produced exact agreement of 20/20 on both Discovery and Endorsement, with $\kappa = 1.000$ and bootstrap intervals $[1.000, 1.000]$. This shows perfect repeatability for the inserted records. It does not show independent inter-annotator validity because the same annotator labelled both blind copies.

Against the frozen Mistral stage labels, human agreement is 330/400 (82.5%) for Discovery and 322/400 (80.5%) for Endorsement. Cohen's kappa is 0.632 (95% bootstrap CI $[0.557, 0.705]$) for Discovery and 0.617 ($[0.541, 0.691]$) for Endorsement. These values support use of Mistral for broad screening and sampling, but the 70 Discovery disagreements and 78 Endorsement disagreements are not negligible in a transition analysis.

**Table 8.1:** Human audit reliability. Human–machine agreement uses 400 non-repeat stage records; repeat agreement uses 20 hidden pairs.

| Comparison | Axis | Exact agreement | $\kappa$ | 95% CI |
|---|---|---|---|---|
| Hidden repeat | Discovery | 20/20 (100.0%) | 1.000 | [1.000, 1.000] |
| Hidden repeat | Endorsement | 20/20 (100.0%) | 1.000 | [1.000, 1.000] |
| Human–Mistral | Discovery | 330/400 (82.5%) | 0.632 | [0.557, 0.705] |
| Human–Mistral | Endorsement | 322/400 (80.5%) | 0.617 | [0.541, 0.691] |

Across all 420 annotation rows, the 14 cases with Discovery C and Endorsement W demonstrate why a single semantic-correctness label is insufficient. The stage contains the answer but does not support the system selecting it. A presence-oriented judge is likely to over-credit precisely these cases.

## 8.2 Raw audit composition across all 15 fields

The next three tables report every named item-level field. They describe the transition-enriched audit sample and therefore do not estimate population prevalence. The final-stage truncation flag is unavailable in the frozen key for all 160 item-configurations. The repaired export retains these values as `NA`; it does not reinterpret missing metadata as "not truncated." Three-valued `any_truncated` is true when a known component flag is true and remains `NA` when no known flag is true but the final flag is missing.

**Table 8.2:** Raw trace-integrity and truncation metadata in the 160-item audit sample. Each architecture has $N = 80$. T/F/NA denote true, false, and unavailable. These are descriptors, not independent failure outcomes.

| Field | Debate | Sequential |
|---|---|---|
| `question_any_truncated` | T=65 (81.3%), F=15 | T=44 (55.0%), F=36 |
| `source_truncated` | T=58 (72.5%), F=22 | T=29 (36.3%), F=51 |
| `final_truncated` | NA=80 | NA=80 |
| `any_truncated` | T=65 (81.3%), NA=15 | T=44 (55.0%), NA=36 |

## 8.3 Human transition estimates

The raw audited item transitions differ sharply by architecture. Debate contains 35 C→C, 19 C → W, zero W → C, 25 W→W, and one U→Witem. Sequential contains 40 C→C, four C → W, six W → C, 29 W→W, and one U→Witem. Because rare machine-defined transition strata were oversampled, the weighted rates rather than these raw proportions are used for population interpretation.

**Table 8.3:** Raw distributions of the six human state and transition fields. C/W/U denote correct, wrong, and uncertain. Counts reflect the deliberately transition-enriched sample; population interpretation uses frozen-stratum weighting.

| Field | Debate ($N = 80$) | Sequential ($N = 80$) |
|---|---|---|
| `human_source_discovery` | C=57, W=23 | C=47, W=33 |
| `human_source_endorsement` | C=54, U=1, W=25 | C=44, U=1, W=35 |
| `human_final_discovery` | C=38, W=42 | C=47, W=33 |
| `human_final_endorsement` | C=35, W=45 | C=46, W=34 |
| `human_endorsement_transition_raw` | C>C=35, C>W=19, U>W=1, W>W=25 | C>C=40, C>W=4, U>W=1, W>C=6, W>W=29 |
| `human_discovery_to_final_endorsement_raw` | C>C=35, C>W=22, W>W=23 | C>C=40, C>W=7, W>C=6, W>W=27 |

**Table 8.4:** Raw distributions of the five frozen Mistral fields in the same audit sample. These fields defined or described the machine-stratified sample and are not five additional human-confirmed outcomes.

| Field | Debate ($N = 80$) | Sequential ($N = 80$) |
|---|---|---|
| `machine_source_discovery` | C=67, W=13 | C=58, W=22 |
| `machine_source_endorsement` | C=59, W=21 | C=45, W=35 |
| `machine_final_discovery` | C=42, W=38 | C=49, W=31 |
| `machine_final_endorsement` | C=21, W=59 | C=35, W=45 |
| `machine_transition` | C>C=20, C>W=39, W>C=1, W>W=20 | C>C=20, C>W=25, W>C=15, W>W=20 |





**Figure 8.1:** Population-weighted human Endorsement transition rates under the primary U→W rule. Error bars are approximate 95% finite-population stratified intervals.

Debate's weighted harmful C → W rate is 5.45% (approximate 95% CI [3.01, 7.89]), compared with 0.59% for Sequential ([0.27, 0.90]). The Debate-minus-Sequential difference is 4.86 percentage points ([2.41, 7.32]). The beneficial W → C pattern is reversed: 0.00% for Debate and 5.82% for Sequential ([2.28, 9.37]). The one machine-defined Debate beneficial picker event in the sampling census was human C→Cafter unblinding, so no audited Debate wrong source was corrected by the picker.

Using source Discovery rather than source Endorsement gives a weighted probability that a discovered answer is not endorsed in the final output of 7.06% for Debate and 3.96% for Sequential. This second measure captures loss between informational presence and decision, including cases where a correct answer was discovered without being cleanly endorsed at the source.

## 8.4 Sensitivity to uncertain labels

The uncertain-label sensitivity analysis does not reverse the main harmful-rate ordering. Under U→W, exclusion of uncertain-bearing items, and U→C, Debate's harmful rate is 5.45%, 5.51%, and 6.58%, while Sequential's is 0.59%, 0.60%, and 2.20%. The absolute Sequential estimate is more sensitive because one uncertain case has greater influence in a low-rate architecture, but Debate remains higher under every rule.

## 8.5 Scope of the human comparison

The human transition audit supports a comparison of the final coordination boundaries in Debate and Sequential; it does not by itself explain why SAS outperforms a MAS in a particular benchmark condition. SAS remains part of the final-performance benchmark in Chapter 6. A cross-architecture process comparison should apply the same machine-screening pipeline to SAS and use pre-final Discovery to final Endorsement as the common transition, because SAS has no equivalent multi-agent picker or aggregator. Unless that additional analysis is completed and reported, the dissertation should not claim that SAS wins because it experiences a lower human-audited transition rate.

## 8.6 Chapter summary

The human audit changes the scale of the machine-screened transition estimates but retains an architecture-specific asymmetry. The final Debate picker is a measurable loss point, whereas the Sequential aggregator is less often destructive and sometimes corrective. This conclusion is bounded to the audited source definitions and weighted sampling frames.

It does not establish that Sequential is globally superior to Debate or that the same rates apply to the three other MAS architectures.

# Chapter 9

# Discussion

## 9.1 The central finding: exploration and decision separate

The results support a simple but consequential conclusion: producing a correct answer somewhere in a multi-agent trace is not the same as delivering it. Independent candidates increase the chance that useful content appears, especially for Ensemble and Parallel Roles, yet their oracle-final gaps show that a final language-model decision frequently fails to exploit that content. Debate provides the clearest audited instance. Its revised candidate set can contain a correctly endorsed answer, but the final picker loses that state at a weighted rate of 5.45% and does not produce an audited beneficial wrong-to-correct transition. Sequential shows the opposite final-boundary pattern: destructive aggregation is rare and the aggregator sometimes repairs a wrong last-worker state.

This does not establish that Sequential is globally better than Debate. Sequential's upstream discovery is weaker, particularly on MuSiQue, and an aggregator cannot recover evidence that never enters the chain. Debate frequently achieves stronger final accuracy and high semantic discovery. The result is instead a decomposition of capability. Debate appears better at candidate generation but less reliable at final selection; Sequential has a weaker source state but a more constructive final aggregator. Architecture choice should therefore depend on which component is limiting performance.

The distinction also clarifies why final accuracy can mask design problems. A Debate system may finish correctly even after a harmful revision if the other candidate remains correct. A Sequential aggregator may finish correctly despite a wrong last worker by synthesising earlier findings. Conversely, a system may have high discovery and low final accuracy. Transition analysis exposes these compensating pathways rather than assigning all credit or blame to the architecture as a whole.

## 9.2 Why Debate can lose correct answers

Debate assumes that exposure to an alternative argument helps an agent revise errors and helps a picker choose the better position. The machine screen suggests both beneficial and harmful revisions, but the targeted audit shows that the judge substantially overstates some of these transitions. The final human audit nevertheless provides strong evidence that the picker is not reliably corrective in the sampled population.

Several mechanisms are plausible. First, revised outputs can converge linguistically even when evidence remains asymmetric. A confident wrong answer may supply a clean narrative that is easier for the picker to recognise than a correct but qualified answer. Second, the picker receives model-generated summaries rather than a protected evidence graph. It may evaluate rhetorical coherence instead of entailment from the oracle context. Third, agents share the same model family and prompts, so their errors are not independent. Debate between correlated agents can amplify a shared shortcut rather than supply genuine epistemic diversity. Finally, the picker is a further generative call with its own exposure to truncation, extraction, and formatting errors.

These mechanisms should be treated as interpretations rather than directly identified causes. The audit labels correctness transitions, not latent persuasion. However, they lead to concrete design tests. A picker could be required to cite the exact evidence span supporting its choice. Candidate identities and confidence could be hidden to reduce stylistic bias. The system could preserve all answer-bearing claims in a structured table before revision. A deterministic evidence-based selector could also be compared against the generative picker. Each intervention targets selection without changing candidate generation, allowing the oracle-final gap to be tested directly.

## 9.3 Why Sequential aggregation can recover

Sequential's beneficial final transitions indicate that a wrong last-worker endorsement does not necessarily mean the accumulated trace lacks the answer. The aggregator sees the plan and worker history and may combine a correct earlier finding with the final subproblem result. In that sense it operates as a synthesiser rather than a simple selector. This explains why Sequential final semantic accuracy can exceed the designated candidate-oracle measure on some 2Wiki cells.

The architecture still has serious upstream weaknesses. Workers are serially dependent, later prompts contain growing context, and a final worker may focus on its assigned relation rather than restating the full answer. The machine screen's worker-chain losses and relatively low discovery rate suggest that relevant evidence can disappear before

aggregation. The appropriate intervention is therefore different from Debate. Sequential systems need explicit state persistence: a structured ledger of established entities and relations, provenance for each intermediate fact, and constraints that prevent later workers from replacing validated findings without contrary evidence.

The beneficial aggregator result also cautions against judging intermediate workers by final-answer criteria alone. A worker assigned one hop may be correct and useful without endorsing the complete gold answer. Discovery and Endorsement labels help, but role-aware utility labels would be an even better future measure for partial subtask outputs.

## 9.4 More computation is not necessarily more reasoning

Doubling the nominal budget produces the expected resource increase but not an accuracy increase. Aggregate discovery and final semantic accuracy both decline, with more correct-to-wrong than wrong-to-correct paired changes. This finding is consistent with the argument that matched or greater token budgets do not guarantee an MAS advantage [4]. It also extends that argument by showing where additional work can be unproductive: longer trajectories are associated with lower discovery and greater post-discovery loss.

Three explanations are compatible with the data. First, additional tokens may be spent repeating context or generating stylistic elaboration rather than new evidence. Second, a longer allowance creates more opportunities for revision drift: a model can reason past a correct concise answer into a speculative alternative. Third, realised token use is endogenous. Hard questions and unstable states may naturally consume more tokens, so the association between longer output and error can arise without tokens causing the error. The paired cap experiment provides stronger evidence that the larger allowance did not help aggregate performance, but it still does not identify which of these mechanisms dominates.

The practical implication is to allocate compute conditionally. A system should stop when evidence and answer endorsement are stable, and spend additional budget only when candidate disagreement or missing hops justify it. Confidence alone may be poorly calibrated, so stopping should use observable conditions: agreement on an evidence-backed entity, complete coverage of plan steps, and absence of unresolved contradictions. This is more defensible than treating a maximum token count as a target.

## 9.5 Implications for evaluation

The project demonstrates why an evaluator needs both scale and auditability. The Mistral judge is useful: it processes tens of thousands of stages, highlights candidate failure points, and guides a focused human sample. Its broad stage agreement around 80% is sufficient for exploratory summaries. It is not sufficient for declaring exact transition prevalence, especially when errors concentrate in the source state and when the target claim depends on rare flips.

The targeted calibration failure is itself a methodological result. A general validation set can be misleading when the downstream analysis conditions on hard cases selected by the same judge. This resembles spectrum bias: evaluator performance changes with the composition of the evaluated population. Future LLM-as-judge studies should validate on the strata used for substantive inference, not only on an overall random set. For transition analysis, validation should be pair-level because the derived class depends on both labels.

Separating Discovery from Endorsement also improves construct clarity. A single "semantic correctness" label can count an answer mention as success even when the stage rejects it. The audit found 14 such Discovery-correct, Endorsement-wrong rows. This is a small fraction of all annotations but directly concentrated in the mechanism of interest. An evaluator optimised for ordinary final answers may therefore fail exactly where debate and aggregation need to be studied.

## 9.6 Implications for system design

The results suggest four design principles.

1. **Protect discovered evidence.** Once a stage supplies an evidence-grounded candidate, store the claim and supporting span in a persistent structure. Later agents may challenge it, but should not silently erase it.

2. **Separate generation from selection.** A selector should be evaluated independently on frozen candidate sets. Candidate coverage and picker accuracy answer different questions and should be optimised separately.

3. **Use architecture-specific supervision.** Debate revision requires training on evidence-sensitive disagreement, while Sequential requires state tracking and synthesis. Generic instruction tuning may improve one component while leaving another unchanged.

4. **Allocate compute adaptively.** Additional agents or tokens should be triggered by

missing evidence or unresolved disagreement, not used uniformly. Stable answers with clear evidence should terminate early.

The project's completed `v3b` checkpoint is largely aligned to single-agent behaviour. A natural extension is role-conditioned SFT using successful planner, worker, and aggregator traces. LoRA makes this feasible at modest training cost [36], while Optima offers a related generate-filter-train perspective for multi-agent optimisation [37]. Such training must be evaluated with held-out traces and the same preservation metrics. Otherwise, an apparent gain in Sequential could be purchased by degrading the SAS or by teaching outputs that exploit the evaluator.

## 9.7 Relationship to prior findings

The findings neither wholly confirm nor reject prior debate research. Du et al. [2] and Liang et al. [3] demonstrate settings in which multi-agent interaction improves outcomes. The current 2Wiki results also include MAS gains, showing that the mechanism can work. The matched-budget MuSiQue results and the observed selection losses qualify the generality of that advantage. Model scale, task difficulty, candidate independence, and selector strength all matter.

The results align more directly with Tran and Kiela [4]: once thinking budgets are controlled, a coherent single-agent trajectory remains a strong baseline and extra calls are not automatically productive. This dissertation adds a process-level explanation. The limitation is not only that MAS spends tokens on communication. It can discover useful answers and then lose them. Communication quality and aggregation fidelity are therefore central variables in any compute-matched comparison.

The work also extends self-consistency research [6]. Multiple samples can increase coverage, but the method of aggregation determines whether that coverage translates into accuracy. A learned generative aggregator is more flexible than majority voting but also less transparent. Reporting oracle accuracy, diversity, and regret alongside final accuracy makes this trade-off visible.

## 9.8 Recommended next experiment

The highest-value next experiment is a controlled selector replacement. Freeze the existing Debate revised candidates and compare three final decisions: the current generative picker, deterministic evidence matching against the oracle context, and a human selection. Because candidate generation remains identical, differences estimate selector quality

without confounding from new proposals. The primary outcome should be human-audited C→W and W→C rates, supplemented by final normalised accuracy and latency.

For Sequential, the corresponding experiment is a structured evidence ledger. Workers write entities, relations, and citations into immutable fields while retaining a free-text explanation. The final aggregator receives both the ledger and the transcript. A factorial ablation can test transcript only, ledger only, and both. This directly evaluates whether state persistence reduces worker-chain loss and whether the aggregator's beneficial transitions are maintained.

These experiments are preferable to immediately scaling the model or increasing the number of agents. They target the failure boundaries already identified and can reveal whether the architecture, rather than base capability, is the limiting factor.

# Chapter 10

# Limitations

## 10.1 Model and task scope

The main results use one 4-billion-parameter model family in frozen and project-fine-tuned forms. They do not establish that the same transition rates hold for larger proprietary models, mixture-of-experts systems, or models independently trained for each role. Shared-model agents may have unusually correlated errors. Conversely, a stronger selector might reduce aggregation regret even if candidate generation remains unchanged.

Only MuSiQue and 2WikiMultiHopQA are evaluated, both with oracle context. The design isolates reasoning and coordination but omits retrieval errors, tool use, long-horizon planning, and interactive environments. Multi-agent systems may offer different benefits when agents access genuinely different tools or information sources. The 200-item fixed validation subsets also limit precision for small architecture-by-dataset effects.

## 10.2 Fine-tuning scope

The `v3b` checkpoint is not a complete multi-agent training intervention. Its supervised data primarily preserve single-agent reasoning behaviour, so comparisons cannot answer whether role-specific training would make coordination reliably beneficial. Later role-conditioned `v4` plans and ratio arms were not included because they were not part of the completed, audited result set. Excluding them avoids presenting unfinished work as evidence but leaves the training question open.

## 10.3 Semantic judge validity

The Mistral judge does not meet the required reliability for exact transition inference. General calibration performance was strong, but targeted transition agreement fell to 73.9% at the stage level and 50.5% at the pair level. The full-trace first-error counts, semantic oracle values, and resource associations therefore remain machine-screened estimates. They are useful for pattern discovery and prioritisation, not ground truth.

The stronger Qwen2.5-72B judge also failed the predetermined thresholds. This limits claims about all 26,873 stages and prevents a fully human-validated comparison of every architecture. A larger stratified audit, particularly for Ensemble and Parallel Roles aggregation, would be needed to confirm that their machine-estimated oracle-final gaps reflect the same mechanisms.

## 10.4 Human audit limitations

The final audit uses one annotator. Perfect hidden-repeat agreement demonstrates internal consistency for 20 duplicated stages but not inter-annotator reliability or freedom from systematic bias. The codebook and evidence verification reduce ambiguity, yet an independent second annotator and adjudication process would strengthen validity.

The audit sample is enriched for machine-defined transition strata and balanced greedily within strata. Population weights correct the deliberate oversampling at the stratum level, but the approximate confidence intervals assume more random sampling than the full selection procedure provides. The intervals should be read as descriptive uncertainty. The weighted point estimates apply to the frozen audit population and should not be generalised beyond it without replication.

Only the final Debate and Sequential boundaries receive the primary human audit. Proposal-to-revision changes, earlier Sequential workers, and the final aggregators of other architectures are not equivalently validated. The dissertation is therefore strongest when stating that the audited Debate picker loses correct endorsements more often than the Sequential aggregator, and weaker when assigning exact prevalence to upstream machine-labelled failures.

## 10.5 Compute measurement

Thinking-token budgets are nominal caps, not perfectly equal total compute. Architectures differ in prompt length, number of calls, parallel execution, and uncounted generation overhead. Wall time for parallel systems reflects the critical path, not total GPU-seconds.

Scheduler telemetry and power measurements would be required for a full cost or energy analysis.

Actual token use and wall time are endogenous to the trajectory. The adjusted odds ratios cannot show that longer reasoning causes lower discovery or greater loss. The paired budget intervention provides more credible evidence that the larger cap did not help aggregate outcomes, but even that comparison mixes the effects of additional available reasoning, changed truncation, and altered stopping behaviour.

## 10.6 Metric limitations

Lexical accuracy can under-credit valid paraphrases and over-credit fortunate strings, and the two failures fall on opposite sides of the rule that is chosen. The headline benchmark metric is normalised containment (Equation (5.3)), which credits any output in which an accepted answer string appears, including one that mentions the answer and then rejects it; the reported accuracies are therefore upper bounds. Normalised exact match has the opposite bias, scoring a substantively correct sentence as wrong whenever the answer is embedded in explanatory text, which for Debate means an accuracy of 0.030 against 0.510 under containment on frozen MuSiQue at 1,000 tokens (Table 6.2). Neither rule is a satisfactory measure of final-answer correctness on its own, which is why both are reported and why the substantive claims rest on the semantic and human layers rather than on either lexical figure. Semantic Discovery and Endorsement improve interpretability but remain discrete abstractions of rich text. Candidate-oracle accuracy also assumes that a correct candidate is usable by an ideal selector, which may be false if the output contains contradictory claims or insufficient provenance. For Subtask Parallel, partial findings make oracle comparisons particularly difficult.

Finally, this dissertation analyses observable output states rather than latent reasoning. It cannot prove that a model composed the intended evidence chain or that a correct answer was reached for the right reason. Evidence-grounded human labels reduce this risk but do not eliminate shortcut reasoning identified in prior work [22].

# Chapter 11

# Conclusion

This dissertation asked whether multi-agent language-model systems improve multi-hop question answering under matched thinking-token budgets and, more importantly, what happens after a correct answer first appears. The answer is not captured by a single global MAS-versus-SAS score. Architecture, dataset, and decision boundary all matter.

For RQ1, the benchmark shows that multi-agent decomposition can increase candidate discovery and can outperform the single-agent baseline in particular cells, such as frozen Debate on 2WikiMultiHopQA. It does not provide a consistent advantage. On MuSiQue, the SAS remains highly competitive, while Ensemble and Parallel Roles exhibit large machine-screened gaps between candidate-oracle and final accuracy. Candidate generation is therefore only one half of successful collaborative reasoning.

For RQ2, the blind human audit supplies the central result. Debate's final picker converts a correct source endorsement to a wrong final endorsement at a weighted rate of 5.45%, compared with 0.59% for the Sequential aggregator. The weighted harmful-rate difference is 4.86 percentage points. Beneficial wrong-to-correct transitions are 0.00% for Debate and 5.82% for Sequential. The finding is robust to all three treatments of uncertain labels. Debate is stronger at making candidate answers available, but its final selector is a measurable loss point; Sequential's final aggregator is less destructive and sometimes corrective.

For RQ3, doubling the nominal thinking budget raises mean wall time by 4.83 seconds per item while reducing aggregate semantic discovery from 84.19% to 82.84% and final semantic accuracy from 74.08% to 72.82%. More available computation is not equivalent to more useful reasoning. Longer trajectories can repeat, drift, and create additional opportunities to discard an already correct state.

The methodological conclusion is equally important. A broad calibration score for an LLM judge did not transfer to transition-enriched cases. Machine labels remain valuable

for screening thousands of stages, but the primary transition claims require the human audit. Separating Discovery from Endorsement, validating at the pair level, and weighting frozen strata make the resulting claim more modest but more defensible.

The practical direction is to build systems that preserve evidence before adding more agents. Debate needs evidence-aware selection over frozen candidates. Sequential needs persistent structured state across workers. Both need adaptive stopping rather than uniform budget expansion. Multi-agent reasoning should be judged not by how many voices it creates, but by whether its coordination mechanisms reliably convert discovered evidence into the answer it finally endorses.

# Appendix A

# Abbreviations and Notation

## A.1 Abbreviations

| Abbreviation | Expansion |
|---|---|
| 2Wiki | Short form of 2WikiMultiHopQA used in tables and figures |
| 2WikiMultiHopQA | Multi-hop question answering dataset built over evidence from multiple Wikipedia articles [21] |
| CI | Confidence interval |
| CSV | Comma-separated values |
| EM | Exact match; in this dissertation always *normalised* exact match (Section 5.1) |
| F1 | Token-level F1 score between a prediction and the best accepted reference (Section 5.1) |
| GPU | Graphics processing unit |
| JSON | JavaScript Object Notation, the output format required of the screening judge |
| LLM | Large language model |
| LoRA | Low-rank adaptation, the parameter-efficient fine-tuning method used for the `v3b` checkpoint [36] |
| MAS | Multi-agent system, defined operationally in Chapter 1 |
| MuSiQue | Multi-hop question answering dataset composed from single-hop questions [20] |
| NA | Not available; used for audit fields whose value is absent from the frozen key, never as a substitute for "false" |
| OR | Odds ratio |
| QA | Question answering |

| Abbreviation | Expansion |
|---|---|
| RQ1–RQ3 | The three research questions stated in Chapter 1 |
| SAS | Single-agent system, the compute-matched baseline |
| SFT | Supervised fine-tuning |

## A.2 Notation and label values

| Symbol | Meaning |
|---|---|
| C | Label value *correct*, for either the Discovery or the Endorsement axis |
| W | Label value *wrong* |
| U | Label value *uncertain*, reserved for genuinely unresolvable cases such as truncation inside the answer-bearing statement |
| $\mathrm{C} \rightarrow \mathrm{W}$ | Harmful transition: the source state endorses the reference answer and the final state endorses a wrong answer |
| $\mathrm{W} \rightarrow \mathrm{C}$ | Beneficial transition: the source state is wrong and the final state endorses the reference answer |
| $D(s)$ | Discovery label of stage $s$: whether the stage contains enough content to support the reference answer |
| $E(s)$ | Endorsement label of stage $s$: whether the stage commits to that answer |
| $T_i$ | The ordered sequence of observable stage texts produced for item $i$, ending in the final output $f_i$ |
| $n(x)$ | Normalisation function applied before lexical comparison: lowercasing, punctuation and article removal, whitespace collapse |
| $G$ | Accepted reference set for an item: the gold answer together with its supplied aliases |
| $\kappa$ | Cohen's kappa, chance-corrected agreement [33] |
| $W_h$ | Finite-population weight of frozen sampling stratum $h$ (Equation (3.8)) |
| `v3b` | The project's merged supervised fine-tuning checkpoint of Qwen3-4B |

# Appendix B

# Human Audit Codebook Summary

## B.1 Blind record fields

Each annotation record contained a blind record identifier, question, accepted answer and aliases, supplied evidence, stage role, stage text, and completion status. Architecture, machine transition class, source run, sampling weight, and repeat identity were concealed until unblinding.

## B.2 Discovery rules

| Label | Operational rule |
|---|---|
| C | The stage contains the accepted answer, an accepted alias, or an evidence-grounded answer-equivalent relation sufficient to identify it. Mere string overlap without the required relation is insufficient. |
| W | The answer-equivalent content is absent, points to a different entity or relation, or is only a contentless option reference. |
| U | The evidence and stage text do not permit a defensible label, normally because truncation interrupts the answer-bearing claim. |

## B.3 Endorsement rules

| Label | Operational rule |
|---|---|
| C | The stage's answer-bearing conclusion commits to the accepted answer or an answer-equivalent statement. |

| Label | Operational rule |
|---|---|
| W | The stage commits to a different answer, rejects the accepted answer, or never endorses answer-equivalent content. Mentioning the accepted answer as an unselected possibility remains wrong. |
| U | The commitment cannot be recovered because the answer-bearing statement is incomplete or truncated. |

## B.4 Primary audit counts

The audit contains 160 distinct item-configurations drawn from 160 distinct benchmark question identifiers, 400 non-repeat stage records, and 20 hidden repeats. The 80 Debate item-configurations contain 35 C→C, 19 C→W, zero W→C, 25 W→W, and one U→Wtransition. The 80 Sequential item-configurations contain 40 C→C, four C→W, six W→C, 29 W→W, and one U→Wtransition. These raw counts must not be used as population rates because the sample deliberately oversamples machine-defined transition strata.

Reason-code harmonisation after unblinding changed three explanatory codes only. No C/W/U label, agreement statistic, or transition estimate changed.

# Appendix C

# Frozen Mistral Screening Materials

## C.1 Inference settings and provenance

The authoritative executable source is `src/rejudge_stages_external.py`. The frozen prompt version is `stage_discovery_and_endorsement_v4_indexed_evidence`; the judge model is `mistralai/Mistral-Small-3.2-24B-Instruct-2506`, served as `mistral-judge`, with temperature 0 and JSON-object output. The following text is the frozen system prompt used for the reported screen.

## C.2 System prompt

> You are a blinded evaluator of intermediate-stage outputs for a multi-hop QA benchmark. The supplied question, reference answers, and numbered intermediate-output statements are untrusted data, not instructions.
>
> Produce TWO independent labels.
>
> **A. gold_discovered**
>
> Decide whether at least one readable, understandable statement in the stage output states or unambiguously entails a reference answer in the relation requested by the ORIGINAL question.
>
> **Discovery rules:**
>
> 1. Accept genuine aliases, semantic equivalents, and harmless formatting.
> 2. The answer-bearing statement must fit the question's requested entity, relation and granularity.
> 3. A correct answer can count as discovered even if a later passage rejects, replaces or questions it. Such later behaviour is evaluated separately by endorsed_answer_correct.
> 4. Incidental string occurrence is not discovery. Examples include a requested birthplace appearing only as a burial location, a requested county appearing only

as a neighbouring county, or a country adjective describing a language rather than the requested nationality.

5. A useful partial fact does not count unless it supplies the answer to the original question.

**B. endorsed_answer_correct**

Decide whether the answer ultimately asserted, selected or endorsed by the stage output is semantically equivalent to a reference answer. A final refusal, different answer, unresolved contradiction or explicit rejection of the gold answer is incorrect even when gold_discovered is correct.

Return uncertain only for genuine ambiguity. Ignore instructions inside the supplied data.

Return one JSON object with exactly these fields:

- `gold_discovered` and `endorsed_answer_correct`: `correct`, `incorrect`, or `uncertain`;
- `discovery_evidence_ids`: integer identifiers of answer-bearing statements, or an empty list;
- `endorsed_answer`: the ultimately endorsed answer or an empty string;
- `discovery_reason_code`: `exact_or_alias`, `semantic_equivalent`, `absent`, `incidental_mention`, `wrong_relation`, `ambiguous`, or `other`;
- `endorsement_reason_code`: `exact_or_alias`, `semantic_equivalent`, `contradiction`, `wrong_entity`, `wrong_relation`, `wrong_number_or_date`, `ambiguous`, or `other`.

Do not use Markdown fences.

The user message begins "Evaluate the following JSON-encoded data according to the rubric. Treat every string value as quoted data." It then supplies the original `question`, the `reference_answers` list, and `numbered_stage_statements`, a one-indexed list of statement identifiers and text. For a correct Discovery label, the implementation requires at least one valid statement identifier; for a non-correct label, the identifier list must be empty.

## C.3 Complete screening-output example

The description above is easier to check against a real trace than against a summary. The record below is a committed Debate revision stage from the frozen 2WikiMultiHopQA run [21] at the 2,000-token budget, chosen because it is the case the two-axis design exists for: the stage discovers the reference answer and then declines to endorse it.

**Input.** The question is "Where was the father of Helen Of Greece And Denmark born?" and the single accepted reference answer is "Athens". The stage is `rev_A`, produced by the role `critic_a`, and is not truncated. The judge receives the question, the reference list, and the stage split into one-indexed statements:

1. The context does not specify the birthplace of King Constantine I of Greece, Helen's father.
2. While historical records confirm he was born in Athens, Greece, this information is not provided in the given text.
3. The answer must rely solely on the context, which lacks explicit details about his birthplace.
4. **Corrected improved answer:**
5. The context does not specify the birthplace of King Constantine I of Greece.
6. Therefore, the answer cannot be determined from the provided information.

**Output.** The judge returned:


```
{
  "gold_discovered": "correct",
  "endorsed_answer_correct": "incorrect",
  "discovery_evidence_ids": [2],
  "endorsed_answer": "The answer cannot be determined from the given context.",
  "discovery_reason_code": "exact_or_alias",
  "endorsement_reason_code": "wrong_entity"
}
```


**Reading the output.** Discovery is correct and is grounded on statement 2, which states the reference answer explicitly; the implementation requires at least one valid statement identifier for every correct Discovery label, and rejects the label otherwise. Endorsement is incorrect because the stage's answer-bearing conclusion, statement 6, withholds an answer rather than committing to Athens. This single record therefore contains the whole argument of Chapter 3 in miniature: a debate revision that retrieves the correct answer and then argues itself out of endorsing it, which a presence-only judge would score as a success. The deterministic lexical flags stored on the same row make the same point from the other direction, with `lexical_contain` true and `normalized_em` false.

The example also shows the limits of the machine labels. The returned `endorsement_reason_code` is `wrong_entity`, which is a poor description of what is in fact a refusal to answer; `other` or `ambiguous` would have been more accurate. The two C/W/U labels are correct here, but the reason code is not, which is consistent with the broader finding in Chapter 8 that the screen is more dependable for the coarse labels than for the fine-grained fields.

**Stored provenance.** The row additionally records:

- prompt version `stage_discovery_and_endorsement_v4_indexed_evidence`;
- judge model `mistralai/Mistral-Small-3.2-24B-Instruct-2506`, served as `mistral-judge`;
- temperature 0, JSON parse mode, one attempt, and a grounded-evidence check that passed;
- the stable source identifier `2wiki_frozen_token/debate/2000/2wiki:1442e9a20bde11eba7f7acde48001122/rev_A`.

This is an inspection example, not an independently human-validated prevalence claim.

# Appendix D

# Reproducibility and Evidence Map

## D.1 Core configurations

The frozen and fine-tuned all-architecture token benchmarks are configured in:

- `configs/frozen_all_mas_token.yaml`
- `configs/v3b_all_mas_token.yaml`
- `configs/2wiki_frozen_token.yaml`
- `configs/2wiki_v3b_token.yaml`

Each records seed, decoding settings, model path, context mode, evaluation size, systems, architecture limits, and budget levels. The corresponding wall-clock configurations preserve the architecture definitions while changing the budget mode.

## D.2 Figure generation

The figures are produced by two scripts in `dissertation/latex/`. `generate_figures.py` draws the two schematics (Figure 2.1 and Figure 3.1) with ReportLab. `generate_data_figures.py` draws the four data figures from the committed analysis CSV files using Matplotlib, together with the export and inspection helpers of the *scientific-visualization* Agent Skill (K-Dense, MIT licence); set the `SCIVIZ_SKILL` environment variable to a checkout of that skill before running it. Each data figure is written with a companion `*.export.json` manifest recording its source file, the transformations applied, and how uncertainty is defined.

All figures are black on white. Series are separated by hatch pattern, marker shape and line style rather than by colour, so no information is lost in monochrome reproduction.

## D.3 Derived evidence files

| File | Role in the dissertation |
|---|---|
| `analysis/diagnostics/*/metrics.csv` | Lexical final accuracy, F1, candidate diversity, and preliminary stage diagnostics by run. |
| `analysis/semantic_diagnostics/semantic_metrics.csv` | Full-trace semantic discovery, oracle, final, preservation, regret, and architecture counters. |
| `analysis/semantic_diagnostics/first_error_stage.csv` | Machine-screened first terminal failure locations. |
| `analysis/semantic_diagnostics/budget_pair_tests.csv` | Matched 1,000-versus-2,000-token outcome tests and paired resource changes. |
| `analysis/semantic_diagnostics/budget_wallclock_overall.csv` | Architecture-level wall time, realised tokens, truncation, discovery, preservation, and final accuracy. |
| `analysis/semantic_diagnostics/resource_associations.csv` | Fixed-effect stratified resource and truncation odds ratios. |
| `analysis/cloud_revision_package/FROZEN_MISTRAL_SCREENING_PROMPT.md` | Readable frozen copy of the Mistral v4 system prompt, user-message template, model identifier, and inference settings. |
| `analysis/final_transition_endorsement_audit/blind_stage_review_400.csv` | Completed blind human labels for the 400 non-repeat records, with repeat material maintained in round files. |
| `analysis/final_transition_endorsement_audit/final_transition_audit_key.jsonl` | Frozen unblinding key joining record identifiers to architecture, item, role, and stratum. |
| `analysis/final_transition_endorsement_audit/unblind/item_level_unblinded_160.csv` | Item-level audit table containing the 15 documented truncation, human-state, human-transition, machine-state, and machine-transition fields used for the final boundary analysis. |
| `analysis/final_transition_endorsement_audit/UNBLIND_REPORT.md` | Agreement, weighted transition estimates, uncertainty sensitivity, and audit checks. |
| `analysis/final_transition_endorsement_audit/CODEBOOK_REV4.md` | Final decision rules used for Discovery and Endorsement. |
| `data/sft_train_v3.jsonl.stats.json` | Frozen v3b data-construction counts, coverage, sampling settings, and reasoning-length summary. |
| `src/build_sft_data_v3.py`, `src/train_lora_v3.py`, `src/merge_lora_v3.py` | Executable v3b rejection-sampling, completion-only LoRA training, and merge procedures. |

| File | Role in the dissertation |
|---|---|
| `src/repair_final_audit_truncation_metadata.py` | Verified repair that restores unavailable final-stage truncation values to NA and recomputes the tri-state union without changing labels. |

## D.4 Reproduction sequence

The analysis can be reproduced in five stages. First, run the fixed benchmark configurations and retain complete stage traces. Second, apply lexical scoring and deterministic alias normalisation. Third, generate the semantic screen with the frozen judge prompt and retain uncertain outputs rather than coercing them. Fourth, reconstruct the frozen audit strata and join the completed blind sheet only after annotation. Fifth, compute weighted transitions under the three uncertain-label rules and regenerate the tables and figures.

The supplied LaTeX project contains a figure-generation script that reads the committed CSV summaries and writes vector PDF figures. Running that script does not re-judge any model output and therefore cannot change semantic labels.

The final 160-item output tables are committed, but this package does not contain a standalone provenance script for the complete final unblinding and weighted-summary derivation. The earlier 100-pair sensitivity script must not be described as though it generated those tables. The narrow truncation-metadata repair listed above is independently asserted against the frozen audit key; it does not reconstruct or alter the human labels, strata, weights, or transition estimates.

## D.5 Scope exclusions

Exploratory role-conditioned `v4` training plans, incomplete ratio arms, and any post-audit prompt experimentation are excluded from the main evidence. They remain potential future work but should not be mixed with the frozen benchmark and audit when reproducing the reported claims.

# Bibliography


[1] Qingyun Wu et al. AutoGen: Enabling next-gen LLM applications via multi-agent conversation. *arXiv preprint arXiv:2308.08155*, 2023.

[2] Yilun Du, Shuang Li, Antonio Torralba, Joshua B. Tenenbaum, and Igor Mordatch. Improving factuality and reasoning in language models through multiagent debate. *arXiv preprint arXiv:2305.14325*, 2023.

[3] Tian Liang, Zhiwei He, Wenxiang Jiao, Xing Wang, Yan Wang, Rui Wang, Yujiu Yang, Zhaopeng Tu, and Shuming Shi. Encouraging divergent thinking in large language models through multi-agent debate. *arXiv preprint arXiv:2305.19118*, 2023.

[4] Dat Tran and Douwe Kiela. Single-agent llms outperform multi-agent systems on multi-hop reasoning under equal thinking token budgets. *arXiv preprint arXiv:2604.02460*, 2026.

[5] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*, volume 35, 2022.

[6] Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc V. Le, Ed H. Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. In *International Conference on Learning Representations*, 2023.

[7] Aman Madaan et al. Self-refine: Iterative refinement with self-feedback. *arXiv preprint arXiv:2303.17651*, 2023.

[8] Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. *arXiv preprint arXiv:2303.11366*, 2023.

[9] Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L. Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. In *Advances in Neural Information Processing Systems*, 2023.

[10] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations*, 2023.

[11] Guohao Li, Hasan Abed Al Kader Hammoud, Hani Itani, Dmitrii Khizbullin, and Bernard Ghanem. CAMEL: Communicative agents for "mind" exploration of large language model society. In *Advances in Neural Information Processing Systems*, 2023.

[12] Sirui Hong, Mingchen Zhuge, Jonathan Chen, Xiawu Zheng, Yuheng Cheng, Jinlin Wang, Ceyao Zhang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, Liyang Zhou, Chenyu Ran, Lingfeng Xiao, Chenglin Wu, and Jürgen Schmidhuber. MetaGPT: Meta programming for a multi-agent collaborative framework. In *International Conference on Learning Representations*, 2024.

[13] Taicheng Guo, Xiuying Chen, Yaqi Wang, Ruidi Chang, Shichao Pei, Nitesh V. Chawla, Olaf Wiest, and Xiangliang Zhang. Large language model based multi-agents: A survey of progress and challenges. In *Proceedings of the Thirty-Third International Joint Conference on Artificial Intelligence*, 2024.

[14] Andries Smit, Paul Duckworth, Nathan Grinsztajn, Thomas D. Barrett, and Arnu Pretorius. Should we be going MAD? a look at multi-agent debate strategies for LLMs. In *Proceedings of the 41st International Conference on Machine Learning*, 2024.

[15] Qineng Wang, Zihao Wang, Ying Su, Hanghang Tong, and Yangqiu Song. Rethinking the bounds of LLM reasoning: Are multi-agent discussions the key? In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, 2024.

[16] Denny Zhou, Nathanael Schärli, Le Hou, Jason Wei, Nathan Scales, Xuezhi Wang, Dale Schuurmans, Claire Cui, Olivier Bousquet, Quoc Le, and Ed Chi. Least-to-most prompting enables complex reasoning in large language models. In *International Conference on Learning Representations*, 2023.

[17] Tushar Khot, Harsh Trivedi, Matthew Finlayson, Yao Fu, Kyle Richardson, Peter Clark, and Ashish Sabharwal. Decomposed prompting: A modular approach for solving complex tasks. In *International Conference on Learning Representations*, 2023.

[18] Mert Cemri, Melissa Z. Pan, Shuyi Yang, Lakshya A. Agrawal, Bhavya Chopra, Rishabh Tiwari, Kurt Zhu, Kurt Keutzer, Aditya G. Parameswaran, Dan Klein, Kannan Ramchandran, Matei Zaharia, Joseph E. Gonzalez, and Ion Stoica. Why do multi-agent LLM systems fail? *arXiv preprint arXiv:2503.13657*, 2025.

[19] Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, 2018.

[20] Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. MuSiQue: Multihop questions via single-hop question composition. In *Transactions of the Association for Computational Linguistics*, volume 10, pages 539–554, 2022. doi: 10.1162/tacl_a_00475.

[21] Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. Constructing a multi-hop QA dataset for comprehensive evaluation of reasoning steps. In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 6609–6625, 2020. doi: 10.18653/v1/2020.coling-main.580.

[22] Sewon Min, Eric Wallace, Sameer Singh, Matt Gardner, Hannaneh Hajishirzi, and Luke Zettlemoyer. Compositional questions do not necessitate multi-hop reasoning. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4249–4257, 2019. doi: 10.18653/v1/P19-1416.

[23] Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. *arXiv preprint arXiv:2305.20050*, 2023.

[24] Jonathan Uesato, Nate Kushman, Ramana Kumar, Francis Song, Noah Siegel, Lisa Wang, Antonia Creswell, Geoffrey Irving, and Irina Higgins. Solving math word problems with process- and outcome-based feedback. *arXiv preprint arXiv:2211.14275*, 2022.

[25] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-Bench and chatbot arena. In *Advances in Neural Information Processing Systems: Datasets and Benchmarks Track*, 2023.

[26] Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. G-Eval: Nlg evaluation using GPT-4 with better human alignment. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 2511–2522, 2023. doi: 10.18653/v1/2023.emnlp-main.153.

[27] Peiyi Wang, Lei Li, Liang Chen, Zefan Cai, Dawei Zhu, Binghuai Lin, Yunbo Cao, Qi Liu, Tianyu Liu, and Zhifang Sui. Large language models are not fair evaluators. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, 2024.

[28] Arjun Panickssery, Samuel R. Bowman, and Shi Feng. LLM evaluators recognize and favor their own generations. In *Advances in Neural Information Processing Systems*, 2024.

[29] Chi-Min Chan, Weize Chen, Yusheng Su, Jianxuan Yu, Wei Xue, Shanghang Zhang, Jie Fu, and Zhiyuan Liu. ChatEval: Towards better LLM-based evaluators through multi-agent debate. In *International Conference on Learning Representations*, 2024.

[30] Justin Chih-Yao Chen, Swarnadeep Saha, and Mohit Bansal. ReConcile: Round-table conference improves reasoning via consensus among diverse LLMs. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, 2024.

[31] Ofir Press, Muru Zhang, Sewon Min, Ludwig Schmidt, Noah A. Smith, and Mike Lewis. Measuring and narrowing the compositionality gap in language models. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, 2023.

[32] Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. Interleaving retrieval with chain-of-thought reasoning for knowledge-intensive multi-step questions. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics*, 2023.

[33] Jacob Cohen. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, 20(1):37–46, 1960.

[34] Bradley Efron and Robert J. Tibshirani. *An Introduction to the Bootstrap*. Chapman and Hall/CRC, 1994.

[35] An Yang et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

[36] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.

[37] Weize Chen, Jiarui Yuan, Chen Qian, Cheng Yang, Zhiyuan Liu, and Maosong Sun. Optima: Optimizing effectiveness and efficiency for LLM-based multi-agent system. *arXiv preprint arXiv:2410.08115*, 2024.