

Package ‘spm’

November 30, 2019

Title SPM extract package

Version 1.1

Date 2019-11-30

Author A. Dunn

Description A set of R functions for extracting from SPM output files.

Maintainer A Dunn <Alistair.Dunn@OceanEnvironmental.co.nz>

License CPL v1.0. See the SPM User Manual for license details.

URL <http://www.niwa.co.nz>

Copyright National Institute of Water & Atmospheric Research (NIWA), New Zealand Ministry for Primary Industries.

R topics documented:

spm-package	2
calc.abundance	3
extract	3
extract.ageingerror	4
extract.agesize	4
extract.ageweight	4
extract.covariance	5
extract.derivedquantity	5
extract.derivedquantitybycell	5
extract.estimatesummary	6
extract.estimatevalue	6
extract.initialisationphase	6
extract.layer	7
extract.layerderivedview	7
extract.MCMC	7
extract.objectivefunction	8
extract.observation	8
extract.partition	8
extract.partitionbiomass	9
extract.randomnumberseed	9
extract.selectivity	9
extract.simulations	10
extract.sizeweight	10
extract.spatialmap	10

generate.MVU	11
PF	11
PFconstant	12
PFdoublenormal	12
PFexponential	13
PFinverselogistic	13
PFlogistic	14
PFnormal	14
PFthreshold	15
spm.area	15
spm.convert.to.lines	15
spm.dplot	16
spm.extract.simulated.observation	16
spm.get.lines	16
spm.is.whole.number	17
spm.isin	17
spm.make.filename	17
spm.make.list	18
spm.make.table	18
spm.pos	18
spm.pos.match	19
spm.recodevector	19
spm.remove.first.words	19
spm.remove.last.words	20
spm.report.types	20
spm.string.to.vector.of.numbers	20
spm.string.to.vector.of.words	21
spm.unpaste	21
spm.zeroFun	21

Index 22

spm-package	<i>SPM extract package</i>
-------------	----------------------------

Description

A set of R functions for extracting and processing SPM output.

Details

Package: spm
 Date: 2013-02-12
 License: See the SPM manual, or use 'spm -l' at the command line to view the SPM license.
 URL: <http://www.niwa.co.nz>
 Copyright: National Institute of Water & Atmospheric Research (NIWA).

Index:

extract	Extract elements from an SPM output file
---------	--

spm-package SPM package

Author(s)

A. Dunn

Maintainer: A Dunn <a.dunn@niwa.co.nz>

calc.abundance	<i>Generate a multivariate uniform distribution based on the bounds for the estimated parameters</i>
----------------	--

Description

Generate a multivariate uniform distribution based on the bounds for the estimated parameters

Usage

```
calc.abundance(data, categories = NULL, ages = NULL, total = T)
```

Arguments

data	data representing a partition
categories	Optional subset of categories
ages	Optional subset of ages
total	If true, then sum over selected categories and ages. Default = TRUE

Author(s)

Alistair Dunn

extract	<i>Extract SPM output into R</i>
---------	----------------------------------

Description

Extract SPM output into R

Usage

```
extract(file, path = "", ignore.unknown = FALSE)
```

Arguments

file	the name of the input file containing model output to extract
path	Optionally, the path to the file
ignore.unknown	Ignore unknown objects in the output file

Author(s)

Alistair Dunn

extract.ageingerror	<i>Utility extract function</i>
---------------------	---------------------------------

Description

Utility extract function

Usage

```
extract.ageingerror(lines)
```

Author(s)

Alistair Dunn

extract.agesize	<i>Utility extract function</i>
-----------------	---------------------------------

Description

Utility extract function

Usage

```
extract.agesize(lines)
```

Author(s)

Alistair Dunn

extract.ageweight	<i>Utility extract function</i>
-------------------	---------------------------------

Description

Utility extract function

Usage

```
extract.ageweight(lines)
```

Author(s)

Alistair Dunn

extract.covariance	<i>Utility extract function</i>
--------------------	---------------------------------

Description

Utility extract function

Usage

```
extract.covariance(lines)
```

Author(s)

Alistair Dunn

extract.derivedquantity	<i>Utility extract function</i>
-------------------------	---------------------------------

Description

Utility extract function

Usage

```
extract.derivedquantity(lines)
```

Author(s)

Alistair Dunn

extract.derivedquantitybycell	<i>Utility extract function</i>
-------------------------------	---------------------------------

Description

Utility extract function

Usage

```
extract.derivedquantitybycell(lines)
```

Author(s)

Alistair Dunn

```
extract.estimatesummary
```

Utility extract function

Description

Utility extract function

Usage

```
extract.estimatesummary(lines)
```

Author(s)

Alistair Dunn

```
extract.estimatevalue
```

Utility extract function

Description

Utility extract function

Usage

```
extract.estimatevalue(lines)
```

Author(s)

Alistair Dunn

```
extract.initialisationphase
```

Utility extract function

Description

Utility extract function

Usage

```
extract.initialisationphase(lines)
```

Arguments

lines a file of scanned lines

Author(s)

Alistair Dunn

extract.layer	<i>Utility extract function</i>
---------------	---------------------------------

Description

Utility extract function

Usage

```
extract.layer(lines)
```

Author(s)

Alistair Dunn

extract.layerderivedview	<i>Utility extract function</i>
--------------------------	---------------------------------

Description

Utility extract function

Usage

```
extract.layerderivedview(lines)
```

Author(s)

Alistair Dunn

extract.MCMC	<i>Utility extract function</i>
--------------	---------------------------------

Description

Utility extract function

Usage

```
extract.MCMC(lines)
```

Author(s)

Alistair Dunn

`extract.objectivefunction`
Utility extract function

Description

Utility extract function

Usage

`extract.objectivefunction(lines)`

Author(s)

Alistair Dunn

`extract.observation` *Utility extract function*

Description

Utility extract function

Usage

`extract.observation(lines)`

Author(s)

Alistair Dunn

`extract.partition` *Utility extract function*

Description

Utility extract function

Usage

`extract.partition(lines)`

Author(s)

Alistair Dunn

extract.partitionbiomass
Utility extract function

Description

Utility extract function

Usage

extract.partitionbiomass(lines)

Author(s)

Alistair Dunn

extract.randomnumberseed
Utility extract function

Description

Utility extract function

Usage

extract.randomnumberseed(lines)

Author(s)

Alistair Dunn

extract.selectivity *Utility extract function*

Description

Utility extract function

Usage

extract.selectivity(lines)

Author(s)

Alistair Dunn

extract.simulations	<i>Utility extract function</i>
---------------------	---------------------------------

Description

Utility extract function

Usage

```
extract.simulations(file, path = "")
```

Author(s)

Alistair Dunn

extract.sizeweight	<i>Utility extract function</i>
--------------------	---------------------------------

Description

Utility extract function

Usage

```
extract.sizeweight(lines)
```

Author(s)

Alistair Dunn

extract.spatialmap	<i>Utility extract function</i>
--------------------	---------------------------------

Description

Utility extract function

Usage

```
extract.spatialmap(lines)
```

Author(s)

Alistair Dunn

generate.MVU	<i>Generate a multivariate uniform distribution based on the bounds for the estimated parameters</i>
--------------	--

Description

Generate a multivariate uniform distribution based on the bounds for the estimated parameters

Usage

```
generate.MVU(file, path = "", output.file, sample.size = 1)
```

Arguments

file	the name of the input file containing the estimated fits
path	Optionally, the path to the file
output.file	The name of the output file to write randomly generated values
sample.size	The number of samples to generate

Author(s)

Sophie Mormede

PF	<i>Evaluate a preference function</i>
----	---------------------------------------

Description

Evaluate a preference function

Usage

```
PF(type = "none", x, alpha, ..., rescale = T)
```

Arguments

type	A type of preference function. Valid values include "constant", "doublenormal", "exponential", "inverselogistic", "logistic", "normal", and "threshold"
x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
...	the parameters of the preference functions
rescale	Rescale the function to have value 1. Default = TRUE

Author(s)

Alistair Dunn

PFconstant	<i>Evaluate the constant preference function</i>
------------	--

Description

Evaluate the constant preference function

Usage

```
PFconstant(x, alpha, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

PFdoublenormal	<i>Evaluate the double normal preference function</i>
----------------	---

Description

Evaluate the double normal preference function

Usage

```
PFdoublenormal(x, alpha, mu, sigmaL, sigmaR, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
mu	the mean of the double normal
sigmaL	the standard deviation of the left-hand side of the double normal
sigmaR	the standard deviation of the right-hand side of the double normal
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

PFexponential	<i>Evaluate the exponential preference function</i>
---------------	---

Description

Evaluate the exponential preference function

Usage

```
PFexponential(x, alpha, lambda, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
lambda	the rate of the exponential
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

PFinverselogistic	<i>Evaluate the inverse-logistic preference function</i>
-------------------	--

Description

Evaluate the inverse-logistic preference function

Usage

```
PFinverselogistic(x, alpha, a50, ato95, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
a50	the a50 value of the inverse logisitic
ato95	the ato95 value of the inverse logisitic
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

PFlogistic	<i>Evaluate the logistic preference function</i>
------------	--

Description

Evaluate the logistic preference function

Usage

```
PFlogistic(x, alpha, a50, ato95, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
a50	the a50 value of the logisitic
ato95	the ato95 value of the logisitic
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

PFnormal	<i>Evaluate the normal preference function</i>
----------	--

Description

Evaluate the normal preference function

Usage

```
PFnormal(x, alpha, mu, sigma, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
mu	the mean of the normal
sigma	the standard deviation of the normal
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

PFthreshold	<i>Evaluate the threshold preference function</i>
-------------	---

Description

Evaluate the threshold preference function

Usage

```
PFthreshold(x, alpha, N, lambda, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
N	the threshold value
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

spm.area	<i>utility function</i>
----------	-------------------------

Description

utility function

Usage

```
spm.area(corners)
```

Author(s)

Alistair Dunn

spm.convert.to.lines	<i>utility function</i>
----------------------	-------------------------

Description

utility function

Usage

```
spm.convert.to.lines(filename)
```

Author(s)

Alistair Dunn

spm.dplot	<i>utility function</i>
-----------	-------------------------

Description

utility function

Usage

```
spm.dplot(..., name = T, quantiles = c(0.5), plot.mean = F,  
  main = "", xlab = "", ylab = "", ylim, srtx = 0, bw = "nrd0",  
  adjust = 1/3, adj = 0, fill = F, gap = 0.2)
```

Author(s)

Alistair Dunn

spm.extract.simulated.observation	<i>utility function</i>
-----------------------------------	-------------------------

Description

utility function

Usage

```
spm.extract.simulated.observation(lines)
```

Author(s)

Alistair Dunn

spm.get.lines	<i>utility function</i>
---------------	-------------------------

Description

utility function

Usage

```
spm.get.lines(lines, from = -1, to = -1, contains = "",  
  starts.with = "", clip.to = "", clip.from = "",  
  clip.to.match = "", clip.from.match = "", ...)
```

Author(s)

Alistair Dunn

spm.is.whole.number	<i>utility function</i>
---------------------	-------------------------

Description

utility function

Usage

```
spm.is.whole.number(string)
```

Author(s)

Alistair Dunn

spm.isin	<i>utility function</i>
----------	-------------------------

Description

utility function

Usage

```
spm.isin(x, y)
```

Author(s)

Alistair Dunn

spm.make.filename	<i>utility function</i>
-------------------	-------------------------

Description

utility function

Usage

```
spm.make.filename(file, path = "")
```

Author(s)

Alistair Dunn

spm.make.list	<i>utility function</i>
---------------	-------------------------

Description

utility function

Usage

```
spm.make.list(lines)
```

Author(s)

Alistair Dunn

spm.make.table	<i>utility function</i>
----------------	-------------------------

Description

utility function

Usage

```
spm.make.table(lines)
```

Author(s)

Alistair Dunn

spm.pos	<i>utility function</i>
---------	-------------------------

Description

utility function

Usage

```
spm.pos(vector, x)
```

Author(s)

Alistair Dunn

spm.pos.match	<i>utility function</i>
---------------	-------------------------

Description

utility function

Usage

```
spm.pos.match(vector, regexp)
```

Author(s)

Alistair Dunn

spm.recodevector	<i>utility function</i>
------------------	-------------------------

Description

utility function

Usage

```
spm.recodevector(in.data, from.vals, to.vals)
```

Author(s)

Alistair Dunn

spm.remove.first.words	<i>utility function</i>
------------------------	-------------------------

Description

utility function

Usage

```
spm.remove.first.words(string, words = 1)
```

Author(s)

Alistair Dunn

`spm.remove.last.words` *utility function*

Description

utility function

Usage

```
spm.remove.last.words(string, words = 1)
```

Author(s)

Alistair Dunn

`spm.report.types` *utility function*

Description

utility function

Usage

```
spm.report.types()
```

Author(s)

Alistair Dunn

`spm.string.to.vector.of.numbers`
utility function

Description

utility function

Usage

```
spm.string.to.vector.of.numbers(string, sep = " ")
```

Author(s)

Alistair Dunn

spm.string.to.vector.of.words
utility function

Description

utility function

Usage

```
spm.string.to.vector.of.words(string, sep = " ")
```

Author(s)

Alistair Dunn

spm.unpaste *utility function*

Description

utility function

Usage

```
spm.unpaste(string, sep = " ")
```

Author(s)

Alistair Dunn

spm.zeroFun *utility function*

Description

utility function

Usage

```
spm.zeroFun(x, delta = 1e-11)
```

Author(s)

Alistair Dunn

Index

*Topic **package**

spm-package, [2](#)

calc.abundance, [3](#)

extract, [3](#)

extract.ageingerror, [4](#)

extract.agesize, [4](#)

extract.ageweight, [4](#)

extract.covariance, [5](#)

extract.derivedquantity, [5](#)

extract.derivedquantitybycell, [5](#)

extract.estimatesummary, [6](#)

extract.estimatevalue, [6](#)

extract.initialisationphase, [6](#)

extract.layer, [7](#)

extract.layerderivedview, [7](#)

extract.MCMC, [7](#)

extract.objectivefunction, [8](#)

extract.observation, [8](#)

extract.partition, [8](#)

extract.partitionbiomass, [9](#)

extract.randomnumberseed, [9](#)

extract.selectivity, [9](#)

extract.simulations, [10](#)

extract.sizeweight, [10](#)

extract.spatialmap, [10](#)

generate.MVU, [11](#)

PF, [11](#)

PFconstant, [12](#)

PFdoublenormal, [12](#)

PFexponential, [13](#)

PFinverselogistic, [13](#)

PFlogistic, [14](#)

PFnormal, [14](#)

PFthreshold, [15](#)

spm (spm-package), [2](#)

spm-package, [2](#)

spm.area, [15](#)

spm.convert.to.lines, [15](#)

spm.dplot, [16](#)

spm.extract.simulated.observation, [16](#)

spm.get.lines, [16](#)

spm.is.whole.number, [17](#)

spm.isin, [17](#)

spm.make.filename, [17](#)

spm.make.list, [18](#)

spm.make.table, [18](#)

spm.pos, [18](#)

spm.pos.match, [19](#)

spm.recodevector, [19](#)

spm.remove.first.words, [19](#)

spm.remove.last.words, [20](#)

spm.report.types, [20](#)

spm.string.to.vector.of.numbers, [20](#)

spm.string.to.vector.of.words, [21](#)

spm.unpaste, [21](#)

spm.zeroFun, [21](#)