

Package ‘spm’

December 11, 2019

Title SPM extract package

Version 1.1

Date 2019-12-09

Author A. Dunn

Description A set of R functions for extracting from SPM output files.

Maintainer A Dunn <Alistair.Dunn@OceanEnvironmental.co.nz>

License CPL v1.0. See the SPM User Manual for license details.

URL <http://www.niwa.co.nz>

Copyright National Institute of Water & Atmospheric Research (NIWA), New Zealand Ministry for Primary Industries.

R topics documented:

spm-package	2
calc.abundance	3
extract	3
extract.ageingerror	4
extract.agesize	4
extract.ageweight	5
extract.covariance	5
extract.derivedquantity	6
extract.derivedquantitybycell	6
extract.estimatesummary	7
extract.estimatevalue	7
extract.initialisationphase	8
extract.layer	8
extract.layerderivedview	9
extract.MCMC	9
extract.objectivefunction	10
extract.observation	10
extract.partition	11
extract.partitionbiomass	11
extract.preferencefunction	12
extract.process	12
extract.randomnumberseed	13
extract.selectivity	13
extract.simulations	14

extract.sizeweight	14
extract.spatialmap	15
generate.MVU	15
PF	16
PFconstant	16
PFdoublenormal	17
PFexponential	17
PFinverselogistic	18
PFlogistic	18
PFnormal	19
PFthreshold	19
spm.area	20
spm.convert.to.lines	20
spm.dplot	20
spm.extract.simulated.observation	21
spm.get.lines	21
spm.is.whole.number	21
spm.isin	22
spm.make.filename	22
spm.make.list	22
spm.make.table	23
spm.pos	23
spm.pos.match	23
spm.recodevector	24
spm.remove.first.words	24
spm.remove.last.words	24
spm.report.types	25
spm.string.to.vector.of.numbers	25
spm.string.to.vector.of.words	25
spm.unpaste	26
spm.zeroFun	26

Index	27
--------------	-----------

spm-package	<i>SPM extract package</i>
-------------	----------------------------

Description

A set of R functions for extracting and processing SPM output.

Details

Package: spm
Date: 2013-02-12
License: See the SPM manual, or use 'spm -l' at the command line to view the SPM license.
URL: <http://www.niwa.co.nz>
Copyright: National Institute of Water & Atmospheric Research (NIWA).

Index:

extract	Extract elements from an SPM output file
spm-package	SPM package

Author(s)

A. Dunn

Maintainer: A Dunn <a.dunn@niwa.co.nz>

calc.abundance	<i>Generate a multivariate uniform distribution based on the bounds for the estimated parameters</i>
----------------	--

Description

Generate a multivariate uniform distribution based on the bounds for the estimated parameters

Usage

```
calc.abundance(data, categories = NULL, ages = NULL, total = T)
```

Arguments

data	data representing a partition
categories	Optional subset of categories
ages	Optional subset of ages
total	If true, then sum over selected categories and ages. Default = TRUE

Author(s)

Alistair Dunn

extract	<i>Extract SPM output into R</i>
---------	----------------------------------

Description

Extract SPM output into R

Usage

```
extract(file, path = "", ignore.unknown = FALSE)
```

Arguments

file	the name of the input file containing model output to extract
path	Optionally, the path to the file
ignore.unknown	Ignore unknown objects in the output file

Author(s)

Alistair Dunn

extract.ageingerror	<i>Helper function for 'extract'</i>
---------------------	--------------------------------------

Description

Helper function for 'extract'

Usage

```
extract.ageingerror(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.agesize	<i>Helper function for 'extract'</i>
-----------------	--------------------------------------

Description

Helper function for 'extract'

Usage

```
extract.agesize(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.ageweight	<i>Helper function for 'extract'</i>
-------------------	--------------------------------------

Description

Helper function for 'extract'

Usage

```
extract.ageweight(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.covariance	<i>Helper function for 'extract'</i>
--------------------	--------------------------------------

Description

Helper function for 'extract'

Usage

```
extract.covariance(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

```
extract.derivedquantity
```

Helper function for 'extract'

Description

Helper function for 'extract'

Usage

```
extract.derivedquantity(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

```
extract.derivedquantitybycell
```

Helper function for 'extract'

Description

Helper function for 'extract'

Usage

```
extract.derivedquantitybycell(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

`extract.estimatevalue`*Helper function for 'extract'*

Description

Helper function for 'extract'

Usage

```
extract.estimatevalue(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

`extract.estimatevalue` *Helper function for 'extract'*

Description

Helper function for 'extract'

Usage

```
extract.estimatevalue(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.initialisationphase
Helper function for 'extract'

Description

Helper function for 'extract'

Usage

```
extract.initialisationphase(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.layer *Helper function for 'extract'*

Description

Helper function for 'extract'

Usage

```
extract.layer(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.layerderivedview
Helper function for 'extract'

Description

Helper function for 'extract'

Usage

```
extract.layerderivedview(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.MCMC *Helper function for 'extract'*

Description

Helper function for 'extract'

Usage

```
extract.MCMC(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.objectivefunction
Helper function for 'extract'

Description

Helper function for 'extract'

Usage

```
extract.objectivefunction(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.observation *Helper function for 'extract'*

Description

Helper function for 'extract'

Usage

```
extract.observation(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.partition	<i>Helper function for 'extract'</i>
-------------------	--------------------------------------

Description

Helper function for 'extract'

Usage

```
extract.partition(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.partitionbiomass	<i>Helper function for 'extract'</i>
--------------------------	--------------------------------------

Description

Helper function for 'extract'

Usage

```
extract.partitionbiomass(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.preferencefunction
Helper function for 'extract'

Description

Helper function for 'extract'

Usage

```
extract.preferencefunction(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.process *Helper function for 'extract'*

Description

Helper function for 'extract'

Usage

```
extract.process(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.randomnumberseed
Helper function for 'extract'

Description

Helper function for 'extract'

Usage

```
extract.randomnumberseed(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.selectivity *Helper function for 'extract'*

Description

Helper function for 'extract'

Usage

```
extract.selectivity(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.simulations	<i>Helper function for 'extract'</i>
---------------------	--------------------------------------

Description

Helper function for 'extract'

Usage

```
extract.simulations(file, path = "")
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.sizeweight	<i>Helper function for 'extract'</i>
--------------------	--------------------------------------

Description

Helper function for 'extract'

Usage

```
extract.sizeweight(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

extract.spatialmap	<i>Helper function for 'extract'</i>
--------------------	--------------------------------------

Description

Helper function for 'extract'

Usage

```
extract.spatialmap(lines)
```

Arguments

lines	list of lines to process
-------	--------------------------

Author(s)

Alistair Dunn

generate.MVU	<i>Generate a multivariate uniform distribution based on the bounds for the estimated parameters</i>
--------------	--

Description

Generate a multivariate uniform distribution based on the bounds for the estimated parameters

Usage

```
generate.MVU(file, path = "", output.file, sample.size = 1)
```

Arguments

file	the name of the input file containing the estimated fits
path	Optionally, the path to the file
output.file	The name of the output file to write randomly generated values
sample.size	The number f samples to generate

Author(s)

Sophie Mormede

PF	<i>Evaluate a preference function</i>
----	---------------------------------------

Description

Evaluate a preference function

Usage

```
PF(type = "none", x, alpha, ..., rescale = T)
```

Arguments

type	A type of preference function. Valid values include constant", "doublenormal", "exponential", "inverselogistic", "logistic", "normal", and "threshold"
x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
...	the parameters of the preference functions
rescale	Rescale the function to have value 1. Default = TRUE

Author(s)

Alistair Dunn

PFconstant	<i>Evaluate the constant preference function</i>
------------	--

Description

Evaluate the constant preference function

Usage

```
PFconstant(x, alpha, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

PFdoublenormal	<i>Evaluate the double normal preference function</i>
----------------	---

Description

Evaluate the double normal preference function

Usage

```
PFdoublenormal(x, alpha, mu, sigmaL, sigmaR, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
mu	the mean of the double normal
sigmaL	the standard deviation of the left-hand side of the double normal
sigmaR	the standard deviation of the right-hand side of the double normal
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

PFexponential	<i>Evaluate the exponential preference function</i>
---------------	---

Description

Evaluate the exponential preference function

Usage

```
PFexponential(x, alpha, lambda, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
lambda	the rate of the exponential
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

PFinverselogistic	<i>Evaluate the inverse-logistic preference function</i>
-------------------	--

Description

Evaluate the inverse-logistic preference function

Usage

```
PFinverselogistic(x, alpha, a50, ato95, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
a50	the a50 value of the inverse logisitic
ato95	the ato95 value of the inverse logisitic
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

PFlogistic	<i>Evaluate the logistic preference function</i>
------------	--

Description

Evaluate the logistic preference function

Usage

```
PFlogistic(x, alpha, a50, ato95, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
a50	the a50 value of the logisitic
ato95	the ato95 value of the logisitic
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

PFnormal	<i>Evaluate the normal preference function</i>
----------	--

Description

Evaluate the normal preference function

Usage

```
PFnormal(x, alpha, mu, sigma, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
mu	the mean of the normal
sigma	the standard deviation of the normal
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

PFthreshold	<i>Evaluate the threshold preference function</i>
-------------	---

Description

Evaluate the threshold preference function

Usage

```
PFthreshold(x, alpha, N, lambda, rescale = T)
```

Arguments

x	x-values over which to evaluate. Default = 1
alpha	The value of the alpha parameter. Default = 1
N	the threshold value
rescale	Rescale the function to have value 1?. Default = TRUE

Author(s)

Alistair Dunn

spm.area	<i>utility function</i>
----------	-------------------------

Description

utility function

Usage

```
spm.area(corners)
```

Author(s)

Alistair Dunn

spm.convert.to.lines	<i>utility function</i>
----------------------	-------------------------

Description

utility function

Usage

```
spm.convert.to.lines(filename)
```

Author(s)

Alistair Dunn

spm.dplot	<i>utility function</i>
-----------	-------------------------

Description

utility function

Usage

```
spm.dplot(..., name = T, quantiles = c(0.5), plot.mean = F,  
  main = "", xlab = "", ylab = "", ylim, srtx = 0, bw = "nrd0",  
  adjust = 1/3, adj = 0, fill = F, gap = 0.2)
```

Author(s)

Alistair Dunn

spm.extract.simulated.observation
utility function

Description

utility function

Usage

```
spm.extract.simulated.observation(lines)
```

Author(s)

Alistair Dunn

spm.get.lines *utility function*

Description

utility function

Usage

```
spm.get.lines(lines, from = -1, to = -1, contains = "",  
  starts.with = "", clip.to = "", clip.from = "",  
  clip.to.match = "", clip.from.match = "", ...)
```

Author(s)

Alistair Dunn

spm.is.whole.number *utility function*

Description

utility function

Usage

```
spm.is.whole.number(string)
```

Author(s)

Alistair Dunn

spm.isin	<i>utility function</i>
----------	-------------------------

Description

utility function

Usage

```
spm.isin(x, y)
```

Author(s)

Alistair Dunn

spm.make.filename	<i>utility function</i>
-------------------	-------------------------

Description

utility function

Usage

```
spm.make.filename(file, path = "")
```

Author(s)

Alistair Dunn

spm.make.list	<i>utility function</i>
---------------	-------------------------

Description

utility function

Usage

```
spm.make.list(lines)
```

Author(s)

Alistair Dunn

spm.make.table	<i>utility function</i>
----------------	-------------------------

Description

utility function

Usage

```
spm.make.table(lines)
```

Author(s)

Alistair Dunn

spm.pos	<i>utility function</i>
---------	-------------------------

Description

utility function

Usage

```
spm.pos(vector, x)
```

Author(s)

Alistair Dunn

spm.pos.match	<i>utility function</i>
---------------	-------------------------

Description

utility function

Usage

```
spm.pos.match(vector, regexp)
```

Author(s)

Alistair Dunn

spm.recodevector *utility function*

Description

utility function

Usage

```
spm.recodevector(in.data, from.vals, to.vals)
```

Author(s)

Alistair Dunn

spm.remove.first.words
utility function

Description

utility function

Usage

```
spm.remove.first.words(string, words = 1)
```

Author(s)

Alistair Dunn

spm.remove.last.words *utility function*

Description

utility function

Usage

```
spm.remove.last.words(string, words = 1)
```

Author(s)

Alistair Dunn

spm.report.types	<i>utility function</i>
------------------	-------------------------

Description

utility function

Usage

spm.report.types()

Author(s)

Alistair Dunn

spm.string.to.vector.of.numbers
<i>utility function</i>

Description

utility function

Usage

spm.string.to.vector.of.numbers(string, sep = " ")

Author(s)

Alistair Dunn

spm.string.to.vector.of.words
<i>utility function</i>

Description

utility function

Usage

spm.string.to.vector.of.words(string, sep = " ")

Author(s)

Alistair Dunn

spm.unpaste	<i>utility function</i>
-------------	-------------------------

Description

utility function

Usage

```
spm.unpaste(string, sep = " ")
```

Author(s)

Alistair Dunn

spm.zeroFun	<i>utility function</i>
-------------	-------------------------

Description

utility function

Usage

```
spm.zeroFun(x, delta = 1e-11)
```

Author(s)

Alistair Dunn

Index

*Topic **package**

spm-package, [2](#)

calc.abundance, [3](#)

extract, [3](#)

extract.ageingerror, [4](#)

extract.agesize, [4](#)

extract.ageweight, [5](#)

extract.covariance, [5](#)

extract.derivedquantity, [6](#)

extract.derivedquantitybycell, [6](#)

extract.estimatesummary, [7](#)

extract.estimatevalue, [7](#)

extract.initialisationphase, [8](#)

extract.layer, [8](#)

extract.layerderivedview, [9](#)

extract.MCMC, [9](#)

extract.objectivefunction, [10](#)

extract.observation, [10](#)

extract.partition, [11](#)

extract.partitionbiomass, [11](#)

extract.preferencefunction, [12](#)

extract.process, [12](#)

extract.randomnumberseed, [13](#)

extract.selectivity, [13](#)

extract.simulations, [14](#)

extract.sizeweight, [14](#)

extract.spatialmap, [15](#)

generate.MVU, [15](#)

PF, [16](#)

PFconstant, [16](#)

PFdoublenormal, [17](#)

PFexponential, [17](#)

PFinverselogistic, [18](#)

PFlogistic, [18](#)

PFnormal, [19](#)

PFthreshold, [19](#)

spm (spm-package), [2](#)

spm-package, [2](#)

spm.area, [20](#)

spm.convert.to.lines, [20](#)

spm.dplot, [20](#)

spm.extract.simulated.observation, [21](#)

spm.get.lines, [21](#)

spm.is.whole.number, [21](#)

spm.isin, [22](#)

spm.make.filename, [22](#)

spm.make.list, [22](#)

spm.make.table, [23](#)

spm.pos, [23](#)

spm.pos.match, [23](#)

spm.recodevector, [24](#)

spm.remove.first.words, [24](#)

spm.remove.last.words, [24](#)

spm.report.types, [25](#)

spm.string.to.vector.of.numbers, [25](#)

spm.string.to.vector.of.words, [25](#)

spm.unpaste, [26](#)

spm.zeroFun, [26](#)