




PCB design/layout
notes &
considerations

Design notes

Design Capabilities





PCB design/layout
notes &
considerations

Design notes


Design Capabilities



PV Refrigerator v0.1.2
High Current H-Bridge

Cct Designed by Mike MacKay
Rev A Date 2017-01-26


Sheet 2 of 26



PCB design/layout
notes &
considerations

Design notes


Design Capabilities



PCB design/layout notes & considerations

Design notes


Design Capabilities



PCB design/layout notes & considerations

Design notes

Design Capabilities



PCB design/layout
notes &
considerations

Design notes

Design Capabilities



PV Refridgerator v0.1.2


N-FET Driver

Cct Designed by Mike MacKay

Rev A Date 2017-02-04

Sheet 3 of 26

Use a 14-guage terminal block with only 4 leads



VPS24-5400

- 1. Maximum Power: 130.0VA
 - 2. Primary – Series: 230VAC, 50/60Hz; Parallel: 115VAC, 50/60Hz
 - 3. Secondary: Series: 24.0V CT@ 5.4A; Parallel: 12.0V @ 10.8A
- Input:** Series – 6 and 1, Jumper 5 to 2
Parallel – 6 and 1, Jumper 6 to 2 and 5 to 1
- Output:** Series – 12 and 7, Jumper 11 to 8
Parallel – 12 and 7, Jumper 12 to 8 and 11 to 7

PCB design/layout
notes &
considerations

Design notes

Design Capabilities




PV Refridgerator v0.1.2

Transformer

Cct Designed by Mike MacKay

Rev A Date 2017-01-26

Sheet 5 of 26



PCB design/layout
notes &
considerations

Design notes

Design Capabilities




Table 6-1 Electrical Conductor Spacing

Voltage Between Conductors (DC or AC Peaks)	Minimum Spacing						
	Bare Board				Assembly		
	B1	B2	B3	B4	A5	A6	A7
0-15	0.05 mm	0.1 mm	0.1 mm	0.05 mm	0.13 mm	0.13 mm	0.13 mm
16-30	0.05 mm	0.1 mm	0.1 mm	0.05 mm	0.13 mm	0.25 mm	0.13 mm
31-50	0.1 mm	0.6 mm	0.6 mm	0.13 mm	0.13 mm	0.4 mm	0.13 mm
51-100	0.1 mm	0.6 mm	1.5 mm	0.13 mm	0.13 mm	0.5 mm	0.13 mm
101-150	0.2 mm	0.6 mm	3.2 mm	0.4 mm	0.4 mm	0.8 mm	0.4 mm
151-170	0.2 mm	1.25 mm	3.2 mm	0.4 mm	0.4 mm	0.8 mm	0.4 mm
171-250	0.2 mm	1.25 mm	6.4 mm	0.4 mm	0.4 mm	0.8 mm	0.4 mm
251-300	0.2 mm	1.25 mm	12.5 mm	0.4 mm	0.4 mm	0.8 mm	0.8 mm
301-500	0.25 mm	2.5 mm	12.5 mm	0.8 mm	0.8 mm	1.5 mm	0.8 mm
> 500	0.0025 mm /volt	0.005 mm /volt	0.025 mm /volt	0.00305 mm /volt	0.00305 mm /volt	0.00305 mm /volt	0.00305 mm /volt
See para. 6.3 for calc.							

B1 - Internal Conductors
B2 - External Conductors, uncoated, sea level to 3050 m
B3 - External Conductors, uncoated, over 3050 m
B4 - External Conductors, with permanent polymer coating (any elevation)
A5 - External Conductors, with conformal coating over assembly (any elevation)
A6 - External Component lead termination, uncoated
A7 - External Component lead termination, with conformal coating (any elevation)

PCB design/layout notes & considerations

Design notes


Design Capabilities



PV Refrigerator v0.1.2
High Voltage H-Bridge

Cct Rev A Designed by Mike MacKay
Date 2017-01-26

Sheet 7 of 26



PCB design/layout
notes &
considerations

Design notes



Design Capabilities



PV Refridgerator v0.1.2
3.3VDC Powersupply

Cct
Rev **B** Designed by Craig Comberbach
Date 2017-02-10

Sheet 9 of 26




PCB design/layout
notes &
considerations

Design notes

Design Capabilities

50k resistor costs 2\$+ in bulk, 100k is 0.15\$ each. 2x 100k in parallel is 50k, I choose cost savings!
50k is not a standard value in any of the En series despite looking like it should be. 49.9k oddly enough is part of the standard E96 (+/-1%) and E192 (+/- 0.5%, 0.25%, and 0.1%) series.



PCB design/layout
notes &
considerations

Design notes

Design Capabilities



PV Refridgerator v0.1.2

Vsense from 0 to 69.3V

Cct

Rev


A

Designed by Mike MacKay

Date 2017-02-08

Sheet 12 of 26

50k resistor costs 2\$+ in bulk, 100k is 0.15\$ each. 2x 100k in parallel is 50k, I choose cost savings!
50k is not a standard value in any of the En series despite looking like it should be. 49.9k oddly enough is part of the standard E96 (+/-1%) and E192 (+/- 0.5%, 0.25%, and 0.1%) series.



PCB design/layout
notes &
considerations

Design notes

Design Capabilities



PV Refridgerator v0.1.2

Vsense from 0 to 69.3V


Cct
Rev A

Designed by Mike MacKay

Date 2017-02-08

Sheet 12 of 26

50k resistor costs 2\$+ in bulk, 100k is 0.15\$ each. 2x 100k in parallel is 50k, I choose cost savings!
50k is not a standard value in any of the En series despite looking like it should be. 49.9k oddly enough is part of the standard E96 (+/-1%) and E192 (+/- 0.5%, 0.25%, and 0.1%) series.



PCB design/layout
notes &
considerations

Design notes

Design Capabilities



PV Refridgerator v0.1.2

Vsense from 0 to 69.3V

Cct

Rev

A

Designed by Mike MacKay

Date 2017-02-08

Sheet 12 of 26

1

2

3

4

A

A

B


B

C

C

D

D



PCB design/layout
notes &
considerations

Design notes

Design Capabilities



PV Refridgerator v0.1.2

Vsense from 0 to 223.3V

Cct
Rev

A

Designed by Mike MacKay

Date 2017-02-08


Sheet 13 of 26

1

2

3

4



PCB design/layout
notes &
considerations

Design notes

Design Capabilities



PV Refridgerator v0.1.2

Vsense from 0 to 223.3V


Cct
Rev

A

Designed by Mike MacKay

Date 2017-02-08

Sheet 13 of 26



PCB design/layout
notes &
considerations

Design notes

Design Capabilities



PV Refridgerator v0.1.2

Vsense from 0 to 223.3V


Cct
Rev

A

Designed by Mike MacKay

Date 2017-02-08

Sheet 13 of 26



PCB design/layout
notes &
considerations

Design notes

Design Capabilities




PV Refridgerator v0.1.2

Vsense from 0 to 223.3V

Cct
Rev

Designed by Mike MacKay
Date 2017-02-08


Sheet 13 of 26



PCB design/layout
notes &
considerations

Design notes

Design Capabilities



PCB design/layout
notes &
considerations

Design notes

Design Capabilities



PV Refridgerator v0.1.2

Vsense from 0 to 223.3V

Cct
Rev

A

Designed by Mike MacKay

Date 2017-02-08

Sheet 14 of 26

1

2

3

4

A

A

B


B

C

C

D

D



PCB design/layout
notes &
considerations

Design notes

Design Capabilities



PV Refridgerator v0.1.2

Vsense from 0 to 223.3V

Cct
Rev

A

Designed by Mike MacKay

Date 2017-02-08

Sheet 14 of 26

1

2

3

4

1

2

3

4

A

A

B


B

C

C

D

D



PCB design/layout
notes &
considerations

Design notes

Design Capabilities



PV Refridgerator v0.1.2

Vsense from 0 to 223.3V

Cct

Rev

A

Designed by Mike MacKay

Date

2017-02-08

Sheet 14 of 26

1

2

3

4

1

2

3

4

A

A

B


B

C

C

D

D



PCB design/layout
notes &
considerations

Design notes

Design Capabilities



PV Refridgerator v0.1.2

Vsense from 0 to 223.3V

Cct

Rev

A

Designed by Mike MacKay

Date

2017-02-08

Sheet 14 of 26


1

2

3

4

Take the leads directly off the resistors. The resistance is so low the copper trace will be a significant source of error. Use a Kelvin connection!



PCB design/layout
notes &
considerations

Design notes

Design Capabilities




PV Refridgerator v0.1.2

Vsense from 0 to 69.3V

Cct Designed by Mike MacKay

Rev A Date 2017-02-08

Sheet 15 of 26



PCB design/layout
notes &
considerations

Design notes

Design Capabilities