

BumbleboxExampleAnalysis

2023-11-07

Part 1: Load and plot data tracking data from single video

```
#Get list of unique trials (using recursive search in case there are subfolders)
trials <- list.files(pdir, pattern = '*averages.csv', full.names = TRUE, recursive = TRUE)


#Select a random trial - trial 10 in this list
i <- 10

#Load background photo
background_im <- readPNG(str_replace(trials[i], '_averages.csv', '.png'))

#Clip image excess
background_im <- background_im[1:3040,]

#Optional: plot image
#image(background_im, col = gray.colors(33))

#tracking data
tracking_data <- read.csv(str_replace(trials[i], '_averages.csv', '_updated.csv'))
tracking_data$ID <- as.factor(tracking_data$ID)
ggplot(tracking_data, aes(x = centroidX, y = centroidY, colour = ID)) + geom_point() + xlim(c(0,xl)) + ylim(c(0,yl))
```



```
#average data
summary_data <- read.csv(trials[i])
summary_data
```

```
##                               filename ID average.distance.from.center
## 1  bumblebox-01_2023-10-28_00-55-03  0                           783
## 2  bumblebox-01_2023-10-28_00-55-03  1                           194
## 3  bumblebox-01_2023-10-28_00-55-03  2                           492
## 4  bumblebox-01_2023-10-28_00-55-03  3                          1060
## 5  bumblebox-01_2023-10-28_00-55-03  4                           497
## 6  bumblebox-01_2023-10-28_00-55-03  5                           433
## 7  bumblebox-01_2023-10-28_00-55-03  6                           177
## 8  bumblebox-01_2023-10-28_00-55-03  7                          1086
## 9  bumblebox-01_2023-10-28_00-55-03  8                           571
## 10 bumblebox-01_2023-10-28_00-55-03  9                           334
## 11 bumblebox-01_2023-10-28_00-55-03 10                          1522
## 12 bumblebox-01_2023-10-28_00-55-03 12                           413
## 13 bumblebox-01_2023-10-28_00-55-03 13                           537
## 14 bumblebox-01_2023-10-28_00-55-03 14                           973
##   average.speed frames.tracked.in.video
## 1             130                  35
## 2              20                  48
## 3               6                  45
## 4              52                  9
## 5              49                 28
## 6              20                 48
```

## 7	43	13
## 8	47	52
## 9	75	40
## 10	63	28
## 11	1	52
## 12	32	52
## 13	140	4
## 14	9	23

Part II: Combine data across all trials


```
#Make sure you don't have a 'comb_data' object in memory
rm('tracking_data')

for(file in trials){

  data <- read.csv(str_replace(file, '_averages.csv', '_raw.csv'))
  ## Compile average data
  #Check to see if output data frame exists
  if(!exists('tracking_data')){
    tracking_data <- data #If not, create it from the first loop
  } else {
    tracking_data <- rbind(tracking_data, data) #Otherwise append new data to the end
  }

}

tracking_data$ID <- as.factor(tracking_data$ID)
ggplot(tracking_data, aes(x = centroidX, y = centroidY, colour = ID)) + geom_point(alpha = 0.3, cex = 0
```



```
#Make sure you don't have a 'comb_data' object in memory
rm('comb_data')
```

```
## Warning in rm("comb_data"): object 'comb_data' not found

for(file in trials){

  data <- read.csv(file)
  ## Compile average data
  #Check to see if output data frame exists
  if(!exists('comb_data')){
    comb_data <- data #If not, create it from the first loop
  } else {
    comb_data <- rbind(comb_data, data) #Otherwise append new data to the end
  }


}

comb_data$ID <- as.factor(comb_data$ID)
```

```
#Clean out missing data
comb_data <- comb_data[complete.cases(comb_data),]
```

```
#Boxplot of speed vs. individual
ggplot(comb_data, aes(x = reorder(ID, average.speed, FUN = median), y = log10(average.speed)))+geom_boxp
```

```
## Warning: Removed 103 rows containing non-finite values ('stat_boxplot()').
```




```
#Check for evidence of individual variation
model <- lmer(log10(1+average.speed)~ID + (1|filename), data = comb_data)
model.1 <- lmer(log10(1+average.speed)~1 + (1|filename), data = comb_data)
anova(model, model.1)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: comb_data
## Models:
## model.1: log10(1 + average.speed) ~ 1 + (1 | filename)
## model: log10(1 + average.speed) ~ ID + (1 | filename)
##          npar    AIC    BIC  logLik deviance Chisq Df Pr(>Chisq)
## model.1     3 4660.9 4678.9 -2327.5    4654.9
## model      18 4199.4 4307.3 -2081.7    4163.4 491.56 15 < 2.2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
#Show distance from center by individual
```

```
ggplot(comb_data, aes(x = reorder(ID, average.distance.from.center, FUN = median), y = average.distance
```



```
#Get individual averages
individual_averages <- aggregate(cbind(average.distance.from.center, average.speed, frames.tracked.in.v),
colnames(individual_averages) <- c('ID', 'dist', 'speed', 'frames_tracked')

# Remove outlier with zero velocity
individual_averages <- subset(individual_averages, speed > 1)


#Visualize individual speed/distance over time

#Set up timestamps
start.date <- parse_date_time('2023-10-28 00:00:00', "%Y-%m-%d %H:%M:%S")
comb_data$datetime <- parse_date_time(substr(comb_data$filename, 14, 32), "%Y-%m-%d_%H-%M-%S")
comb_data$time.num <- as.numeric(difftime(comb_data$datetime, start.date, units = 'days'))

comb_data <- comb_data[order(comb_data$ID, comb_data$time.num),]

p1 <- ggplot(comb_data, aes(x = time.num, y = average.speed, colour = ID)) + geom_point(alpha = 0.3, cex = 1)
p2 <- ggplot(comb_data, aes(x = reorder(ID, average.speed, FUN = median), y = average.speed, colour = ID))

grid.arrange(p1, p2, ncol=2)
```



```

p1 <- ggplot(comb_data, aes(x = time.num, y = average.distance.from.center, colour = ID)) + geom_point()
p2 <- ggplot(comb_data, aes(x = reorder(ID, average.distance.from.center, FUN = median), y = average.distance.from.center))

grid.arrange(p1, p2, ncol=2)
    
```

