Setup your virtual machines. Add a network rule that blocks all traffic from internal network 1 to internal network 2 except for one port. Use traceroute to show this port is open and that there are no other hosts between your target and PFSense. You should submit the following.

1. A screen shot showing what happens when you use traceroute to the target when the port is open vs when it is closed.

Sub Task 1

TraceRoute command with port 80 open

```
Shell No.1 _ _ _ X

File Actions Edit View Help

root@kali:~# traceroute -T -p 80 192.168.1.112

traceroute to 192.168.1.112 (192.168.1.112), 30 hops max, 60 byte packets
1 192.168.1.112 (192.168.1.112) 0.573 ms 0.596 ms 0.580 ms

root@kali:~#
```

TraceRoute command with port 80 closed

```
File Actions Edit View Help

root@kali:~# traceroute -T -p 80 192.168.1.112
traceroute to 192.168.1.112 (192.168.1.112), 30 hops max, 60 byte packets

1 ***
2 ***
3 ***
4 ***
5 ***
6 ***
7 ***
8 ***
9 ***
10 ***
11 **
12 **
13 ***
14 **
15 **
16 **
17 **
18 **
19 **
20 **
21 **
22 **
23 **
24 **
25 **
26 **
27 **
28 **
29 **
30 **
root@kali:~#
```