

Please be advised this tool ships with minimal, non-vehicle specific software.

To download software to use on the vehicles you service, the tool must be registered first.

Please follow the following steps:

Contents

1. Register Tool	1
1.1 Registration Via Tool	2
1.2 Registration Via a Windows-based PC	3
2. Download Software	4
3. Download BAS Firmware	5
4. Pair VCI to Tablet	5
4.1 Pair Tablet with VCI Via Bluetooth	5
4.2 Check for VCI Firmware	6
5. Print via Windows PC to Wi-Fi Printer	7



1. REGISTER TOOL



- Power on the BT608. Swipe down from the top of the screen and a drop-down menu will display.
- Long press the WLAN icon to enter the WLAN setting menu.



- Swipe the WLAN toggle to turn on the Wi-Fi.
- Select your network and enter password to sign in.



 The Wi-Fi icon will display at the top right corner of the screen when connection is established.



1. REGISTER TOOL

1.1 REGISTRATION VIA TABLET



- After the device is connected to Wi-Fi, access **Update**
- A dialog box will display asking you to register your tool.
- Tap **0K**.



- Enter your email address, password and tap **Verification code**
- Check your email for the verification code, enter the verification code, and tap Sign up



- A sign-in screen will display
- Create an Autel ID using an accessible email address



- The serial number and password fields will be automatically completed.
- Tap REGISTER




1. REGISTER TOOL

1.2 REGISTRATION VIA A WINDOWS-BASED PC




- Using a computer, launch an Internet browser and go to http://pro.autel.com
- Click Create Autel ID on the left side of the screen
- . If you already have an Autel ID, sign in and skip to Step 6



- An email titled "Verification Code for New User Registration" will be sent to you.
- . Open email and copy the 6-digit verification code
- Return to http://pro.autel.com to continue registration



- · Click Create Autel ID at the bottom of the screen
- Registration Complete screen will display.
- Click **Sign in Now** and log in



 To locate the tool's serial number and password: from the Main Menu select the Setting icon and tap About

- One account is all you need

 An Analysis and the second of the second of
 - · Set preferred language
 - Enter your email address as Autel ID
 - Click Get Verification Code



- Enter verification code and all other required information marked with a red asterisk
- . Enter Captcha code as shown
- Read the Autel Terms of Use and Privacy Policy and select the check box




- · Select Product Registration from the menu list
- Product Registration screen will display.



- Input your tool's Product Serial Number and Password
- Type Captcha code as shown
- Click Submit to complete tablet registration



2. DOWNLOAD SOFTWARE



- If updates are available, the number of available updates will display above the green Update button
 Select the **Update** button to view a list
- Select the **Update** button to view a list of available updates.



 Download the system update by selecting the **Download** button on the right.



 Download update for each vehicle manufacturer you service



3. DOWNLOAD BAS FIRMWARE




- Select Settings from the main screen and tap BAS management
- On the Firmware tab page, select Detect Firmware.



- A dialog box will display when new firmware version is available.
- Select Get the new version to download the new BAS firmware.

4. PAIR VCI TO TABLET

4.1 PAIR TABLET WITH VCI VIA BLUETOOTH



- Connect the VCI to a vehicle or USB power source
- Select Settings from the main screen and tap VCI manager.



- Your tool will automatically start scanning for available VCI devices. Found devices are listed on the bottom of the screen.
- Press your VCI device serial number to pair the tablet with VCI.



- A green bluetooth icon will display when the tool and VCI are paired.

4. PAIR VCI TO TABLET

4.2 CHECK FOR VCI FIRMWARE



- Connect the VCI to a vehicle and turn ignition on.
- Select Settings from the main screen and tap VCI manager
- On the Firmware upgrade tab page, select Detect Firmware



- A dialog box will display when new firmware version is available.
- Select Get the new version to download the new VCI firmware.



5. PRINT VIA WINDOWS PC TO WI-FI PRINTER

Works with any printer with a Wi-Fi connection. No need for special software or driver on the tablet.



- Aut Update Tools

 Open A

 Commission for a commission for
- Make sure your Window PC and tablet are on the same Wi-Fi network
 On your computer, go to Autel.com, select Support > Downloads > Autel

 Here
- Update Tools
- · Open the zip file



- \bullet Select $\mbox{\it MaxiSYS Print},$ then click the setup.exe file to install the program
- MauSys Printer

 Quick Print Test Print Print Print Print Setting

 Open PDF file Print List

 Print List

 Print Setting

 Open PDF file Print List

 Print List

 Print Setting

 Open PDF file Print List

 Print List

 Print Setting

 Open PDF file Print List

 Print List

 Print Setting

 Open PDF file Print List

 P
- Within the program dialogue box, check **Auto Print** to automatically use the default
 printer
- . Select Quick Print to use the default printer or select Print to choose a printer