


Shodan Pentesting Guide

Delving deep into Shodan's mine

2.8k
SHARES



Shodan Pentesting Guide




Shodan is a tool for searching devices connected to the internet. Unlike search engines which help you find websites, Shodan helps you find information about desktops, servers, IoT devices, and more. This information includes metadata such as the software running on each device.

Common uses of Shodan include **Network Security**, **Market Research**, **Cyber Risk**, **scanning IoT devices**, and **Tracking Ransomware**. This guide will focus on comprehensively covering these applications in a pentesting context.

Table of Contents [[show](#)]





What is Shodan?

Shodan is a search engine for Internet-connected devices. It was created by John C. Matherly (@achillean) in 2009.

Shodan is a tool that lets you explore the internet; discovering connected devices or network services, monitoring network security, making global statistics and so on.

The Shodan's website/database references results from extensive port scanning of the Internet.

Shodan interfaces

This section will show you the various ways you can connect to Shodan.

It's possible to interact with Shodan via the well known [website](#), the official python command-line interface tool and library, a variety of community driven libraries for many languages and also the official REST API.

CLI tool

The official shodan command-line interface ([CLI](#)) is written in python, for quick usage in your terminal.

Install

In a virtual python environment like [pyenv](#):

```
$ easy_install shodan
```

On [BlackArch](#) you can also install the following package:

```
# pacman -S python-shodan
```

Once you have installed shodan CLI tool, to setup your API token just do:

```
$ shodan init <YOUR_API_KEY>
```

Command overview

A dozen of straightforward commands are available:

-help

```
$ shodan -help
Usage: shodan [OPTIONS] COMMAND [ARGS]...
```

Options:

```
-h, --help Show this message and exit.
```

Commands:

alert	Manage the network alerts for your account.
convert	Convert the given input data file into a different format.
count	Returns the number of results for a search.
data	Bulk data access to Shodan.
domain	View all available information for a domain.
download	Download search results and save them in a compressed JSON file.
honeyscore	Check whether the IP is a honeypot or not.
host	View all available information for an IP address.
info	Shows general information about your account.
init	Initialize the Shodan command-line.
myip	Print your external IP address.
org	Manage your organization's access to Shodan.
parse	Extract information out of compressed JSON files.
radar	Real-Time Map of some results as Shodan finds them.
scan	Scan an IP/ netblock using Shodan.

search	Search the Shodan database.
stats	Provide summary information about a search query.
stream	Stream data in real-time.
version	Print version of this tool.

info

If you have setup your API token, you can check the number of credits you have left:

```
$ shodan info  
Query credits available: 100  
Scan credits available: 100
```

Query credits are used to search Shodan and scan credits are used to scan IPs.

A search request consumes 1 query credit and scanning 1 IP consumes 1 scan credit.

version

When writing this article I was using shdoan 1.21.2:

```
$ shodan version  
1.21.2
```

count

Returns the number of results for a search query.

```
$ shodan count openssh  
23128  
$ shodan count openssh 7  
219
```

download

Search Shodan and download the results into a file where each line is a JSON [banner](#).

By **default it will only download 1,000 results**, if you want to download more look at the –limit flag.

The download command lets you save the results and process them afterwards using the parse command.

So if you often search for the same queries it will help you save credits.

The export credits are used to download data from the website at the rate of: **1 export credit lets you download up to 10,000 results**. They are single-use which means that once you use them they don't automatically renew at the start of the month.

But if you don't have export credits, you can use 1 query credit to save 100 results.

```
$ shodan download -h  
Usage: shodan download [OPTIONS] <filename> <search query>
```

```
Download search results and save them in a compressed JSON file.
```

Options:

```
--limit INTEGER The number of results you want to download. -1 to download  
all the data possible.  
--skip INTEGER The number of results to skip when starting the download.  
-h, --help Show this message and exit.
```

For example here I will download 1000 results of the query openssh:

```
$ shodan download openssh-data openssh  
Search query: openssh  
Total number of results: 23128  
Query credits left: 100  
Output file: openssh-data.json.gz  
[#####]-] 99% 00:00:00  
Saved 1000 results into file openssh-data.json.gz
```

After the download you can check how many credits you have left:

```
$ shodan info  
Query credits available: 95  
Scan credits available: 100
```

host

See information about the host such as where it's located, what ports are open and which organization owns the IP.

```
$ shodan host 1.1.1.1
1.1.1.1
Hostnames: one.one.one.one
Country: Australia
Organization: Mountain View Communications
Updated: 2020-01-21T22:26:00.168041
Number of open ports: 3

Ports:
53/udp
80/tcp
443/tcp
|-- SSL Versions: -SSLv2, -SSLv3, TLSv1, TLSv1.1, TLSv1.2, TLSv1.3

$ shodan host 138.201.81.199
138.201.81.199
Hostnames: apollo.archlinux.org
Country: Germany
```

Organization: Hetzner Online GmbH
Updated: 2020-01-21T03:02:11.476262
Number of open ports: 4

Ports:

22/tcp OpenSSH (8.1)
25/tcp Postfix smtpd
80/tcp nginx (1.16.1)
443/tcp nginx (1.16.1)
|-- SSL Versions: -SSLv2, -SSLv3, -TLSv1, -TLSv1.1, TLSv1.2, TLSv1.3

myip

Returns your Internet-facing IP address.

```
$ shodan myip  
199.30.49.210
```

parse

Use parse to analyze a file that was generated using the download command.

It lets you filter out the fields that you're interested in, convert the JSON to a CSV and is friendly for piping to other scripts.

```
$ shodan parse -h
Usage: shodan parse [OPTIONS] <filenames>

Extract information out of compressed JSON files.

Options:
--color / --no-color
--fields TEXT List of properties to output.
-f, --filters TEXT Filter the results for specific values using key:value
pairs.
-O, --filename TEXT Save the filtered results in the given file (append if
file exists).
--separator TEXT The separator between the properties of the search
results.
-h, --help Show this message and exit.
```

The following command outputs filtered data for the previously downloaded openssh data:

```
$ shodan parse --fields location.country_code3,ip_str,hostnames -f port:2222 openssh-
data.json.gz
ITA 89.107.109.247
```

HUN 193.6.173.187
FRA 77.87.111.110 pro-sip1.srv.proceau.net
USA 50.210.94.33
USA 35.130.36.118 035-130-036-118.biz.spectrum.com
AUT 80.120.19.180
JPN 124.155.95.212 v095212.ppp.asahi-net.or.jp
POL 83.144.70.114 83-144-70-114.static.chello.pl
BGR 84.238.200.8
AUT 80.120.19.168
USA 162.211.126.140
CAN 76.10.173.222 mail.nanoman.ca
USA 24.172.82.71 rrcs-24-172-82-71.midsouth.biz.rr.com
AUT 80.120.19.182
ITA 188.14.96.151 host151-96-static.14-188-b.business.telecomitalia.it
USA 216.67.111.198 216-67-111-198.static.acsalaska.net
USA 73.179.238.221 c-73-179-238-221.hsd1.fl.comcast.net
HKG 113.28.18.59 113-28-18-59.static.imsbiz.com

```
$ shodan parse --fields port,ip_str,location.city,location.postal_code -f
location.country_code:FR --separator , openssh-data.json.gz
22,188.92.65.5,Hésingue,68220
2222,77.87.111.110,,,
22,51.89.105.163,,,
```

```
22,5.135.218.249,,  
22,93.177.70.142,,  
2222,81.250.129.207,Paris,75116  
22,51.255.85.97,,  
22,193.52.218.40,Aix-en-provence,13090  
22,51.77.112.86,,  
22,149.202.19.41,,  
22,5.39.117.104,,  
22,195.154.53.223,Beaumont,95260  
22,37.71.132.198,,  
22,178.33.71.35,,  
22,212.83.188.179,Jouy-le-moutier,95280  
2222,195.200.166.216,Berre-l'etang,13130  
22,82.251.157.165,Paris,75004
```

search

This command lets you search Shodan and view the results in a terminal-friendly way.

By default it will display the IP, port, hostnames and data. You can use the `-fields` parameter to print whichever banner fields you're interested in.

A simple query won't consume any credits but if you use a search filter or request page 2 and beyond, credits will be consumed.

```
$ shodan search -h
Usage: shodan search [OPTIONS] <search query>

Search the Shodan database

Options:
--color / --no-color
--fields TEXT List of properties to show in the search results.
--limit INTEGER The number of search results that should be returned.
Maximum: 1000
--separator TEXT The separator between the properties of the search
results.
-h, --help Show this message and exit.
```

Example of query that won't cost credits:

```
$ shodan search --fields ip_str,port,os smb
156.226.167.81 445 Windows Server 2008 R2 Datacenter 7601 Service Pack 1
156.243.104.194 445 Windows Server 2008 R2 Enterprise 7601 Service Pack 1
91.230.243.89 445 Windows 10 Pro 16299
85.3.170.18 445 Windows 6.1
```

```
213.238.170.132 445 Windows Server 2012 R2 Standard 9600
154.208.176.81 445 Windows Server 2008 R2 Enterprise 7601 Service Pack 1
103.235.171.78 445 Windows Server 2016 Datacenter 14393
102.130.40.85 445 Windows Server 2016 Standard 14393
50.3.151.113 445 Windows Server 2012 R2 Standard 9600
220.241.112.233 445 Windows Server 2019 Standard 17763
100.27.15.229 445 Windows Server 2012 R2 Standard 9600
212.71.136.11 445 Unix
156.255.174.225 445 Windows Server 2008 R2 Datacenter 7601 Service Pack 1
156.232.162.239 445 Windows Server 2008 R2 Enterprise 7601 Service Pack 1
186.210.102.132 445 Unix
154.94.153.34 445 Windows Server 2012 R2 Datacenter 9600
213.130.28.31 445 Windows 6.1
```

Example of query that will cost 1 credit (because using a filter):

```
$ shodan search --fields ip_str,port,org,info product:mongodb
165.22.3.203 27017 Digital Ocean
213.159.208.76 27017 JSC The First
209.6.48.11 27017 RCN
23.239.0.110 27017 Linode
52.220.230.134 27017 Amazon.com
47.91.139.188 27017 Alibaba
```

```
159.203.169.196 27017 Digital Ocean
49.233.135.180 27017 Tencent cloud computing
122.228.113.75 27017 WENZHOU, ZHEJIANG Province, P.R.China.
106.14.42.66 27017 Hangzhou Alibaba Advertising Co.,Ltd.
59.108.91.3 27017 Beijing Founder Broadband Network Technology Co.,L
115.29.176.18 27017 Hangzhou Alibaba Advertising Co.,Ltd.
148.251.46.75 27017 Hetzner Online GmbH
3.121.222.150 27017 Amazon.com
47.75.211.162 27017 Alibaba
200.219.217.122 27017 Equinix Brazil
```

scan

Scan an IP/ netblock using Shodan.

```
$ shodan scan -h
Usage: shodan scan [OPTIONS] COMMAND [ARGS] ...
```

Scan an IP/ netblock using Shodan.

Options:

-h, --help Show this message and exit.

Commands:

```
internet Scan the Internet for a specific port and protocol using the...
list Show recently launched scans
protocols List the protocols that you can scan with using Shodan.
status Check the status of an on-demand scan.
submit Scan an IP/ netblock using Shodan.
```

Launching a scan will cost credits:

1 scan credit lets you scan 1 IP

By default a scan result will be displayed to *stdout* but you can save it to a file to be able to parse it later.

```
$ shodan scan submit --filename 104.27.154.244_scan.json.gz 104.27.154.244
```

If the host has already been scanned in the last 24 hours, you won't be able to scan it again without an Enterprise grade plan.

```
$ shodan scan submit --filename 104.27.154.244_scan.json.gz 104.27.154.244
```

```
Starting Shodan scan at 2020-01-22 23:46 - 100 scan credits left
```

```
No open ports found or the host has been recently crawled and can't get scanned again so soon.
```

You are also able to see the scans you previously launched with their ID and status:

```
$ shodan scan list
# 2 Scans Total - Showing 10 most recent scans:
# Scan ID Status Size Timestamp
zmWj3RNgiPbiQjx9 PROCESSING 1 2020-01-22T22:49:39.037000
8J9yu7jqTQO7AIiP PROCESSING 1 2020-01-22T22:46:34.790000
```

To save your scan results you are not forced to use `-filename`. You can simply launch a scan without saving it, and download the results later thanks to the scan ID:

```
$ shodan download --limit -1 scan-results.json.gz scan:zmWj3RNgiPbiQjx9
```

As scans are done asynchronously, you can check the status of a scan at any moment.

```
$ shodan scan status zmWj3RNgiPbiQjx9
DONE
```

To see the scan ID when launching a scan you can use the verbose mode:

```
$ shodan scan submit --verbose 13.226.145.4
```

```
Starting Shodan scan at 2020-01-23 00:00 - 97 scan credits left
# Scan ID: 3z6Cqf1CCyVLtc6P
# Scan status: DONE
```

Customers with an Enterprise Data License will be allowed to request a scan of the entire Internet by simply specifying the port and protocol/module.

```
$ shodan scan internet 8080 wemo-http
```

Available protocols and modules can be listed with shodan scan protocols.

stats

Provide summary information about a search query

```
$ shodan stats -h
Usage: shodan stats [OPTIONS] <search query>
```

Provide summary information about a search query

Options:

```
--limit INTEGER The number of results to return.
--facets TEXT List of facets to get statistics for.
```

```
-o, --filename TEXT Save the results in a CSV file of the provided name.  
-h, --help Show this message and exit.
```

It seems that by default you will get only top 10 and not for all facets:

```
$ shodan stats nginx  
Top 10 Results for Facet: country  
US 13,598,596  
CN 6,013,993  
ZA 3,067,296  
DE 1,560,114  
HK 1,065,990  
RU 869,931  
FR 859,715  
GB 555,946  
NL 550,591  
JP 526,386
```

```
Top 10 Results for Facet: org  
Amazon.com 1,897,943  
CloudInnovation infrastructure 1,288,280  
Leaseweb USA 1,200,146  
EGIHosting 1,131,973
```

```
DXTL Tseung Kwan O Service 1,052,688
Hangzhou Alibaba Advertising Co.,Ltd. 770,553
Digital Ocean 749,221
Asline Limited 680,364
Power Line Datacenter 678,264
Quantil Networks 585,935
```

But we can customize this behavior:

```
$ shodan stats --facets domain,port,asn --limit 5 nginx
Top 5 Results for Facet: domain
amazonaws.com 2,208,958
scalabledns.com 435,980
googleusercontent.com 308,114
t-ipconnect.de 225,276
your-server.de 180,711
```

```
Top 5 Results for Facet: port
80 10,019,366
443 5,300,058
5000 588,809
5001 563,208
8080 453,604
```

Top 5 Results for Facet: asn

as37353 2,447,679

as35916 1,878,181

as15003 1,508,786

as16509 1,236,249

as18779 1,132,180

Website

Main interface

The main interface of Shodan is the [search engine](#).

Shodan Developers Monitor View All...

SHODAN MongoDB

Exploits Maps Images Share Search Download Results Create Report

TOTAL RESULTS 73,473

TOP COUNTRIES

Country	Count
China	25,892
United States	18,633
Germany	4,191
Singapore	3,137
France	2,907

TOP SERVICES

Service	Count
MongoDB	72,116
8001	246
9001	234
3001	135
Webmin	92

TOP ORGANIZATIONS

Organization	Count
Hangzhou Alibaba Advertising Co.,Ltd.	12,766
Amazon.com	10,460
Digital Ocean	5,630
Tencent cloud computing	4,883
Google Cloud	1,677

TOP OPERATING SYSTEMS

OS	Count
Linux 3.x	20
Windows 8.1	8
linus	5
Windows Server 2008	4
Windows 7 or 8	4

TOP PRODUCTS

Product	Count
MongoDB	72,116
nginx	29
rsyncd	14
Apache httpd	13
Postfix smtpd	9

New Service: Keep track of what you have connected to the Internet. Check out [Shodan Monitor](#)

18.139.57.113
ec2-18-139-57-113.ap-southeast-1.compute.amazonaws.com
Amazon.com
Added on 2020-01-23 21:29:57 GMT
Singapore, Singapore

[database](#)

MongoDB Server Information
Authentication partially enabled

```
{
  "storageEngines": [
    "bigtiger",
    "devnull",
    "ephemeralForTest",
    "wiredtiger"
  ],
  "maxBsonObjectSize": 16777216,
  "ok": 1.0,
  "bits": 64,
  "modules": [],
  "openssl": {
    ...
  }
}
```

35.236.34.234
234.34.236.35.1c.googleusercontent.com
Google Cloud
Added on 2020-01-23 21:23:56 GMT
United States, Mountain View

[database](#)

MongoDB Server Information
Authentication partially enabled

```
{
  "storageEngines": [
    "devnull",
    "ephemeralForTest",
    "mmapv1",
    "wiredtiger"
  ],
  "maxBsonObjectSize": 16777216,
  "ok": 1.0,
  "bits": 64,
  "modules": [],
  "openssl": {
    ...
  }
}
```

106.12.153.137
Beijing Baidu Netcom Science and Technology Co.
Added on 2020-01-23 21:25:08 GMT
China

[database](#)

240.0 MB

5 Databases

Database Name	Size
local	80.0 MB
admin	80.0 MB
gameLogic	80.0 MB

MongoDB Server Information

```
{
  "metrics": [
    "getLastError": {
      "etime": {
        "num": 0,
        "totalMillis": 0
      },
      "wtimeouts": 0
    },
    "storage": {
      "freelist": {
        "search": {
          ...
        }
      }
    }
  }
}
```

It works like the search command of the CLI tool but with a fancy WebUI to display the results. It shows a summary for each host, the total count of hosts that matched the query like the count command of the CLI and some stats like the stats command.

SHODAN Developers Monitor View All... Explore Downloads Reports Pricing Enterprise Access Show API Key Try out the new beta website! Help Center My Account

18.139.57.113 ec2-18-139-57-113.ap-southeast-1.compute.amazonaws.com [View Raw Data](#)

Database

City	Singapore
Country	Singapore
Organization	Amazon.com
ISP	Amazon.com
Last Update	2020-01-23T21:20:57.090403
Hostnames	ec2-18-139-57-113.ap-southeast-1.compute.amazonaws.com
ASN	AS3

Web Technologies

- Bootstrap
- Google Font API
- jQuery
- Kibana
- Node.js

Vulnerabilities

Note: the device may not be impacted by all of these issues. The vulnerabilities are implied based on the software and version.

CVE-2019-0196	A vulnerability was found in Apache HTTP Server 2.4.17 to 2.4.38. Using fuzzed network input, the http/2 request handling could be made to access freed memory in string comparison when determining the method of a request and thus process the request incorrectly.
CVE-2019-0197	A vulnerability was found in Apache HTTP Server 2.4.34 to 2.4.38. When HTTP/2 was enabled for a http host or H2Upgrade was enabled for h2 on a https host, an Upgrade request from http/1.1 to http/2 that was not the first request on a connection could lead to a denial of service condition.

Ports

80 443 3000 3001 3002 3310 5601 8000 9000 9090 9091 27017

Services

Apache httpd Version: 2.4.29

HTTP/1.1 200 OK
Date: Mon, 20 Jan 2020 05:17:28 GMT
Server: Apache/2.4.29 (Ubuntu)
Last-Modified: Tue, 11 Jun 2019 11:42:43 GMT
ETag: "2aa6-59b8a0ccb001500"
Accept-Ranges: bytes
Content-Length: 10918
Vary: Accept-Encoding
Content-Type: text/html

Apache httpd Version: 2.4.29

HTTP/1.1 200 OK
Date: Sun, 19 Jan 2020 28:05:08 GMT
Server: Apache/2.4.29 (Ubuntu)
Last-Modified: Fri, 17 Jan 2020 11:43:11 GMT
ETag: "c93-59c54723b1f78"
Accept-Ranges: bytes
Content-Length: 3219
Vary: Accept-Encoding
Content-Type: text/html

Once you have selected a host, you will be able to see a shot specification table, vulnerabilities impacting the host, open ports and banners for open ports.

Downloading data

After you made a search, a *Download Results* button will be available:

The screenshot shows the Shodan search interface for the query "Tomcat". The top navigation bar includes links for Shodan, Developers, Monitor, View All..., Show API Key, Try out the new beta website!, Help Center, and My Account. Below the navigation is a search bar with the term "Tomcat" and a "Search" button. To the right of the search bar are links for Explore, Downloads, Reports, Pricing, and Enterprise Access. A red box highlights the "Download Results" button, which is located below the search bar. The main content area displays search results for "Tomcat" with a total count of 94,664. It includes sections for TOP COUNTRIES (China, United States, Brazil, Germany, Japan), TOP SERVICES (8081, 8083, HTTPS, Splunk, HTTPS (8443)), TOP ORGANIZATIONS (Amazon.com, Hangzhou Alibaba Advertising Co.,Ltd, China Telecom, China Union Beijing, Tencent cloud computing), TOP OPERATING SYSTEMS (Windows 7 or 8, Linux 3.x, Windows Server 2008, Linux, Linux 2.6.x), and TOP PRODUCTS (Apache Tomcat/Coyote JSP engine, Apache Tomcat, nginx, Apache httpd, Microsoft IIS httpd). Each result entry provides a link to a detailed view, including an SSL certificate, supported SSL versions, and raw HTTP/HTTPS responses.

Download Results

Landing Page

SSL Certificate

Supported SSL Versions

HTTP Response Headers

Raw HTTP Response

Raw HTTPS Response

Apache Tomcat/7.0.59

SSL Certificate

Supported SSL Versions

HTTP Response Headers

Raw HTTP Response

Apache Tomcat/8.0.30

SSL Certificate

Supported SSL Versions

HTTP Response Headers

Raw HTTP Response

Apache Tomcat/9.0.30

SSL Certificate

Supported SSL Versions

HTTP Response Headers

Raw HTTP Response

Apache Tomcat/9.0.31


SSL Certificate

Supported SSL Versions

HTTP Response Headers

Raw HTTP Response

Then you will be able to download the search results in JSON, CSV or XML.



Only the JSON format will contain the full data and be compatible with the Shodan CLI tool. CSV format will only contain IP, port, banner, organization and hostnames.

The XML format is deprecated by Shodan and consumes more space than the JSON one.

You can then view your download history in the [Downloads](#) section.

S Shodan Developers Monitor View All...

SHODAN tomcat

Exploits Maps Images Share Search Download Results Create Report

TOTAL RESULTS 94,664

TOP COUNTRIES

Country	Results
China	36,555
United States	18,056
Brazil	4,615
Germany	2,896
Japan	2,706

TOP SERVICES

Service	Results
8081	25,086

New Service: Keep track of what you have connected to the Internet. Check out [Shodan Monitor](#)

Landing Page 198.73.99.203
Infinite Campus, Incorporated
Added on 2020-01-25 15:06:54 GMT
United States

SSL Certificate
Issued By:
- Common Name: DigiCert SHA2 Secure Server CA
- Organization: DigiCert Inc
Issued To:
- Common Name: *.infinitecampus.org
- Organization: Infinite Campus, Inc.

HTTP/1.1 200
X-Frame-Options: SAMEORIGIN
X-Content-Type-Options: nosniff
X-XSS-Protection: 1; mode=block
Cache-Control: max-age=2678400
Expires: Tue, 25 Feb 2020 15:06:54 GMT
Content-Type: text/html; charset=UTF-8
Content-Length: 432
Date: Sat, 25 Jan 2020 15:06:54 GMT
Server: Apache Tom...

114.215.200.25 Hangzhou Alibaba Advertising Co.,Ltd.
Added on 2020-01-25 15:06:32 GMT
China

HTTP/1.1 200 OK
Server: Apache-Coyote/1.1
Content-Type: text/html; charset=ISO-8859-1

Generating reports

The website lets you generate a report based off of a search query.

The report contains graphs/ charts providing you a big picture view of how the results are distributed across the Internet. This feature is free and available to anyone.

To generate a report, click on the Create Report button from the search results page:

Shodan Developers Monitor View All...

SHODAN smtp Explore Downloads Reports Pricing Enter

Exploits Maps Images Share Search Download Results **Create Report**

TOTAL RESULTS

261,449

TOP COUNTRIES



New Service: Keep track of what you have connected to the Internet

129.121.5.23

ip-129-121-5-23.local

A Small Orange LLC

Added on 2020-01-25 15:25:57 GMT

United States

220 Welcome to LAVENDER \$

103.7.40.221

hnvietnam.vn

Superdata

Added on 2020-01-25 15:23:51 GMT

554 SMTP synchronization

Name your report:

Create Report

Create a report that provides statistics and breakdowns on various facets of your search query.


Title:


Close **Create Report**


250-WOAD.arvixe.com
250-SIZE-100000000

Creating a report will usually take a few minutes, you will receive an email when the report is ready with the link.

Else you can find all your previous reports on the [report page](#).







Top Domains



SSL Versions



SSL Expired Certificates



© 2013-2020, All Rights Reserved - Shodan®

A report is static and won't update automatically.

Maps

The [map interface](#) to search the Shodan database works like the stats command of the CLI but displays the results in an interactive map depending on the physical location of the host.



As it won't show more than 1000 results, you will have to zoom in and out or move around to display other results

Images

[Images](#) is a searchable gallery of screenshots from crawled devices.




Image data is gathered from 5 different sources: VNC, Remote Desktop (RDP), RTSP, Webcams and X Windows.

A **has_screenshot:true** filter can be used in the global search engine to keep only hosts that have a screenshot.

Exploits

[Exploits](#) is a search engine that looks for exploits across a variety of vulnerability databases at once.

The screenshot shows the Shodan Exploit search interface. The search term 'mongodb' has returned 15 results. The results are categorized by source (exploitdb, metasploit), platform (php, linux, windows, multiple, Linux), type (webapps, remote, exploit), and author (Ozer Goker, hyp3rlinx, agix, LiquidWorm, SEC Consult). Each result entry includes a brief description and a link to the exploit details page.

TOTAL RESULTS
15

SOURCE

Source	Count
exploitdb	14
metasploit	1

PLATFORM

Platform	Count
php	7
linux	3
windows	2
multiple	2
Linux	1

TYPE

Type	Count
webapps	11
remote	3
exploit	1

AUTHOR

Author	Count
Ozer Goker	3
hyp3rlinx	2
agix	2
LiquidWorm	2
SEC Consult	1

MongoDB nativeHelper.apply Remote Code Execution
agix
Linux

... This module exploit a the nativeHelper feature from spiderMonkey which allows to control execution by calling it wit specially crafted arguments. This module has been tested successfully on MongoDB 2.2.3 on Ubuntu 10.04 and Debian Squeeze. ...

MongoDB nativeHelper.apply Remote Code Execution
agix
Linux

... This module exploit a the nativeHelper feature from spiderMonkey which allows to control execution by calling it wit specially crafted arguments. This module has been tested successfully on MongoDB 2.2.3 on Ubuntu 10.04 and Debian Squeeze. ...

MongoDB - 'conn' Mongo Object Remote Code Execution
SCRT Security
remote

... source: <https://www.securityfocus.com/bid/61389/info>
MongoDB is prone to a remote code execution vulnerability because it fails to properly sanitize user-supplied input.
An attacker can exploit this vulnerability to execute arbitrary code within the context of the affected application ...

MongoDB 2.2.3 - nativeHelper.apply Remote Code Execution
agix
H3R0K

... #title: MongoDB nativeHelper.apply Remote Code Execution
#author: agixid <http://blog.scrt.ch/2012/03/24/mongodb-9-day-nzjti-to-rc/>
#software Link: <http://fastdl.mongodb.org/linux/mongodb-linux-10gen-2.2.3.tgz>
#Version: 2.2.3
The following PoC exploits the "nativeHelper" feature ...


RedwoodHQ 2.5.5 - Authentication Bypass
EthicalHCP
webapps

...
RedwoodHQ doesn't require that MongoDB is installed on the machine because this tool have her own Mongo Launcher.
The problem is that this vendor database doesn't require any authentication to read her data.
So, I use the same syntax that use the Framework to create my admin user ...

phoMoAdmin MongoDB GUI 1.1.5 - Cross-Site Request Forgery / Cross-Site Scripting

Developer dashboard

Your developer dashboard shows you your credits consumption and API plan.



Network monitor

Keep track of the devices that you have exposed to the Internet. Setup notifications, launch scans and gain complete visibility into what you have connected.

The [monitor](#) dashboard let you tracks your devices, alert you if something suspicious was detected, launch scan and display what's found on synthetic dashboard.

To begin with, add an IP, a range or a domain to monitor and choose a notification service.

The screenshot shows the Shodan Monitor Network dashboard. At the top, there are navigation links: Shodan, Developer, Book, More..., SHODAN, Monitor, Dashboard, Manage Assets, and Settings. The main title is "Monitor Network".

General Information: A text input field labeled "Name (ex. Production Network)" contains "My ip". To the right, it says "16 IPs remaining" and provides instructions: "Your account is allowed to monitor up to 16 IPs in total. To monitor additional IPs please upgrade your plan from the [Billing section](#)".

Notification Services: A list box shows a single entry with a blurred IP address. Below the list is a green button labeled "ADD NETWORK".

Footer: The text "Shodan® All rights reserved" is at the bottom center. The entire interface has a dark background with light-colored text and buttons.

Then you can manage your assets, from here you can launch scans or modify trigger rules.

The screenshot shows the Shodan Monitor interface with the 'Manage Assets' section. At the top, there are navigation links: Shodan, Developer, Book, More..., SHODAN (with a red gear icon), Monitor, Dashboard, Manage Assets (which is active and highlighted in blue), and Settings. Below the navigation is a search bar with placeholder text 'Search Shodan' and a magnifying glass icon. Under the search bar, there are two green buttons: 'ADD NETWORK' and 'ADD DOMAIN'. The main area is titled 'Manage Assets' and displays two asset entries. Each entry includes a small thumbnail image, the asset type ('1 IP'), and a list of tags: 'malware, open_database, uncommon, internet_scanner, new_service, ssl_expired, vulnerable'. To the right of each entry are three small square icons with symbols: a gear, a document, and a shield. At the bottom of the page, the Shodan logo and the text 'Shodan® All rights reserved.' are visible.

You can select which kind of event will trigger an alert.

Trigger Rules

Select the types of notifications that you would like to receive. If none are selected we will let you know whenever Shodan discovers any service.

- industrial_control_system i
- internet_scanner i
- iot i
- malware i
- new_service i
- open_database i
- ssl_expired i
- uncommon i
- vulnerable i



SAVE CHANGES


Remove Network

Then the dashboard shows the exposed services.

The screenshot shows the Shodan Monitor dashboard. At the top, there are navigation links: Shodan, Developer, Book, More..., SHODAN, Monitor, Dashboard, Manage Assets, and Settings. The main title is "Dashboard". On the right, it says "// USAGE" and "2 IPs monitored". Below this, there are three main sections: "Top Open Ports" (Ports discovered on your network ranges!), "Notable Ports" (Services that typically aren't publicly accessible), and "Top Vulnerabilities" (No vulnerabilities identified). The "Top Open Ports" section lists: 8081 (1), 443 (1), and 80 (1). The "Notable Ports" section lists: 8081 (1). The "Top Vulnerabilities" section lists several CVE entries: cve-2019-9641 (1), cve-2019-9639 (1), cve-2019-9638 (1), cve-2019-9637 (1), cve-2019-9024 (1), and cve-2019-9023 (1). At the bottom center, it says "Shodan® All rights reserved".

ICS radar

[ICS Radar](#) is a 3D map of Industrial Control Systems (ICS) devices found by Shodan crawlers.



Honeypot score

The service called [Honeypot or not?](#) will attribute a *Honeyscore* to an IP address, a probability of being a honeypot.



Shodan ScanHub Developers View All...



Honeypot Or Not?

Enter an IP to check whether it is a honeypot or a real control system:

Looks like a real system!

Frequently Asked Questions

1. How does it work?

The defining characteristics of known honeypots were extracted and used to create a tool to let you identify honeypots! The probability that an IP is a honeypot is captured in a "Honeyscore" value that can range from 0.0 to 1.0. This is still a prototype/ work-in-progress so if you find some problems please email me at jmath@shodan.io

2. What's the purpose?

Honeypots are a great tool for learning more about the Internet, the latest malware being used and keep track of infections. When trying to catch an intelligent attacker though, many honeypots fall short in creating a realistic environment. Honeyscore was created to raise awareness of the short-comings of honeypots.

3. What technology did you use?

The Honeyscore website and algorithm uses the following APIs/ frameworks:

- Shodan Developer API
- Python
- Jade Node Template Engine

4. Contact information?

You can reach me at the following locations:

Email: jmath@shodan.io
Twitter: [@achilean](#)

It's just an abstraction of the API like the honeyscore command of the CLI:


```
$ shodan honeyscore 46.244.103.227
```

```
Not a honeypot
```

Score: 0.3


Shodan 2000

Sodan 2000 is a Tron-like interface that randomly displays an host.



Community queries

You can [explore](#) queries exported and shared by other users of the community.



The screenshot shows the Shodan homepage. At the top, there is a navigation bar with links for "Shodan", "Developers", "Monitor", and "View All...". Below the navigation bar is the Shodan logo and a search bar with a magnifying glass icon. To the right of the search bar is a red rectangular box containing the word "Explore", with a red arrow pointing towards it from the bottom left. The main content area is divided into several sections: "Getting Started" with articles like "What is Shodan?", "Search Query Fundamentals", etc.; "Latest Additions" showing shared searches such as "cape-town", "Dm", "qdPM", "Printer", and "1234"; "SHORT VIDEOS" displaying a list of results for "Facet: port" with counts like 443, 993, 995, 8443, 465, 3389, 992, and 444; and "IMAGES" showing a grid of small thumbnail images. The overall layout is clean and modern, with a dark header and light-colored content blocks.


The shared queries have a title, a description and tags so you can browse them easily.

SHODAN Developers Monitor View All...  Explore Downloads Reports Pricing Enterprise Access Show API Key Try out the new beta website! Help Center My Account

Explore

Discover the Internet using search queries shared by other users.

Featured Categories



Top Voted

11,667	Webcam best ip cam search I have found yet. webcam surveillance cams 2010-05-15
4,755	Cams admin admin cam webcam 2012-02-06
2,515	Netcam Netcam netcam 2012-01-13
1,892	default password Finds results with "default password" in the ba... router default password 2010-01-14
1,156	dreambox dreambox dreambox 2010-08-13

Recently Shared

1	cape-town cape 2020-01-24
1	Dm 2020-01-24
1	qdPM Free Web-Based PC Credit Goes To: Rishal Dwive... 2020-01-23
2	Printer port:9100 pjl 2020-01-23
3	1234 IoT devices whose password is "1234" 1234 iot hacked 2020-01-23

To share a query, click the *Share Search* button on a search result page.

Shodan Developers Monitor View All...

SHODAN mongodb Explore Downloads Reports Pricing Enterprise Access

Exploits Maps Images **Share Search** Download Results Create Report

TOTAL RESULTS **73,286**

TOP COUNTRIES

Country	Count
China	25,548
United States	18,604
Germany	4,200
Singapore	3,120
France	2,910

TOP SERVICES

Service	Count
MongoDB	71,937
8081	241
9001	223
3001	134
Webmin	95

TOP ORGANIZATIONS

Organization	Count
Hangzhou Alibaba Advertising Co.,Ltd.	12,838
Amazon.com	10,743
Digital Ocean	5,658
Tencent cloud computing	4,873
Google Cloud	1,755

New Service: Keep track of what you have connected to the Internet. Check out [Shodan Monitor](#)

35.186.150.97
97.150.186.35.bc.googleusercontent.com
Google Cloud
Added on 2020-01-25 15:24:15 GMT
United States, Mountain View

database cloud

13.235.229.198
ec2-13-235-229-198.ap-south-1.compute.amazonaws.com
Amazon.com
Added on 2020-01-25 15:23:34 GMT
India, Mumbai

database cloud

508.0 kB **4 Databases**


Database Name	Size
my11beast	296.0 kB
admin	80.0 kB

MongoDB Server Information
Authentication partially enabled

```
{
  "storageEngines": [
    "devnull",
    "ephemeralForTest",
    " mmapv1",
    "wiredTiger"
  ],
  "maxBsonObjectSize": 16777216,
  "ok": 1.0,
  "bits": 64,
  "modules": [],
  "openssl": {
    ...
  }
}
```

MongoDB Server Information

```
{
  "metrics": {
    "commands": {
      "updateUser": {
        "failed": 0,
        "total": 0
      },
      "killAllSessions": {
        "failed": 0,
        "total": 0
      }
    }
  }
}
```



REST API

Shodan comes with a REST API, it can be used to build a web application service based on Shodan or create a wrapper library if none already exists in your favorite language.

The base URL of the API is: <https://api.shodan.io> and all API methods are rate-limited to 1 req/sec.

The API is authenticated so if you forget to provide your API key, you will get a HTTP 401 error.

Here is an example of how you can query your API Plan Information with curl:

```
curl -s https://api.shodan.io/api-info?key={YOUR_API_KEY} | jq
```

```
{  
  "scan_credits": 95,  
  "usage_limits": {  
    "scan_credits": 100,  
    "query_credits": 100,  
    "monitored_ips": 16  
  },  
  "plan": "dev",  
  "https": false,  
  "unlocked": true,  
  "query_credits": 94,  
  "monitored_ips": 2,  
  "unlocked_left": 94,  
  "telnet": false  
}
```

Another query to get a host information:

```
curl -s https://api.shodan.io/shodan/host/1.1.1.1?key={YOUR_API_KEY} | jq
```

```
{  
  "region_code": null,  
  "ip": 16843009,  
  "postal_code": null,  
  "country_code": "AU",  
  "city": null,  
  "dma_code": null,  
  "last_update": "2020-01-25T15:55:54.880090",  
  "latitude": -33.494,  
  "tags": [],  
  "area_code": null,  
  "country_name": "Australia",  
  "hostnames": [  
    "one.one.one.one"  
  ],  
  "org": "Mountain View Communications",  
  "data": [  
    {  
      "_shodan": {  
        "id": "f4218ca0-2728-4d7b-97f8-875f4f04149d",  
        "options": {  
          "referrer": "601b650e-3cc7-4189-babe-921fdf53a9e2",  
          "hostname": "www.1yhaoduo.com"  
        }  
      }  
    }  
  ]  
}
```

```
},
"ptr": true,
"module": "http",
"crawler": "d264629436af1b777b3b513ca6ed1404d7395d80"
},
"hash": -237371161,
"os": null,
"opts": {},
"ip": 16843009,
"isp": "APNIC and Cloudflare DNS Resolver project",
"http": {
"html_hash": 1145258596,
"robots_hash": null,
"redirects": [],
"securitytxt": null,
"title": "DNS resolution error | www.1yhaoduo.com | Cloudflare",
"sitemap_hash": null,
"waf": "CloudFlare",
"robots": null,
"favicon": null,
"host": "www.1yhaoduo.com",
...
}
```

Check the [REST API Documentation](#) for a complete description of all methods.

Language wrappers (libraries)

To interface your tool with the Shodan API you can use one of the wrapper libraries.

The official one is made in Python, but there are also [community libraries](#) in Ruby, PHP, Haskell, Rust, Perl, Node.js, Go, PowerShell, Java and C#.

I will give examples for those three:

- [Python – shodan-python](#)
- [Ruby – shodanz](#)
- [Node.js – shodan-client](#)

Python – shodan-python

Installation

The installation is the same as for the CLI tool as the CLI tool is made upon the python library, they are packaged together.

In a virtual python environment like [pyenv](#):

```
$ easy_install shodan
```

On [BlackArch](#) you can also install the following package:

```
# pacman -S python-shodan
```

Then the API key will always be initialized like that in our code:

```
import shodan

SHODAN_API_KEY = 'API key here'

api = shodan.Shodan(SHODAN_API_KEY)
```

Note: the library is working for both python 2 and 3 but we'll use only python 3 as python 2 is deprecated.

Examples

Basic search:

```
try:
    # Search Shodan
    results = api.search('apache')

    ## Show results
    print('Results found: {}'.format(results['total']))
    for result in results['matches']:
```

```
        print('IP: {}'.format(result['ip_str']))
        print(result['data'])
        print('')
    except shodan.APIError as e:
        print('Error: {}'.format(e))
```

Example of output:

```
IP: 65.99.237.196
HTTP/1.1 200 OK
Date: Sat, 25 Jan 2020 16:07:19 GMT
Server: Apache
Transfer-Encoding: chunked
Content-Type: text/html
```

```
IP: 212.72.184.58
HTTP/1.1 200 OK
Date: Sat, 25 Jan 2020 16:07:29 GMT
Server: Apache/2.2.22 (Debian) mod_python/3.3.1 Python/2.7.3 mod_ssl/2.2.22
OpenSSL/1.0.1t
X-Powered-By: PHP/5.4.45-0+deb7u14
```

```
Expires: Mon, 26 Jul 1997 05:00:00 GMT
Cache-Control: no-store, no-cache, must-revalidate
Pragma: no-cache
Last-Modified: Sat, 25 Jan 2020 16:07:29 GMT
Vary: Accept-Encoding
Transfer-Encoding: chunked
Content-Type: text/html
```

```
IP: 208.109.44.217
HTTP/1.1 404 Not Found
Date: Sat, 25 Jan 2020 16:07:20 GMT
Server: Apache
Content-Length: 381
Content-Type: text/html; charset=iso-8859-1
```

Available ports of a host:

```
try:
    # Lookup the host
    host = api.host('1.1.1.1')
```

```
# Print general info
print("""
    IP: {}
    Organization: {}
    Operating System: {}
""".format(host['ip_str'], host.get('org', 'n/a'), host.get('os', 'n/a')))

# Print all banners
for item in host['data']:
    print("""
        Port: {}
        Banner: {}
    """.format(item['port'], item['data']))
except shodan.APIError as e:
    print('Error: {}'.format(e))
```

Example of output:

```
IP: 1.1.1.1
Organization: Mountain View Communications
Operating System: None
```

Port: 80

Banner: HTTP/1.1 409 Conflict

Date: Sat, 25 Jan 2020 15:55:54 GMT

Content-Type: text/html; charset=UTF-8

Transfer-Encoding: chunked

Connection: close

Set-Cookie: __cfduid=d6241813d879cf2a39d03f5d6ce5a1abc1579967754; expires=Mon, 24-Feb-20
15:55:54 GMT; path=/; domain=.www.1yhaoduo.com; HttpOnly; SameSite=Lax

Cache-Control: max-age=6

Expires: Sat, 25 Jan 2020 15:56:00 GMT

X-Frame-Options: SAMEORIGIN

Vary: Accept-Encoding

Server: cloudflare

CF-RAY: 55ab6f23aee09cbd-AMS

Port: 443

Banner: HTTP/1.1 301 Moved Permanently

Date: Sat, 25 Jan 2020 15:47:19 GMT

Transfer-Encoding: chunked

Connection: keep-alive

Cache-Control: max-age=3600

Expires: Sat, 25 Jan 2020 16:47:19 GMT

```
Location: https://get.vitalsource.com/
Expect-CT: max-age=604800, report-uri="https://report-uri.cloudflare.com/cdn-
cgi/beacon/expect-ct"
Vary: Accept-Encoding
Server: cloudflare
CF-RAY: 55ab628f3b05acca-OTP

Port: 53
Banner: \x00\x00\x80\x83\x00\x01\x00\x00\x00\x01\x00\x00\t_services\x07_dns-
sd\x04_udp\x05local\x00\x00\x0c\x00\x01\x00\x00\x06\x00\x01\x00\x00(\xac\x00@\x01a\x0croo-
t-servers\x03net\x00\x05nstld\x0cverisign-
grs\x03com\x00xf\xf1\xd4\x00\x00\x07\x08\x00\x00\x03\x84\x00\t:\x80\x00\x01Q\x80
```

Displaying stats:

```
# The list of properties we want summary information on
FACETS = [
    ('org', 3),
    'domain',
    'port',
    'asn',
    ('country', 10),
```

```
]

FACET_TITLES = {
    'org': 'Top 3 Organizations',
    'domain': 'Top 5 Domains',
    'port': 'Top 5 Ports',
    'asn': 'Top 5 Autonomous Systems',
    'country': 'Top 10 Countries',
}

try:
    # Query
    query = 'apache 2.4'

    # Count results
    result = api.count(query, facets=FACETS)

    print('Shodan Summary Information')
    print('Query: %s' % query)
    print('Total Results: %s\n' % result['total'])

    # Print the summary info from the facets
    for facet in result['facets']:
```

```
print(FACET_TITLES[facet])

    for term in result['facets'][facet]:
        print('%s: %s' % (term['value'], term['count']))

    # Print an empty line between summary info
    print('')

except shodan.APIError as e:
    print('Error: {}'.format(e))
```

Example of output:

```
Shodan Summary Information
```

```
Query: apache 2.4
```

```
Total Results: 64678
```

```
Top 3 Organizations
```

```
Liquid Web, L.L.C: 23199
```

```
Amazon.com: 7588
```

```
Hetzner Online GmbH: 1818
```

```
Top 5 Domains
```

amazonaws.com: 10679
telecom.net.ar: 1661
your-server.de: 1243
t-ipconnect.de: 664
vultr.com: 443

Top 5 Ports

80: 21212
443: 19890
8080: 3024
10000: 1723
8081: 1366

Top 5 Autonomous Systems

as53824: 13848
as32244: 9351
as16509: 6294
as24940: 1759
as7303: 1453

Top 10 Countries

US: 31090
DE: 5833

```
CN: 4554  
BR: 3010  
AR: 1809  
JP: 1475  
GB: 1168  
IN: 1009  
FR: 756  
CA: 613
```

Note: this examples comes from the [official documentation](#) but were adapted for Python 3 and updated to better suit this article.

Ruby – shodanz

Installation

In a virtual ruby environment like [rbenv](#):

```
$ gem install shodanz
```

Then the API key will always be initialized like that in our code:

```
require 'shodanz'  
  
api = Shodanz.client.new(key: 'YOUR_API_KEY')
```

For production projects you may prefer read the API key via the environment variable SHODAN_API_KEY.

Examples

Basic search:

```
# Search Shodan
results = api.host_search('apache')

# Show results
puts "Results found: #{results['total']}"
results['matches'].each do |result|
  puts "IP: #{result['ip_str']}"
  puts result['data'] + "\n"
end
```

Example of output:

```
IP: 154.218.139.58
HTTP/1.1 200 OK
Date: Tue, 28 Jan 2020 22:13:53 GMT
Server: Apache
Upgrade: h2
Connection: Upgrade, close
Last-Modified: Wed, 26 Apr 2017 08:03:47 GMT
```

ETag: "52e-54e0d47a39ec0"
Accept-Ranges: bytes
Content-Length: 1326
Vary: Accept-Encoding
Content-Type: text/html

IP: 132.148.235.102
HTTP/1.1 200 OK
Date: Tue, 28 Jan 2020 22:13:53 GMT
Server: Apache
Upgrade: h2,h2c
Connection: Upgrade
Last-Modified: Fri, 10 May 2019 09:10:49 GMT

ETag: "a4edb-7ab-58884f152c219"
Accept-Ranges: bytes
Content-Length: 1963
Vary: Accept-Encoding,User-Agent
Content-Type: text/html

IP: 112.126.140.94
HTTP/1.1 404 Not Found

```
Date: Tue, 28 Jan 2020 22:13:34 GMT
Server: Apache
X-Powered-By: PHP/5.2.17
X-UA-Compatible: IE=EmulateIE7
Transfer-Encoding: chunked
Content-Type: text/html
```

Available ports of a host:

```
# Lookup the host
host = api.host('1.1.1.1')

# Print general info
puts "
  IP: #{host['ip_str']}
  Organization: #{host['org'] || 'n/a'}
  Operating System: #{host['os'] || 'n/a'}
"

# Print all banners
host['data'].each do |item|
  puts "
    Port: #{item['port'] || 'n/a'}
```

```
Banner: #{item['data'] || 'n/a'}
```

"

```
end
```

Example of ouput:

```
IP: 1.1.1.1
Organization: Mountain View Communications
Operating System: n/a
```

```
Port: 443
Banner: HTTP/1.1 403 Forbidden
Server: cloudflare
Date: Tue, 28 Jan 2020 18:34:35 GMT
Content-Type: text/html
Content-Length: 553
Connection: keep-alive
CF-RAY: 55c50fb4e8149d5a-AMS
```

```
Port: 80
Banner: HTTP/1.1 409 Conflict
```

Date: Tue, 28 Jan 2020 17:26:54 GMT
Content-Type: text/html; charset=UTF-8
Transfer-Encoding: chunked
Connection: close
Set-Cookie: __cfduid=d189a930262f96d94a707a90d853a56bd1580232414; expires=Thu, 27-Feb-20
17:26:54 GMT; path=/; domain=.www.1yhaoduo.com; HttpOnly; SameSite=Lax
Cache-Control: max-age=6
Expires: Tue, 28 Jan 2020 17:27:00 GMT
X-Frame-Options: SAMEORIGIN
Vary: Accept-Encoding
Server: cloudflare
CF-RAY: 55c4ac8fba63801a-SAN

Port: 53
Banner:
Recursion: enabled
Resolver ID: AMS

Displaying stats:

```
# The list of properties we want summary information on
FACETS = {
```

```
'org': 3,
'domain': 5,
'port': 5,
'asn': 5,
'country': 10,
}

FACET_TITLES = {
'org': 'Top 3 Organizations',
'domain': 'Top 5 Domains',
'port': 'Top 5 Ports',
'asn': 'Top 5 Autonomous Systems',
'country': 'Top 10 Countries',
}

# Query
query = 'apache 2.4'

# Count results
result = api.host_count(query, facets: FACETS)
puts 'Shodan Summary Information'
puts "Query: #{query}"
puts "Total Results: #{result['total']}\n"
```

```
# Print the summary info from the facets
result['facets'].each do |facet, _v|
  puts FACET_TITLES[facet]

  result['facets'][facet].each do |term|
    puts "#{term['value']}: #{term['count']}"
  end

  # Print an empty line between summary info
  puts ''
end
```

Example of output:

```
Shodan Summary Information
```

```
Query: apache 2.4
```

```
Total Results: 63939
```

```
Liquid Web, L.L.C: 23126
```

```
Amazon.com: 7843
```

```
Hetzner Online GmbH: 1798
```

amazonaws.com: 10398
telecom.net.ar: 1609
your-server.de: 1232
t-ipconnect.de: 629
vultr.com: 450

80: 21131
443: 19772
8080: 3023
10000: 1672
8081: 1372

as53824: 13810
as32244: 9316
as16509: 6138
as24940: 1740
as7303: 1410

US: 30877

```
DE: 5781
CN: 4432
BR: 2949
AR: 1757
JP: 1472
GB: 1168
IN: 1030
FR: 720
CA: 613
```

Async support with the stream API:

```
require 'async'
require 'shodanz'

api = Shodanz.client.new(key: 'YOUR_API_KEY')

# Asynchronously stream banner info from shodan and check any
# IP addresses against the experimental honeypot scoring service.
api.streaming_api.banners do |banner|
  if ip = banner['ip_str']
    Async do
      score = api.rest_api.honeypot_score(ip).wait
```

```
    puts "#{ip} has a #{score * 100}% chance of being a honeypot"
    rescue Shodanz::Errors::RateLimited
      sleep rand
      retry
      rescue # any other errors
      next
    end
  end
end
```

Warning: Freelancer API plan or better required for using the stream API, developer or free plan won't work.

Note: this async example comes from the shodanz documentation.

Useful methods

```
# Returns all the protocols that can be used when launching an Internet scan
api.protocols

# Returns a list of port numbers that the Shodan crawlers are looking for
```

```
api.ports

# Returns information about the Shodan account linked to this API key
api.profile

# Look up the IP address for the provided list of hostnames
api.resolve('archlinux.org', 'blackarch.org')

# Look up the hostnames that have been defined for the given list of IP addresses
api.reverse_lookup('138.201.81.199', '176.31.253.211')

# Get your current IP address as seen from the Internet
api.my_ip

# Calculates a honeypot probability score ranging from 0 (not a honeypot) to 1.0 (is a
honeypot)
api.honeypot_score('1.1.1.1')

# API Plan Information
api.info
```

Exploits API

```
puts client.exploit_count(port: 22, page: 1)
puts client.exploit_search('rce couchdb', type: 'remote', platform: 'linux', author: 'Metasploit')
```

You can find more examples [here](#) or read the shodanz [API documentation](#).

Node.js – shodan-client

Installation

In a virtual nodejs environment like [nodenv](#):

```
$ npm i shodan-client
```

Then the API key will always be initialized like that in our code:

```
const util = require('util');
const api = require('shodan-client');

const key = 'API key here';
```

Examples

Basic search

```
const searchOpts = {};
```

```
const searchQuery = 'apache';

api
  .search(searchQuery, key, searchOpts) // Search Shodan
  .then(results => {
    console.log('Results found: ' + results['total'] + "\n"); // Show results
    for (const result of results['matches']) {
      console.log(`IP: ${result['ip_str']}`);
      console.log(result['data'] + "\n");
    }
  })
  .catch(err => {
    console.log('Error:');
    console.log(err);
  });
});
```

Example of output:

```
Results found: 25855805

IP: 210.143.102.156
HTTP/1.1 302 Found
Date: Sat, 01 Feb 2020 18:45:43 GMT
```

Server: Apache/2.2.15 (Scientific Linux)
Location: https://210.143.102.156/
Content-Length: 299
Connection: close
Content-Type: text/html; charset=iso-8859-1

IP: 52.168.162.242
HTTP/1.1 200 OK
Date: Sat, 01 Feb 2020 18:44:49 GMT
Server: Apache
X-Frame-Options: SAMEORIGIN
Last-Modified: Tue, 13 Aug 2019 14:51:43 GMT
ETag: "f11-59000c7615dc0"
Accept-Ranges: bytes
Content-Length: 3857
X-XSS-Protection: 1; mode=block
Cache-Control: no-cache, no-store, must-revalidate
Pragma: no-cache
Expires: 0
Content-Type: text/html; charset=UTF-8
Set-Cookie: pwcount=2; Secure; Path=/

```
Cache-Control: no-cache
```

```
IP: 217.160.91.209
HTTP/1.1 403 Forbidden
Date: Sat, 01 Feb 2020 18:45:18 GMT
Server: Apache
Content-Length: 1364
X-Frame-Options: deny
Content-Type: text/html
```

Available ports of a host

```
const searchOpts = { };

const ip = '1.1.1.1';

api
  .host(ip, key, searchOpts) // Lookup the host
  .then(host => {
    // Print general info
    console.log(`
```

```
    IP: ${host['ip_str']}
    Organization: ${host['org'] || 'n/a'}
    Operating System: ${host['os'] || 'n/a'}
  `);
  // Print all banners
  for (const item of host['data']) {
    console.log(`
      Port: ${item['port'] || 'n/a'}
      Banner: ${item['data'] || 'n/a'}
    `);
  }
}

.catch(err => {
  console.log('Error:');
  console.log(err);
}) ;
```

Example of output:

```
IP: 1.1.1.1
Organization: Mountain View Communications
Operating System: n/a
```

Port: 443
Banner: HTTP/1.1 403 Forbidden
Server: cloudflare
Date: Sat, 01 Feb 2020 19:26:14 GMT
Content-Type: text/html
Content-Length: 553
Connection: keep-alive
CF-RAY: 55e650de89868020-SAN

Port: 80
Banner: HTTP/1.1 409 Conflict
Date: Sat, 01 Feb 2020 19:16:16 GMT
Content-Type: text/html; charset=UTF-8
Transfer-Encoding: chunked
Connection: close
Set-Cookie: __cfduid=dd6d38c961c18135646e1681bd1f809ad1580584576; expires=Mon, 02-Mar-20
19:16:16 GMT; path=/; domain=.www.1yhaoduo.com; HttpOnly; SameSite=Lax
Cache-Control: max-age=6
Expires: Sat, 01 Feb 2020 19:16:22 GMT
X-Frame-Options: SAMEORIGIN

Vary: Accept-Encoding
Server: cloudflare
CF-RAY: 55e64240bb5a801a-SAN

Displaying stats

```
const FACETS = {  
  'org': 3,  
  'domain': 5,  
  'port': 5,  
  'asn': 5,  
  'country': 10,  
};  
  
const FACET_TITLES = {  
  'org': 'Top 3 Organizations',  
  'domain': 'Top 5 Domains',  
  'port': 'Top 5 Ports',  
  'asn': 'Top 5 Autonomous Systems',  
  'country': 'Top 10 Countries',  
};  
  
// https://github.com/jesusprubio/shodan-client/issues/34
```

```
// const opts = { facets: FACETS };

const opts = { facets: JSON.stringify(FACETS).replace(/["{}"]/g, '') };
```



```
// Query
```

```
const query = 'apache 2.4';
```



```
api
```

```
    .count(query, key, opts) // Count results
```

```
    .then(result => {
        console.log('Shodan Summary Information');
        console.log(`Query: ${query}`);
        console.log(`Total Results: ${result['total']}\n`);

        // Print the summary info from the facets
        for (const facet in result['facets']) {
            console.log(FACET_TITLES[facet]);

            for (const term of result['facets'][facet]) {
                console.log(`${term['value']}: ${term['count']}`);
            }

            // Print an empty line between summary info
            console.log('');
        }
    });
}
```

```
        }
    } )
    .catch(err => {
    console.log('Error:');
    console.log(err);
}) ;
```

Example of output:

Shodan Summary Information

Query: apache 2.4

Total Results: 63112

Top 3 Organizations

Liquid Web, L.L.C: 22985

Amazon.com: 8614

Hetzner Online GmbH: 1797

Top 5 Domains

amazonaws.com: 10051

telecom.net.ar: 1600

your-server.de: 1220

t-ipconnect.de: 603

vultr.com: 429

Top 5 Ports

80: 21098

443: 19669

8080: 3040

10000: 1669

8081: 1411

Top 5 Autonomous Systems

as53824: 13725

as32244: 9260

as16509: 5941

as24940: 1750

as7303: 1383

Top 10 Countries

US: 30672

DE: 5780

CN: 4072

BR: 2931

AR: 1745

JP: 1415

GB: 1147

IN: 939


FR: 738

CA: 675

Plugins

Firefox

Shodan.io




This add-on retrieves data gathered by Shodan.io of the current website you're browsing. It displays you general information such as the Organisation but also open ports.

[Source](#)

Chromium

[Shodan](#)



The Shodan plugin tells you where the website is hosted (country, city), who owns the IP and what other services/ports are open.

The Shodan plugin for Chrome automatically checks whether Shodan has any information for the current website. Is the website also running FTP, DNS, SSH or some unusual service? With this plugin you can see all the info that Shodan has collected on a given website/domain.

Shodan Search Query Syntax

Banner and properties

To get the most out of Shodan it's important to understand the search query syntax.

In Shodan's vocabulary **a banner** is an object containing the information of a service.

In the [official documentation](#) the below example of a simplified banner is given:

```
{  
  "data": "Moxa Nport Device  
          Status: Authentication disabled  
          Name: NP5232I_4728  
          MAC: 00:90:e8:47:10:2d",  
  "ip_str": "46.252.132.235",
```

```
"port": 4800,  
"org": "Starhub Mobile",  
"location": {  
    "country_code": "SG"  
}  
}
```

Each key of the dictionary is called **a property** (data, ip_str, port, etc.). Each property stores a different type of information about the service.

By default Shodan is looking only into the data property, if no filter is provided.

Search filters

You could have found the previous example banner by searching Moxa Nport Device, but if you would have searched for devices from Starhub Mobile it wouldn't have returned the expected result. That's because, as I said earlier, by default, Shodan only searches the data property!

To search data using other properties we must use **filters**.

Search filters are special keywords to tell Shodan that you wish to search specific properties.

Filters are formatted as key:value.

Some examples:

- To search for devices located in the Starhub Mobile Network:
 - org:"Starhub Mobile"
- To search for devices located in Singapore:
 - country:SG
- And of course they can be combined:
 - org:"Starhub Mobile" country:SG

Properties/filters specification

Here is the complete list of properties for banners (Source: [Official documentation](#)).

General properties

Property	[Type] Description
asn	[String] The autonomous system number (ex. “AS4837”).
data	[String] Contains the banner information for the service.
ip	[Integer] The IP address of the host as an integer.
ip_str	[String] The IP address of the host as a string.

ipv6	[String] The IPv6 address of the host as a string. If this is present then the “ip” and “ip_str” fields wont be.
port	[Integer] The port number that the service is operating on.
timestamp	[String] The timestamp for when the banner was fetched from the device in the UTC timezone. Example: “2014-01-15T05:49:56.283713”
hostnames	[String[]] An array of strings containing all of the hostnames that have been assigned to the IP address for this device.
domains	[String[]] An array of strings containing the top-level domains for the hostnames of the device. This is a utility property in case you want to filter by TLD instead of subdomain. It is smart enough to handle global TLDs with several dots in the domain (ex. “co.uk”)
location	[Object] An object containing all of the location information for the device.
location.area_code	[Integer] The area code for the device’s location. Only available for the US.
location.city	[String] The name of the city where the device is located.
location.country_code	[String] The 2-letter country code for the device location.
location.country_code3	[String] The 3-letter country code for the device location.

location.country_name	[String] The name of the country where the device is located.
location.dma_code	[Integer] The designated market area code for the area where the device is located. Only available for the US.
location.latitude	[Double] The latitude for the geolocation of the device.
location.longitude	[Double] The longitude for the geolocation of the device.
location.postal_code	[String] The postal code for the device's location.
location.region_code	[String] The name of the region where the device is located.
opts	[Object] Contains experimental and supplemental data for the service. This can include the SSL certificate, robots.txt and other raw information that hasn't yet been formalized into the Banner Specification.
org	[String] The name of the organization that is assigned the IP space for this device.
isp	[String] The ISP that is providing the organization with the IP space for this device. Consider this the “parent” of the organization in terms of IP ownership.
os	[String] The operating system that powers the device.
transport	[String] Either “udp” or “tcp” to indicate which IP transport protocol was used to

Optional Properties

Property	[Type] Description
uptime	[Integer] The number of minutes that the device has been online.
link	[String] The network link type. Possible values are: “Ethernet or modem”, “generic tunnel or VPN”, “DSL”, “IPIP or SIT”, “SLIP”, “IPSec or GRE”, “VLAN”, “jumbo Ethernet”, “Google”, “GIF”, “PPTP”, “loopback”, “AX.25 radio modem”.
title	[String] The title of the website as extracted from the HTML source.
html	[String] The raw HTML source for the website.
product	[String] The name of the product that generated the banner.
version	[String] The version of the product that generated the banner.
devicetype	[String] The type of device (webcam, router, etc.).
info	[String] Miscellaneous information that was extracted about the product.
cpe	[String] The relevant Common Platform Enumeration for the product or known

vulnerabilities if available. For more information on CPE and the official dictionary of values visit the [CPE Dictionary](#).

SSL Properties

Property	[Type] Description
ssl.cert	[Object] The parsed certificate properties that includes information such as when it was issued, the SSL extensions, the issuer, subject etc.
ssl.cipher	[Object] Preferred cipher for the SSL connection
ssl.chain	[Array] An array of certificates, where each string is a PEM-encoded SSL certificate. This includes the user SSL certificate up to its root certificate.
ssl.dhparams	[Object] The Diffie-Hellman parameters if available: “prime”, “public_key”, “bits”, “generator” and an optional “fingerprint” if we know which program generated these parameters.
ssl.versions	[Array] A list of SSL versions that are supported by the server. If a version isn't supported the value is prefixed with a “-”. Example: [“TLSv1”, “-SSLv2”] means that the server supports TLSv1 but doesn't support SSLv2.

Miscellaneous

The beta version of the website offers two useful pages:

- o **Filters** – A filter/property cheat sheet list
- o **Examples** – A list of search query examples

The screenshot shows the Shodan search interface with the title "Search Query Examples". Below the title, there are eight search filters, each with a "RUN SEARCH" button:

- Websites that require HTTPS connections
HTTP Strict-Transport-Security
- Services that have the word "Apache" in their headers
Apache
- Apache web servers
product:Apache
- Websites that have the word "Apache" in their HTML
http.html:Apache
- Websites that are using the Bootstrap CSS framework
http.component:bootstrap
- Websites that support TLS 1.3
sslversion:tlsv1.3 HTTP
- Services that support SSLv2 and don't support TLS
sslversion:sslv2 -sslversion:tlsv1 tlsv1.2 tlsv1.3
- Websites that support HTTP/2
sslAlpn:h2

Shodan dorks & use cases

I'll start by showcasing some simple [snippets from shodan](#).

Examples are given for the CLI:

Number of devices vulnerable to Heartbleed

```
$ shodan count vuln:cve-2014-0160  
80467
```

Get a list of subdomains for a domain

```
$ shodan domain cnn.com  
CNN.COM  
  
A 151.101.193.67  
A 151.101.129.67  
A 151.101.65.67  
A 151.101.1.67  
...  
newsroom.blogs CNAME cnnnewsroom.wordpress.com  
newsstream.blogs CNAME cnnnewsstream.wordpress.com  
now CNAME www.cnn.com  
ntm.blogs CNAME ntm.blogs.cnn.com.edgesuite.net  
olympics.blogs CNAME olympics.blogs.cnn.com.edgesuite.net  
olympics.edition CNAME cnn.site.scribblelive.com
```

```
on A 157.166.224.172
outfront.blogs CNAME cnnoutfront.wordpress.com
pagingdrgupta.blogs CNAME cnnpagingdrgupta.wordpress.com
parkerspitzer.blogs CNAME cnnparkerspitzer.wordpress.com
...
```

Create a private firehose for your network and subscribe to it

```
$ shodan alert create mynetwork 198.20.58.0/24 && shodan stream --alerts=all
```

Find the top 10 most common vulnerabilities in Switzerland

```
$ shodan stats --facets vuln country:CH
Top 10 Results for Facet: vuln
cve-2018-1312 36,562
cve-2017-7679 31,109
cve-2019-0220 28,882
cve-2016-8612 27,638
cve-2018-17199 26,706
cve-2016-4975 26,560
cve-2018-1283 25,477
cve-2017-15715 25,477
cve-2017-15710 25,477
cve-2017-7668 23,261
```

I will continue with some publicly [shared queries](#):

D-Link Internet Camera DCS-5300 series, without authentication

```
$ shodan search 'd-Link Internet Camera, 200 OK'
```

FTP server with anonymous authentication enabled

```
$ shodan search '230 login successful port:21'
```

Databases

```
# MySQL
$ shodan search 'product:MySQL'

# MongoDB
$ shodan search 'product:MongoDB'

# elastic
$ shodan search 'port:9200 json'

# Memcached
$ shodan search 'product:Memcached'

# CouchDB
```

```
$ shodan search 'product:CouchDB'

# PostgreSQL
$ shodan search 'port:5432 PostgreSQL'

# Riak
$ shodan search 'port:8087 Riak'

# Redis
$ shodan search 'product:Redis'

# Cassandra
$ shodan search 'product:Cassandra'
```

Games

```
# Minecraft
$ shodan search 'Minecraft Server port:25565'

# Counter-Strike: Global Offensive
$ shodan search 'product:"Counter-Strike Global Offensive"'

# Starbound
```

```
$ shodan search 'product:Starbound'

# ARK: Survival Evolved
$ shodan search 'product:"ARK Survival Evolved"'
```

Industrial Control Systems

```
# XZERES Wind Turbine
$ shodan search 'title:"xzeres wind"'

# PIPS Automated License Plate Reader
$ shodan search 'html:"PIPS Technology ALPR Processors"'

# Modbus
$ shodan search 'port:502'

# Niagara Fox
$ shodan search 'port:1911,4911 product:Niagara'

# GE-SRTP
$ shodan search 'port:18245,18246 product:"general electric"'

# MELSEC-Q
```

```
$ shodan search 'port:5006,5007 product:mitsubishi'

# CODESYS

$ shodan search 'port:2455 operating system'

# S7

$ shodan search 'port:102'

# BACnet

$ shodan search 'port:47808'

# HART-IP

$ shodan search 'port:5094 hart-ip'

# Omron FINS

$ shodan search 'port:9600 response code'

# IEC 60870-5-104

$ shodan search 'port:2404 asdu address'

# DNP3

$ shodan search 'port:20000 source address'
```

```
# EtherNet/IP
$ shodan search 'port:44818'

# PCWorx
$ shodan search 'port:1962 PLC'

# Crimson v3.0
$ shodan search 'port:789 product:"Red Lion Controls"'

# ProConOS
$ shodan search 'port:20547 PLC'
```

And now, some [dorks](#) from [dalmoz](#):

ASCII video examples

[Shodan on asciinema.org](#)

Hacked Ubiquiti Networks Device

```
$ shodan search 'hacked-router-help-sos'
```

Surveillance cameras, user: admin, no password

```
$ shodan search 'hacked-router-help-sos'
```

Home routers' storage/attached USB storage

```
$ shodan search 'IPC$ all storage devices'
```

PBX phone gateways without authentication

```
$ shodan search 'port:23 console gateway -password'
```

Lantronix ethernet adapter's admin interface without password

```
$ shodan search 'Press Enter for Setup Mode port:9999'
```

Polycom video-conference system no-auth shell

```
$ shodan search '"polycom command shell"'
```

VNC servers without authentication

```
$ shodan search '"authentication disabled" port:5900,5901'
```

NPort serial-to-eth / MoCA devices without password

```
$ shodan search 'nport -keyin port:23'
```

Some *PenTest/T* queries:

Default Jenkins installations

```
$ shodan search 'http.favicon.hash:81586312'
```

SonarQube installations

```
$ shodan search 'http.favicon.hash:1485257654'
```

IBM WebSphere version disclosure

```
$ shodan search 'WASRemoteRuntimeVersion'
```

And to finish, a collection of search queries: *Awesome Shodan Search Queries*

- [Website](#)
- [GitHub](#)

Tools using Shodan

- <https://developer.shodan.io/apps>
- <https://github.com/BullsEye0/shodan-eye>
- https://www.rapid7.com/db/modules/auxiliary/gather/shodan_search
- <https://github.com/s0md3v/Striker>
- <https://github.com/lanmaster53/recon-ng>
- <https://github.com/smicallef/spiderfoot>
- https://github.com/DefensePointSecurity/threat_note
- <https://github.com/OWASP/Amass>

- <https://github.com/woj-ciech/Kamerka-GUI>
- <https://github.com/random-robbie/My-Shodan-Scripts>
- <https://github.com/jakejarvis/awesome-shodan-queries>
- <https://github.com/pielco11/fav-up>

ShodanSexploit

It allows you to use all Shodan calls on your terminal and making detailed queries.

Github repository: <https://github.com/shodansploit/shodansploit>

Install:

```
git clone https://github.com/ismailtasdelen/shodansploit.git
```

```
cd shodansploit
```

```
python shodansploit.py
```

```
docker run -t ismailtasdelen/shodansploit
```

Docker Run:

```
docker run -rm -it ismailtasdelen/shodansploit
```

Menu:

- [1] GET > /shodan/host/{ip}
- [2] GET > /shodan/host/count
- [3] GET > /shodan/host/search
- [4] GET > /shodan/host/search/tokens
- [5] GET > /shodan/ports
- [6] GET > /shodan/exploit/author
- [7] GET > /shodan/exploit/cve
- [8] GET > /shodan/exploit/msb
- [9] GET > /shodan/exploit/bugtraq-id
- [10] GET > /shodan/exploit/osvdb

[11] GET > /shodan/exploit/title

[12] GET > /shodan/exploit/description

[13] GET > /shodan/exploit/date

[14] GET > /shodan/exploit/code

[15] GET > /shodan/exploit/platform

[16] GET > /shodan/exploit/port

[17] GET > /dns/resolve

[18] GET > /dns/reverse

[19] GET > /labs/honeyscore/{ip}

[20] GET > /account/profile

[21] GET > /tools/myip

[22] GET > /tools/httpheaders

[23] GET > /api-info

[24] Exit

Fav-Up

Description:

Lookups for real IP starting from the favicon icon and using Shodan.

Install:

At least python3.6 is required due to spicy syntax.

```
git clone https://github.com/pielco11/fav-up.git
```

```
pip3 install -r requirements.txt
```

Command overview:

```
usage: python3 favup [options]

optional arguments:
  -h, --help            show this help message and exit
  -kf KEY_FILE, --key-file KEY_FILE
                        Specify the file which contains the API key.
  -k KEY, --key KEY    Specify the API key.
  -sc, --shodan-cli    Load the API key from Shodan CLI.
  -ff FAVICON_FILE, --favicon-file FAVICON_FILE
                        Load the favicon icon from a local file.
  -fu FAVICON_URL, --favicon-url FAVICON_URL
                        Load the favicon icon from an URL.
  -w WEB, --web WEB    Extracts the favicon location from the page.
  -fh FAVICON_HASH, --favicon-hash FAVICON_HASH
                        Running from direct favicon hash number
  -fl FAVICON_LIST, --favicon-list FAVICON_LIST
                        Iterate over a file that contains the full path of all
                        the icons which you want to lookup.
  -ul URL_LIST, --url-list URL_LIST
                        Iterate over a file that contains the full URL of all
                        the icons which you want to lookup.
  -wl WEB_LIST, --web-list WEB_LIST
                        Iterate over a file that contains all the domains
                        which you want to lookup.
  -o OUTPUT, --output OUTPUT
                        Specify output file, currently supported formats are
                        CSV and JSON.
```

Examples

Favicon-file:

```
python3 favUp.py --favicon-file favicon.ico -sc
```

Favicon-url

```
python3 favUp.py -favicon-url https://domain.behind.cloudflare/assets/favicon.ico -sc
```

Web

```
python3 favUp.py -web domain.behind.cloudflare -sc
```

Module

```
from favUp import FavUp

f = FavUp()

f.shodanCLI = True

f.web = "domain.behind.cloudflare"

f.show = True

f.run()
```

```
for result in f.faviconsList:

    print(f"Real-IP: {result['found_ips']}")

    print(f"Hash: {result['favhash']}")
```

Related info:

<https://pielco11.ovh/posts/cloud-hunting/>

Articles of advanced uses

- [Pivoting with Property Hashes](#)
- [Working with Shodan Data Files](#)
- [Create a GIF from an IP Image History](#)

Shodan alternatives

Web commercial alternatives

- [Onyphe](#) – pretty like Shodan but in addition of scanning it also crawls data from passive DNS lookup, threatlist lookup and paste sites lookup. However the free version is more limited than Shodan.

- [ZoomEye](#) – is also very similar to Shodan, has a great set of advanced filters that are more documented than Shodan's and a ton of pre-set queries. There is also a great free API tier.
- [Censys](#) – like Shodan, it also has the ability to track changes, send alerts, etc. It seems there is no free API plan, the only free option is to use the website.
- [thingful](#) – a search engine that is targeting only the Internet of Things
- [FOFA](#) – is like Shodan, it also has a CLI tool and a Java, Go, C and Python library.
- [Greynoise](#) – is like Shodan, but there is no free API plan, only web visualizer access. Also has a python library and a CLI tool.
- [BinaryEdge](#) – like Shodan there are the search engine, honeypots/sensors detector but also an uncommon feature: Torrents/DHT Monitoring. There is a free Web & API plan.

Open source self hosted alternatives

- [IVRE](#) – [Source](#) > is a network recon framework, including tools for passive recon (flow analytics relying on Bro, Argus, Nfdump, fingerprint analytics based on Bro and p0f) and active recon (IVRE uses Nmap to run scans, can use ZMap as a pre-scanner; IVRE can also import XML output from Nmap and Masscan).
- It has a WebUI and a CLI tool.
- [purplepee](#) – [Source](#) > it allows you to view general relations about a websites HTTP header, websites DNS records, websites SSL certificates and open TCP ports as well as ASN whois information.
- In addition of the open-source project, there is also a public instance hosted online.

Thanks

First I want to thanks John C. Matherly a.k.a. @achillean to have created Shodan and maintained it for 10 years.

Then I also want to thanks Porter Adams (Co-Founder of Disappear Digital) and Ismael Gonzalez (<http://osint.team/> member).

Finally I want to thanks Nathaniel Fried and Peter James Hansen for their amazing work at TurgenSec.

References

- [SHODAN for Penetration testers](#)
- [Shodan – CLI Snippets](#)
- [Shodan Command-Line Interface](#)
- [Shodan library documentation](#)
- [Shodan help center](#)
- More references directly quoted during the article

About the author

My name is *Alexandre ZANNI* aka **noraj**. I'm a penetration tester and ethical hacker. Also I'm a staff member of the [RTFM association](#) and a developer of [BlackArch Linux](#).

My hacker page: pwn.by/noraj

COMMENTS

[Leave a Reply](#)**bill.liu**

3 months ago

Hi,Alex,as I know the shodan company was established in 2009,but as you know is in 2008,would double check and reply?

[Reply](#)**bill.liu**

3 months ago

Hi Alex,would help to show some examples for us ?

[Reply](#)**L E A V E A R E P L Y**

Your email address will not be published. Required fields are marked *

 Comment* Name*

Email*

Website

Save my name, email, and website in this browser for the next time I comment.

Post Comment

SEARCH

Search ...



TURGENSEC

Community

Breaches

OSINT & Social Engineering

Research and Development

Business Resources

Pentesting

TurgenSec

Services

Exosystem Monitoring

Intelligence Acquisition

Data Shadow

Research

Personal Automated Intelligence

Table of Contents [[hide](#)]

[What is Shodan?](#)

[Shodan interfaces](#)

[CLI tool](#)

[Website](#)

[REST API](#)

[Language wrappers \(libraries\)](#)

[Plugins](#)

[Shodan Search Query Syntax](#)

[Banner and properties](#)

[Search filters](#)

[Properties/filters specification](#)

[Miscellaneous](#)

[Shodan dorks & use cases](#)

[Tools using Shodan](#)

[ShodanSploit](#)

[Fav-Up](#)

[Articles of advanced uses](#)

[Shodan alternatives](#)

[Thanks](#)

[References](#)

[About the author](#)



© 2020 by TurgenSec

[Home](#) [Contact us](#) [Policies](#)

