

Free Diagram Documentation

Link to schema: https://app.quickdatabasediagrams.com/#/d/ez23bl

DefaultDjangoUser

| Field | Description | Туре | Default | Other | |
|-------|-------------|------|---------|-------|--|
| id | | int | | PK | |

UserProfile

| Field | Description | Туре | Default | Other |
|----------|----------------------------------------------------------------------|-------|---------|-----------------|
| id | | int | | PK |
| user_id | | | | FK |
| photo_id | User preview photo id. | | | FK, NULLABLE |
| api_key | Can be used to exchange messages on behalf of a user or create bots. | bytes | | |

Bot

Bot - a system that can be used for a variety of tasks from chat administration to remote control of another computer.

| Field | Description | Туре | Default | Other |
|------------|-------------|-------|---------|-------|
| id | | int | | PK |
| creator_id | | | | FK |
| name | | str | | |
| token | | bytes | | |

Chat

Chat - an object that connects two or more chat members.

When sending a message, all members of the chat will receive it.

| Field | Description | Туре | Default | Other |
|----------|-------------|------|---------|-------|
| id | | int | | PK |
| is_group | | bool | | |

ChatMember

Chat member - a wrapper for user or bot that simplifies the work with the database.

| Field | Description | Туре | Default | Other |
|---------|-------------|------|---------|-----------------|
| id | | int | | PK |
| user_id | | | | FK |
| bot_id | | | | FK, NULLABLE |

QuickDBD-Free Diagram Page 1 of 2



| Field | Description | Туре | Default | Other |
|---------|-------------|------|---------|-------|
| chat_id | | | | FK |
| is_bot | | bool | | |

Message

| Field | Description | Туре | Default | Other |
|-----------------|----------------------------------------------------------------------------------------------------|-------|---------|----------|
| id | | | | PK |
| chat_id | | | | FK |
| sender_id | | | | FK |
| type | Message type, possible types: text; executable; photo; document; other; | str | | |
| text | Encrypted text of the message. Can perform the role of caption when sending files. | bytes | | NULLABLE |
| files_password | Encrypted password for encrypted files attached to the message. | bytes | | NULLABLE |
| encryption_type | Content (such as text & file_password) of each message is encrypted using 2048-bit RSA encryption. | str | | |

File

| Field | Description | Туре | Default | Other |
|-----------------|----------------------------------------------------------------|------|---------|-------|
| id | | int | | PK |
| name | | str | | |
| link | Link to a file stored in the cloud storage. | str | | |
| message_id | | | | FK |
| encryption_type | Each file is encrypted using 256-bit AES symmetric encryption. | str | | |

QuickDBD-Free Diagram Page 2 of 2