

CRP229 Quick Start Guide

LAUNCH

Front & Side View



CRP229 Display Tablet


- Camera Lens
- Audio Speaker

Rear View

Connections

1. Locate vehicle's DLC socket: it provides standard 16 pins and is generally located on driver's side, about 12 inch away from the center of dashboard. See Figure **DLC Location**. If DLC is not equipped under dashboard, an label indicating its position will be given. In case no DLC is found, please refer to Automobile Repair Manual;

Note: Remember to remove the diagnostic connector from the DLC if it keeps unattended.




2. Plug one end of the diagnostic cable into the DB15 connector and the other end into the vehicle's DLC. For vehicles with non-16PIN DLC, please choose the desired connector. Normally the power indicator of CRP229 will light up.

1 Charge CRP229 & Power On

1. Remove the cover of USB port, and then connect USB end of the included charger to the USB port of CRP229;
2. Connect the other end of the charger into the AC outlet.
If CRP229 is being charged, the charging indicator illuminates red; Once the indicator turns green, it indicates that charging is OK.
3. Press [POWER] button, the system starts initializing and then enter the desktop.



2 Wi-Fi Connection

1. Tap [Settings] on the desktop and then slide the Wi-Fi switch to ON;
2. Select the desired Wi-Fi connection from the list (Correct password may be required for secured networks).
3. When "Connected" appears, tap  to exit and return to the desktop.



3 Register

1. Launch the CRP229 application on the desktop, a disclaimer page appears. Tap [I have read it] to enter the main menu screen;
2. Tap "Diagnose" and then tap "Login" on the upper right corner of the screen.




3 Register (Cont'd)


3. Username is generated based on the S/N (can be obtained from Device Info on Android's home screen) automatically and Password is generated by system randomly.
Key in your valid email address, tap "Register".
A confirmation dialog box appears, tap "Confirm" and the system will send the registration information to your email.



4 Update/Download Software

1. Tap "Update" on the main menu screen;
2. By default, all vehicle diagnosis software are selected. To deselect all, tap ; To deselect certain software, just uncheck the box next to the software version.



3. Tap  to start downloading. Once download finishes, the software packages will be installed automatically.