

```

1 #Bryson Cook
2 #ISYE6501, Spring 2018
3 #Homework 1
4
5 #Part 2.2.1a: SVM
6
7 install.packages("kknn")
8 install.packages("kernlab")
9
10 library(kknn)
11 library(kernlab)
12
13
14 mydata = as.matrix(read.csv("credit_card_data.csv",header=FALSE))
15
16 model = ksvm(mydata[,1:10], mydata[,11],type="C-svc",
17 kernel="vanilladot",C=100,scaled=TRUE)
18 # calculate a1-am
19 a = colSums(model@xmatrix[[1]] * model@coef[[1]])
20 a
21
22 # calculate a0
23 a0 = -model@b
24 a0
25
26 # see what the model predicts
27 pred = predict(model,mydata[,1:10])
28 pred
29
30 # see what fraction of the model's predictions match the actual classification
31 sum(pred == mydata[,11]) / nrow(mydata)
32
33 #Part 2.2.1b: Vary C values to view accuracy. C varies on a logarithmic scale.
34
35 Cvals = seq(-10,10)
36 ans = matrix(, nrow = length(Cvals), ncol = 2)
37 y = 0
38 for (x in Cvals){
39     model = ksvm(mydata[,1:10], mydata[,11],type="C-svc",
40 kernel="vanilladot",C=1*10^x,scaled=TRUE)
41     pred = predict(model,mydata[,1:10])
42     accuracy = sum(pred == mydata[,11]) / nrow(mydata)
43     y=y+1
44     ans[y,1]= 1*10^x
45     ans[y,2] = accuracy
46 }
47
48 #Prints C values then the accuracy:
49 plot(log10(ans[,1]), ans[,2], main="KSVM Accuracies",
50 xlab="Log(C Value)", ylab="Accuracy")
51
52 # As C increases, the max accuracy is found between  $1*10^{-3}$  and 100, and also at
53 100,000. As C increases,
54 # we are decreasing the margin, but error should also get smaller, though only up to
55 # a certain point (C =  $1*10^5$  apparently).
56
57 #####
58 #Part 3, K-Nearest Neighbor
59
60 mydata = data.frame(read.csv("credit_card_data.csv",header=FALSE))
61 steps = seq(1,100)
62 answey = matrix(, nrow = length(steps), ncol = 2)
63 z=1

```

```

64 for (y in steps){
65   answerx = matrix(, nrow(mydata), ncol = 1)
66   #answerx = matrix(, nrow=100, ncol = 1)
67   #for (x in 1:100){
68   for (x in 1:nrow(mydata)){
69     knn = kknn(V11~., mydata[-x,], mydata[x,], k = y, scale=TRUE)
70     class = round(fitted(knn),0)
71     match = class == mydata[x,11]
72     answerx[x,1] = match
73     total = sum(answerx)
74   }
75   answery[z,1] = y
76   accuracy = total / nrow(mydata)
77   answery[z,2] = accuracy
78   z = z+1
79 }
80 #The max accuracy,0.8532110 occurs at a k-values of 12 and 15
81 plot(answery[,1], answery[,2], main="K-Nearest Neighbor Accuracies",
82       xlab="k Values", ylab="Accuracy")
83

```

```

1 > #Bryson Cook
2 > #ISYE6501, Spring 2018
3 > #Homework 1
4 >
5 > #Part 2.2.1a: SVM
6 >
7 > install.packages("kknn")
8 Installing package into 'C:/Users/212450481/Documents/R/win-library/3.4'
9 (as 'lib' is unspecified)
10 also installing the dependencies 'irlba', 'pkgconfig', 'igraph'
11
12 trying URL 'https://cran.rstudio.com/bin/windows/contrib/3.4/irlba_2.3.2.zip'
13 Content type 'application/zip' length 279988 bytes (273 KB)
14 downloaded 273 KB
15
16 trying URL 'https://cran.rstudio.com/bin/windows/contrib/3.4/pkgconfig_2.0.1.zip'
17 Content type 'application/zip' length 20040 bytes (19 KB)
18 downloaded 19 KB
19
20 trying URL 'https://cran.rstudio.com/bin/windows/contrib/3.4/igraph_1.1.2.zip'
21 Content type 'application/zip' length 8246053 bytes (7.9 MB)
22 downloaded 7.9 MB
23
24 trying URL 'https://cran.rstudio.com/bin/windows/contrib/3.4/kknn_1.3.1.zip'
25 Content type 'application/zip' length 334837 bytes (326 KB)
26 downloaded 326 KB
27
28 package 'irlba' successfully unpacked and MD5 sums checked
29 package 'pkgconfig' successfully unpacked and MD5 sums checked
30 package 'igraph' successfully unpacked and MD5 sums checked
31 package 'kknn' successfully unpacked and MD5 sums checked
32
33 The downloaded binary packages are in
34 C:\Users\212450481\AppData\Local\Temp\Rtmpq0ayYb\downloaded_packages
35 > install.packages("kernlab")
36 Installing package into 'C:/Users/212450481/Documents/R/win-library/3.4'
37 (as 'lib' is unspecified)
38 trying URL 'https://cran.rstudio.com/bin/windows/contrib/3.4/kernlab_0.9-25.zip'
39 Content type 'application/zip' length 2218659 bytes (2.1 MB)
40 downloaded 2.1 MB
41
42 package 'kernlab' successfully unpacked and MD5 sums checked
43
44 The downloaded binary packages are in
45 C:\Users\212450481\AppData\Local\Temp\Rtmpq0ayYb\downloaded_packages
46 >
47 > library(kknn)
48 > library(kernlab)
49 >
50 >
51 > mydata = as.matrix(read.csv("credit_card_data.csv",header=FALSE))
52 >
53 > model = ksvm(mydata[,1:10], mydata[,11],type="C-svc",
54 kernel="vanilladot",C=100,scaled=TRUE)
55 Setting default kernel parameters
56 > # calculate a1-am
57 > a = colSums(model@xmatrix[[1]] * model@coef[[1]])
58 > a
59      V1      V2      V3      V4      V5      V6
60 -0.0010065348 -0.0011729048 -0.0016261967 0.0030064203 1.0049405641 -0.0028259432
61      V7      V8      V9     V10
62 0.0002600295 -0.0005349551 -0.0012283758 0.1063633995
63 >
64 > # calculate a0
65 > a0 = -model@b
66 > a0

```


[illegible]

```

116 Setting default kernel parameters
117 Setting default kernel parameters
118 Setting default kernel parameters
119 Setting default kernel parameters
120 Setting default kernel parameters
121 Setting default kernel parameters
122 Setting default kernel parameters
123 Setting default kernel parameters
124 Setting default kernel parameters
125 Setting default kernel parameters
126 Setting default kernel parameters
127 >
128 > #Prints C values then the accuracy:
129 > plot(log10(ans[,1]), ans[,2], main="KSVM Accuracies",
130 +       xlab="Log(C Value)", ylab="Accuracy")
131 >
132 > # As C increases, the max accuracy is found between  $1 \cdot 10^{-3}$  and 100, and also at
133 > # 100,000. As C increases,
134 > # we are decreasing the margin, but error should also get smaller, though only up to
135 > # a certain point ( $C = 1 \cdot 10^5$  apparently).
136 >
137 > #####
138 > #Part 3, K-Nearest Neighbor
139 >
140 > mydata = data.frame(read.csv("credit_card_data.csv",header=FALSE))
141 > steps = seq(1,100)
142 > answery = matrix(, nrow = length(steps), ncol = 2)
143 > z=1
144 >
145 > for (y in steps){
146 +   answerx = matrix(, nrow(mydata), ncol = 1)
147 +   #answerx = matrix(, nrow=100, ncol = 1)
148 +   #for (x in 1:100){
149 +   for (x in 1:nrow(mydata)){
150 +     knn = kknn(V11~., mydata[-x,], mydata[x,], k = y, scale=TRUE)
151 +     class = round(fitted(knn),0)
152 +     match = class == mydata[x,11]
153 +     answerx[x,1] = match
154 +     total = sum(answerx)
155 +   }
156 +   answery[z,1] = y
157 +   accuracy = total / nrow(mydata)
158 +   answery[z,2] = accuracy
159 +   z = z+1
160 + }
161 > #The max accuracy,0.8532110 occurs at a k-values of 12 and 15
162 > plot(answery[,1], answery[,2], main="K-Nearest Neighbor Accuracies",
163 +       xlab="k Values", ylab="Accuracy")

```

K-Nearest Neighbor Accuracies



KSVM Accuracies

