

NFT 60103 LUCHAIRE

SCOPE

Petroleum products. Closed flash point of lubricants and fuels oils.

LUCHAIRE FLASH POINT TESTER AUTOMATIC VERSION

- NLU 440 -

- REF 40200 -

MAIN CHARACTERISTICS

- ✓ Test Temperature Range: Ambient to 400°C
- ✓ Automatic Flash point detection
- ✓ Data Storage: 200 results
- ✓ Automatic Flame Lightening and extinguishing
- ✓ Optional low gas cartridge to work in all types of environments
- ✓ Automatic Gas cut-off at the end of the test
- ✓ Emergency safety switch
- ✓ RS 232 C output
- ✓ Data acquisition Supervisor Software included possibility to collect the data for a LIMS

SCOPE OF DELIVERY

NLU 440 delivered ready for use with:

REF 40213 Luchaire cup for temperatures above 100°C Luchaire cup for temperatures below 100°C

REF 40211 Pt 100 probe
REF 40439 Insulated plate
1 m of gas tubing

OPTIONAL ACCESSORIES

REF 40483 Gas cartridge case and 1 x 250ml gas cartridge

CONSUMABLES

REF 40484 100ml Gas cartridge for optional case **REF 14110** Tube for butane propane gas 6 x 12 (10m)



ORDERING INFORMATION

REF 40200

NLU 440 For use on AC 230 V - 50 Hz - 0.3 A

(W) 320x (D) 580x (H) 360 mm (±17 kg)

CONTACT: sales@normalab.com

NORMALAB FRANCE SAS

ZA Caux Multipôles 1 - F-76 190 Valliquerville

Tel.: +33 232 700 100 Fax: +33 232 704 732 DISTRIBUTED BY

www.normalab.com
REF 40200 Leaflet 15