CUSTOM ORB®

Minimum recommended roof pitch = 5° (1 in 12)

FINISH
ZINCALUME® steel
ZINCALUME® steel Perforated
Galvanised Z450
COLORBOND® steel
COLORBOND® Ultra steel
COLORBOND® steel Matt
COLORBOND® Metallic steel Corstrip
COLORBOND® steel Hi Gloss 80%
COLORBOND® steel Double Sided Hi Gloss
COLORBOND® steel Double Sided
COLORBOND® COOLMAX® steel
COLORBOND® steel Perforated - Surfmist® only
ZINCALUME® steel
COLORBOND® steel
COLORBOND® Ultra steel
COLORBOND® steel Matt
COLORBOND® COOLMAX® steel

To convert price to **lineal metres multiply** by 0.762

Maximum length* = 35,000mm, Minimum rollformed length* = 305mm (Please check with your local branch)

CUSTOM ORB® FASTENERS

	APPLICATION
	Steel battens up to 1.0mm BMT
	Steel Purlins 1.2mm to 1.9mm BMT
	Timber – Softwood
	Timber – Hardwood

CUSTOM ORB® STANDARD FLASHINGS

	PRODUCT	PROD. CODE
	Ridge Capping	RCCOZL RCCO** RCCOU** RCCO**M
	Roll Top Ridge Capping	RCRT55390ZL RCRT55390** RCRT55390U** RCRT55390**M
	Tile Flashing	TFCOZL TFCO** TFCOU** TFCO**M
	Apron Flashing	AFCOZL AFCO** AFCOU** AFCO**M
	Valley Gutter	VG55400ZL VG55400** VG55400U** VG55400**M
	Barge Capping	BCCOZL BCCO** BCCOU** BCCO**M
	Barge Roll Capping (Gable roll capping) - max. length 2400mm	BRCAPZL BRCAP** BRCAPU** BRCAP**M
	Barge Roll - max. length 2400mm	BR55ZL50 BR55**50 BR55U**50 BR55**M50
	Spear Point	BRSPZL BRSP** BPSPGA BRSP**M

Maximum length* = 8000mm, Minimum length* = 1000mm (Rolltop maximum length* = 9000mm, Minimum length* = 800mm)