FLATDEK®

	FINISH
 Minimum recommended roof pitch = 2° (1 in 30)	COLORBOND® steel Double-Sided Hi Gloss 80% – (Underside) COLORBOND® steel – (Topside)

To convert price to **lineal metres multiply** by 0.250

Maximum length = 9000mm, Minimum length = 500mm

FLATDEK® RECEIVER CHANNEL

	PRODUCT
	FLATDEK® Receiver Channel 1mm

Note: Only available in lengths of 6,100mm in Classic Cream, Paperbark and Thredbo White

FLATDEK® ROOF INFILL STRIP

	PRODUCT
	Profile Foam Infill (50mm H x 20mm W)

FLATDEK® FOAM STRIP

	PRODUCT
	Foam Strip for receiver channel (2000mm x 50mm x 10mm)

FLATDEK® FASTENERS

	APPLICATION
	Steel up to 1.9mm BMT
	Steel up to 3.0mm BMT

Note: 4 fasteners per m^2. (Estimate for non-cyclonic area)

FLATDEK® TRANSLUCENT SHEETING

	PRODUCT
	Fibreglass Gel Coated (Wonderglass)

Maximum length = 9000mm, Minimum length = 900mm

Notes:

TRANSLUCENT SHEETING ACCESSORIES

	PRODUCT
	Roofing Wire (2 x 300 x 150mm)
	Lapseal
	Weatherlok Washer (Fibreglass only)