MULTICLAD®

	FINISH
	ZINCALUME® steel
	COLORBOND® steel
	ZINCALUME® steel
	COLORBOND® steel

MULTICLAD® FASTENERS

APPLICATION	PROD. CODE	TYPE
Steel battens up to 1.9mm BMT	DH5251000 DH525100 DH525**1000 DH525**100	Designer Head M5 - 16 x 25
	RZ625500 RZ625100 RZ625**500 RZ625**100	Roof Zip R625
Timber – Softwood	RZ625500 RZ625100 RZ625**500 RZ625**100	Roof Zip R625

WALLING METAL TRIMS

PROFILE	PRODUCT	SUITABLE FOR
	CD 21 Butt Joint Trim – Overlap	MULTICLAD® (1)
	CD 22 Edge Trim	MULTICLAD® (2) MINI ORB® (1)
	CD 23 External Corner	PANELRIB® MULTICLAD® (1) 2PF 300 (1) MINI ORB®
	CD 24 Internal Corner	PANELRIB® MULTICLAD® (1) MINI ORB® 2PF 300 (1)
	CD 27 Fascia to Soffit Section	PANELRIB® MULTICLAD® MINI ORB®
	CD 30 Fascia Capping	TRIMWALL® (3) PANELRIB® (3) MULTICLAD® (3) MINI ORB® (3) 2PF 300 (3)
	CD 39 Trim Channel	2PF 300
	EC 3 Fascia Capping	TRIMWALL® (3) PANELRIB® (3) MULTICLAD® (3) MINI ORB® (3) 2PF 300 (3)

Notes:
1. Suitable only to these profiles in certain applications.
2. Fit may be tight.
3. Suitable depending on support details.
4. Minimum length is = 300mm. Maximum length is = 4800mm.

WALLING METAL TRIMS

PROFILE	PRODUCT	SUITABLE FOR
	CD 1 Trim Channel	MULTICLAD®
	CD 3 Fascia to Soffit Section	PANELRIB® MULTICLAD® MINI ORB®
	CD 4 Feature Section Soffit**	PANELRIB® MULTICLAD® MINI ORB®
	CD 5 External Corner Trim	PANELRIB® (*) MULTICLAD® MINI ORB® (*) 2PF 300
	CD 6 Internal Corner Trim	PANELRIB® (*) MULTICLAD® MINI ORB® (*) 2PF 300

Notes:
1. *Suitable only to these profiles in certain applications.
2. **CD4 - maximum length of 4 metres (subject to enquiry).
3. Minimum length = 300mm, Maximum length = 4800mm.